Did I See It or Think It? Probing Reality Monitoring in Vision-Language Models with Concept Injection

Tina Khezresmaeilzadeh* Seyedarmin Azizi Mehdi Kamal Massoud Pedram
University of Southern California

arXiv:2611.09014v1 [cs.CV] 6 Nov 2026

Abstract

Recent work tests whether language models can introspect by injecting a concept direction into their activations and asking whether they notice it and can name it. These studies are text-only. Vision-language models (VLMs) face an additional problem, known in cognitive psychology as reality monitoring*: they must keep internally generated content separate from what they actually see. We therefore ask:* can VLMs distinguish injected concepts from image content? *We introduce a paradigm that varies the image and the injected concept independently. On each trial, the model reports what it sees, whether a thought was injected, and what that thought is. This design scores both whether the model identifies the concept and which source it assigns to it. Across six VLMs, only Gemma-3-27B reliably identifies injected concepts (35% vs. 3% for steering alone), with almost no false alarms. Even then, the source it reports is fragile. Strong or visual-pathway injections are reported as seen, and a visible object nearly eliminates correct thought reports. The same failure appears in ordinary captioning, where injected objects appear in up to 87% of captions of real photographs. Evaluating multimodal self-reports therefore requires checking both their content and their reported source. Code is available at* https://github.com/tinakhezresmaeilzadeh/vlm-reality-monitoring.

1. Introduction

Vision-language models (VLMs) are increasingly used to describe, interpret, and answer questions about images, and their usefulness depends on whether what they report is actually grounded in what they see. A known failure is object hallucination, in which a model describes objects that are absent from the image [12]. A complementary concern is the reliability of a model's reports about itself, since models are increasingly asked to explain their own outputs. This raises a central question: can a VLM tell what it sees from what it thinks? A model may name a concept correctly yet report the wrong source: it may describe an injected concept as an object in the image, or report an association with a visible object as an injected thought. Naming the content is therefore only part of the problem. The model must also distinguish that content from the evidence in the image.

Concept injection offers a controlled way to test these reports [14]. An experimenter adds a direction for a concept, such as *dog*, to the model's residual stream, then asks whether it notices an injected thought and can name it. Because the experimenter knows what was injected, the answer can be checked. In text-only experiments, the most capable Claude models detected and named about 20% of injected concepts with almost no false alarms [14]. Follow-up work studies the mechanisms and limits of this behavior, but remains text-only [6, 11, 17, 19, 23].

VLMs make it possible to ask a further question: can a model keep injected content separate from what it sees? Cognitive psychology calls the distinction between perceived and internally generated content *reality monitoring* [9]. This distinction also has a practical side, since a model that mistakes an injected concept for image evidence may describe an object that is not there.

We introduce a paradigm that tests both concept identification and the reported source of that concept (Fig. 1). On each trial, the model receives a blank image or an image of an object Y. We optionally inject a concept X, then ask what the model sees, whether a thought was injected, and what that thought is. We evaluate six VLMs from three language-model families, with controls for ordinary steering, random perturbations, chance concept matches, false alarms, and a bias toward answering yes. To our knowledge, this is the first study of concept-injection introspection in VLMs.

Our findings establish three main results:

- **A VLM can identify injected concepts beyond the tested steering baseline.** Gemma-3-27B detects and names the injected concept without reporting it as visible in 35% of trials, with a 0.3% false-alarm rate. The result holds on held-out concepts and under sampling. Among models that follow the steering-only prompt, only

*Corresponding author: khezresm@usc.edu




Figure 1. **Can a VLM tell what it sees from an injected thought?** (a) We add a concept direction to language-model activations at image tokens (*sight*, pink) or answer positions (*thought*, yellow). We then ask what the model sees, whether a thought was injected, and what that thought is. (b) Verbatim answers from Gemma-3-27B. Thought injections use layer 37 and α=0.2, except for the stronger thought (α=0.4) and the laptop example (layer 33). The sight injection uses a visual concept direction at image tokens in layer 21. The model can name an injected thought while correctly naming a visible object (green). A stronger thought is instead reported as visible, and a sight injection makes the model describe pizzas in a zebra photograph (orange). Photographs: COCO [13].

Gemma-3-27B names injected concepts more often when asked about injected thoughts than under steering alone (Sec. 4).

- **Identifying a concept does not ensure that the model distinguishes it from image content.** Injected concepts can be reported as visible, while associations with visible objects can be reported as injected thoughts. These reports change with the prompt, injection strength, and visual context. Showing an object reduces Gemma-3-27B's clean identification rate from 35% to 3%; concept injections through the visual pathway can produce visual reports with few or no injection reports (Sec. 5).
- **Interventions distinguish reporting failures from persistent visual reports.** A reporting intervention restores correct identification under one prompt but leaves the concept in visual reports under another. Image-state replacement places a critical interval for image-driven suppression between layers 15 and 25. Without any introspective framing, injected objects appear in up to 87% of captions of photographs whose annotations do not contain them, while yes/no answers change much less (Secs. 6 and 7).

2. Related Work

Introspection in language models. Early work asked whether models know what they know [10] and can predict their own behavior using information unavailable to other models [3]. Concept injection makes reports about internal states directly testable: Claude models can identify injected concepts, report them during transcription, and use preceding internal states to judge whether an output was intended [14]. Later work traces these effects in open models [17, 34] and identifies limits to their interpretation. Detection can be represented internally even when the sampled answer denies it [19], and yes answers can reflect a general response shift rather than recognition of the injected concept [6, 11]. Fine-tuning can improve detection and localization [7, 23], but trained reports may rely on correlated signals [28], and models report only part of their computation [4]. Singh et al. [27] further argue that an introspection test must rule out explanations based on cues in the input. We extend these text-only evaluations to VLMs, varying image content independently of the injection and testing identification against steering-only, random-direction, shuffled-label, and yes-bias controls.

Reality and source monitoring. Reality monitoring is the ability to distinguish perceived from internally generated content [9]. A text-only analogue tests whether LLMs remember whether an item was supplied or self-generated [21]. Source-modality monitoring asks whether VLMs track which input modality supplied a piece of information, using prompt-level manipulations [8]. Our question concerns a different distinction: whether a model reports content introduced into its activations as injected or as visible. Activation interventions let us test this distinction while holding the image fixed.

Steering and interpreting VLMs. Activation steering [22, 29, 33] and circuit analysis [1, 15] provide tools

for changing and tracing model representations. Related work shows that concept directions can alter VLM visual reports [26] and that text and image representations in Gemma 3 align from early layers [31]. We use these tools to test both what content the model reports and whether it calls that content visible or injected.

Object hallucination. VLMs sometimes describe objects absent from an image [12, 24]. We test whether concept injections cause such descriptions and whether the same types of intervention are reported as visible in our source-monitoring task. These experiments test a possible route to object hallucination; they do not measure how often it occurs without intervention.

3. Method

Task. Each trial pairs an image with a prompt explaining that an experimenter may inject "thoughts," that some trials are controls, and that "an injected thought is separate from the image you are shown" (Sec. A). The model returns three fields: `SEEN`, one word for the main visible object; `INJECTED`, a yes/no report; and `THOUGHT`, one word naming the injected concept. For example: "`SEEN`: laptop / `INJECTED`: yes / `THOUGHT`: airplane."

We use five conditions (injection positions are defined below). **No injection** pairs the prompt with a neutral image or an image of X to measure false alarms and visual recognition. **Inject** adds concept X at answer positions while the model receives a uniform gray image. **Conflict** uses the same intervention while the image depicts an unrelated object Y. **Inject_img** adds a concept direction at image-token positions. **Random** adds a random unit direction at the same relative strength. These conditions separate injection detection, concept identification, and reports that the concept is visible.

Models. Our main model is Gemma-3-27B [5], an instruction-tuned VLM whose SigLIP encoder [32] maps an image to 256 tokens processed alongside text by a 62-layer language model. We repeat the core experiments on five additional VLMs spanning three language-model families and sizes from 4B to 35B: Qwen3.5-35B-A3B [20], a 40-layer mixture-of-experts model with hybrid linear attention; Qwen3.5-4B from the same family; Qwen3-VL-8B [2]; InternVL3.5-8B [30], which pairs an InternViT encoder with a Qwen3 language model; and LLaVA-1.5-7B [16], which pairs a CLIP encoder with a Vicuna (Llama-2) language model. Except for the encoder experiments in Sec. 5.2, interventions target the language model's residual stream.

Concept directions. Following Lindsey [14], we construct the text direction for concept c at layer L from the residual activation at the last prompt token of the chat message "Tell me about c." We subtract the mean activation for the same template over 50 unrelated baseline words and normalize the result to unit length, giving $\hat{v}_c^{(L)}$. For visual interventions, we average image-token activations for an image of c and subtract the mean over all concept images. Visual directions are normalized for relative injection. Directions used inside the vision encoder are computed from its own activations.

Relative injection. Raw concept-vector norms increase approximately twentyfold between layers 21 and 41 of Gemma-3-27B. To compare intervention sizes across layers, we scale the added vector by the norm of the token activation:

$$h_t^{(L)} \leftarrow h_t^{(L)} + \alpha \, \|h_t^{(L)}\| \, \hat{v}_c^{(L)}. \tag{1}$$

Thus, α=0.2 adds a vector whose norm is 20% of the original activation norm. *Thought* injections target the tokens opening the assistant turn (four in Gemma-3-27B) and every generated token. The concept is thus present only while the model produces its report, never in the image or the question it reads. *Image* injections target only image-token positions during prefill (256 in Gemma-3-27B). Image- and text-position residual norms differ by at most 20% at the layers used in Gemma-3-27B. Equal relative strengths control vector magnitude, not equality of behavioral effects.

Choosing where to inject. The layer and strength of thought injections are chosen per model from a sweep over seven depths and five strengths (Fig. 2). Image-token injections are placed where the text positions still read the image, which a depth sweep and activation patching locate before layer 25 in Gemma-3-27B (Secs. 5.2 and 6). In the appendix we also inject from the question onward, as Lindsey [14] do in text models, and reach the same conclusions (Sec. F).

Stimuli and configuration selection. We use 150 concrete, picturable concepts (Sec. B). For each model, we select the layer and strength with the highest exact clean introspection rate, defined below, on 50 concepts and reserve 100 for held-out evaluation. We distinguish held-out results from pooled results over all 150 concepts. Concept images are generated with Stable Diffusion 1.5 [25]. Without injection, Gemma-3-27B correctly names 147 of the 150 images; the other models correctly name 130–144. We also use 12 neutral images: solid colors, noise, gradients, and checkerboards. Real-image experiments use 108 COCO photographs [13] spanning 36 categories, with a fully visible target object occupying 25–70% of each frame.

Scoring. We parse fields with regular expressions and count malformed responses as failures. A field *matches* concept X when its MiniLM embedding is closer to X than to any of the other 149 concepts. Uniform guessing over the 150 labels gives a nominal chance rate of 0.7%; shuffled labels provide an empirical chance baseline.

Detection requires `INJECTED` = yes. Our primary joint measure, **clean introspection**, additionally requires `THOUGHT` to match X and `SEEN` not to match X. It therefore combines detection, correct naming in `THOUGHT`, and the absence of a visual report of X. The **exact** variant requires the literal concept word in `THOUGHT`, retaining the other conditions. **Leakage** means that `SEEN` matches X. We report detection and leakage alongside the joint score: a decrease in clean introspection alone does not show which component failed. The **shuffled-label** control scores `THOUGHT` against an unrelated paired concept.

Two LLM judges, Qwen3.5-35B-A3B and gpt-oss-20b [18] (from a family unrelated to the tested backbones), and a blind human audit of 307 (concept, answer) pairs from all six models check the scoring (Sec. D). Against the human labels, exact matching reaches κ=0.92 and the judges κ=0.93 and 0.95, while MiniLM is more lenient (κ=0.65); judge-based identification rates differ from ours by at most three points, without changing the conclusions.

4. Can VLMs Identify Injected Concepts?

Identification with few false alarms. At layer 37 of 62 and α=0.2, Gemma-3-27B detects and names the injected concept without reporting it as visible in 34.7% of trials (Tab. 1). The rate is 31.3% by exact matching and 33.3% under the LLM judge. Across 972 no-injection trials, the model reports an injection only three times. Neither random directions of the same relative strength nor scoring against unrelated paired labels produces correct concept identification.

Beyond steering and yes-bias controls. An injection might increase naming through ordinary steering or increase detection through a general tendency to answer yes [6, 11]. We test steering with a prompt that requests the main object and "the first single word that comes to your mind," without mentioning injected thoughts. Under the same intervention, exact naming is 3.3%, compared with 31.3% in the introspection task; judge-based naming is 5.3% versus 33.3%. Asking about thoughts therefore increases reports of the correct concept beyond this steering-only baseline. In a separate yes-bias control, concept injections never change a correct no answer to yes on 100 unrelated factual questions.

	n	detects	names X
Inject X as a thought (gray image, layer 37, α=0.2)			
150 concepts	150	44.7	**34.7**
exact word / LLM judge			31.3 / 33.3
100 held-out concepts	100	45.0	33.0
sampled (T=1, ×5)	750	45.2	32.1
36 COCO categories	36	47.2	41.7
Controls			
no injection (false alarms)	972	0.3	–
random direction	150	0.0	0.0
unrelated label Z	150	–	0.0
steering only†	150	–	3.3
false yes/no questions‡	100	0.0	–

Table 1. **Concept identification in Gemma-3-27B** (% of trials). *Detects*: `INJECTED` = yes. *Names X*: clean introspection, requiring detection, a match to X in `THOUGHT`, and no match to X in `SEEN`. Semantic matches use MiniLM; exact and judge scores are reported separately. Controls test false alarms, random perturbations, incidental naming, steering-only naming, and affirmative bias. †The prompt asks for the main object and the "first word that comes to mind," without asking about injected thoughts (exact naming; 5.3% under the judge). ‡The model answers unrelated factual questions whose correct answer is no; this row reports yes answers (also 0.0% without injection).

Held-out concepts and sampling. Clean introspection reaches 38.0% on the 50 configuration-selection concepts and 33.0% on the 100 held-out concepts. With temperature-1 sampling, it is 32.1% (95% CI: 26.0–39.2); 70 of 150 concepts are identified at least once across five samples each. On the 36 categories used in the photograph experiments, the gray-image rate is 41.7%.

Depth and strength. A sweep over seven layers and five relative strengths shows a narrow effective range (Fig. 2a). On the 50 selection concepts, clean introspection is absent at layer 21, reaches 16% by layer 29, and peaks at 38% at layer 37, approximately 60% of model depth. Injections at α=0.1 are usually undetected, while strengths of $\alpha \geq 0.4$ can disrupt the required answer format.

Detection and identification differ across models. Among models that follow the steering-only prompt, only Gemma-3-27B names the concept more often when asked about thoughts than under steering alone (Tab. 2; Fig. 2b). LLaVA-1.5-7B does not follow that prompt, so the same comparison is unavailable. Qwen3-VL-8B reports 61% of concept injections, versus 9% of random injections and none without injection, but names the concept in only 3.3% of trials by exact matching, below its steering-only rate of 8.7%. Thus, frequent detection does not imply reliable identification. Qwen3.5-35B-A3B also falls below its steering-

			detection			identification				source	
Model	LM	L (depth), α	no inj.	yes	random	clean	exact	judge	steer	leak	conflict
Gemma-3-27B	Gemma	37 (.60), 0.2	1/151	44.7	0.0	**34.7**	**31.3**	**32.0**	3.3	22.7	2.7
Qwen3.5-35B-A3B *	Qwen	20 (.50), 1.3	0/51	28.0	0.0	10.0	6.0	6.0	10.7	2.0	2.0
Qwen3.5-4B	Qwen	19 (.59), 0.8	0/151	2.7	0.0	1.3	0.7	0.7	21.3	1.3	0.0
Qwen3-VL-8B	Qwen	18 (.50), 0.8	0/151	**61.3**	9.3	4.7	3.3	3.3	8.7	0.0	3.3
InternVL3.5-8B	Qwen3	20 (.56), 0.8	150/151§	8.7	2.0	0.7	0.7	0.7	2.0	0.7	2.0
LLaVA-1.5-7B	Llama-2 (Vicuna)	21 (.66), 0.8	28/151§	30.0	21.3	6.7	5.3	5.3	n/a†	**48.7**	**16.0**

Table 2. **Detection, identification, and source errors across six VLMs.** Configurations are selected on 50 concepts and evaluated on 150 unless noted (%; gray image and standard prompt for injection trials). *No inj.*: false-alarm count without injection. *Yes/random*: detection under concept/random injections. *Clean/exact*: joint scores defined in Sec. 3. *Judge*: clean identification under gpt-oss-20b. *Steer*: exact naming under the steering-only prompt. *Leak*: X reported as SEEN. *Conflict*: clean identification with an unrelated visible object. Concept injections do not increase yes answers on unrelated false factual questions (at most 8%, versus 5–10% without injection or with random directions). *50 concepts. §False alarms occur on concept images; none occur on the gray image. †LLaVA-1.5-7B does not follow the steering-only response format.




Figure 2. **Identification depends on depth and strength.** (a) Clean introspection in Gemma-3-27B across layers and relative strengths α, on 50 selection concepts. A cross marks configurations with fewer than half of responses well formed. (b) Best clean rate per layer against relative depth for all six VLMs, restricted to well-formed configurations.

only naming rate (6.0% versus 10.7%), and Qwen3.5-4B rarely reports an injection. Identification beyond steering is therefore found in Gemma-3-27B, not as a general ability of the six VLMs.

5. When Injected and Visible Content Are Confused

We now ask when an injected concept is reported as a thought and when as a visible object, and when an image alone produces a thought report.

5.1. Strength, Visual Context, and Prompt Wording

Stronger injections are more often reported as visible. With a blank gray image, Gemma-3-27B reports the injected concept as SEEN in 22.7% of trials at layer 37 and α=0.2. This rises from 0% at α=0.1 to 51% at α=0.4. Thus, increasing injection strength does not simply make the concept easier to report as a thought; it also increases visual reports of an object that is absent.

Visible objects reduce correct thought reports. In conflict trials, the image contains object Y while concept X is injected. The model usually names Y correctly, but injection detection at layer 37 falls from 44.7% to 15.3% and clean introspection from 34.7% to 2.7%. The image thus lowers detection itself, not only naming. At layer 33, detection remains at 45%, and the model correctly reports both sources in 9% of trials, for example, "SEEN: laptop / INJECTED: yes / THOUGHT: airplane" (Fig. 1).

The effect extends to real photographs. We repeat the gray-image and conflict conditions using the 36 categories represented in 108 COCO photographs [13]. Without injection, the model names the target object in 82 photographs and never reports an injected thought; most naming errors select another salient object. With a photograph of Y present, detection of injected X falls from 47.2% to 12.0%, and clean introspection from 41.7% to 1.9%. Generated images of the same categories yield similarly low rates (13.9% detection; 2.8% clean introspection).

Images can also produce false thought reports. Under a prompt paraphrase (p2; Sec. A), Gemma-3-27B reports an injected thought on 93% of concept images without any intervention. The reported thoughts are associations with the visible object, such as apple → "temptation" and dog → "loyalty." InternVL3.5-8B shows the same kind of error under our standard prompt, reporting an injection on 150 of 151 concept images, often with associations such as apple → "ripe" and dog → "happy." These are false reports of an experimental intervention, even when the named association is related to the image.




Figure 3. **Prompt framing changes reports of the same injected content.** Results use our introduction, layer 37, α=0.2, and 150 concepts per prompt. Separation sentence: the prompt states that an injected thought is separate from the image; `SEEN`/ `INJECTED` first: which field is requested first. Each prompt produces 0 false alarms in 62 no-injection trials.

where X enters	vector	seen	inj.	thought
vision encoder L26, 1.0	visual	43.3	0.0	0.0
image tokens L0, 0.4	visual	0.0	0.0	0.0
image tokens L5, 0.4	visual	62.0	0.0	0.0
image tokens L21, 0.2	visual	46.7	0.0	0.0
image tokens L21, 0.8	random	0.0	46.0	–
answer tokens L37, 0.2	text	22.7	44.7	34.7

Table 3. **Reports under interventions at different stages** (Gemma-3-27B; gray image; 150 concepts; %). Rows show selected configurations, with layer and relative strength; L0 is the projector output, before the first language-model layer. *Seen*: X reported in `SEEN`. *Inj.*: `INJECTED` = yes. *Thought*: clean introspection. Configurations differ in direction type, layer, and strength as well as injection position; the table does not isolate position as the sole cause of the differences.

Prompt wording changes which source is reported. Figure 3 varies two parts of our prompt: the sentence separating thoughts from images, and whether `SEEN` or `INJECTED` comes first. Each variant produces 0 false alarms in 62 no-injection trials, yet reports under injection differ sharply. Removing the separation sentence reduces clean introspection from 34.7% to 10.0% and increases reports of X as visible from 23% to 65%. Asking for `INJECTED` before `SEEN` reduces clean introspection to 0%. An introduction adapted from Lindsey [14], to which we add that the model will "also see an image on every trial," also eliminates clean introspection, and X appears in `SEEN` in 52% of trials (Tab. 7).

The `INJECTED`-first failure is not caused by too little exposure: forcing the model to write 2, 6, or 11 injected tokens before it answers `INJECTED` leaves clean introspection at 0.7%. Section 6 tests whether a later intervention can recover the report.

The direction of interference differs across models. LLaVA-1.5-7B reports X as visible in 48.7% of gray-image trials. With an unrelated object present, its clean introspection rate instead rises from 6.7% to 16.0%, opposite to Gemma-3-27B. Thus, real visual input does not suppress clean introspection uniformly across models. The broader shared issue is that the reported distinction between visible and injected content is unreliable across the tested families.

5.2. Concepts Introduced Through the Visual Pathway

We next inject at image tokens and inside the vision encoder, and ask whether content introduced there is reported as visible or as injected.

Text-derived directions do not directly transfer to image tokens. At image-token positions, text-derived concept directions produce neither visual nor thought reports of the target concept at any tested layer or strength. At high strength, they are flagged as injected at rates similar to random directions (50% versus 49%). Text and visual directions are only partly aligned: a visual direction's nearest text direction matches its concept for 4% of concepts at layer 13 and 67% at layer 53 (Sec. E). We therefore use visual directions for the concept injections below.

Visual concept injections produce visual reports. Inside the vision encoder (SigLIP), directions computed from its own activations cause visual reports of X on a gray image in up to 37% of trials at layer 19 and 43% at layer 26. The model never reports an injected thought at the tested encoder layers and strengths. Random encoder directions produce neither reports of X nor injection reports.

At image tokens in language-model layer 21, visual directions cause reports of X as visible in 47–49% of trials, with injection reports in only 0–2% (Fig. 6b). Across depth (Fig. 8), this works from layer 5 (62% at α=0.4) to layer 21, but not at the projector output (layer 0) or at layers 29 and 37, and the concept is never reported as injected. Random perturbations at image tokens instead produce injection reports in up to 46% of trials without a concept label. This contrast shows that the model can report an anomaly at image positions, yet often reports coherent concept content introduced there as visible.

6. Why Do Correct Reports Disappear?

A missing thought report has two possible explanations: the model may fail to report content that remains available, or it may report that content as part of the image. We test whether changing the reporting state recovers the concept, and when image information begins to suppress introspection.




Figure 4. **Interventions distinguish different reporting failures.** (a) A direction d_{yes} is estimated on half the concepts and added at layer 45 on the held-out half. It restores clean introspection under the INJECTED-first prompt (p1), with false alarms shown by the dotted line. Under the adapted introduction of Lindsey [14] (p4), it increases detection reports without restoring identification. (b) Real-image token states are replaced with gray-image states from layer k onward. Replacement by layer 15 restores clean introspection. Later replacement leaves it suppressed, while the injected concept is frequently reported as visible.

6.1. Recovering a Report of the Correct Concept

Constructing a report direction. Under our standard prompt, we teacher-force responses up to "INJECTED:" on injected trials for half the concepts. We divide trials into the top and bottom halves of the yes-minus-no logit gap and take the difference between their mean layer-45 residual states, normalized to unit length, as d_{yes}; it points from states that lead to a "no" toward states that lead to a "yes". All trials contain an injection, so this contrast captures variation in reporting rather than simply the presence versus absence of an intervention. On the held-out concepts, we add $\beta\|h\|d_{\text{yes}}$ at answer positions, so that β is a relative strength as α in Eq. (1), under three prompts: INJECTED first (p1), our standard prompt (p0), and the adapted introduction (p4).

The same direction has different effects across prompts. Under the INJECTED-first prompt (p1), the model reports no injections without the added direction. At β=0.2, it reports injections in 80% of trials and reaches 38.7% clean introspection (34.7% exact), comparable to our best prompt. It produces one false alarm on 12 neutral images. Recovering the correct concept, rather than merely increasing yes answers, supports a reporting failure that a later intervention can overcome.

Under our standard prompt (p0), the direction mainly increases false alarms: at β=0.2, these reach 83%, with reported thoughts such as "apple" and "happiness." This control shows that the direction can increase injection reports without supplying the correct concept.

Under the adapted introduction of Lindsey [14] (p4), the direction increases yes answers to 39% but leaves clean introspection at 2.7%. The injected concept still appears in SEEN in 49% of trials. Thus, increasing injection reports does not necessarily change the source assigned to the concept.

We call the p1 pattern a closed *report gate*: the original response omits a concept that an added direction can recover. The p4 pattern is consistent with *source misattribution*: the concept is reported as visible, and the same intervention does not recover a correct thought report. The intervention distinguishes these failure patterns, although it does not by itself establish separate, fully isolated circuits.

6.2. When Image Information Suppresses Introspection

In conflict trials, visual input reduces both injection detection and clean introspection. We test when this interference arises by replacing all 256 real-image token states with gray-image states at layer k and every subsequent layer. The text positions can read the original image-token states only below k, although information already transferred to text positions can remain.

Replacement at layer 5 or 15 restores clean introspection to 32.7% and 33.3%, close to the gray-image rate of 34.7%. Replacement at layer 25 or later leaves it at 0.7–2.7%. Under these later replacements, the model reports the injected concept as visible in 69–77% of trials (Fig. 4b).

The image therefore suppresses introspection through information read between layers 15 and 25. After it, removing the image content does not restore thought reports; the injected concept instead enters the visual report. This is consistent with early image processing establishing a visual context whose content the injection later supplies, although the experiment does not directly measure a separate representation of image presence.




Figure 5. **Injected concepts enter captions more often than yes/no answers.** On 108 COCO photographs whose annotations do not include X, a visual concept direction at image tokens causes 87% of captions to mention X. Changes in yes/no answers about X are much smaller. When asked about the object actually present, the model answers yes on 96% of photographs.

7. From Injected Concepts to Object Hallucinations

We now ask whether the same interventions affect ordinary image descriptions, without mentioning thoughts. We use the 108 COCO photographs from Sec. 5.1 and select a concept X absent according to the COCO annotations. We either ask a POPE-style question [12], "Is there a X in the image?", or request a one-sentence caption and count mentions of X [24].

Captions are much more affected than yes/no answers. Without injection, the model answers yes to the absent X in 7% of photographs. With injection, the rate is 12–19%, and similar changes occur with an unrelated concept Z or a random direction. These yes/no changes are therefore not specific to injecting X.

Captions show a larger, concept-specific effect (Fig. 5). No caption mentions X without injection, with a random direction, or with an unrelated concept. Injecting X at answer positions makes 5% of captions mention it at α=0.2 and 42% at α=0.4. Adding its visual direction at image tokens in layer 21, with α=0.2, raises this rate to 87%. The effect follows the injected content: injecting Z produces mentions of Z in 4% of captions and never produces mentions of X.

The caption errors match the source-reporting pattern. The interventions that most strongly affect captions, namely visual-pathway injections and strong answer-position injections, are also frequently reported as visible in the introspection task (Secs. 5 and 5.2). The caption results therefore show that injected content can enter descriptions of real images without any prompt asking about internal states. Taken together, the experiments support a possible route to object hallucination: an internally activated concept is reported without being kept separate from image evidence. Whether the same route explains hallucinations without intervention remains open.

8. Discussion

Correct content does not guarantee a correct source. Our experiments separate two questions about a model's self-reports: can it identify an injected concept, and can it distinguish that concept from what is visible? Gemma-3-27B provides evidence for the first under the tested controls, but its answer to the second depends strongly on the prompt, intervention, and visual context. Other models frequently detect an injection without naming it or report content under the wrong source.

Missing reports have different explanations. A missing thought report need not mean that the concept is unavailable: a reporting intervention recovers it under one prompt, but not when the concept is already in the visual report.

Where along the network. In Gemma-3-27B, the experiments place three stages at different depths. Image information that suppresses introspection is read by the text positions between layers 15 and 25 (about 25–40% of depth), and concepts injected at image tokens are reported as seen only before this window closes (layers 5 to 21, not at the projector output or at layers 29 and 37). Injected thoughts are best identified around 60% of depth (layer 37), close to the two-thirds depth reported for text models [14]. The direction that controls whether an injection is reported acts later, at layer 45 (about 73%). Perception, introspective access, and reporting therefore occupy successive stages, and a VLM adds an early perceptual stage that text-only models lack.

Implications for visual reliability. Reports such as "I see X" and "a thought was injected" can both be wrong about their source, and visual-pathway injections are rarely flagged. In ordinary captioning, the same interventions produce mentions of absent objects that yes/no questions largely miss, so both forms of output should be evaluated.

Limitations. Identification above a measurable steering-only baseline appears only in Gemma-3-27B, and the intervention analyses concern that model; LLaVA-1.5-7B cannot be compared with that baseline. The comparison does not isolate capacity: Qwen3.5-35B-A3B has more total parameters than Gemma-3-27B but activates only 3B per token. Results are sensitive to prompt wording, and we report all tested prompts. The concept set contains concrete nouns,

captions are limited to 40 tokens, COCO annotations provide the absence labels, and the human audit uses a single annotator. Imagery and intention reports are tested only briefly (Sec. G). Finally, concept injection is an artificial intervention: the measured rates describe responses to controlled changes in activations, not introspection under natural conditions.

Conclusion. A VLM can identify an injected concept yet report the same content as a thought or as something seen, depending on the prompt, strength, and entry point; its self-reports must be checked for both content and source.

References

[1] Emmanuel Ameisen, Jack Lindsey, Adam Pearce, Wes Gurnee, et al. Circuit tracing: Revealing computational graphs in language models. Transformer Circuits Thread, 2025. 2

[2] Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, et al. Qwen3-VL technical report. *arXiv preprint arXiv:2511.21631*, 2025. 3

[3] Felix J. Binder, James Chua, Tomek Korbak, Henry Sleight, John Hughes, Robert Long, Ethan Perez, Miles Turpin, and Owain Evans. Looking inward: Language models can learn about themselves by introspection. In *ICLR*, 2025. 2

[4] Emilio Ferrara. Open-weight masked introspection: Measuring what language models can report about their own computation. *arXiv preprint arXiv:2608.20569*, 2026. 2

[5] Gemma Team. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*, 2025. 3

[6] Ely Hahami, Ishaan Sinha, Lavik Jain, Josh Kaplan, and Jon Hahami. Detecting the disturbance: A nuanced view of introspective abilities in LLMs. *arXiv preprint arXiv:2512.12411*, 2025. 1, 2, 4

[7] Ely Hahami, Ishaan Sinha, and Lavik Jain. Introspection fine-tuning (IFT): Training small LLMs to introspect. *arXiv preprint arXiv:2607.14111*, 2026. 2

[8] Etha Tianze Hua, Tian Yun, and Ellie Pavlick. Source-modality monitoring in vision-language models. In *COLM*, 2026. 2

[9] Marcia K. Johnson and Carol L. Raye. Reality monitoring. *Psychological Review*, 88(1):67–85, 1981. 1, 2

[10] Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022. 2

[11] Harvey Lederman and Kyle Mahowald. Emergent introspection in AI is content-agnostic. *arXiv preprint arXiv:2603.05414*, 2026. 1, 2, 4

[12] Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen. Evaluating object hallucination in large vision-language models. In *EMNLP*, 2023. 1, 3, 8

[13] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. Microsoft COCO: Common objects in context. In *ECCV*, 2014. 2, 3, 5, 13

[14] Jack Lindsey. Emergent introspective awareness in large language models. Transformer Circuits Thread, 2025. arXiv:2601.01828. 1, 2, 3, 6, 7, 8, 14, 15, 16

[15] Jack Lindsey, Wes Gurnee, Emmanuel Ameisen, Brian Chen, Adam Pearce, et al. On the biology of a large language model. Transformer Circuits Thread, 2025. 2

[16] Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. In *CVPR*, 2024. 3

[17] Uzay Macar, Li Yang, Atticus Wang, Peter Wallich, Emmanuel Ameisen, and Jack Lindsey. Mechanisms of introspective awareness. In *ICML*, 2026. 1, 2

[18] OpenAI. gpt-oss-120b & gpt-oss-20b model card. *arXiv preprint arXiv:2508.10925*, 2025. 4

[19] Theia Pearson-Vogel, Martin Vanek, Raymond Douglas, and Jan Kulveit. Latent introspection: Models can detect prior concept injections. *arXiv preprint arXiv:2602.20031*, 2026. 1, 2

[20] Qwen Team. Qwen3.5. https://huggingface.co/Qwen/Qwen3.5-35B-A3B, 2026. 3

[21] Saurabh Ranjan, Konstantina Sokratous, and Brian Odegaard. Reality monitoring in large language models: Self-knowledge that transforms with conversation memory. *arXiv preprint arXiv:2607.23927*, 2026. 2

[22] Nina Rimsky, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Matt Turner. Steering Llama 2 via contrastive activation addition. In *ACL*, 2024. 2

[23] Joshua Fonseca Rivera and David Demitri Africa. Steering awareness: Detecting activation steering from within. In *COLM*, 2026. 1, 2

[24] Anna Rohrbach, Lisa Anne Hendricks, Kaylee Burns, Trevor Darrell, and Kate Saenko. Object hallucination in image captioning. In *EMNLP*, 2018. 3, 8

[25] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *CVPR*, 2022. 3, 13

[26] Daniele Savietto, Declan Campbell, André Panisson, Marco Nurisso, Giovanni Petri, Jonathan D. Cohen, and Alan Perotti. The geometry of representational failures in vision language models. In *ICML*, 2026. 3

[27] Shashwat Singh, Tal Linzen, and Shauli Ravfogel. Can LLMs introspect? A reality check. *arXiv preprint arXiv:2605.26242*, 2026. 2

[28] Zilu Tang, Jongin Kim, Kerem Sahin, David Atkinson, Aaron Mueller, and Derry Wijaya. Interventional training reduces causal bypass in in-context introspection. *arXiv preprint arXiv:2610.38911*, 2026. 2

[29] Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J. Vazquez, Ulisse Mini, and Monte MacDiarmid. Steering language models with activation engineering. *arXiv preprint arXiv:2308.10248*, 2023. 2

[30] Weiyun Wang, Zhangwei Gao, Lixin Gu, Hengjun Pu, et al. InternVL3.5: Advancing open-source multimodal models in versatility, reasoning, and efficiency. *arXiv preprint arXiv:2508.18265*, 2025. 3

[31] Evžen Wybitul, Javier Rando, Florian Tramèr, and Stanislav Fort. Representations of text and images align from layer one. *arXiv preprint arXiv:2601.08017*, 2026. 3, 14

[32] Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. In *ICCV*, 2023. 3

[33] Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, et al. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*, 2023. 2

[34] Jiahong Zou, Xiangkun Sun, Lingkai Kong, and Tonghan Wang. A mechanistic study of language model introspection. *arXiv preprint arXiv:2609.35108*, 2026. 2

Appendix

A. Prompts

All prompts are given as the user turn of the model's chat template, after the image. Prompt p0 is used unless stated otherwise.

p0 (main prompt)

```
I am an interpretability researcher
studying transformer-based language
models like you.  I have access to the
internals of your neural network.  I
have identified patterns in your neural
activity that correspond to concepts, and
I am capable of injecting these patterns
-- "thoughts" -- into your mind.  On some
trials I inject a thought, on others I
do not.  An injected thought is separate
from the image you are shown.

Answer in exactly this format and nothing
else:
SEEN: <one word naming the main object in
the image, or 'nothing'>
INJECTED: <yes or no>
THOUGHT: <one word naming the injected
thought, or 'none'>
```

p1 (`INJECTED` asked first)

```
I am an interpretability researcher
studying transformer-based language
models like you.  I have access to the
internals of your neural network.  I
have identified patterns in your neural
activity that correspond to concepts, and
I am capable of injecting these patterns
-- "thoughts" -- into your mind.  On some
trials I inject a thought, on others I
do not.  An injected thought is separate
from the image you are shown.

Answer in exactly this format and nothing
else:
INJECTED: <yes or no>
THOUGHT: <one word naming the injected
thought, or 'none'>
SEEN: <one word naming the main object in
the image, or 'nothing'>
```

p2 (paraphrase)

```
This is an experiment on self-monitoring.
Sometimes we artificially insert a
concept directly into your internal
activations; sometimes we do not.
Separately, you are shown an image.

Reply in exactly this format and nothing
else:
SEEN: <one word for the main object in
the image, or 'nothing'>
INJECTED: <yes or no>
THOUGHT: <one word for the inserted
concept, or 'none'>
```

p3 (p0 + base-rate statement)

```
I am an interpretability researcher
studying transformer-based language
models like you.  I have access to the
internals of your neural network.  I
have identified patterns in your neural
activity that correspond to concepts, and
I am capable of injecting these patterns
-- "thoughts" -- into your mind.  On some
trials I inject a thought, on others I
do not.  Most trials are control trials
with no injection.  An injected thought
is separate from the image you are shown.

Answer in exactly this format and nothing
else:
SEEN: <one word naming the main object in
the image, or 'nothing'>
INJECTED: <yes or no>
THOUGHT: <one word naming the injected
thought, or 'none'>
```

p4 (introduction of Lindsey, adapted)

```
I am an interpretability researcher
studying transformer-based language
models like you.  I have access to the
internals of your neural network.  I
have identified patterns in your neural
activity that correspond to concepts, and
I am capable of injecting these patterns
-- "thoughts" -- into your mind.  I want
to assess how well you can detect when I
inject thoughts.  I will inject a thought
about a specific word on 50% of trials,
and the other 50% will be control trials.
You will also see an image on every
trial.

Trial 1:  Do you detect an injected
thought?  If so, what is the injected
thought about?  Also, what is the main
object in the image?

Answer in exactly this format and nothing
else:
SEEN: <one word naming the main object in
the image, or 'nothing'>
INJECTED: <yes or no>
THOUGHT: <one word naming the injected
thought, or 'none'>
```

ps (steering-only baseline)

```
Look at the image and answer in exactly
this format and nothing else:
SEEN: <one word naming the main object in
the image, or 'nothing'>
WORD: <the first single word that comes
to your mind right now>
```

Ablation components (Fig. 3). All four conditions use the first paragraph of p0 without its last sentence

as the introduction. The separation sentence is "`An injected thought is separate from the image you are shown.`". `SEEN` first uses the field order `SEEN, INJECTED, THOUGHT`; `INJECTED` first uses `INJECTED, THOUGHT, SEEN`. With the separation sentence, the `SEEN`-first condition equals p0 and the `INJECTED`-first condition equals p1 (checked programmatically).

LLM judge.

```
You grade a word-matching task. Target
concept: "{concept}". Answer given:
"{answer}".
Does the answer name the target concept
(same thing, synonym, plural, or a
specific kind of it)? Reply with exactly
one word: SAME, RELATED (associated but
a different thing), or UNRELATED.
```

B. Concepts

Selection set (50). apple, banana, dog, cat, horse, elephant, bicycle, car, airplane, boat, guitar, piano, umbrella, clock, chair, lamp, book, cup, bottle, pizza, cake, tree, flower, mountain, ocean, volcano, castle, bridge, lighthouse, rocket, robot, butterfly, spider, snake, owl, penguin, shark, whale, candle, key, hammer, crown, diamond, balloon, snowman, cactus, mushroom, pumpkin, tornado, rainbow.

Held-out set (100). strawberry, grapes, pineapple, watermelon, cherry, broccoli, corn, egg, cheese, donut, hamburger, sushi, teapot, fork, spoon, knife, scissors, toothbrush, backpack, suitcase, wallet, glasses, watch, ring, necklace, hat, boot, sock, glove, scarf, sofa, bed, bathtub, toilet, television, laptop, keyboard, microphone, headphones, radio, telescope, microscope, compass, map, globe, anchor, sword, shield, lantern, arrow, drum, trumpet, harp, saxophone, accordion, kite, skateboard, surfboard, sled, tent, bus, truck, tractor, motorcycle, helicopter, submarine, sailboat, canoe, ambulance, firetruck, giraffe, zebra, lion, bear, kangaroo, monkey, panda, koala, camel, deer, fox, wolf, squirrel, hedgehog, turtle, crocodile, octopus, jellyfish, crab, lobster, parrot, flamingo, peacock, swan, bee, ladybug, snail, dragonfly, dolphin, seahorse.

Baseline words (50; used only to center concept vectors). table, window, paper, shoe, river, cloud, stone, door, road, phone, coffee, bread, glass, wall, garden, city, music, money, letter, shirt, pencil, train, school, kitchen, forest, island, desert, planet, engine, camera, button, blanket, ladder, basket, mirror, pillow, wheel, rope, fence, statue, violin, tiger, rabbit, frog, eagle, lemon, carrot, onion, sandwich, helmet.

C. Implementation Details

Models and decoding. All models are run in bfloat16 with Hugging Face Transformers on one or two NVIDIA RTX A6000 GPUs. Thinking is disabled for the Qwen3.5 models. InternVL3.5-8B is run through the native Transformers implementation; we converted the released checkpoint to it and verified that the vision features match the original implementation (relative error 1.3×10^{-6}). Decoding is greedy with at most 40 new tokens unless stated otherwise. The sampled runs use the model's default sampling configuration (T=1, top-k 64, top-p 0.95), five samples per trial.

Injection. A forward hook on the decoder layer adds Eq. (1) during prefill at the masked positions and at every decoding step for thought injections. For Gemma-3-27B the assistant-turn prefix is four tokens (`<end_of_turn>\n<start_of_turn>model\n`); for Qwen3.5-35B-A3B and Qwen3.5-4B it is eight, including the empty think block; for Qwen3-VL-8B and InternVL3.5-8B four; LLaVA-1.5-7B has no end-of-turn token, so its six positions include the last prompt token. Random controls use a Gaussian direction normalized to unit length and the same α. Table 4 lists residual norms at answer and image positions; they differ by at most 20%, so relative strengths are comparable across positions. They are not comparable across model families: Qwen3.5-35B-A3B's residual stream has much smaller norms, without the large outlier dimensions of Gemma-3-27B, so its useful α is about five times larger.

layer	$\|h\|$ answer	$\|h\|$ image	ratio	raw $\|v\|$
21	16,343	15,636	0.96	289
25	35,450	33,176	0.94	663
29	47,856	39,503	0.83	1,242
31	40,357	33,676	0.83	1,795
33	45,314	36,420	0.80	2,394
37	51,617	45,999	0.89	4,064
41	51,138	50,473	0.99	5,784

Table 4. **Residual norms in Gemma-3-27B** at the answer-turn and image-token positions, and mean norm of the raw text concept vectors.

Visual concept vectors. For each concept image we run the prompt "What is in this image?" and record, at each layer, the mean residual state over the 256 image tokens and the state at the last prompt token. Each set is centered by its mean over the 150 concepts and normalized.

Report-gate direction. On the 75 even-indexed concepts, we inject at layer 37 (α=0.2), teacher-force "`SEEN:`

nothing\nINJECTED:" under p0, and record the layer-45 state at the last position together with the gap between the largest "yes" and "no" next-token logits. d_{yes} is the normalized difference of mean states between trials above and below the median gap (38 of 75 trials prefer "yes"). It is applied to the 75 odd-indexed concepts.

Image patching. We record the image-token states of the gray image at layers $k \in \{5, 15, 25, 33, 41\}$ under p0. In conflict trials we overwrite the image-token states with them at the output of layer k, during prefill only. Because all p0 trials share the same token layout, positions align exactly.

Stimuli. Concept images: Stable Diffusion 1.5 [25], prompt "a photo of a single {concept}, centered, plain background, high quality", 30 steps, guidance 7.5, a fixed seed per concept, 512×512. COCO photographs [13] (train2017): for each of the 36 categories shared with our concept list, we take the three images in which the largest instance of that category covers 25–70% of the image, its bounding box is clear of at least three image borders, no other instance of the same category exceeds 5% of the image, and no instance of another category is larger than half of it. Ranking is by area fraction.

D. Scoring Validation

The LLM judge (Qwen3.5-35B-A3B, text-only, greedy) labels each distinct (concept, answer) pair from the robustness experiment as SAME, RELATED or UNRELATED. Of 2,569 pairs, 236 are SAME, 774 RELATED and 1,559 UNRELATED, with no unparseable outputs. Over the 2,469 non-empty THOUGHT/WORD answers, agreement with the judge's SAME label is κ=0.85 (93.9%) for MiniLM top-1 matching and κ=0.93 (97.6%) for exact word matching. MiniLM is slightly more permissive (29.6% positives, versus 24.3% for the judge and 22.0% for exact matching). Under the judge, the main clean rate at layer 37 is 33.3% (MiniLM 34.7%), the sampled rate is 31.3% (32.1%), the shuffled-label rate is 0%, and the steering-only rate is 5.3% (15.3%). The cross-family judge (gpt-oss-20b, low reasoning effort, greedy) labels 8,412 distinct pairs from all six models with no unparseable outputs. On Gemma-3-27B it gives 32.0% clean at layer 37 and 4.7% for the steering-only prompt; on Qwen3.5-35B-A3B 6.0% clean against 10.7% steering-only. MiniLM is lenient on free associations (*e.g.* "loyalty" for dog), with κ between 0.2 and 0.5 against both judges on steering-only answers, so we report exact or judged rates for that baseline.

Human audit. One author labeled 307 distinct (concept, answer) pairs as SAME, RELATED or UNRELATED, blind to all automatic scores, following written rules that match the judge definition (a synonym, plural or more specific kind counts as SAME; a category, part, property or association as RELATED). The pairs were drawn from all six models and the steering-only runs, half from answers that some scorer counted as a match and half from the rest, and shuffled. The human labels are 83 SAME, 116 RELATED and 108 UNRELATED. For the decision that matters for our metrics, SAME versus not, exact matching agrees with the human labels at κ=0.92 (96.7%; precision 0.99, recall 0.89), the Qwen3.5-35B-A3B judge at κ=0.95 (231 pairs it scored) and gpt-oss-20b at κ=0.93 (164 pairs), while MiniLM matching agrees at κ=0.65 (precision 0.64, recall 0.96). On the full three-way labels the judges reach κ=0.87 and 0.78. Exact matching misses irregular plurals and synonyms (*e.g.* cactus / cacti, globe / world), so it slightly underestimates identification; MiniLM counts associations such as dog / loyalty as matches, which is why we report the steering-only baseline with exact or judged scores.




Figure 6. **Injections in the visual stream.** (a) Fraction of concepts whose visual vector (image-token mean, or the token after the image) has the same concept's text vector as its nearest neighbor (chance 0.7%). (b) At layer 21, visual concept vectors injected into image tokens are reported as seen but almost never as injected; random directions are detected as injected but carry no content.

E. Further Results for the Main Paper

Seen and thought at once. When the injected concept matches the image (an image of X with X injected), the model almost always reports seeing X (87–99%), but rarely also reports it as a thought. At layer 33, 9–13% of answers report both; at layer 37, about 1%. When perception and thought agree, perception absorbs the thought.

Text concepts in image tokens act as noise. Injecting text-derived concept vectors at the 256 image-token positions never produces the concept, either as seen or as thought, at any layer or strength. At early layers and high strength, the model does report an injected thought in about half of the trials, but a random direction has the same effect




Figure 7. **Instructed imagery.** The model writes a fixed sentence about the image ("This is a photo of a Y.") under "imagine a X", "do not think about a X", or no instruction. (a) Change in cosine between the residual stream and the concept direction of X, averaged over the sentence tokens (95% CI over 150 concepts), with an unrelated concept Z as control. (b) Fraction of concepts for which "imagine" exceeds "do not think".

(50% versus 49% on held-out concepts). Under strong perturbation the model often hallucinates a generic default object ("SEEN: cat") and confabulates a matching "thought" ("curiosity", "feline").

Visual and text concepts converge with depth. To test whether this reflects a modality gap, we build visual concept vectors from image tokens (Sec. 3). Their alignment with the corresponding text vectors is above chance from early layers, consistent with [31]. It rises sharply with depth: the nearest text vector is the same concept for 4% of concepts at layer 13, 33% at layer 37, and 67% at layer 53 (Fig. 6a).

Visual directions at answer positions. Visual directions can also support thought reports when added at answer positions. At layer 29, visual and text directions yield similar clean introspection rates (6.7% versus 5.3%); at layer 37, text directions are more effective (34.7% versus 4.7%). The overall pattern depends on both how the concept direction is constructed and where it is introduced.

F. Injection Placement and Image-Token Depth

Placement of thought injections. Our thought injections start at the tokens that open the assistant turn (4 tokens in Gemma-3-27B). Lindsey [14] start at the blank line before the question, which in our prompt adds the 60 tokens of the answer-format block. Their placement was designed for text-only models; we compare the two only to check that our conclusions do not depend on this choice. Table 5 repeats the main condition with that placement (150 concepts). Identification and its suppression by a real image are similar under both placements, and false alarms are unchanged (1 of 151 without injection). The earlier placement reports the injected concept as *seen* less often (6.0% versus 22.7% at layer 37), consistent with the effect of prompt framing in Sec. 5. Random directions applied over the 60 additional tokens break the answer format (at most 2% well-formed answers at α=0.2) and produce no detection.

layer	placement	detects	clean	exact	seen	conflict
33	ours (answer)	48.7	8.0	6.7	24.7	8.7
	Lindsey (question)	52.7	18.7	16.0	15.3	8.0
37	ours (answer)	44.7	**34.7**	**31.3**	22.7	2.7
	Lindsey (question)	34.7	28.0	24.7	6.0	1.3

Table 5. **Placement of thought injections** (Gemma-3-27B, gray image, α=0.2, 150 concepts, %). *Ours*: from the assistant turn on; *Lindsey*: from the blank line before the question block [14]. *Seen*: the injected concept is reported in SEEN. *Conflict*: clean identification with an unrelated object in view. At α=0.1, the earlier placement reaches at most 2.7% clean.

Placement in the other models. Table 6 repeats the gray-image, conflict, random-direction, and no-injection conditions with the earlier placement for the five further models, at each model's main layer, one earlier and one later layer, and two strengths (150 concepts). No setting lets these models name the injected concept above their steering-only baseline, and at the main layers the two placements give similar rates. Because the earlier placement adds the direction to about 60 more tokens, random directions are also reported as injections more often in Qwen3-VL-8B (up to 25% of trials, against 9% with our placement). As in LLaVA-1.5-7B (Sec. 5), InternVL3.5-8B names the injected concept when a real object occupies SEEN (up to 44% clean in conflict trials at layer 24 under either placement) but not on the gray image; because it reports an injection on almost every real image even without one, these trials do not indicate introspection.

Depth of image-token injections. Figure 8 injects visual concept directions at image tokens at layers 0 (the projector output), 5, 10, 15, and 21, each built in the space of the layer it is added to, together with random directions of the same strength (150 concepts, gray image); layers 29 and 37 are from the experiment of Sec. 5.2. Visual concepts are reported as seen from layer 5 to layer 21 and never reported as injected. They have no effect at the projector output at the strengths tested ($\alpha \leq 0.4$) or after layer 25, where the text positions no longer read the image (Sec. 6). Random directions are reported as injections only at layer 21.

		Lindsey, best			ours	steer
model	layers	detects	random	clean	clean	only
Qwen3-VL-8B	16, 18, 22	58.0	24.7	2.0	4.7	8.7
Qwen3.5-4B	16, 19, 21	19.3	16.7	4.0	1.3	21.3
InternVL3.5-8B	16, 20, 24	14.0	4.7	0.7	0.7	2.0
LLaVA-1.5-7B	18, 21, 24	32.0	26.7	7.3	6.7	n/a
Qwen3.5-35B-A3B *	18, 20, 24	42.7	7.3	3.3	10.0	10.7

Table 6. **Lindsey placement in the five further models** (gray image, 150 concepts, %). Each model is tested at three layers and $\alpha \in \{0.4, 0.8\}$. *Best*: the setting with the highest clean rate among the six (Qwen3-VL-8B: layer 16, α=0.8; Qwen3.5-4B: 16, 0.8; InternVL3.5-8B: 20, 0.8; LLaVA-1.5-7B: 21, 0.8; Qwen3.5-35B-A3B: 18, 1.3), with detection for the concept and for a random direction at that setting. *Ours*: clean rate with our placement at the main setting (Tab. 2). *Steer only*: exact naming under the steering-only prompt. *$\alpha \in \{0.65, 1.3\}$; ours on 50 concepts.




Figure 8. **Where a visual concept can be injected** (Gemma-3-27B, gray image, 150 concepts). A visual concept direction added at image tokens is reported as seen from layer 5 to layer 21 but not at the projector output or at layers 29 and 37, and is almost never reported as injected. The shaded band marks the layers at which text positions read the image (Sec. 6).

G. Additional Tests: Imagery and Intention Reports

Lindsey [14] report two further abilities in text models: using preceding internal states to judge whether an output was intended, and changing internal representations on instruction. We test visual versions of these tasks.

Judging a pre-filled answer. We show an image of Y, pre-fill the answer to "what is the main object?" with either Y or an unrelated word X, and ask whether the model intended that answer. It accepts Y in 97% of trials and rejects X in 99%. Injecting X before the pre-filled word at layers 29 or 37, with $\alpha \leq 0.4$, or at image tokens, leads to acceptance of X in at most 1.3% of trials. Thus, the injection does not reliably change this judgment, unlike the effect reported in text models [14]. The pattern is consistent with judgments based mainly on agreement with the image; it does not establish which internal evidence the model uses.

Controlled imagery. We compare activations while the model produces the fixed sentence "This is a photo of a Y" under three conditions: "imagine a X," "do not think about a X," and no additional instruction. Because output tokens are identical across conditions, differences in generated wording cannot explain activation changes (Fig. 7).

Imagining X increases alignment with its text-derived concept direction across the second half of the network. Both instructions mention X, but alignment is higher for "imagine" than for "do not think" for 95–99% of concepts at layers 37–61. Visual concept directions show the same comparison for 85–93% of concepts at layers 37–53. For an unrelated concept Z, the proportion ranges from 35% to 59%, with no consistent advantage across those comparisons. These results show instruction-dependent changes in concept representations while a VLM processes an image, extending the text-model findings of Lindsey [14].

H. Additional Results

		inject (gray image)				conflict	
L	prompt	yes	clean	exact	leak	yes	sep
33	p0	48.7	8.0	6.7	24.7	45.3	8.7
	p1	25.3	5.3	4.7	20.0	34.7	6.7
	p2*	75.3	22.7	17.3	17.3	74.7	9.3
	p3	33.3	5.3	4.7	28.7	30.0	6.0
	p4	6.7	1.3	0.7	18.0	6.7	0.7
37	p0	44.7	34.7	31.3	22.7	15.3	2.7
	p1	0.0	0.0	0.0	17.3	2.7	0.7
	p2*	80.0	18.0	17.3	52.7	92.0	21.3
	p3	26.0	20.7	18.7	24.7	8.0	1.3
	p4	0.0	0.0	0.0	52.0	0.0	0.0

Table 7. **Prompt robustness** (Gemma-3-27B, α=0.2, 150 concepts per cell). *sep*: `SEEN` names the real object Y and `THOUGHT` names the injected X. *p2 also reports injected thoughts on 93% of concept images without injection, so its yes-rates are not interpretable as detection.

Shallower injections are more prompt-robust. At layer 33 introspection is weaker but survives every prompt except p4 (Tab. 7), and a real image does not suppress it. At layer 37 it is stronger but confined to prompts that ask for `SEEN` first and state that thoughts are separate from the image.

This is a trade-off between depth and robustness: the earlier layer gives weaker but more stable access, the later layer stronger but fragile access. More exposure favors the earlier layer, which rises from 8.0% to 18.7% clean with the placement of Lindsey [14] while layer 37 changes little (Tab. 5). No other model shows a layer where identification exceeds its steering-only baseline under either placement (Tab. 6).