

Oracle® Fusion Middleware

Error Messages Reference for Oracle GoldenGate for Windows
and UNIX

12c (12.2.0.1)

E67828-02

January 2016

Provides information about the error messages in Oracle
GoldenGate for Windows and UNIX.

E67828-02

Copyright © 2013, 2016, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface	v
Audience.....	v
Documentation Accessibility	v
Related Documents	v
Conventions	vi

1 OGG-00001 to OGG-25050

Preface

This guide explains the Oracle GoldenGate error messages and their resolutions.

Audience

This guide is intended for installers, database administrators, and system administrators who are installing, configuring and running Oracle GoldenGate.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at
<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit
<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit
<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documents

The Oracle GoldenGate documentation set includes the following components:

Windows, UNIX, and Linux Platforms

- *Installing and Configuring Oracle GoldenGate for DB2 for i*
- *Installing and Configuring Oracle GoldenGate for DB2 LUW*
- *Installing and Configuring Oracle GoldenGate for DB2 z/OS*
- *Installing and Configuring Oracle GoldenGate for Informix*
- *Installing and Configuring Oracle GoldenGate for MySQL*
- *Installing and Configuring Oracle GoldenGate for NonStop SQL/MX*
- *Installing and Configuring Oracle GoldenGate for SQL Server*
- *Installing and Configuring Oracle GoldenGate for Oracle TimesTen*
- *Installing and Configuring Oracle GoldenGate for Oracle Database*
- *Installing and Configuring Oracle GoldenGate for Sybase*

- *Installing and Configuring Oracle GoldenGate for Teradata*
- *Administering Oracle GoldenGate for Windows and UNIX*
- *Reference for Oracle GoldenGate for Windows and UNIX*
- *Logdump Reference for Oracle GoldenGate*
- *Upgrading Oracle GoldenGate for Windows and UNIX*
- *Error Messages Reference for Oracle GoldenGate for Windows and UNIX*

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, such as "From the File menu, select Save ." Boldface also is used for terms defined in text or in the glossary.
<i>italic</i>	Italic type indicates placeholder variables for which you supply particular values, such as in the parameter statement: TABLE <i>table_name</i> . Italic type also is used for book titles and emphasis.
monospace MONOSPACE	Monospace type indicates code components such as user exits and scripts; the names of files and database objects; URL paths; and input and output text that appears on the screen. Uppercase monospace type is generally used to represent the names of Oracle GoldenGate parameters, commands, and user-configurable functions, as well as SQL commands and keywords.
UPPERCASE	Uppercase in the regular text font indicates the name of a utility unless the name is intended to be a specific case.
{ }	Braces within syntax enclose a set of options that are separated by pipe symbols, one of which must be selected, for example: { <i>option1</i> <i>option2</i> <i>option3</i> }.
[]	Brackets within syntax indicate an optional element. For example in this syntax, the SAVE clause is optional: CLEANUP REPLICAT <i>group_name</i> [, SAVE <i>count</i>]. Multiple options within an optional element are separated by a pipe symbol, for example: [<i>option1</i> <i>option2</i>].

OGG-00001 to OGG-25050

OGG-00001: Execution cannot continue - Program Terminating

Cause: This is a generic message that indicates a process failure.

Action: Look for other messages in the process report and error log that provide more context for this failure. If you cannot determine and resolve the problem, contact Oracle Support.

OGG-00002: Missing directory name

Cause: The directory name is missing from the DIRECTORY option of the TRANSMEMORY or LOBMEMORY parameter.

Action: Specify a directory for temporary storage with the DIRECTORY option, or use the default storage by removing the DIRECTORY option.

OGG-00003: Missing directory name end quote

Cause: A trailing (end) quote is missing from the directory specification in the DIRECTORY option of the TRANSMEMORY or LOBMEMORY parameter.

Action: Enclose the directory name within double quotes.

OGG-00004: Directory too long

Cause: The directory name that is specified with the DIRECTORY option of TRANSMEMORY or LOBMEMORY exceeds the length limit that is supported by the operating system.

Action: Specify a directory that has a path name that is within the operating system limitations.

OGG-00005: Invalid number for directory file size

Cause: The DIRECTORY option of TRANSMEMORY or LOBMEMORY contains an invalid value for the maximum file size, such as a non-numeric value or an invalid size specifier.

Action: Specify a valid value. See the Oracle GoldenGate reference documentation for valid directory size and valid size specifiers (such as GB for gigabytes and MB for megabytes).

OGG-00006: Directory options must be enclosed in parentheses

Cause: The directory specification of the DIRECTORY option of TRANSMEMORY or LOBMEMORY is not enclosed within parentheses.

Action: Enclose the entire directory specification in parentheses, as in this example: DIRECTORY (c:\test\dirtmp, 3000000000, 300000000)

OGG-00007: Invalid number for directory size

Cause: The DIRECTORY option of TRANSMEMORY or LOBMEMORY contains an invalid value for the maximum directory size, such as a non-numeric value or an invalid size specifier.

Action: Specify a valid value. See the Oracle GoldenGate reference documentation for valid directory size and valid size specifiers (such as GB for gigabytes and MB for megabytes).

OGG-00008: Missing directory file size

Cause: The file size specification is missing from the DIRECTORY option of TRANSMEMORY or LOBMEMORY.

Action: Specify a fully qualified directory name, a maximum directory size, and the maximum size of each file, as in: DIRECTORY (c:\test\dirtmp, 3000000000, 300000000).

OGG-00009: Directory parentheses must contain valid options

Cause: The DIRECTORY option of TRANSMEMORY or LOBMEMORY contains parentheses but no specification within them.

Action: Specify a fully qualified directory name, a maximum directory size, and the maximum size of each file, as in: DIRECTORY (c:\test\dirtmp, 3000000000, 300000000).

OGG-00010: Missing directory size and directory file size

Cause: The DIRECTORY option of TRANSMEMORY or LOBMEMORY does not contain a specification for the maximum directory and file size.

Action: Specify a fully qualified directory name, a maximum directory size, and the maximum size of each file, as in: DIRECTORY (c:\test\dirtmp, 3000000000, 300000000).

OGG-00011: Missing directory file size

Cause: The DIRECTORY option of TRANSMEMORY or LOBMEMORY does not contain a specification for the maximum file size.

Action: Specify a fully qualified directory name, a maximum directory size, and the maximum size of each file, as in: DIRECTORY (c:\test\dirtmp, 3000000000, 300000000).

OGG-00012: Command line error:invalid startup syntax: {0}

Cause: An unknown parameter is specified for the Extract or Replicat process that is being started from the command line

Action: Correct the syntax. The command can only contain PARAMFILE and REPORTFILE parameters, for example: /oggdir/extract paramfile dirprm/ext.prm reportfile /user/reports/ext.rpt.

OGG-00013: Missing {0} argument at startup

Cause: An argument is missing from the specified parameter.

Action: Supply the correct syntax. For help, see the Oracle GoldenGate reference documentation.

OGG-00014: Unrecognized parameter: {0}. Parameter could be misspelled or unsupported.

Cause: The specified parameter is not valid for this version of Oracle GoldenGate.

Action: Check the parameter file for the correct syntax, spelling, and any required terminators such as the semi-colon. Also make certain the parameter is supported

for this version of Oracle GoldenGate. To do both of those things, check the reference documentation for your version of Oracle GoldenGate.

OGG-00015: {0} is not supported. Check spelling or see Oracle GoldenGate Reference Guide for supported parameters.

Cause: The specified parameter is not valid for this version of Oracle GoldenGate.

Action: Check the parameter file for the correct syntax, spelling, and any required terminators such as the semi-colon. Also make certain the parameter is supported for this version of Oracle GoldenGate. To do both of those things, check the reference documentation for your version of Oracle GoldenGate.

OGG-00016: {0} is not supported. Check spelling or see Oracle GoldenGate Reference Guide for supported parameters.

Cause: The specified parameter is not valid for this version of Oracle GoldenGate.

Action: Check the parameter file for the correct syntax, spelling, and any required terminators such as the semi-colon. Also make certain the parameter is supported for this version of Oracle GoldenGate. To do both of those things, check the reference documentation for your version of Oracle GoldenGate.

OGG-00017: Not enough stack space. Specify FUNCTIONSTACKSIZE greater than {0,number,0}

Cause: The size of the memory stack that is used for processing Oracle GoldenGate column-conversion functions needs to be increased.

Action: Add the FUNCTIONSTACKSIZE parameter to the parameter file before the point where parameters that contain conversion functions are listed, and set it to at least the value shown in the error message. The value specifies the number of function arguments to allow in a parameter clause.

OGG-00018: {0} ignored when running as a RMTTASK.

Cause: The specified parameter is not supported for a remote task and is being ignored.

Action: Remove the parameter from the parameter file to avoid future messages like this.

OGG-00019: No GROUP value given for RMTTASK in EXTRACT parameter file.

Correct: GROUP group_name.

Cause: The RMTTASK parameter is missing the required GROUP clause.

Action: Add the GROUP clause so that the syntax is RMTTASK REPLICAT, GROUP group_name, where group_name is the name of the Replicat group on the target.

OGG-00020: The GROUP value in RMTTASK in the EXTRACT parameter file is too long.

Cause: The name of the group in the GROUP clause of RMTTASK is probably too long. An Oracle GoldenGate group name can be up to eight characters long.

Action: Reduce the length of the group name.

OGG-00021: The REPLICAT parameter in RMTTASK in the EXTRACT parameter file is not present.

Cause: The RMTTASK parameter requires the REPLICAT keyword.

Action: The correct syntax is RMTTASK REPLICAT, GROUP group_name, where group_name is the name of the Replicat group on the target.

OGG-00022: The GROUP parameter in a RMTTASK line in the EXTRACT param file is not present. GROUP group_name

Cause: The RMTTASK parameter is missing the required GROUP clause.

Action: Add the GROUP clause so that the syntax is RMTTASK REPLICAT, GROUP group_name, where group_name is the name of the Replicat group on the target.

OGG-00023: TCPBUFSIZE and TCPFLUSHBYTES are not supported in RMTTASK mode

Cause: The RMTHOST parameter contains the TCPBUFSIZE or TCPFLUSHBYTES option (or both), which are not supported for a remote task.

Action: Remove these options from the parameter file.

OGG-00024: Cannot specify both FORMATASCII and ENCRYPTTRAIL for '{0}'

Cause: ENCRYPTTRAIL and NOENCRYPTTRAIL cannot be used when FORMATASCII is used to write data to a file in ASCII format. The trail or file must be written in the default Oracle GoldenGate canonical format when encryption is used.

Action: Remove either FORMATASCII or ENCRYPTTRAIL from the parameter file, depending on the configuration requirement.

OGG-00025: Bulk load is only supported for Oracle 8i and above.

Cause: The BULKLOAD parameter is being used for Replicat against an Oracle version that is earlier than 8i.

Action: Do not use the BULKLOAD initial load method. See the Oracle GoldenGate administration documentation for other supported load methods.

OGG-00026: Bulk load not implemented for this database type.

Cause: The BULKLOAD parameter is being used for Replicat against a database that is not an Oracle database.

Action: Do not use the BULKLOAD initial load method. See the Oracle GoldenGate administration documentation for other supported load methods.

OGG-00027: {0} was not specified. Check Oracle GoldenGate documentation for correct usage.

Cause: The specified parameter is required but missing from the parameter file.

Action: Add the parameter. See the Oracle GoldenGate reference documentation for help with syntax and usage.

OGG-00028: Failed to retrieve column handle for table {0}, column #{1,number,0} while getting table definition.

Cause: The process could not retrieve the metadata for the specified table. Most likely, the table does not exist.

Action: Exclude the table from the TABLE or MAP statement.

OGG-00029: Failed to retrieve column list handle for table {0} while getting table definition.

Cause: The process could not retrieve the metadata for the specified table. Most likely, the table does not exist.

Action: Exclude the table from the TABLE or MAP statement.

OGG-00030: Could not resolve parameter {0}. Check spelling and usage in parameter file.

Cause: Oracle GoldenGate could not resolve the specified parameter. It might be misspelled or used incorrectly.

Action: Check the Oracle GoldenGate reference documentation for correct syntax and usage.

OGG-00031: Unspecified parameter name.

Cause: There are no runtime substitution parameters specified.

Action: To use parameter substitution, declare a runtime parameter instead of an actual value, and precede the runtime parameter name with a question mark (?), such as EXTFILE ?EXTFILE. Then, before starting the process, use the shell of the operating system to pass the runtime values by means of an environment variable. For more information, see the Oracle GoldenGate administration documentation.

OGG-00032: Parameter {0} was already specified.

Cause: The specified parameter appears more than once in the parameter file.

Action: Remove all but one instance of this parameter, and make sure it is the one that contains the correct options and values for your intended configuration.

OGG-00033: Parameter {0} was already specified ({1})

Cause: The specified parameter appears more than once in the parameter file.

Action: Remove all but one instance of this parameter, and make sure it is the one that contains the correct options and values for your intended configuration.

OGG-00034: Missing value for startup parameter {0}.

Cause: A value was not given for the specified parameter.

Action: Specify a value for this parameter. For permissible values, see the Oracle GoldenGate reference documentation.

OGG-00035: {0} does not take any additional parameters

Cause: Too many values are supplied for the specified parameter.

Action: See the Oracle GoldenGate reference documentation for correct syntax, options, and values.

OGG-00036: No tables specified in parameter file

Cause: The parameter file does not contain a TABLE or MAP parameter to specify the tables that are to be processed by Oracle GoldenGate.

Action: Add one or more TABLE parameters to an Extract parameter file or one or more MAP parameters to a Replicat parameter file.

OGG-00037: {0} file {1} already exists

Cause: The specified file name already exists.

Action: Specify a different file name or delete the existing file.

OGG-00038: Could not start TCP/IP (status {0,number,0}, err {1,number,0})

Cause: There was a Windows Sockets (Winsock) error when Oracle GoldenGate attempted to start TCP/IP services.

Action: Fix the problem that is reported in the Winsock error message.

OGG-00039: Invalid timeout value {0}

Cause: The value for the Collector timeout was not between 1 and 1800 seconds.

Action: Specify a value between 1 and 1800 for the -w Collector parameter.

OGG-00040: Missing timeout value

Cause: A value for the -w Collector timeout parameter was not provided.

Action: Specify a value between 1 and 1800 seconds for the -w Collector parameter.

OGG-00041: Data source not specified

Cause: The Oracle GoldenGate Extract (capture) process is configured with an unknown data source type.

Action: Recreate the Extract group with a supported data source type, such as TRANLOG, VAM, EXTTRAILSOURCE, or SOURCEISTABLE. For a complete list of data source options, see the ADD EXTRACT command in the Oracle GoldenGate reference documentation.

OGG-00042: {0} may not be used with this type of Extract

Cause: The specified parameter is not valid for use with the current Extract configuration.

Action: Remove the parameter. For help with configuring Extract for your requirements, see the Oracle GoldenGate documentation.

OGG-00044: PASSTHRU parameter can only be used with an extract data pump

Cause: The PASSTHRU parameter is specified in the parameter file of a primary Extract or a Replicat group.

Action: Remove PASSTHRU or create the Extract group to be a data pump, as applicable to your requirements.

OGG-00045: Trails cannot be used with {0}

Cause: A remote task is specified for this configuration of Oracle GoldenGate, but the RMTTRAIL or EXTTRAIL parameter is also used.

Action: Remove the trail parameters.

OGG-00046: Begin time must be specified for a {0}

Cause: The parameter file contains the SPECIALRUN parameter, but not a BEGIN parameter.

Action: Add the BEGIN parameter to the parameter file to specify a start time for the special run.

OGG-00047: Expected {0} parameter for task

Cause: The RMTTASK parameter is missing from the parameter file.

Action: Add the RMTTASK parameter.

OGG-00049: Trails cannot be used when SOURCEISTABLE/SOURCEISFILE is specified

Cause: The ADD EXTRACT command that created the Extract process was issued with the SOURCEISTABLE or SOURCEISFILE option to create a remote task. A remote task does not use disk storage for data, but a trail parameter was specified in the parameter file.

Action: Remove the EXTTRAIL or RMTTRAIL parameter.

OGG-00051: Must specify extract file when specifying {0}

Cause: The SPECIALRUN parameter is being used, but there is no EXTFILE or EXTTRAIL parameter to specify the output storage file.

Action: Add an EXTFILE or EXTTRAIL parameter.

OGG-00052: No replication maps specified

Cause: There are no MAP parameters in the Replicat parameter file to specify source and target table mappings.

Action: Add one or more MAP parameters to the Replicat parameter file.

OGG-00053: No extraction maps specified

Cause: There are no TABLE parameters in the Extract parameter file to specify source tables for which to capture data.

Action: Add one or more TABLE parameters to the Extract parameter file.

OGG-00054: Remote task entry encountered in the parameter file without a remote host entry given first

Cause: The RMOTTASK parameter is used in the Extract parameter file to specify a remote task, but the target host is not specified with the RMTHOST parameter.

Action: Add the RMTHOST parameter to the Extract parameter file. For help with configuring a remote task, see the Oracle GoldenGate administration documentation. For more information about RMTHOST and RMOTTASK, see the Oracle GoldenGate reference documentation.

OGG-00055: {0} is not supported for passive mode

Cause: The Extract group was created as a passive Extract by using the ADD EXTRACT command with the PASSIVE option, but the parameter file for this group contains the specified parameter, which is not supported in passive mode.

Action: Remove the parameter from the Extract parameter file.

OGG-00056: Too many trail/file definitions in passive mode

Cause: This Extract process is configured in PASSIVE mode, but there are multiple RMTFILE or RMTTRAIL definitions.

Action: Remove all but one RMTFILE or RMTTRAIL definition.

OGG-00057: Only REMOTE trail/file is allowed in passive mode

Cause: The Extract group was added in PASSIVE mode, but the parameter file specifies an EXTTRAIL or EXTFILE local trail or file.

Action: Remove the specification for the local file, and use the RMTTRAIL or RMTFILE parameter instead.

OGG-00058: Begin time {{0,date} {0,time}} must precede end time {{1,date} {1,time}}

Cause: The parameter file contains a parameter that takes a begin and end time as input, but the end time is listed before the begin time.

Action: Edit the parameter syntax to specify the begin time before the end time. For help, see the Oracle GoldenGate reference documentation.

OGG-00059: GGS sets error {0,number,0} to {1} internally, cannot override the error response to {2}

Cause: The REPERROR parameter contains a response rule for the specified error number, but this error is handled internally by Oracle GoldenGate, and the REPERROR setting is ignored.

Action: Remove the REPERROR rule that caused the error.

OGG-00060: Extract requires a value specified for parameter {0} when in archived log only mode.

Cause: The specified parameter is a required parameter when Extract operates in archived-log mode.

Action: Add the parameter to the Extract parameter file, and then restart the process. For syntax and usage, see the Oracle GoldenGate reference documentation.

OGG-00061: DEFERAPPLYINTERVAL cannot be less than EOFDELAY.

Cause: The DEFERAPPLYINTERVAL parameter is used in the parameter file to control how long Replicat waits before applying data to the target; however, the value is lower than the value of EOFDELAY, which controls how often Replicat checks for new data in the trail.

Action: Set DEFERAPPLYINTERVAL to a higher value than that of EOFDELAY.

OGG-00062: DEFERAPPLYINTERVAL cannot be greater than 1 week.

Cause: The value of DEFERAPPLYINTERVAL is set to more than seven days (one week).

Action: Reduce the value to seven or fewer days (or the equivalent seconds, minutes, or hours). See the Oracle GoldenGate reference documentation for valid units.

OGG-00063: CHECKOPCOMPLETE: No operation type was set in the VAMRead

Cause: The operation type attribute of the record that is being passed by the VAM API was not set by the VAM module.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00064: CHECKOPCOMPLETE: The DDL database object type has an invalid operation type: {0,number,0}

Cause: The operation type attribute for the record that is being passed by the VAM API does not match one of the DDL database object types.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00065: CHECKOPCOMPLETE: The table database object type has an invalid operation type: {0,number,0}

Cause: The operation type attribute for the record being passed by the VAM API does not match the table database object type.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00066: CHECKOPCOMPLETE: The database object type is invalid: {0,number,0}

Cause: The database object type attribute for the record being passed by the VAM API does not match any known database object types.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00067: CHECKOPCOMPLETE: No DDL statement was received for a record with a DDL database object type

Cause: No DDL statement was given by the VAM API for the DDL record that is being processed.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00068: CHECKOPCOMPLETE: No object name was set for operation type: {0,number,0}

Cause: The object name attribute for the record being passed by the VAM API was not set by the VAM module.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00069: CHECKOPCOMPLETE: No object owner was set for operation type: {0,number,0}

Cause: The object owner attribute for the record being passed by the VAM API was not set by the VAM module.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00070: CHECKOPCOMPLETE: No timestamp was set for operation type: {0,number,0}

Cause: The timestamp attribute for the record being passed by the VAM API was not set by the VAM module.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00071: CHECKOPCOMPLETE: No transaction identifier was set for operation type: {0,number,0}

Cause: The transaction identifier attribute for the record being passed by the VAM API was not set by the VAM module.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00073: CHECKOPCOMPLETE: No before keys in primary key update were added for operation type: {0,number,0}

Cause: No before image key fields were sent for a primary key update record being passed by the VAM API.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00074: CHECKOPCOMPLETE: Before key in primary key update was not added for column(s): {1}: Operation type: {0,number,0}

Cause: No before image key fields were sent for a primary key update record being passed by the VAM API.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00075: CHECKOPCOMPLETE: Key column was not added for column(s) {1}: Operation type: {0,number,0}

Cause: The value for the after image key column required for an update record was not passed by the VAM API.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00076: GG_OBJ_RECORD: GG_ATTR_OBJECT_NAME: Object owner attribute was already set as part of the object name

Cause: The object owner attribute for the record being passed by the VAM API was already included in the object name attribute.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00077: GG_OBJ_RECORD: GG_ATTR_OBJECT_NAME: Object owner attribute must be set before the object name is set

Cause: The object owner attribute for the record being passed by the VAM API was set after the object name attribute was set. It is a VAM API requirement that it be set before the object name attribute.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00078: DDL processing is not implemented for this target

Cause: A DDL record was encountered in the transaction log. Oracle GoldenGate does not support the capture or replication of DDL for this type of database.

Action: Because DDL was applied on the source but not replicated, the source and target definitions are out of synchronization. Future DML may result in errors. You can ignore this message and accept the inconsistencies, or you can apply the DDL on the target before allowing DML operations on this object. Stop and start Replicat after the DDL changes are made.

OGG-00079: Metadata object processing is not implemented for this target

Cause: The VAM API does not support the exchange of table metadata for the database being used.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00080: Invalid I/O type encountered {0,number,0}

Cause: This message is specific to the Teradata VAM implementation. An end transaction record was expected, but another record type was received.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00081: GG_OBJ_METADATA: GG_ATTR_MD_COLUMN_COUNT: Column count must be greater than zero

Cause: An insert, update, or delete record was sent by the VAM API, but no columns for the record were received.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00082: GG_OBJ_METADATA: GG_ATTR_MD_COLUMN_COUNT: Previous table not completed

Cause: The metadata processing for the current table was not complete when an attempt was made to start processing the metadata for the next table in the sequence.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00083: Transaction list update: Number of transactions has changed

Cause: This message is specific to the Teradata VAM implementation. Recovery processing cannot complete because the recovery trail file has been updated by another process after recovery processing started.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00084: Transaction list processing only available in maximum protection mode

Cause: This message is specific to the Teradata VAM implementation. Recovery processing is only supported in maximum protection mode and maximum performance mode was specified.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00085: {1}:Invalid attribute {0,number,0}]

Cause: The attribute type set by the VAM module is unknown.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00086: {1}:Attribute {0,number,0} has invalid value

Cause: The attribute value set by the VAM module is invalid for the attribute type.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00087: Transaction list update: Transaction ID has changed for index {0,number,0}

Cause: This message is specific to the Teradata VAM implementation. Recovery processing cannot complete because the recovery transaction list passed to the VAM module is no longer valid.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00088: {1}: Attribute {0,number,0}: The pointer to the return parameter for the attribute length cannot be null

Cause: No return buffer was given to hold the length of the value when the VAM module is retrieving a value from the VAM kernel.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00089: Object {0,number,0}: Attribute {1,number,0}: Attribute is invalid for object

Cause: The attribute type assigned by the VAM module is invalid for the VAM API object type it is setting.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00090: Transaction list is not available for the generic VAM

Cause: The functionality being requested is only available for the Teradata VAM implementation.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00091: {0}

Cause: The error message that is displayed is returned from a separate sub-subsystem called by the VAM API.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00092: {0}: A maximum return length of zero and a null pointer to the return parameter for the attribute length are an invalid combination

Cause: No return buffer was given to hold the length of the value when the VAM module is retrieving the length of value from the VAM kernel.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00094: Object {0,number,0}: Attribute {1,number,0}: Length ust be greater than zero

Cause: The attribute for the object being passed to the VAM API by the VAM module must contain a value.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00095: {1}: Attempting to add attribute {0,number,0} before index set for column

Cause: A column attribute is being passed to the VAM API by the VAM module before the column index identifying that column has been set.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00096: {3}: Attribute {0,number,0} Length given ({2,number,0}) exceeds maximum length allowed ({1,number,0})

Cause: The length of the attribute being passed to the VAM API by the VAM module exceeds the maximum length allowed for that attribute type.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00097: {0}: Invalid length for an integer value

Cause: An integer value is being passed to the VAM API by the VAM module, but the length given is not either 1, 2, 4 or 8 bytes, which are the only lengths allowed.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00098: Object {0,number,0}: Attribute {1,number,0}: Invalid length {2,number,0}

Cause: A C/C++ int value is being passed to the VAM API by the VAM module, but the length given is not the same as the length of an int as returned by that compiler.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00099: {0}: Invalid data format type

Cause: The data format type assigned by the VAM module is invalid for the VAM API attribute type it is setting.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00100: {1}: Attribute {0,number,0}: Column is not nullable]

Cause: A null value was passed to the VAM API by the VAM module for a column whose metadata marked it as not nullable.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00101: {1}: Attribute {0,number,0}: Only integers are scalable]

Cause: A decimal scale was passed to the VAM API by the VAM module for a column data type for which it is invalid.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00102: {1}: Attribute {0,number,0}: Scale does not match table definition

Cause: The decimal scale passed to the VAM API by the VAM module for a column does not match the table metadata definition.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00103: {1}: {0}: GG_ATTR_MD_COLUMN_COUNT not set

Cause: A metadata attribute from the Extract parameter file is being retrieved via the VAM API by the VAM module before the metadata processing has started for that table.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00104: VAM module calling GGCollMetadataAddByIndex without setting GG_ATTR_MD_COLUMN_COUNT with the number of columns to be added

Cause: A column metadata attribute is being passed to the VAM API by the VAM module before the column processing has started.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00105: {0}: Table lookup in database has either not taken place or failed: Check return code of GGAttrSet for GG_ATTR_OBJECT_NAME

Cause: The VAM module is attempting to continue processing the metadata for a table after the VAM API returned an error code on a previous call.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00106: {0}: Adding column before operation type set

Cause: A column value is being passed to the VAM API by the VAM module before the operation type was set for the record.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00107: GG_OBJ_RECORD: Invalid VAM operation type {0,number,0}

Cause: The operation type attribute being passed to the VAM API by the VAM module for the VAM API record object is unknown.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00108: GG_OBJ_RECORD: No transaction ID was given in DCI interface call

Cause: No transaction identifier was given in the Direct Call Interface call when the VAM module was sending a record via the VAM API.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00109: {0} requires maximum protection mode

Cause: This message is specific to the Teradata VAM implementation. The VAM module sent a prepare transaction record via the VAM API in maximum performance mode. This is only allowed in maximum protection mode.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00110: {0}: VAM session using local ASCII format timestamps for position time: Integer format Julian GMT timestamps invalid.

Cause: The VAM module is sending timestamps in a Julian format as an integer value while the session protocol is to use ASCII timestamps.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00111: {0}: VAM session using integer format Julian GMT timestamps for position time: Local ASCII format timestamps invalid.

Cause: The VAM module is sending timestamps in an ASCII format while the session protocol is to use a Julian format passed as an integer.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00112: GG_OBJ_RECORD: {0} must be set before {1}

Cause: A required attribute in the VAM API record object was not set in the right order by the VAM module.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00113: GG_OBJ_RECORD: GG_ATTR_BEFORE_AFTER can only be used with GG_OPTYPE_UPDATE for primary key updates

Cause: The VAM module tried to add a before key for a record that is not a primary key update.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00115: GG_OBJ_RECORD: Attribute {0,number,0}: Null pointer passed for value

Cause: No buffer was given for the VAM kernel to retrieve the value when the VAM module is setting an attribute value via the VAM API.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00116: VAMMessage error returned by VAM

Cause: A call from GGSCI to the VAMMessage function implemented by the user in the VAM module returned with an error.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00117: VAMMessage called before VAM module initialized

Cause: A call from GGSCI to the VAMMessage function was made before the VAM module was initialized by a call to VAMInitialize.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00118: {1}: Index {0,number,0} is not in sequential order

Cause: A column was sent out of sequential order by the VAM module when sending the columns for an insert, update or delete record.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00119: {1}: Index {0,number,0} is out of range of columns added to record

Cause: A column index was sent by the VAM module that is greater than the number of columns available for the table, when sending the columns for an insert, update or delete record.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00120: The maximum length allowed for LOB row ID was exceeded

Cause: The maximum size of the buffer available to hold the unique ID generated for a LOB column was exceeded by the length of the ID that was generated.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00121: {1}: Invalid VAM action {0,number,0}]

Cause: An invalid action type was passed by the VAM module when generating an informational, warning or error message to be sent to and output by the VAM API.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00122: Large column support is not implemented in this release

Cause: The maximum column size was exceeded for the column value sent by the VAM module by the VAM API.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00123: No columns given in DCI interface call

Cause: An insert, update or delete record was sent in the Direct Call Interface call to the VAM API but no columns for the record were received.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00124: Input data format must be set to zero

Cause: The data format type was set by the VAM module for an attribute passed to the VAM API that does not possess a data type. The data format value should be set to zero in this case.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00125: Object {0,number,0}: Attribute {1,number,0}: Column values can not be set directly

Cause: An attempt was made to use one of the deprecated column attributes that were originally used to set column values directly.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00126: Object {0,number,0}: Attribute {1,number,0}: String does not contain a value

Cause: An attribute value was sent by the VAM module as a null-terminated string, but the null-terminated string has a length of zero instead of a value (required).

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00127: Object {0,number,0}: Attribute {1,number,0}: Maximum length allowed exceeded

Cause: The attribute value set by the VAM module for the transaction identifier in the VAM API record object exceeds the maximum length allowed for transaction identifier.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00128: Large column processing in progress: invalid data format

Cause: An invalid data format type was passed by the VAM module when processing large and LOB columns that are sent in blocks across the VAM API.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00129: Adding column before metadata retrieved

Cause: The VAM module is sending the column values for a table via the VAM API before the metadata exchange for that table has taken place.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00130: Table {0}: Column {1} has invalid type for a key column

Cause: The data type of the primary key of this table is not supported by Oracle GoldenGate as a key.

Action: Specify an alternate key by using a KEYCOLS clause in the parameter file. For more information, see the Oracle GoldenGate reference documentation. For supported data types in keys, see the Oracle GoldenGate installation and setup documentation for your database.

OGG-00133: GG_OBJ_METADATA: {0} returned an error

Cause: There was an error trying to retrieve metadata with the specified VAM function.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00134: VAM attempting retrieve GG_ATTR_MD_KEYCOLUMNS when GG_ATTR_MD_KEYCOLUMNS_COUNT is set to zero and there are no key columns to return

Cause: During the table metadata exchange the VAM module is attempting to retrieve the value of the KEYCOLUMNS array specified in the Extract parameter file when there are no KEYCOLUMNS values to retrieve.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00135: GG_OBJ_METADATA: Table {0} has no key columns specified and no columns that can be used as key columns

Cause: The specified table contains no defined key columns and no other columns that Oracle GoldenGate can use as key columns. Oracle GoldenGate will attempt

to use all of the columns as a key, or you can specify a KEYCOLS clause in the source TABLE and target MAP parameters. For more information, see the Oracle GoldenGate reference documentation.

Action: None

OGG-00136: {0} is a deprecated VAM API function and is longer in use

Cause: An incompatible version of the VAM API module is being used.

Action: Contact Oracle Support to obtain the current version.

OGG-00137: GG_OBJ_COLUMN: Invalid integer type {0,number,0}

Cause: An invalid integer was passed by the VAM module when sending the columns for an insert, update or delete record via the VAM API.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00138: A SORTTRANLOG extract requires either a TERADATA or a VAMTRD pre-processor define to build successfully

Cause: This message is specific to the Teradata VAM implementation. The executable was built without the defines that are required in order to enable the functionality being requested.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00139: Extract was not built with VAM functionality included

Cause: This Extract build does not include a VAM module.

Action: Obtain the correct Extract build for your database from Oracle.

OGG-00140: Error {0,number,0}, source {1,number,0} - {2}

Cause: Inter-process communication failed. This error is related to the Oracle GoldenGate vendor access module (VAM).

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00141: {1} Invalid VAM type:{0,number,0}

Cause: The Extract type was not given in the TRANLOGOPTIONS clause in the Extract parameter file for the Teradata implementation of the VAM API.

Action: Specify the correct Extract type, either COMMITTEDTRANLOG, CREATETRANLOG, or SORTTRANLOG. If the problem persists, contact Oracle Support.

OGG-00142: {0}: Adding column before table owner set

Cause: The VAM module sent a column through the VAM API for an insert, update or delete operation before it set the required record attribute that specifies the object owner of the record.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00143: {0}: Adding column before table name set

Cause: The VAM module sent a column through the VAM API for an insert, update or delete operation before it set the required record attribute specifying the object name of the record.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00144: Fatal error reported by VAM reader thread

Cause: A fatal error was reported in another thread in the multi-threaded VAM Extract, and this thread terminated because of that error.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00145: Call to {0} returned with error status {1,number,0}

Cause: One of the VAM API functions implemented in the VAM module returned an error status on completion of the call to that function in the VAM kernel.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00146: Call to {0} returned with error status {1,number,0}: {2}

Cause: One of the VAM API functions implemented in the VAM module returned an error status on completion of the call to that function in the VAM kernel, after previously reporting a fatal error in the call.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00147: Call to {0} returned with error status {1,number,0}: {2}

Cause: The VAM API VAMControl function returned an error when being called as part of the shutdown processing caused by a previously reported fatal error.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00148: Prepare is invalid in maximum performance mode

Cause: This message is specific to the Teradata VAM implementation. The VAM module sent a prepare transaction record via the VAM API in maximum performance mode. This is only allowed in maximum protection mode.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00149: Rollbacks of transactions are not allowed in maximum protection mode

Cause: This message is specific to the Teradata VAM implementation. The VAM module sent a rollback transaction record via the VAM API, but only successfully committed transactions can be sent by the VAM module for the Teradata implementation.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00150: No value set for table name

Cause: The metadata for the table in the VAM kernel does not contain a valid table name. This is required for the standard header structure used to preface each output trail file record to identify the table in that file.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00151: The GG_ATTR_OP_COMPLETE attribute was not checked after adding a record before the VAMRead completed

Cause: The optional validation checking is on, and the VAM module did not make the final call to verify that the validation was successful. This validation checking is on by default in debug builds to ensure that the VAM module completed all of the requirements for sending a record via the VAM API. It is designed to be used for development by third-parties that are building their own VAM module as a dynamic link library or shared library.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00152: Begin transaction - transaction {0} already exists in file memory

Cause: A duplicate begin-transaction identifier was encountered for a database transaction. An identifier must be unique to maintain transaction integrity.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00153: Invalid GG_ATTR_OPTYPE: {0}: Transaction type is invalid for VAM generic mode]

Cause: The VAM module sent an unknown or invalid operation type via the VAM API. An example of an invalid operation is a prepare-transaction record for implementations that do not support a two-phase commit mechanism. This can occur in the Teradata implementation, where Extract is in COMMITTEDTRANLOG mode and does not support prepare-transaction records (although in CREATETRANLOG and SORTTRANLOG modes it does).

Action: If using the Teradata implementation, check that Extract is being run in CREATETRANLOG or SORTTRANLOG mode. If the problem persists contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00154: GG_OBJ_METADATA: The new table entry pointer is null

Cause: Table metadata is being looked up by the VAM module as the table is encountered dynamically, and there was an error in the defined protocol for exchanging the table metadata.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00155: GG_OBJ_METADATA: Table name has a length of {0,number,0}, but the maximum allowed is {1,number,0}

Cause: The name of the table contains too many characters to be supported by Oracle GoldenGate.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00156: GG_OBJ_METADATA: Owner name has a length of {0,number,0}, but the maximum allowed is {1,number,0}

Cause: The owner name of the table contains too many characters to be supported by Oracle GoldenGate.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00157: GG_OBJ_METADATA: Number of tables processed ({1,number,0}) does not match the number given ({0,number,0})

Cause: The table metadata is being exchanged statically in the VAMInitialize function from the VAM module to the VAM kernel or vice-versa, and the number

of tables that require a metadata exchange does not match the number of tables that were exchanged.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00158: GG_OBJ_METADATA: REP_get_table_by_name returned without finding a match

Cause: A TABLE parameter in the Extract parameter file lists a table explicitly by its full name, but Oracle GoldenGate could not find the table name in the metadata dictionary that was retrieved from the database catalog.

Action: Check the parameter file for errors in the TABLE specification. Make certain that the table exists in the database.

OGG-00159: GG_OBJ_METADATA: WILDCARD_check_table returned without finding a match

Cause: The TABLE parameter in the Extract parameter file contains a wildcarded table list, but no tables to satisfy it could be found in the metadata dictionary that was retrieved from the database catalog.

Action: Check the parameter file for errors in the TABLE specification. Make certain that the database contains tables that match the wildcard specification and which you want to be captured.

OGG-00160: GG_OBJ_METADATA: WILDCARD_getNextStaticTable returned with no entry found

Cause: The TABLE parameter in the Extract parameter file contains a wildcarded table list, but no tables to satisfy it could be found in the metadata dictionary that was retrieved from the database catalog.

Action: Check the parameter file for errors in the TABLE specification. Make certain that the database contains tables that match the wildcard specification and which you want to be captured.

OGG-00161: More than one output queue file specified for CREATETRANLOG VAM

Cause: This is specific to the Teradata implementation of the VAM API. The Extract group is configured in CREATETRANLOG mode, but there is more than one EXTTRAIL entry in the Extract parameter file. In this mode, Extract can only write to one local trail.

Action: Edit the Extract parameter file to remove the extra EXTTRAIL specifications, and then restart the Extract process.

OGG-00162: Remote queue file specified for CREATETRANLOG VAM

Cause: This is specific to the Teradata implementation of the VAM API. The Extract group is configured in CREATETRANLOG mode, but there is a RMTTRAIL parameter in the Extract parameter file.

Action: Replace the RMTTRAIL parameter with an EXTTRAIL parameter. In CREATETRANLOG mode, Extract must write to one local trail, not a remote trail.

OGG-00163: Checkpointing is mandatory

Cause: This message is specific to the Teradata VAM implementation. Checkpointing is required for this implementation and checkpointing was not initialized.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00164: The maximum item identifier length ({0,number,0}) has been exceeded

Cause: The VAM module set an attribute through the VAM API with a value that is longer than the maximum defined for that attribute in the VAM API specifications.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00165: No options parameters were specified in the parameter file

Cause: The DSOPTIONS parameter is missing from the parameter file, but is required to specify the processing actions that this Extract group performs.

Action: Add DSOPTIONS with the correct processing options for this Extract group. For help with configuring Extract for Teradata, see the Oracle GoldenGate installation and setup documentation for the Teradata database.

OGG-00166: Lookup failure on table {0}

Cause: The specified table is listed in the TABLE parameter but the metadata for this table could not be found.

Action: Check the parameter file for a misspelling of the table name. If there are no mistakes in the parameter file, make certain that the table exists in the database. If the table exists and the parameter file is correct, contact Oracle Support.

OGG-00167: Only wildcarded table definitions are allowed in the parameter file for the transaction reader implementation of the VAM

Cause: In the Teradata VAM implementation, tables can only be looked up as they are encountered dynamically, so the table metadata cannot be exchanged statically in the VAM API VAMInitialize function.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00168: WILDCARDRESOLVE DYNAMIC parameter is mandatory for the transaction reader implementation of the VAM

Cause: The WILDCARDRESOLVE parameter is not set to DYNAMIC, which is the required setting for the VAM implementation.

Action: Edit the parameter file to change WILDCARDRESOLVE to DYNAMIC, or add WILDCARDRESOLVE DYNAMIC if it is not present.

OGG-00169: No VAM parameters were specified in the parameter file

Cause: The parameter file for this VAM-based Extract process does not contain the VAM parameter. This parameter is required for VAM-based Extract groups for this source database.

Action: Add the VAM parameter with the associated PARAMS clause to the Extract parameter file. For syntax per source database type, see the Oracle GoldenGate reference documentation.

OGG-00170: No VAM PARAMS items were found in the param file

Cause: The parameter file for this VAM-based Extract process does not contain the VAM parameter with PARAMS options. PARAMS input is required for VAM-based Extract groups for this source database.

Action: Add the VAM parameter with the PARAMS clause to the Extract parameter file. For syntax and required input for PARAMS per source database type, see the Oracle GoldenGate reference documentation.

OGG-00171: The PARAMS section in the VAM options is invalid

Cause: The PARAMS clause of the VAM parameter in the Extract parameter file is incorrect.

Action: Check the parameter syntax for typographical errors. For syntax and valid options, see the VAM parameter in the Oracle GoldenGate reference documentation.

OGG-00172: No VAM PARAMS section was found in the param file

Cause: The parameter file for this VAM-based Extract process does not contain the VAM parameter with the PARAMS option. This parameter is required for VAM-based Extract groups for this source database to specify VAM input parameters.

Action: Add the VAM parameter with the PARAMS clause to the Extract parameter file. For syntax and required input for PARAMS per source database type, see the Oracle GoldenGate reference documentation.

OGG-00173: The {0} option is not implemented in this release

Cause: The specified option is not supported in this release of Oracle GoldenGate.

Action: For valid syntax, see the Oracle GoldenGate reference documentation.

OGG-00174: {0} is incompatible with the other options given

Cause: The specified parameter option is being used with other, incompatible options.

Action: To determine the correct syntax and valid options, see the Oracle GoldenGate reference documentation.

OGG-00175: Length of VAM load module exceeds maximum allowed

Cause: The length of the name of the VAM load module exceeds the allowed length.

Action: Rename the module to an acceptable length, then specify the new name wherever the module is specified in parameters, then restart the Extract process.

OGG-00176: No VAM load module was specified in the param file

Cause: The VAM load module is not specified with the VAM parameter in the Extract parameter file.

Action: Specify the load module with VAM and then restart Extract.

OGG-00177: {0} is not supported for VAM based extracts.

Cause: The specified parameter is not supported for a VAM-based Extract.

Action: Remove the parameter from the parameter file, and then restart the Extract process.

OGG-00178: {0}

Cause: The specified VAM error occurred.

Action: Resolve the problem according to the error message or contact Oracle Support.

OGG-00179: Operation type {0,number,0} is invalid: Rollback to savepoint in a transaction is not allowed

Cause: The Oracle GoldenGate VAM does not support partial rollback operations. A transaction must be either committed or rolled back in its entirety.

Action: Contact Oracle Support.

OGG-00180: The transaction reader VAM cannot be run in single-threaded mode if HAVEPTHREADS is defined as a pre-processor build directive

Cause: The VAM API kernel was built in multi-threaded mode, but the rest of the Extract executable was built in single-threaded mode.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00181: The transaction reader VAM cannot be run in multi-threaded mode unless HAVEPTHREADS is defined as a pre-processor build directive

Cause: The VAM API kernel was built in single-threaded mode, but the rest of the Extract executable was built in multi-threaded mode.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00182: VAM API running in single-threaded mode

Cause: The Oracle GoldenGate VAM is running in single-threaded mode.
Informational only.

Action: None

OGG-00183: VAM API running in multi-threaded mode

Cause: The Oracle GoldenGate VAM is running in multi-threaded mode.
Informational only.

Action: None

OGG-00184: {0} is not supported for SQL/MX ODBC replicat.

Cause: The specified parameter is not supported by Replicat for a SQL/MX database.

Action: Remove the parameter, and then restart the process.

OGG-00185: Warning table {0} does not exist in SQL/MX db.

Cause: The specified table is listed in the Oracle GoldenGate parameter file but does not exist in the database.

Action: Edit the parameter file to remove the table, or add the table to the database.

OGG-00186: Encountered SQL/MX fetching from table {0}

Cause: A fetch from the specified table failed.

Action: Look for further error messages to determine the cause.

OGG-00187: TMFVAM_read Record version mismatch.

Cause: The record version does not match the version that Extract expects. This indicates that the vamserv module is not the same version as that of Extract.

Action: Install the version of vamserv that matches the version of Extract.

OGG-00188: TMFVAM Error {1,number,0} returned from {0}

Cause: The specified error occurred in the vamserv module.

Action: If you cannot determine the cause and resolution based on the error text, contact Oracle Support.

OGG-00189: TMFVAM_init() was not called

Cause: This is an internal logic error.

Action: Contact Oracle Support.

OGG-00190: Unable to determine the Guardian filename for '{0}'

Cause: Extract cannot determine a valid Guardian filename. The symlink is either missing or pointing to an invalid file name.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00191: Error {1,number,0} Completing I/O to {0}

Cause: An interprocess message from Extract to the vamserv module failed.

Action: Not recoverable. Restart Extract. If the problem persists, contact Oracle Support.

OGG-00192: Unknown response code {1,number,0} from {0}

Cause: Extract received a message from the vamserv module that it cannot process.

Action: Not recoverable. Restart Extract. If the problem persists, contact Oracle Support.

OGG-00193: Error {1,number,0} Posting WRITEREAD request to {0}

Cause: Extract encountered a file system error while initiating a request to vamserv.

Action: Not recoverable. Restart Extract. If the problem persists, contact Oracle Support.

OGG-00194: Error '{0}' process not open.

Cause: The VAMSERV process is has not been opened for interprocess communication.

Action: Not recoverable. Restart Extract. If the problem persists, contact Oracle Support.

OGG-00195: FILE_OPEN_error {2,number,0} on process {0} ({1})

Cause: An open on the vamserv process failed.

Action: Not recoverable. Restart Extract. If the problem persists, contact Oracle Support.

OGG-00196: PROCESS_CREATE_error {1,number,0},{2,number,0} on {0}

Cause: The creation of a vamserv process failed. The OS error is shown in the message text.

Action: Evaluate the OS error in the message and take the appropriate action. If the problem persists, contact Oracle Support.

OGG-00197: Missing argument

Cause: A parameter contains a missing or invalid input argument.

Action: Edit the parameter file to correct the syntax. For help, see the Oracle GoldenGate reference documentation.

OGG-00198: Missing/invalid argument

Cause: A parameter contains a missing or invalid input argument.

Action: Edit the parameter file to correct the syntax. For help, see the Oracle GoldenGate reference documentation.

OGG-00199: Table {0} does not exist in target database

Cause: The specified table that is named in the Replicat parameter file does not exist in the target database.

Action: Verify the table specification in the parameter file and in the database. Edit the parameter file accordingly.

OGG-00200: Table name missing

Cause: A parameter requires the name of a table as input, and the name was not supplied.

Action: Edit the parameter file to supply the table name.

OGG-00201: Column {0} not found

Cause: A column that is specified in the parameter file cannot be found in the table metadata.

Action: Verify the column specification in the parameter file and in the table definition. Edit the parameter file accordingly.

OGG-00202: Record definition name missing

Cause: The DEF option for a TABLE parameter in a DEFGEN parameter file is missing a value that specifies the definitions template.

Action: Specify the name of the definitions template.

OGG-00203: Unknown param for Table/File {0}

Cause: The TABLE or FILE parameter contains an unknown or invalid option.

Action: Verify that the TABLE or FILE syntax is correct, and look for typographical errors. For help with syntax, see the Oracle GoldenGate reference documentation.

OGG-00204: Missing {0} specification

Cause: The specified parameter syntax is required.

Action: Add the specified syntax. For help, see the Oracle GoldenGate reference documentation.

OGG-00205: Syntax error in size specification: {0}

Cause: The size given as input to this parameter is either invalid or supplied in an invalid format.

Action: Specify a valid size specification for this parameter. For help, see the Oracle GoldenGate reference documentation.

OGG-00206: Invalid {0} specification

Cause: The parameter contains an invalid input specification.

Action: Specify a valid input specification for this parameter. For help, see the Oracle GoldenGate reference documentation.

OGG-00207: Invalid {0} specification ({1})

Cause: The parameter contains an invalid input specification.

Action: Specify a valid input specification for this parameter. For help, see the Oracle GoldenGate reference documentation.

OGG-00208: Missing/invalid {0} specification

Cause: An input specification is missing or invalid for the parameter.

Action: Specify a valid input specification for this parameter. For help, see the Oracle GoldenGate reference documentation.

OGG-00209: Missing value for {0}

Cause: The specified parameter does not contain an input value.

Action: Specify a value for this parameter. For help with syntax and values, see the Oracle GoldenGate reference documentation.

OGG-00210: Invalid option for {0}

Cause: The parameter could not be parsed because it contains an invalid option.

Action: Fix the syntax. For help with syntax and values, see the Oracle GoldenGate reference documentation.

OGG-00211: Invalid option: {0}

Cause: The parameter could not be parsed because the specified option is invalid.

Action: Fix the syntax. For help with syntax and values, see the Oracle GoldenGate reference documentation.

OGG-00212: Invalid option for {0}: {1}

Cause: The parameter could not be parsed because the specified option is invalid.

Action: Fix the syntax. For help with syntax and values, see the Oracle GoldenGate reference documentation.

OGG-00213: Missing or invalid option for {0}

Cause: The parameter could not be parsed because a given option is either invalid or missing.

Action: Check the syntax for the specified parameter. For help with syntax and values, see the Oracle GoldenGate reference documentation.

OGG-00214: Value must be between {0,number,0} and {1,number,0}

Cause: The value is not valid.

Action: Supply a value that is within the stated range.

OGG-00215: Value for {0} must be between {1,number,0} and {2,number,0}

Cause: The value given for the specified parameter is not valid.

Action: Supply a value that is within the stated range.

OGG-00216: Value for {0} must be numeric, found {1}

Cause: An invalid value was given for the specified parameter.

Action: Provide a numeric value. For valid values, see the Oracle GoldenGate reference documentation.

OGG-00217: Value for {0} must be numeric

Cause: An invalid value was given for the specified parameter.

Action: Provide a numeric value. For valid values, see the Oracle GoldenGate reference documentation.

OGG-00218: Invalid value for {0}

Cause: An invalid value was given for the specified parameter.

Action: Provide a valid value. For help with syntax and values, see the Oracle GoldenGate reference documentation.

OGG-00219: Invalid value for {0}: {1}

Cause: The specified parameter contains an invalid value.

Action: Fix the problem that is shown in the error in the message text. For help with syntax and values, see the Oracle GoldenGate reference documentation.

OGG-00220: Invalid number of arguments for {0} {1}

Cause: The specified parameter requires more option arguments than were provided.

Action: Add the required arguments. For help with syntax, see the Oracle GoldenGate reference documentation.

OGG-00221: Invalid {0} setting for {1}; {2}

Cause: The specified option of this parameter is set to an invalid value.

Action: Specify a valid value. For more information, see the Oracle GoldenGate reference documentation.

OGG-00222: The column(s) used for the @RANGE filter for table {0} contain only NULL value(s) : There must be at least one non-NULL value present

Cause: The columns that are specified for the @RANGE filter contain only null values.

Action: Specify columns that have values, or remove the columns specification so that @RANGE uses the KEYCOLS clause (if one exists) or the primary key as the columns on which to allocate the range. For more information, see the Oracle GoldenGate reference documentation for @RANGE.

OGG-00223: USESNAPSHOT option NOT available for Oracle 8

Cause: USESNAPSHOT is only available for Oracle 9i and later. It causes Extract to use the Flashback Query mechanism to fetch data needed to reconstruct certain operations.

Action: Remove USESNAPSHOT from FETCHOPTIONS.

OGG-00240: Already specified USERID or PASSWORD

Cause: There are duplicate USERID or PASSWORD database credentials specified in the parameter file. Only one set of credentials is allowed.

Action: Remove the invalid credentials statements, and then restart the process.

OGG-00241: Error on key name {0}, {1}

Cause: There was an error parsing the encryption key name that is specified with the ENCRYPT option.

Action: Fix the problem according to the error text that is given in the message.

OGG-00242: No KEYNAME given for BLOWFISH encryption

Cause: BLOWFISH encryption is specified, but the KEYNAME option is not included to specify the key name.

Action: Add the KEYNAME option to the ENCRYPT clause, as in ENCRYPT BLOWFISH, KEYNAME key_name. For more information, see the Oracle GoldenGate security documentation.

OGG-00243: A KEYNAME was supplied but encryption was not specified

Cause: A KEYNAME parameter was specified without an accompanying ENCRYPT parameter.

Action: Specify an ENCRYPT parameter with an optional algorithm, or remove the KEYNAME parameter. For help with syntax, see the Oracle GoldenGate security documentation.

OGG-00244: KEYNAME is not supported for GGS encryption

Cause: A KEYNAME parameter was specified incorrectly.

Action: Remove the KEYNAME parameter or use valid ENCRYPT syntax. For help, see the Oracle GoldenGate security documentation.

OGG-00245: Not logged on, cannot execute statement

Cause: Login credentials were not provided with the SOURCEDB or TARGETDB to execute the query or stored procedure.

Action: Add the SOURCEDB or TARGETDB parameter to the parameter file, including the USERID portion if required for your database. See the Oracle GoldenGate reference documentation for correct syntax for your database.

OGG-00246: Maximum input column length exceeded for col {0,number,0}

Cause: The size of the specified input or output parameter exceeds the supported length.

Action: Shorten the length of the column to 10,000 bytes or less.

OGG-00247: Invalid query - all result columns must be named explicitly (col {0,number,0})

Cause: The process could not find the name of a column that is specified in an output parameter for SQLEXEC.

Action: Check the Sybase error log to find the error that is associated with this SQLEXEC execution, and resolve the problem based on that message.

OGG-00248: Invalid query specified: {0}

Cause: The specified syntax is not a valid query for SQLEXEC.

Action: Fix the query syntax and then restart the process. For help with using SQLEXEC, see the Oracle GoldenGate reference documentation.

OGG-00249: Cannot handle an input parameter of type {0}

Cause: The specified SQLEXEC statement in the parameter file contains an unsupported parameter or column type.

Action: Specify a valid parameter or column type, and then restart the process. For help with using SQLEXEC, see the Oracle GoldenGate reference documentation.

OGG-00250: Stored procedure/function {0} does not exist

Cause: The SQLEXEC parameter refers to a stored procedure or function, but it does not exist in the database.

Action: Check the spelling of the name of the procedure or function in the parameter file. Create the procedure, if needed, and then restart the process.

OGG-00251: Stored procedure/function {0} does not exist ({1})

Cause: The SQLEXEC parameter refers to a stored procedure or function, but it does not exist in the database.

Action: Refer to the database error shown in the message, and check the spelling of the name of the procedure or function in the parameter file. Fix the problem according to the error message, and then restart the process.

OGG-00252: ODBC driver does not adequately support stored procedures (level={0,number,0})

Cause: The current version of the ODBC driver does not support stored procedures. Conformance level 2 is required.

Action: Upgrade to the ODBC driver that has a conformance level 2 (SQL_OAC_LEVEL2).

OGG-00254: {0} is a deprecated parameter

Cause: The specified parameter is deprecated and not valid for the current release of Oracle GoldenGate.

Action: Remove the parameter from the parameter file. Consult the current release notes and documentation for any newer parameters or enhanced functionality that is related to this parameter, and for any required migration steps, or contact Oracle Support.

OGG-00255: {0} value is too small, defaulting to minimum value {{1,number,0}}

Cause: The value that is specified for the parameter is smaller than the allowable minimum value. The minimum value is being used.

Action: None

OGG-00256: Missing or invalid cache item count

Cause: The value for the SPMAXCACHEITEMS parameter is missing.

Action: Enter a valid value and then restart the process.

OGG-00257: Dynamic wildcarding is not supported for SOURCEISTABLE extract

Cause: WILDCARDRESOLVE DYNAMIC (the default) is specified, but SOURCEISTABLE is being used. This combination is not supported.

Action: Set WILDCARDRESOLVE to IMMEDIATE.

OGG-00258: Missing table name specification

Cause: The name of the source table is missing from the TABLE or MAP parameter.

Action: Specify the name of the source table.

OGG-00259: Schema name cannot be wildcarded

Cause: Oracle GoldenGate does not support wildcarded schema names in parameter files or commands.

Action: Spell out the schema name in the parameter or command specification, and then restart the process.

OGG-00260: Tandem \$Volume.Subvol Name can not be wildcarded

Cause: A wildcard has been specified as part of a file name. Oracle GoldenGate does not support the wildcarding of Guardian file names.

Action: Change the parameter file to uniquely list each file by name.

OGG-00261: Immediate wildcard resolution is not currently supported for c-tree (use WILDCARDRESOLVE DYNAMIC)

Cause: WILDCARDRESOLVE IMMEDIATE is not supported for c-tree.

Action: Change WILDCARDRESOLVE to DYNAMIC, and then restart the process.

OGG-00264: Unable to replace wildcard '*' with source table name

Cause: The wildcard resolution failed.

Action: Examine the wildcarded table names to make certain that the syntax is correct. Keep in mind that for source objects, you can use a partial name with a wildcard (like hq.t_*) but for target objects, you cannot use a wildcard with a partial name, because the asterisk is replaced with the name of the source object. Therefore, a target wildcarded specification can only be an asterisk (like rpt.*). For more information, see TABLE and MAP in the Oracle GoldenGate reference documentation.

OGG-00265: Unable to replace wildcard '*' with owner name

Cause: This message is deprecated.

Action: None

OGG-00266: Could not open obey file {0} (err {1,number,0}, {2})

Cause: The process could not open the specified OBEY file because of the operating system error that is shown in the message text.

Action: Fix the cause of the error (typically lack of read privilege) and then restart the process.

OGG-00267: Obey file {0} does not exist

Cause: The file that is specified with OBEY does not exist.

Action: Compare the specified file name with the actual name of the obey file. Make the appropriate corrections, and then restart the process.

OGG-00268: Parameter unterminated

Cause: OBEY is used without a file name as input.

Action: Use the correct syntax of OBEY file_name.

OGG-00269: No obey file specified

Cause: No file name is given for the OBEY parameter.

Action: Specify the name of the obey file, and then restart the process.

OGG-00270: Nested obey files not supported

Cause: There are one or more nested OBEY files in the current OBEY file. OBEY statements cannot be nested within other OBEY statements.

Action: Remove the nested OBEY statement, or merge the contents into the main OBEY statement. As an alternative to using nested OBEY files, you can use macros to call frequently used parameters, and then call the macro in the OBEY statement. For more information, see the Oracle GoldenGate documentation.

OGG-00271: Invalid options specified

Cause: The OBEY parameter contains more than one input file name.

Action: Fix the syntax to specify only one file, and then restart the process.

OGG-00272: Invalid MACRO invocation {{0}}

Cause: There is a syntax error in the invocation of the specified macro.

Action: Correct the macro syntax. For help, see the Oracle GoldenGate reference documentation.

OGG-00273: Missing parameter name {1} in macro {0}

Cause: The parameter name is used in the body of MACRO but is not specified in the PARAMS list.

Action: Add the parameter to the PARAMS list.

OGG-00274: Invalid MACRO invocation (macro {0}, {2,number,0} params specified, {1,number,0} required)

Cause: The invocation of the specified macro does not supply the same number of parameter values as the macro definition.

Action: Edit the invocation syntax to specify the correct number of parameter values. Remember to separate values with commas.

OGG-00275: Quoted string not terminated in MACRO invocation

Cause: A macro is invoked in the parameter file, with a quoted string as a parameter value, but the ending quote marks are missing.

Action: Add the ending quote marks.

OGG-00276: Missing open parentheses in MACRO {0} invocation

Cause: A macro is invoked in the parameter file, but a parentheses is missing.

Action: Add the parentheses. For help, see the Oracle GoldenGate reference documentation.

OGG-00277: No definition found for MACRO {0}

Cause: A definition for the specified macro could not be found.

Action: Define the macro within the MACRO parameter. For help, see the Oracle GoldenGate reference documentation.

OGG-00278: Invalid MACRO definition (body too long)

Cause: The body of the macro definition is too long.

Action: Shorten the body length to 99999 bytes or less.

OGG-00279: Invalid MACRO definition. The BEGIN keyword is not specified in the MACRO {0}.

Cause: Invalid MACRO definition. The BEGIN keyword is not specified in the MACRO {0}.

Action: Add the BEGIN keyword. For help, see the Oracle GoldenGate reference documentation.

OGG-00280: Duplicate MACRO name {0}

Cause: There are two identical macro names in the parameter file.

Action: Change one of the names to a different, unique value.

OGG-00281: Invalid MACRO name

Cause: The name in the MACRO statement is invalid.

Action: Make certain that the name is one word (alphanumeric with no spaces) and begins with a valid macro character (# symbol or one defined with the MACROCHAR parameter). For additional help, see the Oracle GoldenGate reference documentation.

OGG-00282: Invalid MACRO definition

Cause: The macro definition is not valid.

Action: Examine the macro syntax to find errors. For help, see the Oracle GoldenGate documentation.

OGG-00283: Duplicate macro parameter name {0} in the macro {1}.

Cause: The MACRO parameter contains a duplicate parameter name.

Action: Remove the duplicate name or change it to a unique one.

OGG-00284: Too many parameters specified in macro

Cause: The PARAMS clause of the MACRO definition is too long.

Action: Reduce the size of PARAMS to a maximum of 9999 bytes and no more than 99 parameters.

OGG-00285: Invalid macro parameter name in the MACRO {0}. {{1} - must begin with {2}}

Cause: The name of the parameter is not preceded by the macro character.

Action: Add the macro character that is shown in this error message. This character must precede all macro parameter names.

OGG-00286: Invalid trailing characters in MACRO

Cause: The MACRO statement ends with the wrong character.

Action: Terminate the MACRO statement with the END keyword and a semicolon (END;).

OGG-00287: Invalid MACRO definition (params too long)

Cause: The PARAMS clause of the MACRO definition is too long.

Action: Reduce the size of PARAMS to a maximum of 9999 bytes and no more than 99 parameters.

OGG-00288: Unrecognized option in DDL statement [{0}]

Cause: The specified option is not a valid one for the DDL parameter.

Action: Specify a valid option. See the Oracle GoldenGate reference documentation for help with syntax.

OGG-00289: Unrecognized option in DDLOPTIONS [{0}]

Cause: The specified option is not a valid one for DDLOPTIONS.

Action: Specify a valid option. See the Oracle GoldenGate reference documentation for help with syntax.

OGG-00290: Error decoding encrypted password in DDLOPTIONS**DEFAULTUSERPASSWORD [{0}]**

Cause: The encrypted password is not correct.

Action: In GGSCI, encrypt the password with the ENCRYPT PASSWORD command and then copy and paste it into the DEFAULTUSERPASSWORD syntax. Check the Oracle GoldenGate reference documentation for the appropriate options to use with DEFAULTUSERPASSWORD and ENCRYPT PASSWORD.

OGG-00291: Password missing in DDLOPTIONS DEFAULTUSERPASSWORD

Cause: A clear-text or encrypted password is not specified for DEFAULTUSERPASSWORD.

Action: Specify a password. See DDLOPTIONS in the Oracle GoldenGate reference documentation for parameter encryption options.

OGG-00292: Error code specified in DDLERROR, but no action (IGNORE, DISCARD, ABEND) [{0}]

Cause: An action for handling the error is not specified for the error code in the DDLERROR statement.

Action: Specify one of the actions, and then restart the process. For more information, see DDLERROR in the Oracle GoldenGate reference documentation.

OGG-00293: Error action for DDLERROR already specified (IGNORE, DISCARD, ABEND) [{0}]

Cause: The DDLERROR parameter contains duplicate error-handling (action) specifications.

Action: Remove the duplicate syntax, and then restart the process.

OGG-00294: Error code or DEFAULT already specified in DDLERROR [{0}]

Cause: The DDLERROR parameter contains duplicate specifications for the same error code or the DEFAULT keyword.

Action: Remove the duplicate syntax, and then restart the process.

OGG-00295: Not a valid option for [MAXRETRIES numberOfSeconds] [{0}]

Cause: The RETRYOP option of DDLERROR has a MAXRETRIES option, but an invalid value was supplied.

Action: Specify a value between 1 and 10000, and then restart the process.

OGG-00296: Not a valid option for [RETRYDELAY numberOfSeconds] [{0}]

Cause: An invalid value is given for RETRYDELAY.

Action: Specify RETRYDELAY in the form of a number of seconds that represents the desired delay before retrying the operation.

OGG-00297: Error code or DEFAULT already specified in DDLERROR

Cause: The DDLERROR parameter contains duplicate specifications for the same error code or the DEFAULT keyword.

Action: Remove the duplicate syntax, and then restart the process.

OGG-00298: error with property {1} in node {0}: {2}

Cause: An element or attribute is missing from the XML message. This is an internal error in Oracle GoldenGate Veridata Server.

Action: Contact Oracle Support.

OGG-00299: invalid true/false value ({2}) for expected property {1} in node {0}

Cause: A boolean attribute in an XML message does not have a true/false value. This is an internal error in Oracle GoldenGate Veridata Server.

Action: Contact Oracle Support.

OGG-00300: maximum length exceeded ({2,number,0}), property {1} in node {0}

Cause: An XML message has an element or attribute that exceeds the defined limit. This is an internal error in Oracle GoldenGate Veridata Server.

Action: Contact Oracle Support.

OGG-00301: could not find expected property {1} for {0}

Cause: An XML message is missing an expected attribute. This is an internal error in Oracle GoldenGate Veridata Server.

Action: Contact Oracle Support.

OGG-00302: Invalid compare files

Cause: A report, trace, status, or parameter file name in an XML message cannot be opened. This is an internal error in Oracle GoldenGate Veridata Server.

Action: Contact Oracle Support.

OGG-00303: {0}

Cause: The syntax of the specified parameter is incorrect.

Action: Check for spelling errors, or see the Oracle GoldenGate reference documentation for the correct syntax.

OGG-00304: {0}

Cause: This is an informational message that displays the result of checking permission.

Action: None

OGG-00306: Directory name missing

Cause: This message is deprecated.

Action: None

OGG-00307: user name missing

Cause: This message is deprecated.

Action: None

OGG-00308: Missing end quote

Cause: This message is deprecated.

Action: None

OGG-00309: Delimiter value missing

Cause: This message is deprecated.

Action: None

OGG-00310: Extension specifier missing

Cause: This message is deprecated.

Action: None

OGG-00311: Did not recognize argument: {0}

Cause: This message is deprecated.

Action: None

OGG-00312: Closing parenthesis missing for {0}

Cause: This message is deprecated.

Action: None

OGG-00313: Opening parenthesis missing for {0}

Cause: This message is deprecated.

Action: None

OGG-00314: Cannot specify COLUMNS or EXCLUDECOLUMNS more than once

Cause: This message is deprecated.

Action: None

OGG-00315: Delimiter must be a single character

Cause: This message is deprecated.

Action: None

OGG-00316: Delimiter must be a decimal value or enclosed in single quotes

Cause: This message is deprecated.

Action: None

OGG-00317: Delimiter must be between 1 and 127

Cause: This message is deprecated.

Action: None

OGG-00318: No columns specified for trigger

Cause: This message is deprecated.

Action: None

OGG-00319: Invalid rule specification

Cause: A rule in the ACCESSRULE parameter is not formatted properly.

Action: Correct the syntax and restart Manager. Note that this parameter is deprecated. For more information, contact Oracle Support.

OGG-00320: Too many rules specified

Cause: There are too many rules in the ACCESSRULE parameter.

Action: Remove some rules, and then restart Manager. Note that this parameter is deprecated. For more information, contact Oracle Support.

OGG-00321: Invalid or missing argument in run command

Cause: An argument in a Manager parameter is either missing or invalid.

Action: Correct the parameter syntax. For help, see the Oracle GoldenGate reference documentation.

OGG-00322: Missing group specifier

Cause: A process was not specified for the specified parameter to act upon.

Action: This parameter accepts values of ER, EXTRACT, or REPLICAT. For more information, see the Oracle GoldenGate reference documentation.

OGG-00323: Missing group specification for {0}

Cause: A process was not specified for the specified parameter to act upon.

Action: This parameter accepts values of ER, EXTRACT, or REPLICAT. For more information, see the Oracle GoldenGate reference documentation.

OGG-00324: Must specify EXTRACT, REPLICAT or ER for group type

Cause: A process was not specified for the specified parameter to act upon.

Action: This parameter accepts values of ER, EXTRACT, or REPLICAT. For more information, see the Oracle GoldenGate reference documentation.

OGG-00325: Must specify ER, EXTRACT, or REPLICAT for {0}

Cause: A process was not given for the specified parameter to act upon.

Action: This parameter accepts values of ER, EXTRACT, or REPLICAT. For more information, see the Oracle GoldenGate reference documentation.

OGG-00326: Missing file set parameter ({0})

Cause: The process was not given a set of file names to act upon.

Action: Make certain that any parameters in the Manager parameter file that require file names contain them in a valid format. For help, see the Oracle GoldenGate reference documentation.

OGG-00327: Too many {0} entries (max is {1,number,0})

Cause: There are too many instances of the specified parameter.

Action: Reduce the instances of this parameter to the permitted number. You may be able to combine options from these multiple instances into fewer instances or one instance of this parameter. For more information, see the Oracle GoldenGate reference documentation.

OGG-00328: The maximum number of {0} parameters allowed is {1,number,0}

Cause: There are too many instances of the specified parameter.

Action: Reduce the instances of this parameter to the permitted number. You may be able to combine options from these multiple instances into fewer instances or one instance of this parameter. For more information, see the Oracle GoldenGate reference documentation.

OGG-00329: Invalid protocol ({0})

Cause: An unsupported communications protocol was specified.

Action: Specify either TCP or UDP as the protocol.

OGG-00330: Ending port must be greater than or equal to starting port ({0})

Cause: The specified port number at the end of the DYNAMICPORTLIST range of ports is a lower value than the one at the beginning of the range.

Action: Edit the parameter to specify a valid range that increases in value.

Correct: 7830-7835 ; Incorrect: 7835-7830.

OGG-00331: Invalid ending port number ({0})

Cause: The specified port number at the end of the DYNAMICPORTLIST range of ports is not valid.

Action: Edit the Manager parameter file to specify a valid port range, and then restart Manager. An example is 7830-7835.

OGG-00332: Invalid port range ({0})

Cause: An invalid range of port numbers is specified for the DYNAMICPORTLIST parameter in the Manager parameter file.

Action: Specify a valid range of port numbers. For help with syntax, see the Oracle GoldenGate reference documentation.

OGG-00333: Invalid port number ({0})

Cause: The TCP/IP port number that is specified in the Manager parameter file is not a valid port number.

Action: Specify a valid, unused port number for the PORT parameter in the Manager parameter file, and then restart Manager.

OGG-00334: Must specify {0} or {1}

Cause: One of the two required parameters must be included in the parameter file, but not both.

Action: Add the required parameters, and then restart the process.

OGG-00335: Invalid specifier {0} for AFTER option, expected DAYS or HOURS

Cause: The PURGEOLDTASKS parameter is being used with the AFTER option, but the syntax is not correct.

Action: Specify AFTER n {DAYS | HOURS}.

OGG-00336: Must specify DAYS or HOURS for AFTER option

Cause: The PURGEOLDTASKS parameter is being used with the AFTER option, but the syntax is not correct.

Action: Use one of the time specifiers in this syntax: AFTER n {DAYS | HOURS}. Restart the process after correcting the syntax.

OGG-00337: Missing history table name

Cause: The PURGEOLDHISTORY parameter is being used, but the name of the DDL history table is not the default name, and the user-defined name is not specified with the DDLTABLE parameter in the GLOBALS file.

Action: Specify the name of the DDL history table with DDLTABLE, and then restart the process.

OGG-00338: SQL clause not specified

Cause: The SQL for the QUERY clause is missing.

Action: Specify the query in the QUERY clause. For help with syntax, see SQLEXEC in the Oracle GoldenGate reference documentation.

OGG-00339: Invalid interval for SQLEXEC

Cause: The interval that is defined with the EVERY option is not a whole, positive integer.

Action: Change the value to 1 or greater, and then restart the process.

OGG-00340: SQLEXEC interval must be 1 or greater

Cause: The interval that is defined with the EVERY option is not a whole, positive integer.

Action: Change the value to 1 or greater, and then restart the process.

OGG-00341: Error in SQLEXEC clause, id {0}: Missing/invalid argument for {1}

Cause: An argument is missing or incorrect in the specified syntax.

Action: Check for a typographical error, and refer to the SQLEXEC reference documentation for help with syntax.

OGG-00342: Error in SQLEXEC clause, id {0}: Invalid value for {1} option ({2})

Cause: The specified option contains an invalid value.

Action: Check the SQLEXEC documentation in the Oracle GoldenGate reference documentation for valid values.

OGG-00343: Error in SQLEXEC clause, id {0}: Invalid TRACE options

Cause: The TRACE syntax is incorrect.

Action: Specify TRACE with either ALL to trace input and output parameters for each invocation of the procedure or query (the default) or ERROR to trace the parameters for each invocation only after a SQL error occurs.

OGG-00344: Error in SQLEXEC clause, id {0}: Unrecognized option for SQLEXEC: {1}

Cause: The SQLEXEC statement contains the specified incorrect syntax.

Action: Check for a typographical error, and refer to the SQLEXEC reference documentation for help with syntax.

OGG-00345: Error in SQLEXEC clause, id {0}: SPNAME or QUERY is required

Cause: The SQLEXEC statement does not contain a clause that specifies whether it will execute a procedure (SPNAME) or a query (QUERY).

Action: Add the SPNAME or QUERY clause, based on syntax for SQLEXEC in the Oracle GoldenGate reference documentation.

OGG-00346: Error in SQLEXEC clause, id {0}: ID is required when QUERY specified

Cause: The ID specification is missing from the SQLEXEC statement. It is required so that a name can be used by Oracle GoldenGate to reference the column values returned by the query.

Action: Add the ID clause. For help, see SQLEXEC in the Oracle GoldenGate reference documentation.

OGG-00347: Error in SQLEXEC clause, id {0}: Invalid PARAMS specification ({1})

Cause: The specified SQLEXEC clause contains a PARAMS specification that has a syntax error.

Action: Fix the PARAMS clause according to the syntax listed for SQLEXEC in the Oracle GoldenGate reference documentation.

OGG-00348: Error in SQLEXEC clause, id {0}: Missing/invalid PARAMS specification for stored proc {1}

Cause: The specified SQLEXEC clause requires a PARAMS specification to supply input parameters.

Action: Add a PARAMS clause, or fix any syntax errors in the existing one. For help with syntax, see SQLEXEC in the Oracle GoldenGate reference documentation.

OGG-00349: Error in SQLEXEC clause, id {0}: Missing equals sign for param specifier ({1})

Cause: The parameter specifier must be in the format of parameter = value.

Action: Fix the error, and then restart the process. For more help with syntax, see the Oracle GoldenGate reference documentation.

OGG-00350: Error in SQLEXEC clause, id {0}: Invalid parameter name: {1}

Cause: There is an invalid parameter in the specified SQLEXEC clause.

Action: Check for a typographical error in the parameter name. For valid parameters, see SQLEXEC in the Oracle GoldenGate reference documentation. Fix the syntax, and then restart the process.

OGG-00351: Error in SQLEXEC clause, id {0}: Error in PARAM clause for {1}

Cause: There is a syntax error in the specified SQLEXEC clause.

Action: Fix the syntax for the specified parameter in the PARAMS clause, and then restart the process. For help, see SQLEXEC in the Oracle GoldenGate reference documentation.

OGG-00352: Error in SQLEXEC clause, id {0}: Missing required parameter: {1}

Cause: A required parameter is missing from the specified SQLEXEC clause.

Action: Check the Oracle GoldenGate reference documentation for the correct SQLEXEC syntax and required options.

OGG-00353: Could not find stored procedure param ({0})

Cause: A parameter is specified in a PARAMS clause of a SQLEXEC statement but cannot be found in the procedure.

Action: Compare the procedure with the PARAMS clause, and either add the required parameter to the procedure, or remove it from the SQLEXEC statement.

OGG-00354: Invalid BEFORE column: {0}

Cause: An invalid column name was specified.

Action: Specify the correct column name in your input.

OGG-00355: Programming error registering BEFORE image resource

Cause: A before image was registered twice to handle an update statement.

Action: This is an internal error. Contact Oracle Support.

OGG-00356: Must specify COMPARE before destination files or TABLE entries

Cause: This message is deprecated.

Action: None

OGG-00357: Missing equal sign

Cause: An equal sign is missing from the DDL history.

Action: Contact Oracle Support.

OGG-00360: {0} cannot be used with {1}

Cause: The specified parameters are incompatible or mutually exclusive.

Action: Remove one of the parameters, depending on the required Oracle GoldenGate configuration. For help, see the Oracle GoldenGate reference documentation.

OGG-00361: Must specify both {0} and {1}

Cause: Both of the specified parameters must be included in the parameter file.

Action: Add the required parameters, and then restart the process.

OGG-00362: {0} must be specified before {1}

Cause: The order of the parameters in the parameter file is incorrect.

Action: Change the order of the parameters, and then restart the process.

OGG-00363: {0} must occur before SOURCEDEFS/TARGETDEFS entries to have an effect. Parameter ignored.

Cause: The NUMFILES or ALLOCFILES parameter is specified after the SOURCEDEFS or TARGETDEFS parameter.

Action: Place NUMFILES or ALLOCFILES before SOURCEDEFS or TARGETDEFS in the parameter file.

OGG-00364: REPERROR clause {0} is not valid with DEFAULT/DEFAULT2.

Parameter ignored.

Cause: The REPERROR syntax is incorrect.

Action: Correct the syntax. For help, see the Oracle GoldenGate reference documentation.

OGG-00365: {0} cannot be specified more than once per TABLE

Cause: The specified option can only be used once in a TABLE statement.

Action: Remove any extra instances of this option.

OGG-00366: Invalid column specified in {0}: {1}

Cause: The specified column does not exist. This message can apply to any of several different parameters that take a column name as input.

Action: Check the parameter file for parameters or options that take a column name as input, and verify that the name(s) are valid. Specify a valid name or remove the parameter.

OGG-00367: Error in {0} list: {1}

Cause: There is a syntax error in the specified parameter, such as a missing double quote.

Action: Check and correct the syntax. For help, see the Oracle GoldenGate reference documentation.

OGG-00368: Already specified column list for current table

Cause: There are two or more COLS clauses for the same specified table.

Action: Remove all but one COLS clause for this table.

OGG-00369: Error in token clause for {0}

Cause: The TOKENS clause of the specified parameter contains an error in syntax.

Action: Fix the syntax error. For correct syntax, see the Oracle GoldenGate reference documentation.

OGG-00370: Invalid function definition

Cause: There is a syntax error in the definition of a column function, such as a missing parenthesis or an unmatched quote mark.

Action: Fix the syntax. For help, see the Oracle GoldenGate reference documentation.

OGG-00371: Function definition exceeds max length of {0,number,0}

Cause: This message is deprecated.

Action: None

OGG-00372: Missing TOKEN value/function

Cause: The TOKENS clause of TABLE does not contain a value.

Action: Supply a value that can be a constant that is enclosed within double quotes or the result of an Oracle GoldenGate column-conversion function.

OGG-00373: Bad TOKEN name

Cause: The name of the token in the TOKENS clause is invalid.

Action: Supply an ASCII alphanumeric name of any length. TOKENS is not case-sensitive.

OGG-00374: Expected TOKEN name

Cause: The name of the token in the TOKENS clause is missing.

Action: Supply an ASCII alphanumeric name of any length. TOKENS is not case-sensitive.

OGG-00375: Error in FILTER clause

Cause: The FILTER statement in TABLE or MAP contains a syntax error.

Action: Correct the syntax error. For more information, see the TABLE and MAP reference documentation.

OGG-00376: FILTER condition missing

Cause: The FILTER statement in TABLE or MAP does not contain a filter expression.

Action: Add a filter expression. For more information, see the TABLE and MAP reference documentation.

OGG-00377: Query/Table {0} already identified

Cause: Table metadata is resolved, but the table is specified by the QUERY parameter. This parameter is deprecated.

Action: Remove the QUERY parameter.

OGG-00378: Missing query statement

Cause: The query statement is missing from the QUERY parameter. This parameter is deprecated.

Action: Add the query statement.

OGG-00379: Missing query name

Cause: The query name is missing from the QUERY parameter. This parameter is deprecated.

Action: Add the query name.

OGG-00380: TIMEZONE must be LOC, GMT or SOURCE

Cause: An invalid option is specified for TIMEZONE.

Action: Provide a value that is one of 'LOC', 'SOURCE', or 'GMT'.

OGG-00381: Invalid option

Cause: A parameter contains an invalid argument.

Action: Edit the parameter file to specify the correct argument. For help, see the Oracle GoldenGate reference documentaiton.

OGG-00382: Invalid option for {0}

Cause: The specified parameter contains an invalid option.

Action: Specify the correct option syntax. For help, see the Oracle GoldenGate reference documentation.

OGG-00383: Invalid parameter value

Cause: The specified parameter contains an invalid value.

Action: Specify the correct value. For help, see the Oracle GoldenGate reference documentation.

OGG-00384: {0} name must not have schema name.

Cause: Schema values are not allowed when specifying the table name for this parameter.

Action: Remove the schema name from the table name.

OGG-00385: Expecting table name after {0}

Cause: The specified parameter requires a table name.

Action: Specify the name of the table to be used with the parameter.

OGG-00386: Expecting schema name after {0}

Cause: The GGSHEMA parameter in the GLOBALS file does not specify the schema that contains the database objects that support DDL synchronization for Oracle.

Action: Edit the GLOBALS file and supply the DDL schema name.

OGG-00387: Expecting service name after {0}

Cause: The MGRSERVNAME parameter in the GLOBALS file does not contain a Windows service name for Manager.

Action: Edit the GLOBALS file and supply the service name of Manager in the MGRSERVNAME parameter.

OGG-00388: Missing argument (line {0,number,0})

Cause: The process is generating a BCP format file to load data into a SQL Server table based on a template file, but the template file name is missing.

Action: Provide a template file name with the GENLOADFILES parameter.

OGG-00389: Invalid files section entry (line {0,number,0})

Cause: The section on the specified line of the template contains an invalid entry.

Action: Specify a valid file entry. For help, see GENLOADFILES in the Oracle GoldenGate reference documentation.

OGG-00390: {1} entry missing from template (line {0,number,0})

Cause: The specified section is missing from the control file template.

Action: Specify a valid entry. For help, see GENLOADFILES in the Oracle GoldenGate reference documentation.

OGG-00391: Cannot replace template {1}. Replacement too big. (line {0,number,0})

Cause: While generating a BCP format file for loading a SQL Server table based on a template file, the startup template parameter is too long.

Action: Correct the template parameter that is shown in the message.

OGG-00392: Bad delimiter specified

Cause: An invalid delimiter value is specified for the DELIMITER parameter in FORMATASCII.

Action: Specify a valid delimiter. For help, see the Oracle GoldenGate reference documentation.

OGG-00393: Missing delimiter

Cause: The DELIMITER parameter in FORMATASCII is missing the delimiter specification.

Action: Specify the delimiter. For help, see the Oracle GoldenGate reference documentation.

OGG-00394: Command is too long

Cause: A command in the parameter file is too long.

Action: Look for a syntax error like a missing delimiter or white space.

OGG-00395: Argument is too long

Cause: A command argument in the parameter file is too long.

Action: Look for a syntax error like a missing delimiter or white space.

OGG-00396: Command '{0}' not terminated by semi-colon

Cause: A command is not terminated by a semi-colon.

Action: Add the semi-colon.

OGG-00397: Missing {1} option for {0}

Cause: The specified parameter requires the specified option.

Action: Add the option and then restart the process. See the Oracle GoldenGate reference documentation for help with syntax.

OGG-00398: String before WITH in DDLSUBST cannot be empty

Cause: The DDLSUBST statement does not contain the string in the source DDL that is to be replaced in the target DDL.

Action: Supply a search string in this clause: DDLSUBST search_string WITH new_string. For more help, see the Oracle GoldenGate reference documentation.

OGG-00399: Missing string after WITH in DDLSUBST

Cause: The string that replaces the source string in the target DDL is missing.

Action: Supply a replacement string in this clause: DDLSUBST search_string WITH new_string.

OGG-00400: DDLSUBST parsing error: {0}

Cause: The specified error occurred while processing the DDLSUBST parameter.

Action: Fix the problem based on the reported error, and then restart the process.

OGG-00401: DDL Replication must be enabled in order to use {0} (use DDL statement earlier)

Cause: DDL replication is not enabled.

Action: Install (if applicable) and enable DDL replication. For help, see the Oracle GoldenGate administration documentation.

OGG-00402: WILDCARDRESOLVE parameter must be set to DYNAMIC when DDL replication is enabled.

Cause: The WILDCARDRESOLVE parameter is not set to DYNAMIC.

Action: Set WILDCARDRESOLVE to DYNAMIC and restart the process.

OGG-00403: There can be only one DDL filtering statement. If DDL filter is long, use ampersand (&) sign to continue it on another line.

Cause: The parameter file contains more than one DDL statement.

Action: Combine the filtering in the statements into one DDL statement. See the Oracle GoldenGate reference documentation for help with syntax. You can divide a long DDL statement onto separate lines by using an ampersand at the end of each line.

OGG-00405: {0} must be used with DDL replication.

Cause: The specified parameter is required when using DDL replication.

Action: Add the parameter, and then restart the process. See the Oracle GoldenGate reference documentation for more information about this parameter.

OGG-00406: DDL replication is not compatible with {0} parameter.

Cause: The specified parameter cannot be used when DDL replication is enabled.

Action: Remove the parameter from the parameter file, and then restart the process.

OGG-00407: Not a valid error code for DDLError [{0}]

Cause: The specified error code is not valid.

Action: Specify a valid error code, or use the DEFAULT option. See the Oracle GoldenGate reference documentation for correct DDLError syntax.

OGG-00408: RETRYOP not specified prior to RETRYDELAY

Cause: RETRYOP MAXRETRIES must be specified before RETRYDELAY in the DDLError syntax.

Action: Fix the syntax. See the Oracle GoldenGate reference documentation for correct DDLError syntax.

OGG-00409: Error code or DEFAULT not specified prior to RETRYOP

Cause: The DDLError parameter does not specify an error type.

Action: Fix the syntax by providing an error type. See the Oracle GoldenGate reference documentation for correct DDLError syntax.

OGG-00410: {0} is limited by the DBMS to a maximum of {1,number,0}

Cause: The number specified in MAXSQLSTATEMENTS is greater than the maximum active statements allowed by the underlying database.

Action: Adjust the MAXSQLSTATEMENTS value to be at most the maximum number supported by the database.

OGG-00411: Must be PURGE or APPEND

Cause: The file specification is missing the PURGE or APPEND option.

Action: Specify the appropriate option.

OGG-00412: Invalid DISCARDFILE option. Valid options are PURGE, APPEND, MAXBYTES, or MEGABYTES

Cause: The DISCARDFILE parameter contains an invalid option.

Action: Valid options are APPEND or PURGE and MAXBYTES or MEGABYTES.

OGG-00413: {0} must include both date and time

Cause: An incomplete timestamp is supplied in the parameter file.

Action: Edit the parameter file to include both a date and time in the timestamp, in the format of yyyy-mm-dd hh:mi:ss[.cccccc]

OGG-00414: Invalid {0} format

Cause: An invalid date and time are specified for the BEGIN or END parameter.

Action: Specify a valid date and time.

OGG-00415: {0}

Cause: The user exit contains a bad argument.

Action: Supply a valid argument. See the Oracle GoldenGate reference documentation for user exit syntax.

OGG-00416: Value for {0} must be greater than 0

Cause: The value for the specified parameter must be greater than zero.

Action: Supply a valid value.

OGG-00417: Value for {0} must be greater than or equal to 0

Cause: The value for the specified parameter must be greater than, or equal to, zero.

Action: Supply a valid value.

OGG-00418: Error encountered when verifying deferrable constraint

Cause: The state of the target constraints could not be verified.

Action: Look for a subsequent error message that states the reason for the failure.

OGG-00419: TARGET doesn't have deferrable constraint when HANDLETPKUPDATE specified

Cause: The parameter file contains the HANDLETPKUPDATE parameter, and the integrity constraints on the target tables are not set to DEFERRABLE. If the target constraints are not DEFERRABLE, Replicat handles the errors according to existing rules specified with the HANDLECOLLISIONS and REPERROR parameters, or else it abends.

Action: Create the constraints on the target tables as DEFERRABLE INITIALLY IMMEDIATE.

OGG-00420: The value for {0} is too long

Cause: The specified parameter value is too long to fit into the internal buffer that is assigned to it at runtime.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-00422: {0} specification must be enclosed in quotes

Cause: The specified parameter must be in quotes.

Action: Edit the parameter file to add the quotes. For syntax help, see the Oracle GoldenGate reference documentation.

OGG-00423: Could not find definition for {0}

Cause: The process could not find a definition for the specified table when building the object cache on startup.

Action: Remove the table from the TABLE and/or MAP parameter. If using wildcards, you can exclude the table with TABLEEXCLUDE or MAPEXCLUDE.

OGG-00424: {0}, table {1} does not exist in target database

Cause: Replicat could not find metadata for the specified table in the target database. The table is listed in the MAP statement either explicitly or as the result of a wildcard.

Action: Remove the table from the MAP parameter. If using wildcards in that parameter, you can exclude the table with MAPEXCLUDE.

OGG-00425: No DB login established to retrieve a definition for table {0}

Cause: The DBLOGIN command must be issued before issuing commands that interact with the database or sourcedefs must be used.

Action: Issue DBLOGIN or provide sourcedefs or use automatic metadata in trail.

OGG-00427: Must be IGNORE, DISCARD, ABEND, EXCEPTION, TRANSABORT, TRANSDISCARD, TRANSEXCEPTION or RETRYOP

Cause: The response is not set correctly in a REPERROR statement.

Action: See the Oracle GoldenGate reference documentation for REPERROR syntax.

OGG-00428: Missing error number for REPERROR

Cause: The error specification is either missing or invalid.

Action: Supply a valid SQL error number, a user-defined error that is set with RAISEERROR, or the DEFAULT keyword. For more information, see the MAP and REPERROR reference documentation.

OGG-00429: Must be error number or DEFAULT

Cause: An invalid argument was supplied for the error specification.

Action: Supply a valid SQL error number, a user-defined error that is set with RAISEERROR, or the DEFAULT keyword. For more information, see the MAP and REPERROR reference documentation.

OGG-00430: RESET not valid REPERROR on MAP statement

Cause: REPERROR is being used in a MAP statement, and the RESET option is included. This option is only supported for REPERROR at the root level of the parameter file (as a standalone REPERROR statement).

Action: Remove RESET from REPERROR in the MAP file.

OGG-00431: Unable to set {0}

Cause: The specified option for RMTHOST is not valid.

Action: Correct the syntax. For help, see the Oracle GoldenGate reference documentation.

OGG-00432: Unable to set {0} value to {1,number,0}

Cause: The specified parameter does not support the given value.

Action: Specify a valid value. For help, see the Oracle GoldenGate reference documentation.

OGG-00433: No RMTHOST has been specified yet

Cause: The parameter file does not contain the RMTHOST parameter.

Action: Add the RMTHOST parameter.

OGG-00434: Missing file name

Cause: A file name is expected for EXTFILE or RMTFILE.

Action: Specify a file name for this parameter.

OGG-00435: Valid options for {0} are: {1}.

Cause: An invalid argument was specified for EXTTRAIL, EXTFILE, RMTTRAIL, or RMTFILE.

Action: See the Oracle GoldenGate reference guide for valid options for the specified parameters.

OGG-00436: Table {0} is not defined

Cause: The process could not find metadata for the specified table. The DEFGEN utility probably was not run for the specified table, or it was run but the definitions were not added to the existing source- or target-definitions file.

Action: Make certain that the table is specified correctly in the TABLE or MAP parameter. If so, then run DEFGEN for the table and add those definitions to the file that is specified with SOURCEDEFS or TARGETDEFS.

OGG-00437: Record definition {0} is not defined

Cause: The process could not find metadata for the specified table that is in a DDL operation. The DEFGEN utility probably was not run for the specified table, or it was run but the definitions were not added to the existing source- or target-definitions file.

Action: Make certain that the table is specified correctly in the TABLE or MAP parameter. If so, then run DEFGEN for the table and add those definitions to the file that is specified with SOURCEDEFS or TARGETDEFS.

OGG-00438: Error retrieving GGS logtrail next checkpoint

Cause: The process could not open the next checkpoint file.

Action: Make certain that the process has read and write privileges on the checkpoint files. Make certain that the file that caused the error is not corrupted. If the process cannot open the next checkpoint file, contact Oracle Support.

OGG-00439: Failed to read checkpoint file {0}

Cause: The process could not open the checkpoint file.

Action: Check the operating system privileges on the file, and make certain that the process has read and write privileges on it. Make certain the file is not corrupted. If the file remains unreadable, contact Oracle Support.

OGG-00440: Failed to lock checkpoint file {0}, another collector instance might be using this file

Cause: The process could not lock the specified checkpoint file.

Action: Check to determine whether another Server/Collector process is using this checkpoint file. If you cannot resolve this issue, contact Oracle Support.

OGG-00441: Checkpoint file {0} doesn't exist

Cause: The process is trying to find the specified checkpoint file.

Action: Restore the file. Check to see if it was moved, renamed, or deleted.

OGG-00442: Cannot support DB checkpointing for this database.

Cause: The checkpoint table feature (database checkpointing) is not supported for the current database. The ADD CHECKPOINTTABLE command might have been issued, or parameters that support a checkpoint table might exist.

Action: Remove the CHECKPOINTTABLE parameter from the GLOBALS file, if present. Issue ADD REPLICAT without any CHECKPOINTTABLE options.

OGG-00443: Get checkpoint error

Cause: The reporting process encountered an I/O error while reading the checkpoint file.

Action: Check the health of the file system where Oracle GoldenGate is installed. Correct any problems that could cause this error, and then restart the process. If the problem persists, contact Oracle Support.

OGG-00444: Get next checkpoint error

Cause: The reporting process encountered an I/O error while reading the checkpoint file.

Action: Check the health of the file system where Oracle GoldenGate is installed. Correct any problems that could cause this error, and then restart the process. If the problem persists, contact Oracle Support.

OGG-00445: Detected migrated group {0}, updating DB checkpoint dir from {1} to {2}

Cause: The Replicat checkpoint table in the database was pointing to an invalid directory for the checkpoint file that is stored on disk. Every time that Replicat updates the checkpoint table, it verifies the location of the checkpoint file. If there is a mismatch, Replicat updates the table with the correct location. This is an informational message to notify you that the directory for the checkpoint file was the first value shown in the message, but now is the second one shown.

Action: None

OGG-00446: {0}

Cause: An error was encountered while processing the checkpoint file.

Action: Contact Oracle Support.

OGG-00447: Could not find definition for {0}, error {1}

Cause: The DDL metadata could not be obtained from the source database because of the error that is shown in the message.

Action: Correct the problem based on the error message. If you cannot resolve the problem, contact Oracle Support.

OGG-00448: DDL record definition found in sourcedefs file(s) will be ignored, continuing

Cause: DDL was executed on a table that has a source definitions file specified for it with the SOURCEDEFS parameter. This is informational only.

Action: None

OGG-00449: Target not resolved for source [{0}].

Cause: The process could not find the specified target table.

Action: Create the target table or use IGNOREMISSINGTABLES in the DDLError parameter.

OGG-00450: Source sequence [{0}] cannot be resolved in any MAP statement

Cause: The process could not find the specified target sequence.

Action: Create the target sequence or use IGNOREMISSINGTABLES in the DDLError parameter.

OGG-00451: Source sequence [{0}] could not be resolved, error [{1}].

Cause: The specified sequence could not be found.

Action: Make certain the sequence exists.

OGG-00452: Target sequence [{0}] could not be resolved, error [{1}].

Cause: The process could not find the specified target sequence.

Action: Create the target sequence or use IGNOREMISSINGTABLES in the DDLError parameter.

OGG-00453: DDL Replication is not supported for this database

Cause: Oracle GoldenGate does not support DDL replication for the current database.

Action: Remove any parameters that apply to DDL replication. See the Oracle GoldenGate reference documentation for more information.

OGG-00454: Cannot initialize DDL/sequence processing, error [{0}]

Cause: Oracle GoldenGate could not initiate DDL processing because the specified error occurred.

Action: If you cannot resolve the problem based on the error that is returned, contact Oracle Support.

OGG-00455: Problem in resolving [{0}]: {1}, try to fix this issue in order to avoid possible fatal error

Cause: The process could not resolve the metadata for the specified table. The cause of the problem is stated in the message text.

Action: Try to resolve the problem to avoid a fatal error. If you cannot resolve the problem, contact Oracle Support.

OGG-00456: Object that is not replicated [{0}] was renamed into object that is [{1}] even though DDLOPTIONS NOCROSSRENAME is in effect. This may result in new (renamed) objects not processed correctly.

Cause: The DDLOPTIONS parameter includes NOCROSSRENAME, and the table was renamed to one that is included in a TABLE statement (probably because of a wildcard). This can cause the object to be replicated incorrectly, depending on whether a target exists and how it is defined. This might also cause data to be replicated that you do not want to be replicated.

Action: Ensure that the source and target tables match, for both the original and renamed tables. If you cannot resolve the problem, contact Oracle Support.

OGG-00457: Object [{0}] was renamed even though it's marked excluded with NORENAME. Renamed object (if included) may or may not be picked up (you should not rename objects marked with NORENAME)

Cause: The object is specified in a TABLEEXCLUDE parameter that has the NORENAME option enabled, and the table was renamed to one that is included in a TABLE statement (probably because of a wildcard). This can cause the object to be replicated incorrectly, depending on whether a target exists and how it is defined. This might also cause data to be replicated that you do not want to be replicated.

Action: Ensure that the source and target tables match, for both the original and renamed tables. If you cannot resolve the problem, contact Oracle Support.

OGG-00458: Cannot find metadata property {0}. DDL metadata [{1}]

Cause: A metadata property that Oracle GoldenGate needs to resolve is not present.

Action: Contact Oracle Support.

OGG-00459: Cannot find metadata property {1} for object {0}. DDL metadata [{2}]

Cause: A metadata property that Oracle GoldenGate needs to resolve the specified object is not present.

Action: Contact Oracle Support.

OGG-00460: Cannot find metadata property {2} for object {0}.{1}. DDL metadata [{3}]

Cause: A metadata property that Oracle GoldenGate needs to resolve the specified object is not present.

Action: Contact Oracle Support.

OGG-00461: Cannot find metadata property {1} for column {0}. DDL metadata [{2}]

Cause: A metadata property that Oracle GoldenGate needs to resolve the specified object is not present.

Action: Contact Oracle Support.

OGG-00462: Error in substitute string in DDL statement. DDL metadata [{0}]

Cause: Oracle GoldenGate could not perform string substitution in the DDL statement.

Action: Contact Oracle Support.

OGG-00463: Cannot substitute string in DDL statement, old statement = [{0}], new statement is too big. DDL metadata [{1}]

Cause: The size of the substitute string that is specified in the DDLSUBST parameter is larger than the size that the database supports.

Action: Supply a string that is a supported size.

OGG-00464: Cannot remove DDL comments in DDL statement. DDL metadata [{0}]

Cause: Oracle GoldenGate could not parse the DDL statement for comments.

Action: Contact Oracle Support.

OGG-00465: Cannot restructure string in DDL statement for {0}, statement = [{1}]. DDL metadata [{2}]

Cause: Oracle GoldenGate could not process internal changes to the DDL data.

Action: Contact Oracle Support.

OGG-00466: Cannot restructure string in DDL statement for {0}. DDL metadata [{1}]

Cause: Oracle GoldenGate could not process internal changes to the DDL data.

Action: Contact Oracle Support.

OGG-00467: Wrong parameter when getting ddl property. DDL metadata [{0}]

Cause: An unexpected parameter was encountered when processing DDL data.

Action: Contact Oracle Support.

OGG-00468: Wrong format of ddl property string (missing equal sign). DDL metadata [{0}]

Cause: The DDL is of a format that is not known to or supported by Oracle GoldenGate.

Action: Contact Oracle Support.

OGG-00469: Wrong format of ddl property string (missing starting delimiter). DDL metadata [{0}]

Cause: The DDL is of a format that is not known to or supported by Oracle GoldenGate.

Action: Contact Oracle Support.

OGG-00470: Wrong format of ddl property string (missing end delimiter). DDL metadata [{0}]

Cause: The DDL is of a format that is not known to or supported by Oracle GoldenGate.

Action: Contact Oracle Support.

OGG-00471: DDL metadata item too big. DDL metadata [{0}]

Cause: The DDL data exceeds the allocated space.

Action: Contact Oracle Support.

OGG-00472: Expected number in metadata, can't convert it. DDL metadata [{0}]

Cause: A number was expected for this metadata, but it was not in numerical format.

Action: Contact Oracle Support.

OGG-00473: Error in restructure string in DDL statement when removing DDL signature string, trail record = [{0}]

Cause: The string could not be processed.

Action: Contact Oracle Support.

OGG-00474: Cannot restructure string in DDL statement when removing DDL signature string, statement = [{0}]. DDL metadata [{1}]

Cause: The string could not be processed.

Action: Contact Oracle Support.

OGG-00475: DDL is too large - DDL IGNORED, details: {0}.

Cause: The DDL exceeds 2 MB, the maximum that is supported by Oracle GoldenGate.

Action: Apply the DDL manually.

OGG-00476: Gathering metadata for [{0}] not successful even though object was resolved, retrying [{1,number,0}] times with {2,number,0} second interval

Cause: Extract could not obtain metadata for the specified object, and is trying again.

Action: Extract may produce other warning or error messages prior to or in between these messages. Examine the Extract report file for more information. If the problem persists, contact Oracle Support.

OGG-00477: Successfully added TRAN DATA for table [{0}.{1}], operation [{2}]

Cause: Extract successfully added supplemental log data for the table.

Action: None

OGG-00479: Successfully deleted TRAN DATA for [{0}] DDL operation, table [{1}.{2}], operation [{3}]

Cause: Extract successfully deleted the supplemental log data for the table. Extract sometimes creates temporary supplemental log data groups, and those are eventually deleted.

Action: None

OGG-00480: Derived object name [{0}] mapped to [{1}]

Cause: The specified derived object name was mapped to the target name, because a MAP statement exists for the derived object.

Action: None

OGG-00482: DDL found, operation [{0}]

Cause: A DDL operation was found in the data source.

Action: None

OGG-00483: DDL operation successful

Cause: Oracle GoldenGate successfully processed a DDL operation.

Action: None

OGG-00484: Executing DDL operation{0,choice,0#|1# trying again due to RETRYOP parameter}

Cause: Oracle GoldenGate is executing a DDL operation.

Action: None

OGG-00485: Comments removed (REMOVECOMMENTS {0}), DDL operation remained the same

Cause: DDLOPTIONS contains the REMOVECOMMENTS option, but the DDL contains no comments.

Action: None

OGG-00486: Comments removed from DDL operation (REMOVECOMMENTS {0}), new operation [{1}]

Cause: The comments were removed from the DDL operation according to the DDLOPTIONS parameter with REMOVECOMMENTS.

Action: None

OGG-00487: DDL operation included [{0}], optype [{1}], objtype [{2}], objowner [{3}], objname [{4}]

Cause: The specified DDL operation was included in DDL replication because it meets the criteria of an INCLUDE clause.

Action: None

OGG-00488: DDL operation excluded [{0}], optype [{1}], objtype [{2}], objowner [{3}], objname [{4}]

Cause: The specified DDL operation was excluded from DDL replication because it meets the criteria of an EXCLUDE clause or was not included in an INCLUDE clause.

Action: None

OGG-00489: DDL is of mapped scope, after mapping new operation [{0}]

Cause: The DDL operation is of MAPPED scope. This is a DDL operation that is included in a TABLE or MAP statement.

Action: None

OGG-00490: DDL operation is of unmapped scope

Cause: The DDL operation is of UNMAPPED scope. This is a DDL operation that is supported for use in a TABLE or MAP statement, but its base object name is not included in one of those parameters.

Action: None

OGG-00491: DDL operation is of default scope

Cause: The DDL operation is of the default OTHER scope. This is a DDL operation that cannot be mapped.

Action: None

OGG-00492: DDL error ignored: error code [{0}], filter [{1}], error text [{2}]

Cause: The specified DDL error was ignored according to the response rule in the DDLError parameter.

Action: None

OGG-00493: Error in DDL ignored, [{0,number,0}] more errors left to ignore, input data [{1}]

Cause: DDLOPTIONS with SKIPTRIGGERERROR is used in the parameter file, and the trigger error was ignored. Because SKIPTRIGGERERROR specifies a maximum number of trigger errors that can be ignored, this message shows how many are remaining.

Action: None

OGG-00494: DDL error discarded: error code [{0}], filter [{1}], error text [{2}]

Cause: The specified DDL error was ignored according to the response rule in the DDLError parameter.

Action: None

OGG-00495: DDL error ignored for next retry: error code [{0}], filter [{1}], error text [{2}], retry [{3,number,0}]

Cause: The specified DDL error was ignored according to the response rule in the DDLError parameter. The DDL will be retried for the specified number of times according to the RETRYOP option.

Action: None

OGG-00496: DDL error ignored [RESTARTCOLLISIONS]: error [{0}]

Cause: The specified error was ignored because RESTARTCOLLISIONS is being used. RESTARTCOLLISIONS applies HANDLECOLLISIONS logic for the first transaction after startup.

Action: None

OGG-00497: Writing DDL operation to extract trail file

Cause: Extract is writing a DDL operation to the trail. Informational only.

Action: None

OGG-00499: DDL RENAME found, old owner [{0}] object [{1}], new owner [{2}] object [{3}]

Cause: A RENAME operation was processed. Informational only.

Action: None

OGG-00500: DDL RENAME found, old owner [{0}] object [{1}], new owner [{2}] object [{3}], RENAME converted to ALTER TABLE, new operation [{4}]

Cause: A RENAME was converted to the equivalent ALTER TABLE RENAME. The reason is that RENAME does not support the use of a schema name, but a schema name is required in case the DDL statement on the target maps to a different schema.

Action: None

OGG-00501: Skipping DDL operation due to RESTARTSKIP, [{0,number,0}] more left to skip, DDL operation [{1}]

Cause: The Extract parameter file contains DDLError with the RESTARTSKIP option. Extract is skipping the specified number of DDL operations.

Action: None

OGG-00502: DDL substitution [{0}] with [{1}] excluded [{2}]

Cause: Text substitution in the DDL was not performed because the DDL is listed in the EXCLUDE option in the DDLSUBST parameter.

Action: None

OGG-00503: DDL substitution [{0}] with [{1}] excluded [no matching include]

Cause: Text substitution in the DDL was not performed because the DDL is not listed with an INCLUDE in the DDLSUBST parameter.

Action: None

OGG-00504: DDL substitution [{0}] with [{1}] included [{2}], new operation [{3}]

Cause: Text substitution was performed according to the rules in the DDLSUBST parameter.

Action: None

OGG-00505: DDL substitution [{0}] with [{1}] included [{2}], DDL operation remained the same after substitution

Cause: Text substition was performed according to the rules of DDLSUBST, but the DDL text remained the same after the substitution.

Action: None

OGG-00506: Both GETTRUNCATES and DDL replication are enabled

Cause: The parameter file contains the GETTRUNCATES parameter, but DDL replication is enabled.

Action: Specify GETTRUNCATES (it is TABLE/MAP-specific) only for tables for which truncates must be replicated but are not part of the DDL configuration. GETTRUNCATES should not be used for tables that have DDL replication enabled, because truncates are supported by the DDL feature.

OGG-00507: Target [{0}] is missing but ignored due to {1}

Cause: A DML operation on a non-existing table was ignored because the parameter file contains DDLOPTIONS with IGNOREMISSINGOBJECTS.

Action: None

OGG-00508: Fragment number gap detected (faulty data) in DDL object versioning table, fragment #{1,number,0} for SCN {0}, query [{2}]

Cause: The data in the DDL history table is corrupted.

Action: Contact Oracle Support.

OGG-00509: CREATE/ALTER USER with IDENTIFIED clause encoutered, but no DDLOPTIONS DEFAULTUSERPASSWORD specified

Cause: A CREATE or ALTER USER with an IDENTIFIED BY clause was processed. The Extract parameter file contains DDLOPTIONS with the NOREPLICATEPASSWORD option to prevent the source password from being propagated, but the Replicat parameter file does not contain DDLOPTIONS with DEFAULTUSERPASSWORD to specify an alternate password for the target IDENTIFIED BY clause.

Action: Add the DDLOPTIONS with DEFAULTUSERPASSWORD.

OGG-00510: Unexpected query selector in selecting DDL metadata

Cause: There was an internal error when querying the DDL history table.

Action: Contact Oracle Support.

OGG-00511: Cannot access DDL history table. DDL schema owner is [{0}]. It must match schema used in DDL installation as well as GGSHEMA parameter in GLOBALS file. Currently logged user [{1}] must have been given privileges to access DDL history table

Cause: The database user by which the process is running cannot read the GGS_DDL_HIST table (history table).

Action: Make certain that the schema that is specified in the error text is the same one that is specified for the GGSHEMA parameter in the GLOBALS file (and that this parameter exists there). If this parameter is correct, make certain that the specified user has full SELECT and DML privileges on the table. The privileges can be granted by running the role_setup.sql script to create the default GGS_GGSUSER_ROLE role, and then by granting the role to the Extract user. For more information, see the Oracle GoldenGate DDL installation and setup instructions.

OGG-00512: RECYCLEBIN must be turned off. For 10gr2 and up, set RECYCLEBIN in parameter file to OFF. For 10gr1, set _RECYCLEBIN in parameter file to FALSE. Then restart database and extract

Cause: The Oracle database recycle bin is enabled.

Action: Disable the Oracle recycle bin by setting the Oracle initialization parameters according to the instructions in the message.

OGG-00513: Table with SOURCEDEF cannot have DDL operations (table [{0}]).

Either remove SOURCEDEF or filter out table from DDL operations

Cause: The table is configured for DDL replication, but also is configured to replicate to a dissimilar target. Oracle Supports DDL synchronization only in a like-to-like database environment, where source and target tables have identical definitions and are of the same database type.

Action: Either map this table to an identical target, or remove it from the DDL INCLUDE or EXCLUDE options.

OGG-00514: Failed to substitute string in DDL operation [{0}], error [{1}]

Cause: The DDLSUBST parameter is being used, but the substitution failed.

Action: Make sure that the DDL INCLUDE specification is compatible with the DDLSUBST INCLUDE specification (for example, that the targeted object is contained in both). Also make sure that REMOVECOMMENTS BEFORE is not specified. For more information, see the guidelines in the DDLSUBST reference documentation.

OGG-00515: Unknown operation code in DDLError structure

Cause: There is syntax in the INCLUDE or EXCLUDE statement, or in the error-handling syntax, of the DDLError parameter that cannot be parsed correctly.

Action: Review the DDLError syntax and fix any errors. Consult the DDLError documentation for help with syntax.

OGG-00516: Fatal error executing DDL replication: error [{1}], due to explicit ABEND error handling and filter [{0}]

Cause: The DDLError statement is configured to cause the process to abend on the specified DDL error.

Action: Fix the problem based on your data requirements. If ABEND is the error-handling rule, have a plan for manually fixing the problem, or contact Oracle Support.

OGG-00517: Fatal error executing DDL replication: error [{0}], because it's not included in error handling

Cause: There was an error processing a DDL operation, and the error was not handled because the filtering criteria in the DDLError statement excluded that operation from error handling.

Action: Fix the problem based on the error text and then, if appropriate, include the operation type or object in the error handling.

OGG-00518: Fatal error executing DDL replication: error [{1}], due to exclusion from error handling because of filter [{0}]

Cause: There was an error processing a DDL operation, and the error was not handled because the filtering criteria in the DDLError statement excluded that operation from error handling.

Action: Fix the problem based on the error text and then, if appropriate, include the operation type or object in the error handling.

OGG-00519: Fatal error executing DDL replication: error [{0}], no error handler present

Cause: There was an error processing a DDL operation, but because there is no error handling specified with the DDLERROR parameter, the process abended.

Action: Fix the problem based on the error text in the message, and then add one or more DDLERROR parameters to handle future errors so that processing can continue.

OGG-00520: DDL replication is not supported for standby databases

Cause: Oracle GoldenGate does not support DDL replication to or from standby databases.

Action: Remove the DDL configuration parameters and objects from the standby database.

OGG-00521: Object was resolved, however in the same resolution call both DDL history and database metadata resolution failed, cannot recover, {0} [{1}], object id [{2}]

Cause: The DDL object was not found in the database nor in the DDL history record. Depending on the object, this message may or may not be ignored.

Action: Check whether the object was dropped from the database. Also, make sure DDL history table did not get partially or fully truncated. If it did, restore the missing records. Make certain that the PURGEDDLHISTORY parameter does not delete DDL history records while they are still needed.

OGG-00523: Object ID in marker data is not a number

Cause: The object metadata contains an object ID that is not in the form of a number.

Action: Contact Oracle Support.

OGG-00524: Error in DDL trigger has been detected: {0}. Please investigate trace log file or contact Oracle Support

Cause: There was an error while processing DDL with the DDL trigger.

Action: Examine the DDL trigger trace file and determine if the error is due to a system problem (such as a shut-down of the database or a lack of space for the DDL objects) or if it requires the attention of Oracle Support.

OGG-00525: Oracle GoldenGate DDL trigger is not installed correctly, details: {0}.

Cause: The DDL trigger was not installed correctly.

Action: Install the DDL trigger again. For instructions, see the Oracle GoldenGate installation documentation for the Oracle database. If the problem persists, contact Oracle Support.

OGG-00526: Cannot find DDL statement in marker data

Cause: Extract could not find the text of the DDL operation in the DDL record.

Action: Contact Oracle Support.

OGG-00528: The DDL parameter is not supported for this data source. Please remove this parameter and all DDL operations will be propagated in pass-through (PASSTHRU) mode.

Cause: The DDL parameter is specified in the parameter file of a data pump. DDL mapping or filtering is not supported for a data pump and must be passed through as-is.

Action: Remove the DDL parameter from the data pump parameter file, and place the PASSTHRU parameter before all of the TABLE statements that contain tables that use DDL support. You can place the NOPASSTHRU parameter before any TABLE statements that contain tables that do not use DDL support, if you want data filtering, mapping, or transformation to be performed for them. For more information on configuring DDL support, see the Oracle GoldenGate administration documentation.

OGG-00529: DDL Replication is enabled but table {0} is not found. Please check DDL installation in the database

Cause: The specified table supports the Oracle GoldenGate DDL configuration and cannot be found during processing.

Action: Consult the Oracle GoldenGate installation documentation for your database to find out which objects must be installed in the database to support DDL replication. Install the objects according to the instructions in that documentation.

OGG-00530: Table DDL metadata changes are only changes supported at this time, type found [{0}]

Cause: Extract encountered an unsupported DDL operation. Oracle GoldenGate currently supports only table or sequence DDL operations.

Action: Contact Oracle Support.

OGG-00531: Cannot resolve sequence: {0} because of invalid ROWID for sequence UPDATE

Cause: A DDL change to a sequence produced incorrect ROWID data.

Action: Contact Oracle Support.

OGG-00532: Cannot convert highwater value for sequence, value [{0}]

Cause: Oracle GoldenGate cannot update the target sequence to increase the highwater value, so that the target sequence remains ahead of the source.

Action: Contact Oracle Support.

OGG-00533: Sequence name [{0}.{1}] doesn't match hashed name [{2}.{3}] and object id [{4,number,0}] (DDL may have been used, but not enabled)

Cause: DDL operations were performed on sequence objects, but Oracle GoldenGate DDL support is not installed.

Action: Install Oracle GoldenGate DDL support before executing DDL operations on sequence objects. For instructions, see the Oracle GoldenGate installation and setup guide for the Oracle database.

OGG-00534: Sequence update too large [{0}]

Cause: The update to the sequence value is greater than, or equal to, 100 million. Oracle GoldenGate does not support value updates that are greater than 100 million.

Action: Use an update value of less than 100 million.

OGG-00535: Sequence cache value too large [{0}]

Cause: The sequence cache size is too large. Oracle GoldenGate does not support sequence CACHE values greater than 100 million.

Action: Use a CACHE value of less than 100 million.

OGG-00536: Sequence increment by value too large [{0}]

Cause: The sequence increment interval is too large. Oracle GoldenGate does not support INCREMENTBY values greater than 100 million.

Action: Use an INCREMENTBY value of less than 100 million.

OGG-00537: Object type found [{0,number,0}] when resolving DDL object attributes unknown

Cause: The object type was not a table or sequence.

Action: Contact Oracle Support.

OGG-00538: Metadata not invalidated for [{1}.{2}] because of {0}

Cause: Usually this message is for DDL operations that do not affect metadata, such as TRUNCATE TABLE or ANALYZE TABLE. This message explains why Extract did not clear the metadata (remove it from the DDL cache). It is beneficial not to clear metadata if possible: retaining it improves performance because the process does not need to re-read the metadata for the next DML operation.

Action: None

OGG-00539: Metadata not invalidated for [{1}.{2}] because of {0} [{3}]

Cause: Usually this message is for DDL operations that do not affect metadata, such as TRUNCATE TABLE or ANALYZE TABLE. This message explains why Extract did not clear the metadata (remove it from the DDL cache). It is beneficial not to clear metadata if possible: retaining it improves performance because the process does not need to re-read the metadata for the next DML operation.

Action: None

OGG-00540: Metadata not cleared for [{1}.{2}] because of {0}

Cause: Usually this message is for DDL operations that do not affect metadata, such as TRUNCATE TABLE or ANALYZE TABLE. This message explains why Extract did not clear the metadata (remove it from the DDL cache). It is beneficial not to clear metadata if possible: retaining it improves performance because the process does not need to re-read the metadata for the next DML operation.

Action: None

OGG-00541: Metadata not cleared for [{1}.{2}] because of {0} [{3}]

Cause: Usually this message is for DDL operations that do not affect metadata, such as TRUNCATE TABLE or ANALYZE TABLE. This message explains why Extract did not clear the metadata (remove it from the DDL cache). It is beneficial not to clear metadata if possible: retaining it improves performance because the process does not need to re-read the metadata for the next DML operation.

Action: None

OGG-00542: Unexpected threading library failure. Error code {0,number,0} ({1})

Cause: An internal error occurred while the process was executing a multi-threaded application.

Action: Contact Oracle Support.

OGG-00543: Unexpected threading library failure. Error code {0,number,0} ({1})

Cause: An internal error occurred while executing a multi-threaded application. Oracle GoldenGate recovered from the error.

Action: Contact Oracle Support for assistance if this warning continues to be issued.

OGG-00544: Invalid argument passed to threading function.

Cause: An unexpected programming logic error has occurred.

Action: Contact Oracle Support.

OGG-00545: Threaded access not supported

Cause: Call Attachment Facility (CAF) does not permit a process to be threaded. There can be only one thread per Oracle GoldenGate process.

Action: Either use the RRSAF (Recoverable Resource Manager Services Attachment Facility) attachment type or do not configure processes to be multi-threaded. For more information, see the Oracle GoldenGate installation and setup documentation for DB2 z/OS.

OGG-00546: Default thread stack size: {0,number,0}

Cause: Oracle GoldenGate determined the default number of Posix threads on the system.

Action: None

OGG-00547: Increasing thread stack size from {0,number,0} to {1,number,0}

Cause: Oracle GoldenGate is increasing the number of Posix threads to support its processing requirements.

Action: None

OGG-00549: Database operation failed: {0}. Unable to initialize using RRSAF - please check that RRS is available and functioning correctly. {1}

Cause: The MVSATTACHTYPE is set to RRSAF, but RRSAF could not be initialized.

Action: Install RRSAF and make certain that it is configured properly.

OGG-00550: Database operation failed: {0}. Unable to initialize using RRSAF - please check that RRS is available and functioning correctly. {1}

Cause: The MVSATTACHTYPE is set to RRSAF, but RRSAF could not be initialized.

Action: Install RRSAF and make certain that it is configured properly.

OGG-00551: Database operation failed: {0}. ODBC error: SQLSTATE {2} native database error {3,number,0}. {1}

Cause: The Oracle GoldenGate process could not complete its SQL operation because of the specified errors.

Action: Correct the problem with the driver or database, and then restart the process.

OGG-00552: Database operation failed: {0}. ODBC error: SQLSTATE {2} native database error {3,number,0}. {1}

Cause: The Oracle GoldenGate process could not complete its SQL operation because of the specified errors.

Action: Correct the problem with the driver or database, and then restart the process.

OGG-00554: Failed to execute SQL statement '{0}'

Cause: The specified SQL statement returned an error on execution.

Action: Correct the problem that is related to the SQL statement and then restart the process.

OGG-00555: Executing fetch. ODBC error {{0,number,0}}. {1}

Cause: A fetch failed.

Action: Fix the problem based on the ODBC error message, and then restart the process.

OGG-00556: ODBC Driver for {0} does not provide ODBC level 1 conformance

Cause: ODBC driver conformance level of at least level 1 is required.

Action: Contact the database vendor and download the latest ODBC driver with conformance level of at least 1.

OGG-00557: ODBC Driver for {0} does not adequately support prepared statements

Cause: The ODBC driver for this database does not support prepared statements.

Action: Upgrade to the latest ODBC driver for this database to correct the problem, and then restart the process.

OGG-00558: Failed to set implicit transactions off

Cause: An error occurred while disabling implicit transactions.

Action: Determine whether the underlying database supports the SET IMPLICIT_TRANSACTIONS OFF command to return to autocommit mode. Correct the problem, and then restart the process.

OGG-00559: Failed to begin named transaction '{0}'

Cause: An error occurred while trying to start a named transaction command (such as BEGIN TRANSACTION tran_name).

Action: Determine whether the underlying database supports named transactions. Correct the problem and then restart the process.

OGG-00560: Failed to change IDENTITY_INSERT state for table {0}

Cause: The execution of SET IDENTITY_INSERT failed with an error.

Action: Make sure that the user that is used to connect to the database has sufficient privileges to use SET IDENTITY_INSERT. The user must either own the object in question, or be a member of the sysadmin fixed server role, or the db_owner and db_ddladmin fixed database roles.

OGG-00561: Failed to rollback to save-point '{0}'

Cause: There was an error when trying to roll back the transaction to a savepoint.

Action: Note the name of the savepoint and then contact Oracle Support.

OGG-00562: Failed to save transaction '{0}'

Cause: The process failed to set a savepoint on the active transaction.

Action: Note the name of the savepoint and then contact Oracle Support.

OGG-00563: Failed to retrieve IDENTITY information for table {0}

Cause: Replicat does not have the information that is required to process an IDENTITY column properly.

Action: If the specified table does not contain an IDENTITY column, you can ignore this message. If the specified table does contain an IDENTITY column, make certain that you configured Oracle GoldenGate properly to handle these

column types. For more information, see the Oracle GoldenGate documentation for SQL Server. If you cannot resolve the problem, contact Oracle Support.

OGG-00564: ODBC Driver for {0} does not support enough concurrent SQL statements. Need at least {1,number,0} and only {2,number,0} are available.

Cause: The ODBC driver does not support the number of concurrent SQL statements that are allowed by Oracle GoldenGate.

Action: Set the MAXSQLSTATEMENTS parameter to a value that is supported by the driver.

OGG-00565: Cannot initialize ODBC operations

Cause: The system encountered an error while allocating an environment handle and the associated resources.

Action: Contact the DBA of the underlying database, because this error probably relates to an unrecoverable system error.

OGG-00566: Table {0}.{1} does not exist in target database

Cause: The table is configured within Oracle GoldenGate for replication, but Replicat tried to get column information for the table on startup and was not able to find any metadata for it.

Action: The table probably does not exist in the target database. Either add the table, or remove it from the Replicat configuration.

OGG-00567: Indexed value '{2}' not a column of table {0}.{1}

Cause: When the process tried to resolve a column name to its index, a column-not-found error occurred when cross-referencing the name with the current table metadata.

Action: Stop and then restart the process to refresh the metadata record that the process keeps. If the problem persists, contact Oracle Support.

OGG-00568: The current ODBC session does not support multiple active transactions. Oracle Support recommends using multiple transactions to ensure transaction integrity and to enable releasing catalog locks as soon as possible. The ODBC initialization file should have both 'MVSATTACHTYPE=RRSAF' and 'MULTICONTEXT=1'.

Cause: The ODBC session does not support multiple active transactions.

Action: Stop the Oracle GoldenGate process, then add the specified parameters to the ODBC initialization file, and then start the process again.

OGG-00570: Installed Teradata ODBC driver does not support batch SQL statement re-use. Upgrade driver to version {0,number,0}.{1,number,0}.{2,number,0}.{3,number,0} or greater.

Cause: The current ODBC driver does not support the BATCHSQL parameter.

Action: Upgrade to the recommended driver.

OGG-00571: Outstanding SQL statements supported ({0,number,0}) less than maximum ({1,number,0})

Cause: The database does not support the number of prepared SQL statements that the current Oracle GoldenGate configuration allows.

Action: Set the MAXSQLSTATEMENTS parameter to a value that is supported by the database. For more information about MAXSQLSTATEMENTS, see the Oracle GoldenGate reference documentation.

OGG-00572: Outstanding SQL statements limited to {0,number,0} by the Teradata ODBC driver.

Cause: The driver does not support the number of prepared SQL statements that the current Oracle GoldenGate configuration allows.

Action: Set the MAXSQLSTATEMENTS parameter to a value that is supported by the database driver. For more information about MAXSQLSTATEMENTS, see the Oracle GoldenGate reference documentation.

OGG-00573: SQLExecute did not return a valid parameter status [{0,number,0}]

Cause: During the execution of an array operation into a target table, the parameter status array for this row is not populated correctly.

Action: Report the issue to the ODBC driver vendor. There should be an error message for the offending row. Contact Oracle Support if problem persists.

OGG-00575: Driver for {0} does not support transactions

Cause: The specified ODBC driver does not support transactions.

Action: Upgrade the ODBC driver to one that supports transactions.

OGG-00576: Unexpected error ({0,number,0}) in fetch status array

Cause: The array fetch through ODBC resulted in an error for one or more rows in the array.

Action: Attempt to resolve the problem based on the error code if possible. If you cannot resolve the problem, contact Oracle Support.

OGG-00577: Data length ({2,number,0}) exceeded maximum allowed value ({1,number,0}) for file {0}

Cause: This message is deprecated.

Action: None

OGG-00578: Key length ({2,number,0}) exceeded maximum allowed value ({1,number,0}) for file {0}

Cause: This message is deprecated.

Action: None

OGG-00579: Unexpected before image with key length ({0,number,0}) and record length ({1,number,0})

Cause: This message is deprecated.

Action: None

OGG-00580: File {0} does not exist

Cause: This message is deprecated.

Action: None

OGG-00581: C-tree error ({2,number,0}, {1}): {0}

Cause: This message is deprecated.

Action: None

OGG-00582: C-tree error ({2,number,0}, {1}): {0}

Cause: This message is deprecated.

Action: None

OGG-00583: Incorrect result type {1,number,0} describing table {0}

Cause: The describe request for the specified table or column definitions returned the specified unexpected result from the database.

Action: Correct the problem based on the message. To help diagnose the problem, look for other Sybase-related messages in the report file for this Oracle GoldenGate process, and also check the Sybase error log.

OGG-00584: Incorrect result type {0,number,0} describing query definition

Cause: There was the specified unexpected result while describing a SQLEXEC query definition from the database. The SQLEXEC syntax probably contains an error.

Action: View the SQLEXEC statement in the parameter file to find and correct the syntax error. For help with SQLEXEC syntax, see the Oracle GoldenGate reference documentation.

OGG-00585: Incorrect result type {0,number,0} describing table definition

Cause: While describing the SQLEXEC query definition from the database, the specified unexpected result type was received

Action: View the SQLEXEC statement in the parameter file to find and correct the syntax error. For help with SQLEXEC syntax, see the Oracle GoldenGate reference documentation.

OGG-00586: Internal error opening data source for context

Cause: This is an internal error and should not be received in a production environment.

Action: If you receive this error, contact Oracle Support.

OGG-00587: error executing sp while retrieving results

Cause: While executing a SQLEXEC stored procedure or query, an unexpected result was received.

Action: View the SQLEXEC statement in the parameter file to find and fix syntax errors. For help with syntax, see SQLEXEC in the Oracle GoldenGate reference documentation. If the problem persists, check for other errors in the Oracle GoldenGate process report and the database error log before contacting Oracle Support. You might be able to determine the syntax error or other problem that is the cause.

OGG-00588: Unexpected error describing stored procedure

Cause: The SQLEXEC query execution failed because it failed to get syscolumn information.

Action: Make certain that the Oracle GoldenGate user that executes SQLEXEC has permission to access the syscolumn table.

OGG-00593: SYBUTIL_convert_to_sybase_timestamp: Not one of the date/time datatypes: {0,number,0}

Cause: The specified data type is not supported by Oracle GoldenGate for this database version.

Action: For supported data types, see the Oracle GoldenGate documentation that applies to the database.

OGG-00594: TIMECNV_convert_to_db_timestamp failed {0,number,0}

Cause: The conversion of a timestamp from the Oracle GoldenGate generic format to the Sybase timestamp data type failed. The timestamp is from a source database of a type other than that of the target.

Action: Verify that the type of timestamp in the source can be converted to the format that is used by the target. For supported data types, see the Oracle GoldenGate documentation for the database.

OGG-00651: Failed to process SQL statement - error {0,number,0}

Cause: The query in the SQLEXEC statement failed due to the specified server error.

Action: Check the SQLEXEC syntax in the parameter file for errors, and also make certain that the Oracle GoldenGate user that issues the SQLEXEC has the permission to execute the SQL that it contains. If these are not the cause of the problem, note the error number that is in the message text, and then look for possible causes or workarounds within the Sybase database.

OGG-00652: Failed to get results from server - error {0,number,0}

Cause: The query failed while fetching data for a SQLEXEC query or stored procedure.

Action: Check the SQLEXEC syntax in the parameter file for errors, and also make certain that the Oracle GoldenGate user that issues the SQLEXEC has the permission to execute the SQL that it contains. If these are not the cause of the problem, note the error number that is in the message text, and then look for possible causes or workarounds within the Sybase database.

OGG-00653: Failed to send command for SQLEXEC - error {0,number,0}

Cause: The SQLEXEC query failed while sending data to the Sybase database.

Action: Check the SQLEXEC syntax in the parameter file for errors, and also make certain that the Oracle GoldenGate user that issues the SQLEXEC has the permission to execute the SQL that it contains. If these are not the cause of the problem, note the error number that is in the message text, and then look for possible causes or workarounds within the Sybase database.

OGG-00654: Failed to prepare statement for SQLEXEC - error {0,number,0}

Cause: Sybase failed to prepare the SQLEXEC statement.

Action: Fix the problem based on the error that is shown in the message text. Some possible causes are: The SQLEXEC syntax in the parameter file contains an error, or the Oracle GoldenGate user that issues the SQLEXEC does not have the permission for this particular query or stored procedure.

OGG-00655: Failed to allocate statement for SQLEXEC - error {0,number,0}

Cause: The SQLEXEC query failed because Sybase did not allocate space for a command structure for the query or stored procedure.

Action: Check the SQLEXEC syntax in the parameter file for errors, and also make certain that the Oracle GoldenGate user that issues the SQLEXEC has the permission to execute the SQL that it contains. If these are not the cause of the problem, note the error number that is in the message text, and then look for possible causes or workarounds within the Sybase database.

OGG-00656: Server message ({0} Context): number({1,number,0})

severity({2,number,0}) state({3,number,0}) line({4,number,0}). Procedure({5})
Details ({6})

Cause: The specified error occurred in the Sybase server.

Action: Resolve the problem with the server based on the Sybase error.

OGG-00657: Current online log {0} with sequence# {1,number,0} is STALE without alternative. Last read on RBA {2,number,0}, timestamp {3}, SCN {4,number,0}..{5,number,0}

Cause: Extract reached the end of an archive log on RAC, and the next log is not available. This can happen even though the other Extract threads are reading logs. This is by design to maintain transactional integrity. However, it is also possible that one of the RAC instances failed and is not generating archive logs. In this case, Extract stops.

Action: If all RAC instances are running correctly, no action is needed. Extract will continue when more data is available. If an instance fails and you can restore it, do so and then start Extract (if stopped). Parameters are available that enable Extract to continue processing if an instance fails (but with loss of data from that instance). For more information, contact Oracle Support.

OGG-00658: Unable to open archive log {0}, {1}

Cause: Oracle GoldenGate could not open the specified archive log.

Action: Check to see if the disk is full. If not, verify whether the Extract user has operating system privileges to read the file. If you have to grant permissions, stop Manager and then exit GGSCI. Next, close the terminal session. Start the processes again from a new session.

OGG-00659: Unknown specifier in archive log format

Cause: Oracle GoldenGate cannot determine the format of the archive logs.

Action: Use the TRANLOGOPTIONS parameter with the ALTARCHIVEDLOGFORMAT option to specify a string that overrides the archive log format. For the string, provide the same specifier that is set for the Oracle parameter LOG_ARCHIVE_FORMAT. On RAC, set this on each node. For other important details, see the TRANLOGOPTIONS reference documentation.

OGG-00660: Could not find unique key column within table definition, SQL <{0}>

Cause: The table only contains columns that are LONG, LOB or UDT. Oracle GoldenGate cannot construct a key from those column types.

Action: Create a primary or unique key on the table, or remove it from the Oracle GoldenGate configuration. To remove a table when its name satisfies a wildcard definition, you can use the TABLEEXCLUDE parameter for Extract and the MAPEXCLUDE parameter for Replicat.

OGG-00661: Error selecting unique keys for {0}: {1}, SQL <{2}>

Cause: The process could not select a unique key for the specified table.

Action: Resolve the problem based on the error that is shown in the message.

OGG-00662: OCI Error {1} (status = {0,number,0})

Cause: An error occurred in the OCI.

Action: Resolve the problem based on the error that is shown in this message. If you cannot resolve the problem, contact Oracle Support.

OGG-00663: OCI Error {1} (status = {0,number,0}), SQL <{2}>

Cause: An error occurred in the OCI.

Action: Resolve the problem based on the error that is shown in this message. If you cannot resolve the problem, contact Oracle Support.

OGG-00664: OCI Error {2} (status = {0,number,0}-{1})

Cause: An error occurred in the OCI.

Action: Resolve the problem based on the error that is shown in this message. If you cannot resolve the problem, contact Oracle Support.

OGG-00665: OCI Error {2} (status = {0,number,0}-{1}), SQL<{3}>

Cause: An error occurred in the OCI.

Action: Resolve the problem based on the error that is shown in this message. If you cannot resolve the problem, contact Oracle Support.

OGG-00666: SQL operation failed: {2} SQL Error {0,number,0}: {1}

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00667: OCI error ({0,number,0}-{1}) retrieving length info of a

ROWID/UROWID column (table: '{2}', column: '{3}')

Cause: The specified column name does not exist in the specified table.

Action: Make certain that the column is spelled correctly in any parameters where it is specified in the parameter file. Make certain that the column exists in the table.

OGG-00668: OCI error ({0,number,0}-{1}) initializing query to obtain

ROWID/UROWID length (table: '{2}', column: '{3}')

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00669: OCI error ({0,number,0}-{1}) retrieving precision info of a NUMBER column (table: '{2}', column: '{3}')

Cause: The specified column does not exist in the specified table.

Action: Make certain that the column is spelled correctly in any parameters where it is specified in the parameter file. Make certain that the column exists in the table.

OGG-00670: OCI error ({0,number,0}-{1}) initializing query to obtain NUMBER precision (table: '{2}', column: '{3}')

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00671: Error selecting table_name from all_tables - SQL <{0}>

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00672: OCI error ({0,number,0}, {1}) fetching accessible schemas

Cause: An error occurred when retrieving all accessible tables for this user.

Action: Contact Oracle Support.

OGG-00673: OCI error ({0,number,0}, {1}) executing select to get accessible schemas

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00674: OCI error ({0,number,0}, {1}) preparing query (sql {2})

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00675: OCI error ({2,number,0}, {3}) fetching unique keys for table {0}.{1}

Cause: The specified table probably lacks a primary key, unique constraint, or unique index.

Action: Check to see if the table contains a primary key, unique constraint, or unique index, and create one of these objects if none exist. If you continue to get this error, contact Oracle Support.

OGG-00676: OCI error ({2,number,0}, {3}) executing select to get unique keys for table {0}.{1}

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00678: Could not determine instance startup time ({0}), SQL <{1}>

Cause: The instance number could be invalid.

Action: Contact Oracle Support.

OGG-00679: Could not determine instance state ({0}), SQL <{1}>

Cause: The instance number could be invalid.

Action: Contact Oracle Support.

OGG-00680: Missing all_objects entry for {0}.{1}, SQL <{2}>

Cause: The object name does not exist in the database.

Action: Add the object to the database if appropriate, or check for spelling errors in the parameter file. If the object does exist and is specified correctly in the parameter file, contact Oracle Support.

OGG-00681: Could not retrieve query on all_objects ({0}), SQL <{1}>

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00685: begin time {0,date} {0,time} prior to oldest log in log history. Last SQL executed <{1}>

Cause: The begin time that is specified with the ADD EXTRACT or ALTER EXTRACT command is prior to the oldest log that Extract can find.

Action: The most recent SQL that Extract can find is shown in the message. If possible, restore the log that contains the data from the specified timeframe from the backups. Otherwise, specify a start time during which there is redo history.

OGG-00686: Could not retrieve row from table {0}

Cause: A call to the database to fetch table metadata failed.

Action: Contact Oracle GoldenGate Support.

OGG-00687: Found inconsistent row in table {0}

Cause: A call to the database to fetch table metadata failed.

Action: Contact Oracle GoldenGate Support.

OGG-00688: {0}.{1} {2}:ROWID/UROWID column length query returned NULL.

Cause: A SQL statement that queries the Oracle system table failed.

Action: Contact Oracle GoldenGate Support.

OGG-00689: {0}.{1} {2}:Column data type is not ROWID nor UROWID.

Cause: A SQL statement that queries the Oracle system table failed.

Action: Contact Oracle GoldenGate Support.

OGG-00690: {0} is not supported for this platform.

Cause: The specified function is not supported.

Action: None

OGG-00691: Error updating I/O checkpoint on thread {0,number,0}, at (Seq#: {1,number,0}, RBA: {2,number,0}) with err: [{3}]

Cause: Extract is updating its checkpoint.

Action: None

OGG-00692: Found a transaction (XID {0}, secondary XID {1}) without header information.

Cause: The specified transaction in the Oracle GoldenGate memory pool does not have the transaction header portion.

Action: Restart Extract.

OGG-00693: unexpected message type {0,number,0}

Cause: The process encountered an unknown message type.

Action: Restart Extract.

OGG-00694: encountered commit SCN {0} that is not greater than the highest SCN already processed {1} {2} ({3,number,0}) xid {4,number,0}.{5,number,0}.{6,number,0} (0x{7}.{8}.{9}), starting seq.rba {10,number,0}.{11,number,0}, scn {12}, commit seq.rba {13,number,0}.{14,number,0} commit timestamp {15}

Cause: Extract processed a transaction that has a commit SCN which is not greater than the previous SCN that was processed. There probably was a mis-ordering of transactions from multiple node threads.

Action: Restart Extract.

OGG-00695: encountered commit SCN {0} that is not greater than the highest SCN already processed {1} {2} ({3,number,0}) xid {4,number,0}.{5,number,0}.{6,number,0} (0x{7}.{8}.{9}), starting seq.rba {10,number,0}.{11,number,0}, scn {12}, commit seq.rba {13,number,0}.{14,number,0} commit timestamp {15}

Cause: Extract processed a transaction that has a commit SCN which is not greater than the previous SCN that was processed. There probably was a mis-ordering of transactions from multiple node threads.

Action: Restart Extract.

OGG-00696: tran_hdr == NULL. errtext = '{0}'

Cause: A transaction in the Extract memory that does not have a transaction header.

Action: Restart Extract.

OGG-00697: bad txn header mt: {0} th: {1} idx: {2,number,0}

Cause: A transaction that was generated by the Extract producer thread has a thread index that does not match the thread number from any node.

Action: Restart Extract.

OGG-00698: unexpected message type {0,number,0} size {1,number,0}

Cause: A command or message received by the Extract producer thread is not valid.

Action: Restart Extract.

OGG-00699: OCI initialization error [{0,number,0}]

Cause: A SQL statement in Oracle that retrieves metadata for the target table failed.

Action: Contact Oracle Support.

OGG-00700: Number of columns in table is set to zero

Cause: A SQL statement in Oracle that retrieves metadata for the target table failed.

Action: Contact Oracle Support.

OGG-00701: No table name given

Cause: A SQL statement in Oracle that retrieves metadata for the target table failed.

Action: Contact Oracle Support.

OGG-00702: OCI call failed

Cause: An OCI call to the Oracle database failed. This is a generic message that captures any type of OCI failure.

Action: Contact Oracle Support.

OGG-00703: OCINewHandleFree error in {1} [type={0,number,0}]

Cause: The attempt to free a previously allocated Oracle OCI handle failed.

Action: Contact Oracle Support.

OGG-00704: OCINewHandleFree error in {1} [type={0,number,0}]

Cause: The attempt to free a previously allocated Oracle OCI handle failed.

Action: Contact Oracle Support.

OGG-00705: OCIDescriptorFree error in {1} [type={0,number,0}]

Cause: The attempt to free a previously allocated Oracle OCI descriptor failed.

Action: Contact Oracle Support.

OGG-00706: Failed to add supplemental log group on table {0} due to {1}

Cause: ADD TRANDATA was issued for the specified table, but Oracle GoldenGate was not able to add a supplemental log group on the table.

Action: Fix the problem based on the database error that is returned in the message.

OGG-00707: Table {0} has no valid key columns, no supplemental log group was added.

Cause: The table does not have any primary or unique key columns defined on it, so a supplemental log group cannot be created.

Action: If the table contains any columns that always will be unique, you can specify them as a key by using a KEYCOLS clause. Otherwise, Oracle GoldenGate will use all of the columns as a key. For more information about KEYCOLS, see the Oracle GoldenGate reference documentation.

OGG-00708: Key column may exists after column {0}, may not be able to handle row chaining

Cause: There is a key column after a LONG, LOB, or UDT column. This message supports trigger-based extraction, which is no longer supported by Oracle GoldenGate.

Action: None

OGG-00709: OCI error ({0,number,0}-{1}) building query to fetch codepoint info

Cause: The value for NLS_LANG might be invalid.

Action: This warning is deprecated.

OGG-00710: OCI error ({0,number,0}-{1}) fetching codepoint info, use default codepoint value 1

Cause: This is an internal error that indicates the process could not fetch codepoint information.

Action: This warning is deprecated.

OGG-00711: Cannot derive characterset conversion ({0}), use default codepoint value 1

Cause: The process could not derive a character-conversion formula to convert the source data to the target data. This is a warning message.

Action: This warning is deprecated.

OGG-00712: Updating I/O checkpoint after purging orphaned transactions on thread {0,number,0} with current position (Seq#: {1,number,0}, RBA: {2,number,0}).

Cause: A node failed and Extract could not capture the rollback. This causes the transaction to become orphaned. Because the TRANLOGOPTIONS parameter includes the PURGEORPHANEDTRANSACTIONS option, Extract validated that the transaction was orphaned and purged it. This message indicates that Extract is updating its checkpoint in consideration of the purge.

Action: None

OGG-00713: [Thread #{0,number,0}] Purging orphaned transaction (transaction id: {1}, start time: {2}, start seqno: {3,number,0}, start RBA: {4,number,0}) due to orphaned transaction with immediate purge.

Cause: A node failed and Extract could not capture the rollback. This causes the transaction to become orphaned. Because the TRANLOGOPTIONS parameter includes the PURGEORPHANEDTRANSACTIONS option, Extract validated that the transaction was orphaned and purged it.

Action: None

OGG-00714: [Thread #{0,number,0}] Purging orphaned transaction (transaction id: {1}, start time: {2}, start seqno: {3,number,0}, start RBA: {4,number,0}) due to monitoring on orphaned transaction.

Cause: A node failed and Extract could not capture the rollback. This causes the transaction to become orphaned. Because the TRANLOGOPTIONS parameter includes the PURGEORPHANEDTRANSACTIONS option, Extract validated that the transaction was orphaned and purged it.

Action: None

OGG-00715: [Thread #{0,number,0}] Purging transaction (transaction id: {1}, start time: {2}, start seqno: {3,number,0}, start RBA: {4,number,0}).

Cause: A node failed and Extract could not capture the rollback. This causes the transaction to become orphaned. Because the TRANLOGOPTIONS parameter

includes the PURGEORPHANEDTRANSACTIONS option, Extract validated that the transaction was orphaned and purged it.

Action: None

OGG-00716: Skipping unsupported in-memory undo record in sequence {0,number,0}, at RBA {1,number,0}, with SCN {2} ... Minimum supplemental logging must be enabled to prevent data loss.

Cause: Minimal supplemental logging is not enabled, so Oracle may use in-memory undo. This causes multiple undo/redo pairs to be written within the same redo record. Extract does not support these types of records.

Action: Enable minimal supplemental logging. For instructions on how to set logging for Oracle GoldenGate, see the Oracle GoldenGate installation and setup documentation for the Oracle database.

OGG-00717: Found unsupported in-memory undo record in sequence {0,number,0}, at RBA {1,number,0}, with SCN {2} ... Minimum supplemental logging must be enabled to prevent data loss.

Cause: Minimal supplemental logging is not enabled, so Oracle may use in-memory undo. This causes multiple undo/redo pairs to be written within the same redo record. Extract does not support these types of records.

Action: Enable minimal supplemental logging. For instructions on how to set logging for Oracle GoldenGate, see the Oracle GoldenGate installation and setup documentation for the Oracle database.

OGG-00719: Switched log to seqno {0,number,0} while reading rec with size {1,number,0}, has read {2,number,0} bytes.

Cause: Extract detected a log that spans more than one log file. This indicates possible log corruption.

Action: Restart Extract. If the problem persists, you might need to manually issue ALTER EXTRACT to skip this record or log; however data loss may occur. For help, contact Oracle Support.

OGG-00720: Waiting for archive log {0} for seqno {1,number,0}, has read {2,number,0} bytes, to be flushed

Cause: Extract is waiting for more log data.

Action: None

OGG-00721: Not able to open log file {0} for next sequence {1,number,0} after reaching limit of {2,number,0} seconds on waiting. Last read position seqno {3,number,0}, rba {4,number,0}.

Cause: Extract has reached its limit for the number of times that it tries to open a log file.

Action: Make sure that the Extract database user has privileges to read the specified log file, and that the file is not corrupted.

OGG-00722: Failed to process redo records on table {0} due to {12} on record at seqno {1,number,0} rba {2,number,0}, in transaction {3,number,0}.{4,number,0}.{5,number,0} (0x{6}.{7}.{8}), with head rowid {9} row piece rowid {10}, timestamp {11}.

Cause: Extract detected an error while processing a chained record. If the database is Oracle 9i, there could be a problem with the log parallelism feature when parallelism is greater than 1.

Action: If using Oracle 9i, disable log parallelism. If not using Oracle9i with log parallelism greater than 1, restart Extract.

OGG-00723: Record with class# {0,number,0}, slt# {1,number,0}, at seqno {2,number,0}, rba {3,number,0} SCN {4} has secondary transaction ID that is duplicate of existing open uncommitted transaction.

Cause: There is more than one transaction with matching secondary transaction IDs from the same thread.

Action: Restart Extract. If this does not solve the problem, contact Oracle Support.

OGG-00724: Conflict exists in secondary transaction ID after purging orphaned transaction. Class# {0,number,0}, slt# {1,number,0}, seqno {2,number,0}, rba {3,number,0}, SCN {4}.

Cause: Extract detected a transaction that has a matching secondary transaction ID even after deleting the earliest transaction with this matching transaction ID.

Action: Restart Extract.

OGG-00725: The primary transaction ID is duplicate of existing open transaction. Transaction ID: {0,number,0}.{1,number,0}.{2,number,0}

Cause: Extract detected a transaction that has a primary transaction ID that matches an existing open transaction in the memory pool.

Action: Restart Extract.

OGG-00726: The number of Oracle redo threads ({0,number,0}) is not the same as the number of checkpoint threads ({1,number,0}). EXTRACT groups on RAC systems should be created with the THREADS parameter (e.g., ADD EXT <group name>, TRANLOG, THREADS {0,number,0}, BEGIN...)

Cause: The RAC system has the specified number of redo threads (instances) but the Extract group is not configured to read the same number of threads. Data will be missed.

Action: You need to redirect Extract to capture from all RAC instances by doing the following: Issue STOP EXTRACT in GGSCI, then issue DELETE EXTRACT. Next, if the database is Oracle Enterprise Edition 10.2 or higher, issue DBLOGIN as a user with the privileges listed in the DBLOGIN documentation. Finally, issue ADD EXTRACT to add back the group with the same name. Do not change the name. Include the following options in the command: TRANLOG and BEGIN with a begin time. Set BEGIN to the timestamp of the earliest record that the old Extract captured.

OGG-00727: Switch extract to archived log only mode on physical standby database.

Cause: Extract is configured to capture from an Oracle standby database, but the TRANLOGOPTIONS parameter does not contain the ARCHIVEDLOGONLY option.

Action: Add the ARCHIVEDLOGONLY option to force Extract to read the archives that were shipped over from the source. If the _NOARCHIVEDLOGONLY option is being used, remove it. For more information about ALO mode, see the TRANLOGOPTIONS parameter.

OGG-00728: Extract is forced to stay in non archived log only mode when the database it connects to is a physical standby database.

Cause: The database is in standby mode, and the TRANLOGOPTIONS parameter contains the _NOARCHIVEDLOGONLY option to override the default behavior (switch to Archived Log Only mode and capture only from the archives).

Action: _NOARCHIVEDLOGONLY is an internal parameter, and this setting might be intentional as part of a support case. If this is intentional, no action is required. Otherwise, remove the ARCHIVEDLOGONLY option from the Extract parameter file. For more information about ALO mode, see the TRANLOGOPTIONS parameter.

OGG-00729: Running extract against a single thread (thread# {1,number,0}) in a RAC configuration with {0,number,0} threads. All transactions owned by other redo threads will be ignored.

Cause: Oracle GoldenGate is being started in an Oracle RAC installation that has more than one instance, but the Extract process is only running against a single RAC instance.

Action: You need to redirect Extract to capture from all RAC instances by doing the following: Issue STOP EXTRACT in GGSCI, then issue DELETE EXTRACT. Next, if the database is Oracle Enterprise Edition 10.2 or higher, issue DBLOGIN as a user with the privileges listed in the DBLOGIN documentation. Finally, issue ADD EXTRACT to add back the group with the same name. Do not change the name. Include the following options in the command: TRANLOG and BEGIN with a begin time. Set BEGIN to the timestamp of the earliest record that the old Extract captured.

OGG-00730: No minimum supplemental logging is enabled. This may cause extract process to handle key update incorrectly if key column is not in first row piece.

Cause: Minimal supplemental logging is not enabled. Supplemental logging must be enabled for Extract to successfully process records from the redo log.

Action: Enable minimal supplemental logging.

OGG-00731: No minimum supplemental logging is enabled. This may cause extract process to handle key update incorrectly if key column is not in first row piece

Cause: Minimal supplemental logging is not enabled. Supplemental logging must be enabled for Extract to successfully process records from the redo log.

Action: Enable minimal supplemental logging.

OGG-00732: Found crash recovery marker from thread #{0,number,0} on sequence {1,number,0} at RBA {2,number,0}. Aborting uncommitted transactions.

Cause: Extract found a crash recovery marker in the redo log. This is an informational message only.

Action: None

OGG-00733: Marker table {0} not found

Cause: Extract could not find the DDL marker table.

Action: Install the DDL objects properly by running the ddl_setup script. For help, see the Oracle GoldenGate for Oracle installation and setup documentation.

OGG-00734: Failed to find LONG column index in table {0} to match up LONG data

Cause: The table is marked with a LONG column, but Extract could not find the LONG column when it resolved the table metadata.

Action: Restart Extract to refresh the metadata in memory.

OGG-00735: Error converting Oracle numeric value to ASCII for column {0}

Cause: Extract failed to convert data in a numeric column from the native Oracle format to the Oracle GoldenGate internal format.

Action: Restart Extract. If the problem persists, exclude this table from the Extract configuration so that processing continues, and then contact Oracle Support.

OGG-00736: Transaction has been FORCED to trail, however there is no valid SCN present, transaction ID: {0}

Cause: SEND EXTRACT was issued with the FORCETRANS option to force the specified transaction to the trail. However, Oracle GoldenGate was not able to locate a System Change Number (SCN) for the commit record.

Action: Contact Oracle Support.

OGG-00737: Cannot support {0,number,0} byte integer boundary

Cause: Extract detected that the native data structure alignment on the specified word is higher than 4 bytes.

Action: Move the Oracle GoldenGate installation to a platform with a lower data structure alignment. For assistance, contact Oracle Support.

OGG-00738: Object id [{0,number,0}], SCN [{1}], commit SCN [{2}] could not be resolved. Most likely this happens if DDL history for it was deleted. Please check purge parameters in manager parameter file (if it is too short). If that is ok, this was probably an object that was not filtered out and this can be ignored

Cause: Either this object ID represents something that Extract is not supposed to capture, or it is supposed to be captured but Oracle GoldenGate could not interpret the metadata, probably because the table was dropped after this record was generated.

Action: If this record is an object that must be captured, restore the GGS_DDL_HIST (DDL history) table from backup to restore the metadata for the specified object ID and SCN. To prevent future loss, set PURGEDDLHISTORY so that the retained history exceeds Extract lag.

OGG-00739: invalid datetime ({1}) for obj attr ({0})

Cause: The specified date or timestamp value is invalid. The date format must be YYYY-MM-DD HH24:MI:SS and the timestamp format must be YYYY-MM-DD HH24:MI:SS.FF.

Action: Use a value that conforms to the required format.

OGG-00740: invalid number ({1}) for obj attr ({0}), OCI Error {2}

Cause: The specified number value is not a valid Oracle number.

Action: Use a valid Oracle number. For help, see the Oracle documentation.

OGG-00741: invalid string ({1}) for obj attr ({0})

Cause: An attempt to map an XML value attribute of type string to an attribute of an Oracle user-defined datatype failed.

Action: Review the schema for the associated user-defined data type. Contact Oracle Support for additional assistance.

OGG-00742: invalid raw string ({1}) for obj attr ({0})

Cause: The field contains invalid characters. A RAW field can have only characters from 0123456789ABCDEF.

Action: Remove any characters that are not from 0123456789ABCDEF.

OGG-00743: Error ({0,number,0}, {1}) start select in {2}

Cause: Parse and binding on one of the internal queries failed.

Action: Contact Oracle Support.

OGG-00744: Error ({0,number,0}, {1}) start select in {2}

Cause: Parse and binding on one of the internal queries failed.

Action: Contact Oracle Support.

OGG-00745: Error ({0,number,0}, {1}) start cursor in {2}

Cause: Parse and binding on one of the internal queries failed.

Action: Contact Oracle Support.

OGG-00746: Error ({0,number,0}, {1}) selecting data in {2}

Cause: An error occurred when fetching data from an internal cursor.

Action: Contact Oracle Support.

OGG-00747: Error ({0,number,0}, {1}) selecting data in {2}

Cause: An error occurred when fetching data from an internal cursor.

Action: Contact Oracle Support.

OGG-00748: Error ({2,number,0}, {3}) retrieving data in {4}() for table {0}.{1}

Cause: The process cannot find the specified table.

Action: Ensure that the table exists in the database, and that it is specified correctly in the parameter file of the process. If these checks prove true, contact Oracle Support.

OGG-00749: Error ({1,number,0}, {2}) retrieving owner/object name for object id {0,number,0}

Cause: The process cannot find the object name by using the specified object ID.

Action: Contact Oracle Support.

OGG-00750: Error ({3,number,0}, {4}) retrieving LOB object_id for col {2}, table {0}.{1}

Cause: The process cannot find the LOB object name by using the specified object ID.

Action: Contact Oracle Support.

OGG-00751: Failed to validate table {0}. Likely due to existence of unused columns.

Cause: It will cause data integrity issue if you are not using sourcedefs in downstream Replicat or the target table doesn't have the same unused columns due to ASSUMETARGETDEFS or DDL replication. Please use 'DBOPTIONS ALLOWUNUSEDCOLUMN' parameter to override this.

Cause: The specified table contains unused columns. Oracle Supports tables with unused columns, but the support is disabled by default. Extract abends on these columns unless you use the DBOPTIONS parameter with the ALLOWUNUSEDCOLUMN option to force Extract to generate a warning and continue processing.

Action: Specify DBOPTIONS with ALLOWUNUSEDCOLUMN. When using this parameter, either the same unused column must exist in the target table, or a source definitions file must be created for Replicat with the DEFGEN utility. For more information about the source definitions file, see the Oracle GoldenGate administration documentation.

OGG-00752: Failed to validate table {0}. Likely due to existence of unused column.

Cause: Please make sure you use sourcedefs in downstream Replicat, or the target table has exactly the same unused columns when using ASSUMETARGETDEFS or DDL replication.

Cause: The specified table contains unused columns. Oracle Supports tables with unused columns, but the support is disabled by default. Extract abends on these columns unless you use the DBOPTIONS parameter with the ALLOWUNUSEDCOLUMN option to force Extract to generate a warning and continue processing.

Action: Specify DBOPTIONS with ALLOWUNUSEDCOLUMN. When using this parameter, either the same unused column must exist in the target table, or a source definitions file must be created for Replicat with the DEFGEN utility. For more information about the source definitions file, see the Oracle GoldenGate administration documentation.

OGG-00753: Error ({2,number,0}, {3}) retrieving partition count for table {0}.{1}

Cause: The process could not find the number of partitions in the specified table.

Action: Contact Oracle Support.

OGG-00754: Error ({2,number,0}, {3}) retrieving subpartition count for table {0}.{1}

Cause: The process could not find the number of sub-partitions in the specified table.

Action: Contact Oracle Support.

OGG-00755: Failed to lookup user ID for table {0}

Cause: The process could not find the owner of the specified table.

Action: Ensure that the table is qualified with the correct owner in the parameter file and that the table exists in the schema to which the process is connected.

OGG-00756: Failed to lookup user ID for sequence {0}

Cause: The process could not find the owner of the specified sequence.

Action: Ensure that the sequence is qualified with the correct owner in the parameter file and that the sequence exists in the schema to which the process is connected.

OGG-00757: Error ({2,number,0}, {3}) fetching alternate object IDs for table {0}.{1}

Cause: The process could not get the sub-partition IDs of the specified table.

Action: Contact Oracle Support.

OGG-00758: Error ({0,number,0}, {1}) retrieving user name in {2}{0}

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00759: Error ({1,number,0}, {2}) retrieving user_id for username {0}

Cause: The process could not find the specified user name.

Action: Ensure that the user exists in the database.

OGG-00760: Error ({3,number,0}, {4}) select data segcol# in {5}{0} for {0}.{1} column# {2,number,0}

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00761: Error ({3,number,0}, {4}) retrieving col# & seqcl# for col {2}, table {0}.{1}

Cause: The process could not find the specified column name in the table.

Action: Add the column to the table, or remove it from any parameters that use it as the basis for filtering or other processing.

OGG-00762: Error ({2,number,0}, {3}) fetching table name {0}.{1}

Cause: The process could not find the specified table name in the database.

Action: Add the table to the database, or remove it from the Oracle GoldenGate configuration.

OGG-00763: Error ({0,number,0}, {1}) retrieving database block size

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00764: Error ({3,number,0}, {4}) checking log group on log {2} for table {0}.{1}

Cause: Supplemental logging is not enabled for the specified table.

Action: Enable supplemental logging for the table.

OGG-00765: Error ({3,number,0}, {4}) checking log group on log {2} for table {0}.{1}

Cause: Supplemental logging is not enabled for the specified table.

Action: Enable supplemental logging for the table.

OGG-00766: Error ({2,number,0}, {3}) retrieving total columns for user {0}, table {1}

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-00767: Error ({3,number,0}, {4}) retrieving status in {5}{0} for trigger {2} table {0}.{1}

Cause: This error is deprecated.

Action: None

OGG-00768: {0}. SQL error ({1,number,0}). {2}

Cause: This is a generic error message and there can be multiple reasons for it. One reason could be that a query to set the session timeout failed. Ignoring this message results in the session being disconnected after a default time period if the connection has been idle. This error message also is used when an operation against the database fails, such as a query.

Action: To resolve this error, verify in the database why the query or other operation would fail. For example, verify that the user that executed the operation has the correct privileges to do so.

OGG-00769: {0}. SQL error ({1,number,0}). {2}

Cause: This is a generic error message and there can be multiple reasons for it. One reason could be that a query to set the session timeout failed. Ignoring this message results in the session being disconnected after a default time period if the connection has been idle. This error message also is used when an operation against the database fails, such as a query.

Action: To resolve this error, verify in the database why the query or other operation would fail. For example, verify that the user that executed the operation has the correct privileges to do so.

OGG-00770: Failed to connect to MySQL database engine for HOST {0}, DATABASE {1}, USER {2}, PORT {3,number,0}

Cause: One of the Oracle GoldenGate parameters that specifies connection information is incorrect.

Action: Verify the login credentials of the Oracle GoldenGate process (as a database user), the connection port, the database name, and the host name that are

specified in the parameter file. In the case of the host name, the name might be incorrectly specified, or the MySQL server could not resolve it. It also is possible that the host name was not specified when the MySQL user was created, so the MySQL system table does not contain an entry for the user.

OGG-00771: Cannot initialize MySQL connection handler

Cause: The MySQL API failed to allocate, initialize, and return a new object that is used throughout the session to connect to the object. This error only occurs when there is not sufficient memory.

Action: Add memory.

OGG-00772: Setting session isolation level to REPEATABLE READ

Cause: The query to set the session default isolation level to REPEATABLE READ in the MySQL database failed.

Action: Make certain the user has the appropriate privilege to set the default isolation level.

OGG-00773: Disabling autocommit mode

Cause: The query to set the auto-commit variable (autocommit=0) failed.

Action: Make certain the user has the appropriate privilege to perform this operation, and make certain that the MySQL server is running.

OGG-00774: Unrecognized field type {{1,number,0}} for column {0}

Cause: The specified column contains a data type that is not supported by Oracle GoldenGate.

Action: Remove tables or columns that contain unsupported data types from the Oracle GoldenGate configuration. For supported data types, see the Oracle GoldenGate installation and setup guide for the MySQL database.

OGG-00775: Unable to determine database case sensitivity, setting to insensitive

Cause: Oracle Supports case sensitivity but cannot determine the case of the database.

Action: Oracle GoldenGate checks the database collation to determine whether the database object names should be compared in case sensitive or case insensitive mode. View the collation of the database to make certain it is set correctly. Certain collation-dependent objects and duplicate names, for example, can cause a COLLATE definition to fail. For more information, see the Microsoft SQL Server documentation.

OGG-00776: 'SELECT INTO/BULKCOPY' option is enabled for database: {0}.

SELECT INTO operations on permanent tables are not written to logs. These operations will therefore not get replicated.

Cause: Bulk copy is not supported.

Action: To avoid this error, issue the following SQL Server command to avoid the select for the specified schema: exec sp_dboption 'owner/schema', 'select into/bulkcopy', false.

OGG-00777: Supplemental logging is disabled for database '{0}'. To enable logging, perform the following: 1) Set 'trunc. log on chkpt.' to false. 2) Create a full backup of the database. Please refer to the "Oracle GoldenGate For Windows and UNIX Administration Guide" for details.

Cause: Undefined

Action: Undefined

OGG-00778: Logging of supplemental log data is disabled for table {0}

Cause: Supplemental (extended) logging is not enabled for the specified table.

Action: Issue the DBLOGIN command in GGSCI, and then issue the ADD TRANDATA command to enable the supplemental logging. For more information, see the Oracle GoldenGate for SQL Server documentation.

OGG-00779: Error in getting logging status for table: '{0}'

Cause: The process could not determine whether the specified table has supplemental logging enabled.

Action: Check the database connection settings and whether SQL Server was configured according to the directions in the Oracle GoldenGate installation documentation for SQL Server.

OGG-00780: Error in getting logging status for table: '{0}' ({1})

Cause: The process could not determine whether the specified table has supplemental logging enabled.

Action: Check the database connection settings and whether SQL Server was configured according to the directions in the Oracle GoldenGate installation documentation for SQL Server.

OGG-00781: Error in changing transaction logging for table: '{0}' ({1})

Cause: Oracle GoldenGate failed to enable or disable supplemental logging for the specified table.

Action: Look for other warnings or error messages, because there are many possible causes for this error, such as insufficient privileges for the Oracle GoldenGate user and connectivity failures.

OGG-00782: Error in changing transaction logging for table: '{0}'

Cause: Oracle GoldenGate failed to enable or disable supplemental logging for the specified table.

Action: Look for other warnings or error messages, because there are many possible causes for this error, such as insufficient privileges for the Oracle GoldenGate user and connectivity failures.

OGG-00783: Unable to enable replication on '{0}' ({1})

Cause: Oracle GoldenGate failed to enable or disable supplemental logging for the specified table.

Action: Look for other warnings or error messages, because there are many possible causes for this error, such as insufficient privileges for the Oracle GoldenGate user and connectivity failures.

OGG-00784: Unable to determine if {0}.{1} is of computed column: {2}

Cause: Oracle GoldenGate failed to determine if the specified column is a computer column.

Action: Look for other warnings or error messages, because there are many possible causes for this error, such as insufficient privileges for the Oracle GoldenGate user and connectivity failures.

OGG-00785: Before image with timestamp {0} does not match table definition for {1} at {2}.{3,number,0}. Sync of source and target to a later point in time is required before capture can resume. REORG is recommended.

Cause: The table was altered so that the current definition does not match the log record.

Action: Synchronize source and target data to a point in time beyond that reported in the message. Then, restart Extract.

OGG-00786: DATA CORRUPTION may result from use of the NOMERGEMEMBERS option in a data sharing environment.

Cause: The undocumented option _NOMERGEMEMBERS is specified in the TRANLOGOPTIONS statement for Extract in a data sharing environment.

Action: Contact Oracle Support.

OGG-00787: unexpected status {0} at {1}.{2,number,0}

Cause: This is a warning that the process is at the end of the log and waiting for more data.

Action: None

OGG-00788: check DB2 maintenance for the presence of PQ78544 and the absence of PQ96356 - contact Oracle Support if PQ96356 has been applied.

Cause: Log record types 10, 11, 12, and 13 are either the result of a short-lived APAR PQ78544 (reversed by PQ96356) or changes subsequent to PQ96356.

Action: Contact Oracle Support if any of these types appear without PQ78544.

OGG-00789: Table Space {0}.{1} is LOG NO - Table {2} Column # {3,number,0} will be captured via fetch

Cause: The specified LOB tablespace was created as LOG NO; therefore, the specified LOB column cannot be captured from the log and must be captured by means of a fetch.

Action: None

OGG-00790: A resource was unavailable while attempting to read the log at {0}.

Retry in {1,number,0} seconds.

Cause: The process is retrying a log read.

Action: None

OGG-00791: Invalid log record

Cause: A processing check failed.

Action: Save this message and other preceding messages that provide the context for it, and contact Oracle Support.

OGG-00794: A resource was unavailable while attempting to read the log at {0}. check SYSLOG for details.

Cause: The process is trying to read a log file that is no longer available.

Action: Make certain that the BSDS name was specified correctly, and that the ADD EXTRACT or ALTER EXTRACT command was issued correctly. If a start time was used, instead of the NOW option, it is possible to specify a start point for which logs are no longer available. If Extract is configured properly, contact Oracle Support.

OGG-00795: DB2 Monitor Trace Class 1 must be active

Cause: DB2 Monitor Trace Class 1 is required to allow Extract to read the active log, but Monitor Trace Class 1 is not active.

Action: See the Oracle GoldenGate installation and setup documentation for instructions on activating Monitor Trace Class 1.

OGG-00796: unexpected IFI error {0}

Cause: A processing check failed.

Action: Save this message and other messages that provide context for it, and contact Oracle Support.

OGG-00797: DB2 IFI abend - check logrec {0}

Cause: A processing check failed.

Action: Save this message and other preceding messages that provide context for it, and contact Oracle Support.

OGG-00798: BUFSIZE too small for log record

Cause: The internal buffer that holds the results of each read of the transaction log is too small to hold the data returned.

Action: Use the TRANLOGOPTIONS parameter with the BUFSIZE option to increase the buffer size.

OGG-00799: Error {4} diagnostic {5} retrieving log record for table {0} (dbid x'{1}' psid x'{2}' obid x'{3}'')

Cause: The process could not retrieve the next log record for the specified table.

Action: Save this message and other preceding messages that provide context for it, and contact Oracle Support.

OGG-00800: Unable to decompress log record for table {0} Error {4} diagnostic {5} (dbid x'{1}' psid x'{2}' obid x'{3}''). The compression dictionary changed since the log record was written

Cause: DB2 z/OS was not able to decompress the log record. It is likely that a compression dictionary matching the record is not available.

Action: Save this message and other preceding messages that provide context for it, and contact Oracle Support.

OGG-00801: Unable to retrieve log record for table {0}. Error {4} diagnostic {5} (dbid x'{1}' psid x'{2}' obid x'{3}''). The buffer is too small to hold the log record.

Cause: The internal buffer that holds the results of each read of the transaction log is too small to hold the data returned.

Action: Use the TRANLOGOPTIONS parameter with the BUFSIZE option to increase the buffer size.

OGG-00803: Unable to find {0}

Cause: The initialization of the IFI interface failed.

Action: Save this message and other preceding messages that provide context for it, and contact Oracle Support.

OGG-00804: Unable to initialize IFI

Cause: The initialization of the IFI interface failed.

Action: Save this message and other preceding messages that provide context for it, and contact Oracle Support.

OGG-00805: LOBCol {0} expected {1,number,0} bytes copied {2,number,0} bytes

Cause: The number of bytes that were moved from LOB storage to the base row did not match what the process expected.

Action: Save this message and other preceding messages that provide context for it, and contact Oracle Support.

OGG-00806: moving {1,number,0} bytes to base row for LOBcol {0}

Cause: The process failed to move data from LOB storage to the base row.

Action: Save this message and other preceding messages that provide context for it, and contact Oracle Support.

OGG-00808: Invalid sequence at line {1,number,0} - type {0,number,0} cannot be first

Cause: An out-of-sequence log record was encountered.

Action: Save this message and other preceding messages that provide context for it, and contact Oracle Support.

OGG-00809: Variant mismatch at line {0,number,0}

Cause: An unknown type of log record was encountered.

Action: Save this message and other preceding messages that provide context for it, and contact Oracle Support.

OGG-00810: Validation error at line {0,number,0}

Cause: An out-of-sequence log record was encountered.

Action: Save this message and other preceding messages that provide context for it, and contact Oracle Support.

OGG-00811: Invalid sequence at line {0,number,0}

Cause: An out-of-sequence log record was encountered.

Action: Save this message and other preceding messages that provide context for it, and contact Oracle Support.

OGG-00812: Extract is not APF authorized.

Cause: Extract is not APF authorized.

Action: Determine why Extract is not APF authorized and correct the problem. Extract and all dll files must have the APF bit turned on and all load libraries in the execution concatenation must be APF authorized.

OGG-00813: Unexpected (non-URCTL) record type

Cause: An unexpected log error was encountered.

Action: Contact Oracle Support.

OGG-00814: SQL_NO_DATA_FOUND from SQLGetData for col {1} table {0} PTF UK34243 is required

Cause: A bug in DB2 z/OS occasionally causes no data to be found when Extract tries to fetch LOB data. Extract checks to see if the specified IBM fix was applied and, if not, generates this message.

Action: Apply the required IBM fix shown in the message.

OGG-00815: db2ReadLog error [RC={0,number,0}:SQLCA structure may be corrupted]

Cause: The DB2ReadLog API has encountered an error reading the transaction log.

Action: Contact Oracle Support.

OGG-00816: db2ReadLog error [{0}] [{1}]

Cause: An invalid parameter has been supplied to the DB2ReadLog API. This is an internal error.

Action: Contact Oracle Support.

OGG-00817: db2ReadLog error [{0}]

Cause: The DB2ReadLog API encountered an error while trying to obtain the current LSN in the transaction log. This is an internal error.

Action: Contact Oracle Support.

OGG-00818: Unknown Log Manager log record component ID

encountered:{0,number,0}

Cause: An unrecognized component ID was encountered during the processing of a log record. This is an internal error.

Action: Contact Oracle Support.

OGG-00820: Reposition to key {0,number,0} failed

Cause: Extract was not able to reposition to the specified timestamp. This is an internal error.

Action: Contact Oracle Support.

OGG-00821: LSN requested ({0,number,0}) is no longer valid, positioning to the next LSN in the log files

Cause: Extract was positioned to start at the specified LSN, but it does not exist in the log files. Extract is positioned to the closest next LSN that exists in the log files.

Action: None

OGG-00822: LSN requested ({0,number,0}) was not found in the the DB2 log files, using next available LSN at {1,number,0}

Cause: Extract was positioned to start at the specified LSN, but it does not exist in the log files. Extract is positioned to the closest next LSN that exists in the log files.

Action: None

OGG-00823: A key column on the after image was not present in the before image on table {0} column index {1,number,0} This is because column(s) were added to the table after it was originally created. This is a known issue with DB2 LUW that can only be addressed by IBM.

Cause: Columns were added to the specified table, so the after image contains a column that was not present in the before image that is used by Oracle GoldenGate for comparison purposes.

Action: Exclude this table from the Oracle GoldenGate configuration, stop user activity on it, and then resynchronize it with the target table. Add it back to the Oracle GoldenGate configuration, and then restart the processes.

OGG-00824: Column index {1,number,0} in table {0} cannot be used as a key field

Cause: The table has a unique index that includes a column type that is not supported by Oracle GoldenGate as a key.

Action: Use the KEYCOLS clause to specify unique columns that can be used as a key. You can use the existing index columns minus the nonsupported column in the KEYCOLS clause, if the remaining columns ensure uniqueness.

OGG-00825: Table {0} column {1,number,0} : Invalid LOB column value

Cause: The Extract process encountered an internal error while processing a log record containing a LOB column.

Action: Contact Oracle Support.

OGG-00826: Table {0} column {1,number,0} : Invalid packed decimal column value

Cause: The Extract process encountered an internal error while processing a log record containing a PACKED DECIMAL column.

Action: Contact Oracle Support.

**OGG-00827: Insert of new hash item for tablespace:table:transID
{0,number,0}:{1,number,0} failed**

Cause: The Extract process encountered an internal storage allocation error.

Action: Contact Oracle Support.

**OGG-00828: Retrieval of hash item for tablespace:table:transID
{0,number,0}:{1,number,0} failed**

Cause: The Extract process encountered an internal storage access error.

Action: Contact Oracle Support.

**OGG-00829: Retrieval of hash item for tablespace:table:transID
{0,number,0}:{1,number,0} succeeded unexpectedly**

Cause: The Extract process encountered an internal storage access error.

Action: Contact Oracle Support.

OGG-00830: Delete of hash item failed

Cause: The Extract process encountered an internal storage access error.

Action: Contact Oracle Support.

OGG-00831: Neither a valid checkpoint start LSN nor a timestamp was passed to REDO_position

Cause: An internal error was encountered by Extract where the process could not determine the positioning mode at startup.

Action: Contact Oracle Support.

OGG-00832: ASCII formatting not implemented

Cause: The FORMATASCII parameter is not supported for this database implementation.

Action: Remove FORMATASCII from the Extract parameter file.

OGG-00833: Invalid component ID encountered {0,number,0}

Cause: The Extract process did not recognize the component identifier from the specified record.

Action: Contact Oracle Support.

OGG-00834: Invalid row type {0,number,0} was received while creating a LOB row for an LOB record type: {1,number,0}

Cause: The Extract process did not recognize the row type from the specified LOB record.

Action: Contact Oracle Support.

OGG-00835: Invalid row type {0,number,0} was received while creating a LFM row for an LFM record type: {1,number,0}

Cause: The Extract process did not recognize the LFM type from the specified LOB record.

Action: Contact Oracle Support.

OGG-00836: No items were found in the transaction for tablespace:table:trans ID {0,number,0}:{1,number,0}:{2}

Cause: The Extract process unexpectedly encountered an empty transaction while trying to output the transaction.

Action: Contact Oracle Support.

OGG-00837: db2CfgGet error [{0}]

Cause: An error occurred while processing a table truncate.

Action: Contact Oracle Support.

OGG-00838: db2CfgGet error [RC={0,number,0}:SQLCA structure may be corrupted]

Cause: An error occurred while processing a table truncate.

Action: Contact Oracle Support.

OGG-00839: Table {0} does not have DATA CAPTURE CHANGES turned on : Table will be ignored

Cause: The specified table does not have DATA CAPTURE CHANGES turned on, and Extract is ignoring it because TRANLOGOPTIONS includes IGNOREDATACAPTURECHANGES.

Action: None

OGG-00840: Table {0} does not have DATA CAPTURE CHANGES turned on : Use the TRANLOGOPTIONS IGNOREDATACAPTURECHANGES parameter to override

Cause: The specified table does not have DATA CAPTURE CHANGES turned on. This is required by Extract.

Action: Use the TRANLOGOPTIONS parameter with the IGNOREDATACAPTURECHANGES option to cause Extract to ignore tables for which DATA CAPTURE CHANGES is not set. This option enables you to use a wildcarded table specification for tables that have change capture enabled, while skipping tables with matching names that do not have it enabled.

OGG-00841: An update after image converted to an insert was not followed by its corresponding row ID update. An internal dms type of {0,number,0} was encountered in the following record

Cause: The after image of an update that was converted to an insert was not followed by its corresponding row ID update. This is an internal logic error.

Action: Contact Oracle Support.

OGG-00842: No records left in transaction:An update after image converted to an insert with LSN {0,number,0} was not followed by its corresponding update

Cause: Extract encountered an internal logic error while processing an update record at the specified LSN.

Action: Contact Oracle Support.

OGG-00843: No tables were defined for extraction in the EXTRACT param file

Cause: Extract was started but the parameter file contains no table specifications.

Action: Specify tables for capture with the TABLE parameter.

OGG-00844: Source table entry not found in file array

Cause: A table that is specified for capture in the Extract parameter file does not exist in the specified database.

Action: Add the table to the database or remove it from the TABLE parameter file.

OGG-00845: Rollback ID {1,number,0} does not match last record ID of {0,number,0} in FM transaction manager

Cause: An internal inconsistency was detected in the Extract process while processing a transaction rollback.

Action: Contact Oracle Support.

OGG-00846: Row row: Expecting an update/delete/undo record after receiving an update converted to an insert in migrated row sequence: Received record type {0,number,0} instead

Cause: Extract encountered an unexpected sequence of records in the transaction log. This is an internal logic error.

Action: Contact Oracle Support.

OGG-00847: Multi-dimensional clustered tables using formatted user data records with value compression are not supported in this release

Cause: The TABLE parameter includes a table that is defined with an unsupported database feature.

Action: Remove the table that is not supported from the TABLE specification. If the table name is one of many that satisfy a wildcard, you can use TABLEEXCLUDE to exclude it.

OGG-00848: A log record with the previous LSN:{0,number,0} was not found in the DB2 log files: lookup failed

Cause: Extract failed to process backward in the LSN chain to find the first record of the transaction. This is an internal logic error.

Action: Contact Oracle Support.

OGG-00849: Database name must be 8 characters or less

Cause: The database name that is specified in the parameter file is too long. The database name can be up to eight characters.

Action: Check the parameter file for a typographical error.

OGG-00850: Database instance {0} has both USEREXIT and LOGRETAIN set to off

Cause: The database is not configured to retain the transaction logs.

Action: Turn on the USEREXIT parameter, which automatically sets LOGRETAIN to RECOVERY and forces a user exit program to archive and retrieve the log files. Alternatively, you can set the LOGRETAIN parameter to RECOVERY, which retains the logs and enables them to be used for forward recovery.

OGG-00851: Invalid {1} record: row type {0,number,0} was received with an associated {1} record type: {2,number,0}

Cause: Extract failed an internal sanity check of the log record.

Action: Contact Oracle Support.

OGG-00852: Invalid DMS record type received: {0,number,0}

Cause: Extract failed an internal sanity check of the log record.

Action: Contact Oracle Support.

OGG-00853: Table {0} column {1,number,0} : invalid decimal digit in packed decimal field

Cause: The specified table contains invalid data in a packed decimal column.

Action: Contact Oracle Support.

OGG-00854: Table {0} column {1,number,0} : maximum decimal precision exceeded

Cause: The specified table contains a decimal value that is larger than the maximum permitted value.

Action: Contact Oracle Support.

OGG-00855: Table {0} column {1,number,0} : error {2,number,0} occurred

Cause: Extract encountered an error while converting the data in the specified column.

Action: Contact Oracle Support.

OGG-00856: Table {0} does not have DATA CAPTURE CHANGES enabled for

LONG columns. Use the TRANLOGOPTIONS

NOREQUIRELONGDATACAPTURECHANGES parameter to override

Cause: DB2 LUW Data Capture Changes is not enabled for LONG columns on this table. The TRANLOGOPTIONS parameter is set to its default of REQUIRELONGDATACAPTURECHANGES, which forces Extract to abend when LONGs are not captured. When NOREQUIRELONGDATACAPTURECHANGES is used, Extract issues a warning and continues processing the record.

Action: Change TRANLOGOPTIONS to NOREQUIRELONGDATACAPTURECHANGES to avoid an abend, or enable capture of LONG columns.

OGG-00857: Table {0} does not have DATA CAPTURE CHANGES enabled for
LONG columns. Use the TRANLOGOPTIONS

NOREQUIRELONGDATACAPTURECHANGES parameter to override

Cause: DB2 LUW Data Capture Changes is not enabled for LONG columns on this table. The TRANLOGOPTIONS parameter is set to its default of REQUIRELONGDATACAPTURECHANGES, which forces Extract to abend when LONGs are not captured. When NOREQUIRELONGDATACAPTURECHANGES is used, Extract issues a warning and continues processing the record.

Action: Change TRANLOGOPTIONS to NOREQUIRELONGDATACAPTURECHANGES to avoid an abend, or enable capture of LONG columns.

OGG-00858: LONG columns are not supported for the NOCOMPRESSDELETES option for DB2 LUW. LONG columns from table {0} will not be included for delete operations

Cause: NOCOMPRESSDELETES writes all of the table columns to the trail, but LOBs are not supported for this feature. Because this is a DELETE, replication will not be affected by this limitation.

Action: None

OGG-00862: Number of log records read: {0,number,0}. Number of log records dumped to file: {1,number,0}.

Cause: This message is reported when Extract is running in a diagnostic mode under the direction of Oracle Support.

Action: None

OGG-00863: DB2 Extract log dump stopped

Cause: This message is reported when Extract is running in a diagnostic mode under the direction of Oracle Support.

Action: None

OGG-00864: DB2 Extract log dump has reached the maximum number of log records it can process in a single run: {0,number,0}

Cause: This message is reported when Extract is running in a diagnostic mode under the direction of Oracle Support.

Action: None

OGG-00865: Reached RECORDCOUNT value requested of {0,number,0}

Cause: This message is reported when Extract is running in a diagnostic mode under the direction of Oracle Support.

Action: None

OGG-00866: Reached STOPATLSN value requested of {0,number,0}

Cause: This message is reported when Extract is running in a diagnostic mode under the direction of Oracle Support.

Action: None

OGG-00867: Only dumping propagated log records

Cause: This message is reported when Extract is running in a diagnostic mode under the direction of Oracle Support.

Action: None

OGG-00868: {0}

Cause: The specified database error occurred.

Action: Follow the directions in the error message to resolve the problem, or contact Oracle Support.

OGG-00869: {0}

Cause: The specified database error occurred, but can be ignored.

Action: Contact Oracle Support only if a problem persists.

OGG-00870: Database error {0,number,0} ({1})

Cause: The specified database error occurred.

Action: Resolve the error. If the problem persists, contact Oracle Support.

OGG-00871: Could not find column {1} in table {0}

Cause: The XML input to the Veridata Agent (VERIAGT) refers to a column that does not exist in the specified table. This usually is caused by an internal error in Veridata Server, which is responsible for validating column references before putting them into the XML messages.

Action: Contact Oracle Support.

OGG-00873: Could not find primary key column {1} in table {0}

Cause: The process encountered an internal error while retrieving primary key information from the database.

Action: Contact Oracle Support.

OGG-00874: Expected number of output params (sqlexec id {0}) greater than actual ({1,number,0})

Cause: The SQLEXEC query or stored procedure contains fewer column parameters than the result of the fetch from the database.

Action: Correct the SQLEXEC parameter specification. If the problem persists, contact Oracle Support.

OGG-00875: Unexpected error looking for col {0,number,0} in lobmem

Cause: The LOB column is missing from the database. Oracle GoldenGate fetches LOB values in certain cases. The table might have been updated to delete the LOB column between the time the transaction record was generated and the time that Extract processed it.

Action: Contact Oracle Support.

OGG-00876: LOB data exceeds max size ({0,number,0}) for column {2,number,0} ({1})

Cause: The LOB exceeds the size that is supported by Oracle GoldenGate.

Action: You can restart Replicat to skip this record with START options, or you can use a REPERROR rule to handle this type of record. Another option is to alter the target table definition to accept null values. For MySQL and Sybase, you can use TRANLOGOPTIONS with ALLOWLOBDATATRUNCATE to truncate LOBs that are too large for a target column.

OGG-00877: Could not map zero length BLOB from source column {0} into non-nullable target column {1}

Cause: The target column does not support null column values.

Action: You can restart Replicat to skip this record with START options, or you can use a REPERROR rule to handle this type of record. Another option is to alter the target table definition to accept null values. You can use TRANLOGOPTIONS with EMPTYLOBSTRING to substitute a string value for empty (zero-length) LOB columns that are replicated to the target. By default, Oracle GoldenGate sets empty columns to NULL on the target and will abend if the target database does not permit LOB columns to be NULL. EMPTYLOBSTRING prevents Replicat from abending.

OGG-00878: Could not execute SQL, not logged onto database

Cause: The process could not execute the SQL operation because it did not log onto the database.

Action: Check the parameter file for the USERID parameter and, if applicable, the SOURCEDB or TARGETDB parameter. These parameters provide the necessary login information. For more information, see the Oracle GoldenGate reference documentation.

OGG-00879: Owner is not specified in table '{0}'.

Cause: An owner is not included for this table in the TABLE and/or MAP specification.

Action: Qualify all table names with an owner.

OGG-00880: Owner is not specified in table '{0}'.

Cause: The specified table is not qualified with an owner name in the parameter file.

Action: Add the owner to the table specification, as in hq.sales.

OGG-00881: NODYNSQL cannot be used for columns > 4K

Cause: The NODYNSQL parameter is specified for Replicat, but a LOB column greater than 4K in size was encountered during replication.

Action: Remove NODYNSQL or ensure that there are no LOB values greater than 4K.

OGG-00882: NODYNSQL option is not supported for the wide character types (SQL_WCHAR, SQL_WLONGVARCHAR and SQL_WVARCHAR)

Cause: NODYNSQL is being used in the Replicat parameter file, but a wide character type was encountered. In NODYNSQL mode, the process cannot expand the data into a static SQL statement.

Action: Remove NODYNSQL, and then restart the process.

OGG-00883: failed to update entry in trace table '{0}', group {1}. Number of rows updated is {2,number,0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-00884: Fetched fields ({1,number,0}) does not equal total columns ({0,number,0})

Cause: The number of fetched columns for the specified table does not match the number of columns for this table as shown in the metadata.

Action: Find out whether this table was changed since the time that this transaction record was generated. Try restarting the process to see if the problem resolves. If the problem persists, contact Oracle Support.

OGG-00885: error encountered converting fetched column ({0}) from ascii val {1} ({2})

Cause: An error occurred when the process tried to convert a fetched column value to an internal format. More information can be obtained from the error message that is provided in the message.

Action: If you cannot fix the problem based on the error message, contact Oracle Support.

OGG-00886: Unsuccessful execution on interval: {0}

Cause: An error occurred when the process tried to execute a SQL statement in a given interval.

Action: Resolve the problem based on the error text, and then restart the process. If the problem persists, contact Oracle Support.

OGG-00887: Unsuccessful SQL execution on interval: {0}

Cause: A non-fatal error occurred when the process tried to execute a SQL statement in a given interval.

Action: Resolve the problem based on the error text, and then restart the process. If the problem persists, contact Oracle Support.

OGG-00888: SQL statement executed successfully on interval.

Cause: The process successfully executed the SQL statement.

Action: None

OGG-00889: Error performing SQL statement at end of transaction

Cause: A fatal error occurred when the process tried to execute a SQL statement at the end of a transaction.

Action: Resolve the problem based on the SQL error. If the problem persists, contact Oracle Support.

OGG-00890: Error performing SQL statement at end of transaction

Cause: A non-fatal error occurred when the process tried to execute a SQL statement at the end of a transaction.

Action: Resolve the problem based on the SQL error. If the problem persists, contact Oracle Support.

OGG-00891: Unsuccessful execution: {0}

Cause: A fatal error occurred when the process tried to execute a SQL statement.

Action: Resolve the problem based on the SQL error. If the problem persists, contact Oracle Support.

OGG-00892: Unsuccessful SQL execution: {0}

Cause: The process was not able to execute the SQL statement because of a database error that is stated in the error text.

Action: Correct the cause of the error, and then restart the process.

OGG-00893: SQL statement executed successfully.

Cause: The process successfully executed a SQL statement.

Action: None

OGG-00894: SQL error {1,number,0} occurred when updating duplicate row in table {0}

Cause: The specified error occurred when the process issued an update on a duplicate row. There may be a constraint error.

Action: Remove the duplicate row or change the constraint, and then restart the process.

OGG-00895: Unexpected error: could not add HASH for table {0}

Cause: An internal error occurred when the process tried to add a hash for the specified table.

Action: Save this message and any related messages, and contact Oracle Support.

OGG-00896: Unexpected error: Delete of item known to be in hash table failed

Cause: An internal error occurred.

Action: Save this message and any related messages, and contact Oracle Support.

OGG-00897: Unexpected error: could not find newly added table ({0}) by name

Cause: The specified table was resolved by the Extract producer thread but cannot be resolved by the Extract consumer thread.

Action: Check to see if this table still exists. If not, restart Extract.

OGG-00898: Unexpected error: could not find newly added table ({0}) by Object ID ({1})

Cause: Extract could not find the specified table by its object ID.

Action: Contact Oracle Support.

OGG-00899: Table {0} does not exist

Cause: The specified table does not exist in the database, but is specified in the Oracle GoldenGate configuration.

Action: Remove the table from the TABLE and MAP statements.

OGG-00900: Table {0} object id {1} not found

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-00901: Failed to lookup object ID for table {0}

Cause: The DB2 catalog query for the specified table failed.

Action: The table might have been dropped. If the table still exists, start the process again. If the error persists, contact Oracle Support.

OGG-00902: Total byte length of table {0} is too long (at column {1}, offset = {2,number,0})

Cause: The specified column is longer than the maximum length supported by Oracle GoldenGate for the Sybase database.

Action: Decrease the length of the column.

OGG-00903: Error retrieving row count for last executed statement

Cause: The SQLRowCount() call returned an error.

Action: Check the SQLRowCount() API page to see the possible issues associated with this call and correct the problem. If the problem persists, contact Oracle Support.

OGG-00904: Calling {0} when there is no active transaction (seqno: {1,number,0}, rba: {2,number,0}). Request ignored.

Cause: An internal error occurred because a ROLLBACK or COMMIT was called when there was no open transaction.

Action: Save the trail files, and contact Oracle Support.

OGG-00905: Calling BEGIN when there is still an active transaction (seqno: {0,number,0}, rba: {1,number,0}). Request ignored.

Cause: An internal error occurred because a BEGIN TRANSACTION was issued for an open transaction.

Action: Save the trail files, and contact Oracle Support.

OGG-00906: Unrecognized data type: {0,number,0}

Cause: An unexpected data type was encountered.

Action: Contact Oracle Support.

OGG-00908: Table {0} column {1,number,0} : value truncated to {2,number,0}

Cause: The value of the specified column was truncated because the target database does not support the full length. The target data may not be an accurate reflection of the source.

Action: Extend the target column length, or you can treat these cases as exceptions and apply the DML manually if you want to retain the full data length. For more information, see the error handling documentation in the Oracle GoldenGate Administration documentation.

OGG-00909: Table {0}, column {1}, unrecognized data type: {2,number,0}

Cause: The specified column contains an unsupported data type.

Action: For supported data types, see the Oracle GoldenGate documentation for this database.

OGG-00910: Table {0}, column {1}, unrecognized data type: {2}

Cause: The specified column contains an unrecognized or unsupported data type.

Action: For supported data types, see the Oracle GoldenGate documentation for this database.

OGG-00911: Table {0}, column {1}, unrecognized or unsupported data type: {2}

Cause: The specified column contains an unrecognized or unsupported data type.

Action: For supported data types, see the Oracle GoldenGate documentation for this database.

OGG-00912: Could not find key column {1} within definition for table {0}

Cause: The key definition probably was changed. Oracle GoldenGate needs to know of the new definition.

Action: Stop and then immediately start the process, so a new object cache can be built.

OGG-00913: Invalid datatype ({2,number,0}) processing column {0} ({1,number,0})

Cause: The specified column contains an unrecognized or unsupported data type.

Action: For supported data types, see the Oracle GoldenGate documentation for this database.

OGG-00914: Table {0} contains too many columns. Max columns allowed is {1,number,0}

Cause: The number of columns in the table exceeds that which is supported by Oracle GoldenGate.

Action: You can exclude columns, if permissible, by using the COLSEXCEPT clause of TABLE and MAP, or you can remove the table from the Oracle GoldenGate configuration.

OGG-00915: Column '{1}' in table '{0}' cannot be used as a key column.

Cause: The specified column is of a type that is not supported for use as a key by Oracle GoldenGate.

Action: If the key cannot be altered to remove the column, you can specify a unique index or you can define a key with the KEYCOLS clause of TABLE and MAP. The index or KEYCOLS must match on the source and target tables.

OGG-00916: Column '{1}' cannot be used as a key column. Define a unique index for table '{0}' without this column or use the KEYCOLS parameter to correct this issue

Cause: The specified column in the table key is of a type that is not supported for use as a key by Oracle GoldenGate.

Action: If the key cannot be altered to remove the column, you can specify a unique index or you can define a key with the KEYCOLS clause of TABLE and MAP. The index or KEYCOLS must match on the source and target tables.

OGG-00917: KEYCOLS parameter references column '{1}' which cannot be used as a key column. Remove this column from the KEYCOLS parameter for table '{0}' to correct this issue

Cause: The specified column is of a type that is not supported for use as a key by Oracle GoldenGate.

Action: Remove the column from the KEYCOLS clause.

OGG-00918: Key column {0} is missing from map

Cause: Some, but not all, key columns are mapped in a COLMAP clause. If mapping key columns, all key columns must be mapped.

Action: Add all key column(s) to the COLMAP clause.

OGG-00919: Error in {0} clause

Cause: There is a syntax error in the specified clause in the parameter file.

Action: Fix the error. For help, see the Oracle GoldenGate reference documentation.

OGG-00920: Error ({1,number,0}) executing command {0}

Cause: The execution of an immediate SQL statement failed.

Action: Contact Oracle Support.

OGG-00921: Unable to determine the database name

Cause: The process could not determine the name of the database in order to establish a connection.

Action: Make certain that the Oracle GoldenGate user has privileges to query the database name. Also, make certain that the SOURCEDB or TARGETDB parameter is specified, if required for this database type.

OGG-00924: The wildcard specification length has a length of {1,number,0}. The maximum allowed in the return buffer is {0,number,0}

Cause: The wildcard specification has too many characters.

Action: Reduce the length of the wildcard specification to the size specified in the message.

OGG-00925: tables out-of-sync: source {0}, target {1}, rows {2,number,0}

Cause: This message is deprecated.

Action: None

OGG-00926: tables in sync: source {0}, target {1}

Cause: This message is deprecated.

Action: None

OGG-00927: Error in status file: missing {0} attribute

Cause: The specified attribute is missing from the XML message for the Oracle GoldenGate server or agent process. This indicates an internal error.

Action: Contact Oracle Support.

OGG-00928: exceeded max_tables ({0,number,0})

Cause: Oracle GoldenGate Veridata Agent was asked to list all tables or views in a remote database or schema, and the number of tables exceeds the amount that can fit in the message.

Action: File an enhancement request with Oracle Support to increase the maximum number of tables supported.

OGG-00929: exceeded max_schemas ({0,number,0})

Cause: Oracle GoldenGate Veridata Agent was asked to list all tables or views in a remote database or schema, and the number of tables exceeds the number of schemas that can fit in the message.

Action: File an enhancement request with Oracle Support to increase the maximum number of schemas supported.

OGG-00930: Invalid XML in parameter file {0}

Cause: This message is deprecated.

Action: None

OGG-00931: Invalid configuration file: {0}

Cause: This message is deprecated.

Action: None

OGG-00932: FILENAME_RESOLVE_error {0,number,0} on {1}

Cause: This error occurs on a NonStop system when the agent cannot determine the Guardian file name for an Oracle GoldenGate sub-directory. The Guardian error code is displayed with the message.

Action: Take the appropriate action based on the Guardian error code.

OGG-00933: could not find name for table entry {0,number,0}

Cause: The attribute for the table name is missing from the XML file.

Action: Contact Oracle Support.

OGG-00934: could not find table-info node for {0}

Cause: The table-info element is missing from the XML file.

Action: Contact Oracle Support.

OGG-00935: No keycols specified for table {0} that does not have a primary key

Cause: No defined primary key or user-defined key columns are defined for the specified comparison table.

Action: Contact Oracle Support.

OGG-00936: Access denied (request from {0}, rule #{1,number,0})

Cause: Access to Manager was denied to the specified address based on rules set in the ACCESSRULE parameter.

Action: Determine why the connection attempt was made. If it is legitimate, you can adjust the rules of ACCESSRULE.

OGG-00937: Error ({0,number,0}) decrypting password: {1}

Cause: Manager on the target cannot decrypt the password that was specified with the ENCRYPT PASSWORD command on the source.

Action: If you defined your own key, make certain the ENCKEYS files on the source and target exist, and that they contain the same key. If you used an Oracle GoldenGate-generated default key, make certain it was copied correctly into the USERID or TRANLOGOPTIONS ASMUSER parameters. You might need to retry the default encryption again.

OGG-00938: Manager is stopping at user request

Cause: The Manager process was stopped by a user.

Action: None, if intentional. Note that when Manager is stopped, Oracle GoldenGate processes cannot continue to replicate data.

OGG-00939: Service Control Manager requested PAUSE

Cause: The Windows Service Control Manager issued a PAUSE command for the Manager service.

Action: None, if intentional. Note that when Manager is paused, Oracle GoldenGate processes cannot continue to replicate data.

OGG-00940: Service Control Manager requested STOP

Cause: The Windows Service Control Manager issued a STOP command for the Manager service.

Action: None, if intentional. Note that when Manager is stopped, Oracle GoldenGate processes cannot continue to replicate data.

OGG-00941: Service Control Manager requested CONTINUE

Cause: The Windows Service Control Manager issued a CONTINUE (Resume) command for the Manager service.

Action: None

OGG-00942: Service Control Manager requested SHUTDOWN

Cause: The Windows Service Control Manager issued a SHUTDOWN command for the Manager service.

Action: None, if intentional. Note that when Manager is stopped, Oracle GoldenGate processes cannot continue to replicate data.

OGG-00943: Error in service processing: Creating thread for batch tasks (error {0,number,0})

Cause: The process could not create a thread for batch tasks.

Action: Verify that the system has the capacity for creating more threads. If you cannot resolve the problem, contact Oracle Support.

OGG-00944: Error in service processing: Calling {0} (error {1,number,0})

Cause: A call to the Windows SetServiceStatus or RegisterServiceCtrlHandler failed.

Action: Check the Windows system error log and correct the problem. If you cannot resolve the problem, contact Oracle Support.

OGG-00945: Startup of {0} {1} failed ({2})

Cause: The specified process cannot start.

Action: Look for additional error messages that indicate why the process cannot start, and then correct the problem.

OGG-00946: {0} {1} abended

Cause: The specified process abended.

Action: Look for additional error messages that indicate why the process abended, and then correct the problem.

OGG-00947: Lag for {0} {1} is {2} (checkpoint updated {3} ago)

Cause: The setting of the LAGINFO parameter prompted Manager to report lag information to the error log. This message is considered a warning message because the lag is greater than the value specified with the LAGCRITICAL parameter.

Action: Correct the problem that is causing the lag. For help with configuring Oracle GoldenGate to reduce lag, see the Oracle GoldenGate troubleshooting and performance documentation.

OGG-00948: Lag for {0} {1} is {2} (checkpoint updated {3} ago)

Cause: The setting of the LAGINFO parameter prompted Manager to report lag information to the error log. This message is considered an informational message because the lag is not greater than the value specified with the LAGCRITICAL parameter.

Action: None

OGG-00949: Invalid checkpoint type {{2,number,0}}, cannot determine lag threshold for {0} {1}

Cause: The checkpoint is invalid.

Action: Contact Oracle Support.

OGG-00950: Purge of old extract file {0} failed because the prev seqno exists. Purge rule was {1}

Cause: There is a MINKEEP rule in the PURGEOLDEXTRACTS parameter that requires a minimum number of files to be retained.

Action: None

OGG-00951: Purging task {0} {1}: could not delete file {2} {{3,number,0} {4}}

Cause: Manager could not purge the named remote task because it could not delete the specified file due to an operating system error.

Action: Fix the operating system error.

OGG-00952: Purging log history from {0} older than {1}: {2}

Cause: Manager successfully purged rows in the log table that were older than the date shown. Informational only. This message appears in older Oracle GoldenGate versions that support trigger-based capture.

Action: None

OGG-00953: Purging log history from {0} older than {1}: {2}

Cause: Manager is purging history from the log table. Informational only. This message appears in older Oracle GoldenGate versions that support trigger-based capture.

Action: None

OGG-00954: Purging rows from {0} older than {1}: {2}

Cause: Manager failed to purge rows in the log table that are older than the date shown. Informational only. This message appears in older Oracle GoldenGate versions that support trigger-based capture.

Action: Delete the rows manually.

OGG-00955: Purging rows from {0} older than {1}: {2}

Cause: Manager successfully purged rows in the log table that were older than the date shown. Informational only. This message appears in older Oracle GoldenGate versions that support trigger-based capture.

Action: None

OGG-00956: hours_since_modified calculated as {1,number,0}, modtime is {2,number,0} for {0}

Cause: Manager determined that the specified file remained unmodified for the number of hours shown in this message, with the last modification being performed at the time shown.

Action: None

OGG-00957: Purged old extract file {0}, {1}

Cause: The specified file was purged under the rules shown in the message text.

Action: None

OGG-00958: {0} (MINKEEPFILES option not used; last MINKEEP time option entered will be used)

Cause: The PURGEOLDEXTRACTS parameter contains the option MINKEEPOOURS or MINKEEPDAYS with the option MINKEEPFILES. These are mutually exclusive. If either MINKEEPOOURS or MINKEEPDAYS is used with MINKEEPFILES, then MINKEEPOOURS or MINKEEPDAYS is accepted, and MINKEEPFILES is ignored.

Action: Remove MINKEEPFILES (or MINKEEP{HOURS | DAYS} depending on your requirements).

OGG-00959: {0} (MINKEEPFILES option not used.)

Cause: The PURGEOLDEXTRACTS parameter contains the option MINKEEPOOURS or MINKEEPDAYS with the option MINKEEPFILES. These are mutually exclusive. If either MINKEEPOOURS or MINKEEPDAYS is used with MINKEEPFILES, then MINKEEPOOURS or MINKEEPDAYS is accepted, and MINKEEPFILES is ignored.

Action: Remove MINKEEPFILES (or MINKEEP{HOURS | DAYS} depending on your requirements).

OGG-00960: Access granted (rule #{0,number,0})

Cause: Access to Oracle GoldenGate was granted based on the specified rule.

Action: None

OGG-00961: DEBUG {0}: {1}

Cause: This is an informational message for debugging purposes.

Action: None

OGG-00962: {1} did not recognize command {0}

Cause: Manager received an unrecognized command.

Action: Check the syntax of the command for typographical errors or invalid options. For help, see the Oracle GoldenGate reference documentation or the online GGSCI help.

OGG-00963: Command received from {0} on host {1} ({2})

Cause: Manager received the specified command from the specified host.

Action: None

OGG-00964: {0} {1} started automatically

Cause: The specified process was restarted automatically based on the AUTOSTART parameter.

Action: None

OGG-00965: {0} {1} restarted automatically

Cause: The specified process was restarted automatically based on rules in the AUTORESTART parameter.

Action: None

OGG-00966: {0} {1} is already running

Cause: A START command was issued for a process that is already running.

Action: None

OGG-00967: Manager performing AUTOSTART processing

Cause: Manager is automatically starting processes according to the AUTOSTART parameter(s) in the Manager parameter file.

Action: None

OGG-00968: ERROR: can not send command to Manager

Cause: The last command could not be sent to Manager.

Action: Make certain that Manager is running and that the network connections to it are working properly.

OGG-00969: ERROR: Manager responded with {0}

Cause: Manager could not start the passive Extract.

Action: Check the process report and the error log for additional messages that provide context for this problem. If you cannot resolve the problem based on other messages, contact Oracle Support.

OGG-00970: ERROR: Bad reply message from Manager

Cause: The Manager reply is not valid.

Action: Contact Oracle Support. Save the process report and the error log for the support case.

OGG-00971: ERROR: {0}

Cause: An Oracle GoldenGate component failed to start.

Action: Check the report file that is issued by the process, and check the error log for other messages adjacent to this one that might help you resolve the problem. Make certain Manager is running for other processes to start. The database also must be running. Trail files must be properly created. Parameter files must be in the expected location. For additional help, see the Oracle GoldenGate troubleshooting documentation. If you cannot resolve the problem, contact Oracle Support.

OGG-00972: {0} {1} -> {2}@{3} started on port {4}

Cause: The specified program started on the specified port number.

Action: None

OGG-00973: Manager started replicat task process (Port {0,number,0})

Cause: Manager started a Replicat task on the specified port number.

Action: None

OGG-00974: Manager started collector process (Port {0,number,0})

Cause: Manager started a Collector process on the specified port number.

Action: None

OGG-00975: {0}

Cause: This is a generic informational message and does not indicate any problem.

Action: None

OGG-00976: Manager started '{0}' process on port {1,number,0}

Cause: Manager started the specified process on the specified port number.

Action: None

OGG-00978: {0} {1} is running

-
- Cause:** The specified process is running.
Action: None
- OGG-00979: {0} {1} is down (gracefully)**
Cause: The specified process stopped gracefully.
Action: None
- OGG-00980: Purged task {0} {1}**
Cause: The specified task was purged according to the rules in the PURGEOLDTASKS parameter.
Action: None
- OGG-00981: Task {0} {1} is running, cannot purge**
Cause: The specified task is still running.
Action: Stop the task to enable purging.
- OGG-00982: Rule {0,number,0}: {1}, seqno: {2,number,0}, hours_since_modified: {3,number,0}, modtime: {4,number,0}, oldest chkpt: {5,number,0}**
Cause: Manager is purging old trail files based on the rules specified in PURGEOLDEXTRACTS.
Action: None
- OGG-00983: Manager started (port {0,number,0})**
Cause: The Manager process started on the specified port number.
Action: None
- OGG-00984: Delaying {0,number,0} minutes, {1,number,0} seconds before further processing**
Cause: The BOOTDELAYMINUTES parameter is being used for Manager, and Manager is waiting for the specified amount of time before performing its startup activities.
Action: None
- OGG-00985: Purged old veriagt report {0}**
Cause: The Veridata Agent report was purged successfully.
Action: None
- OGG-00986: Error {1,number,0} Purging old veriagt report {0}**
Cause: The Veridata Agent report could not be purged due to the specified error from the operating system.
Action: Correct the operating system error.
- OGG-00987: GGSCI command ({0}): {1}**
Cause: The specified command from GGSCI was received.
Action: None
- OGG-00988: WARNING: Unsupported operation. This might cause transactional inconsistency. Modifying input checkpoint #{3,number,0}, Oracle thread #{4,number,0} of {2}: ioseq = {0,number,0} iorba = {1,number,0}**
Cause: An ALTER EXTRACT command was issued to alter the read position of an Extract thread that reads one of the logs in a RAC configuration.

Action: None. This is a warning but assumes the action is intentional. For help, contact Oracle Support.

OGG-00989: WARNING: Unsupported operation. This might cause transactional inconsistency. Modifying iocheckpoint: ioseq = {0,number,0} iorba = {1,number,0}

Cause: An unsupported ALTER operation was received.

Action: None. This is a warning but assumes the action is intentional. For help, contact Oracle Support.

OGG-00990: {0} stop forced by user

Cause: The specified Extract or Replicat process was stopped forcefully by a user.

Action: None

OGG-00991: {0} stopped normally

Cause: The specified Extract process stopped gracefully.

Action: None

OGG-00992: {0} starting

Cause: The specified Extract process is performing its startup.

Action: None

OGG-00993: {0} started

Cause: The specified Extract process started successfully.

Action: None

OGG-00994: {0} stopped normally

Cause: The specified Replicat process stopped gracefully.

Action: None

OGG-00995: {0} starting

Cause: The specified Replicat process is performing its startup.

Action: None

OGG-00996: {0} started

Cause: The specified Replicat process started successfully.

Action: None

OGG-00997: Purge of old extract file {0} failed (error {1,number,0}, {2})

Cause: The process tried to purge old trail files based on the rules in the PURGEOLDEXTRACTS parameter, but it encountered the specified operating-system error.

Action: Correct the cause of the error or contact the system administrator.

OGG-00998: Purging old extract file {0}

Cause: The process is purging old trail files based on the rules in the PURGEOLDEXTRACTS parameter.

Action: None

OGG-00999: Missing transaction begin, {0,number,0} records bypassed

Cause: The process skipped the specified number of records because the begin-transaction record is missing.

Action: None

OGG-01000: Reperror {0} rule for error {1,number,0} found, Action {2}, Maxretries {3,number,0} exceeded

Cause: Replicat parsed a REPERROR rule statement with the specified error number and action, and retried the operation up to the maximum number of times that is specified with the MAXRETRIES option.

Action: Correct the problem that caused the error, and then restart Replicat.

OGG-01001: Reperror {0} rule for error {1,number,0} found, Action {2}

Cause: Replicat parsed a REPERROR rule statement and will take the specified action for the operation that returned the specified error number.

Action: None

OGG-01002: Reperror {0} rule for error {1,number,0} found, Action {2}, retries {3,number,0}

Cause: Replicat parsed a REPERROR rule statement that includes the RETRYOP option, and will retry the operation that returned the specified error number.

Action: None

OGG-01003: Repositioning to rba {1,number,0}{0,choice,-1#|0# in seqno {0,number,0}}

Cause: The process is repositioning its read point to the specified location in the trail.

Action: None

OGG-01004: Aborted grouped transaction on '{0}', Database error {1,number,0} ({2})

Cause: Replicat is not able to apply the GROUPTRANSOPS-controlled grouped transaction on the specified table, due to the SQL error that is reported in the message text.

Action: Correct the problem that is reported in the error message. For more information on GROUPTRANSOPS, see the Oracle GoldenGate reference documentation.

OGG-01005: A value of zero for GROUPTRANSOPS is invalid. Using a value of one instead.

Cause: A value of zero is specified for the GROUPTRANSOPS parameter. A value of 1 executes the operations within the same transaction boundaries as the source transaction. Any value above 1 sets the minimum number of operations within a Replicat transaction.

Action: Increase the value of GROUPTRANSOPS. See the Oracle GoldenGate reference documentation to determine an appropriate value.

OGG-01006: Maximum records exceeded in discard file ({0,number,0})

Cause: The maximum number of records allowed in the file specified with the DISCARDFILE parameter has been reached.

Action: Increase the file size up to maximum permitted by the MAXBYTES or MEGABYTES option of DISCARDFILE.

OGG-01007: Maximum records exceeded in discard file ({0,number,0})

Cause: The maximum number of records allowed in the file specified with the DISCARDFILE parameter has been reached.

Action: Increase the file size up to maximum permitted by the MAXBYTES or MEGABYTES option of DISCARDFILE.

OGG-01008: Discarding bad record (discard recs = {0,number,0})

Cause: The process is discarding a record that it cannot process, and it is reporting the current number of discarded records that are in the DISCARDFILE file.

Action: None

OGG-01009: Error executing stored proc {0}: {1}

Cause: The process attempted to execute the specified stored procedure, but the specified database error was returned.

Action: Fix the cause of the error that is shown in the message text.

OGG-01010: Error executing stored proc {0}: {1}

Cause: The process attempted to execute the specified stored procedure, but the specified database error was returned.

Action: Fix the cause of the error that is shown in the message text.

OGG-01011: Skipped {0}.

Cause: The SEND EXTRACT command was issued with SKIPTRANS, and Extract skipped the specified long-running transaction.

Action: None

OGG-01012: Failed to skip {0} due to error ({1}).

Cause: The SEND EXTRACT command was issued with SKIPTRANS, but Extract cannot skip the specified long-running transaction. Some possible causes are: the specified transaction is not the oldest one in the list of transactions shown with SHOWTRANS, or the THREAD option was not used if the database is Oracle RAC.

Action: Fix the cause of the error that is shown in the message text.

OGG-01013: Cannot replace missing not-null column '{1}' of table '{0}'

Cause: The process encountered a not-null column for which no data existed, and it attempted to fetch a value from the database, but failed.

Action: None

OGG-01014: Positioning with begin time: {0,date} {0,time}, starting record time:

{1,date} {1,time} at {2,choice,-1#|0#extseqno {2,number,0}, }extrba {3,number,0}

Cause: The process is configured to start processing at the specified time, and it is starting with the specified record as the first one to be processed.

Action: None

OGG-01015: Positioning with begin time: {0,date} {0,time}, waiting for data: at extseqno {1,number,0}, extrba {2,number,0}

Cause: The process is configured to start processing at the specified time. It is currently waiting for data at the specified position in the data source.

Action: None

OGG-01016: Positioning with begin time: {0,date} {0,time}, skipping incomplete record - starting record time: {1,date} {1,time} at extseqno {2,number,0}, extrba {3,number,0}

Cause: The process is configured to start processing at the specified time. The first record with that timestamp is incomplete, so it is being skipped.

Action: None

OGG-01017: Wildcard resolution set to IMMEDIATE because SOURCEISTABLE is used

Cause: The WILDCARDRESOLVE parameter is set to its default of DYNAMIC, but the process overrode the setting because SOURCEISTABLE is also used in the parameter file. IMMEDIATE is the forced default for SOURCEISTABLE. Source objects that satisfy a wildcard definition are processed at startup.

Action: None

OGG-01018: Recovered from error at rba {1,number,0} in seqno {0,number,0}, replicat continuing

Cause: The recovery from the failed operation succeeded.

Action: None

OGG-01019: Marker processed by {0}, group {1}, lag {2}

Cause: The Oracle GoldenGate marker record was processed successfully.

Action: None

OGG-01020: Processed extract process {0} record at seq {2,number,0}, rba {3,number,0} (aborted {1,number,0} records)

Cause: Extract processed the specified record. Informational only.

Action: None

OGG-01021: Command received from {0}: {1}

Cause: A command was received from the specified process. This is informational only.

Action: None

OGG-01022: Unknown {1,number,0} bytes message received from {2}:{3,number,0} - {0}

Cause: An incomplete command was received from the specified process and cannot be executed.

Action: If this message continues to appear, contact Oracle Support.

OGG-01023: Recovered from retryable error on table {0}

Cause: Replicat successfully applied a SQL operation that caused an error in a previous attempt. Informational only.

Action: None

OGG-01024: Retrying SQL error {3,number,0} at rba {2,number,0} in seqno {1,number,0}, updating {0} in {4,number,0} seconds

Cause: Replicat is retrying a SQL operation that caused an error, based on REPERROR with the RETRYOP option. Informational only.

Action: None

OGG-01025: REPLICAT task started by manager (port {0,number,0})

Cause: The Manager on the target started a remote-task Replicat. Informational only.

Action: None

OGG-01026: Rolling over remote file {0}

Cause: Extract is closing the current remote file and starting a new one.
Informational only.

Action: None

OGG-01027: {0}

Cause: A non-recoverable error occurred in Extract or Replicat.

Action: Contact Oracle Support and provide the details of this message.

OGG-01028: {0}

Cause: A non-recoverable error occurred in Extract or Replicat.

Action: Contact Oracle Support and provide the details of this message.

OGG-01029: Extract reposition err - {0}

Cause: The process encountered an error while attempting to position to a specific point in the trail file.

Action: Verify that the specified sequence number and RBA exist, and specify valid ones if necessary. Restart the process. Contact Oracle Support if this problem persists.

OGG-01030: Could not find checkpoint for output file {0}

Cause: During recovery, Extract encountered a trail file that is no longer assigned to it.

Action: Specify the correct trail for this process, and delete the incorrect trail file with the DELETE EXTTRAIL or DELETE RMTTRAIL command.

OGG-01031: There is a problem in network communication, a remote file problem, encryption keys for target and source do not match (if using ENCRYPT) or an unknown error. (Reply received is {0})

Cause: Extract was not able to send data to the target.

Action: Examine the network for an outage between the source and target system. Make certain that MGRPORT in RMTHOST matches the one in the parameter file of the remote Manager. Check for errors on the target system that indicate the Manager or Collector process is not running, or that Collector does not have privileges to write to the remote trail. Check for encryption errors if the ENCRYPT option is specified with the RMTHOST or RMTHOSTOPTIONS parameter: This might indicate that the encryption key that was sent from the source does not match the one in the ENCKEYS file on the target, or that the key or ENCKEYS file on the target is missing.

OGG-01032: There is a problem in network communication, a remote file problem, encryption keys for target and source do not match (if using ENCRYPT) or an unknown error. Length is {1,number,0} - {0}

Cause: Extract was not able to send data to the target.

Action: Examine the network for an outage between the source and target system. Make certain that MGRPORT in RMTHOST matches the one in the parameter file of the remote Manager. Check for errors on the target system that indicate the Manager or Collector process is not running, or that Collector does not have privileges to write to the remote trail. Check for encryption errors if the ENCRYPT option is specified with the RMTHOST or RMTHOSTOPTIONS parameter: This might indicate that the encryption key that was sent from the source does not match the one in the ENCKEYS file on the target, or that the key or ENCKEYS file on the target is missing.

OGG-01033: There is a problem in network communication, a remote file problem, encryption keys for target and source do not match (if using ENCRYPT) or an unknown error. (Remote file used is {0}, reply received is {1})

Cause: Extract was not able to send data to the target.

Action: Examine the network for an outage between the source and target system. Make certain that MGRPORT in RMTHOST matches the one in the parameter file of the remote Manager. Check for errors on the target system that indicate the Manager or Collector process is not running, or that Collector does not have privileges to write to the remote trail. Check for encryption errors if the ENCRYPT option is specified with the RMTHOST or RMTHOSTOPTIONS parameter: This might indicate that the encryption key that was sent from the source does not match the one in the ENCKEYS file on the target, or that the key or ENCKEYS file on the target is missing.

OGG-01034: There is a problem in network communication, a remote file problem, encryption keys for target and source do not match (if using ENCRYPT) or an unknown error. (Remote file used is {0})

Cause: Extract was not able to send data to the target.

Action: Examine the network for an outage between the source and target system. Make certain that MGRPORT in RMTHOST matches the one in the parameter file of the remote Manager. Check for errors on the target system that indicate the Manager or Collector process is not running, or that Collector does not have privileges to write to the remote trail. Check for encryption errors if the ENCRYPT option is specified with the RMTHOST or RMTHOSTOPTIONS parameter: This might indicate that the encryption key that was sent from the source does not match the one in the ENCKEYS file on the target, or that the key or ENCKEYS file on the target is missing.

OGG-01035: File {0} already exists and purge not specified

Cause: The process will not write to an existing file unless the PURGE option is used with the RMTFILE parameter.

Action: Add the PURGE option, and then restart the process.

OGG-01038: Cannot fetch required data from table {0} due to missing key columns

Cause: Row data could not be fetched from the table because no key is defined on the table.

Action: Define a key or specify unique columns with the KEYCOLS clause of the TABLE statement.

OGG-01039: mergeFetchedCols() failed to merge result fetched from table

Cause: Extract was not able to merge the fetched data with the row data that was obtained from the transaction log.

Action: Contact Oracle Support.

OGG-01040: Failed to prepare fetch on table {0}.

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-01041: Failed to prepare fetch on table {0} due to lack of defined key columns. Use KEYCOLS.

Cause: Row data could not be fetched from the table because no key is defined on the table.

Action: Define a key or specify unique columns with the KEYCOLUMNS clause of the TABLE statement.

OGG-01042: Invalid token length, expected: {0,number,0}, got: {1,number,0}

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-01043: Terminate on fetch result = {1} ({2,number,0}) (table: '{0}')

Cause: The process failed to fetch column data, and the ABEND action is specified by the REPFETCHEDCOOPTIONS parameter.

Action: None. This is the expected result for ABEND.

OGG-01044: The trail '{0}' is not assigned to extract '{1}'. Assign the trail to the extract with the command "ADD EXTTRAIL/RMTTRAIL {0}, EXTRACT {2}"

Cause: The trail is specified in the Extract parameter file with an EXTTRAIL or RMTTRAIL parameter, but the required command to link the trail to the Extract process was not issued.

Action: In GGSCI, issue the ADD EXTTRAIL or ADD RMTTRAIL command.

OGG-01045: Unrecognized response from server recovering target file {0}, at RBA {1,number,0}

Cause: Extract encountered a parsing error while reading values from a reply sent by the Server (Collector) process.

Action: Contact Oracle Support.

OGG-01046: Target does not support append recovery mode. Reverting to overwrite recovery mode in file {0}, at RBA {1,number,0}

Cause: The version of the Server (Collector) is older than the version of Extract, and it does not support APPEND mode for trails or files. It is just a warning. Extract handles this situation automatically.

Action: None

OGG-01048: Server error while recovering target file {0}, at RBA {1,number,0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01049: Invalid server return code ({0,number,0}) for target file {1}, at RBA {2,number,0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01051: Reverting to overwrite recovery mode at user's request...

Cause: The recovery method (controlled by the RECOVERYOPTIONS parameter) was changed to overwrite mode, from the default of append mode. Informational only.

Action: None

OGG-01052: No recovery is required for target file {0}, at RBA {1,number,0} (file not opened)

Cause: No trail exists to recover.

Action: None

OGG-01053: Recovery completed for target file {0}, at RBA {1,number,0}

Cause: Extract completed its recovery.

Action: None

OGG-01054: Recovery completed for target file {0}, at RBA {1,number,0}, CSN {2}

Cause: Extract completed its recovery.

Action: None

OGG-01055: Recovery initialization completed for target file {0}, at RBA {1,number,0}

Cause: The initialization phase of recovery completed. No transaction was found in the portion of the trail that was scanned, probably because Extract is inactive.

Action: None

OGG-01056: Recovery initialization completed for target file {0}, at RBA {1,number,0}, CSN {2}

Cause: The initialization phase of recovery completed, and transaction were found in the portion of the trail that was scanned. This is informational only.

Action: None

OGG-01057: Recovery completed for all targets

Cause: Extract recovered successfully for all of its targets.

Action: None

OGG-01058: Empty commit sequence number (CSN) detected in target file {0}, at RBA {1,number,0}

Cause: An inconsistency occurred in the communication between Extract and Server (Collector).

Action: Contact Oracle Support.

OGG-01059: Invalid commit sequence number (CSN) detected in target file {0}, at RBA {1,number,0}

Cause: An inconsistency occurred in the communication between Extract and Server (Collector).

Action: Contact Oracle Support.

OGG-01060: Failed to retrieve CSN from data source during recovery

Cause: The current CSN read point from the transaction log could not be found during Extract recovery.

Action: Contact Oracle Support.

OGG-01061: Invalid CSN value length({0,number,0}) from data source during recovery

Cause: The current CSN in the transaction record has an invalid length.

Action: Contact Oracle Support.

OGG-01062: Invalid last CSN value length({1,number,0}) for trail {0} during recovery

Cause: The length of the CSN of the last completed transaction is invalid.

Action: Contact Oracle Support.

OGG-01063: Current CSN value length({1,number,0}) differs from last CSN value length({2,number,0}), trail {0} during recovery

Cause: The length of the current CSN does not match the length of the CSN of the last completed transaction.

Action: Contact Oracle Support.

OGG-01064: {5}: Buffer overflow, needed: {1,number,0}, allocated: {0,number,0} in trail {2}, Seqno {3,number,0}, RBA {4,number,0}

Cause: While updating the CSN, transaction ID, or transaction ID list in memory, the process determined that there is not enough space for this information in the buffer.

Action: Contact Oracle Support.

OGG-01065: no CSN token found in record in trail {0}, Seqno {1,number,0}, RBA {2,number,0}

Cause: The CSN is missing from the trail record.

Action: Contact Oracle Support.

OGG-01066: Input record from trail file {0}, Seqno {1,number,0}, RBA {2,number,0}, has CSN {3} but no Transaction ID

Cause: The transaction identifier is missing from the trail record.

Action: Contact Oracle Support.

OGG-01067: Empty transaction ID detected in target file {0}, at RBA {1,number,0}

Cause: The transaction identifier in the trail record is empty.

Action: Contact Oracle Support.

OGG-01068: Invalid transaction ID detected in target file {0}, at RBA {1,number,0}

Cause: The transaction identifier in the trail record is invalid.

Action: Contact Oracle Support.

OGG-01069: Exceeded tran ID list size recovering target file {0}, at RBA {1,number,0}

Cause: While adding a transaction ID to the transaction ID list that is maintained for the current CSN, the process detected that there is no space left to add more transaction IDs.

Action: Contact Oracle Support.

OGG-01070: Cannot translate threshold status word for target file {0}, at RBA {1,number,0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01071: {0} cannot be used with stored data

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01072: {2}: Buffer overflow, needed: {1,number,0}, allocated: {0,number,0}

Cause: A variable value did not fit into the internal buffer that was assigned to it at runtime. This is an internal error.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-01073: {1}: Array overflow, {0,number,0} maximum entries

Cause: An array element in an XML message exceeded the defined limit.

Action: Contact Oracle Support.

OGG-01074: Invalid case statement, value {0,number,0} in {1}

Cause: This message is deprecated.

Action: None

OGG-01075: The table object ID cannot be used to look up the table entry if the tables were added via a SOURCEDEFS file

Cause: The definitions file prevents correct table name resolution. DB2 LUW only gives the tablespace ID and the table object ID in the log records. To be able to resolve the actual owner and table name as they are given in the TABLE parameter, Extract looks up the tablespace and object IDs in the database catalog. The IDs are used in an ODBC query against the system catalog tables to retrieve the table name. This process is not possible if a SOURCEDEFS or TARGETDEFS file is used as input.

Action: Remove the SOURCEDEFS or TARGETDEFS parameter.

OGG-01076: The table object ID cannot be used to look up the table entry if the table is a target table definition

Cause: This message is deprecated.

Action: None

OGG-01077: Error closing file, handle: 0x{0}, err: {1,number,0} - {2}

Cause: An operating system error was returned when attempting to close a file.

Action: Check the local file systems for errors.

OGG-01078: fcntl failure closing files after fork() {0,number,0} - {1,number,0}: {2}

Cause: Manager started a new Extract or Replicat process, but failed to close unused open file handles to reduce the number of open file handles.

Action: Check the host system for a possible file handle shortage. Consider restarting Manager and all Extract and Replicat processes if this warning persists.

OGG-01079: Data for column {0,number,0} is {2,number,0} bytes which exceeds the maximum of {1,number,0} bytes. Column data truncated for user exit.

Cause: The data for the specified column exceeds the size allowed by the user exit. Informational only.

Action: None

OGG-01080: SP {0} column {1} nearing buffer maximum of {2,number,0} bytes

Cause: The process is approaching the maximum buffer size that is set with the PARAMBUFSIZE of the SQLLEXEC parameter. This buffer stores input and output parameters.

Action: Stop the process, increase the buffer size, and then restart the process.

OGG-01081: SP {0} column {1} exceeded buffer maximum of {2,number,0} bytes

Cause: The SQLLEXEC input/output parameters exceeded the maximum buffer size that is set with the PARAMBUFSIZE of the SQLLEXEC parameter.

Action: Stop the process, increase the buffer size, and then restart the process.

OGG-01082: The call to the {0} function from {2} failed with return code {1,number,0}

Cause: An API error occurred.

Action: Contact Oracle Support.

OGG-01083: The call to the {0} function from {1} failed with return code {2,number,0} ({3})

Cause: A call to an operating system-provided API failed.

Action: Check the operating system for related problems, and resolve them or contact your system administrator. If you cannot resolve the problem, contact Oracle Support.

OGG-01084: WIN32 API CALL {0} failed {1,number,0} ({2})

Cause: A call to an operating system-provided API failed.

Action: Check the operating system for related problems, and resolve them or contact your system administrator. If you cannot resolve the problem, contact Oracle Support.

OGG-01085: {0} received window closed event

Cause: A user terminated an interactive process by closing the console window instead of issuing a STOP command from GGSCI. This is informational only.

Action: None

OGG-01086: {0} received system shutdown event

Cause: An interactive process was terminated due to a system shutdown instead of a STOP command from GGSCI. This message is informational only.

Action: None

OGG-01087: {0} received user logoff event

Cause: A logged-on user terminated the Windows desktop session. This message only occurs when Oracle GoldenGate is configured to run as a Windows service, and it is informational only.

Action: None

OGG-01088: Out of memory condition encountered. {2} attempting to allocate {1,number} bytes with {0}.{3,choice,0#|1# Process using {3,number} KB physical memory.}{4,choice,0#|1# Process using {4,number} KB virtual memory.}

Cause: An attempt to allocate memory from the host system failed.

Action: Check the system for a possible memory shortage. On some operating systems, this message is accompanied by a detailed memory-usage report that might assist with troubleshooting efforts.

OGG-01089: Directory {0} does not exist

Cause: The directory that is specified with TRANSMEMORY does not exist.

Action: Specify a different directory, or check the file system for possible damage.

OGG-01090: Unable to create directory "{0}" (error {1,number,0}, {2})

Cause: The specified directory could not be created. The path does not exist or the disk is full.

Action: Specify a valid directory name if the disk is not full.

OGG-01091: Unable to open file "{0}" (error {1,number,0}, {2})

Cause: The process could not open the specified file.

Action: Verify that the Oracle GoldenGate user has the privilege to open and write to files.

OGG-01092: Unable to lock file "{0}" (error {1,number,0}, {2})

Cause: The process could not lock the specified file.

Action: Determine whether this file is locked by another process and, if so, determine whether the other process is supposed to access this file or not. Check the Oracle GoldenGate configuration and fix any errors in the file specifications. If the problem persists, contact Oracle Support.

OGG-01093: Unable to delete file "{0}" (error {1,number,0}, {2})

Cause: The process could not remove the specified file.

Action: Verify that the process has privileges to remove the file.

OGG-01094: Unable to delete file "{0}" (error {1,number,0}, {2})

Cause: The process could not remove the specified file.

Action: Verify that the process has privileges to remove the file.

OGG-01095: Unable to redirect file "{0}" (error {1,number,0}, {2})

Cause: The process could not redirect to the output file.

Action: Verify that the process had privilege to redirect.

OGG-01096: Unable to write to file "{0}" (error {1,number,0}, {2})

Cause: An error occurred while the process was writing to an open file.

Action: Check for related errors in the error log of the operating system. If you cannot resolve the problem, contact Oracle Support.

OGG-01097: Could not sync "{0}" (error {1,number,0}, {2})

Cause: The process could not sync the specified file to disk.

Action: Check for related errors in the error log of the operating system. If you cannot resolve the problem, contact Oracle Support.

OGG-01098: Could not flush "{0}" (error {1,number,0}, {2})

Cause: The specified operating system error occurred when the process tried to flush the file.

Action: Contact Oracle Support.

OGG-01099: Function {1}, argument {0} cannot be NULL

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01100: Unrecoverable XML configuration error

Cause: A library error occurred while parsing the XML document.

Action: Check for a message that was issued by the library. If you cannot resolve the problem based on other errors, contact Oracle Support.

OGG-01101: unable build IPC message from XML node

Cause: A library error occurred while building an XML message.

Action: Check for a message that was issued by the XML processor. If you cannot resolve the problem based on other errors, contact Oracle Support.

OGG-01102: Error {0,number,0} - ({1})

Cause: This message is deprecated.

Action: Contact Oracle Support.

OGG-01103: missing err property in xml msg message

Cause: This message is deprecated.

Action: None

OGG-01104: Unknown error starting remote program {0}

Cause: An internal error occurred when Oracle GoldenGate Veridata Server tried to start an agent process.

Action: Contact Oracle Support.

OGG-01105: Error starting remote program {0} ({1} {2})

Cause: Oracle GoldenGate Veridata Server cannot start a remote agent.

Action: Follow the directions provided in the message text. Look for additional troubleshooting information in the error log of the remote Oracle GoldenGate installation. If you cannot resolve the problem, contact Oracle Support.

OGG-01106: IPC_client_writeread failed starting program {0} ({1,number,0}, {2})

Cause: Oracle GoldenGate Veridata Server cannot start a remote agent.

Action: Follow the directions provided in the message text. Look for additional troubleshooting information in the error log of the remote Oracle GoldenGate installation. If you cannot resolve the problem, contact Oracle Support.

OGG-01107: IPC_client_open failed opening port to Manager ({0,number,0}, {1})

Cause: Veridata server cannot connect to the remote Manager.

Action: Make certain that the remote Manager is running, and that the remote Manager port and host are specified correctly in the Oracle GoldenGate Veridata configuration. Follow any directions provided in the message text to resolve the problem. Look for additional troubleshooting information in the error log of the remote Oracle GoldenGate installation. If you cannot resolve the problem, contact Oracle Support.

OGG-01108: error decompressing IPC message ({1}, complen={0,number,0})

Cause: The IPC message could not be decompressed.

Action: Contact Oracle Support.

OGG-01109: error compressing IPC message ({1}, inlen={0,number,0})

Cause: The IPC message could not be compressed.

Action: Contact Oracle Support.

OGG-01110: Definition mismatch: column {1,number,0} {0} defined length

{2,number,0}, actual length {3,number,0}

Cause: The actual length of the data from the specified column is different from the length that is specified in the table definition.

Action: None

OGG-01111: Column-level ASCII/EBCDIC conversion is not currently supported

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-01112: Unexpected condition in {0} at line {1,number,0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01113: Unexpected condition in {0} at line {1,number,0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01114: invalid reply ({0})

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01115: Function {0} not implemented.

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01116: Marker fragment and current fragment out of sync

Cause: This message is deprecated.

Action: None

OGG-01117: Received signal: {1} ({0,number,0})

Cause: Oracle GoldenGate received a signal from the operating system indicating that processing cannot continue. The signal can be raised internally by an application error or externally by other means.

Action: Contact Oracle Support.

OGG-01118: Unhandled exception 0x{0} at 0x{1}

Cause: Oracle GoldenGate encountered a non-recoverable processing exception.

Action: Contact Oracle Support.

OGG-01119: XML error: {0}

Cause: An error occurred in the Oracle GoldenGate Veridata XML processor. The cause is reported in the message.

Action: If you cannot resolve the problem based on the message, contact Oracle Support.

OGG-01120: XML parse error on line ({0,number,0}) ({1}), Reason: {2}

Cause: An error was returned by the Oracle GoldenGate Veridata XML processor.

Action: If you cannot determine the cause and resolution from the message, contact Oracle Support.

OGG-01121: XML parse error

Cause: An error was returned by the Oracle GoldenGate Veridata XML processor.

Action: If you cannot determine the cause and resolution from the message, contact Oracle Support.

OGG-01122: Error opening module {0} - {1}]

Cause: An error occurred when Extract tried to open a dynamically linked library module.

Action: Make certain that the library exists and that its location is specified correctly. If the problem persists, contact Oracle Support.

OGG-01123: Error loading function {1} from {0} - {2}]

Cause: An error occurred when Extract tried to link to an exported function in a dynamically linked library module.

Action: Contact Oracle Support.

OGG-01124: Unauthorized access to {0} (CMDSEC)

Cause: The program is not authorized to read the CMDSEC (command security) file.

Action: You can grant read access as needed, but Oracle GoldenGate recommends denying write and delete access to everyone but Oracle GoldenGate Administrators.

OGG-01125: *ERROR* in CMDSEC: {0}

Cause: The CMDSEC (command security) file contains the specified error.

Action: Fix the error, and then restart the process.

OGG-01126: Abending at user-exit request

Cause: The instructions in a user exit caused the process to abend. Informational only.

Action: None

OGG-01127: cuserexit param PASSTHRU can not be used with {0}

Cause: The CUSEREXIT parameter contains the PASSTHRU option, which cannot be used with the specified parameter.

Action: Either remove the PASSTHRU option, or do not use the specified parameter (depending on your replication requirements).

OGG-01128: cuserexit param PASSTHRU may only be used with an Extract pump

Cause: The parameter file for a primary Extract process or a Replicat process contains the CUSEREXIT parameter with the PASSTHRU option. PASSTHRU is only valid for a data-pump Extract.

Action: Remove the PASSTHRU option, and then restart the process.

OGG-01129: NSort error {0,number,0} - {1}

Cause: The Nsort sorting function failed with the specified error.

Action: Fix the problem according to the Nsort error message.

OGG-01130: NSort function {0} failed with {1,number,0} - {2}

Cause: The Nsort sorting function failed with the specified error.

Action: Fix the problem according to the Nsort error message.

OGG-01131: error {2,number,0} reading queue file {0} at rba {1,number,0} ({3})

Cause: An operating system error occurred when the process tried to read the specified file.

Action: Resolve the operating system error, and then restart the process.

OGG-01132: error {2,number,0} positioning queue file {0} to rba {1,number,0} ({3})

Cause: The process cannot position in the trail file.

Action: Contact Oracle Support.

OGG-01134: Cannot find executable file '{0}'

Cause: An Oracle GoldenGate executable file is missing from the installation directory.

Action: Make certain that no files were removed from the Oracle GoldenGate installation directory. Repair or reinstall the Oracle GoldenGate software. If this problem persists, contact Oracle Support.

OGG-01135: fork() failed creating new process

Cause: An Oracle GoldenGate process could not be started.

Action: Check the operating system logs for a resource shortage.

OGG-01136: Child process is no longer alive

Cause: An Oracle GoldenGate process terminated immediately after starting successfully.

Action: Check the operating system logs for a resource shortage.

OGG-01137: BATCHSQL suspended, continuing in normal mode

Cause: Replicat suspended batch mode and is trying to apply the exceptions in normal mode within the GROUPTRANSOPS transaction boundary. Informational only.

Action: None

OGG-01139: BATCHSQL resumed, recovered from error

Cause: The Replicat parameter file contains the BATCHSQL parameter with the BATCHERRORMODE option. Replicat recovered from the error without leaving batch mode. Informational only.

Action: None

OGG-01142: Invalid format type 0x{0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01143: before image missing from key update for table {0}

Cause: A primary key was updated, but the before image is not in the Oracle redo log record. Supplemental logging for this table was not enabled before starting capture of its data.

Action: First, make certain that database-level supplemental logging is enabled. Next, do the following, without delay between steps, so that Extract lag is kept to a minimum: Stop Extract, then remove the table from the TABLE parameter, then restart Extract. Next issue ADD TRANDATA for the table. Stop activity on the table, and resynchronize it with the target. Stop Extract, then add the table back to the TABLE parameter. Start Extract and enable user activity on the table.

OGG-01144: Error mapping source hex-string data into a native floating-point format, col: [{0}], input: [{1}]

Cause: An error occurred while converting the specified column from a hex string to a native floating-point number.

Action: Contact Oracle Support.

OGG-01145: {0}

Cause: An internal error occurred during column mapping. The text of this message is generated by a lower-level function and is variable.

Action: Contact Oracle Support.

OGG-01146: {0}

Cause: An internal error occurred during column mapping. The text of this message is generated by a lower-level function and is variable.

Action: Contact Oracle Support.

OGG-01147: {0}

Cause: An internal error occurred during column mapping. The text of this message is generated by a lower-level function and is variable.

Action: Contact Oracle Support.

OGG-01148: {0}

Cause: An internal error occurred during column mapping. The text of this message is generated by a lower-level function and is variable.

Action: Contact Oracle Support.

OGG-01149: Invalid time format {0}

Cause: The mapping specification contains an invalid time format.

Action: To determine the correct format, see the Oracle GoldenGate reference documentation for the parameter or function that contains the incorrect format.

OGG-01150: Invalid timestamp/datetime format {0}

Cause: The mapping specification contains an invalid timestamp or datetime format.

Action: To determine the correct format, see the Oracle GoldenGate reference documentation for the parameter or function that contains the incorrect format.

OGG-01151: Error mapping from {0} to {1}

Cause: The mapping of the specified source and target tables failed.

Action: Look for other, related messages that provide details on the failure and can help you resolve the problem on your own. If the problem persists, contact Oracle Support.

OGG-01152: {0} ({1}) not mapped

Cause: The mapping of the specified source and target tables failed.

Action: Look for other, related messages that provide details on the failure and can help you resolve the problem on your own. If the problem persists, contact Oracle Support.

OGG-01154: SQL error {2,number,0} mapping {0} to {1} {3}

Cause: The specified SQL error occurred when mapping the specified source table to the specified target table.

Action: Depending on other parameter options that are specified in the Replicat parameter file, Replicat may attempt, and succeed, to handle the error and then continue processing. If the error cannot be handled, expect the process to fail with an error message.

OGG-01155: Filter not passed: user error {2,number,0} mapping {0} to {1}

Cause: The specified error occurred on the syntax of the FILTER clause for the specified source-target table mapping.

Action: Correct the syntax based on the error code, and then restart the process. For FILTER rules, see the TABLE and MAP parameters in the Oracle GoldenGate reference documentation.

OGG-01157: Error in WHERE clause for {0}

Cause: There was a syntax error in the WHERE clause of a TABLE or MAP statement.

Action: Correct the syntax error. For help, see TABLE and MAP in the Oracle GoldenGate reference documentation.

OGG-01158: Timestamp out of range: {0,number,0}

Cause: There was an internal error converting a timestamp value.

Action: Contact Oracle Support.

OGG-01159: Value ({0}) exceeds minimum value of column.

Cause: A numeric conversion failed because the resulting negative value cannot be represented in the space provided.

Action: Correct the specified value.

OGG-01160: Value ({0}) exceeds maximum value of column.

Cause: A numeric conversion failed because the resulting positive value cannot be represented in the space provided.

Action: Correct the specified value.

OGG-01161: Bad column index ({2,number,0}) specified for table {0}, max columns = {1,number,0}.

Cause: Oracle GoldenGate encountered a reference to a column ordinal that is not within an expected range.

Action: Verify that the definitions for the specified table are correct, and verify the correctness of the MAP statement for the specified table.

OGG-01162: Total data length ({2,number,0}) specified for table {0} exceeds record length ({1,number,0}).

Cause: There was an internal error converting trail file data. A buffer overflow was detected.

Action: Contact Oracle Support.

OGG-01163: Bad column length ({3,number,0}) specified for column {1} in table {0}, maximum allowable length is {2,number,0}.

Cause: There was an internal error converting trail file data. A buffer overflow was detected.

Action: Contact Oracle Support.

OGG-01164: Column index ({1,number,0}) out of sequence for table {0}, last column index = {2,number,0}.

Cause: There was an internal error converting trail file data. The columns are out of sequence.

Action: Contact Oracle Support.

OGG-01165: Record length exceeds maximum record length permitted

Cause: An internal error occurred while constructing a trail record. The constructed record exceeds the maximum allowable record length.

Action: Contact Oracle Support.

OGG-01166: Records larger than 32KB are not supported when using ETOLDFORMAT. Current record is {0,number,0} bytes.

Cause: The Extract parameter file contains the ETOLDFORMAT parameter. When this parameter is used, the trail file does not support records that are larger than 32KB.

Action: To continue using the ETOLDFORMAT parameter, which should only be used if the target Replicat is older than Oracle GoldenGate version 6.0, remove tables that generate the larger record size. Otherwise, you can upgrade Replicat so that ETOLDFORMAT is not needed.

OGG-01167: Old format record headers are not supported in PASSTHRU mode

Cause: The primary Extract parameter file contains the ETOLDFORMAT parameter, but older trail header formats cannot be read by a pump Extract that is configured in PASSTHRU mode.

Action: If possible, remove PASSTHRU from the data pump. As an alternative, you can use ETOLDFORMAT in the data pump parameter file instead of the primary Extract parameter file. This will write the trail to the old format to support the Replicat version for which this conversion is necessary.

OGG-01168: Encountered an update for target table {0}, which has no unique key defined. KEYCOLS can be used to define a key. Use ALLOWNOOPUPDATES to process the update without applying it to the target database. Use APPLYNOOPUPDATES to force the update to be applied using all columns in both the SET and WHERE clause.

Cause: Replicat tried to apply a record by using a unique key for row selection, but a matching key does not exist in the target table.

Action: If the source and target tables do not have identical key columns, use an identical KEYCOLS clause in the source TABLE parameter and the target MAP parameter. For more information about KEYCOLS, see the Oracle GoldenGate reference documentation. To learn about ALLOWNOOPUPDATES and APPLYNOOPUPDATES, contact Oracle Support.

OGG-01169: Encountered an update where all key columns for target table {0} are not present

Cause: Replicat tried to apply a record by using a specific key from the source table, but some or all of the matching key columns do not exist in the target table.

Action: If the source and target tables do not have identical key columns, use an identical KEYCOLS clause in the source TABLE parameter and the target MAP parameter. For more information about KEYCOLS, see the Oracle GoldenGate reference documentation. To learn about options that cause Replicat to skip such operations, or turn them into inserts by using whatever data is available in the trail record, contact Oracle Support.

OGG-01170: Exceeded maximum discard records, abending

Cause: The maximum number of discard records that is specified with the MAXDISCARDRECS parameter was exceeded.

Action: You can use the PURGE option of the DISCARDFILE parameter to purge content when new content is written. As an alternative, you can specify a different discard file with the DISCARDFILE parameter, and then restart the process. This maintains the old discard file intact.

OGG-01171: Failed to process MBU record.

Cause: Extract could not link multi-block undo records.

Action: Make certain that supplemental logging is enabled. If the problem persists, remove the table from the Oracle GoldenGate configuration.

OGG-01172: Discard file ({0}) exceeded max bytes ({1,number,0})

Cause: The size of the discard file that is specified with the DISCARDFILE parameter exceeded the size that is allowed with the MAXBYTES option.

Action: See the Oracle GoldenGate reference documentation for DISCARDFILE for default, minimum, and maximum size values, and for purge options.

OGG-01173: Error mapping a number for column {0}, (input value [{1}])

Cause: The specified value could not be converted for a numeric column.

Action: Verify the MAP statement to make certain that the columns in the mapping are supported for conversion. For help, see the Oracle GoldenGate administration documentation.

OGG-01174: Unexpected non-numeric encountered for column {0}

Cause: The specified numeric column contains non-numeric data.

Action: Verify that the source and target tables that are specified for the comparison have the same schema.

OGG-01175: Cannot Column map from an Enscribe auditcomp record

Cause: Enscribe auditcomp records are not supported by Oracle GoldenGate for Windows and UNIX.

Action: Remove these record types from the Extract configuration on the NonStop system.

OGG-01176: Error converting data to ascii format

Cause: The data could not be converted to ASCII format.

Action: Exclude the table or column from the Oracle GoldenGate configuration.

OGG-01177: Old record version encountered in {0} at {1}

Cause: This message is deprecated.

Action: None

OGG-01178: New record version encountered (data may be missing) in {0} at {1}

Cause: This message is deprecated.

Action: None

OGG-01179: Mismatched record version/bad data in {0} at {1}

Cause: The trail contains an incomplete record. A previously active Extract group probably was dropped and recreated to link to the same trail name as before. The new Extract started to write to the beginning of the first file in the trail, which caused it to overlay new data over the data that was written by the old group. Because record lengths vary, the new data overwrote record headers, causing one or more incomplete records. Replicat expects a record to start with a header; otherwise it abends.

Action: Examine the parameter files to determine if the parameter file for one Extract group was copied as the basis for the second group, but trail names were not changed for the second group. If this is the case, the best solution is to start over due to lost or corrupted data. To do this, back up the old trail files, drop and recreate the Extract groups and trails, and create new Replicat groups. Then, resynchronize the data. Save any debug509.txt files that are generated in case you need to open a support case. For Oracle GoldenGate versions 10.0 and later, there is a RECOVERYOPTIONS parameter that also might be influencing the way that a recovering Extract writes to the trail. See the Oracle GoldenGate reference documentatin for more information.

OGG-01180: LOB chunk too short ({0,number,0} bytes), minimum length: {1,number,0} bytes

Cause: The size of the LOB chunk in the trail file is too small. The trail file may be corrupted.

Action: Contact Oracle Support.

OGG-01181: LOB chunk header size must be {0,number,0} bytes

Cause: The size of the LOB chunk in the trail file is invalid. The trail file may be corrupted.

Action: Contact Oracle Support.

OGG-01182: Cannot retrieve io_type property from the record header in extract file {0}, rba {1,number,0}

Cause: The trail record header does not contain the I/O type. The trail file may be corrupted.

Action: Contact Oracle Support.

OGG-01183: Total length of record is {1,number,0}, maximum length allowed is {0,number,0}

Cause: The length of the trail record is too long. The trail file may be corrupted.

Action: Contact Oracle Support.

OGG-01184: Expected {3,number,0} bytes, but got {4,number,0} bytes, in trail {0}, seqno {1,number,0}, reading record trailer token at RBA {2,number,0}

Cause: The actual length of the trail record is different from the length field.

Action: Contact Oracle Support. The trail file may be corrupted.

OGG-01185: Bad trailer token in trail {0}, seqno {1,number,0}, at RBA {2,number,0}

Cause: A bad trail token was found. The trail file may be corrupted.

Action: Contact Oracle Support.

OGG-01186: Indicated beginning of record occurs before beginning of file after reading record trailer token at RBA {2,number,0} in trail {0}, seqno {1,number,0}

Cause: The trail file contains an invalid record position. The trail file may be corrupted.

Action: Contact Oracle Support.

OGG-01187: Duplicate entry encountered for {0}, Reloading definition...

Cause: A duplicate entry was found in the definitions file.

Action: Edit the definitions file to remove the duplicate entry.

OGG-01188: Short redefine encountered in {0}, Continuing...

Cause: An Enscribe short redefine was found in the definitions file.

Action: Edit the definitions file to remove the short redefine entry.

OGG-01189: Sequence number ({0,number,0}) received : Expecting ({1,number,0})

Cause: The initial load Replicat encountered an unexpected sequence number. The trail file might be corrupted.

Action: Contact Oracle Support.

OGG-01190: Non-numeric data sequence number [{0}]

Cause: The initial load Replicat encountered a non-numeric sequence number field. The trail file might be corrupted.

Action: Contact Oracle Support.

OGG-01191: Bad/unrecognized block format converting timestamps

Cause: The initial load Replicat cannot convert commit timestamp data. The trial file might be corrupted.

Action: Contact Oracle Support.

OGG-01192: Trying to use RMTTASK on data types which may be written as LOB chunks (Table: '{0}')

Cause: The Oracle GoldenGate direct load method (performed as a remote-task) does not support tables that have columns that contain LOBs, LONGS, user-defined types (UDT), or any other large data type that is greater than 4k in size.

Action: Exclude these tables from the load.

OGG-01193: Remote tasks cannot be used when other targets files or trails are specified

Cause: The Extract parameter file specifies RMTTASK to configure a remote task for an Oracle GoldenGate direct load, but it is possible that an ADD command to add a trail or file was issued to link a trail or file with the remote-task Extract, or that a local or remote trail or file was specified in the remote-task Extract parameter file. Disk storage is not used for a remote task, and there can be only one target Replicat for the task. A remote task cannot be run from the same Extract that also writes to a trail.

Action: Remove the trail or file specification from the parameter file of the remote-task Extract, and/or delete the trail that is linked with that Extract. Also make certain that the remote-task Replicat was added as a SPECIALRUN, and that its parameter file does not contain any trail or file specifications. To configure an Oracle GoldenGate direct load, see the Oracle GoldenGate administration documentation.

OGG-01194: EXTRACT task {0} abended : {1}

Cause: The initial load Extract task abended due to the specified error.

Action: Refer to the associated error message for the cause and action to take.

OGG-01195: Invalid response code received <0x{0} {1}>

Cause: The initial load Extract received an invalid TCP/IP response code.

Action: Make certain that the network connections are open and working. If this problem persists, contact Oracle Support.

OGG-01196: Did not recognize command <0x{0}>

Cause: The initial load Extract received an unrecognized TCP/IP command.

Action: Make certain that the network connections are open and working. If this problem persists, contact Oracle Support.

OGG-01197: Did not recognize command <0x{0} {1}>

Cause: The initial load Extract received an unrecognized TCP/IP command.

Action: Make certain that the network connections are open and working. If this problem persists, contact Oracle Support.

OGG-01198: Unknown data type received <0x{0} {1}>

Cause: The initial load Extract received an unrecognized data type.

Action: Make certain that the network connections are open and working. If this problem persists, contact Oracle Support.

OGG-01199: REPLICAT (initial data load task) stopped by EXTRACT

Cause: Extract stopped the initial-load Replicat after the load completed successfully. Informational only.

Action: None

OGG-01201: Error reported by MGR : {0}

Cause: The specified error was returned by Manager.

Action: Resolve the problem based on the reported error message.

OGG-01202: TCP/IP link with manager was unexpectedly terminated

Cause: The connection that Extract had with the remote Manager terminated.

Action: Verify that the remote host and Manager are still running. Use network diagnostic tools to resolve the error if it is network related, or consult the network administrator.

OGG-01203: EXTRACT abending

Cause: The initial load Replicat failed.

Action: Check the process report file for related errors, and take action based on that error.

OGG-01204: Command sent was not recognised by receiving process

Cause: The initial load Replicat did not recognize a command that was sent to it. There could be a TCP/IP network problem.

Action: Check the Replicat report file for related error messages, and take action based on them.

OGG-01205: The transaction to be deleted is not the current transaction on the list.

Current: 0x{0}, Given: 0x{1}

Cause: The transaction to be deleted is not the current one.

Action: Contact Oracle Support.

OGG-01206: Error [A fatal error was previously returned by FMLARGEROW, check error log and report file for details]

Cause: This message is deprecated.

Action: None

OGG-01207: The length given for the unique row identifier required for LOBROW is zero

Cause: The length of the LOB that is being processed is zero.

Action: Contact Oracle Support.

OGG-01208: The {0} function failed with return code {1,number,0}: {2}

Cause: This is a generic message about file memory.

Action: Check for lower-level error messages, and then try to resolve the problem based on those messages. For example, they may report a disk problem. If you cannot determine or resolve the problem, contact Oracle Support.

OGG-01209: Error [A block with a length of zero has been added for column index ({0,number,0}) without indicating that this is the last block in the LOB being added]

Cause: The block that was being added to column data has a zero length, and this is not the last block to be added.

Action: Contact Oracle Support.

OGG-01210: Error [Column index ({0,number,0}) does not have an entry in the column mapping for the LOB map entry]

Cause: While trying to add a block to column data, the process determined that the specified column is not mapped.

Action: Contact Oracle Support.

OGG-01211: Invalid LOB row to put chunk into

Cause: An internal error occurred while processing a LOB row.

Action: Contact Oracle Support.

OGG-01212: Programming error - LOB chunk size ({0,number,0}) exceeds maximum allowed ({1,number,0})

Cause: The size of the LOB chunk exceeds the maximum allowed limit.

Action: Contact Oracle Support.

OGG-01213: Unexpected error allocating LOB column memory structure

Cause: While storing a LOB chunk in memory, the process detected that the transaction information is missing.

Action: Contact Oracle Support.

OGG-01214: oldest uncommitted transaction has no tran_hdr data

Cause: The transaction does not contain a header.

Action: Contact Oracle Support.

OGG-01216: Cannot allocate more memory for a new transaction without violating memory settings (INITTRANSRAM = {0,number,0} bytes)

Cause: An internal memory allocation error occurred while initializing the Cache Object Manager.

Action: Contact Oracle Support.

OGG-01217: TCP/IP process name exceeds maximum length allowed ({0})

Cause: This message is not used by Oracle GoldenGate for Windows and UNIX.

Action: Contact Oracle Support if you receive this message on Windows, Linux, or UNIX.

OGG-01218: Error in {2}: {0,number,0} ({1})

Cause: A TCP/IP system call failed.

Action: Check for a duplicate process that is running, such as another Manager. Make certain that the remote process is still running. Check for any firewalls that forbid the connection, such as blocking certain ports or processes.

OGG-01219: TCP/IP message header is not numeric ({0})

Cause: This message is deprecated.

Action: None

OGG-01220: Could not establish host TCP/IP address

Cause: The RMTHOST parameter specifies a host name, and Oracle GoldenGate was unable to resolve that host name to an IP address.

Action: Consult your network administrator to make certain that the remote host is listed correctly in the domain name server.

OGG-01221: Connect failed to {0}:{1,number,0}, error {2,number,0}:{3}

Cause: The process attempted to connect to the specified IP address and port number, but failed with the TCP error that is shown. Typical connection problems are that the target Manager or Collector process is not running, or that Extract is pointing to the wrong IP address or Manager port number.

Action: Verify that the Manager port in the target Manager parameter file is the same as that in the RMTHOST parameter in the source Extract parameter file, and verify the IP address in RMTHOST. Connection errors also can indicate Collector security violations, a full file system, or errors relating to the system or to the Oracle GoldenGate configuration. If the error condition does not resolve itself in a reasonable amount of time (depending on the error type) consult the network administrator.

OGG-01222: Connect failed to {0}:{1,number,0}, error {2,number,0}:{3} - retries exceeded

Cause: The process failed to establish a TCP/IP link and retried the link for the maximum number of times allowed by the system or the tcperrs file.

Action: Make certain that the remote process is still running. Check for any firewalls that forbid the connection, such as blocking certain ports or processes.

OGG-01223: {0}

Cause: A TCP/IP error occurred. The process will retry based on the tcperrs file setting for retries.

Action: Make certain that the remote process is still running. Check for any firewalls that forbid the connection, such as blocking certain ports or processes. Make certain that the RMTHOST parameter is configured correctly. Consult your network administrator if you cannot resolve the problem, before contacting Oracle Support, to rule out any other network issues.

OGG-01224: {0}

Cause: A TCP/IP error occurred. The process will retry based on the tcperrs file setting for retries.

Action: Make certain that the remote process is still running. Check for any firewalls that forbid the connection, such as blocking certain ports or processes. Make certain that the RMTHOST parameter is configured correctly. Consult your network administrator if you cannot resolve the problem, before contacting Oracle Support, to rule out any other network issues.

OGG-01226: Socket buffer size set to {0,number,0} (flush size {1,number,0})

Cause: The TCP socket buffer size is set to the specified size, which is either the default size or the size specified with the TCPBUFSIZE setting in the RMTHOST or RMTHOSTOPTIONS parameter. The buffer that collects data that is ready to be sent across the network is set to the specified size, which is either the default size or the size specified with the TCPFLUSHBYTES option. Informational only.

Action: None

OGG-01227: Waiting for connection on port {0,number,0} ...

Cause: The process is waiting to connect to the specified listening port. Informational only.

Action: None

OGG-01228: Timeout in {0,number,0} seconds

Cause: The process connection will timeout in the specified time frame.

Action: None

OGG-01229: Connected to {0}:{1,number,0}

Cause: Informational message showing the host name and port number that the process is connected to.

Action: None

OGG-01230: Recovered from TCP error, host {0}, port {1,number,0}

Cause: Oracle GoldenGate recovered from a TCP error. Informational only.

Action: None

OGG-01231: Remote host TCP params error: {0}

Cause: A TCP/IP error occurred. The process will retry based on the tcperrs file setting for retries.

Action: Make certain that the remote process is still running. Check for any firewalls that forbid the connection, such as blocking certain ports or processes. Make certain that the RMTHOST parameter is configured correctly. Consult your network administrator if you cannot resolve the problem, before contacting Oracle Support, to rule out any other network issues.

OGG-01232: Receive TCP params error: {0}

Cause: An error in the TCP/IP layer prevented the process from receiving a full message, probably because of a network error. This message is generated when all retries that are permitted by the tcperrs file fail.

Action: Make certain that the sending process is still running, and that the network is still available. If you or the network administrator cannot resolve the problem, contact Oracle Support.

OGG-01233: Send TCP params error: {0}

Cause: An error in the TCP/IP layer prevented the process from sending a full message, probably because of a network error. This message is generated when all retries that are permitted by the tcperrs file fail.

Action: Make certain that the receiving process is still running, and that the network is still available. If you or the network administrator cannot resolve the problem, contact Oracle Support.

OGG-01234: Command sent was not recognised by receiving process

Cause: The command received from the TCP/IP packet is not recognizable. The TCP packet itself is correct, but the enclosed message is unrecognizable.

Action: Make certain that the Oracle GoldenGate versions on the source and target are the same. If the problem persists, contact Oracle Support.

OGG-01235: Command not allowed by receiving manager process

Cause: A TCP command was not permitted by the receiving Manager process.

Action: Contact Oracle Support.

OGG-01236: Trace file {0} opened

Cause: The specified trace file was opened by the process. Informational only.

Action: None

OGG-01237: Trace file {0} closed

Cause: The specified trace file was closed by the process. Informational only.

Action: None

OGG-01239: {0}

Cause: There was an internal error parsing the binary Activity Logging file.

Action: Verify that the target file was generated by the Activity Logging subsystem and contact Product Development for additional assistance.

OGG-01242: Invalid key field: {0}

Cause: The column that is specified in KEYCOLS is not specified in the COBOLDEFSFILE.

Action: Correct the KEYCOLS specification to be a valid column.

OGG-01243: No key fields specified

Cause: This message is deprecated.

Action: None

OGG-01244: {0}

Cause: This is a generic message for an error that occurred while parsing the COBOLDEFSFILE.

Action: Attempt to correct the problem based on the error that is returned. If it persists, contact Oracle Support.

OGG-01245: Missing source file DEFINITION for target {0}

Cause: The DEF parameter is missing the record name detail.

Action: Add the record name to be used in the DEF file output.

OGG-01246: DEFINITION {0} was not defined

Cause: The FILE input record was not found in the COBOLDEFSFILE.

Action: Correct the FILE entry to match the source DDL record name.

OGG-01247: Error processing {0} params: {1}

Cause: An invalid EXPANDDL option was used in the parameter file.

Action: For valid EXPANDDL options, see the Oracle GoldenGate reference documentation.

OGG-01248: Could not retrieve definition for table {0}

Cause: The table was not found in the database.

Action: Add the table to the database or remove it from the DDLGEN configuration.

OGG-01249: Invalid template file, missing one or more required sections

Cause: The template file is missing an expected section.

Action: Get or create a valid copy of the template (TMPL) file.

OGG-01250: Invalid line (no section yet designated): {0}

Cause: The template file is missing an expected section.

Action: Get or create a valid copy of the template (TMPL) file.

OGG-01251: Invalid param in template: {0}

Cause: There is an invalid parameter in the template file.

Action: Get or create a valid copy of the template (TMPL) file.

OGG-01252: Invalid column name mapping line: {0}

Cause: The template file is missing the precision or scale for the data type.

Action: Add the precision and scale to the template (TMPL) file.

OGG-01253: Invalid column type mapping line: {0}

Cause: The template file is missing the precision or scale for the data type.

Action: Add the precision and scale to the template (TMPL) file.

OGG-01254: Unable to replace '*' with '' in "{0}"

Cause: This message is deprecated.

Action: None

OGG-01255: Missing entry for data type {0}

Cause: The template file does not contain the source column type to map to a target column type.

Action: Add the missing type to the template (TMPL) file.

OGG-01256: {1}: FM_cache_pool_init: {0}

Cause: The process failed to create a memory pool to store the captured transactional data.

Action: Make certain the system allocated enough resources to create the memory pool.

OGG-01257: File cache directory: {0}, does not exist or is write protected.

Cause: The paging directory that is specified with the CACHEDIRECTORY option of the CACHEMGR parameter, or the default dirtmp directory in the Oracle GoldenGate installation directory, is write protected or cannot be found.

Action: If the directory exists, assign Oracle GoldenGate full control of that directory. If the directory does not exist, create it or specify an existing directory for CACHEDIRECTORY.

OGG-01258: ERROR: INVALID CACHE MEMORY VALUES

Cause: The CACHESIZE, CACHEBUFFERSIZE, or CACHEPAGEOUTSIZE specifications of the CACHEMGR parameter contain invalid value specifications. See the Oracle GoldenGate reference documentation for correct value ranges and syntax.

Action: None

OGG-01259: Duplicate directory: {1}, for VM parameter: {0}.

Cause: A CACHEDIRECTORY option of the CACHEMGR parameter contains duplicate directory entries, or there are duplicate CACHEDIRECTORY entries that specify the same directory.

Action: Correct the syntax and then restart the process. Only one directory can be specified per CACHEDIRECTORY entry. For syntax and usage of CACHEMGR, see the Oracle GoldenGate reference documentation.

OGG-01262: The call to the {0}() function from line {2,number,0} in {3}() failed with reason '{1}'

Cause: An internal error occurred. Usually this message is logged along with other messages that provide more specific information. In some cases, the message text will indicate a cause and possible action.

Action: If you cannot resolve the problem based on the related messages, contact Oracle Support.

OGG-01263: The call to the {0}() function from line {1,number,0} in {2}() returned an unexpected value

Cause: There is a problem with the function that was called. Usually this message is preceded by other messages that provide more specific information.

Action: If the related messages do not help you resolve the problem, contact Oracle Support.

OGG-01264: The call to the {0}() function from line {1,number,0} in {2}() returned an unexpected value

Cause: There is a problem with the function that was called. Usually this message is preceded by other messages that provide more specific information.

Action: If the related messages do not help you resolve the problem, contact Oracle Support.

OGG-01266: {0}

Cause: The cache object manager (COM) returned an internal error. Usually this message is preceded by other messages that provide more specific information.

Action: If the related messages do not help you resolve the problem, contact Oracle Support.

OGG-01268: {2}: exceeded maximum allocation attempts ({0,number,0}): {1}

Cause: The Oracle GoldenGate cache manager failed to allocate virtual memory for transaction data after the maximum permissible number of retries. There is not sufficient free virtual memory, based on the implicit or explicit CACHESIZE setting of the CACHEMGR parameter, to satisfy new memory requests. Data will be paged to disk, if eligible. For more information, see the CACHEMGR parameter in the Oracle GoldenGate reference documentation.

Action: None

OGG-01269: The call to the {0}() function for address 0x{1}, size 0x{2} from line {3,number,0} in {4}() returned an unexpected value

Cause: An attempt to unmap virtual memory failed.

Action: Examine any preceding error messages for a possible cause and resolution; otherwise, contact Oracle Support.

OGG-01270: {1}: Bad Parameter: {0}

Cause: The CACHEMGR parameter contains invalid syntax, or is not supported for the database type.

Action: Check the CACHEMGR reference documentation to verify that the database is supported. If true, then correct the syntax and then restart the process.

OGG-01271: {1}: Bad Parameter Argument: {0}

Cause: The CACHEMGR parameter contains invalid syntax.

Action: Correct the syntax and then restart the process. For syntax and usage of CACHEMGR, see the Oracle GoldenGate reference documentation.

OGG-01273: {1}: INVALID ARGUMENT SYNTAX: {0}

Cause: The CACHEMGR parameter contains invalid syntax.

Action: Correct the syntax and then restart the process. For syntax and usage of CACHEMGR, see the Oracle GoldenGate reference documentation.

OGG-01274: {1}: Duplicate Argument: {0}

Cause: The CACHEMGR parameter contains duplicate syntax.

Action: Correct the syntax and then restart the process. For syntax and usage of CACHEMGR, see the Oracle GoldenGate reference documentation.

OGG-01275: EXCEEDED ARGUMENT COUNT FOR: {0} max allowed: {1,number,0}

Cause: There are too many arguments in the CACHEMGR parameter, such as: CACHESIZE 16G 64G, when only one size should be specified.

Action: Fix the parameter, and then restart the process.

OGG-01276: {1}: BAD DIRECTORY PARAMETER: {0}

Cause: The CACHEMGR parameter contains a CACHEDIRECTORY option that has invalid syntax.

Action: Specify a directory path and a maximum directory size for each CACHEDIRECTORY entry, and separate each CACHEDIRECTORY entry with a comma, as in: CACHEDIRECTORY /ogg1/temp 2GB, CACHEDIRECTORY /ogg2/temp 2GB

OGG-01277: {2}: INVALID DIRECTORY SIZE SPECIFICATION: {1} ({0})

Cause: The directory size for the CACHEDIRECTORY option of the CACHEMGR parameter is incorrect.

Action: Specify a value that is between the maximum size imposed by the file system and the minimum size of 2 GB.

OGG-01278: {2}: cm_memdir_add: {0} size: {1}

Cause: The disk space that is allocated to the CACHEMGR paging directories and specified with the CACHEDIRECTORY option was exceeded.

Action: Add disk space if needed, and change the CACHEDIRECTORY option to allocate more space to the cache directories.

OGG-01279: {1}: max # of directories allocated: {0,number,0}

Cause: The maximum number of paging directories that are specified for the CACHEDIRECTORY option of the CACHEMGR parameter was exceeded.

Action: Reduce the number of directories.

OGG-01280: {1}: Duplicate CACHEDIRECTORY: {0}

Cause: The CACHEDIRECTORY option of the CACHEMGR parameter contains one or more duplicate entries.

Action: Remove the duplicate entries.

OGG-01281: {0}

Cause: This is a generic Event Marker Infrastructure informational message. It may be useful for operational, performance, or diagnostic purposes.

Action: None

OGG-01282: {0}

Cause: This is a generic Event Marker Infrastructure warning message that may indicate a potential problem. The data provided may be useful for operational, performance, or diagnostic purposes.

Action: Take action based on the message that is returned. If you cannot resolve the problem, contact Oracle Support.

OGG-01283: Stopping process due to {0} event {1}{2} {3}

Cause: The parameter file contains the EVENTACTIONS parameter with the STOP option. The process stopped gracefully after completing open transactions and any grouped transactions. Informational only.

Action: None

OGG-01284: Stopping process due to {0} event {1}{2}. STOP request will be executed immediately (current transaction aborted)

Cause: The parameter file contains the EVENTACTIONS parameter with the STOP option. The process stopped immediately and aborted the current transaction, because it was still open when the event record was processed. Informational only.

Action: None

OGG-01285: Processed {0} event {1}{2}

Cause: The parameter file contains the EVENTACTIONS parameter with the specified option, and the action was performed successfully. Informational only.

Action: None

OGG-01286: Executing shell command '{0}' due to SHELL event {1}{2}

Cause: The parameter file contains EVENTACTIONS with the SHELL option, and the shell command is being executed because the event was triggered. Informational only.

Action: None

OGG-01287: Successfully executed shell command '{0}'

Cause: The parameter file contains EVENTACTIONS with the SHELL option, and the shell command succeeded when the event was triggered. In the UNIX shell language, a zero exit status equals success. Informational only.

Action: None

OGG-01288: Failed to execute shell command '{0}', exit status = {1,number,0}

Cause: The parameter file contains EVENTACTIONS with the SHELL option, but the shell command failed when the event was triggered. In the UNIX shell language, a non-zero exit status equals failure.

Action: Check the syntax of the command that is specified in the EVENTACTIONS parameter, and fix it if it is wrong. If the syntax is correct, find out if there is a problem with the file system or operating system that prevents the command from succeeding.

OGG-01289: Aborting process due to {0} event {1}{2}

Cause: EVENTACTIONS with the ABORT option is specified in the parameter file, and the event record triggered the ABORT. If DISCARD was also specified, the event record is in the discard file. This is informational to alert you that the event occurred.

Action: None, unless manual procedures are required outside Oracle GoldenGate as a result of the event. The process will undergo recovery on startup.

OGG-01290: Event action ABORT cannot be combined with any of the following actions: STOP, FORCESTOP, IGNORE, LOG, ROLLOVER, TRACE, CHECKPOINT AFTER, CHECKPOINT BOTH or SYNC

Cause: The EVENTACTIONS parameter includes an ABORT option and at least one of the other specified options. These options are mutually exclusive.

Action: Remove mutually exclusive options. For more information, see TABLE and MAP in the Oracle GoldenGate reference documentation.

OGG-01291: Event action FORCESTOP cannot be combined with STOP, CHECKPOINT AFTER, CHECKPOINT BOTH, or SYNC

Cause: The EVENTACTIONS parameter includes a FORCESTOP option and at least one of the other specified options. These options are mutually exclusive.

Action: Remove mutually exclusive options. For more information, see TABLE and MAP in the Oracle GoldenGate reference documentation.

OGG-01292: Event action IGNORE cannot be combined with DISCARD

Cause: The EVENTACTIONS parameter includes an IGNORE option and a DISCARD option. These options are mutually exclusive.

Action: Remove one of the options. For more information, see TABLE and MAP in the Oracle GoldenGate reference documentation.

OGG-01293: TABLE specification without TARGET must include either IGNORE or DISCARD event action

Cause: A TABLE specification does not declare a TARGET. Without a TARGET clause, the EVENTACTIONS specification requires the action to be either IGNORE or DISCARD.

Action: Add a TARGET clause to the TABLE statement or use IGNORE or DISCARD for the EVENTACTIONS clause.

OGG-01294: Cannot process {0} event {1}{2} because the event record is not the first record in the transaction

Cause: EVENTACTIONS is being used in the parameter file. Certain EVENTACTIONS options require the event record to be the first record in a transaction. The event record is a record in the TABLE or MAP statement, typically specified with filtering criteria, that triggers the specified EVENTACTIONS action.

Action: Specify an event record that is the beginning of a transaction. For more information, see TABLE and MAP in the Oracle GoldenGate reference documentation.

OGG-01296: Error mapping from {0} to {1}

Cause: The mapping of the specified source and target tables failed.

Action: Examine the accompanying messages that provide details about the mapping failure, and resolve the problem based on those messages. If the problem persists, contact Oracle Support.

OGG-01297: Column function diagnostic message: could not find resource {0}

Cause: The GETVAL column-conversion function contains an invalid specification.

Action: Correct the syntax. Make certain the procedure or query name is correct and that the parameter portion contains a valid parameter name or return value. For help, see the Oracle GoldenGate reference documentation.

OGG-01298: Column function diagnostic message: could not find column {0}

Cause: The specified column could not be found when the column-conversion function executed.

Action: Specify the correct column name.

OGG-01299: Column function diagnostic message: DAT_{0} Bad value for century {1,number,0}

Cause: Column conversion failed. Century data from the source database or trail file may be corrupted, or a century value was specified for non-century data.

Action: Make certain that the source column contains valid century data. If it does not contain century data, remove the century specification from the column-conversion function and specify an appropriate data type.

OGG-01300: Column function diagnostic message: DAT_{0} Bad value for year {1,number,0}

Cause: Column conversion failed. Year data from the source database or trail file may be corrupted, or a year value was specified for non-year data.

Action: Make certain that the source column contains valid year data. If it does not contain year data, remove the year specification from the column-conversion function and specify an appropriate data type.

OGG-01301: Column function diagnostic message: DAT_{0} Bad value for month {1,number,0}

Cause: Column conversion failed. Month data from the source database or trail file may be corrupted, or a month value was specified for non-month data.

Action: Make certain that the source column contains valid month data. If it does not contain month data, remove the month specification from the column-conversion function and specify an appropriate data type.

OGG-01302: Column function diagnostic message: DAT_{0} Bad value for day {1,number,0}

Cause: Column conversion failed. Day data from the source database or trail file may be corrupted, or a day value was specified for non-day data.

Action: Make certain that the source column contains valid day data. If it does not contain day data, remove the day specification from the column-conversion function and specify an appropriate data type.

OGG-01303: Column function diagnostic message: DAT_{0} Bad value for day of year {1,number,0}

Cause: Column conversion failed. Day-of-year data from the source database or trail file may be corrupted, or a day-of-year value was specified for data that is not day-of-year.

Action: Make certain that the source column contains valid day-of-year data. If it does not contain day-of-year data, remove the day-of-year specification from the column-conversion function and specify an appropriate data type.

OGG-01304: Column function diagnostic message: DAT_{0} Bad value for day of week {1,number,0}

Cause: Column conversion failed. Day-of-week data from the source database or trail file may be corrupted, or a day-of-week value was specified for data that is not day-of-week.

Action: Make certain that the source column contains valid day-of-week data. If it does not contain day-of-week data, remove the day-of-week specification from the column-conversion function and specify an appropriate data type.

OGG-01305: Column function diagnostic message: DAT_{0} Bad value for day of paramType, week

Cause: Column conversion failed on a bad value for a day-of- data type (such as day-of-year). The data in the source column or trail file may be corrupted, or a day-of- value was specified for data that is not day-of- data.

Action: Make certain that the source column is supposed to contain this kind of data. If not, remove the day-of- specification from the column-conversion function and specify an appropriate data type.

OGG-01306: Column function diagnostic message: DAT_{0} Bad value for hour {1,number,0}

Cause: Column conversion failed. Hour data from the source database or trail file may be corrupted, or an hour value was specified for non-hour data.

Action: Make certain that the source column contains valid hour data. If it does not contain hour data, remove the hour specification from the column-conversion function and specify an appropriate data type.

OGG-01307: Column function diagnostic message: DAT_{0} Bad value for minute {1,number,0}

Cause: Column conversion failed. Minute data from the source database or trail file may be corrupted, or a minute value was specified for non-minute data.

Action: Make certain that the source column contains valid minute data. If it does not contain minute data, remove the minute specification from the column-conversion function and specify an appropriate data type.

OGG-01308: Column function diagnostic message: DAT_{0} Bad value for second {1,number,0}

Cause: Column conversion failed. Second data from the source database or trail file may be corrupted, or a second value was specified for non-second data.

Action: Make certain that the source column contains valid second data. If it does not contain second data, remove the second specification from the column-conversion function and specify an appropriate data type.

OGG-01309: Column function diagnostic message: DAT_{0} Bad value for julian day

Cause: Column conversion failed on a bad value for a Julian day data type. The data in the source column or trail file may be corrupted, or a Julian day value was specified for data that is not Julian day.

Action: Make certain that the source column is supposed to contain Julian day data. If not, remove the Julian day specification from the column-conversion function and specify an appropriate data type.

OGG-01310: Column function diagnostic message: DAT_{0} Bad value for julian time

Cause: Column conversion failed on a bad value for a Julian time data type. The data in the source column or trail file may be corrupted, or a Julian time value was specified for data that is not Julian time data.

Action: Make certain that the source column is supposed to contain Julian time data. If not, remove the Julian time specification from the column-conversion function and specify an appropriate data type.

OGG-01311: Column function diagnostic message: DAT_{0} Bad value for C date

Cause: Column conversion failed on a bad value for a C date. The data in the source column or trail file may be corrupted, or a C date value was specified for data that is not a C date.

Action: Make certain that the source column is supposed to contain C date data. If not, remove the C date specification from the column-conversion function and specify an appropriate data type.

OGG-01312: Column function diagnostic message: DAT_{0} Bad value for TTS date

Cause: Column conversion failed on a bad value for a TTS date. The data in the source column or trail file may be corrupted, or a TTS date value was specified for data that is not a TTS date.

Action: Make certain that the source column is supposed to contain TTS date data. If not, remove the TTS date specification from the column-conversion function and specify an appropriate data type.

OGG-01313: Column function diagnostic message: DAT_{0} Bad value for stratus date

Cause: Column conversion failed on a bad value for a Stratus date. The data in the source column or trail file may be corrupted, or a Stratus date value was specified for data that is not a Stratus date.

Action: Make certain that the source column is supposed to contain a Stratus date. If not, remove the Stratus date specification from the column-conversion function and specify an appropriate data type.

OGG-01314: Column function diagnostic message: Output needs full year

Cause: The timestamp data in the column does not contain the full year, but a full year (CC and YY) is specified by the output date and time descriptor of the @DATE column-conversion function.

Action: Remove one or both of the CC and YY specifications, depending on what the column contains.

OGG-01315: Column function diagnostic message: Output needs year

Cause: The timestamp data in the column does not contain a year, but a year (YY) is specified by the output date and time descriptor of the @DATE column-conversion function.

Action: Remove the YY specification.

OGG-01316: Column function diagnostic message: Output needs month

Cause: The timestamp data in the column does not contain a month, but a month (MMM or MM) is specified by the output date and time descriptor of the @DATE column-conversion function.

Action: Remove the month specification.

OGG-01317: Column function diagnostic message: Output needs day

Cause: The timestamp data in the column does not contain a day, but a day (DD) is specified by the output date and time descriptor of the @DATE column-conversion function.

Action: Remove the day specification.

OGG-01318: Column function diagnostic message: Output needs day or DOY

Cause: The timestamp data in the column does not contain a day-of-year, but a day-of-year (DOY) is specified by the output date and time descriptor of the @DATE column-conversion function.

Action: Remove the day-of-year specification.

OGG-01319: Column function diagnostic message: Output needs day or DOW

Cause: The timestamp data in the column does not contain a day-of-week, but a day-of-week (DOW) is specified by the output date and time descriptor of the @DATE column-conversion function.

Action: Remove the day-of-week specification.

OGG-01320: Column function diagnostic message: Output needs hour

Cause: The timestamp data in the column does not contain an hour, but an hour (HH) is specified by the output date and time descriptor of the @DATE column-conversion function.

Action: Remove the hour specification.

OGG-01321: Column function diagnostic message: Output needs minute

Cause: The timestamp data in the column does not contain a minute, but a minute (MI) is specified by the output date and time descriptor of the @DATE column-conversion function.

Action: Remove the minute specification.

OGG-01322: Column function diagnostic message: Output needs second

Cause: The timestamp data in the column does not contain a second, but a second (SS) is specified by the output date and time descriptor of the @DATE column-conversion function.

Action: Remove the second specification.

OGG-01323: Column function diagnostic message: Output needs timestamp

Cause: The timestamp data in the column does not contain a year, month, or day, but these timestamp components are specified by the output date and time descriptor of the @DATE column-conversion function.

Action: Remove the erroneous specification, which can be one of the following: JTSGMT, JTSLCT, JTS, PHAMIS, STRATUS, CDATE, TTS.

OGG-01324: Column function diagnostic message: Output needs timestamp fraction

Cause: The timestamp data in the column does not contain a fraction, but a fraction (FFFFFF) is specified by the output date and time descriptor of the @DATE column-conversion function.

Action: Remove the fraction specification.

OGG-01325: Column function diagnostic message: Unknown output requirement

Cause: An invalid date and time format descriptor is specified by the @DATE column-conversion function.

Action: Specify a valid date and time format descriptor. For help with syntax and supported values, see the Oracle GoldenGate reference documentation.

OGG-01326: Column function diagnostic message: Start offset is greater than end offset

Cause: The begin position in the @STREXT function syntax is later in the string than the end position that is specified.

Action: Correct the begin and end positions in the syntax.

OGG-01327: Column function diagnostic message: Invalid range arguments, must be @RANGE(<this range>, <tot ranges> [, <column>...])

Cause: The syntax for @RANGE is incorrect.

Action: The syntax should be in the format shown in the error message, where the input is the number of the range partition, the total number of ranges, and the name of the column on which to base the range. See the Oracle GoldenGate reference documentation for more information.

OGG-01328: Column function diagnostic message: Could not find expected key column ({0})

Cause: The @RANGE function cannot create the ranges because a column on which to base the range is not defined.

Action: Add a primary key to the table definition, or specify a column on which to base the range allocation to the third position of the syntax as follows: @RANGE (range_number , total_number_of_ranges , base_column). See the Oracle GoldenGate reference documentation for more information.

OGG-01329: Column function diagnostic message: No key columns for @RANGE clause

Cause: The @RANGE function cannot create the ranges because a column on which to base the range is not defined.

Action: Add a primary key to the table definition, or specify a column on which to base the range allocation to the third position of the syntax as follows: @RANGE (range_number , total_number_of_ranges , base_column). See the Oracle GoldenGate reference documentation for more information.

OGG-01331: File {0} does not have a valid Oracle GoldenGate signature.

Cause: The specified trail is not a valid Oracle GoldenGate trail.

Action: Contact Oracle Support.

OGG-01332: File {0}, with compatibility level {1,number,0}, is not compatible with the current software version's compatibility level of {2,number,0}. Modify the file writer's parameter file to generate the appropriate format using the FORMAT LEVEL {2,number,0} option.

Cause: The version of the trail file and the version of the process that reads it (Extract or Replicat) are not the same. The trail version must be the same as, or older than, that of the reader process. LEVEL is an internal option that specifies a compatibility level that is independent of the Oracle GoldenGate software version and only changes if new functionality was added to a version that affects the trail format. A value of 1 or greater specifies a format that is supported by Oracle GoldenGate versions 10.0 and later. A value of 0 specifies a format that is supported by Oracle GoldenGate versions prior to 10.0.

Action: Edit the parameter file to set the EXTFILE, EXTTRAIL, RMTFILE, or RMTTRAIL parameter to 0 to write a trail that is backward compatible with the reader process. Next, issue the ALTER EXTRACT command with the ETROLLOVER option in GGSCI. The rollover creates a new trail file in the specified format. Start Extract to begin writing to the new trail file. For more information, see the Oracle GoldenGate reference documentation for the trail or file parameters.

OGG-01334: Error mapping data from {0} to {1}.{2} in function {3}

Cause: The specified source table could not be mapped to the specified target table in the specified column-conversion function.

Action: Make certain that the mapping syntax is correct and that names are spelled correctly. For help, see the Oracle GoldenGate reference documentation.

OGG-01335: Error mapping data from {0} to {1}.{2} in function {3}

Cause: The specified source table could not be mapped to the specified target table in the specified column-conversion function.

Action: Make certain that the mapping syntax is correct and that names are spelled correctly. For help, see the Oracle GoldenGate reference documentation.

OGG-01336: Switching to next trail file {0} at {1}{3} with current RBA {2,number,0}

Cause: The process is rolling over the trail to the next file in the sequence. Informational only.

Action: None

OGG-01337: Trail file {0}, IO error {1,number,0} ({2})

Cause: The process cannot open the trail file because there was an operating system error.

Action: Resolve the operating system error. Consult the system documentation or the system administrator if you cannot determine the cause of the problem.

OGG-01338: {1}: The {0} service was started successfully.

Cause: The specified service started successfully. Informational only.

Action: None

OGG-01339: {1}: Failed to start the {0} service, error code {2,number,0} ({3}).

Cause: Manager could not start the specified service.

Action: Make certain that Oracle GoldenGate is installed properly and that Manager has permission on the system to start the process. Make certain that the parameter file is in the right place and that database is running. Check the related message that is specified in this text for additional troubleshooting details.

OGG-01342: DDL found, operation [{0}], start {1} [{2}], DDL seqno [{3}]

Cause: A DDL operation with the specified identifier is being processed. Informational only.

Action: None

OGG-01343: Restart Timer failed. status = {0} waitState: {1,number,0}

Cause: A restart failed.

Action: Contact Oracle Support.

OGG-01344: Restart notification failure. status = {0}.

Cause: A restart notification failed.

Action: Contact Oracle Support.

OGG-01348: Invalid CHARSET and A2E character set configuration

Cause: The value specified for the CHARSET global option does not match the CHARSET value specified in the A2E parameter.

Action: Correct the A2E parameter or GLOBALS file so that the character sets match.

OGG-01349: Could not convert ASCII data to EBCDIC. Error occurred at or about byte {0} in the {1} byte string beginning: {2}

Cause: A conversion of character data from ASCII to EBCDIC failed.

Action: Verify that the column definitions are correct.

OGG-01350: Could not convert EBCDIC data to ASCII. Error occurred at or about byte {0} in the {1} byte string beginning: {2}

Cause: A conversion of character data from EBCDIC to ASCII failed.

Action: Verify that the column definitions are correct.

OGG-01351: Could not convert CHAR/VARCHAR to NCHAR/NVARCHAR

Cause: Invalid character data was found during mapping from a CHAR/VARCHAR column to a target NCHAR/NVARCHAR column.

Action: Fix the source column data, or use the REPLACEBADCHAR parameter in the Extract and Replicat parameter files.

OGG-01352: Could not convert NCHAR/NVARCHAR to CHAR/VARCHAR

Cause: Invalid character data was found during mapping from a NCHAR/NVARCHAR column to a target CHAR/VARCHAR column.

Action: Fix the source column data, or use the REPLACEBADCHAR parameter in the Extract and Replicat parameter files.

OGG-01353: Could not convert CLOB/TEXT to NCLOB/NTEXT

Cause: An error occurred while converting single-byte character data to multi-byte character data.

Action: Check the column mapping for incorrect specifications, especially if it contains textual LOB data, and determine whether the character sets involved are compatible.

OGG-01354: Could not convert NCLOB/NTEXT to CLOB/TEXT

Cause: An error occurred while converting multi-byte character data to single-byte character data.

Action: Check the column mapping for incorrect specifications, especially if it contains textual LOB data, and determine whether the character sets involved are compatible.

OGG-01355: Following CHAR/NCHAR conversion is being used

Cause: Oracle GoldenGate is converting character data. Informational only.

Action: None

OGG-01356: CHAR/VARCHAR: {0}

Cause: Character data is in the format of the specified character set. Informational only.

Action: None

OGG-01357: CHAR/VARCHAR: Default

Cause: Character data is in the format of the default character set. Informational only.

Action: None

OGG-01358: NCHAR/NVARCHAR: UTF-16/UTF-8

Cause: The multibyte data is in the format of UTF-16/UTF-8. Informational only.

Action: None

OGG-01359: The WILDCARDRESOLVE and (NO)DYNAMICRESOLUTION parameters are deprecated. Defaulting to WILDCARDRESOLVE {0}.

Cause: The WILDCARDRESOLVE parameter is deprecated and was specified.

Action: Remove the WILDCARDRESOLVE parameter. If immediate resolution is necessary for Replicat or data pump, specify ASSUMETARGETDEFS or SOURCEDEFS with the OVERRIDE option.

OGG-01364: No opening parenthesis was found for the {0} {1} parameter.

Cause: An opening parenthesis is missing from the beginning of the specified parameter option.

Action: Add the parenthesis. See the Oracle GoldenGate reference documentation for correct syntax. To test for correct syntax in a parameter file, add the CHECKPARAMS parameter to the first line of the parameter file, save the file, and then start the process. The process stops automatically after the test is finished. To determine if there were syntax errors, view the process report file. Correct the syntax errors in the parameter file. To test again, repeat these steps. Remove CHECKPARAMS when you are finished testing syntax.

OGG-01365: No closing parenthesis was found for the {0} {1} parameter.

Cause: A closing parenthesis is missing from the end of the specified parameter option.

Action: Add the parenthesis. See the Oracle GoldenGate reference documentation for correct syntax. To test for correct syntax in a parameter file, add the CHECKPARAMS parameter to the first line of the parameter file, save the file, and then start the process. The process stops automatically after the test is finished. To determine if there were syntax errors, view the process report file. Correct the syntax errors in the parameter file. To test again, repeat these steps. Remove CHECKPARAMS when you are finished testing syntax.

OGG-01366: Text was found before the opening parenthesis for the {0} {1} parameter.

Cause: There is a syntax error for the specified parameter option.

Action: Look for characters that precede the opening parenthesis without a space between them, and make certain that the characters that precede the opening parenthesis are also valid syntax. See the Oracle GoldenGate reference documentation for correct syntax. To test for correct syntax in a parameter file, add the CHECKPARAMS parameter to the first line of the parameter file, save the file, and then start the process. The process stops automatically after the test is finished. To determine if there were syntax errors, view the process report file. Correct the syntax errors in the parameter file. To test again, repeat these steps. Remove CHECKPARAMS when you are finished testing syntax.

OGG-01367: Length of CSN {0}, {1,number,0}, from input data source not equal to that of previous CSN, {2,number,0}

Cause: There is a possible memory corruption or invalid data in the trail.

Action: Contact Oracle Support.

OGG-01368: Could not truncate file "{0}" at RBA {1,number,0} (error {2,number,0}, {3})

Cause: The process could not truncate the trail during recovery.

Action: Check for a full disk, disk failure, network failure, or other system-related problem.

OGG-01369: DDL operation mapped to target database [{0}], new DDL operation [{1}]

Cause: Replicat successfully applied the DDL operation to the specified target. Informational only.

Action: None

OGG-01370: User requested START SKIPTRANSACTION. The current transaction will be skipped. Transaction ID {0}, position Seqno {1,number,0}, RBA {2,number,0}.

Cause: The START REPLICAT command was issued with the SKIPTRANSACTION option. Replicat will skip the specified transaction in the trail, which is the first one after its expected startup point. All operations from the first transaction are excluded. If the MAXTRANSOPS parameter is also being used for this Replicat, it is possible that the process will start to read the trail file from somewhere in the middle of a transaction. In that case, the remainder of the partial transaction is skipped, and Replicat resumes normal processing from the next begin-transaction record in the file.

Action: None

OGG-01371: No discard file specified. Records discarded due to SKIPTRANSACTION will not be logged.

Cause: The START REPLICAT command was issued with the SKIPTRANSACTION option, but because a discard file is not specified in the parameter file, the skipped operations cannot be persisted to a file.

Action: None, unless you want future SKIPTRANSACTION transactions to be logged. In that case, stop Replicat and specify a discard file with DISCARDFILE, then restart the process.

OGG-01372: User requested start at CSN {0}

Cause: A START REPLICAT command was issued with the ATCSN option to start processing beginning with the transaction that has the specified CSN (Commit Sequence Number). All transactions before this one are skipped.

Action: None

OGG-01373: User requested start after CSN {0}

Cause: A START REPLICAT command was issued with the AFTERCSN option to start processing at the transaction immediately after the one that has the specified SCN (Commit Sequence Number). All transactions in the trail up to, and including the one with the specified SCN, are skipped.

Action: None

OGG-01374: Transaction delivery commencing at position Seqno {0,number,0}, RBA {1,number,0}, Transaction ID {2}, CSN {3}, {4,number,0} transaction(s) skipped.

Cause: A START REPLICAT command was issued with the ATCSN or AFTERCSN option. Replicat is starting processing from the specified sequence number and RBA of the input trail, with the specified transaction in the trail. The number of transactions that were skipped is stated in the message. This message can also apply to START EXTRACT for Data Pump.

Action: None

OGG-01375: Trail format does not support starting at a specific CSN. File header not found.

Cause: A START REPLICAT command was issued with the ATCSN or the AFTERCSN option, but the format of the trail does not support these options. A trail file must have a version that is equal to, or lower than, that of the process that reads it, in this case Replicat. This indicates that the Oracle GoldenGate version of Replicat is older than the version of Extract.

Action: Upgrade the Replicat version to use these options.

OGG-01376: Trail format does not support starting at a specific CSN. CSN token not found at position Seqno {0,number,0}, RBA {1,number,0}.

Cause: A START REPLICAT command was issued with the ATCSN or AFTERCSN option, but the format of the trail does not support these options. A trail file must have a version that is equal to, or lower than, that of the process that reads it, in this case Replicat. This indicates that the Oracle GoldenGate version of Replicat is older than the version of Extract.

Action: Upgrade the Replicat version to use these options.

OGG-01377: CSN format supplied does not match the CSN format in the trail. CSN supplied {0}. Expecting {1} format CSN.

Cause: A START EXTRACT command was issued with the ATCSN or AFTERCSN option, but an invalid format was supplied for the CSN value. The CSN format that you supply must match the CSN format of the trail records, which is based on the CSN format of the source database.

Action: See the Oracle GoldenGate administration documentation for a list of CSN formats per database, and then re-issue the command with the correct CSN format.

OGG-01378: Unrecoverable DDL execution error encountered [{0}]

Cause: The process could not execute a DDL statement.

Action: If you cannot resolve the problem based on the error that is returned in the message, contact Oracle Support.

OGG-01379: Error {0,number,0} creating CSN instance. CSN {1}, DBID {2,number,0}.

Cause: The CSN could not be resolved from the trail record. The trail file may be corrupted because of a disk or network failure.

Action: Contact Oracle Support.

OGG-01380: Start parameters SKIPTRANSACTION, ATCSN, AFTERCSN and FORCECURRENTPOSITION are mutually exclusive. Only one may be specified.

Cause: Only one of the specified parameters can be used in the START REPLICAT command. Note that FORCECURRENTPOSITION is not currently a valid parameter and should not be used.

Action: Re-issue the command with only one of the options.

OGG-01381: The VAM compatibility level must be set via the TRANLOGOPTIONS VAMCOMPATIBILITY <level> parameter, where <level> is a number starting at 1

Cause: A new Oracle GoldenGate Extract has been paired with an older TAM module, but TRANLOGOPTIONS VAMCOMPATIBILITY is not set in the Extract parameter file to support backward compatibility.

Action: Add the TRANLOGOPTIONS parameter with the VAMCOMPATIBILITY option set to 1. As an alternative, you can set the VAM compatibility to 1 with VAMInitialize, and then you can omit TRANLOGOPTIONS with VAMCOMPATIBILITY. To avoid the need to set the VAM compatibility, upgrade the TAM module to that of the Extract version.

OGG-01382: The number of alternate online logs being retrieved exceeds the number returned by the GG_ATTR_SESS_NUM_ALT_ONLINE_LOGS session object attribute of {0,number,0}.

Cause: Too many alternate online logs are specified.

Action: Edit the Extract parameter file and remove some of the log specifications so that the value is within the specified range, and then restart Extract.

OGG-01383: The number of alternate log files must be retrieved via the GG_ATTR_SESS_NUM_ALT_ONLINE_LOGS session object attribute before attempting to retrieve the individual log files.

Cause: The VAM module tried to retrieve the alternate online log file names directly without initiating the required VAM API protocol. This is an internal programming error.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-01384: The maximum number of alternate online log file values allowed for the TRANLOGOPTIONS ALTONLINELOGS parameter is {0,number,0}.

Cause: Too many alternate online logs are specified.

Action: Edit the Extract parameter file and remove some of the log specifications so that the value is within the specified range, and then restart Extract.

OGG-01385: This command is not supported for VAM DDL implementation

Cause: The DDLDUMP command is not supported for the current database type.

Action: None

OGG-01386: Value for {0} must be between {1} and {2}.

Cause: The specified value is not within the range of valid values for the specified parameter.

Action: Edit the parameter file to specify a valid value, and then restart the process. See the Oracle GoldenGate reference documentation for usage guidelines, if needed.

OGG-01387: Table {0} has no valid key columns, added unconditional supplemental log group for all table columns.

Cause: Informational only. The table does not have a primary key or a unique key, and no KEYCOLS clause is defined for it. Oracle GoldenGate is using all of the columns as a key to ensure uniqueness, except for columns that cannot be used as part of a key. For column types that are excluded, see the Oracle GoldenGate installation documentation for your database type.

Action: None

OGG-01388: File header failed to construct tokens. File {0}, last offset {1,number,0}, data: {2}

Cause: The trail file header is corrupted.

Action: First, restart the process. If the problem still exists, contact Oracle Support.

OGG-01389: File header failed to parse tokens. File {0}, last offset {1,number,0}, data: {2}

Cause: There was an error while parsing the trail header.

Action: Contact Oracle Support.

OGG-01391: Trail file {0} has been previously recovered in overwrite mode, and the current checkpoint is not quiescent. To change to append-mode recovery, perform a quiet checkpoint and restart

Cause: Extract is configured to write to the trail in overwrite mode, and the last commit position was not found. The process will continue to try to recover.

Action: None, if overwrite mode is to be retained; however, further errors may occur. Switch to append mode, if possible, which provides a more reliable recovery history. To change to append mode, see the RECOVERYOPTIONS parameter in the Oracle GoldenGate reference documentation.

OGG-01392: No position tokens found in trail {0}, RBA {1,number,0}

Cause: The process could not find the last commit position in the trail.

Action: Contact Oracle Support.

OGG-01394: Using _ALLOWPKMISSINGROWCOLLISIONS may cause data corruption under certain conditions.

Cause: This parameter is being used with HANDLECOLLISIONS to skip key UPDATEs if the corresponding target row does not exist. This can compromise target data integrity and should not be done without guidance from an Oracle support analyst. _ALLOWPKMISSINGROWCOLLISIONS is an unpublished parameter and typically is only used with the guidance of Oracle technical-support personnel.

Action: None

OGG-01395: Using _ALLOWPKMISSINGROWCOLLISIONS may cause data corruption under certain conditions while mapping from {0} to {1}.

Cause: This parameter is being used with HANDLECOLLISIONS to skip key UPDATEs if the corresponding target row does not exist. This can compromise target data integrity and should not be done without guidance from an Oracle support analyst. _ALLOWPKMISSINGROWCOLLISIONS is an unpublished parameter and typically is only used with the guidance of Oracle technical-support personnel.

Action: None

OGG-01396: A complete after image is not available in {0} at rba {1,number,0} in file {2}, while inserting a row into {3} due to missing target row for a key update operation. NOCOMPRESSUPDATES or FETCHOPTIONS

FETCHPKUPDATECOLS may be specified in the EXTRACT parameter file to include a complete image for key update operations.

Cause: HANDLECOLLISIONS is enabled for Replicat. (For details, see the HANDLECOLLISIONS reference documentation.) This error indicates that a primary key was updated, but the record cannot be found on the target. Replicat attempted to populate the missing row, instead of performing the update, but it failed to do so because not all of the column values were available in the trail.

Action: Manually apply the row values to the target, and then skip the record that errored by restarting Replicat with the ATCSN, AFTERCSN, or SKIPTRANSACTION option. If primary keys will continue to be updated, you can stop Extract, and then add either the NOCOMPRESSUPDATES parameter or the FETCHOPTIONS parameter with the FETCHPKUPDATECOLS option.

OGG-01397: {1}: The Token Buffer has exceeded the maximum size of {0,number,0} bytes.

Cause: The TOKENS clause is too large. TOKENS supports a maximum character string of up to 2000 bytes. The data can be either a constant that is enclosed within double quotes or the result of an Oracle GoldenGate column-conversion function.

Action: Edit the TOKENS clause to reduce the character string, if possible. If using the result of a column-conversion function, you might need to select alternate input criteria that does not produce output that is too long.

OGG-01398: Failed to open target trail file {0}, at RBA {1,number,0}; ALTER EXTRACT assumed. Trail file will be created

Cause: The process could not find a remote trail.

Action: Contact Oracle Support.

OGG-01399: DDL of size {0,number,0} cannot be used with this trail format, please use newer trail format

Cause: The version of the trail is older than the version of Extract, and the current trail version does not support the maximum DDL size that Extract does.

Action: To upgrade the trail to the correct format, issue the ALTER EXTRACT command with the ETROLLOVER option to start a new trail file that is of the correct format, and then restart Extract. Note that the version of the process that reads this trail must be at least the same version as the trail, so you might need to upgrade that process and any downstream processes.

OGG-01400: Database operation failed: {0}. ODBC error: SQLCODE {2,number,0}. ODBC error detail is not available - please check that the ODBC configuration is complete, including the DB2 BIND for ODBC plans & packages. {1}

Cause: This indicates a possible invalid or incomplete DB2 ODBC configuration. This situation is seen as error -805 and there is no additional detail available.

Action: Check the DB2 ODBC configuration, plans, and packages to ensure they are valid and complete. Restart the process after fixing these issues.

OGG-01401: Database operation failed: {0}. ODBC error: SQLCODE {2,number,0}. ODBC error detail is not available - please check that the ODBC configuration is complete, including the DB2 BIND for ODBC plans & packages. {1}

Cause: This indicates a possible invalid or incomplete DB2 ODBC configuration. This situation is seen as error -805 and there is no additional detail available.

Action: Check the DB2 ODBC configuration, plans, and packages to ensure they are valid and complete. Restart the process after fixing these issues.

OGG-01402: CACHEMGR: item allocation too large: {0,number,0} > {1,number,0} (max single allocation)

Cause: The size of the row data or LOB exceeded the allowed maximum.

Action: Double the value specified with the CACHESIZE option of the CACHEMGR parameter. If the problem persists, contact Oracle Support.

OGG-01403: Error constructing IPC message {0}. Last offset is {1,number,0}

Cause: There was an error getting the last CSN from the currently active remote trail.

Action: Contact Oracle Support

OGG-01404: Error parsing IPC message {0}. Message length is {1,number,0}, last offset {2,number,0}

Cause: There was an error getting the CSN and other information about the last transaction from the currently active remote trail.

Action: Contact Oracle Support

OGG-01405: Empty commit sequence number (CSN) timestamp detected in target file {0}, at RBA {1,number,0}

Cause: The process could not find the timestamp of the CSN for the last transaction.

Action: Contact Oracle Support

OGG-01406: Invalid commit sequence number (CSN) timestamp detected in target file {0}, at RBA {1,number,0}

Cause: The process could not convert the timestamp (in string form) of the CSN of the last transaction to a numeric value.

Action: Contact Oracle Support

OGG-01407: Setting current schema for DDL operation to [{0}]

Cause: The process is setting the schema for the DDL operation. This is an informational message.

Action: None

OGG-01408: Restoring current schema for DDL operation to [{0}]

Cause: Replicat is setting the schema for DDL operations to the one that is specified. This is informational only.

Action: None

OGG-01409: Unable to detect missing target row for update for table {0} because there are no modifiable columns, at RBA {1,number,0}, in file {2}.

NOCOMPRESSUPDATES may be specified in the EXTRACT parameter file to include a complete image for update operations.

Cause: Replicat could not perform the update, probably because the source and target tables do not have a primary or unique key (or a KEYCOLS clause) and, therefore, Replicat could not locate the target row. By default, Extract only writes the primary key, unique key, or KEYCOLS columns to the trail (plus the changed columns), which provides enough information for the Replicat SQL operation for updates. However, without a key, Replicat only has the change data, which is not enough.

Action: You can do one of the following: Use the Extract NOCOMPRESSUPDATES parameter to send all of the columns to the trail, so that when a table definition does not include a primary key or unique index, Replicat can use all of the columns as a key. Alternatively, you can define a substitute key for the table by using a KEYCOLS clause in the TABLE parameter.

OGG-01410: Unable to apply NOOP update for table {0} because there are no modifiable columns, at RBA {1,number,0}, in file {2}. NOCOMPRESSUPDATES may be specified in the EXTRACT parameter file to include a complete image for update operations.

Cause: Replicat could not perform the update, probably because the source and target tables do not have a primary or unique key (or a KEYCOLS clause) and, therefore, Replicat could not locate the target row. By default, Extract only writes the primary key, unique key, or KEYCOLS columns to the trail (plus the changed columns), which provides enough information for the Replicat SQL operation for updates. However, without a key, Replicat only has the change data, which is not enough.

Action: You can do one of the following: Use the Extract NOCOMPRESSUPDATES parameter to send all of the columns to the trail, so that when a table definition does not include a primary key or unique index, Replicat can use all of the columns as a key. Alternatively, you can define a substitute key for the table by using a KEYCOLS clause in the TABLE parameter.

OGG-01411: Cannot convert input file {0} with format {1} to output file {2} with format {3}

Cause: The output trail of the data pump has a different format (version) than the input trail of the data pump. The input and output trail formats must be identical for a data pump.

Action: The FORMAT RELEASE option of EXTFILE or EXTTRAIL and RMTFILE or RMTTRAIL must be the same when associated with a data pump. For more information, see the Oracle GoldenGate reference documentation.

OGG-01412: Invalid query specified: Large objects cannot be tokenized with the getval function in SQLEXEC statements.

Cause: Large object types (LOBs) are not supported by GETVAL or SQLEXEC for this database system.

Action: Use a supported data type for the SQLEXEC query. See the SQLEXEC reference documentation for supported data types.

OGG-01413: Missing argument for the shell command.

Cause: The SHELL action of EVENTACTIONS does not include a valid argument to execute.

Action: For the SHELL command, specify a valid command or script.

OGG-01414: CACHEMGR: tran id: 0 length memtran: 0x{0}

Cause: A primary key or unique identifier is not present in the captured data.

Action: Open a support case with Oracle GoldenGate.

OGG-01415: CACHEMGR: secondary tran id: 0 length tran id: {0}

Cause: A secondary key or unique identifier is not present in the captured data.

Action: Open a support case with Oracle GoldenGate.

OGG-01416: File {0}, with format {1}, does not match current format specification of {2}. Modify the parameter file to specify format {1} or issue ETROLLOVER prior to restart.

Cause: The version of Extract and the version of the output file or trail do not match. Extract may have been upgraded to a newer version. By default, Extract expects the trail version to be the same as its own version; otherwise a different version must be specified in the parameter file if you want to retain backward compatibility for an older Replicat.

Action: You have two choices, depending on whether the Replicat process is the same version as the Extract process, or whether it is older: To continue using an older Replicat process, you must specify the FORMAT option in the RMTTRAIL, EXTTRAIL, RMTFILE, or EXTFILE parameter, depending on which is being used. If you are upgrading Replicat to the same version of Extract, issue the ALTER EXTRACT command with the ETROLLOVER option in GGSCI before you start Extract. The rollover sets the trail format to the same as that of the new Extract. For more information, see the Oracle GoldenGate reference documentation for these parameters.

OGG-01417: CACHEMGR: duplicate transaction secondary key: {1} primary key: {0}

Cause: The Oracle GoldenGate object pool in memory already contains an object with the same secondary identifier.

Action: Determine whether old (already processed) transaction data was processed by Extract. If you are certain that the transaction logs are not corrupted, open a support case with Oracle.

OGG-01418: Unsupported datatype {0} ({1,number,0}) found in UDT attribute {2}.

Cause: An NCLOB, NCHAR, or NVARCHAR2 datatype is defined in the object table. These data types are not supported.

Action: Exclude the UDT from the Oracle GoldenGate configuration.

OGG-01419: Source table {0} is mapped to multiple targets. Combination of EBCDIC and non EBCDIC targets is not supported.

Cause: The source table is mapped to multiple targets, but the encoding is specified differently for each target. One is specified as EBCDIC but the other is not.

Action: Change the encoding so that it is the same for all targets (either EBCDIC or ASCII). To keep the existing configuration, use different Extract groups for each encoding scheme.

OGG-01420: CACHEMGR: duplicate transaction primary key: {0}

Cause: The Oracle GoldenGate object pool in memory already contains an object with the same unique identifier, typically a transaction identifier.

Action: Determine whether old (already processed) transaction data was processed by Extract. If you are certain that the transaction logs are not corrupted, open a support case with Oracle.

OGG-01421: CACHEMGR: no primary key

Cause: The Oracle GoldenGate memory manager cannot ascertain a unique identifier for the transaction or object that Extract processed.

Action: Open a support case with Oracle.

OGG-01422: CACHEMGR: no secondary key primary key: {0}

Cause: The length of a secondary key was provided in the transaction record, but no secondary key could be found by the memory manager.

Action: Open a support case with Oracle.

OGG-01424: Event processing not supported for Teradata maximum performance mode.

Cause: This message is deprecated.

Action: None

OGG-01425: Missing context item number {0,number,0}, '{1}', for message issued from line {3,number,0} of '{2}'

Cause: Internal error: An expected message token is missing.

Action: Contact Oracle Support.

OGG-01426: DDL operation excluded by user exit [{0}], optype [{1}], objtype [{2}], objowner [{3}], objname [{4}]

Cause: The specified user exit excluded the specified DDL. This is informational only.

Action: None

OGG-01427: {1} ignored when {0} is used

Cause: The specified parameter is incompatible with another parameter in the process configuration and was ignored.

Action: Remove the parameter.

OGG-01428: Reached maximum number of retries {{0,number,0}} on Oracle error {1,number,0}

Cause: The number of retries that is specified with the MAXRETRIES option of the REPERROR parameter has been reached.

Action: Try to fix the problem with the data that is causing the error. If the problem cannot be resolved, you can change the REPERROR options to discard the operation so that you can examine it and apply it manually, if possible. You can also START REPLICAT with the SKIPTRANSACTION, ATCSN, or AFTERCSN option to skip the transaction.

OGG-01431: Aborted grouped transaction on '{0}', Mapping error

Cause: There was an error mapping the source table to the target table while applying a grouped transaction.

Action: Resolve the mapping error and restart the process.

OGG-01432: Aborted grouped transaction on '{0}', Filter not passed

Cause: There was an error in the filter logic.

Action: Fix the filter specification in the parameter file, and then restart the process.

OGG-01433: Failed to validate table {0}. The table is compressed and extract will not be able to extract data from Oracle logs

Cause: Oracle GoldenGate does not support tables created with table compression or OLTP table compression.

Action: Remove the table from the Extract and Replicat configurations, and then restart the processes.

OGG-01434: {0}

Cause: The specified error occurred when the process tried to map memory.

Action: If you cannot resolve the error based on the content of the message, such as add system memory resources, contact Oracle Support.

OGG-01435: mmap: len: 0x{0} prot: 0x{1} flags: 0x{2} fd: {3,number,0} off: 0x{4} errno: {5,number,0} ({6})

Cause: Internal warning. A memory mapping operation failed.

Action: Verify that the installation directory is on a file system that supports memory mapped files.

OGG-01436: Detected and skipped incomplete log write at end of Oracle log with sequence# of {0,number,0} and log write starting rba of {1,number,0}

Cause: The end of the file was reached before the log writer buffer was completed.

Action: Add the TRANLOGOPTIONS parameter with the OPENARCHIVEIMMEDIATE option to the Extract parameter file, so that the process uses the archive log immediately.

OGG-01437: Failed to modify trail record image prior to write to trail file {0}

Cause: The in-memory trail record could be corrupted, causing an update to its fields or other properties to fail.

Action: Save the checkpoint file and the trail files, and then contact Oracle Support.

OGG-01438: Checkpoint marked as from graceful shutdown, but records found after checkpoint in trail {0}. Expected EOF Seqno {1,number,0}, RBA {2,number,0}. Found Seqno {3,number,0}, RBA {4,number,0}

Cause: The process found records that were generated after the checkpoint in the trail. This is just a warning. A correction will be attempted.

Action: None

OGG-01443: The key columns available in the table {0} may not guarantee uniqueness due to exclusion of virtual, nullable, or other unusable column(s).

Cause: A key column contains one or more of the specified column types. Oracle GoldenGate accepts nullable columns in a key definition if no other key exists, but does not accept the other specified column types in a key definition. If one or more columns of these types helps to provide uniqueness to the key, the exclusion of them leaves open the possibility for data inaccuracies on the target. Nullable columns by virtue of their definition cannot be considered unique.

Action: None, if you know that excluding these columns does not compromise uniqueness. To view the rules of Oracle GoldenGate key selection, see the installation and setup guide for the database type.

OGG-01444: Error in replicating sequence value [{0}]

Cause: The specified database error occurred while the process was replicating a sequence value.

Action: Resolve the database error that is indicated in the error message and then restart the process.

OGG-01445: Buffer overflow (max buffer size {0,number,0}), no xmldata extracted

Cause: The length of the embedded XML data exceeds the size of the memory buffer that is specified with the XMLBUFSIZE option of DBOPTIONS.

Action: Increase the value of this parameter, and then restart Extract.

OGG-01446: Object table {0} is not supported for this database version.

Cause: An object table was specified in an Oracle GoldenGate parameter file or command, and the Oracle version is prior to release 10.2.0.2. Object tables are not supported for those database versions.

Action: Remove the object table from the Oracle GoldenGate configuration.

OGG-01447: Unsupported opaque type ({0}) found

Cause: An XMLTYPE is part of the UDT that is being processed. XMLTYPE is not supported.

Action: Remove the XMLTYPE from the UDT or do not replicate the UDT.

OGG-01448: XmlLoadDom error uploading XML data ({0}) for col:{1} attr:{2} type:{3}

Cause: Extract could not process the specified XML data.

Action: Contact Oracle Support.

OGG-01449: Scan failed in trail file {0}, with scan start seqno {1,number,0}, rba {2,number,0}

Cause: While trying to find the last commit position in a remote trail, the process encountered an internal scan error.

Action: Contact Oracle Support.

OGG-01450: Unrecognized return value '{0,number,0}' from scan of trail file {1}, with scan start seqno {2,number,0}, rba {3,number,0}

Cause: While trying to find the last commit position in a remote trail, the process encountered an unexpected return value.

Action: Contact Oracle Support.

OGG-01451: {0}

Cause: This is a generic informational message that is used to report various different conditions.

Action: Take corrective action based on the message text. Look for related messages that were logged along with this message. If you cannot resolve the problem based on the context provided in the messages, contact Oracle Support.

OGG-01453: Database login information not specified in parameter file.

Cause: The USERID parameter is missing from the parameter file.

Action: Add the USERID parameter according to the directions in the Oracle GoldenGate reference documentation.

OGG-01454: Unable to lock file "{0}" (error {2,number,0}, {3}).{1,choice,0#|1# Lock currently held by process id (PID) {1,number,0}.}

Cause: An attempt by the process to use the operating system to lock a file failed because the file is in use by another process. If possible, the identifier of the offending process is shown.

Action: Make certain that the file is supposed to be in the Oracle GoldenGate configuration, and that a typo did not cause a different file to be used. Verify that the file system that is being used is supported by Oracle GoldenGate.

OGG-01455: Object table {0} is not supported for this database version.

Cause: An object table was specified in an Oracle GoldenGate parameter file or command, and the Oracle version is prior to release 10.2.0.2. Object tables are not supported for those database releases.

Action: Remove the object table from the Oracle GoldenGate configuration.

OGG-01456: Limit of maximum LOB columns ({0,number,0}) exceeded.

Cause: The number of columns with LOBs exceeds the limit that the system can handle.

Action: Contact Oracle Support.

OGG-01457: {1} cannot be called with the VAM compatibility level set to {0,number,0}

Cause: The VAM module and the VAM API kernel in Extract have different compatibility levels and cannot be used together.

Action: Add the TRANLOGOPTIONS parameter with the VAMCOMPATIBILITY option to the Extract parameter file to set the compatibility level for the VAM module. If the problem persists, contact Oracle Support.

OGG-01458: The VAM compatibility level of {0,number,0} set via the TRANLOGOPTIONS VAMCOMPATIBILITY parameter was overridden by the VAM client module in VAMInitialize and set to {1,number,0}

Cause: VAMInitialize overrides the TRANLOGOPTIONS VAMCOMPATIBILITY setting.

Action: None if the VAMInitialize version is correct. Otherwise, make the necessary changes to reflect the correct version. To support backward compatibility with an older TAM module, set TRANLOGOPTIONS with VAMCOMPATIBILITY to a value of 1, or set the value with VAMInitialize.

OGG-01459: The VAM compatibility level must be set via the TRANLOGOPTIONS VAMCOMPATIBILITY <level> parameter, where <level> is a number starting at 1

Cause: A new Oracle GoldenGate for Teradata Extract has been paired with an older TAM module.

Action: To support backward compatibility with the older module, set TRANLOGOPTIONS with VAMCOMPATIBILITY to a value of 1. If you set the VAM compatibility with VAMInitialize, it does not have to be set with TRANLOGOPTIONS. This parameter is not needed if the Extract and the TAM module are the same version.

OGG-01462: Requested TDS packet size of {0,number,0} bytes changed to {1,number,0} by SQL Server

Cause: The request for the TDS packet size was returned successfully, but the value was changed by the database server to the value specified in the warning.

Action: This is a warning message, so no immediate action is needed. If the problem persists, contact Oracle Support.

OGG-01464: mmap: len: 0x{0} prot: 0x{1} flags: 0x{2} fd: {3,number,0} off: 0x{4} errno: {5,number,0} ({6})

Cause: The operating system could not create or allocate a shared memory region of the given size and operation flags. The error value indicates the specific error mode. This operation can fail due to exhausted disk space, the Oracle GoldenGate installation being on a shared (NFS) virtual device, or the associated backing file being in use by another process.

Action: Contact Oracle Support.

OGG-01465: Exceeded transaction timeout threshold ({2,number,0} seconds) waiting for source transaction with XID {3} and CSN {4} at RBA {1,number,0}, in file {0}.

Cause: Replicat has been at the same position for a period of time that is equal to, or greater than, the value that is specified with the TRANSACTIONTIMEOUT parameter. Informational to indicate the beginning of the transaction timeout recovery process.

Action: None

OGG-01466: Exceeded transaction timeout threshold ({2,number,0} seconds) waiting for source transaction at RBA {1,number,0}, in file {0}.

Cause: Replicat has been at the same position for a period of time that is equal to, or greater than, the value that is specified with the TRANSACTIONTIMEOUT parameter. Informational to indicate the beginning of the transaction timeout recovery process.

Action: None

OGG-01467: Recovered to start of partial source transaction with XID {2} and CSN {3} at RBA {1,number,0}, in file {0}. Waiting for more data.

Cause: The value that is specified with the TRANSACTIONTIMEOUT parameter in the Replicat parameter file was reached, and Replicat did not receive the end-of-transaction record. The transaction timeout recovery process successfully backed out the open transaction and recovered to the logical end-of-file, and is now waiting for more data.

Action: None

OGG-01468: Recovered to start of partial source transaction at RBA {1,number,0}, in file {0}. Waiting for more data.

Cause: The value that is specified with the TRANSACTIONTIMEOUT parameter in the Replicat parameter file was reached, and Replicat did not receive the end-of-transaction record. The transaction timeout recovery process successfully backed out the open transaction and recovered to the logical end-of-file, and is now waiting for more data.

Action: None

OGG-01469: New data detected after RBA {1,number,0}, in file {0}. Resuming delivery for transaction with XID {2} and CSN {3}.

Cause: Applies to TRANSACTIONTIMEOUT processing. Additional data has been received while the transaction timeout recovery process was waiting at the logical end-of-file. This message marks the transition from transaction timeout recovery back to normal processing.

Action: None

OGG-01470: New data detected after RBA {1,number,0}, in file {0}. Resuming delivery.

Cause: Applies to TRANSACTIONTIMEOUT processing. Additional data has been received while the transaction timeout recovery process was waiting at the logical end-of-file. This message marks the transition from transaction timeout recovery back to normal processing.

Action: None

OGG-01471: TRANSACTIONTIMEOUT cannot be less than EOFDELAY.

Cause: The value that is specified for TRANSACTIONTIMEOUT is less than the value of the EOFDELAY parameter. It must be greater than the EOFDELAY parameter.

Action: Edit the Replicat parameter file to set TRANSACTIONTIMEOUT to a value that is greater than that of EOFDELAY, and then restart Replicat.

OGG-01472: TRANSACTIONTIMEOUT cannot be greater than 1 week.

Cause: The TRANSACTIONTIMEOUT parameter is being used in the Replicat parameter file, but the value that was specified is greater than the maximum allowed value of one week (seven days).

Action: Change the TRANSACTIONTIMEOUT value to something between one second and one week, and then restart Replicat.

OGG-01473: DDL is too large - DDL IGNORED, details: DDL statement with marker sequence [{0}], ddl sequence [{1}] for [{2}.{3}/{4}] will be ignored. The length of [{5}] bytes exceeds the supported maximum size.

Cause: The DDL statement exceeds the size that is supported by Oracle GoldenGate and will be ignored.

Action: Depends on whether the discarding of the DDL has an effect on any subsequent DML. Future DML may cause an error if discarding the DDL causes metadata inconsistencies. In any case, you can apply the DDL on the target manually. You might need to restart processes if the condition caused an error.

OGG-01474: Cannot automatically start {0} {1}, which abended due to an out of order transaction. Issue ETROLLOVER to advance the output trail sequence past the current trail sequence and restart. Then, use ALTER EXTSEQNO on the subsequent pump EXTRACT, or REPLICAT, process group to start reading from the new trail file created by ALTER ETROLLOVER; the downstream process will not automatically switch to the new trail file.

Cause: Manager cannot start the specified process. The transactions in the current trail file are out of order. One possible cause is that Extract was configured to write to this trail, and then was reconfigured to write to a different trail, but was subsequently reconfigured to write the original trail again. It is also possible that Extract was repositioned backward in the transaction log and the data from the new position was appended to the end of the current trail file. You need to skip this record, and then reposition Replicat to start at the next one.

Action: Stop the Extract that should write to this trail, then issue the ALTER EXTRACT command with ETROLLOVER. Next, restart Extract. Next, issue the ALTER REPLICAT or ALTER EXTRACT command (depending on whether Replicat or a data pump Extract reads the trail) with the EXTSEQNO option and specify the sequence number of the new trail file. Finally, start Replicat or the data pump.

OGG-01475: Cannot automatically restart {0} {1}, which abended due to an out of order transaction. Issue ETROLLOVER to advance the output trail sequence past the current trail sequence and restart. Then, use ALTER EXTSEQNO on the subsequent pump EXTRACT, or REPLICAT, process group to start reading from the new trail file created by ALTER ETROLLOVER; the downstream process will not automatically switch to the new trail file.

Cause: Manager cannot start the specified process. The transactions in the current trail file are out of order. One possible cause is that Extract was configured to write to this trail, and then was reconfigured to write to a different trail, but was subsequently reconfigured to write the original trail again. It is also possible that Extract was repositioned backward in the transaction log and the data from the new position was appended to the end of the current trail file. You need to skip this record, and then reposition Replicat to start at the next one.

Action: Stop the Extract that should write to this trail, then issue the ALTER EXTRACT command with ETROLLOVER. Next, restart Extract. Next, issue the ALTER REPLICAT or ALTER EXTRACT command (depending on whether Replicat or a data pump Extract reads the trail) with the EXTSEQNO option and specify the sequence number of the new trail file. Finally, start Replicat or the data pump.

OGG-01476: The previous run abended due to an out of order transaction. Issue ALTER ETROLLOVER to advance the output trail sequence past the current trail sequence number, then restart. Then, use ALTER EXTSEQNO on the subsequent pump EXTRACT, or REPLICAT, process group to start reading from the new trail file created by ALTER ETROLLOVER; the downstream process will not automatically switch to the new trail file.

Cause: Somehow, the transactions in the current trail file are out of order. A different Extract might have been configured to write to this trail, and old data was overlaid with the new data. You will need to skip this record, and then reposition Replicat to start at the next one.

Action: Stop the Extract that should write to this trail, then issue the ALTER EXTRACT command with ETROLLOVER. Next, restart Extract. Next, issue the ALTER REPLICAT or ALTER EXTRACT command (depending on whether Replicat or a data pump Extract reads the trail) with the EXTSEQNO option and specify the sequence number of the new trail file. Finally, start Replicat or the data pump.

OGG-01477: Target does not support format {1} for file {0}. Reverting to format {2}

Cause: The process that reads this file is of an older version than that of the process that wrote the file. A trail or extract file must have a version that is equal to, or lower than, that of the process that reads it. In addition, the input file and output file of a data pump must be the same version. This message is informational only.

Action: None

OGG-01478: Output file {0} is using format {1}.

Cause: The trail or file that this process is writing to is using the specified trail format. Trail formats can vary from version to version of Oracle GoldenGate. This message is informational only.

Action: None

OGG-01479: {0}

Cause: This message is deprecated.

Action: None

OGG-01482: DDL object type is not supported, type {0}

Cause: The specified database object is not supported by the Oracle GoldenGate DDL replication feature.

Action: Remove the object from the DDL parameter in the parameter file, and then restart the process.

OGG-01483: The key for table [{0}.{1}.{2}] contains one or more variable length columns. These columns may not have their pre-images written to the transaction log during updates. Please use KEYCOLS to specify a key for Oracle GoldenGate to use on this table.

Cause: The specified table does not have a clustered index and has variable length columns. Oracle GoldenGate will use the entire row as the key, so there is the potential for some before images to be lost if data gets stored off page.

Action: Specify columns that contain unique values as key columns by using a KEYCOLS clause in the TABLE and MAP statements, or alternatively define a clustered index on the table. Note that if you define a clustered index, it is a DDL operation. DDL operations are not supported by Oracle GoldenGate for this database, so follow the instructions in the Oracle GoldenGate administration documentation for performing DDL on objects that are in an active replication configuration.

OGG-01485: Error adding item to transaction {0,number,0}:{1,number,0}:{2,number,0}, op={3,number,0}, record LSN={4,number,0}, length={5,number,0}.

Cause: An internal error occurred.

Action: Report the full message content to Oracle Support.

OGG-01487: DDL found, operation [{0}], start {1} [{2}], commit {1} [{3}] instance [{4}], ({5}), DDL seqno [{6}], marker seqno [{7}]

Cause: A DDL operation was processed. Informational only.

Action: None

OGG-01489: Could not add TRAN DATA for table, error [{1}], error code [{0,number,0}], operation [{2}]

Cause: The DDLOPTIONS parameter with the ADDTRANDATA option is specified in the Extract parameter file, and the ALTER TABLE command that adds the supplemental logging did not succeed because of an error.

Action: Correct the problem based on the database error that is returned. If you cannot resolve the problem, contact Oracle Support.

OGG-01495: Error action for ADDTRANDATA already specified (ABEND, RETRYOP) [{0}]

Cause: Both ABEND and RETRY are specified for ADDTRANDATA.

Action: Remove one of these options. They are mutually exclusive.

OGG-01496: Failed to open target trail file {0}, at RBA {1,number,0}

Cause: The process could not find a valid trail during the initial phase of recovery.

Action: Contact Oracle Support.

OGG-01498: Aborting BATCHSQL transaction{0,choice,0#|1# in batch error mode}. Database error {1,number,0} ({2}).

Cause: BATCHERRORMODE processing was not able to apply the transaction successfully due to the specified database error, and is rolling back the transaction. Replicat will process the transaction in normal mode.

Action: None

OGG-01500: Aborting BATCHSQL transaction{0,choice,0#|1# in batch error mode}. Detected inconsistent result: executed {1,number,0} operations in batch, resulting in {2,number,0} affected rows.

Cause: The batched operation resulted in possible data integrity issues based on the number of operations in the batch, versus the number of affected rows returned by the database response. The transaction is being rolled back, and Replicat will re-process the transaction in normal mode.

Action: None

OGG-01501: Aborting BATCHSQL transaction{0,choice,0#|1# in batch error mode}. Database error {1,number,0} ({2}). Temporarily disabling batch mode due to transient key update.

Cause: The batched transaction is being rolled back because the BATCHERRORMODE conversion processing resulted in a transient primary key update. (See the HANDLETPKUPDATE parameter documentation for more information on TPKU.) Replicat will revert to normal processing to apply this transaction.

Action: None

OGG-01502: Aborting BATCHSQL transaction{0,choice,0#|1# in batch error mode}. Database error {1,number,0} ({2}). Override of duplicate failed.

Cause: BATCHSQL is operating in BATCHERRORMODE, but there was a collision converting an insert to an update.

Action: To use BATCHERRORMODE, you must use the HANDLECOLLISIONS parameter in the Replicat parameter file to handle collisions caused by the conversions.

OGG-01503: Aborting BATCHSQL transaction{0,choice,0#|1# in batch error mode}. Mapping error.

Cause: The batched transaction is being aborted, and Replicat will revert to normal processing.

Action: None

OGG-01504: Aborting BATCHSQL transaction{0,choice,0#|1# in batch error mode}. Filter not passed.

Cause: The batched transaction is being aborted due to a filter error. Replicat will revert to normal processing.

Action: None

OGG-01505: OCI Error ({0,number,0}, {1}) maximum cursors exceeded, unable to prepare new statement for table {2}, query = {3}

Cause: The maximum number of cursors allowed by the MAXSQLSTATEMENTS parameter has been reached.

Action: If the database cursor limit permits, and there will be enough cursors for other applications, you can increase the value of MAXSQLSTATEMENTS.

However, see the Oracle GoldenGate reference documentation before changing this parameter.

OGG-01506: Value ({0}) exceeds minimum value of column. Table {1}, column {2}.

Cause: A numeric conversion failed because the resulting negative value cannot be represented in the space provided, based on the catalog definition for the specified column.

Action: Examine any recent changes to the table. The catalog definition for the specified table may not match the data in the archive logs.

OGG-01507: Value ({0}) exceeds maximum value of column. Table {1}, column {2}.

Cause: A numeric conversion failed because the resulting positive value cannot be represented in the space provided, based on the catalog definition for the specified column.

Action: Examine any recent changes to the table. The catalog definition for the specified table may not match the data in the archive logs.

OGG-01508: Failed to initialize monitoring point service for process group {0} (error {1,number,0}). Monitoring point publishing will be disabled.

Cause: An Oracle GoldenGate process failed to initialize the shared memory for its monitoring point registry and service. This failure typically occurs if: there is not enough disk space to host the backing file (Linux); there is not enough memory to host the shared region; the backing file is being stored on an NFS mounted directory (Linux); or the system exhausted its allocation of available handles.

Action: For issues that relate to system resources, such as disk space and handles, increase the available resource by allocating more disk storage, by allocating more handles, or by reducing the consumption of those resources by other processes (as the case may be). For an NFS issue, either install Oracle GoldenGate on a local physical device or set the internal GLOBALS parameter _TMPSTOREDIR to a directory on a local physical device.

OGG-01509: Failed to publish monitoring point value for "{0}" (error {1,number,0}). Monitoring point publishing will be disabled.

Cause: An Oracle GoldenGate process could not establish a shared memory region to hold monitoring point statistics. This inability indicates corruption of the region.

Action: Check for a related message or messages (such as error OGG-01508) to determine how to resolve the problem. If there are no related messages, restart the process. If the error persists, contact Oracle Support.

OGG-01510: Failed to set monitoring point registry ID to "{0}" (error {1,number,0})

Cause: An Oracle GoldenGate process could not establish a shared memory region to hold monitoring point statistics. This inability indicates corruption of the region.

Action: Check for a related message or messages (such as error OGG-01508) to determine how to resolve the problem. If there are no related messages, restart the process. If the error persists, contact Oracle Support.

OGG-01511: Failed to set process status to {0} (error {1,number,0})

Cause: An Oracle GoldenGate process could not establish a shared memory region to hold monitoring point statistics. This inability indicates corruption of the region.

Action: Check for a related message or messages (such as error OGG-01508) to determine how to resolve the problem. If there are no related messages, restart the process. If the error persists, contact Oracle Support.

OGG-01512: WILDCARDRESOLVE DYNAMIC parameter is mandatory for the generic database implementation of the VAM

Cause: In the VAM implementation, tables can only be looked up as they are encountered dynamically. The table metadata cannot be exchanged statically in the VAMInitialize function

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-01513: Positioning to {0}

Cause: Extract is positioning to the specified sequence number.

Action: None

OGG-01514: Positioning to start

Cause: Extract is positioning to the start of the data source on startup, rather than to a specific sequence or time.

Action: None

OGG-01515: Positioning to begin time {0,date} {0,time}

Cause: The process is being positioned to start at the specified timestamp.

Action: None

OGG-01516: Positioned to {0}, {1,date} {1,time}

Cause: The process is now positioned to start at the specified timestamp.

Action: None

OGG-01517: Position of first record processed {0}, {1,date} {1,time}

Cause: The processing began with the first record that has the specified timestamp.

Action: None

OGG-01519: Waiting at EOF on input trail file {0}, which is not marked as complete; but succeeding trail file {1} exists. If ALTER ETROLLOVER has been performed on source extract, ALTER EXTSEQNO must be performed on each corresponding downstream reader.

Cause: Extract was upgraded, and an ALTER EXTRACT command with ETROLLOVER was issued to roll over the existing trail to a new file that is of the correct format for the new version. The process that reads the trail (data pump or Replicat) must be altered to start reading at the beginning of the new trail.

Action: Issue the ALTER EXTRACT or ALTER REPLICAT command (depending on the process) with the EXTSEQNO option, and specify the sequence number of the new trail.

OGG-01520: Rollover performed. For each affected output trail of Version 10 or higher format, after starting the source extract, issue ALTER EXTSEQNO for that trail's reader (either pump EXTRACT or REPLICAT) to move the reader's scan to the new trail file; it will not happen automatically.

Cause: Extract was upgraded, and an ALTER EXTRACT command with ETROLLOVER was issued to roll over the existing trail to a new file that is of the correct format for the new version. The process that reads the trail (data pump or Replicat) must be altered to start reading at the beginning of the new trail.

Action: Issue the ALTER EXTRACT or ALTER REPLICAT command (depending on the process) with the EXTSEQNO option, and specify the sequence number of the new trail.

OGG-01521: Scan resumed.

Cause: A trail was rolled over, and the reading process was altered to begin reading at the beginning of the new trail.

Action: None

OGG-01522: Non-zero value for delay required when calling {0}

Cause: This is an internal error and should not occur in production. A polling error occurred. Configuration of the Oracle GoldenGate error logging subsystem via the Activity Logging class can be set up so that a specific file is polled for every N milliseconds. If N is zero, it is considered a programming error and this message is issued.

Action: Contact Oracle Support.

OGG-01523: Failed to initialize DTD for Activity Logging

Cause: The gglog.dtd XML definition file is invalid in the installation folder.

Action: Fix this file, or contact Oracle Support.

OGG-01525: Failed to open trace output file, '{0}', error {1,number,0} ({2})

Cause: The specified output file could not be opened.

Action: Verify that the file permissions are adequate.

OGG-01526: Unknown appender, '{1}', for logger, '{0}', ignored in configuration file, '{2}'

Cause: The appender named by the 'appender-ref' element is not defined in the XML file.

Action: Specify one of the valid appender class names defined in gglog.dtd. If you cannot resolve the problem, contact Oracle Support.

OGG-01527: Problem validating configuration file, '{1}', {0}. Problem ignored.

Cause: Undefined

Action: Undefined

OGG-01528: Cannot access configuration file '{0}', error {1,number,0} ({2})

Cause: The specified XML configuration file cannot be accessed.

Action: Verify that the file permissions are adequate. If you cannot resolve the problem, contact Oracle Support.

OGG-01529: Failure validating configuration file, '{1}', {0}. Configuration unchanged.

Cause: Undefined

Action: Undefined

OGG-01530: MaxFileSize of '{0}' in configuration file, '{1}', must be between zero and 4GB

Cause: The Activity Logging XML file contains a MaxFileSize parameter for a RollingFileAppender that is not between 0 and 4GB (exclusive).

Action: Change the parameter value to be within the specified size range. If you cannot resolve the problem, contact Oracle Support.

OGG-01531: MaxFileSize of '{0}' in configuration file, '{1}', has an invalid multiplier. Expected 'KB', 'MB', or 'GB'.

Cause: The Activity Logging XML file contains a MaxFileSize parameter for a RollingFileAppender that has a suffix with a value other than 'KB', 'MB', or 'GB' in either upper or lower case.

Action: Change the suffix value to a valid size unit. If you cannot resolve the problem, contact Oracle Support.

OGG-01532: Cannot locate XML configuration file, '{0}'

Cause: The Activity Logging XML file that is specified could not be located in the file system. Both the current directory and the application directory were searched.

Action: Find the configuration file, or create a new one. If you cannot resolve the problem, contact Oracle Support.

OGG-01533: Cannot use XML configuration file, '{0}', validation failed

Cause: Undefined

Action: Undefined

OGG-01534: Error parsing XML configuration file, '{2}', at line {0,number,0}: {1}

Cause: The XML file that is used by Activity Logging is not well-formed. The specific reason is provided by the third-party XML library.

Action: Fix the XML error that is reported by the XML checker. If you cannot resolve the problem, contact Oracle Support.

OGG-01535: Cannot use XML configuration file, '{0}', document root inaccessible

Cause: The XML file was well-formed, valid, and successfully loaded, but the root of the document could not be determined.

Action: Correct the XML file. If you cannot resolve the problem, contact Oracle Support.

OGG-01536: Unknown appender class name, '{1}', for appender '{0}' in configuration file '{2}'

Cause: An invalid class name was specified for an appender element in a Activity Logging XML configuration file.

Action: Specify one of the valid appender class names defined in gglog.dtd. If you cannot resolve the problem, contact Oracle Support.

OGG-01537: Unknown parameter, '{2}', for '{1}' appender class in appender '{0}' in configuration file '{3}'

Cause: An invalid or misspelled parameter name was encountered for an appender element in a Activity Logging XML configuration file.

Action: Specify one of the valid appender class parameters defined in gglog.dtd. If you cannot resolve the problem, contact Oracle Support.

OGG-01538: Unknown layout class name, '{1}', for appender '{0}' in configuration file '{2}'

Cause: An invalid class name was specified for a layout element in a Activity Logging XML configuration file.

Action: Specify one of the valid layout class names defined in gglog.dtd. If you cannot resolve the problem, contact Oracle Support.

OGG-01539: Unknown parameter, '{2}', for '{1}' layout class in appender '{0}' in configuration file '{3}'

Cause: An invalid or misspelled parameter name was encountered for a layout element in a Activity Logging XML configuration file.

Action: Specify one of the valid layout class parameters defined in gglog.dtd. If you cannot resolve the problem, contact Oracle Support.

OGG-01540: Unknown filter class name, '{1}', for appender '{0}' in configuration file '{2}'

Cause: An invalid class name was specified for a filter element in a Activity Logging XML configuration file.

Action: Specify one of the valid filter class names defined in gglog.dtd. If you cannot resolve the problem, contact Oracle Support.

OGG-01541: Unknown parameter, '{2}', for '{1}' filter class in appender '{0}' in configuration file '{3}'

Cause: An invalid or misspelled parameter name was encountered for a filter element in a Activity Logging XML configuration file.

Action: Specify one of the valid parameters for the filter class defined in gglog.dtd. If you cannot resolve the problem, contact Oracle Support.

OGG-01545: Table {0} column {1,number,0} : DATA CORRUPTION may result from the use of "NOT FOR REPLICATION" on a check constraint and OLE DB.

Cause: Alerts you that the check constraint in the specified table is set to NOT FOR REPLICATION. In this mode, the target database does not check constraints when the operation is applied by Replicat. The assumption is that the constraint checking was performed by the source database.

Action: None

OGG-01546: Table {0} column {1,number,0} : DATA CORRUPTION may result from the use of "NOT FOR REPLICATION" on a trigger when OLE DB is being used.

Cause: The trigger in the specified table is set to NOT FOR REPLICATION. In this mode, the target database does not fire the trigger when the operation is applied

by Replicat operating as the replication agent. The assumption is that the triggered operations from the source are captured and replicated.

Action: Verify that the tables affected by the trigger are included in the replication configuration; otherwise, there will be no errors to alert you to integrity violations.

OGG-01547: Table {0} column {1,number,0} : DATA CORRUPTION may result from the use of "NOT FOR REPLICATION" on a foreign key when OLE DB is being used.

Cause: The foreign key in the specified table is set to NOT FOR REPLICATION. The target database does not enforce the constraint when the operation is applied by Replicat operating as the replication agent. This includes CASCADE operations. The assumption is that the constraint was checked on the source database and that the cascaded operations are captured and replicated.

Action: Verify that the referenced tables are included in the replication configuration with the referencing table; otherwise, there will be no errors to alert you to integrity violations, such as if a row gets inserted into a table that contains a foreign key to a non-replicated table.

OGG-01548: Table {0} : To improve performance, consider switching to OLE DB.

Cause: The ODBC API is being used by Replicat, but IDENTITY columns have NOT FOR REPLICATION enabled.

Action: To take advantage of NOT FOR REPLICATION and have Replicat use the better-performing OLE DB API, configure Replicat to connect as the SQL Server Replication user by using the DBOPTIONS parameter with the USEREPLICATIONUSER option. See the Oracle GoldenGate for SQL Server documentation for more information.

OGG-01552: Connection String: {0}

Cause: This is an informational message that indicates the OLE DB connect string (with the password masked) that Replicat used to connect to the target database.

Action: None

OGG-01554: The DBOPTION USEODBC and USEREPLICATIONUSER are mutually exclusive.

Cause: USEODBC and USEREPLICATIONUSER are both specified in the DBOPTIONS parameter.

Action: To have Replicat perform DML through ODBC, remove USEREPLICATIONUSER. To have Replicat perform DML as the SQL Server replication user, remove USEODBC.

OGG-01555: OLE DB Error: Incompatible driver error DSN '{0}' SQL Server {1} requires {2}

Cause: The DSN that is specified with TARGETDB in the Replicat parameter file does not specify a connection driver that is compatible with the selected SQL Server in that specification.

Action: Make certain the correct DSN is specified for TARGETDB and, if so, make certain that the driver and the database server that are specified in the DSN definition are compatible.

OGG-01557: OLE DB Error: Cannot open data source. Error code 0x{0} Detail: {1}

Cause: Replicat failed to connect to the target database with the OLE DB connection.

Action: Check the TARGETDB parameter to make certain that the correct DSN is specified. If that value is correct, examine the DSN definition itself, to make certain that all of the required connection information is present and valid.

OGG-01558: Database operation failed: OLE DB Error 0x{0}

Cause: The Replicat OLE DB operation failed, but no error information can be retrieved from the driver.

Action: Check the process report file for any warning or error messages that occurred prior to this error message, and then contact Oracle Support.

OGG-01560: Positioned to {0}

Cause: Extract positioned to the specified sequence number.

Action: None

OGG-01562: Source schema {0} is mapped to target schema {1} to set the current schema for DDL execution.

Cause: The specified source session schema is now mapped to the target session schema specified in the TARGET clause of DDLOPTIONS

MAPSESSIONSCHEMA. Any DDL executed from this source session schema will be replicated under the TARGET session schema.

Action: None

OGG-01563: Transaction {0} contains {1,number,0} orphaned LOB buffers. These must be deleted before the transaction is completed.

Cause: An internal error occurred while storing a LOB column in the Cache Object Manager (COM).

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-01564: LOB handle {0,number,0} is invalid.

Cause: An internal error occurred while storing a LOB column in the Cache Object Manager.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-01565: LOB handle {0,number,0} has already been associated with another base row column.

Cause: An internal error occurred while storing a LOB column in the Cache Object Manager.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-01566: LOB handle {0,number,0} has already been associated with a base row column and cannot be deleted explicitly.

Cause: An internal error occurred while storing a LOB column in the Cache Object Manager.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-01567: {1}: cannot find first POF: {0}

Cause: The oldest persisted-object file cannot be found. These files contain the persisted transaction data and other information that is needed for Extract to recover from the bounded-recovery checkpoint.

Action: None, unless the log files are not available. Extract will revert to normal recovery for this recovery, and then turn on Bounded Recovery again. If Extract stops because the log file that contains the oldest open transaction is not online, restore that log and any subsequent logs before restarting Extract.

OGG-01568: {3}: unsupported BR version: {0}: version expected: {1,number,0} version found: {2,number,0}

Cause: The persisted-object files were created by a version of Bounded Recovery that is different from the one that currently is running. An Extract upgrade was probably performed and the new version contains a newer Bounded Recovery version.

Action: Restart Extract from the command line with the BRRESET option. BRRESET starts the process as if this is the first run, and the process will use normal recovery. For syntax help, see the BRRESET option of the BR command in the Oracle GoldenGate reference documentation. If you cannot resolve the problem this way, manually remove all of the files that have the group name in the BRDIR directory. If the problem persists, contact Oracle Support.

OGG-01569: {1}: POF crc64 mismatch: POF: {0}

Cause: The recovery file did not pass the integrity check that the Bounded Recovery feature performs.

Action: None. Extract will revert to normal recovery for this recovery, and then turn on Bounded Recovery again.

OGG-01570: {3}: magic number mismatch: {0} expected: 0x{1} found: 0x{2}

Cause: The recovery file did not pass the integrity check that the Bounded Recovery feature performs.

Action: None. Extract will revert to normal recovery for this recovery, and then turn on Bounded Recovery again.

OGG-01571: {3}: footer magic number mismatch: filename: {0}: expected: 0x{1} found: 0x{2}

Cause: The recovery file did not pass the integrity check that the Bounded Recovery feature performs.

Action: None. Extract will revert to normal recovery for this recovery, and then turn on Bounded Recovery again.

OGG-01572: {2}: filename mismatch: POF: {0} mt_filename: {1}

Cause: The name of the persisted-object file is not what is expected based on the Extract Bounded Recovery checkpoint file.

Action: None. Extract will revert to normal recovery for this recovery, and then turn on Bounded Recovery again.

OGG-01573: {1}: failed in call to: {0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01574: {1}: failed in call to: {0}: error code: {2,number,0} ({3})

Cause: Bounded Recovery failed in the specified function invocation.

Action: If the error pertains to the Bounded Recovery storage directory, try to resolve the problem. If you cannot resolve the problem, contact Oracle Support.

OGG-01575: {2}: file operation failed in call to: {0}: filename {1}

Cause: Extract was unable to open the specified file. Extract will revert to normal recovery.

Action: None

OGG-01576: {0}: error code: {1,number,0} ({2})

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01577: {0}: NULL persisted objected pointer

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01578: {1}: unxepected flag in PO (CO): 0x{0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01579: BOUNDED RECOVERY: VALID BCP: {0}

Cause: Bounded Recovery validated the specified checkpoint.

Action: None

OGG-01580: {2}: invalid crc64: CPF: {0} crc: 0x{1}

Cause: The recovery file did not pass the integrity check that the Bounded Recovery feature performs.

Action: None. Extract will revert to normal recovery for this recovery, and then turn on Bounded Recovery again.

OGG-01582: {2}: extract group mismatch: group expected: {0} group found: {1}

Cause: The Extract group in the Bounded Recovery checkpoint file is not the one that is currently running.

Action: Restart Extract from the command line with the BRRESET option. BRRESET starts the process as if this is the first run, and the process will use normal recovery. For syntax help, see the BRRESET option of the BR command in the Oracle GoldenGate reference documentation. If you cannot resolve the problem this way, contact Oracle Support.

OGG-01584: {0}: extract group not supplied

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01585: {1}: unique bounded recovery instance already exists: requested extract group: {0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01586: {2}: {0} {1}: error code: {3,number,0} ({4})

Cause: While Extract was in Bounded Recovery mode, a request to the file system failed with the specified error.

Action: Fix the problem based on the error, if possible. If you cannot resolve the problem, contact Oracle Support.

OGG-01587: {3}: {0}: {1} error code: {4,number,0} ({5}) {2,number,0}

Cause: While Extract was in Bounded Recovery mode, a file system operation by the Cache Object Manager (COM) failed.

Action: Try to resolve the problem based on the error message that is returned. If you cannot resolve the problem, contact Oracle Support.

OGG-01588: {0}: failed

Cause: An internal message occurred in the Cache Object Manager.

Action: Contact Oracle Support.

OGG-01589: {1}: failed in call to: {0}

Cause: An internal message occurred in the Cache Object Manager.

Action: Contact Oracle Support.

OGG-01590: {1}: failed in call to: {0} error code: {2,number,0} ({3})

Cause: The calling internal function failed with the specified system error code. Examine the message text for the specific function and error code.

Action: This message can occur in many contexts. If it indicates a file system error, you might be able to resolve it yourself. If not, contact Oracle Support.

OGG-01591: {2}: failed in call to: {0} pool instance: {1,number,0}

Cause: An internal function failed.

Action: Contact Oracle Support.

OGG-01593: {0}: error code: {1,number,0} ({2})

Cause: The specified function failed with the given system error code.

Action: Contact Oracle Support.

OGG-01596: {2}: mmapc instance address: 0x{0} differs from base address: 0x{1}

Cause: An internal mapping error occurred.

Action: Contact Oracle Support.

OGG-01597: {1}: failed in call to: {0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01598: {1}: failed in call to: {0} error code: {2,number,0} ({3})

Cause: A library function call failed in the given function. This low-level error returns an exception to be handled at a higher level of code.

Action: Examine the error text, the error code, and any preceding related error messages. If a file system error occurred, determine if corrective action can be taken. If you cannot resolve the problem, contact GoldenGate Support.

OGG-01599: {2}: type: {0,number,0} subtype: {1,number,0}

Cause: An internal function failed.

Action: Contact Oracle Support.

OGG-01600: {1}: invalid mode: 0x{0}

Cause: The specified function has an invalid mode.

Action: Contact Oracle Support.

OGG-01601: {2}: memory map length: {0,number,0} differs from registered length: {1,number,0}

Cause: The specified length of the virtual memory map is not equal to its registered length.

Action: Contact Oracle Support.

OGG-01602: {0}: memory map out of space and extend operation failed

Cause: The virtual memory map could not be extended.

Action: Check the free swap size, and increase it if possible. If this message persists, contact Oracle Support.

OGG-01603: {0}: NULL data source pointer

Cause: The address of the internal virtual memory map is missing.

Action: Contact Oracle Support.

OGG-01604: {0}: cannot extend memory map: not marked for extend

Cause: An attempt has been made to extend a non-extendable virtual memory map. This low-level error returns an exception to be handled at a higher level of code.

Action: Contact Oracle Support.

OGG-01610: {0}: NULL dhv pointer found

Cause: An invalid bounded recovery redo state occurred.

Action: Contact Oracle Support.

OGG-01611: {0}: NULL object pointer found

Cause: An object necessary for Bounded Recovery is not present.

Action: Contact Oracle Support.

OGG-01612: {0}: NULL tag pointer found

Cause: A parameter necessary for Bounded Recovery is not present.

Action: Contact Oracle Support.

OGG-01613: {4}: NULL cache object pointer found: rc_co0: 0x{0} rc_co0->rst_co: 0x{1} rc_co1: 0x{2} rc_co1->rst_co: 0x{3},

Cause: A pointer to an object necessary for Bounded Recovery data persistence is not present.

Action: Contact Oracle Support.

OGG-01614: {5}: {0}: <{1,number,0}, {2,number,0}> <{3,number,0}, {4,number,0}>

Cause: A virtual memory map integrity error occurred.

Action: Contact Oracle Support.

OGG-01615: {7}: dhnode_map_traverse: {0} <{1,number,0}, {2,number,0}> (children: {3,number,0}, <{4,number,0}, {5,number,0}> (children: {6,number,0}))

Cause: A virtual memory map integrity error occurred.

Action: Contact Oracle Support.

OGG-01616: {7}: {0} dn: <{1,number,0}, {2,number,0}> (children: {3,number,0}, <{4,number,0}, {5,number,0}> (children: {6,number,0}))

Cause: An internal virtual memory map error occurred with a mismatch on node properties.

Action: Restart Extract. If the problem persists, contact Oracle Support.

OGG-01617: {7}: {0} <{1,number,0}, {2,number,0}> (len: {3,number,0}), <{4,number,0}, {5,number,0}> (len: {6,number,0})

Cause: The found length of child nodes in the virtual memory map does not match the expected length.

Action: Restart Extract. If the problem persists, contact Oracle Support.

OGG-01618: {4}: {0} <{1,number,0}, {2,number,0}> index: {3,number,0}

Cause: The virtual memory map node is invalid for the specified reason.

Action: Restart Extract. If the problem persists, contact Oracle Support.

OGG-01619: {7}: {0} <{1,number,0}, {2,number,0}>, <{3,number,0}, {4,number,0}> indexes: {5,number,0}, {6,number,0}

Cause: A virtual memory map integrity error occurred.

Action: Restart Extract. If the problem persists, contact Oracle Support.

OGG-01620: {3}: {0} <{1,number,0}, {2,number,0}>

Cause: An internal virtual memory map has an invalid type or subtype due to the condition specified in the error text.

Action: Restart Extract. If the problem persists, contact Oracle Support.

OGG-01621: {3}: {0} group type: {1,number,0} type found: {2,number,0}

Cause: An internal virtual memory map definition has an unterminated group entry.

Action: Restart Extract. If the problem persists, contact Oracle Support.

OGG-01622: {6}: count mismatch: HEADERS: in {0,number,0} found: {1,number,0} LEAFS: in {2,number,0} found {3,number,0} TERMINATORS: in {4,number,0} found: {5,number,0}

Cause: The recovery file did not pass the integrity check that the Bounded Recovery feature performs.

Action: None. Extract will revert to normal recovery for this recovery and then return to Bounded Recovery.

OGG-01623: {5}: count mismatch: processed_nodes: {0,number,0} found nodes: {1,number,0} (headers: {2,number,0} leafs: {3,number,0} terminators: {4,number,0})

Cause: The recovery file did not pass the integrity check that the Bounded Recovery feature performs.

Action: None. Extract will revert to normal recovery for this recovery and then return to Bounded Recovery.

OGG-01624: {1}: failed in call to: {0}

Cause: A library function call failed in the given function.

Action: Restart Extract. If the problem persists, contact Oracle Support.

OGG-01625: {2}: {0}: {1}

Cause: An attempt to compile an internal virtual memory map failed. A preceding error message should indicate the cause.

Action: Restart Extract. If the problem persists, contact Oracle Support.

OGG-01626: BOUNDED RECOVERY: Restore FAILED. {1}: {0}: error code: {2,number,0} ({3})

Cause: A Bounded Recovery file operation failed. The cause is indicated in the message text.

Action: Examine the file and directory to see if corrective action can be taken. If you cannot determine any file problems, restart Extract from the command line by using the BRRESET option of the BR parameter. For more information, see the BR parameter in the Oracle GoldenGate reference documentation. If the problem persists, contact Oracle Support.

OGG-01627: {2}: invalid file mode for: {0} mode: 0x{1}

Cause: The specified directory has an invalid permission mode.

Action: Change the directory permissions. If the problem persists, contact Oracle Support.

OGG-01628: {2}: rename({0}, {1}) error code: {3,number,0} ({4})

Cause: The rename of a stale Bounded Recovery file failed with the specified error.

Action: Try to resolve the file problem based on the error, and determine if it will occur for other Bounded Recovery files. If you cannot correct this problem, contact Oracle Support.

OGG-01629: BOUNDED RECOVERY: PERSISTED OBJECTS RECOVERED: {0}{1}

Cause: Extract successfully recovered the transaction data that was persisted to disk.

Action: None

OGG-01630: {4}: INVALID OBJECT COUNT: on OP list: {0,number,0} OP active count: {1,number,0} pool instance: {2,number,0} ({3})

Cause: The number of persisted objects expected for recovery differs from the actual number of long-running transactions that are detected. Bounded Recovery will resolve the difference or else revert to normal recovery.

Action: None

OGG-01631: BOUNDED RECOVERY: NEW VALID BR CHECKPOINT: {0}

Cause: Extract created a new Bounded Recovery checkpoint, concluding another Bounded Recovery interval (as determined by the BRINTERVAL option of the BR parameter.)

Action: None

OGG-01632: {4}: Active object count differs from count from previous instance BCP:

OP active count: {1,number,0} recovered count from previous BCP: {0,number,0} pool instance: {2,number,0} ({3})

Cause: Bounded Recovery detected an anomaly in the checkpoint and is using the previous Bounded Recovery checkpoint for recovery.

Action: None

OGG-01633: BOUNDED RECOVERY: NO VALID BCP FOUND: last file examined: {0}

Cause: Extract could not find a valid Bounded Recovery checkpoint, and will revert to normal recovery.

Action: None

OGG-01634: {2}: file operation failed in call to: {0}: filename {1}

Cause: Extract could not open the specified file, and will revert to normal recovery.

Action: None

OGG-01635: BOUNDED RECOVERY: reset to initial or altered checkpoint

Cause: The BR parameter contains the BRRESET option. Extract will use normal recovery for the current run and then turn on Bounded Recovery after the recovery is complete.

Action: None

OGG-01636: BOUNDED RECOVERY: DISABLED: error during its initialization.

Cause: Extract was unable to initiate a Bounded Recovery checkpoint, and is disabling Bounded Recovery. Extract will revert to normal recovery.

Action: None

OGG-01637: BOUNDED RECOVERY: DISABLED: error when creating its checkpoint

Cause: Extract was unable to create a Bounded Recovery checkpoint, and is disabling Bounded Recovery. Extract will revert to normal recovery.

Action: None

OGG-01638: BOUNDED RECOVERY: DISABLED: error restoring its checkpoint.

Cause: Extract was unable to recover from the expected checkpoint, and is disabling Bounded Recovery. Extract will revert to normal recovery.

Action: None

OGG-01639: BOUNDED RECOVERY: ACTIVE: for object pool {0,number,0}: {1}

Cause: Extract is reporting that Bounded Recovery is currently active.

Action: None

OGG-01640: BOUNDED RECOVERY: recovery start XID: {0}

Cause: Extract is reporting the ID of the transaction with which it will start Bounded Recovery.

Action: None

OGG-01641: BOUNDED RECOVERY: recovery start position: {0}

Cause: Extract is reporting the position in the transaction log where it will start Bounded Recovery.

Action: None

OGG-01642: BOUNDED RECOVERY: recovery end position: {0}

Cause: Extract is reporting the position in the transaction log where it finished its Bounded Recovery.

Action: None

OGG-01643: BOUNDED RECOVERY: CANCELED: for object pool {0,number,0}: {1}

Cause: The Bounded Recovery was abandoned, and Extract will revert to normal recovery.

Action: None

OGG-01644: BOUNDED RECOVERY: COMPLETE: for object pool {0,number,0}: {1} at {2}

-
- Cause:** Extract has completed the Bounded Recovery.
Action: None
- OGG-01645: For an initial load EXTRACT, the SOURCEDB parameter must specify a single APPLID**
Cause: This message is deprecated.
Action: None
- OGG-01646: Unexpected record type {1,number,0} encountered in file {0}**
Cause: This message is deprecated.
Action: None
- OGG-01647: File {0} column {1,number,0}, name length {2,number,0} exceeds maximum supported length {3,number,0}**
Cause: This message is deprecated.
Action: None
- OGG-01648: File {0} column {1}, will be set to data type character, sub data type binary. SYSADATA values: {2,number,0}, {3,number,0}, {4,number,0}**
Cause: This message is deprecated.
Action: None
- OGG-01649: Data set name {0} length {1,number,0} exceeds maximum length {2,number,0}**
Cause: This message is deprecated.
Action: None
- OGG-01650: FLDATA failed for file {0}**
Cause: This message is deprecated.
Action: None
- OGG-01651: Open failed: {0}, error {1,number,0}: {2}**
Cause: This message is deprecated.
Action: None
- OGG-01652: Open File Read Only failed: {0}, file may be empty**
Cause: This message is deprecated.
Action: None
- OGG-01653: Unexpected EOF encountered on {0}**
Cause: This message is deprecated.
Action: None
- OGG-01654: File {0} has no columns**
Cause: This message is deprecated.
Action: None
- OGG-01655: File {0} key start or end is not on a field boundary. The specified SYSADATA member does not match the specified file**
Cause: This message is deprecated.
Action: None

OGG-01656: File {0} type {1} is not supported

Cause: This message is deprecated.

Action: None

OGG-01657: Data set name {0} was not found in the criteria definition contained in the SOURCEDEFS file

Cause: This message is deprecated.

Action: None

OGG-01658: Criteria specification {0} {1} contains an unrecognized type {0}. Valid criteria types are FOR, USE and WHERE.

Cause: This message is deprecated.

Action: None

OGG-01659: Criteria specification {0} {1} type is out of sequence. Expecting USE type

Cause: This message is deprecated.

Action: None

OGG-01660: Criteria specification {0} {1} type is out of sequence. Expecting FOR or WHERE type

Cause: This message is deprecated.

Action: None

OGG-01661: An error occurred trying to position to the last criteria information record in the SOURCEDEFS file. The file may be empty.

Cause: This message is deprecated.

Action: None

OGG-01662: An invalid WHERE clause {0} was encountered. Expecting <column name>=<value>

Cause: Incorrect syntax was used to define a WHERE clause in a TABLE or MAP statement.

Action: See the permissible WHERE operators that are listed in the TABLE and MAP reference documentation, and then fix the syntax in the parameter file.

OGG-01663: An invalid quoted string was encountered in a criteria specification {0} {1}. Quoted strings are only valid for the value component of a WHERE clause. An embedded quote must be represented by a pair of quotes.

Cause: This message is deprecated.

Action: None

OGG-01664: Criteria value {0} is a duplicate for type {1}

Cause: This message is deprecated.

Action: None

OGG-01665: {0}

Cause: This message is deprecated.

Action: None

OGG-01667: {1}: process ID {0,number,0} waiting in sleep loop for diagnostician to attach debugger

Cause: When the _HANGATPROGRAMSTART internal option is specified, or the _HANGONFATALERROR internal option is used and a fatal error is encountered, Oracle GoldenGate will pause in order to allow point-in-time diagnosis.

Action: Remove the parameter from the parameter file and contact Oracle Support for additional assistance.

OGG-01668: PROCESS ABENDING

Cause: An unrecoverable error occurred and processing cannot continue.

Action: Examine previously issued error messages for possible causes and actions.

OGG-01669: Opening {0} (byte {1,number,0}, current EOF {2,number,0})

Cause: The Collector process is opening the specified file. Informational only.

Action: None

OGG-01670: Closing {0}

Cause: The Collector process is closing the specified file. Informational only.

Action: None

OGG-01671: Closing batch file {0} ({1})

Cause: The Collector process is closing the specified batch file. Informational only.

Action: None

OGG-01672: Opening batch file {0}

Cause: The Collector process is opening the specified batch file. Informational only.

Action: None

OGG-01673: Truncated {0}

Cause: The Collector process truncated the specified file. Informational only.

Action: None

OGG-01674: Executed system command "{0}" with status ({1,number,0})

Cause: The Collector process executed the specified system command. The return status is indicated. Informational only.

Action: None

OGG-01675: Terminating because extract is stopped

Cause: The Collector process terminated because its associated Extract terminated.

Action: If the Extract process abended (did not stop normally), look at the Extract report file for errors that may need to be resolved, and resolve them based on their message content.

OGG-01676: Terminating after client disconnect

Cause: The Collector process terminated because the associated Extract client disconnected.

Action: Look for problems with network connectivity between the source system that hosts Extract and the local system. Check the Extract report file for more errors that might help you diagnose and resolve the problem.

OGG-01677: Waiting for connection (started dynamically)

Cause: The Collector process was started by Manager and will find a free listening port dynamically. Informational only.

Action: None

OGG-01678: Listening for requests

Cause: The Collector process was started from the command line on a designated listening port. Informational only.

Action: None

OGG-01679: Connecting to {0}

Cause: The Collector process is verifying the connection to the remote system where a passive Extract or data pump is running. Informational only.

Action: None

OGG-01680: {0}

Cause: The specified number of bytes was received. This message appears when Oracle GoldenGate is in debug mode, as specified with the tcpstats parameter when Collector was started.

Action: Unless you need tcpstats on for debugging purposes, turn it off to improve performance.

OGG-01681: Allocated {0} on DD: {1}

Cause: This message is deprecated.

Action: None

OGG-01682: Deallocated {0} on DD:{1}

Cause: This message is deprecated.

Action: None

OGG-01688: Thread: {0}, Message: {1}

Cause: This is a generic error that forwards another message that contains errors from the Java Agent component of Oracle GoldenGate Monitor.

Action: If you cannot resolve the error that is returned based on the context, contact Oracle Support.

OGG-01689: Thread: {0}, Message: {1}

Cause: This is a generic error that forwards another message that contains errors from the Java Agent component of Oracle GoldenGate Monitor.

Action: If you cannot resolve the error that is returned based on the context, contact Oracle Support.

OGG-01690: Thread: {0}, Message: {1}

Cause: This is a generic error that forwards another message that contains errors from the Java Agent component of Oracle GoldenGate Monitor.

Action: If you cannot resolve the error that is returned based on the context, contact Oracle Support.

OGG-01693: Aborting BATCHSQL transaction{0,choice,0# | 1# in batch error mode}.

Cause: The batched SQL transaction encountered exceptions. Replicat will revert to normal processing (one operation at a time). For more information, see the BATCHSQL reference documentation.

Action: None

OGG-01702: Cannot get file status for '{0}'. Error {1,number,0} ({2})

Cause: While repairing a partial record at the end of a trail, the process could not get the status of the file.

Action: Contact Oracle Support.

OGG-01705: Input checkpoint position {2,number,0} for input trail file '{0}' is greater than the size of the file ({1,number,0}). Please consult Oracle Knowledge Management Doc ID 1138409.1. for instructions.

Cause: This inconsistency is caused by a disk or system failure during which data that was still in cache gets lost. The result is that the reader process (a data pump or Replicat) appears stalled waiting for more data. The writer process (Extract or data pump), when it performs its recovery, creates a new trail file and may write some of the data that has already been processed by the reader process.

Action: To avoid duplicate records, you need to perform a manual recovery, find the duplicate records, and alter the reader process to start processing after those records. See Oracle Knowledge Base solution 1138409.1 for instructions.

OGG-01706: Table {0} is an Index Organized Table (IOT) and only supported for Oracle 10gR2 and above.

Cause: This table type is not supported.

Action: Stop Extract. Edit the parameter file to remove the table and others of this type from the TABLE statements, and then restart Extract. (If TABLE uses a wildcard, you can exclude those tables with TABLEEXCLUDE.)

OGG-01707: Failed to retrieve the singleton instance of {0}

Cause: The metadata cache of the Oracle GoldenGate Monitor C-agent was not initialized properly.

Action: Contact Oracle Support.

OGG-01708: Failed to create an instance of {0}

Cause: The Oracle GoldenGate Monitor Java Agent was not installed properly, or the Java VM ran out of memory.

Action: Reinstall the Oracle GoldenGate Monitor Java Agent according to the instructions in the Oracle GoldenGate Monitor administration documentation.

OGG-01709: Failed to create an array of instances of {0}

Cause: The Oracle GoldenGate Monitor Java Agent was not installed properly, or the Java VM ran out of memory.

Action: Reinstall the Oracle GoldenGate Monitor Java Agent according to the instructions in the Oracle GoldenGate Monitor administration documentation.

OGG-01710: Failed to retrieve {0} from {1}

Cause: The metadata cache of the Oracle GoldenGate Monitor C-agent was not initialized properly.

Action: Contact Oracle Support.

OGG-01711: Failed to find the Java class ID of {0}

Cause: The Oracle GoldenGate Monitor Java Agent was not installed properly.

Action: Reinstall the Oracle GoldenGate Monitor Java Agent according to the instructions in the Oracle GoldenGate Monitor administration documentation. Make certain that the jagent.jar file exists in the dirjar directory.

OGG-01712: Failed to find the ID of method {1} in Java class {0}

Cause: The Oracle GoldenGate Monitor Java Agent was not installed properly.

Action: Reinstall the Oracle GoldenGate Monitor Java Agent according to the instructions in the Oracle GoldenGate Monitor administration documentation. Make certain that the jagent.jar file exists in the dirjar directory.

OGG-01713: Failed to retrieve the Java VM object

Cause: The Oracle GoldenGate Monitor Manager failed to load the Java VM or the Java VM that is loaded is invalid.

Action: Make certain that a supported version of Java is installed on the local system. For the supported Java versions, see the Oracle GoldenGate Monitor administration documentation.

OGG-01714: Failed to allocate memory for {0}

Cause: The Oracle GoldenGate Monitor C-agent failed to create a new Java object because the Java VM ran out of memory.

Action: Contact Oracle Support.

OGG-01715: Failed to call class {0} method {1}

Cause: The Oracle GoldenGate Monitor C-agent failed to call the Java Agent.

Action: Reinstall the Oracle GoldenGate Monitor Java Agent according to the instructions in the Oracle GoldenGate Monitor administration documentation. Make certain that the jagent.jar file exists in the dirjar directory.

OGG-01716: Failed to find the process {0} in the given process list

Cause: The specified Extract or Replicat process could not be found by Oracle GoldenGate Monitor.

Action: None. The process list will be refreshed in the next update interval.

OGG-01717: Failed to create a wrapper object {0} with the given object ID {1}

Cause: The Oracle GoldenGate Monitor C-agent detected an invalid monitoring point.

Action: Contact Oracle Support.

OGG-01718: Failed to retrieve {0} MpObjectInfo from loaded MP metadata

Cause: The Oracle GoldenGate Monitor C-agent detected an invalid monitoring point.

Action: Contact Oracle Support.

OGG-01719: Failed to load Metadata during initialization

Cause: Monitoring point metadata was not properly initialized in the Oracle GoldenGate Monitor C-agent.

Action: Contact Oracle Support.

OGG-01720: Failed to retrieve corresponding JNI type for {0}

Cause: The data type of a monitoring point in the Java agent is not consistent with the data type in the C-agent.

Action: Make certain that the version of the Java Agent is compatible with that of the C-agent, or contact Oracle Support.

OGG-01721: Failed to retrieve PseudoObjectProcAssociation object for object {0}.

Cause: A trail or database object that is maintained in the cache of the Oracle GoldenGate Monitor C-agent is invalid.

Action: Contact Oracle Support.

OGG-01722: Failed to retrieve input parameter {0} in {1} JNI invocation

Cause: An error occurred between the Java Agent and the C-agent because the JNI call parameter is not valid.

Action: Contact Oracle Support.

OGG-01723: Zero MPs returned for pseudo object {0}

Cause: The number of retrieved monitoring points for a trail or database object is not valid.

Action: Contact Oracle Support.

OGG-01724: Pseudo object {0} with associated process name {1} is not found

Cause: The metadata for the monitoring points that are maintained by the Oracle GoldenGate Monitor C-agent is inconsistent with the monitoring points that were captured by the Extract or Replicat process.

Action: Contact Oracle Support.

OGG-01725: Number of MPs {2,number,0} in Pseudo object list does not match the number of MPs {1,number,0} returned from the process {0}

Cause: The metadata for the monitoring points that are maintained by the Oracle GoldenGate Monitor C-agent is inconsistent with the monitoring points that were captured by the Extract or Replicat process.

Action: Contact Oracle Support.

OGG-01726: Failed to retrieve the singleton CprocessManager instance

Cause: An internal error occurred in the Oracle GoldenGate Monitor C-agent.

Action: Contact Oracle Support.

OGG-01727: Failed to retrieve the manager process from collectProcess call

Cause: An internal error occurred in the Oracle GoldenGate Monitor C-agent.

Action: Contact Oracle Support.

OGG-01728: MP id {0} should be in the form of objid:mpid

Cause: The monitoring point passed by the Java agent to the C-agent has an invalid format.

Action: Contact Oracle Support.

OGG-01729: Invalid In-Out type {0,number,0} for getMappedMpid call

Cause: The specified monitoring point is invalid.

Action: Contact Oracle Support.

OGG-01730: Appender '{0}' in configuration file '{3}' uses 'BinaryLayout' in a 'RollingFileAppender' with 'MaxFileSize' of {1}, which is smaller than the minimum of {2}.

Cause: The value for 'MaxFileSize' for a RollingFileAppender when BinaryLayout is used must be larger than the specified size.

Action: Correct the appender definition in the XML file.

OGG-01731: Appender '{0}' in configuration file '{1}' uses 'BinaryLayout' with filters, which is not supported

Cause: Filters are not supported with the BinaryLayout layout.

Action: Remove the Filter element.

OGG-01733: Trail file header file size value {2,number,0} for trail file '{0}' differs from the actual size of the file ({1,number,0}).

Cause: There is a discrepancy between the expected size of the trail file, as stated in the file header, and the actual size of the file. The file was truncated because there is a shortage of disk space or a corruption in the file system.

Action: Contact Oracle Support. Extensive recovery is needed to prevent data loss.

OGG-01735: Synchronizing {0} to disk

Cause: The specified trail file on the target was opened, closed, or rolled over. Informational only.

Action: None

OGG-01736: {2}: Buffer overflow, needed: {1,number,0}, allocated: {0,number,0}. Table {3}, column {4}.

Cause: A numeric conversion failed because the value in the archive logs has more digits than the specified column can contain.

Action: Verify that the column definitions are correct.

OGG-01737: Failed to validate table {0}. This table is an IOT with mapping table and not supported by Extract. Remove this table from Extract's parameter file and restart Extract.

Cause: This table type is not supported.

Action: Edit the parameter file to remove the table and others of this type from the TABLE statements, and then restart Extract. (If TABLE uses a wildcard, you can exclude those tables with TABLEEXCLUDE.)

OGG-01738: BOUNDED RECOVERY: CHECKPOINT: for object pool {0}: {1}.

Cause: A Bounded Recovery checkpoint was issued. Informational only.

Action: None

OGG-01739: {0} must be used with the {1} parameter in order to function correctly.

Cause: A required option or parameter is missing in the parameter file.

Action: Add the specified option or parameter to the parameter file. Stop the process, and then restart it again for the new configuration to take effect.

OGG-01740: Invalid numeric data detected and replaced by _ CONVERTBADNUMBER. Column {0}, table {1}, rowid {2}, row length {3,number,0}, rowdata: {4}

Cause: The redo data is corrupted. Either Extract assigned a zero value or a conversion was made (Oracle GoldenGate version 8 and later). This is a warning to alert you that data was converted.

Action: None

OGG-01741: Unexpected Log Sequence encountered at LSN {0,number,0}, previous log position {1,number,0}, current log position {2,number,0}.

Cause: The transaction records appear to be out of sequence.

Action: Contact Oracle Support with details of this message.

OGG-01742: Command sent to {0} {1} returned with {2,choice,-1#an ERROR | 0#an empty | 1#an invalid} response.

Cause: A command sent to Manager resulted in the specified error response. The expected response is either invalid data or an error indicator.

Action: Retry the command that caused the error. If it fails again, look at the process report file and the error log (and the Windows event browser if Manager is a Windows service) for errors generated before this message. These errors could indicate the cause and possible resolution. If you cannot resolve the error based on these logs, contact Oracle Support.

OGG-01745: Additional columns detected for table {0}. Change data processing may be less efficient until the table is reorganized.

Cause: An ALTER TABLE...ADD COLUMN command was issued to add one or more columns to the specified table.

Action: Reorganize the table to avoid the extra overhead in processing log data for this table. This will ensure that the before image for any future updates match the table definition.

OGG-01746: Support for parameter {0} is not available in the RDBMS version you are using.

Cause: The parameter is not supported for the database or database version (or both) that the associated Oracle GoldenGate process is connected to.

Action: Remove the parameter from the parameter file. See the Oracle GoldenGate documentation to find out if there is a similar parameter that is supported for the database or a specific release of the database.

OGG-01747: Error resetting AES cipher at trail file {0}, RBA {1,number,0} (error {2,number,0}, {3})

Cause: An error occurred while attempting to reset the AES cipher. This message is deprecated.

Action: None

OGG-01748: Error encrypting data record with AES cipher at trail file {0}, RBA {1,number,0} (error {2,number,0}, {3})

Cause: An error occurred while encrypting a data record with an AES cipher. This message is deprecated.

Action: None

OGG-01749: Successfully registered EXTRACT {0} to start managing log retention at SCN {1}.

Cause: An ADD EXTRACT or REGISTER EXTRACT command was issued to register the Extract group with the database to manage retention of the logs that Extract needs for recovery purposes.

Action: None

OGG-01750: Successfully unregistered EXTRACT {0} from database.

Cause: A DELETE EXTRACT or UNREGISTER EXTRACT command was issued to unregister the Extract group from the database.

Action: None

OGG-01751: Cannot register or unregister EXTRACT {0} because no database login was provided. Use DBLOGIN to establish a connection.

Cause: A REGISTER EXTRACT or UNREGISTER EXTRACT command was issued without first issuing a DBLOGIN command.

Action: Issue the DBLOGIN command, and then issue REGISTER EXTRACT or UNREGISTER EXTRACT again.

OGG-01752: Cannot register EXTRACT {0} with database because no database login was provided. You can manually register this group later with the REGISTER EXTRACT command with LOGRETENTION. Issue DBLOGIN first.

Cause: An ADD EXTRACT command was issued without first issuing a DBLOGIN command. This version of the RDBMS requires DBLOGIN before creating Extract groups.

Action: Issue the DBLOGIN command to log into the database, and then issue the REGISTER EXTRACT command with the LOGRETENTION option to register the Extract group.

OGG-01753: Cannot unregister EXTRACT {0} from database because no database login was provided. You can manually unregister this group later with the UNREGISTER EXTRACT command with LOGRETENTION. Issue DBLOGIN first.

Cause: A DELETE EXTRACT command was issued without first issuing a DBLOGIN command. This version of the RDBMS requires DBLOGIN before deleting Extract groups.

Action: Issue the DBLOGIN command to log into the database, and then issue the UNREGISTER EXTRACT command to unregister the Extract group.

OGG-01754: Cannot register or unregister EXTRACT {0} because the Extract is currently running. Stop the Extract and retry the command.

Cause: A REGISTER EXTRACT or UNREGISTER EXTRACT command was issued without first stopping the process.

Action: Stop the Extract process, then issue a DBLOGIN command, and then the REGISTER EXTRACT or UNREGISTER EXTRACT command.

OGG-01755: Cannot register or unregister EXTRACT {0} because of the following SQL error: {1}. See Extract user privileges in the Oracle GoldenGate for Oracle Installation and Setup Guide.

Cause: A REGISTER EXTRACT or UNREGISTER EXTRACT command was issued and an error occurred either while querying the database or when calling a PL/SQL procedure.

Action: Issue DBLOGIN with the appropriate privileges that are required for REGISTER EXTRACT or UNREGISTER EXTRACT. See the Oracle GoldenGate reference documentation.

OGG-01756: Cannot register EXTRACT {0} with database because of the following SQL error: {1}. See Extract user privileges in the Oracle GoldenGate for Oracle Installation and Setup Guide. You can manually register this group with the REGISTER EXTRACT command.

Cause: An ADD EXTRACT command was issued and an error occurred either while querying the database or when calling a PL/SQL procedure.

Action: Issue DBLOGIN with the appropriate privileges that are required for ADD EXTRACT, and then issue the REGISTER EXTRACT command for the Extract group. See the Oracle GoldenGate reference documentation.

OGG-01757: Cannot unregister EXTRACT {0} from database because of the following SQL error: {1}. See Extract user privileges in the Oracle GoldenGate for Oracle documentation. You can manually unregister this group with the UNREGISTER EXTRACT command.

Cause: A DELETE EXTRACT command was issued and an error occurred either while querying the database or when calling a PL/SQL procedure.

Action: Issue the DBLOGIN command with the appropriate privileges that are required for DELETE EXTRACT, and then issue the UNREGISTER EXTRACT command for the Extract group. See the Oracle GoldenGate reference documentation.

OGG-01758: This EXTRACT {0} is already registered with the database.

Cause: An ADD EXTRACT or REGISTER EXTRACT command was issued for an Extract group that is already registered with the database.

Action: None

OGG-01759: Cannot unregister EXTRACT {0} from database because this Extract is not currently registered.

Cause: An UNREGISTER EXTRACT command was issued for an Extract group that is not currently registered with the database.

Action: Make certain the correct Extract name was provided in the command.

OGG-01760: Ignoring REDO records for encrypted tablespace. This could cause data integrity issues.

Cause: The parameter _IGNORETSERECORDS is specified, and encrypted tablespace records were encountered in the redo log.

Action: Configure Extract to decrypt encrypted tablespace records. See DBOPTIONS with the DECRYPTPASSWORD parameter in the Oracle GoldenGate reference documentation.

OGG-01762: The Oracle GoldenGate Monitor service could not be started.

Monitoring might not be supported on this platform or the agent might not be installed correctly.

Cause: Oracle GoldenGate failed to load the required Java VM, or failed to start the Java Agent or C Agent module, or failed to start the service that publishes information on the monitoring points. Monitoring services will not be available.

Action: Make certain that Oracle GoldenGate Monitor is installed on a supported platform, and if so, reinstall the agent. See the administration documentation for instructions.

OGG-01763: Problem generating keys from password, error [{0}]

Cause: The shared secret in the Oracle Wallet and in the Oracle GoldenGate installation are not the same.

Action: Take appropriate action to make the shared secret the same in both places. For help, see the Oracle GoldenGate documentation for the Oracle database.

OGG-01764: Failed to un-wrap the key with password, error [{0}]

Cause: The shared secret in the Oracle Wallet and in the Oracle GoldenGate installation are not the same.

Action: Take appropriate action to make the shared secret the same in both places. For help, see the Oracle GoldenGate documentation for the Oracle database.

OGG-01765: Key digest generation failed, error [{0}]

Cause: The shared secret in the Oracle Wallet and in the Oracle GoldenGate installation are not the same.

Action: Take appropriate action to make the shared secret the same in both places. For help, see the Oracle GoldenGate documentation for the Oracle database.

OGG-01766: Invalid key digest generation failed

Cause: The shared secret in the Oracle Wallet and in the Oracle GoldenGate installation are not the same.

Action: Take appropriate action to make the shared secret the same in both places. For help, see the Oracle GoldenGate documentation for the Oracle database.

OGG-01767: Error in TSE decryption, error [{0}]

Cause: Transparent Data Encryption (TDE) data at the tablespace level was not decrypted properly.

Action: Contact Oracle Support.

OGG-01768: Incorrect integrity algorithm [{0}]

Cause: Transparent Data Encryption (TDE) column data was not decrypted properly. It is possible that DDL was performed on the affected table.

Action: If DDL is to be performed on an encrypted table, install and configure Oracle GoldenGate DDL support. For help see the Oracle GoldenGate documentation for the Oracle database and the Oracle GoldenGate administration documentation.

OGG-01769: Error in TDE decryption: [{0}]

Cause: Transparent Data Encryption (TDE) data at the tablespace level was not decrypted properly.

Action: Contact Oracle Support.

OGG-01770: Error decrypting column [{0}], table [{1}], encalg [{2}], intalg [{3}], salt [{4}], keylen [{5}]: {6}

Cause: Transparent Data Encryption (TDE) column data was not decrypted properly. It is possible that DDL was performed on the affected table.

Action: If DDL is to be performed on an encrypted table, install and configure Oracle GoldenGate DDL support. For help see the Oracle GoldenGate documentation for the Oracle database and the Oracle GoldenGate administration documentation.

OGG-01771: DBOPTIONS DECRYPTPASSWORD must be used to decrypt data that is encrypted with Transparent Data Encryption. Otherwise, contact Oracle Support to use TRANLOGOPTIONS with _IGNORETSERECORDS to skip the capture of tables in an encrypted tablespace.

Cause: Data that is encrypted with Transparent Data Encryption was encountered, but DBOPTIONS with the DECRYPTPASSWORD option is not used in the parameter file.

Action: To support TDE, specify the DBOPTIONS parameter with the DECRYPTPASSWORD option; to ignore TDE data, contact Oracle Support for more information about using TRANLOGOPTIONS with the internal option _IGNORETSERECORDS. To configure Oracle GoldenGate to support TDE, see the Oracle GoldenGate installation and setup documentation for the Oracle database, and see the Oracle GoldenGate administration documentation.

OGG-01772: TSE decryption error: {0}, keylen [{1}]

Cause: Transparent Data Encryption (TDE) data at the tablespace level was not decrypted properly.

Action: Contact Oracle Support.

OGG-01773: TSE record found to be greater than 64K

Cause: A buffer that contains Transparent Data Encryption (TDE) data is too big.
Action: Contact Oracle Support.

OGG-01774: The AIX Oracle library is missing routine 'ztpv52' and needs a patch in order to use TDE/TSE

Cause: The patch for the Oracle libraries that is required by Oracle GoldenGate to support Transparent Data Encryption (TDE) cannot be found.

Action: Apply Oracle Patch 10395645 to the source Oracle database. If you cannot find this patch on the My Oracle Support website (<https://support.oracle.com>), submit a service request (SR) and request a backport.

OGG-01775: TDE/TSE is not supported in this version of Oracle

Cause: Transparent Data Encryption is not supported for this version of the Oracle database.

Action: Either remove the parameters that relate to TDE from the Oracle GoldenGate parameter file, or upgrade and configure the database to a level that supports TDE.

OGG-01776: DBOPTIONS DECRYPTPASSWORD must be set in order to use TDE/TSE encrypted tables

Cause: Data that is encrypted with Transparent Data Encryption was encountered, but DBOPTIONS with the DECRYPTPASSWORD option is not used in the parameter file.

Action: To support TDE, specify the DBOPTIONS parameter with the DECRYPTPASSWORD option; to ignore TDE data, contact Oracle Support for more information about using TRANLOGOPTIONS with the internal option _IGNORETSERECORDS. To configure Oracle GoldenGate to support TDE, see the Oracle GoldenGate installation and setup documentation for the Oracle database, and see the Oracle GoldenGate administration documentation.

OGG-01777: Extract abended as it ran out of sequence numbers used to create TRAIL files. The maximum number of TRAIL files allowed is 999999.

Cause: Extract ran out of sequence numbers that it uses to create trail files.

Action: Contact Oracle Support

OGG-01778: Feature {0} unsupported on the current database version. Upgrade database version to {1} or higher.

Cause: The specified feature is not supported by Oracle GoldenGate for the current database version.

Action: Upgrade to at least the specified database version.

OGG-01779: Invalid specification on {0} command.

Cause: The specified command contains invalid input.

Action: Fix the invalid input. For help, see the Oracle GoldenGate reference documentation.

OGG-01780: Missing/Invalid argument(s) on {0} command.

Cause: Arguments that were provided for the specified command are either incomplete or invalid.

Action: Fix the invalid input. For help, see the Oracle GoldenGate reference documentation.

OGG-01781: Wildcard is not allowed on {0} command.

Cause: The specified command does not allow wildcards as input.

Action: Replace the wildcard with an explicit name specification. For help, see the Oracle GoldenGate reference documentation.

OGG-01782: Unknown command on {0}.

Cause: The specified command is invalid.

Action: Verify the syntax and then issue the command again. For help, see the Oracle GoldenGate reference documentation.

OGG-01783: Cannot verify existence of table function that is required to enable schema level supplemental logging, {0}.

Cause: The function that is used to enable schema level supplemental logging (ADD SCHEMATRANDATA command) is missing from the database.

Action: Apply Oracle Patch 10423000 to the source database.

OGG-01784: INFO SCHEMATRANDATA failed due to error during select start.

Cause: The SELECT statement that underlies the INFO SCHEMATRANDATA command failed.

Action: Try the command again. If the problem persists, contact Oracle Support.

OGG-01785: Schema level supplemental logging is enabled on schema {0}.

Cause: Schema-level supplemental logging is enabled for all objects in the specified schema, as the result of the ADD SCHEMATRANDATA command. Informational only.

Action: None

OGG-01786: Schema level supplemental logging is disabled on schema {0}.

Cause: Schema-level supplemental logging is disabled for the specified schema, as the result of the DELETE SCHEMATRANDATA command. Informational only.

Action: None

OGG-01787: INFO SCHEMATRANDATA failed on schema {0} because of the following OCI error: {1}-{2}

Cause: A OCI error prevented Oracle GoldenGate from getting information about schema-level supplemental logging through the INFO SCHEMATRANDATA command.

Action: Fix the OCI error and retry the INFO SCHEMATRANDATA command. If the OCI error cannot be resolved, contact Oracle Support.

OGG-01788: SCHEMATRANDATA has been added on schema {0}.

Cause: The ADD SCHEMATRANDATA command enabled supplemental logging for all objects in the specified schema. Informational only.

Action: None

OGG-01789: Failed to ADD SCHEMATRANDATA on schema {0}, because schema does not exist.

Cause: The schema that is specified in the ADD SCHEMATRANDATA command does not exist.

Action: Fix any typographical errors or create the schema, and then retry the command.

OGG-01790: Failed to ADD SCHEMATRANDATA on schema {0} because of the following SQL error: {1}

Cause: The specified SQL error prevented the ADD SCHEMATRANDATA command from enabling supplemental logging for the specified schema.

Action: Fix the SQL error and then retry ADD SCHEMATRANDATA.

OGG-01791: Failed to ADD SCHEMATRANDATA on schema {0} because of an internal error: {1}.

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01792: SCHEMATRANDATA has been deleted on schema {0}.

Cause: Schema-level supplemental logging is disabled for the specified schema, as the result of the DELETE SCHEMATRANDATA command. Informational only.

Action: None

OGG-01793: Failed to DELETE SCHEMATRANDATA on schema {0}, because schema does not exist.

Cause: The DELETE SCHEMATRANDATA command failed because the specified schema does not exist.

Action: Verify that the correct schema is specified in the command input, and try the command again.

OGG-01794: Failed to DELETE SCHEMATRANDATA on schema {0} because of the following SQL error: {1}

Cause: DELETE SCHEMATRANDATA failed because of the specified SQL error.

Action: Fix the SQL error and retry the command.

OGG-01795: Failed to DELETE SCHEMATRANDATA on schema {0} because of an internal error: {1}.

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-01796: Schema: {0}, does not exist.

Cause: The specified schema does not exist.

Action: Verify that the schema name is spelled correctly in the command or parameter input. Make certain that the schema still exists in the database.

OGG-01797: Table {0} column values will also be captured in native format: {1}

Cause: ADDNATIVE is used for the specified table in a TABLE statement. In this mode, Extract will also capture supported data values in their native format.

Action: None

OGG-01798: Native data for table {0}, column {1} is not consistent.

Cause: Replicat encountered native data for a column in one operation, but not another. This condition can occur when the '_ADDNATIVE' parameter is added to an Extract process without stopping and starting the associated Replicat processes.

Action: Restart Replicat. If the problem persists, contact Oracle Support.

OGG-01799: Unable to rename file "{0}" to "{1}" (error {2,number,0}, {3})

Cause: The process could not rename the specified file on the local file system. Oracle GoldenGate cannot continue.

Action: Correct the problem based on the operating system error message that is returned. If you cannot resolve the problem, contact Oracle Support.

OGG-01800: Unable to rename file "{0}" to "{1}" (error {2,number,0}, {3})

Cause: The process could not rename the specified file on the local file system. Oracle GoldenGate will continue processing.

Action: To avoid future warnings or possible failures related to this condition, correct the problem based on the operating system error message that is returned. If you cannot resolve the problem, contact Oracle Support.

OGG-01801: Failed to determine discard file name

Cause: An internal error occurred when trying to determine the name of the discard file.

Action: Contact Oracle Support.

OGG-01802: Discard file path name "{0}" is too long. Specify a name that is no more than 250 characters.

Cause: The fully qualified name of the discard file is longer than the 250 characters allowed.

Action: Change the DISCARDFILE parameter to specify a file name that is no more than 250 characters.

OGG-01803: {0} SCHEMATRANDATA option "{1}" is invalid. Valid options are: {2}.

Cause: An invalid option was specified for the ADD SCHEMATRANDATA or DELETE SCHEMATRANDATA command.

Action: See the Oracle GoldenGate Reference Guide for correct syntax.

OGG-01804: Option "{0}" is invalid. INFO SCHEMATRANDATA does not have options.

Cause: The INFO SCHEMATRANDATA command was issued with invalid options. This command takes no options.

Action: See the Oracle GoldenGate Reference Guide for correct syntax.

OGG-01805: Virtual memory allocation error: {0,number,0})

Cause: An attempt to allocate virtual memory failed.

Action: Contact Oracle Support.

OGG-01806: Virtual memory mmap allocation error: {0} (error: {1,number,0})

Cause: An attempt to allocate virtual memory failed.

Action: Contact Oracle Support.

OGG-01807: Virtual memory custom allocation error

Cause: An attempt to allocate virtual memory failed.

Action: Contact Oracle Support.

OGG-01808: Virtual memory file read error

Cause: An attempt to read a file failed.

Action: Contact Oracle Support.

OGG-01809: Virtual memory unmap error: {0} (error: {1,number,0})

Cause: An attempt to unmap virtual memory failed.

Action: Contact Oracle Support.

OGG-01810: Virtual memory custom deallocation error

Cause: An attempt to deallocate virtual memory failed.

Action: Contact Oracle Support.

OGG-01811: Virtual memory file write error

Cause: An attempt to write to a file failed.

Action: Contact Oracle Support.

OGG-01812: Virtual memory probe error: {0}

Cause: An attempt to probe virtual memory failed.

Action: Contact Oracle Support.

OGG-01813: invalid parameter

Cause: An invalid parameter was passed to the VMF constructor.

Action: Contact Oracle Support.

OGG-01814: file utility error: {0}: file: {1}: {2} (error: {3,number,0})

Cause: The specified file utility function failed.

Action: Contact Oracle Support.

OGG-01815: Virtual Memory Facilities for: {0} anon alloc: {1} anon free: {2} file alloc: {3} file free: {4} target directories: {5}

Cause: The virtual memory facilities for the specified module and directories have been determined. Informational only.

Action: None

OGG-01816: Partial operations are not supported in this release.

Cause: Partial LOB/XML update operations are not supported for this database source or target.

Action: Add FETCHPARTIALLOB/FETCHPARTIALXML option(s) as appropriate in the TRANLOGOPTIONS parameter in the Extract parameter file, and then restart Extract.

OGG-01817: The DataFormat token encountered, 0x{0}, in the trail is unknown.

Cause: The data format token in the trail record contains invalid data.

Action: Verify that the version of Extract and Replicat are compatible.

OGG-01818: XMLDiff data is missing, can not continue: table {0}.

Cause: XMLDiff data for a column was read from trail but did not get processed.

Action: It is an internal error. Contact support.

OGG-01819: Operation on table {0} with a deferrable constraint is not supported because a workspace is active.

Cause: A table with a deferrable constraint was modified in a transaction that has an open workspace for handling transient duplicates.

Action: Remove the deferrable constraint, and then restart the process.

OGG-01820: Could not enable workspace

Cause: An attempt to handle transient duplicates in an update statement failed.

Action: Restart Replicat. If the problem persists, grant privileges to the Replicat user by running the dbms_goldengate_auth.grant_admin_privilege procedure. Also resolve any associated errors, such as OCI session errors.

OGG-01821: DYNAMICPORTREASSIGNDELAY parameter has been deprecated. Value will be ignored.

Cause: The DYNAMICPORTREASSIGNDELAY parameter is not valid for the current Oracle GoldenGate version.

Action: Remove the DYNAMICPORTREASSIGNDELAY parameter from the parameter file.

OGG-01822: Invalid trail FORMAT RELEASE {0} is specified.

Cause: Invalid trail FORMAT RELEASE is specified.

Action: Specify the correct FORMAT RELEASE release, such as 10.4, 11.1, 11.2, 12.1 and 12.2.

OGG-01823: Invalid SHELL syntax: {0}. Shell command must be enclosed in parentheses or double quotes.

Cause: The command in EVENTACTIONS SHELL is not enclosed within parentheses or double quotes.

Action: Enclose the command within parentheses or double quotes.

OGG-01824: Resume processing from SUSPEND state for process {0}.

Cause: The process is resuming after an EVENTACTIONS SUSPEND state.

Action: None required.

OGG-01825: DDL operation ignored due to EMI [{0}], optype [{1}], objtype [{2}], objowner [{3}], objname [{4}]

Cause: The specified DDL operation was ignored according to the rule specified in EVENTACTIONS.

Action: None required.

OGG-01826: SPECIALRUN task type is no longer supported for Extract (capture).

Cause: SPECIALRUN as a task type has been removed from Extract processes.

Action: Remove SPECIALRUN task type as a declaring attribute for Extract processes.

OGG-01827: SPECIALRUN task type is no longer supported for Extract (capture).

Cause: SPECIALRUN as a task type has been removed from Extract processes.

Action: Remove SPECIALRUN task type as a declaring attribute for Extract.

OGG-01828: Trail FORMAT {0} or higher is required for operation {1}.

Cause: The EXTRAIL, RMTTRAIL parameter contains the FORMAT option, but the given RELEASE value does not support the specified operation.

Action: To support the specified operation type, set FORMAT RELEASE to at least the version shown in the error message. Note that the reader process (data pump or Replicat) must be at least the specified version.

OGG-01829: Archive log file {0} is truncated. Expected size {1,number,0} bytes, actual size {2,number,0} bytes

Cause: The size of the archive log file is smaller than the size given in the log file header.

Action: Replace the specified log file with one that has the correct size.

OGG-01830: LOGRETENTION is disabled by default in ARCHIVEDLOGONLY mode

Cause: ARCHIVEDLOGONLY is specified in the parameter file.
LOGRETENTION will be disabled by default.

Action: None required.

OGG-01831: Unable to select from sys.user\$ and sys.obj\$, using dba views instead. {0}

Cause: An OCI error occurred when accessing sys.user\$ and sys.obj\$.

Action: Read the detailed OCI error message and check whether privilege has been granted to access sys.obj\$ and sys.user\$.

OGG-01832: Failed to determine if the table is XMLType: table {0}.

Cause: An internal error occurred when trying to verify a table as XMLType.

Action: Contact Oracle Support.

OGG-01833: Missing OID value for table {0}.

Cause: An internal error occurred when processing an object table.

Action: Contact Oracle Support.

OGG-01835: No schema is specified for table {0} in statement '{1}'. Using default schema {2}.

Cause: A schema was not explicitly given in the specification for this table in the parameter file. The default login schema of the process is being used.

Action: To specify a schema other than the default login schema, edit the parameter file to specify the correct schema.

OGG-01836: No schema is specified for table {0} in statement '{1}'. No mapping will be applied.

Cause: A schema was not explicitly given in the specification for this table in the parameter file. No mapping will be applied.

Action: Specify a schema or add DBLOGIN parameter to use default schema. Edit the parameter file to specify the correct schema or add DBLOGIN parameter.

OGG-01837: Fetch requires database redo compatible version {0} or higher.

Cause: The specified database redo-compatible version does not support fetch.

Action: To support fetch, set the database redo-compatible version to at least the version shown in the error message.

OGG-01838: The internal token encountered, 0x{0}, in the trail is unknown.

Cause: The internal token in the trail record is unknown.

Action: Verify that the version of Extract and Replicat are compatible.

OGG-01839: RDBMS OCI Library does not support PARTIAL XML: table {0}.

Cause: RDBMS OCI Library does not support PARTIAL XML.

Action: A workaround is to use FETCHPARTIALXML option in Extract so that Replicat does not encounter PARTIAL XML.

OGG-01840: Internal error in forming SQL from PARTIAL XML: table {0}.

Cause: An internal error occurred while forming SQL from PARTIAL XML read from trail.

Action: A workaround is to use FETCHPARTIALXML option in Extract so that Replicat does not encounter PARTIAL XML. Contact Oracle support.

OGG-01841: {0}

Cause: CACHESIZE is below the valid minimum.

Action: Check the parameter file for an invalid CACHEMGR CACHESIZE setting. Check available swap space on the system. See CACHEMGR in the Oracle GoldenGate reference documentation for setting swap size.

OGG-01842: {0}

Cause: The virtual memory is below the recommended minimum.

Action: Check the swap space available on the system. See the CACHEMGR parameter in the Oracle GoldenGate reference documentation for the recommended swap size.

OGG-01843: {0}

Cause: An internal error occurred. Usually this message is logged along with other messages that provide more specific information. In some cases, the message text will indicate a cause and possible action.

Action: Contact Oracle Support.

OGG-01844: {0}

Cause: An internal error occurred. Usually this message is logged along with other messages that provide more specific information. In some cases, the message text will indicate a cause and possible action.

Action: Contact Oracle Support.

OGG-01845: {0}

Cause: A fatal mmap/MapViewOfFile error has occurred.

Action: Contact Oracle Support.

OGG-01846: {0}

Cause: A VMF (Virtual Memory Facilites) error occurred. See the message body for more details.

Action: Contact Oracle Support.

OGG-01847: {0}

Cause: A VMF (Virtual Memory Facilites) error occurred. See the message body for more details.

Action: Contact Oracle Support.

OGG-01848: cachemgr: filecaching: {0}

Cause: An error during CACHEMGR file caching has occurred. See the preceding error messages for the specifc cause.

Action: Contact Oracle Support.

OGG-01849: cachemgr: filecaching: {0}

Cause: An error during CACHEMGR file caching has occurred. See the preceding error messages for the specifc cause.

Action: Contact Oracle Support.

OGG-01850: CACHEMGR: invalid parameter: {0}

Cause: The CACHEMGR parameter is invalid.

Action: Refer to Oracle GoldenGate documentation for specification of the CACHEMGR parameter.

OGG-01851: filecaching started: thread ID: {0,number,0}

Cause: The filecaching thread was started.

Action: None

OGG-01852: cachemgr: filecaching: {0}

Cause: The CACHEMGR filecaching queue is in an invalid state.

Action: Contact Oracle Support.

OGG-01853: cachemgr: filecaching: {0}

Cause: An error occurred accessing the CACHEMGR temporary cache file.

Action: Contact Oracle Support.

OGG-01854: cachemgr: filecaching: {0}

Cause: An error occurred accessing CACHEMGR mbuf VM.

Action: Contact Oracle Support.

OGG-01855: cachemgr: filecaching: {0}

Cause: The CACHEMGR VM accounting is in an invalid state.

Action: Contact Oracle Support.

OGG-01856: cachemgr: filecaching: {0}

Cause: A threading error has occurred in the CACHEMGR filecaching.

Action: Contact Oracle Support.

OGG-01857: cachemgr: filecaching: {0}

Cause: An error occurred accessing the CACHEMGR temporary cache file.

Action: Contact Oracle Support.

OGG-01858: cachemgr: filecaching: {0}

Cause: An error occurred closing a CACHEMGR temporary cache file.

Action: Contact Oracle Support.

OGG-01859: cachemgr: tpos: {0}

Cause: An error occurred when an item that should be in memory was not found.

Action: Contact Oracle Support.

OGG-01870: The Operating System does not support IPv6 dual stack mode (error: {0,number,0}, {1}).

Cause: The system only has the IPv6 stack enabled or installed, or the IPv6 stack does not support dual stack mode.

Action: None

OGG-01871: Unexpected error fetching from table {0} - {1,number,0}

Cause: This is an internal error.

Action: Contact Oracle Support.

OGG-01872: Transaction delivery commencing with Transaction ID {0}, CSN {1}, {2,number,0} transaction(s) skipped.

Cause: A START EXTRACT command for a Primary Extract was issued with the ATCSN or AFTERCSN option. Extract is starting processing with the specified transaction in the trail. The number of transactions that were skipped is stated in the message.

Action: None

OGG-01873: The parameter TRANLOGOPTIONS PREPAREFORUPGRADETOIE has taken effect. Proceed to the next step in the upgrade process.

Cause: The parameter TRANLOGOPTIONS PREPAREFORUPGRADETOIE has taken effect and Extract is ready for the next step in the process to upgrade from Classic to Integrated Extract; applicable only when upgrading an Oracle RAC environment.

Action: None

OGG-01874: Unsupported trail FORMAT RELEASE {0} is specified.

Cause: Format release 9.0/9.5 or 10.0 is specified. These format releases are no longer supported.

Action: Specify the correct FORMAT RELEASE release, such as 10.4, 11.1, 11.2, 12.1 and 12.2.

OGG-01875: Classic Extract doesn't support RAC parallel direct load of table.

Cause: Oracle GoldenGate Classic Extract does not support parallel direct load with RAC.

Action: Switch to integrated Extract or remove the table from the Extract and Replicat configurations.

OGG-01876: Access to MGR is denied (request from {0}, rule #{1,number,0})

Cause: Access to Manager was denied to the specified address based on rules set in the ACCESSRULE parameter.

Action: Determine why the connection attempt was made. If it is legitimate, adjust the rules of ACCESSRULE.

OGG-01877: Missing explicit accessrule for server collector.

Cause: There was no explicit ACCESSRULE specified for SERVER.

Action: Only allow accessing SERVER from hosts where data pump(s) might send trail files to this host.

OGG-01878: Failed resolving ALLOWOUTPUTDIR {0} (error: {1,number,0}, {2})

Cause: Unable to locate the canonical path of the given directory.

Action: Resolve the reported error.

OGG-01879: ALLOWOUTPUTDIR {0} conflicts with reserved GoldenGate directory {1}

Cause: Specified ALLOWOUTPUTDIR entry is or is within a reserved path.

Action: Pick another directory.

OGG-01880: ALLOWOUTPUTDIR {0} is the same directory where this GoldenGate instance is installed.

Cause: Specified ALLOWOUTPUTDIR entry is the same directory as this Oracle GoldenGate installation. Note that no output files are allowed in GoldenGate home directory.

Action: None

OGG-01881: Output file {0} in the GoldenGate installation directory is not allowed.

Cause: The remote party requested to open an output file in the Oracle GoldenGate home directory.

Action: Specify a different output file directory in the remote data pump parameter file.

OGG-01882: Output file {0} is not in any allowed output directories.

Cause: The remote party requests to open an output file in some directory that is not specified by ALLOWOUTPUTDIR

Action: Specify a different output file directory in the remote data pump parameter file, or add that directory in GLOBALS by ALLOWOUTPUTDIR statement.

OGG-01883: Failed resolving output file {0} (error: {1,number,0}, {2})

Cause: Not able to locate the canonical path of the given file name.

Action: Resolve the reported error.

OGG-01884: Output file {0} is in a reserved GoldenGate directory {1}

Cause: Specified RMTTRAIL in data pump is or is within a reserved path.

Action: Specify another RMTTRAIL location.

OGG-01885: Starting a VERIDATA or VERIAGT process remotely through MGR is not allowed.

Cause: Starting a VERIDATA or VERIAGT process remotely through MGR is not allowed.

Action: None

OGG-01900: Key column {2} cannot be specified in {1} clause of {0}

Cause: A key column is specified in the ALLEXCLUDING clause of the MAP statement.

Action: Remove any key columns from the ALLEXCLUDING clause.

OGG-01901: Incompatible resolution {2} specified for {0}:{1}

Cause: An incompatible resolution was given for the specified conflict.

Action: Specify a valid resolution for this conflict. For valid resolutions per conflict type, see RESOLVECONFLICT Oracle GoldenGate reference documentation.

OGG-01902: Unsupported datatype for column {1} specified in {0} clause

Cause: An unsupported data type is specified in the COMPARECOLS clause of the MAP statement or the GETBEFORECOLS of a TABLE statement.

Action: Specify a column that has a supported data type. For supported data types, see the Oracle GoldenGate reference documentation.

OGG-01903: Column {2} for {0}:{1} previously used in prior conflict resolution

Cause: The same column is specified in more than one conflict resolution type.

Action: Select a different column or column group for each resolution type.

OGG-01904: Missing COLS clause for non-default conflict resolution {0}:{1}

Cause: The RESOLVECONFLICT parameter specifies a non-DEFAULT resolution, but does not contain a COLS clause.

Action: Specify a COLS clause for a non-default resolution. For help with syntax, see the Oracle GoldenGate reference documentation.

OGG-01905: Missing apply col list for non-default conflict resolution {0}:{1}

Cause: The RESOLVECONFLICT parameter specifies a non-DEFAULT resolution, but does not list columns in the COLS clause. For help with syntax, see the Oracle GoldenGate reference documentation.

Action: Specify one or more columns in a COLS clause for a non-default resolution. For help with syntax, see the Oracle GoldenGate reference documentation.

OGG-01906: Missing resolution column for conflict resolution {0}:{1}

Cause: The RESOLVECONFLICT parameter specifies a USEMIN or USEMAX resolution, but no resolution columns are specified. For help with syntax, see the Oracle GoldenGate reference documentation.

Action: Supply a resolution column for USEMIN or USEMAX resolution. For help with syntax, see the Oracle GoldenGate reference documentation.

OGG-01907: Null column {0} cannot be used in delta resolution

Cause: A null column was specified in the USEDELTA resolution in the RESOLVECONFLICT parameter.

Action: Replace USEDELTA with an appropriate resolution for null columns.

OGG-01908: Duplicate specification found for {0} conflict

Cause: A conflict type was specified more than once in a MAP statement.

Action: Remove duplicate conflict specification.

OGG-01909: Invalid ({2}) columns specified in {1} resolution of conflict {0}

Cause: An invalid number of resolution columns was specified for the chosen conflict type.

Action: Specify only one resolution column per conflict type.

OGG-01910: Missing apply columns in non-default conflict resolution {0}:{1}

Cause: A non-default resolution was specified in RESOLVECONFLICT, but the apply (target) columns are not specified.

Action: Specify at least one apply column in a non-default conflict resolution.

OGG-01911: Missing column specification in {1} option of {0}

Cause: Missing column in COMPARECOLS/GETBEFORECOLS option.

Action: Specify at least one column in the COMPARECOLS/GETBEFORECOLS option.

OGG-01912: Duplicate specification of {1} {2} clause in {0} parameter

Cause: Duplicate specification of a COMPARECOLS/GETBEFORECOLS clause in a MAP statement.

Action: Remove duplicate COMPARECOLS/GETBEFORECOLS clause.

OGG-01913: Duplicate {0} parameter found

Cause: Duplicate specification of a conflict resolution parameter in a MAP statement.

Action: Remove the duplicate parameter specification.

OGG-01914: Duplicate {1} resolution found for conflict {0}

Cause: A duplicate resolution name is specified for this conflict.

Action: Specify a unique name for each resolution.

OGG-01915: Missing DEFAULT resolution for conflict {0}

Cause: The specified conflict does not contain a DEFAULT resolution.

Action: Specify a DEFAULT resolution for this conflict in the RESOLVECONFLICT parameter.

OGG-01916: Missing or incomplete specification of resolution {1} for conflict {0}

Cause: The resolution for the specified conflict is missing or incomplete.

Action: Specify a valid resolution for this conflict. For valid resolutions per conflict type, see RESOLVECONFLICT Oracle GoldenGate reference documentation.

OGG-01917: Incorrect or incomplete specification of RESOLVECONFLICT {0}

Cause: The conflict clause of the RESOLVECONFLICT statement is incomplete.

Action: Specify a valid conflict for this RESOLVECONFLICT parameter. For help, see the Oracle GoldenGate reference documentation.

OGG-01918: Missing option {1} or incomplete specification of {0}

Cause: Missing or incomplete specification in COMPARECOLS/GETBEFORECOLS parameter.

Action: Specify valid COMPARECOLS and GETBEFORECOLS options. For help, see the Oracle GoldenGate reference documentation.

OGG-01919: Missing RESOLVECONFLICT for SQL error {0}

Cause: An apply conflict was detected, but the Replicat parameter file does not contain a RESOLVECONFLICT parameter to resolve it.

Action: Specify a matching RESOLVECONFLICT to enable conflict resolution.

OGG-01920: Missing COMPARECOLS column {0} in before image, while mapping to target table {1}. Add the column to GETBEFORECOLS.

Cause: The specified column is in a COMPARECOLS parameter, but is not specified with a GETBEFORECOLS parameter.

Action: Specify the column in a GETBEFORECOLS parameter in the Extract parameter file, so that before images are available for comparison.

OGG-01921: Missing GETBEFORECOLS with conflict detection enabled in target table {0}

Cause: The specified table has a RESOLVECONFLICT parameter, but the before columns required by COMPARECOLS are not specified with GETBEFORECOLS.

Action: Specify GETBEFORECOLS in the Extract parameter file so that before images are captured for COMPARECOLS.

OGG-01922: Missing RESOLUTION COLUMN {0} while mapping to target table {1}

Cause: The before image of the specified column is not available for the conflict resolution.

Action: Specify this column in a GETBEFORECOLS parameter in the Extract parameter file.

OGG-01923: Conflict resolution failed with SQL error {0} on original conflict with SQL error {1}

Cause: A conflict resolution failed with the specified SQL error.

Action: Identify the cause of the SQL error, and then restart Replicat.

OGG-01924: Missing parenthesis for {0}

Cause: The GETBEFORECOLS or COMPARECOLS parameter contains an invalid specification.

Action: Specify valid COMPARECOLS or GETBEFORECOLS options. For help, see the Oracle GoldenGate reference documentation.

OGG-01925: Ignoring redundant string {2} in {0} clause: {1}

Cause: A redundant string was found in the specified parameter.

Action: Remove the redundant string from the parameter.

OGG-01926: Cannot flush sequence {0}. Refer to the Oracle GoldenGate for Oracle documentation for instructions on how to set up and run the sequence.sql script. Error {1}

Cause: The sequence.sql script was not run properly to install the required Oracle database procedures that support FLUSH SEQUENCE.

Action: You must create a DDL user, configure Oracle GoldenGate to recognize this schema, create the procedures with the sequence.sql script, and assign privileges. Refer to Oracle GoldenGate for Oracle installation instructions.

OGG-01927: Child process started, process ID {0,number,0}, command line '{1}'

Cause: The specified Oracle GoldenGate child process was started.

Action: None

OGG-01928: Child process terminated {0,choice,0#successfully | 1#with exit code {0,number,0}}.

Cause: The specified Oracle GoldenGate child process was terminated.

Action: None

OGG-01929: Child process terminated with signal {0,number,0}

Cause: The specified Oracle GoldenGate child process was terminated with a signal.

Action: None

OGG-01931: Datastore '{0}' cannot be opened. Error {1,number,0} ({2})

Cause: The datastore environment cannot be opened.

Action: Verify the datastore is created with the GGSCI command INFO DATASTORE. To add the datastore use the GGSCI command CREATE DATASTORE. To repair an existing datastore stop all GoldenGate processes, including Manager, and issue the GGSCI command REPAIR DATASTORE. Contact Oracle Support if assistance is needed.

OGG-01932: Datastore already exists.

Cause: The datastore environment cannot be created because it already exists.

Action: None

OGG-01933: Datastore create failed.

Cause: The datastore environment cannot be created.

Action: Examine the accompanying warnings and contact Oracle Support if assistance is needed.

OGG-01934: Datastore repair failed.

Cause: The datastore environment cannot be repaired.

Action: To repair an existing datastore stop all GoldenGate processes, including Manager, and issue the GGSCI command REPAIR DATASTORE. If the issue persists contact Oracle Support.

OGG-01935: Error flushing file, handle: 0x{0}, err: {1,number,0} - {2}

Cause: The specified operating system error was returned when attempting to flush a file. This could be something you can resolve yourself, such as a disk failure, insufficient quota or a OS internal error. Otherwise, it probably is an internal Oracle GoldenGate error.

Action: If possible fix the operating system error, and then restart the process. If you cannot resolve the error, contact Oracle Support.

OGG-01936: Due to use of DDLERROR _SKIPDDL, DDL with marker sequence {0} was skipped.

Cause: DDLERROR _SKIPDDL was used to skip a DDL.

Action: None required.

OGG-01937: Extract is not configured to capture changes from thread {0}. To avoid data loss, the Extract must be dropped and recreated with the THREADS option to specify the correct number of RAC instances. See the Oracle GoldenGate administration documentation for the procedure to follow.

Cause: A redo thread was found that does not correspond to a known Extract producer thread. This occurs if the RAC configuration has more instances than were specified when ADD EXTRACT was issued.

Action: See the Oracle GoldenGate administration documentation for full procedure on changing the number of redo threads. You will: stop all processes, delete all processes, delete all trail files. Then: add back the primary Extract with THREADS set to the correct value, add back the local trail, add back the data pump, add back the remote trail, add back the Replicats, all with the same names as before. Then: start the processes.

OGG-01938: OBEY or INCLUDE file is not supported in parameter file {0}.

Cause: The parameter file specifies one or more OBEY or INCLUDE files. OBEY and INCLUDE are not supported.

Action: Remove the OBEY/INCLUDE statement from the parameter file or merge the contents.

OGG-01939: Invalid table name {0} specified by parameter {1} in parameter file {2}.

Cause: The specified table name is not valid.

Action: Correct the table name.

OGG-01940: Invalid schema name {0} specified by parameter {1} in parameter file {2}.

Cause: The specified schema name is not valid.

Action: Correct the schema name.

OGG-01948: Invalid or unsupported character set {0} specified in parameter file {1}.

Cause: An invalid or unsupported character set is specified with the CHARSET parameter.

Action: Specify a valid character set.

OGG-01949: CHARSET parameter is only supported on the first line of parameter file {0}.

Cause: The CHARSET parameter is not specified on the first line of the parameter file.

Action: Move the CHARSET parameter to the first line of the parameter file or remove it from the file.

OGG-01950: Invalid MACRO definition in the MACRO {0}. The END keyword is not specified.

Cause: The MACRO definition does not end with the END keyword.

Action: Add the END keyword.

OGG-01951: Invalid MACRO definition in the MACRO {0}. The macro body is not specified.

Cause: The MACRO definition does not contain a macro body.

Action: Add the macro body.

OGG-01952: Missing open parentheses in MACRO {0} definition.

Cause: A macro is defined in the parameter file, but an open parentheses is missing in PARAMS clause.

Action: Add the open parentheses.

OGG-01953: Missing close parentheses in MACRO {0} definition.

Cause: A macro is defined in the parameter file, but a close parentheses is missing in PARAMS clause.

Action: Add the close parentheses.

OGG-01954: Invalid macro name {{0} - must begin with {1}}

Cause: The name of the macro is not preceded by the macro character.

Action: Add the macro character that is shown in this error message. This character must precede all macro names.

OGG-01955: Unused parameter {1} in the MACRO {0} definition.

Cause: A macro is defined in the parameter file, but there is an unused parameter in the macro body text.

Action: Add the parameter to the macro body text or remove it from the macro body.

OGG-01956: Missing close parentheses in MACRO {0} invocation.

Cause: A macro is invoked in the parameter file, but a close parentheses is missing.

Action: Add the close parentheses.

OGG-01957: Missing open parentheses in parameter {0}.

Cause: An open parentheses is missing from the specified parameter.

Action: Add the open parentheses.

OGG-01958: Missing close parentheses in parameter {0}.

Cause: A close parentheses is missing from the specified parameter.

Action: Add the close parentheses.

OGG-01959: Failed to validate table {0}. The IOT is created with the COMPRESS option to use key compression. This is not supported by Oracle GoldenGate and prevents further redo capture.

Cause: The index-organized table is created with key compression. Oracle GoldenGate does not support IOTs with key compression.

Action: Remove the table from the Extract and Replicat configurations, and then restart the processes.

OGG-01962: OCI Error {1} (status = {0,number,0}). {2}

Cause: An error occurred in the OCI.

Action: Resolve the problem based on the error that is shown in this message. If you cannot resolve the problem, contact Oracle Support.

OGG-01963: Network address and service translation call {0} failed with error (return code = {1,number,0}, errno = {2,number,0}, {3})

Cause: A call to an operating system-provided API regarding network address and service translation failed.

Action: Check the operating system and network configuration for related problems, and resolve them or contact your system administrator. If you cannot resolve the problem, contact Oracle Support.

OGG-01964: No available socket on port {0}.

Cause: Failed to create a socket on the given port.

Action: Check the operating system and network configuration for related problems, and resolve them or contact your system administrator. If you cannot resolve the problem, contact Oracle Support.

OGG-01965: Failed to write checkpoint file {0}

Cause: The process could not write to the checkpoint file.

Action: Check the operating system privileges on the file, and make certain that the process has read and write privileges on it. Make certain the file is not corrupted. If the file remains unwritable, contact Oracle Support.

OGG-01966: AUTOSTART or AUTORESTART group type of '{0}' is invalid.

Cause: The group type for an AUTOSTART or AUTORESTART parameter must be one of ER, EXTRACT, REPLICAT, or JAGENT.

Action: Correct the group type. For more information, see the Oracle GoldenGate reference documentation.

OGG-01967: A supplemental logging group cannot be found for table {0}. Issue the ADD TRANDATA command or enable logging of all columns.

Cause: Extract could not find a supplemental log group for the specified table. Supplemental logging is required so that the values of key columns are available to Extract.

Action: Add a supplemental log group with the ADD TRANDATA command in ggsci or enable supplemental logging of all columns through the database. For more information about logging requirements, see the Oracle GoldenGate for Oracle documentation.

OGG-01968: The supplemental log group for table {0} does not contain all of the columns that Oracle GoldenGate expects to use as the key.

Cause: The supplemental log group for the specified table does not contain all of the key columns that are required by Oracle GoldenGate.

Action: Add a supplemental log group with the ADD TRANDATA command, or enable logging for all of the columns.

OGG-01969: Cannot find metadata property {0}. DDL metadata [{1}]

Cause: A metadata property that Oracle GoldenGate needs to resolve is not present.

Action: Upgrade the DDL trigger to the current version by running the ddl_setup script. For help, see the Oracle GoldenGate documentation for the Oracle database.

OGG-01970: Database is not in archiving mode. Extract may be forced to fetch LONG columns and may miss transaction data if the online logs are recycled.

Cause: The database is not in archiving mode. As a result, the redo log may not contain the full image of LONG columns and Extract may need to fetch the missing data to maintain data integrity. In addition, if capture lag is significant, Extract may miss transaction data if the online log recycles before required data can be captured.

Action: Stop Extract, enable archiving mode, then restart Extract.

OGG-01971: The previous message, '{0} {1}', repeated {2,number,0} times.

Cause: The previous message repeated the specified number of times but was suppressed from logging.

Action: None

OGG-01972: Extract will fetch all LONG columns because archiving mode is disabled.

Cause: Archiving mode is disabled. The redo log may not contain the complete image of LONG columns, so Extract must fetch LONG columns to maintain data integrity.

Action: Enable database archiving mode or use the TRANLOGOPTIONS parameter with the NOFORCEFETCHLONGCOLUMN option.

OGG-01973: The redo record indicates data loss on object {0}.

Cause: Logging of the specified object is not enabled.

Action: Enable logging on the object or use the TRANLOGOPTIONS parameter with the ALLOWDATALOSS option.

OGG-01974: Synchronizing file data to disk is disabled due to system error. (error: {0,number,0}, {1}).

Cause: A system call to synchronize the data of a file to disk failed. This feature has been turned off.

Action: None

OGG-01975: Failed to synchronize input trail to disk. (error: {0,number,0}, {1}).

Cause: A system call to synchronize the input trail to disk failed.

Action: Disable this feature by setting the internal parameter _NOSYNCSOURCETRAILONCHKPT. Contact Oracle Support for usage.

OGG-01976: SCHEMATRANDATA for scheduling columns has been added on schema {0}.

Cause: The ADD SCHEMATRANDATA command enabled supplemental logging for scheduling columns in all the objects in the specified schema. Informational only.

Action: None

OGG-01977: SCHEMATRANDATA for all columns has been added on schema {0}.

Cause: The ADD SCHEMATRANDATA command enabled supplemental logging for all columns in all the objects in the specified schema. Informational only.

Action: None

OGG-01978: SCHEMATRANDATA for all columns has been deleted on schema {0}.

Cause: The DELETE SCHEMATRANDATA command disabled supplemental logging for all columns in all the objects in the specified schema. Informational only.

Action: None

OGG-01979: SCHEMATRANDATA for scheduling columns has been deleted on schema {0}.

Cause: The DELETE SCHEMATRANDATA command disabled supplemental logging for scheduling columns in all the objects in the specified schema. Informational only.

Action: None

OGG-01980: Schema level supplemental logging is enabled on schema {0} for all scheduling columns.

Cause: Schema-level supplemental logging is enabled on all scheduling columns for the specified schema, as the result of the ADD SCHEMATRANDATA command. Informational only.

Action: None

OGG-01981: Schema level supplemental logging is enabled on schema {0} for all columns.

Cause: Schema-level supplemental logging is enabled on all columns for the specified schema, as the result of the ADD SCHEMATRANDATA command. Informational only.

Action: None

OGG-01982: Schema level supplemental logging is disabled on schema {0} for all columns.

Cause: Schema-level supplemental logging is disabled on all columns for the specified schema, as the result of the DELETE SCHEMATRANDATA command. Informational only.

Action: None

OGG-01983: COMPRESSDELETE parameter is ignored since LOGALLSUPCOLS has been specified.

Cause: LOGALLSUPCOLS parameter takes precedence over the parameter COMPRESSDELETES.

Action: None

OGG-01984: IGNOREUPDATEBEFORES parameter is ignored since LOGALLSUPCOLS has been specified.

Cause: LOGALLSUPCOLS parameter takes precedence over the parameter IGNOREUPDATEBEFORES.

Action: None

OGG-01985: Legacy Teradata session character set {0} is not 100% compatible with {2}. Use the new Teradata session character set {1} when possible.

Cause: The legacy Teradata session character set may not support the characters that are defined in the corresponding Windows code page.

Action: Use the new Teradata session character set.

OGG-01986: ODBC session character set of {0} does not match application code page of {1}.

Cause: The ODBC session character set is different from the application code page.

Action: Change ODBC session character set to match the Windows code page.

OGG-01991: Start Replicat from the command shell of the operating system when using the SHOWSYNTAX parameter.

Cause: The parameter file contains the SHOWSYNTAX parameter, but Replicat was started from GGSCI. To use SHOWSYNTAX, Replicat must be started from the command shell of the operating system.

Action: Remove SHOWSYNTAX or start Replicat from the command shell of the operating system.

OGG-01992: SHOWSYNTAX cannot be used with BATCHSQL. BATCHSQL is disabled.

Cause: The parameter file contains the SHOWSYNTAX parameter, which is not compatible with the BATCHSQL parameter. BATCHSQL is disabled.

Action: Remove SHOWSYNTAX to use BATCHSQL or specify the NOBATCHSQL parameter to use SHOWSYNTAX.

OGG-01993: Invalid maximum LOB size {0} specified for SHOWSYNTAX INCLUDELOB parameter.

Cause: An invalid number is specified for SHOWSYNTAX with the INCLUDELOB option.

Action: Specify a valid maximum LOB size or remove SHOWSYNTAX with INCLUDELOB and allow the use of a default maximum LOB size. For valid values, see the Oracle GoldenGate reference documentation for SHOWSYNTAX.

OGG-01994: Replicat is stopping because Stop was specified at the SHOWSYNTAX prompt and the NOAPPLY option is specified.

Cause: Stop was specified at the SHOWSYNTAX prompt. Because NOAPPLY is specified for SHOWSYNTAX, Replicat abends instead of applying the SQL.

Action: None

OGG-01995: Could not create a SQL statement for display, continuing replication.

Error detail: {0}.

Cause: Check the error message for error detail.

Action: Resolve the error that is displayed in the error detail, and then restart Replicat.

OGG-01996: The parameter {0} is no longer supported. Contact Oracle Support for assistance with a possible migration procedure.

Cause: The specified parameter option is no longer valid for the current release of Oracle GoldenGate.

Action: Remove the option from the parameter file. Consult the current release notes and documentation for any newer options or enhanced functionality that is related to this feature, and for any required migration steps, or contact Oracle Support.

OGG-01997: Failure processing command {0}. Error response: {1} cannot be sent to client in streaming mode.

Cause: There was a failure when processing a command received from network. The error message cannot be sent back to the requester in streaming mode, except during checkpoint time.

Action: Contact Oracle Support.

OGG-01998: Oracle GoldenGate received an external signal: {0,number,0}. Process shutting down gracefully.

Cause: A system signal to terminate a program was delivered to Oracle GoldenGate. The receiving process will shutdown gracefully.

Action: None

OGG-01999: Unknown error sending data over TCP. Ensure that the intended receiver program is running; for example, server or manager. Also, ensure that an adequate number of ports is defined with the DYNAMICPORTLIST parameter if one is being used.

Cause: A TCP/IP error occurred. The process will retry based on the tcppers file setting for retries.

Action: Ensure that the remote process is still running and that the number of ports requested do not exceed the number of ports defined in DYNAMICPORTLIST parameter. Check for any firewalls that forbid the connection, such as blocking certain ports or processes. Make certain that the RMTHOST parameter is configured correctly. Contact your Network Administrator if you cannot resolve the problem to rule out any other network issues before contacting Oracle Support.

OGG-02000: Ignoring option {0} because it is incompatible with an integrated capture configuration.

Cause: The specified option is not valid in an integrated capture configuration.

Action: Remove the incompatible option from the Extract parameter file.

OGG-02001: Ignoring integrated capture option {0} because it is incompatible with a classic capture configuration

Cause: The specified integrated capture option is not valid in a classic capture configuration.

Action: Remove the incompatible option from the Extract parameter file.

OGG-02002: Ignoring REGISTER LOGRETENTION because it is incompatible with an integrated capture configuration

Cause: REGISTER EXTRACT with LOGRETENTION is not necessary in an integrated capture configuration because log management is automatically enabled by REGISTER EXTRACT with the DATABASE option.

Action: None

OGG-02003: Extract {0} successfully registered with database at SCN {1}.

Cause: The specified Extract is now registered with the database to support integrated capture.

Action: Use ADD EXTRACT with INTEGRATED TRANLOG or ALTER EXTRACT with UPGRADE TO INTEGRATED TRANLOG to add or upgrade an Extract by the same name.

OGG-02004: This database lacks the required PL/SQL packages to support integrated capture

Cause: The database does not contain the PL/SQL packages that support integrated capture.

Action: Upgrade the Oracle database to a newer version.

OGG-02005: EXTRACT {0} already integrated

Cause: This Extract is already configured for integrated capture.

Action: None

OGG-02006: REGISTER EXTRACT {0} DATABASE must be performed before upgrading to integrated capture.

Cause: The REGISTER EXTRACT command was not issued.

Action: Issue the REGISTER EXTRACT <group> DATABASE command before you upgrade Extract to integrated capture. For help, see the GGSCI help or the Oracle GoldenGate reference documentation.

OGG-02007: Error retrieving current Extract checkpoint value

Cause: Extract failed to obtain the current checkpoint from the checkpoint file.

Action: Make certain the checkpoint file is available.

OGG-02008: Error retrieving Extract recovery checkpoint value

Cause: Extract failed to obtain the recovery checkpoint value from the checkpoint file.

Action: Make certain the checkpoint file is available.

OGG-02009: Extract checkpoint file contains invalid checkpoint type {0}.

Cause: An internal error occurred, or the checkpoint file is corrupted.

Action: Contact Oracle Support.

OGG-02010: Extract {0} is not ready to be upgraded because recovery SCN values are not set

Cause: Extract has not yet established any checkpoints.

Action: Issue this command again after waiting for Extract to write to its checkpoint file. To determine whether Extract established a checkpoint, use the INFO EXTRACT command with the SHOWCH option.

OGG-02011: Extract {0} is not ready to be upgraded because recovery SCN {1,number,0} has not reached SCN {2,number,0}

Cause: Extract has not yet established a checkpoint that is new enough for Extract to be upgraded.

Action: Issue the INFO EXTRACT command with the UPGRADE argument to determine whether Extract is ready to be upgraded, and then issue the ALTER EXTRACT command with the UPGRADE TO INTEGRATED TRANLOG argument to perform the upgrade. For syntax help, see the Oracle GoldenGate reference documentation or online GGSCI help.

OGG-02012: Extract {0} is ready to be upgraded to integrated capture

Cause: Extract can be upgraded to integrated capture.

Action: Issue the ALTER EXTRACT command with the UPGRADE TO INTEGRATED TRANLOG argument. For help with syntax, see the Oracle GoldenGate reference documentation or the GGSCI online help.

OGG-02013: Extract {0} successfully upgraded to integrated capture

Cause: Extract was successfully upgraded to integrated capture.

Action: None

OGG-02014: Extract {0} successfully downgraded from integrated capture

Cause: Extract was successfully downgraded from an integrated capture configuration.

Action: None

OGG-02015: Extract {0} is ready to be downgraded from integrated capture. Archive logs corresponding to SCN {1,number,0} and higher must be accessible by the downgraded extract

Cause: Extract can be downgraded from integrated capture.

Action: Issue the ALTER EXTRACT command with the DOWNGRADE FROM INTEGRATED TRANLOG argument. For help with syntax, see the Oracle GoldenGate reference documentation or the GGSCI online help.

OGG-02016: EXTRACT {0} is not configured for integrated capture

Cause: This Extract is downgraded from integrated capture and is now classic capture.

Action: None

OGG-02017: Extract {0} is not registered with this database

Cause: Extract cannot obtain registration information from this database.

Action: Make certain that you logged into the correct database from GGSCI.

OGG-02018: Invalid syntax for ALTER EXTRACT DOWNGRADE command

Cause: Invalid syntax was specified for the ALTER EXTRACT command with the DOWNGRADE option.

Action: The correct syntax is ALTER EXTRACT <group> DOWNGRADE FROM INTEGRATED TRANLOG. For additional information, see the Oracle GoldenGate reference documentation or the GGSCI online help.

OGG-02019: Invalid syntax for ALTER EXTRACT UPGRADE command

Cause: Invalid syntax was specified for the ALTER EXTRACT UPGRADE command.

Action: The correct syntax is ALTER EXTRACT <group> UPGRADE TO INTEGRATED TRANLOG. For additional information, see the Oracle GoldenGate reference documentation or the GGSCI online help.

OGG-02020: Unable to initialize connection to MININGDB because of error {0}

Cause: Logon to the database specified by MININGDB was successful, but the connection could not be initialized because of the reported error.

Action: Correct the error, and then restart the process.

OGG-02021: This database lacks the required libraries to support integrated capture

Cause: The database does not contain the libraries that support integrated capture.

Action: Upgrade the Oracle database to a newer version which supports integrated capture or check if environment variables LD_LIBRARY_PATH/LIBPATH are pointing to the location containing the right version of oracle libraries. For instructions, see the Oracle GoldenGate installation and setup guide for Oracle database.

OGG-02022: Logmining server does not exist on this Oracle database.

Cause: An logmining server cannot be found on this database.

Action: Make certain that you logged into the correct database from GGSCI.

OGG-02023: The attempt to stop logmining server failed

Cause: The logmining server could not be stopped because of the reported error.

Action: Correct the error, and then retry the operation.

OGG-02024: An attempt to gather information about the logmining server configuration from the Oracle database failed.

Cause: The specified error occurred when Extract tried to get information about the logmining server from the database.

Action: Correct the error and then retry the operation.

OGG-02025: Attempt to write rule checksum failed

Cause: The process failed to write a checksum for a filter rule.

Action: Make certain storage space is available on disk.

OGG-02026: Attempt to set checkpoint retention to value {0} failed

Cause: Extract failed to set checkpoint retention for the logmining server.

Action: Correct the error and then retry the operation.

OGG-02027: Attempt to start logmining server on Oracle database failed

Cause: The specified error occurred when Extract tried to start the logmining server.

Action: Fix the error, and then retry the operation.

OGG-02028: Failed to attach to logmining server {0}

Cause: The specified error occurred when Extract tried to attach to a logmining server.

Action: Fix the error, and then retry the operation.

OGG-02029: Failed to obtain global database name from source database because of the reported error.

Cause: The specified error occurred when Extract tried to query the global database name.

Action: Fix the error, and then retry the operation.

OGG-02030: Failed to set logmining server parameters back to default values

Cause: The specified error occurred when Extract tried to set logmining server parameters to the default values.

Action: Fix the error, and then retry the operation.

OGG-02031: Missing value for TRANLOGOPTIONS INTEGRATEDPARAMS ({0})

Cause: A TRANLOGOPTIONS INTEGRATEDPARAMS parameter was specified without a value.

Action: Specify a value. For help, see the Oracle GoldenGate reference documentation.

OGG-02032: Failed to set TRANLOGOPTIONS INTEGRATEDPARAMS {0}, {1})

Cause: A TRANLOGOPTIONS INTEGRATEDPARAMS parameter or value is invalid.

Action: Correct the parameter name or value. For help, see the Oracle GoldenGate reference documentation.

OGG-02033: Failed to clear filter rules

Cause: An error occurred when Extract tried to clear the filter rules for the logmining server.

Action: Fix the error, and then retry the operation.

OGG-02034: Failed to add include filter rule {0}

Cause: An error occurred when Extract tried to pass an inclusion filter rule to the logmining server.

Action: Fix the error, and then retry the operation.

OGG-02035: Failed to add exclude filter rule for {0}

Cause: An error occurred when Extract tried to pass an exclusion filter rule to the logmining server.

Action: Fix the error, and then retry the operation.

OGG-02036: Integrated capture successfully attached to logmining server {0}

Cause: Extract successfully attached to logmining server.

Action: None

OGG-02037: Failed to retrieve the name of a missing Oracle redo log.

Cause: An error occurred when Extract tried to retrieve the name of a missing Oracle redo log.

Action: Fix the error, and then retry the operation.

OGG-02038: Failed to create a logmining server ruleset

Cause: An error occurred when Extract tried to create a logmining server ruleset.

Action: Fix the error, and then retry the operation.

OGG-02039: Failed to set logmining server parameter {0} to value {1}.

Cause: An error occurred when Extract tried to set a logmining server parameter.

Action: Fix the error, and then retry the operation.

OGG-02040: Extract USERID or TRANLOGOPTIONS MININGUSER {0} does not match the logmining server connect user {1}

Cause: The Extract USERID or TRANLOGOPTIONS MININGUSER parameter does not match the user that issued DBLOGIN or MININGDBLOGIN and REGISTER EXTRACT.

Action: Make certain that the user shown in this message is the value given for USERID or TRANLOGOPTIONS MININGUSER.

OGG-02041: Failed to receive LCR record from logmining server.

Cause: An error occurred when Extract tried to get an LCR from logmining server.
Action: Fix the error, and then retry the operation.

OGG-02042: OCI Error {0}

Cause: An unexpected OCI error was returned.
Action: Fix the error, and then retry the operation.

OGG-02043: ID missing from SQUELXEC EXEC clause, id {0}. If an EXEC clause includes a schema name with the stored procedure name, ID is required due to bug 12989433. See the Oracle GoldenGate reference documentation for details.

Cause: Although ID is optional when SPNAME is present, a known issue documented in Bug 12989433 makes it required if SPNAME takes the form of schema.spname.

Action: To work around this issue, add a logical name with the ID option to the SQUELXEC statement. For syntax, see the Oracle GoldenGate reference documentation.

OGG-02044: Grouped transaction was aborted, most likely to use an Oracle workspace to handle a transient primary-key duplicate. Check for additional messages.

Cause: On encountering an ORA 00001 (unique constraint) error, Replicat disables its grouped transaction and then tries to handle transient primary-key duplicates to resolve the error. These are duplicates that occur temporarily during the execution of a transaction, but are resolved by transaction commit time. To do this, Replicat opens an Oracle workspace. See Bug 13105877 for more details.

Action: None

OGG-02045: Database does not have streams_pool_size initialization parameter configured.

Cause: The database initialization parameter streams_pool_size is not set correctly to support integrated capture.

Action: Set database initialization parameter streams_pool_size. For sizing recommendations, see the Oracle GoldenGate reference documentation.

OGG-02046: Not enough database memory to service current number of Extracts in integrated capture mode: {0}.

Cause: Not enough database memory configured for proper functioning of Extract in integrated capture mode.

Action: Increase database initialization parameter streams_pool_size. For sizing recommendations, see the Oracle GoldenGate reference documentation.

OGG-02047: Extract {0} can not be positioned to SCN {1,number,0}

Cause: Extract could not be positioned to the requested SCN.
Action: Issue the command again with a valid SCN.

OGG-02048: Extract {0} is ready to be downgraded from integrated capture. The THREADS option with a value of {2,number,0} or greater will be required. Archive logs corresponding SCN {1,number,0} and higher need to be accessible by the downgraded extract

Cause: Extract can be downgraded from integrated capture with the THREADS option.

Action: Issue the ALTER EXTRACT command with the DOWNGRADE FROM INTEGRATED TRANLOG argument and the THREADS option. For help with

syntax, see the Oracle GoldenGate reference documentation or the GGSCI online help.

OGG-02049: Extract in integrated capture mode failed to create or allocate an environment or error handle for the OCI session

Cause: There was an error when Extract made an OCI call to create or allocate handles.

Action: Restart Extract. If the problem persists, make sure there is enough system memory. If you cannot resolve the problem, contact Oracle Support.

OGG-02050: Not enough database memory to honor requested MAX_SGA_SIZE of {0}.

Cause: Not enough database memory configured for the MAX_SGA_SIZE specification in TRANLOGOPTIONS INTEGRATEDPARAMS.

Action: Increase the database initialization parameter streams_pool_size or allocate less memory to Extract. For sizing recommendations, see the Oracle GoldenGate reference documentation.

OGG-02051: Not enough database memory to service Extract in integrated capture mode.

Cause: There is not enough database memory to support the recommended amount for Extract in integrated capture mode.

Action: Increase the database initialization parameter streams_pool_size or allocate less memory to Extract by reducing the value of MAX_SGA_SIZE within the INTEGRATEDPARAMS option of the TRANLOGOPTIONS parameter. For sizing recommendations, see the Oracle GoldenGate reference documentation.

OGG-02052: This database lacks the required libraries to support integrated capture.

Cause: The database does not contain the libraries that support integrated capture.

Action: Contact Oracle Support.

OGG-02053: EXTRACT {0} failed to archive the current logfile on the source database because of the following SQL error: {1}. See Extract user privileges in the Oracle GoldenGate for Oracle Installation and Setup Guide.

Cause: A request for a redo logfile archive required for integrated capture configured in downstream mode failed, probably because of insufficient privileges.

Action: Manually archive the current redo logfile on the source database with the command 'alter system archive log current'. Check the Oracle GoldenGate for Oracle documentation to make certain the Extract privileges are set correctly.

OGG-02054: EXTRACT {0} failed to switch the current logfile on the source database because of the following SQL error: {1}. See Extract user privileges in the Oracle GoldenGate for Oracle Installation and Setup Guide.

Cause: A switch of the current redo logfile required for integrated capture in downstream mode failed, probably due to insufficient Extract privileges.

Action: Manually switch the current redo logfile on the source database with the command 'alter system switch logfile'. Check the Oracle GoldenGate for Oracle documentation to make certain the Extract privileges are set correctly.

OGG-02055: ARCHIVELOG mode must be enabled on this Oracle database

Cause: Integrated capture is not supported for this Oracle database because ARCHIVELOG mode is not enabled on this database.

Action: Enable ARCHIVELOG mode on this database, or do not use integrated capture.

OGG-02056: Oracle compatibility version {0} is not supported for integrated capture. Version {1} required.

Cause: Integrated capture can not be supported with the current Oracle compatible parameter setting for this database.

Action: See the Oracle GoldenGate reference documentation for help with required Oracle database compatible parameter setting requirements.

OGG-02057: The Oracle source database is not configured properly to support integrated capture.

Cause: Integrated capture can not be used with this Oracle database because it is not configured properly.

Action: Correct the specified error. Refer to the Oracle GoldenGate reference documentation for help with configuring the Oracle database.

OGG-02058: The Oracle source database is not configured properly to support integrated capture. The following configuration error must be fixed: {0}

Cause: Integrated capture can not be used with this Oracle database because it is not configured properly.

Action: Correct the specified error. Refer to the Oracle GoldenGate reference documentation for help with configuring the Oracle database.

OGG-02059: The Oracle mining database is not configured properly to support integrated capture.

Cause: Integrated capture can not be used with this Oracle database because it is not configured properly.

Action: Correct the specified error. Refer to the Oracle GoldenGate reference documentation for help with configuring the Oracle database.

OGG-02060: The Oracle mining database is not configured properly to support integrated capture. The following configuration error must be fixed: {0}

Cause: Integrated capture can not be used with this Oracle database because it is not configured properly.

Action: Correct the specified error. Refer to the Oracle GoldenGate reference documentation for help with configuring the Oracle database.

OGG-02061: User {0} does not have the required privileges to use integrated capture.

Cause: A user associated with this operation does not have enough Oracle database privileges.

Action: See the Oracle GoldenGate for Oracle Installation and Setup Guide for help with required user privileges.

OGG-02062: User {0} does not have the required privileges to use integrated capture

Cause: A user associated with this operation does not have enough Oracle database privileges.

Action: See the Oracle GoldenGate for Oracle Installation and Setup Guide for help with required user privileges.

OGG-02063: Oracle database version {0} is not supported for integrated capture. Version {1} required.

Cause: Integrated capture is not supported with this version of the Oracle database.

Action: See the Oracle GoldenGate for Oracle Installation and Setup Guide for help with supported Oracle database versions.

OGG-02064: Oracle compatibility version {0} has limited datatype support for integrated capture. Version {1} required for full support.

Cause: Integrated capture has limited datatype support with the current Oracle compatible parameter setting for this database.

Action: See the Oracle GoldenGate reference documentation for help with required Oracle database compatible parameter setting requirements.

OGG-02065: Integrated capture dictionary initialization in progress. State of logmining server: {0}

Cause: Integrated capture is waiting for the logmining server to start.

Action: None

OGG-02066: Integrated capture cannot find the redo logs that contain the dictionary build. State of logmining server: {0}

Cause: The logmining server cannot scan the redo logs because the redo files that contain the dictionary build cannot be found.

Action: Check the redo transport setting at the source database. For details, see the Oracle GoldenGate documentation for the Oracle database.

OGG-02067: This version of the Oracle library does not support the {0} option.

Cause: This version of Oracle library does not support the specified option.

Action: Specify a valid option for the Oracle library. For help, see the Oracle GoldenGate reference documentation.

OGG-02068: Integrated capture successfully attached to logmining server {0} using OGGCapture API

Cause: Extract successfully attached to logmining server using OGGCapture API.

Action: None

OGG-02069: Extract {0} is not ready to be downgraded because recovery SCN values are not set

Cause: Extract has not yet established any checkpoints.

Action: Issue this command again after waiting for Extract to write to its checkpoint file. To determine whether Extract established a checkpoint, use the INFO EXTRACT command with the SHOWCH option.

OGG-02070: Invalid syntax for REGISTER command

Cause: Invalid syntax was specified for the REGISTER command.

Action: For help with syntax, see the Oracle GoldenGate reference documentation or the GGSCI online help.

OGG-02071: Invalid syntax for UNREGISTER command

Cause: Invalid syntax was specified for the UNREGISTER command.

Action: For help with syntax, see the Oracle GoldenGate reference documentation or the GGSCI online help.

OGG-02072: The container list for REGISTER EXTRACT cannot be empty

Cause: The REGISTER EXTRACT command was issued with the DATABASE CONTAINER option, but no container list was supplied.

Action: Supply a container list for the DATABASE CONTAINER option. For help, see the GGSCI help or the Oracle GoldenGate reference documentation.

OGG-02073: WARNING: Parameter {0} is deprecated for Extract.

Cause: The specified parameter is deprecated for Extract.

Action: Remove the deprecated parameter.

OGG-02074: This database lacks the required patch to support V2 LCRCAPTUREPROTOCOL.

Cause: The function that is used to enable V2 LCRCAPTUREPROTOCOL is missing from the database.

Action: Refer to article 1411356.1 at the My Oracle Support website (<https://support.oracle.com>) to get the required Oracle patch.

OGG-02075: This database lacks the required PL/SQL package {0} to support switching LCRCAPTUREPROTOCOL.

Cause: The PL/SQL package that is used to switch the LCRCAPTUREPROTOCOL is missing from the database.

Action: Refer to the post-install steps of the patch readme file to get the required PL/SQL package.

OGG-02076: The Extract parameter value {0} cannot contain a wildcard character.

Cause: The parameter value contains a wildcard character. Wildcards are not supported for this parameter.

Action: Do not use wildcard characters for this parameter value.

OGG-02077: Extract encountered a read error in the asynchronous reader thread and is abending: {0}

Cause: An error occurred while reading the input data stream from the Logmining server.

Action: Contact Oracle Support.

OGG-02078: Extract encountered a fatal error in a processing thread and is abending

Cause: An error was reported in one of the subsidiary threads in Extract.

Action: Contact Oracle Support.

OGG-02079: Extract failed to login to the database as user {0} specified in the MININGUSER parameter because of error {1}

Cause: Logon to the database specified by MININGUSER failed because of the reported error.

Action: Correct the error, and then restart Extract.

OGG-02080: This database lacks the required PL/SQL package {0} to support switching LCRCAPTUREPROTOCOL.

Cause: The PL/SQL package that is used to switch the LCRCAPTUREPROTOCOL is missing from the database.

Action: Refer to the post-install steps of the patch readme file to get the required PL/SQL package.

OGG-02081: Detected duplicate TABLE/MAP entry for source table {0} and target table {1}. Using prior TABLE/MAP specification.

Cause: A duplicate target table mapping was detected. The source table is mapped to the target table twice or more.

Action: Correct the duplicate target table mapping or specify the ALLOWDUPTARGETMAP parameter in the Replicat parameter file to allow duplicate target table mapping.

OGG-02082: Unable to use {0} as input for the EXCLUDETAG parameter. A valid hex value is expected.

Cause: An invalid value was used as input for the EXCLUDETAG parameter.

Action: Specify a valid hex value as input for the EXCLUDETAG parameter, for example FF.

OGG-02083: DDLOPTIONS with ADDTRANDATA is no longer supported.

Cause: The parameter file contains the DDLOPTIONS parameter with the ADDTRANDATA option. This option is deprecated.

Action: Make certain that the ADD SCHEMATRANDATA command was used for each schema in the Extract configuration.

OGG-02084: Oracle database version {0} is not supported for integrated capture upgrade/downgrade. Version {1} required

Cause: Integrated capture upgrade/downgrade is not supported with this version of the Oracle database.

Action: Upgrade the Oracle database to at least the specified database version.

OGG-02085: The logmining server failed to locate a dictionary at scn {0}.

Cause: The logmining server failed to locate a dictionary at this scn number.

Action: Specify a valid scn number. For help, see the Oracle GoldenGate reference documentation. Contact Oracle Support.

OGG-02086: Integrated Dictionary will be used.

Cause: Extract is in integrated mode and is using the logmining server integrated dictionary.

Action: None

OGG-02087: TRANLOGOPTIONS BUFSIZE is too small. It must be greater than {0} bytes.

Cause: The internal buffer that holds the results of each read of the transaction log is too small to hold the data returned.

Action: Use the TRANLOGOPTIONS parameter with the BUFSIZE option to increase the buffer size.

OGG-02088: Drop container {0} failed: {1}

Cause: Failed to drop a container from xout server filter rule.

Action: Contact Oracle Support.

OGG-02089: Source redo compatibility version is: {0}.

Cause: The compatibility of the database is set to {0}.

Action: None

-
- OGG-02090: An invisible column named {0} was encountered in table {1}.{2}.**
Invisible columns are not supported in Oracle GoldenGate.
Cause: Invisible columns in tables are not supported by Oracle GoldenGate.
Action: Exclude the table from the Integrated Capture parameter file using the TABLEEXCLUDE parameter.
- OGG-02091: Operation not supported because enable_goldengate_replication is not set to true**
Cause: The enable_goldengate_replication system parameter is not set to true in the database. This parameter is required to support the attempted operation.
Action: Set the enable_goldengate_replication system parameter to true by executing the following command: alter system set enable_goldengate_replication=true;
- OGG-02092: Unexpected condition in {0} at line {1,number,0}. Index {2} out of range.**
Number of elements: {3}.
Cause: An internal error occurred. Index specified is out of range.
Action: Contact Oracle Support.
- OGG-02093: Unexpected condition in {0} at line {1,number,0}. Missing catalog name.**
Cause: An internal error occurred. Missing catalog name.
Action: Contact Oracle Support.
- OGG-02094: Failed to set environment variable {0}.**
Cause: The process could not set the environment variable that is specified with the SETENV parameter.
Action: Allocate enough memory space for operating system environment or contact Oracle Support.
- OGG-02095: Successfully set environment variable {0}.**
Cause: The process set the environment variable that is specified with the SETENV parameter.
Action: None
- OGG-02096: {0}**
Cause: This is a generic informational message that is used to report various different conditions with GGSCI commands.
Action: Take corrective action based on the message text. Look for related messages that were logged along with this message. If you cannot resolve the problem based on the context provided in the messages, contact Oracle Support.
- OGG-02097: LOB write size {0} is specified by the LOBWRITESIZE parameter, but the SKIPTEMPLOB parameter requires a minimum value of {1}. LOBWRITESIZE will be ignored.**
Cause: The parameter file includes the LOBWRITESIZE parameter, but the specified value does not meet the minimum required size for the SKIPTEMPLOB parameter.
Action: Remove the LOBWRITESIZE parameter or specify a value that is equal to, or greater than, the minimum required size of SKIPTEMPLOB.
- OGG-02098: {0} is not supported for integrated capture with Oracle version {1}. Version {2} required.**

Cause: The requested parameter for integrated capture can not be supported with the current Oracle version for this database.

Action: See the Oracle GoldenGate reference documentation for help with required Oracle database version setting requirements.

OGG-02099: The DBLOGIN and MININGDBLOGIN commands are both connected to the same database (database id: {0})

Cause: The MININGDBLOGIN command was used and connects to the same database as the DBLOGIN command.

Action: If you are configuring Integrated Extract in downstream capture mode, the DBLOGIN command must connect to a different database than the MININGDBLOGIN command. Otherwise, the source and mining connections may connect to the same database.

OGG-02100: Unexpected condition in {0} at line {1,number,0}. NULL session context is returned. User may not have sufficient privileges.

Cause: The Oracle GoldenGate process may not have the privileges that are required to perform the operation.

Action: If this is an Oracle multitenant container database, make certain the Oracle GoldenGate user has sufficient privileges to perform the operation. Consult the Oracle GoldenGate documentation for Oracle Database. If the problem persists, contact Oracle Support.

OGG-02101: OCILobGetChunkSize() returned with invalid handle or zero length: status {0}, chunk_size {1}, column {2} query {3}.

Cause: The Oracle Call Interface returned an unexpected error to Replicat when it queried for the LOB chunk size.

Action: Contact Oracle support.

OGG-02102: {0} option is not compatible with integrated capture.

Cause: The specified option is not valid in an integrated capture configuration.

Action: Remove the incompatible option from the Extract parameter file.

OGG-02103: Invalid COLCHARSET clause {0}.

Cause: The COLCHARSET clause syntax is invalid.

Action: Use valid syntax for the COLCHARSET clause.

OGG-02104: Missing character set in COLCHARSET clause {0}.

Cause: The character set parameter is missing from the COLCHARSET clause.

Action: Specify a character set for the COLCHARSET clause.

OGG-02105: Invalid character set {1} in COLCHARSET clause {0}.

Cause: The character set parameter in the COLCHARSET clause is invalid.

Action: Specify a valid character set for the COLCHARSET clause.

OGG-02106: Invalid column name {1} for table {2} in COLCHARSET clause {0}.

Cause: The column name parameter in the COLCHARSET clause is invalid.

Action: Specify a valid column name for the COLCHARSET clause.

OGG-02107: COLCHARSET PASSTHRU is specified. Ignoring the source database character set for the table {0}, column {1}.

Cause: COLCHARSET PASSTHRU parameter is specified, which directs the process to pass the data as it exists in the trail record, without performing character set conversion for the specified columns.

Action: None

OGG-02108: The source column character set {0} is specified with the COLCHARSET paramter for the table {1}, column {2}.

Cause: The COLCHARSET parameter is specified and assumed as the column character set.

Action: None

OGG-02109: Invalid CHARSET clause {0}.

Cause: The CHARSET clause syntax is invalid.

Action: Use valid syntax for the CHARSET clause.

OGG-02110: Missing character set in CHARSET clause {0}.

Cause: The character set parameter is missing from the CHARSET clause.

Action: Specify a character set for the CHARSET clause.

OGG-02111: Invalid character set {1} in CHARSET clause {0}.

Cause: The character set parameter in the CHARSET clause is invalid.

Action: Specify a valid character set for the CHARSET clause.

OGG-02112: CHARSET PASSTHRU is specified. Ignoring the source database character set for the table {0}, column {1}.

Cause: CHARSET PASSTHRU parameter is specified, which directs the process to pass the data as it exists in the trail record, without performing character set conversion for the character type columns of the specified table.

Action: None

OGG-02113: The source table character set {0} is specified with the CHARSET paramter for the table {1}, column {2}.

Cause: The CHARSET parameter is specified and assumed as the character type column character set of the specified table.

Action: None

OGG-02114: Ignoring COLCHARSET parameter for the table definition file format.

Cause: The COLCHARSET parameter is specified for the incompatible table definition file format.

Action: Specify the table definition file format release 12.1 or later, or remove the COLCHARSET parameter from TABLE clause.

OGG-02115: Ignoring CHARSET parameter for the table definition file format.

Cause: The CHARSET parameter is specified for the incompatible table definition file format.

Action: Specify the table definition file format release 12.1 or later, or remove the CHARSET parameter from TABLE clause.

OGG-02116: Both USEIPV4 and USEIPV6 have been set, but only one should be set. Ignoring USEIPV6 and using USEIPV4, which means only IPv4 will be used.

Cause: In the parameter file both USEIPV4 and USEIPV6 have been set, but only one of them should be set. The USEIPV6 parameter will be ignored and IPv4 will be used.

Action: None

OGG-02117: Parsing error, unexpected token {2} at line {0} column {1}. Expecting token {3}.

Cause: Parser encountered unexpected token.

Action: Contact Oracle Support.

OGG-02118: Parsing error, no viable alternative token {2} at line {0} column {1}.

Cause: Parser encountered no viable alternative token.

Action: Contact Oracle Support.

OGG-02119: Parsing error, missing token {2} element at line {0} column {1}.

Cause: Parser encountered missing token element.

Action: Contact Oracle Support.

OGG-02120: Parsing error, unquoted token {2} at line {0} column {1}.

Cause: Parser encountered unquoted token.

Action: Contact Oracle Support.

OGG-02121: Parsing error, token {2} syntax error at line {0} column {1}.

Cause: Parser encountered syntax error.

Action: Contact Oracle Support.

OGG-02122: Invalid object name {0}.

Cause: The object name is in invalid format.

Action: Specify the object name in correct format.

OGG-02123: The CHARMAP clause does not contain the name of a character mapping file.

Cause: The parameter file contains a CHARMAP clause that does not contain the name of a character mapping file.

Action: Specify a name for the character mapping file in the CHARMAP clause.

OGG-02124: The CHARMAP clause contains an unsupported parameter {0}.

Cause: The CHARMAP clause contains a parameter that is not supported.

Action: Correct the syntax and then restart the process. For syntax help, see the Oracle GoldenGate reference documentation.

OGG-02125: Could not open the character mapping file {0} specified in the CHARMAP clause.

Cause: The character mapping file could not be opened.

Action: Make certain that the name of the character mapping file is correct, that the file exists, and that Oracle GoldenGate has permission to open it in the operating system. Make corrections based on your findings.

OGG-02126: No valid parameter or command found in the parameter {0} in the character mapping file {1}.

Cause: An invalid command or parameter was found in the character mapping file.

Action: Review and fix the specified parameter in the character mapping file.

OGG-02127: The parameter {0} is specified two or more times in the character mapping file {1}. Remove all but one instance of it.

Cause: The specified parameter is specified multiple times. Only one character set can be specified for this parameter.

Action: Edit the parameter so that only one character set is specified.

OGG-02128: No character set is specified for the parameter {0} in the character mapping file {1}.

Cause: The character set is missing from the character set parameter of the character mapping file.

Action: Specify a character set.

OGG-02129: No character set is specified for the {0} parameter in the character mapping file {1}.

Cause: The parameter that specifies the character set is missing from the character mapping file.

Action: Specify a character set parameter. For help, see the Oracle GoldenGate reference documentation for CHARMAP.

OGG-02130: Invalid or unknown character set {0} for the character set parameter {1} in the character mapping file {2}.

Cause: An invalid or unknown character set is specified for the character set parameter in the character mapping file.

Action: Specify a correct character set.

OGG-02131: The character mapping file {0} does not contain a character mapping definition and will be ignored.

Cause: A CHARMAP parameter exists in the parameter file, but the character mapping file does not contain a character mapping definition.

Action: Remove the CHARMAP parameter or define a character mapping in the character mapping file.

OGG-02132: Invalid character mapping defintion {0} in the character mapping file {1}.

Cause: The format of the character mapping definition is invalid.

Action: Specify a valid character mapping definition. For help with syntax, see the Oracle GoldenGate reference documentation.

OGG-02133: Invalid code point range specified for the character mapping definition {0} in the character mapping file {1}.

Cause: The code point range in the character mapping specification is invalid. The start code point is larger than the end code point.

Action: Specify a valid character code point range.

OGG-02134: The source code point does not match the target code point for the character mapping definition {0} in character mapping file {1}.

Cause: The numbers specified for the source and target code points do not match.

Action: Specify a valid character code point range.

OGG-02135: Could not map the source character set {0} code point {1} to the target character set {2} code point {3} specified by the character mapping definition {4} in the character mapping file {5}.

Cause: The source or target code point of the character mapping defintion is incompatible with the character set.

Action: Specify the correct character mapping definition.

OGG-02136: The character mapping override is not supported for the source character set {0} and the target character set {1}.

Cause: The character mapping override is not available for the source or target character set.

Action: Remove the CHARMAP clause from the parameter file.

OGG-02137: The data pump requires a DDL history table. None found.

Cause: A data pump that makes a database connection must have access to a DDL history table if DDL replication is enabled. No history table was found.

Action: You can either convert the primary Extract to classic capture mode, also known as trigger-based capture, or you can add the PASSTHRU parameter to the parameter file of the data pump. For more information about PASSTHRU, see the Oracle GoldenGate reference documentation.

OGG-02138: Extract has encountered an unsupported LCR. This LCR will not be replicated. origop:{0} reason:{1} scn:{2} obj_id:{3} rba:{4} xid:{5,number,0}.{6,number,0}.{7,number,0}

Cause: Redo logs do not contain required data to support replication of this LCR.

Action: Check that nologging keyword is not used in the query and/or force logging is enabled in the database.

OGG-02139: Extract has encountered an unsupported LCR. Extract will abend. origop:{0} reason:{1} scn:{2} obj_id:{3} rba:{4} xid:{5,number,0}.{6,number,0}.{7,number,0}

Cause: Redo logs do not contain required data to support replication of this LCR.

Action: Check that nologging keyword is not used in the query and/or force logging is enabled in the database and restart Extract.

OGG-02140: The ETOLDFORMAT trail is no longer supported.

Cause: The trail format is in Oracle GoldenGate version 7.0 or earlier version format and is no longer supported.

Action: Upgrade the extract or use the newer trail file format.

OGG-02141: Unable to initialize fetch database connection specified by the FETCHUSERID parameter because of error {0}.

Cause: Logon to the fetch database specified by the FETCHUSERID parameter was successful, but the connection could not be initialized because of the reported error.

Action: Correct the error, and then restart the process.

OGG-02142: FETCHUSERID parameter is only supported when Extract is configured in Integrated Capture mode.

Cause: FETCHUSERID parameter was specified in the Extract parameter file, but Integrated Capture mode is not configured.

Action: Remove the FETCHUSERID parameter from the Extract parameter file or configure Extract to use Integrated Capture.

OGG-02143: Unable to obtain fetch database information specified by the FETCHUSERID parameter because of error {0}.

Cause: Logon to the fetch database specified by the FETCHUSERID parameter was successful, but the connection could not be used to obtain database information.

Action: Correct the error, and then restart the process.

OGG-02144: The fetch database specified by the FETCHUSERID parameter must be to an Active Data Guard database.

Cause: The connection information supplied by the FETCHUSERID parameter does not point to an Active Data Guard database.

Action: Remove the FETCHUSERID parameter or correct the login information.

OGG-02145: Failed to obtain global database name from the fetch database specified by the FETCHUSERID parameter because of the reported error.

Cause: The specified error occurred when Extract queried the global database name from the fetch database.

Action: Fix the error, and then restart Extract.

OGG-02146: The fetch database specified by the FETCHUSERID parameter must be to an Active Data Guard of the source database.

Cause: The connection specified by the FETCHUSERID parameter is an Active Data Guard database, but not for the source database connection specified by the USERID parameter.

Action: Correct the FETCHUSERID parameter connection options.

OGG-02147: Waiting for fetch database to process beyond SCN {1}. Current SCN is {0}.

Cause: Extract is waiting to fetch from the fetch database because it has not processed far enough.

Action: None

OGG-02148: Extract failed to login to the fetch database as user {0} specified in the FETCHUSERID parameter because of error {1}.

Cause: Logon to the database specified by FETCHUSERID parameter failed because of the reported error.

Action: Correct the error, and then restart Extract.

OGG-02149: Standby database has made no progress for more than {0} seconds.

Cause: Extract is abending because the Active Standby Database has not been applying redo changes from the source database and has reached its timeout threshold.

Action: Correct the problem on the Active Data Guard standby database or increase the Extract timeout threshold by setting parameter DBOPTIONS FETCHTIMEOUT if using Integrated Capture or TRANLOGOPTIONS ADGTIMEOUT if using Classic Extract.

OGG-02150: Standby database has made no progress for more than {0} seconds because the Oracle Managed Redo Process(MRP) is not running on the Standby database.

Cause: Extract is abending because the Active Standby Database has not been applying redo changes from the source database and has reached its timeout threshold.

Action: Start the Oracle Managed Redo Process (MRP) or increase the Extract timeout threshold by setting parameter DBOPTIONS FETCHTIMEOUT if using Integrated Capture or TRANLOGOPTIONS ADGTIMEOUT if using Classic Extract.

OGG-02151: Oracle Managed Redo Process(MRP) is not running on the Standby database.

Cause: Oracle Managed Redo Process(MRP) is not running.

Action: Start the Oracle Managed Redo Process (MRP).

OGG-02152: Oracle Managed Redo Process(MRP) has been restarted on the Standby database.

Cause: Oracle Managed Redo Process(MRP) was down, but is now running.

Action: None

OGG-02153: Fetch database has processed beyond required SCN {1}. Current SCN is {0}. Extract processing resumed.

Cause: Extract has finished waiting to fetch from the fetch database because it has processed far enough.

Action: None

OGG-02154: Skipping Conflict detection resolution for partial_lob_data.

Cause: A table has a partial_lob_data, which cannot be processed by CDR.

Action: None

OGG-02155: Skipping Conflict detection resolution for xmldiff_data.

Cause: A table has an xmldiff_data, which cannot be processed by CDR.

Action: None

OGG-02156: Unexpected data source function call without data source intialization.

Cause: An internal error occurred. The data source is not initialized properly.

Action: Contact Oracle Support.

OGG-02157: Could not retrieve the logtrail next checkpoint.

Cause: Could not retrieve or find the logtrail checkpoint.

Action: Ensure that the checkpoint file exists with accessible permissions. Contact Oracle Support.

OGG-02158: The mining database character set {0} is not compatible with the source database character set {1}

Cause: The mining database character set is not AL32UTF8 or a superset of the source database character set.

Action: Connect to the mining database and alter its database character set to AL32UTF8.

OGG-02159: The mining database character set {0} is not compatible with the source database character set {1}

Cause: Extract registration completed successfully but the combination of mining and source database character sets is not recommended.

Action: Connect to the mining database and alter its database character set to AL32UTF8.

OGG-02160: Could not find the definition of target table {0}. Assuming the table structure is exactly the same as the source table {1}.

Cause: The definition of the target table is not present in a target definitions file.

Action: If the source and target table definitions are different, create a target definitions file with the DEFGEN utility, and specify the file with the TARGETDEFS parameter. For more information about specifying table definitions, see Administering Oracle GoldenGate for Windows and UNIX.

OGG-02161: Failed to retrieve the trail file begin checkpoint position.

Cause: Could not retrieve the trail file begin checkpoint position.

Action: Ensure that the valid checkpoint and trail file are present on the system. Contact Oracle Support if both exist.

OGG-02162: Failed to retrieve the trail file next checkpoint position.

Cause: Could not retrieve the trail file next checkpoint position.

Action: Ensure that the valid checkpoint and trail file are present on the system. Contact Oracle Support if both exist.

OGG-02163: Trail file {0} not found or no records beyond begin time {1}.

Cause: Trail file does not exist or no records beyond begin time.

Action: Ensure that the valid checkpoint and trail file are present on the system. Contact Oracle support if both exist.

OGG-02164: Could not position in trail file {0}, status {1}.

Cause: The trail file or checkpoint file may be corrupted.

Action: Ensure that the valid checkpoint and trail file are present on the system. Contact Oracle support if both exist.

OGG-02165: Failed to retrieving VAM two phase commit I/O checkpoint.

Cause: Could not retrieve the trail file begin checkpoint position.

Action: Ensure that the valid checkpoint and trail file are present on the system. Contact Oracle support if both exist.

OGG-02166: Buffer overrun while reading extractor initial data load TCP/IP message, status {0}.

Cause: Network buffer overflow was detected while receiving initial data load TCP/IP message.

Action: Check your network connection then contact Oracle Support.

OGG-02167: Invalid or unrecognized record format found when parsing incoming record data, status ({1}).

Cause: Invalid or unrecognized record format found during incoming record data parsing for initial data load apply.

Action: Check your network connection then contact Oracle Support.

OGG-02168: Incompatible record format found when getting record header for initial data load, status ({1}).

Cause: Incompatible record format found while waiting for the record header for the initial data load apply.

Action: Check your network connection then contact Oracle Support.

OGG-02169: Error resetting AES cipher (error {0,number,0}, {1})

Cause: An error occurred while attempting to reset the AES cipher while processing incoming initial load data.

Action: None

OGG-02170: Error encrypting data record with AES cipher (error {0,number,0}, {1})

Cause: An error occurred while encrypting a data record with an AES cipher while processing incoming initial load data.

Action: None

OGG-02171: Error reading LCR from data source. Status {0}, data source type {1}.

Cause: An error occurred while reading the Logical Change Record from the data source.

Action: Check for any additional message detail then fix the issue described. Contact Oracle Support with the status code if no other additional detail was provided.

OGG-02172: The SHARDING parameter is only supported when Extract is configured in Integrated Capture mode.

Cause: The SHARDING parameter was specified in the Extract parameter file, but Integrated Capture mode is not configured.

Action: Remove the SHARDING parameter from the Extract parameter file or configure Extract to use Integrated Capture.

OGG-02173: The SHARDING parameter is not supported with this version of the Oracle Database.

Cause: The SHARDING parameter was specified in the Extract parameter file, but the Oracle Database does not support it.

Action: Remove the SHARDING parameter from the Extract parameter file or connect to a version of the Oracle Database that supports it.

OGG-02174: The SHARDING parameter is only supported when using OGGCAPTURE API protocol.

Cause: The SHARDING parameter was specified in the Extract parameter file, but Extract is not configured to use the OGGCapture API.

Action: Remove the SHARDING parameter from the Extract parameter file or configure Extract to use the OGGCapture API.

OGG-02175: The SHARDING parameter requires OGGCAPTURE API protocol version {0}. The Oracle Database supports up to version {1}.

Cause: The SHARDING parameter was specified in the Extract parameter file, but Extract is not connected to a database that supports it.

Action: Remove the SHARDING parameter from the Extract parameter file or configure Extract to connect to a database that supports it.

OGG-02176: Trail FORMAT {0} or higher is required for SHARDING configuration.

Cause: The EXTFILE, EXTTRAIL, RMTFILE, or RMTTRAIL parameter contains the FORMAT option, but the given RELEASE value does not support the SHARDING configuration.

Action: To support the SHARDING configuration, set FORMAT RELEASE to at least the version shown in the error message. Note that the reader process (data pump or Replicat) must be at least the specified version.

OGG-02177: The SHARDING parameter is not supported with this version of the Oracle mining database.

Cause: The SHARDING parameter was specified in the Extract parameter file, but the Oracle mining database does not support it.

Action: Remove the SHARDING parameter from the Extract parameter file or connect to a version of the Oracle Database that supports it.

OGG-02178: The SHARDING parameter is not supported when Extract is configured with multiple trail files.

Cause: The SHARDING parameter as well as multiple trail files were specified in the Extract parameter file.

Action: Remove the SHARDING parameter from the Extract parameter file or configure Extract to use only one trail file.

OGG-02179: The SHARDING parameter is only supported when the Integrated Dictionary is in use.

Cause: The SHARDING parameter is specified but Extract is not configured to use the Integrated Dictionary.

Action: Remove the SHARDING parameter from the Extract parameter file or configure Extract to use the Integrated Dictionary.

OGG-02180: Table {0} will use legacy trail format to support parameter {1}.

Cause: The indicated parameter provides uncompressed after image data by default so Extract will use legacy format to preserve that data.

Action: If your configuration does not require the presence of uncompressed after image data, then you may specify UPDATERECORDFORMAT COMPACT to eliminate the uncompressed after image data and improve performance.

OGG-02181: Root container timezone information will be used for all containers.

Cause: Container specific timezone information can not be obtained. Specification of parameter USE_ROOT_CONTAINER_TIMEZONE has allowed Extract to proceed with the guarantee that all containers have the same timezone information as the root container.

Action: Ensure all containers have the same timezone information as the root container.

OGG-02182: Container specific timezone can not be obtained. A mining database patch or parameter TRANLOGOPTIONS USE_ROOT_CONTAINER_TIMEZONE is required.

Cause: Container specific timezone information can not be obtained because Extract is running in a sourceless Extract configuration.

Action: Install the required patch on the mining database. Alternatively, a fetch database can be configured. Alternatively, if all containers have the same timezone as the root container then parameter TRANLOGOPTIONS USE_ROOT_CONTAINER_TIMEZONE can be specified.

OGG-02183: Trail file {0} was partially transferred, retransmission is required.

Cause: An error occurred while waiting the trail file transmission completion. Only part of the trail file was transferred.

Action: Check for network and file system problems; resolve any problems found. Contact Oracle Support if no problem was found.

OGG-02184: Invalid trail file name {0}.

Cause: Invalid trail file name found when opening the input trail file.

Action: Check the input trail file configuration. The checkpoint file may be corrupted.

OGG-02185: Buffer overflow while reading trail file {0}. (RBA {1}).

Cause: Buffer overflow happened while reading the trail file. The trail file may be corrupted.

Action: Ensure that the trail file is valid. Contact Oracle Support if the trail file is valid.

OGG-02186: Bad reposition RBA {0} where file header size is {1}.

Cause: Bad trail position was specified when repositioning trail file.

Action: Ensure that the trail file and checkpoint files are valid. Contact Oracle Support if the trail files are valid.

OGG-02187: Could not reposition. Trail file {0} missing.

Cause: Could not find the trail file when attempting to reposition it.

Action: Check the disk space and the network connection for problems. Contact Oracle Support if no problem was found.

OGG-02188: Unexpected LOB record or record fragment in {0}, rba {1}.

Cause: LOB record or record fragment was found without base record in the trail file.

Action: Wrong start RBA was specified or the trail file is corrupted.

OGG-02189: Unexpected RestartOK record in {0}, rba {1}.

Cause: RestartOK record was found in the middle of record.

Action: Trail file may be corrupted. Check the trail file and contact Oracle Support.

OGG-02190: The data length of {0} exceeds the maximum allowed record length of {1}.

Cause: The length of the specified record exceeds the maximum length that is allowed for the trail file.

Action: Contact Oracle Support.

OGG-02191: Incompatible record {0} in {1}, rba {2} when getting trail header.

Cause: Trail file format is not compatible with Oracle GoldenGate.

Action: Trail file may be corrupted or the trail file version is no longer supported. Contact Oracle Support.

OGG-02192: Unrecognized response from trail file parsing {0} in {1}.

Cause: Trail file format is invalid.

Action: Trail file may be corrupted. Contact Oracle Support.

OGG-02194: Error {0} ({1}) while reading trail file {2} (rba {3}).

Cause: Encounter unrecoverable file read error, which can be caused by file system or network issue.

Action: Check additional message detail and try resolve the issue. Contact Oracle Support if you cannot resolve the issue.

OGG-02195: Error {0} ({1}) opening trail file {2} in EOF check.

Cause: Encountered trail file open error when checking logical EOF.

Action: Check additional message detail and try resolve the issue. Contact Oracle Support if you cannot resolve the issue.

OGG-02196: Error {0} ({1}) positioning trail file {2} in EOF check.

Cause: Encountered trail file positioning (seek) error when checking logical EOF.

Action: Check additional message detail and try resolve the issue. Contact Oracle Support if you cannot resolve the issue.

OGG-02197: Error {0} ({1}) reading trail file {2} in EOF check.

Cause: Encountered trail file reading error when checking logical EOF.

Action: Check additional message detail and try resolve the issue. Contact Oracle Support if you cannot resolve the issue.

OGG-02198: Incompatible record (logical EOF) in trail file {0}, rba {1}.

Cause: Incompatible record found in the trail file after logical EOF marker.

Action: Trail file may be corrupted. Check for file system and network issues. Contact Oracle Support if no issue was found.

OGG-02199: Incomplete record in trail file {0}, rba {1} at EOF.

Cause: Incomplete record found in the trail file at EOF.

Action: Trail file may be corrupted. Check for file system and network issues. Contact Oracle Support if no issue was found.

OGG-02200: Unexpected condition in {0} at line {1,number,0}. LCR parameter error.

Cause: An internal error occurred. LCR parameter error.

Action: Contact Oracle Support.

OGG-02201: Unexpected condition in {0} at line {1,number,0}. Duplicate LCR column {2}.

Cause: An internal error occurred. Duplicate LCR column.

Action: Contact Oracle Support.

OGG-02202: Unexpected condition in {0} at line {1,number,0}. Invalid flag {3} for LCR column {2}.

Cause: An internal error occurred. Invalid LCR column flag.

Action: Contact Oracle Support.

OGG-02203: Unexpected condition in {0} at line {1,number,0}. Invalid data chunk offset {3} for column {2}, previous chunk offset {4}, length {5}.

Cause: An internal error occurred. Invalid out of row data chunk offset.

Action: Contact Oracle Support.

OGG-02204: Unexpected condition in {0} at line {1,number,0}. LCR column {2} not found.

Cause: An internal error occurred. LCR column does not exist in the LCR column list.

Action: Contact Oracle Support.

OGG-02205: Unexpected condition in {0} at line {1,number,0}. Table metadata not found. Database ID: {2}, Object ID: {3}, Object Version: {4}, Map ID: {5}.

Cause: An internal error occurred. Table metadata not found for the object ID.

Action: Contact Oracle Support.

OGG-02206: Unexpected condition in {0} at line {1,number,0}. Could not allocate pool buffer.

Cause: An internal error occurred. Could not allocate pool buffer item.

Action: Contact Oracle Support.

OGG-02207: Unexpected condition in {0} at line {1,number, 0}. Invalid data state {2}.

Cause: An internal error occurred. Invalid data state found.

Action: Contact Oracle Support.

OGG-02208: Operator {0} is not available for {1} data type.

Cause: Operator is not available for the data type.

Action: Update parameter file to exclude the operator for the column or other data.

OGG-02209: Data type conversion from {0} data type to {1} data type is not supported.

Cause: Unsupported data type conversion is specified by mapping parameter.

Action: Update the TABLE/MAP parameter and remove the mapping between the two data types.

OGG-02210: Comparison {0} data type {1} {2} data type is not supported.

Cause: Unsupported data type comparison is specified by mapping parameter.

Action: Update the TABLE/MAP parameter and remove the comparison between the two data types.

OGG-02211: Operation {0} is not available for {1} data type.

Cause: Operation is not available for the data type.

Action: Update parameter file to exclude the operation for the column or other data.

OGG-02212: Invalid data found for comparison of {0} data type.

Cause: Invalid data was found when attempting comparison of the data type.

Action: Update parameter file to handle invalid data before the comparison may be using @COLTEST().

OGG-02213: Missing data found for comparison of {0} data type.

Cause: Data is missing and can not compare.

Action: Update parameter file to handle missing data before the comparison may be using @COLTEST().

OGG-02214: Operation {0} is not supported for NULL {1} data type.

Cause: NULL data is not supported for the operation.

Action: Update parameter file to handle NULL data before the operation may be using @COLTEST().

OGG-02215: Operation {0} is not supported for invalid {1} data type.

Cause: Invalid data is not supported for the operation.

Action: Update parameter file to handle invalid data before the operation may be using @COLTEST().

OGG-02216: Operation {0} is not supported for missing {1} data type.

Cause: Missing data is not supported for the operation.

Action: Update parameter file to handle missing data before the operation may be using @COLTEST().

OGG-02217: The character set {0} is not supported for data type conversion.

Cause: The character set is not supported for the data type conversion.

Action: Contact Oracle Support.

OGG-02218: Numeric operation overflow occurred.

Cause: Number overflow occurred.

Action: None

OGG-02219: Numeric operation underflow occurred.

Cause: Number underflow occurred.

Action: None

OGG-02220: Invalid number format {0}.

Cause: Invalid number format found during conversion from numeric string to numeric value.

Action: Provide correct numeric string if numeric string value is given by parameter.

OGG-02221: Invalid argument found. Module: {0}, Function {1}, Line {2}, Argnum {3}.

Cause: Invalid function argument.

Action: Contact Oracle Support.

OGG-02222: Zero division error.

Cause: Zero division occurred.

Action: None

OGG-02223: Floating point number value is not a number.

Cause: NaN detected.

Action: None

OGG-02224: Floating point number value is infinite.

Cause: Inf or -Inf detected.

Action: None

OGG-02225: Data mapping buffer overflow from {1} to {0}.

Cause: Buffer overflow occurred while mapping the source data to the target data container.

Action: None

OGG-02226: Data type conversion is not supported for NULL {0} data type.

Cause: Data type conversion is not supported for the NULL data.

Action: Update parameter file to handle NULL data before the operation may be using @COLTEST().

OGG-02227: Data type conversion is not supported for invalid {0} data type.

Cause: Data type conversion is not supported for the invalid data.

Action: Update parameter file to handle invalid data before the operation may be using @COLTEST().

OGG-02228: Conversion is not supported for missing {0} data type.

Cause: Data type conversion is not supported for the missing data.

Action: Update parameter file to handle missing data before the operation may be using @COLTEST().

OGG-02229: Compression failed with error code {0}. Switch to non-compression mode for the data block.

Cause: Data compression failed. Typically, the compressed data size exceeds the original data size, which rarely happens when the data is encrypted.

Action: None

OGG-02230: Decompression failed with error code {0}.

Cause: Data decompression failed. Possible data loss during network operation.

Action: Check network connection. Contact Oracle Support if this happens often.

OGG-02231: Switching to next trail file {0} at {1}. with current RBA {2}.

Cause: Switch to the next trail file sequence.

Action: None

OGG-02232: Switching to next trail file {0} at {1} due to EOF. with current RBA {2}.

Cause: Switch to the next trail file sequence due to current trail file reached to EOF.

Action: None

OGG-02233: Switching to next trail file {0} at {1} due to logical EOF. with current RBA {2}.

Cause: Switch to the next trail file sequence because the current trail file reached to logical EOF.

Action: None

OGG-02234: Invalid ATTRCHARSET clause {0}.

Cause: The ATTRCHARSET clause syntax is invalid.

Action: Use valid syntax for the ATTRCHARSET clause.

OGG-02235: Missing character set in ATTRCHARSET clause {0}.

Cause: The character set parameter is missing from the ATTRCHARSET clause.

Action: Specify a character set for the ATTRCHARSET clause.

OGG-02236: Invalid character set {1} in ATTRCHARSET clause {0}.

Cause: The character set parameter in the ATTRCHARSET clause is invalid.

Action: Specify a valid character set for the ATTRCHARSET clause.

OGG-02237: Invalid UDT attribute name {1} for table {2} in ATTRCHARSET clause {0}.

Cause: The attribute name parameter in the ATTRCHARSET clause is invalid.

Action: Specify a valid attribute name for the ATTRCHARSET clause.

OGG-02238: The source attribute character set {0} is specified with the ATTRCHARSET parameter for the table {1}, attribute {2}.

Cause: The ATTRCHARSET parameter is specified and assumed as the attribute character set.

Action: None

OGG-02239: Upgrading to OGGCapture API.

Cause: Automatically upgrading to OGGCapture API.

Action: None

OGG-02240: Failed to delete the filter rule checkpoint file {0} because of the following error {1}.

Cause: Extract failed to delete the file rule checkpoint file.

Action: Fix the problem and restart Extract, or manually delete the file. Failure to delete the file will have no impact on Extract.

OGG-02241: LCR column iterator is not supported for record or operation type {0}.

Cause: Internal error. LCR column iterator is not supported for internal record type or SQL operation type.

Action: Contact Oracle Support.

OGG-02242: Invalid operation call was made on invalid LCR record.

Cause: Internal error. LCR column iterator cannot be created for invalid LCR.

Action: Contact Oracle Support.

OGG-02243: Opened trail file {0} at {1}.

Cause: Trail file has been opened.

Action: None

OGG-02244: Error reading LCR from TranLog data source. {0}

Cause: An error occurred while reading the Logical Change Record from the TranLog data source.

Action: Check for message detail then fix the issue described. Contact Oracle Support with the status code if no other additional detail was provided.

OGG-02245: Repositioning was attempted as REPERROR action, but is not supported by RMTTASK.

Cause: Repositioning is not supported by initial load RMTTASK, because it does not use trail file.

Action: Check whether the ALTER REPLICAT was meant for a change-synchronization Replicat instead of the task Replicat, or specify IGNORE/DISCARD for the REPERROR action.

OGG-02246: Source redo compatibility level {0} requires trail FORMAT {1} or higher.

Cause: Source database redo compatibility level can not be supported with the current trail file format.

Action: Specify a trail file format supported for the source redo compatibility.

OGG-02247: Failed to read {0} file {1}: {2}.

Cause: Failed to read the table definition file specified by SOURCEDEFS or TARGETDEFS parameters.

Action: Check for message detail then fix the issue described.

OGG-02248: Logmining server DDL filtering enabled.

Cause: The Extract configuration allows the Logmining server to filter unneeded DDLs.

Action: None

OGG-02249: The Extract configuration does not support a physical standby as the source database.

Cause: The source database role is PHYSICAL STANDBY, which is not supported with the current Extract configuration.

Action: Correct the source database connection information.

OGG-02250: Duplicate specification of parameter {0}.

Cause: The parameter is specified more than once.

Action: Remove all but one specification of the parameter.

OGG-02251: Fetch requires a connection to the source or fetch database.

Cause: Extract attempted a fetch operation that requires a connection to the source or fetch database.

Action: Specify a USERID parameter, FETCHUSERID parameter, or exclude the table.

OGG-02252: WILDCARDRESOLVE parameter must be set to DYNAMIC when NOUSERID parameter is specified.

Cause: The NOUSERID parameter is specified and the WILDCARDRESOLVE parameter is not set to DYNAMIC.

Action: Set WILDCARDRESOLVE to DYNAMIC and restart the process.

OGG-02253: Integrated capture option {0} is incompatible with a classic capture configuration.

Cause: The specified integrated capture option is not valid in a classic capture configuration.

Action: Remove the incompatible option from the Extract parameter file or upgrade to integrated capture.

OGG-02254: Integrated dictionary is required for parameter {0}.

Cause: The specified parameter is only supported when Extract is configured to use the integrated dictionary.

Action: Remove the incompatible option from the Extract parameter file or configure Extract to use the integrated dictionary.

OGG-02255: The MININGDBLOGIN is connected to the source database {0}.

Cause: The MININGDBLOGIN command was used and connects to the same database as the DBLOGIN command.

Action: If you are configuring Integrated Extract in downstream capture mode, the DBLOGIN command must connect to a different database than the MININGDBLOGIN command. Otherwise, the source and mining connections may connect to the same database.

OGG-02256: Source redo initial compatibility version is: {0}.

Cause: The redo compatibility version of the source database at the time of the GGSCI register command.

Action: None

OGG-02257: Using the parameter supplied redo compatibility version: {0}.

Cause: The redo compatibility version of the source database supplied by the Extract parameter file.

Action: None

OGG-02258: The supplied value of _SOURCE_REDO_COMPATIBLE is invalid: {0}.

Cause: The value specified for the parameter _SOURCE_REDO_COMPATIBLE is invalid.

Action: Specify a valid parameter value. Example: 11.2.0.4.

OGG-02259: Extract failed to gather source database metadata from the mining database because of the following error: {0}.

Cause: Extract received a failure while obtaining source database metadata information from the mining database.

Action: Correct the error, and then restart the process.

OGG-02260: Incompatible or invalid RMTTASK format {0}.

Cause: Metadata format from extract is incompatible or invalid for the RMTTASK replicat version.

Action: Check for extract RMTTASK parameter, remove or specify compatible FORMAT RELEASE option.

OGG-02261: Incompatible or invalid trail format {0}.

Cause: Metadata format from extract is incompatible or invalid for the replicat version.

Action: Check for extract EXTRAIL/RMTTRAIL parameter, remove or specify compatible FORMAT RELEASE option.

OGG-02264: Trail file is encrypted but no decryption key was found that is required for MAP (entry {0}).

Cause: The map entry is not passthru and requires trail file decryption in order to access to record data. The trail file header indicates that its content is encrypted, but the reading process could not find the key in the trail metadata. The Oracle GoldenGate source configuration might be using an ENCKEYS file to store an encryption key, but the reading process is not configured to use this method.

Action: Make the map entry to passthru that has no TARGET, FILTER, WHERE, SQUELCH, and COLMAP. Alternatively, make certain that the source and the target configuration for the trail encryption matches. If using ENCKEYS in source, target needs this method as well. Contact Oracle Support if assistance is needed.

OGG-02265: Missing source trail table definition after switching trail sequence.

Cause: Previous sequence trail had table definition, but the new trail file does not have table definition. Requires restarting the pump to reset the table mapping.

Action: Restart extract pump.

OGG-02266: Table definition found in source trail after switching trail sequence.

Cause: Previous sequence trail had no table definition, but the new trail file has table definition. Requires restarting the pump to reset the table mapping.

Action: Restart extract pump.

OGG-02267: Missing source trail decryption key after switching trail sequence.

Cause: Previous sequence trail had trail file decryption key, but the new trail file does not have the decryption key. Requires restarting the pump to reset the table mapping.

Action: Restart extract pump.

OGG-02268: Decryption key found in source trail after switching trail sequence.

Cause: Previous sequence trail had no trail file decryption key, but the new trail file has the trail file decryption key. Requires restarting the pump to reset the table mapping.

Action: Restart extract pump.

OGG-02269: Processing heartbeat table {0} in passthru mode.

Cause: Source trail file is encrypted, but no decryption key was found to update heartbeat table record.

Action: None

OGG-02270: Timezone can not be obtained for container {0}. Either make the container available or install a mining database patch or set parameter TRANLOGOPTIONS USE_ROOT_CONTAINER_TIMEZONE.

Cause: Container specific timezone information can not be obtained because the container is unavailable.

Action: Ensure the container is open or install the required patch on the mining database. Alternatively, a fetch database can be configured. Alternatively, If all containers have the same timezone as the root container then parameter TRANLOGOPTIONS USE_ROOT_CONTAINER_TIMEZONE can be specified.

OGG-02271: Decryption key is missing and record can not be filtered out.

Cause: Record is filtered out by parameter specification while pump/distribution require decryption key when any record is filtered out from encrypted trail for recovery.

Action: Pass through all records including table, sequence, DDL, and procedure using add or modify TABLE, SEQUENCE, DDL or PROCEDURE parameter. Alternatively, you can provide decryption key for Oracle GoldenGate to process records.

OGG-02400: Load library {0} failed with error {1}.

Cause: Loading CRS/XAG shared library failed.

Action: Contact Oracle Support.

OGG-02401: CRS/XAG function call {0} failed with error status {1}.

Cause: CRS function call failed.

Action: Contact Oracle Support.

OGG-02402: Transparent Integration with XAG is enabled but CRS/XAG is not available.

Cause: CRS/XAG is not available.

Action: Contact Oracle Support.

OGG-02403: GGSCI failed to retrieve environment variable OGG_HOME.

Cause: The environment variable OGG_HOME is not set.

Action: Contact Oracle Support.

OGG-02404: No GoldenGate instance is found in XAG resource list.

Cause: GoldenGate instance may not be registered with XAG.

Action: Register the GoldenGate instance with XAG using XAG tool AGCTL and try again. If the problem persists, contact Oracle Support.

OGG-02405: No GoldenGate instance is registered with XAG.

Cause: GoldenGate instance is not registered with XAG.

Action: Register the GoldenGate instance with XAG using XAG tool AGCTL and try again. If the problem persists, contact Oracle Support.

OGG-02406: Command {0} manager failed with error status {1}.

Cause: XAG failed to start/stop manager.

Action: Contact Oracle Support.

OGG-02407: CRS/XAG error {0} is captured in callback function.

Cause: CRS/XAG error is captured in callback function.

Action: None

OGG-02408: More than one GoldenGate instance was found.

Cause: More than one GoldenGate instance, with the same GoldenGate home directory, exists.

Action: Remove the extraneous GoldenGate instances and try again. If the problem persists, contact Oracle Support.

OGG-02501: Unsupported data type code {0} encountered for table {1}, column {2}

Cause: The specified data type is not supported in integrated apply mode.

Action: Replicat will fall back to standard mode for transactions with unsupported data types. To retain integrated apply mode, remove the table from the Replicat configuration or change the incompatible data type to one that is supported.

OGG-02502: Invalid parameter specified for integrated apply mode

Cause: The integrated apply parameter specification is invalid.

Action: Use valid syntax for the INTEGRATEDPARAMS parameter. For help, see the Oracle GoldenGate reference documentation.

OGG-02503: Integrated apply mode not supported by this database version

Cause: Integrated apply was specified, but it is not supported by this database version.

Action: Run Replicat in non-integrated apply mode, or upgrade the database to a version that supports integrated apply.

OGG-02504: Integrated apply '{0}' had a position length of {1} when {2} was expected

Cause: A mismatch in position length was detected.

Action: Contact Oracle Support.

OGG-02505: Integrated apply mode does not support operation code {0}

Cause: An unsupported operation code was encountered while in integrated apply mode.

Action: Contact Oracle Support.

OGG-02506: Cannot register REPLICAT {0} because no database login was provided. Use DBLOGIN to establish a connection.

Cause: A REGISTER REPLICAT command was issued without first issuing a DBLOGIN command.

Action: Issue the DBLOGIN command, and then issue REGISTER REPLICAT again.

OGG-02507: Cannot register REPLICAT {0} because the specified Replicat is running. Stop Replicat and then retry the command.

Cause: A REGISTER REPLICAT command was issued without first stopping the process.

Action: Stop the Replicat process, then issue a DBLOGIN command, and then the REGISTER REPLICAT command.

OGG-02508: Cannot register REPLICAT {0} because of the following SQL error: {1}. See Replicat user privileges in the Oracle GoldenGate for Oracle Installation and Setup Guide.

Cause: A REGISTER REPLICAT command was issued and an error occurred either while querying the database or when calling a PL/SQL procedure.

Action: Issue DBLOGIN with the appropriate privileges that are required for REGISTER REPLICAT. See the Oracle GoldenGate reference documentation.

OGG-02509: REPLICAT {0} is already registered with the database.

Cause: A REGISTER REPLICAT command was issued for a Replicat group that is already registered with the database.

Action: None

OGG-02510: Invalid syntax for REGISTER REPLICAT command. Expecting 'DATABASE', but received '{0}'

Cause: Invalid syntax was specified for the REGISTER REPLICAT command.

Action: The correct syntax is REGISTER REPLICAT groupname DATABASE, where groupname is the name of the group. For additional information, see the Oracle GoldenGate reference documentation or the GGSCI online help.

OGG-02511: Invalid syntax for UNREGISTER REPLICAT command. Expecting 'DATABASE', but received '{0}'

Cause: Invalid syntax was specified for the UNREGISTER REPLICAT command.

Action: The correct syntax is UNREGISTER REPLICAT groupname DATABASE, where groupname is the name of the group. For additional information, see the Oracle GoldenGate reference documentation or the GGSCI online help.

OGG-02512: REPLICAT {0} is not registered with the database.

Cause: An UNREGISTER REPLICAT command was issued for a Replicat group that is not registered with the database.

Action: None

OGG-02513: REPLICAT {0} is not registered with the database.

Cause: An integrated Replicat was started before it was registered with the database.

Action: Register the Replicat before starting it.

OGG-02514: The Replicat {0} is already in integrated mode.

Cause: The specified Replicat is already in integrated apply mode.

Action: None

OGG-02515: The Replicat {0} is already in non-integrated mode.

Cause: The specified Replicat is already in non-integrated apply mode.

Action: None

OGG-02516: Integrated replicat requires a trail source

Cause: Cannot switch to integrated apply mode because the specified Replicat does not have a trail to read.

Action: None

OGG-02517: REGISTER REPLICAT {0} DATABASE must be performed before switching to integrated apply.

Cause: The REGISTER REPLICAT command was not issued.

Action: Issue the command as REGISTER REPLICAT groupname DATABASE, where groupname is the name of the Replicat group. Then switch Replicat to integrated apply.

OGG-02518: Cannot convert data for for table {0} column {1} because the client character set {2} is not supported.

Cause: The client character set is not supported.

Action: Set the client character set to a supported character set.

OGG-02519: Cannot convert data for table {0} column {1} because the server character set {2} is not supported.

Cause: The server character set is not supported.

Action: Set the server character set to a supported character set.

OGG-02520: Character set conversion failure occured for table {0} column {1} when converting from source character set {2} to target character set {3}. Error code: {4,number,0}

Cause: An internal error occurred during character set conversion.

Action: Save the error message and contact Oracle GoldenGate Support.

OGG-02521: Integrated Replicat flush of an OCI call failed

Cause: The OCI flush failed. This could be due to a problem communicating with the database.

Action: Restart Replicat.

OGG-02522: Integrated Replicat failed to get the processed low watermark

Cause: Internal error getting the cached processed low watermark.

Action: Restart Replicat.

OGG-02523: Integrated Replicat query of the error queue failed

Cause: A query of the error queue failed.

Action: Check the connection to the database.

OGG-02524: Integrated Replicat APT-based filtering suppressed an already applied record at SEQNO {0,number,0}, RBA {1,number,0}, with transaction ID {2}.

Cause: APT-based filtering identified an already applied record and filtered it out.

Action: None

OGG-02525: Integrated Replicat has been unregistered

Cause: The integrated Replicat has been switched to non-integrated mode.

Action: None

OGG-02526: Parameter {0} is ignored by Integrated Replicat

Cause: The specified parameter is ignored by Integrated Replicat.

Action: None

OGG-02527: Integrated Replicat does not populate a trace table

Cause: Integrated Replicat does not populate a trace table and ignores any TRACETABLE setting in the parameter file.

Action: Use the NOTRACETABLE parameter in the Integrated Replicat parameter file.

OGG-02528: REPLICAT {0} successfully registered with database as inbound server {1}

Cause: The specified Replicat is now registered with the database to support integrated apply.

Action: None

OGG-02529: Successfully unregistered REPLICAT {0} inbound server OGG\${0} from database

Cause: A DELETE REPLICAT or UNREGISTER REPLICAT command was issued to unregister the Replicat group from the database.

Action: None

OGG-02530: Integrated replicat successfully attached to inbound server {0}

Cause: Replicat successfully attached to the inbound server.

Action: None

OGG-02531: Inbound server {0} error status ORA-{1}:{2}

Cause: The inbound server recorded an error code.

Action: Resolve the error and restart Replicat.

OGG-02532: Checkpoint table required to switch to non-integrated mode

Cause: Replicat was switched to non-integrated mode. This mode requires the use of a checkpoint table.

Action: Issue the ALTER REPLICAT command to associate a checkpoint table with this Replicat group. For help, see the online GGSCI help or the Oracle GoldenGate reference documentation.

OGG-02533: Cannot unregister REPLICAT {0} from database because DBLOGIN command was not issued first. Issue DBLOGIN, then UNREGISTER REPLICAT groupname DATABASE.

Cause: A DELETE REPLICAT command was issued without first issuing a DBLOGIN command. Integrated Replicat requires DBLOGIN before deleting Replicat groups.

Action: Manually unregister the replicat using the UNREGISTER REPLICAT DATABASE command.

OGG-02534: SHOWSYNTAX is not interactive in integrated mode. Refer to the Oracle RDBMS trace files for the SQL trace output.

Cause: SHOWSYNTAX enables SQL trace on the server.

Action: None

OGG-02535: CSN filtering is always active for Integrated and Parallel modes.

Cause: _CSNFILTERING OFF was specified for an Integrated or Parallel Replicat.

Action: Remove the _CSNFILTERING parameter.

OGG-02536: The inbound server ID for Replicat {0} does not match the registered ID.

Cause: The inbound server that was registered was dropped and recreated.

Action: The Integrated Replicat may be in an inconsistent state. Delete the integrated Replicat with the DELETE REPLICAT command and then add it again with the ADD REPLICAT command. For help, see the online GGSCI help or the Oracle GoldenGate reference documentation.

OGG-02537: Cannot unregister REPLICAT {0} because no database login was provided. Use DBLOGIN to establish a connection.

Cause: An UNREGISTER REPLICAT command was issued without first issuing a DBLOGIN command.

Action: Issue the DBLOGIN command, and then issue UNREGISTER REPLICAT again.

OGG-02538: Cannot unregister REPLICAT {0} because of the following SQL error: {1}. See Replicat user privileges in the Oracle GoldenGate for Oracle Installation and Setup Guide.

Cause: An UNREGISTER REPLICAT command was issued and an error occurred either while querying the database or when calling a PL/SQL procedure.

Action: Issue DBLOGIN with the appropriate privileges that are required for UNREGISTER REPLICAT. See the Oracle GoldenGate reference documentation.

OGG-02539: Cannot unregister REPLICAT {0} because the specified Replicat is running. Stop Replicat and then retry the command.

Cause: An UNREGISTER REPLICAT command was issued without first stopping the process.

Action: Stop the Replicat process, then issue a DBLOGIN command, and then the UNREGISTER REPLICAT command.

OGG-02540: Parameter {0} is not supported by Integrated Replicat

Cause: The specified parameter is incompatible with Integrated Replicat.

Action: Remove the parameter and restart replicat.

OGG-02541: Replicat could not process some SQL errors before being dropped or unregistered. This may cause the data to be out of sync.

Cause: In integrated mode, Replicat can be shut down and dropped before it is finished processing any SQL errors that accumulated in the error queue. This warning indicates that Replicat was dropped before it could resolve the errors, and this may cause the source and target data to be out of synchronization.

Action: Before adding a new Replicat (in any mode), verify the state of the data and perform an initial synchronization for any target objects that are out-of-sync.

OGG-02542: Cannot unregister REPLICAT {0} because the specified Replicat is still in Integrated mode. Please DELETE REPLICAT or ALTER to NONINTEGRATED mode then retry the command.

Cause: An UNREGISTER REPLICAT command was issued without first switching Replicat to non-integrated mode or deleting the Replicat group.

Action: Either issue the ALTER REPLICAT command with the NONINTEGRATED option to switch the Replicat in non-integrated mode, or issue the DELETE REPLICAT command to delete the Replicat group, which automatically unregisters Replicat from the database.

OGG-02543: The UNREGISTER REPLICAT {0} command was forced by a user

Cause: An UNREGISTER REPLICAT command was forcefully issued. This command bypassed the requirement to first issue the ALTER REPLICAT command with the NONINTEGRATED option or the DELETE REPLICAT command.

Action: None

OGG-02544: Unhandled error ({0}) while processing the record at SEQNO {1,number,0}, RBA {2,number,0} in Integrated mode. REPLICAT will retry in Direct mode

Cause: An error occurred in the database server while processing a trail record in Integrated mode. Replicat will retry in direct mode.

Action: You can use the REPERROR parameter and/or Conflict Detection Resolution rules to control how Replicat should handle a specific error or conflict.

OGG-02545: Parameter {0} is ignored by Integrated Replicat when parallelism is greater than 1

Cause: Parallelism is greater than 1 for this Integrated Replicat. The specified parameter is only valid when parallelism is 1 and is ignored otherwise.

Action: None

OGG-02546: Database is open in restricted mode. Unable to attach to database inbound server {0}.

Cause: The database is open in restricted mode. Replicat cannot attach to an inbound server.

Action: Disable the restricted session and then restart Replicat.

OGG-02547: Cannot alter Coordinated Replicat {0} to integrated mode

Cause: Cannot switch to integrated apply mode because the specified Replicat is a Coordinated Replicat.

Action: None

OGG-02548: SOURCEISTABLE trail is not supported by Integrated Replicat

Cause: Trail files generated by an initial load Extract are not supported by Integrated Replicat

Action: Use SPECIALRUN replicat instead

OGG-02549: DML handler execution not supported for table {0}

Cause: DML handlers will not run for this table because it contains unsupported data types.

Action: Use the dbms_apply_adm.set_dml_handler procedure to remove the DML handler by specifying the user_procedure as NULL. For more information, see the "SET_DML_HANDLER Procedure" documentation in the Oracle Database PL/SQL Packages and Types Reference, version 12.1

OGG-02550: ORACLE_HOME is not set to Oracle software directory.

Cause: Environment variable ORACLE_HOME is not set.

Action: Check your Oracle database configuration and set the ORACLE_HOME variable if not set to the Oracle software directory.

OGG-02551: ORACLE_HOME is not set to Oracle software directory.

Cause: Environment variable ORACLE_HOME is not set, but may exist in your Windows registry.

Action: If Oracle GoldenGate failed to operate properly, check your Oracle database configuration and set the ORACLE_HOME variable if not set to the Oracle software directory.

OGG-02552: The SOURCECHARSET PASSTHRU parameter does not support CHAR/VARCHAR/CLOB to/from NCHAR/NVARCHAR/NCLOB mappings.

Cause: The parameter file contains the SOURCECHARSET PASSTHRU parameter. This parameter specification does not allow CHAR/VARCHAR/CLOB to NCHAR/NVARCHAR/NCLOB mappings.

Action: To map the specified data types, remove SOURCECHARSET PASSTHRU. To determine how to map between different data types, see the Oracle GoldenGate data integration documentation.

OGG-02553: DDL filtering {0} {1} is not supported by data pump.

Cause: The DDL filtering options is not supported by data pump and is ignored.

Action: Remove the DDL fitering option from data pump parameter.

OGG-02554: Error loading shared library {0}: {1,number,0} {2}

Cause: The library can not be found or loaded.

Action: Add the library path to the dynamic linker search path in the environment variables i.e. LD_LIBRARY_PATH.

OGG-02600: OCI error ({0,number,0}-{1}) when validating checkpoint table {2}, SQL: {3}. The table may not exist. To add it, use the ADD CHECKPOINTTABLE command in GGSCI

Cause: Validation of the checkpoint table failed, possibly because the checkpoint table does not exist.

Action: Add the checkpoint table by using the ADD CHECKPOINTTABLE command in GGSCI. For help, see the ggsci online help or the Oracle GoldenGate reference documentation.

OGG-02601: OCI error ({0,number,0}-{1}) when validating supplemental checkpoint table {2}, SQL: {3}. The table may not exist. If you upgraded from Oracle GoldenGate 11.2.1.0.0 or earlier, add this table with the UPGRADE CHECKPOINTTABLE command in GGSCI

Cause: Validation of the supplemental checkpoint table failed, possibly because the table does not exist. This table is required for upgrades from version 11.2.1.0.0 or earlier.

Action: Add the supplemental checkpoint table with the UPGRADE CHECKPOINTTABLE command in GGSCI after an upgrade from release 11.2.1.0.0 or earlier. For help, see the ggsci online help or the Oracle GoldenGate reference documentation.

OGG-02602: Unable to determine the supplemental checkpoint table name from the checkpoint Table.

Cause: The process could not determine the name of the supplemental checkpoint table.

Action: Make sure you used valid connection credentials to log into the database with the DBLOGIN command in GGSCI.

OGG-02603: Checkpoint table {0} does not exist. Create this table with the ADD CHECKPOINTTABLE command in GGSCI.

Cause: The checkpoint table does not exist.

Action: Use the ADD CHECKPOINTTABLE command in GGSCI to create the table. For help, see the GGSCI online help or the Oracle GoldenGate reference documentation.

OGG-02604: Supplemental checkpoint table does not exist. Create a supplemental checkpoint table with the UPGRADE CHECKPOINTTABLE command in GGSCI if you have upgraded from release 11.2.1.0.0 or earlier.

Cause: Supplemental checkpoint table does not exist.

Action: Create a supplemental checkpoint table with the UPGRADE CHECKPOINTTABLE command in GGSCI. For help, see the GGSCI online help or the Oracle GoldenGate reference documentation.

OGG-02605: The use of a checkpoint table is not supported for {0}.

Cause: Oracle GoldenGate does not support the use of a checkpoint table for the specified target database.

Action: None

OGG-02606: Error retrieving information on checkpoint table: {0}. Database error: {1}. Create the checkpoint table with the ADD CHECKPOINTTABLE command in GGSCI.

Cause: Validation of the Checkpoint table failed, possibly because the checkpoint table was not created.

Action: Create the checkpoint table with the ADD CHECKPOINTTABLE command in GGSCI. For help, see the GGSCI online help or the Oracle GoldenGate reference documentation.

OGG-02607: Error reading status from the checkpoint table: {0}. Database error: {1}.

Cause: An error occurred while reading status information from the checkpoint table.

Action: Re-create the checkpoint table by using the ADD CHECKPOINTTABLE command in GGSCI. For more information, see the GGSCI online help or the Oracle GoldenGate reference documentation.

OGG-02608: Error reading row from checkpoint table: {0}. Database error: {1}.

Cause: An error occurred while reading row data from the checkpoint table.

Action: Re-create the checkpoint table by issuing the ADD CHECKPOINTTABLE command in GGSCI. For more information, see the GGSCI online help or the Oracle GoldenGate reference documentation.

OGG-02609: Error allocating statement handle for validating checkpoint table operations. Checkpoint table: {0}. Database error: {1}.

Cause: A statement handle could not be allocated to access the checkpoint table.

Action: Fix the database connectivity problem according to the error message.

OGG-02610: Error retrieving information on checkpoint table: {0}. SQL Statement: {1}. Database error: {2}.

Cause: Validation of the checkpoint table failed, possibly because the table was not created.

Action: Create or re-create the table with the ADD CHECKPOINTTABLE command in GGSCI. For more information, see the GGSCI online help or the Oracle GoldenGate reference documentation.

OGG-02611: Error ({0,number,0}-{1}) when validating supplemental checkpoint table {2}, SQL: {3}. The table may not exist. If you upgraded from Oracle GoldenGate 11.2.1.0.0 or earlier, add this table with the UPGRADE CHECKPOINTTABLE command in GGSCI.

Cause: Validation of the supplemental checkpoint table failed, possibly because the table does not exist. This table is required for upgrades from version 11.2.1.0.0 or earlier.

Action: Add the supplemental checkpoint table with the UPGRADE CHECKPOINTTABLE command in GGSCI after an upgrade from release 11.2.1.0.0 or earlier. For help, see the GGSCI online help or the Oracle GoldenGate reference documentation.

OGG-02612: Supplemental checkpoint table does not exist. Create a supplemental checkpoint table with the UPGRADE CHECKPOINTTABLE command in GGSCI if you have upgraded from release 12.1.1.0.0 or earlier.

Cause: The supplemental checkpoint table does not exist.

Action: Create a supplemental checkpoint table with the UPGRADE CHECKPOINTTABLE command in GGSCI. For help, see the GGSCI online help or the Oracle GoldenGate reference documentation.

OGG-02613: Error ({0}) while updating DB checkpoint.

Cause: An error occurred in the database server while updating the database checkpoint table.

Action: Resolve the database error and restart Replicat.

OGG-02615: Login to the database as user {0} failed because of error {1}

Cause: Logon to the database failed because of the reported error.

Action: Correct the error, and then restart the process.

OGG-02616: Unable to initialize database connection because of error {0}

Cause: Logon to the database was successful, but the connection could not be initialized because of the reported error.

Action: Correct the error, and then restart the process.

OGG-02617: A default source catalog name is not specified for the SOURCECATALOG parameter.

Cause: The SOURCECATALOG parameter does not contain a specification for the default source catalog name.

Action: Specify the default source catalog name or remove the SOURCECATALOG parameter.

OGG-02618: The SOURCECATALOG parameter is not supported for this database version.

Cause: The parameter file contains the SOURCECATALOG parameter, which is not supported for the database that is configured as the Oracle GoldenGate datasource.

Action: Remove the SOURCECATALOG parameter from the parameter file.

OGG-02619: Wildcards are not supported for the default source catalog name {0} in the SOURCECATALOG parameter.

Cause: The SOURCECATALOG parameter specifies a wildcarded name as the default source catalog name. Wildcards are not permitted for the default catalog name.

Action: Specify the full default source catalog name or remove the SOURCECATALOG parameter.

OGG-02620: The source catalog name for table {0} cannot be wildcard because no catalog name or non-wildcard catalog name is specified for target table {1} in TABLE/MAP.

Cause: The source catalog in the TABLE/MAP parameter is wildcarded, but a catalog is not specified or non-wildcard catalog name is specified for the target table. In this case, the source wildcard cannot be resolved to the correct target catalog.

Action: Edit the TABLE/MAP parameter to specify the full source catalog name, or keep the source wildcard but also specify a wildcard catalog name for the target table.

OGG-02621: A catalog name is specified for source table {1} in the TABLE/MAP parameter, but no schema name is specified for target table {0}.

Cause: In the TABLE/MAP specification, a catalog is specified for the source table, but a schema name is not specified for the target table.

Action: Specify a schema name for the target table in the TABLE/MAP statement.

OGG-02622: A catalog name is specified for target table {1} in the TABLE/MAP parameter, but no schema name is specified for source table {0}.

Cause: In the TABLE/MAP specification, a catalog is specified for the target table, but a schema name is not specified for the source table.

Action: Specify a schema name for the source table.

OGG-02623: Default source catalog name {0} will be used for source table name {1} mapping.

Cause: A default source catalog name is specified with the SOURCECATALOG parameter and will be used when mapping the specified source table.

Action: None

OGG-02624: Default source catalog name {0} is specified but schema name is not specified for the source table name {1}.

Cause: A default source catalog name is specified with the SOURCECATALOG parameter, but schema name is not specified for the source table name.

Action: Remove SOURCECATALOG parameter or specify schema name for the source table name.

OGG-02625: Invalid TARGET wildcard table name {0} is specified.

Cause: The wildcard resolution failed because question mark is specified for the target table name or more than one wildcard was specified for a name part.

Action: Fix the syntax. A target wildcarded specification can have only one asterisk (like rpt.* or rpt.tab*). For more information, see TABLE and MAP in the Oracle GoldenGate reference documentation.

OGG-02626: Processing more than {0} direct load rollback records from redo thread# {1} with xid {2,number,0}.{3,number,0}.{4,number,0} (0x{5}.{6}.{7})

Cause: Extract is processing a rollback operation that resulted in more than the stated number of direct load rows being rolled back.

Action: None

OGG-02627: Object with object number {0} is compressed. Table compression is not supported by classic capture.

Cause: Table compression is not supported by Extract in a classic capture configuration.

Action: None

OGG-02628: Missing exclusion specification for {0} parameter.

Cause: An exclusion object specification for TABLEEXCLUDE, SCHEMAEXCLUDE or CATALOGEXCLUDE is not specified.

Action: Specify an object name in the parameter or remove the parameter.

OGG-02629: Wildcarded schema names are not supported for this database. Ignoring SCHEMAEXCLUDE parameter.

Cause: The SCHEMAEXCLUDE parameter is specified for a database that does not support wildcarded schema names.

Action: Remove the SCHEMAEXCLUDE parameter.

OGG-02630: Catalog names are not supported for this database. Ignoring CATALOGEXCLUDE parameter.

Cause: The CATALOGEXCLUDE parameter is specified for a database that does not support wildcarded catalog names.

Action: Remove the CATALOGEXCLUDE parameter.

OGG-02631: NORENAME option is not supported for CATALOGEXCLUDE parameter.

Cause: The CATALOGEXCLUDE parameter does not support a NORENAME option.

Action: Remove the NORENAME option from the CATALOGEXCLUDE parameter.

OGG-02632: Invalid exclusion specification {0} is specified for {1} parameter.

Cause: The parameter contains an invalid exclusion specification.

Action: Specify a valid exclusion specification. For help, see the Oracle GoldenGate reference documentation.

OGG-02633: Exclusion specification {0} for parameter {1} excludes all objects.

Cause: The parameter contains an invalid exclusion specification that excludes all objects from mapping.

Action: Specify a valid exclusion specification. For help, see the Oracle GoldenGate reference documentation.

OGG-02634: Default source catalog name {0} will be used for table exclusion specification {1}.

Cause: A default source catalog name is specified with the SOURCECATALOG parameter and will be used for the table exclusion specification.

Action: None

OGG-02635: The database does not support catalog names. Ignoring SOURCECATALOG parameter {0} specified for TABLE clause '{1}'.

Cause: The source database does not support catalog names.

Action: Remove the SOURCECATALOG parameter.

OGG-02636: The TABLE specification '{0}' for the source table {1} does not include a catalog name. The database requires a catalog name.

Cause: The source table name in the TABLE statement does not include a catalog name. The database requires a catalog name.

Action: Add a catalog name to the source table specification of the TABLE/MAP statement.

OGG-02637: The target catalog name for table {0} cannot have a wildcard because no catalog name is specified for source table {1} in the MAP parameter.

Cause: The target catalog in the MAP parameter is wildcarded, but a catalog is not specified for the source table. The source wildcard cannot be resolved to the correct target catalog.

Action: Edit the MAP parameter to specify the full target catalog name, or keep the target wildcard and specify a catalog name for the target table.

OGG-02638: No schema is specified for table {0} in the MAP clause '{1}'. Schema is required.

Cause: The table specification does not include an explicit schema name.

Action: To specify a schema other than the default login schema, edit the parameter file to specify the correct schema.

OGG-02639: The table specification {0} in the MAP parameter '{1}' includes a catalog name, but the database does not support catalog names.

Cause: The name of the target table in the TARGET clause of the MAP statement includes a catalog name, but the target database does not support catalog names.

Action: Remove the catalog from the table specification.

OGG-02640: The format of trail file {0} does not support catalog names. Remove the catalog name from table specification {1} in TABLE clause '{2}'.

Cause: The trail file format specified by FORMAT RELEASE/LEVEL does not support catalog names, but the table specification includes a catalog name.

Action: Remove the catalog name from the target table specification.

OGG-02641: Source table name {0} in TABLE clause '{1}' has a wildcarded catalog name. The format of trail file {2} does not support catalog names.

Cause: The trail file format specified by FORMAT RELEASE/LEVEL does not support catalog names. The source table name is being written to the trail file without the catalog name.

Action: Specify a non-wildcarded source catalog name, or specify a trail format that supports catalog names.

OGG-02642: Trail file {0} format does not support catalog names. The catalog name of the source table {1} specified in TABLE clause '{2}' will be removed.

Cause: The trail file format specified by FORMAT RELEASE/LEVEL does not support catalog names. The source table name is being written to the trail file without the catalog name.

Action: None

OGG-02643: Wildcarded catalog name of source table specification {0} cannot be mapped to target table specification {1} that has no catalog name in TABLE clause '{2}'.

Cause: The source table name includes a wildcarded catalog name and is being mapped to a target table name that does not include a catalog name. This is not supported.

Action: Specify a non-wildcarded source catalog name, or specify a target table name that includes a catalog name.

OGG-02644: The catalog portion of source table name {0} in TABLE clause '{1}' will not be written to trail file {2}.

Cause: The catalog portion of the source table name will be removed before being written to the trail, because the source table name is explicitly mapped to a target table name that does not include a catalog name.

Action: None

OGG-02645: Source table name {0} that does not include a catalog name cannot be mapped in TABLE clause '{2}' to target table {1} that has a wildcarded catalog name.

Cause: A source table specification that does not include a catalog name is mapped to a target table specification that includes a wildcarded catalog name.

Action: Specify a non-wildcarded target catalog name, or include a catalog name in the source table specification.

OGG-02646: Source table specification {0} in TABLE clause {1} has no catalog name and will be mapped to target table {2} specification that has a catalog name.

Cause: A source table specification that does not include a catalog name is mapped to a target table specification that includes a catalog name.

Action: None

OGG-02647: Cannot specify table clause '{0}' for trail file {1} because the trail specifies a different target table name format.

Cause: A table name with a catalog name and one without a catalog name cannot be output to the same trail file. A different target table name format is specified by the table clause for the specified trail file.

Action: Remove the catalog name from the TABLE clause or add a catalog name to the TABLE clause, or output the table to a different trail file.

OGG-02648: Table name {0} specified in TABLE/MAP clause '{1}' contains a wildcarded schema or catalog. The database does not support wildcards for those objects.

Cause: Wildcarded schemas or catalogs are not supported by this database.

Action: See the rules for schema and catalog wildcarding in the Oracle GoldenGate documentation or contact Oracle Support.

OGG-02649: Source wildcard specification {0} includes a catalog name, but the source table name {1} does not include a catalog name.

Cause: A catalog name is specified for the source wildcard specification, but the source table name does not include a catalog name.

Action: Remove the catalog name from the source wildcard specification.

OGG-02650: Source wildcard specification {0} does not include a catalog name, but the source table name {1} includes a catalog name.

Cause: A catalog name is not specified for the source wildcard specification, but the source table name includes a catalog name.

Action: Add a catalog name to the source wildcard specification.

OGG-02651: Parameter {0} syntax error: {1}

Cause: The syntax of the specified parameter is incorrect.

Action: Check for spelling errors, or see the Oracle GoldenGate reference documentation for the correct syntax.

OGG-02652: Missing interval value.

Cause: The interval value was not specified.

Action: Specify the interval value.

OGG-02653: Invalid interval value {0} was specified.

Cause: An invalid interval value was specified.

Action: Specify the correct interval value.

OGG-02654: Missing time qualifier in interval specification.

Cause: The time/interval value was specified without a time qualifier such as DAYS, HOURS, MINUTES or SECONDS.

Action: Specify the time qualifier.

OGG-02655: Invalid time qualifier {0} was specified. Time qualifier must be either DAYS, HOURS, MINUTES or SECONDS.

Cause: An invalid time qualifier was specified for the time/interval value.

Action: Specify a valid time qualifier.

OGG-02656: The specified interval value {0} is out of range. The value must be between {1} and {2}.

Cause: The specified interval value is out of range.

Action: Specify a valid interval value.

OGG-02657: No schema is specified for table exclusion specification '{0}'.

Cause: A schema was not explicitly specified for the TABLEEXCLUDE parameter and there was no default schema.

Action: Edit the parameter file to specify the correct schema, or use the default schema by adding DBLOGIN to the parameter file.

OGG-02658: No schema is specified for table exclusion specification '{0}'. Using default schema {1}.

Cause: A schema was not explicitly specified for the TABLEEXCLUDE parameter. The process is using the default login schema.

Action: To use a schema other than the default login schema, edit the parameter file to specify the correct schema.

OGG-02659: Could not retrieve logon catalog name

Cause: A database error may be preventing the process from retrieving the logon catalog name.

Action: Contact Oracle Support.

OGG-02660: Retrieving table definition for table specification {0} is prohibited when logged on to database {1}.

Cause: An attempt to retrieve the table definition failed because the process is not logged on to the root level database.

Action: Either log on to the root database or specify a catalog name in the logon to the current database.

OGG-02661: Replicat is not allowed to log on to the root level database.

Cause: Replicat logged into the root level database.

Action: Modify the Replicat parameter file so that Replicat logs on to a pluggable database, not the root database.

OGG-02662: Exclusion specification {0} specified for {1} parameter has a catalog name, but catalog names are not supported by this database.

Cause: The parameter contains an exclusion specification that specifies a catalog name, but the database does not support catalogs.

Action: Remove the catalog name from the exclusion specification.

OGG-02663: Missing catalog name in exclusion specification {0} specified for {1} parameter.

Cause: The catalog name is missing from the exclusion specification.

Action: Specify a catalog name in the exclusion specification, or specify a default catalog name with the SOURCECATALOG parameter.

OGG-02664: Exclusion specification {0} specified for {1} parameter has a wildcarded schema, but the wildcarded schema name is not supported for the database.

Cause: Wildcarded schemas are not supported for this database.

Action: See the rules for schema wildcarding in the Oracle GoldenGate documentation or contact Oracle Support.

OGG-02665: Login catalog name {0} will be used for target table name {1} mapping.

Cause: A catalog name is not specified for the target table for the database. Login catalog will be used when mapping the specified target table.

Action: None

OGG-02666: Could not retrieve default catalog name

Cause: A database error may be preventing the process from retrieving the default catalog name.

Action: Contact Oracle Support.

OGG-02667: Default catalog name {0} will be used for table exclusion specification {1}.

Cause: A default catalog name will be used for the table exclusion specification.

Action: None

OGG-02668: Default catalog name {0} will be used for source table name {1} mapping.

Cause: A default catalog name will be used when mapping the specified source table.

Action: None

OGG-02669: Default catalog name {0} will be used for target table name {1} mapping.

Cause: A default catalog name will be used when mapping the specified target table.

Action: None

OGG-02670: Default source catalog name {0} will be used for schema exclusion specification {1}.

Cause: A default source catalog name is specified with the SOURCECATALOG parameter and will be used for the schema exclusion specification.

Action: None

OGG-02671: A database login was not established to retrieve a table definition.

Cause: The [SOURCEDB | TARGETDB] USERID parameter to login to the database was not specified before the TABLE parameter.

Action: Add the [SOURCDB] USERID parameter before the TABLE parameter.

OGG-02672: No DB login established to retrieve a definition for table {0}

Cause: The [SOURCEDB | TARGETDB] USERID parameter must be specified in order to retrieve a definition from the database.

Action: Add the [SOURCDB | TARGETDB] USERID parameter before the TABLE or MAP parameter.

OGG-02678: Unrecognized GLOBALS parameter {0} is ignored. Parameter could be misspelled or unsupported.

Cause: The parameter is either specified incorrectly or is not valid for this version of Oracle GoldenGate.

Action: Check the GLOBALS parameter file for the correct syntax, spelling, and any required terminators such as the semi-colon. Also make certain the parameter is supported for this version of Oracle GoldenGate. To do both of those things, check the reference documentation for your version of Oracle GoldenGate.

OGG-02679: The Replicat process logged on to database {0} and can only apply to that database.

Cause: Replicat can only apply to the database it logged on to, and cannot apply to any other database. Informational only.

Action: None

OGG-02680: ENABLECATALOGNAMES parameter is specified, enabling catalog name support.

Cause: ENABLECATALOGNAMES parameter is specified in GLOBALS and the catalog name is supported.

Action: None

OGG-02681: The catalog name is missing. Fully qualified name for table {0} is required for root database

Cause: The process logged on to the root level database, but the table name was specified without a catalog name. A three-part name is required to log onto the root database.

Action: Add a catalog name to the table specification.

OGG-02682: Cannot execute a command to catalog {0} while logged in to catalog {1}

Cause: A process can only execute a command to its login catalog.

Action: Specify a catalog that is the same as the login catalog or log in to the root level database.

OGG-02683: Invalid schema specification {0} for ADD/INFO/DELETE SCHEMATRANDATA.

Cause: An invalid schema was specified for the ADD/INFO/DELETE SCHEMATRANDATA command.

Action: Specify a valid schema.

OGG-02684: Table definition output {0} {1} is specified but the output format level {2} is already specified.

Cause: Table definition file output format is specified twice or more in different output format using FORMAT LEVEL/RELEASE parameter.

Action: Specify table definition file output format only once.

OGG-02685: Ignoring SOURCECATALOG parameter {0} specified for TABLE parameter '{1}' which contains a catalog specification.

Cause: The TABLE clause already specifies a catalog name for the specified source table.

Action: Remove the SOURCECATALOG parameter or remove the catalog name from the source table name.

OGG-02686: Default catalog name {0} will be used for schema exclusion specification {1}.

Cause: A default catalog name will be used for the schema exclusion specification.

Action: None

OGG-02687: Invalid catalog name {0} is specified for SOURCECATALOG parameter.

Cause: The catalog name specified for the SOURCECATALOG parameter is invalid.

Action: Specify the correct catalog name.

OGG-02688: Table definition output character set {0} is specified, but the output character set {1} is already specified.

Cause: Multiple CHARSET parameters exist and specify different values for the output character set of the definitions file.

Action: Specify only one CHARSET definition for the character set of the DEFGEN output file.

OGG-02689: The NOCATALOG parameter is specified after the TABLE parameter.

Cause: NOCATALOG parameter is specified after TABLE parameter.

Action: Specify the NOCATALOG parameter before any TABLE parameters.

OGG-02690: Wildcard catalog name {0} is incompatible with the NOCATALOG parameter.

Cause: A catalog name is specified in a TABLE parameter, but the NOCATALOG parameter is specified for that TABLE parameter.

Action: Remove the NOCATALOG parameter or remove the catalog specification from the TABLE specification.

OGG-02691: Cannot specify TABLE parameters with different catalog names when Defgen parameters NOCATALOG or FORMAT LEVEL 3 or less is specified.

Cause: The NOCATALOG parameter or FORMAT LEVEL 3 or less is being used in the Defgen parameter file to prevent the output of catalog names to the definitions file, but the TABLE parameters specify different catalog names.

Action: Remove the NOCATALOG or FORMAT LEVEL parameter to allow three-part names from different catalogs to be written to the definitions file. To keep those parameters, specify TABLE parameters that all have the same catalog name.

OGG-02692: Cannot specify format level of {0} for definitions file {1} that already has a format level of {2}.

Cause: The output mode of DEFGEN is set to APPEND mode, and the specified format level is different from the current format level of the existing definitions file. In APPEND mode, the existing file and new output must be the same format level.

Action: Remove the FORMAT parameter.

OGG-02693: The checkpoint table name cannot contain a wildcard.

Cause: The checkpoint table name specified with CHECKPOINTTABLE in the GLOBALS file cannot contain a wildcard.

Action: Specify a non-wildcarded name.

OGG-02694: ASCII trail format does not support DDL.

Cause: The DDL option is enabled for one or more trails that are configured for FORMATASCII, FORMATSQ L or FORMATXML output.

Action: Remove the DDL option or do not specify FORMATASCII, FORMATSQ L or FORMATXML as the trail format.

OGG-02695: ANSI SQL parameter syntax is used for parameter parsing.

Cause: Default parameter syntax is used.

Action: None

OGG-02696: NON-ANSI SQL parameter syntax is used for parameter parsing.

Cause: NOUSEANSISQLQUOTES parameter is specified for compatibility with legacy parameter syntax.

Action: None

OGG-02697: LOB write failed. LOB exceeds the supported size. LOB offset: {0}

Cause: The LOB write operation failed because the size of the LOB is equal to or greater than that maximum supported size of 4GB.

Action: Remove the specified LOB column or the table that contains it from the Oracle GoldenGate configuration.

OGG-02698: LOB trim failed. LOB exceeds the supported size. LOB offset: {0}

Cause: The LOB trim operation failed because the size of the LOB is equal to or greater than that maximum supported size of 4GB.

Action: Remove the specified LOB column or the table that contains it from the Oracle GoldenGate configuration.

OGG-02699: LOB erase failed. LOB exceeds the supported size. LOB offset: {0}, length: {1}

Cause: The LOB erase operation failed because the size of the LOB is equal to or greater than that maximum supported size of 4GB.

Action: Remove the specified LOB column or the table that contains it from the Oracle GoldenGate configuration.

OGG-02700: LOB size exceeds the maximum supported size {0} bytes. LOB offset: {1}, length: {2}

Cause: The LOB size exceeds the Oracle GoldenGate maximum allowed size.

Action: Remove the specified LOB column or the table that contains it from the Oracle GoldenGate configuration.

OGG-02701: LOB size exceeds the maximum supported size {0} bytes after character set conversion. LOB offset: {1}, length: {2}

Cause: The LOB size exceeds the Oracle GoldenGate maximum allowed size after character set conversion.

Action: Remove the specified LOB column or the table that contains it from the Oracle GoldenGate configuration.

OGG-02702: VARCHAR2 size exceeds the maximum supported size 4000 bytes.

Table: {0}, Column: {1}

Cause: The VARCHAR2 size exceeds the Oracle GoldenGate extract maximum allowed size. It is only supported by Integrated Extract and initial data load.

Action: Use Integrated Extract or remove the specified VARCHAR2 column or the table that contains it from the Oracle GoldenGate configuration.

OGG-02703: The trail or definitions file is format level {0} and does not support database character set {1}.

Cause: The specified database character set is not supported by the previous release of Oracle GoldenGate. An older version of Replicat may not be able to apply the data properly.

Action: Contact Oracle Support.

OGG-02704: Failed to read entire LOB column {0} of table {1}. Expected length was {2} characters. Only {3} bytes was read.

Cause: Internal LOB read error.

Action: Contact Oracle Support.

OGG-02705: Invalid value given for the DDLOPTIONS parameter {0}

Cause: The specified value is not a valid one for DDLOPTIONS.

Action: See the Oracle GoldenGate reference documentation for further information.

OGG-02706: Unable to set the USE_PASSWORD_VERIFIER_LEVEL to {0} as the requested verifier was not provided in the password.

Cause: The password verifier that was requested was not present in the password string that was generated by the database.

Action: Change the SQLNET.ALLOWED_LOGON_VERSION_SERVER setting to generate the requested password verifier.

OGG-02707: UDT LOB buffer overflow, needed: {0}, allocated: {1}.

Cause: Not enough UDT read buffer was allocated.

Action: Allocate a larger LOB read buffer using the DBOPTIONS LOBBUFSIZE parameter.

OGG-02708: UDT LOB write error: {0}.

Cause: OCI error occurs when writing UDT LOB.

Action: Check the error message detail and resolve the error as described.

OGG-02750: The definition for table {0} from the target database overrides the table metadata from the trail.

Cause: ASSUMETARGETDEFS OVERRIDE was used to override the table metadata from the trail.

Action: None

OGG-02751: Unable to generate metadata record for table {0} because its definition is obtained from an earlier release definitions file, {1}.

Cause: The provided definitions file was generated using format release prior to 12.1.

Action: Regenerate the definitions file using format release 12.1 or later and restart the process.

OGG-02752: The definition for table {0} from definitions file {1} overrides the table metadata from the trail.

Cause: A SOURCEDEFS file was specified with OVERRIDE option to override the table metadata from the trail.

Action: None

OGG-02753: Unable to generate table metadata records because there are no table definitions in {0}.

Cause: Data pump was unable to generate the table metadata when the specified input trail file contained no table metadata.

Action: Perform one of the following steps: Specify a SOURCEDEFS file containing the correct definitions of all the tables in the input trail; 2) Add NO_OBJECTDEFS to the RMTTRAIL option to generate an output trail with no metadata records; 3) Remove the PASSTHRU option from the data pump's parameter file if it's specified.

OGG-02754: Initial load Extract does not support more than 65535 tables.

Cause: Initial load Extract does not support more than 65535 tables.

Action: Reduce the number of tables in the TABLE option.

OGG-02755: Unable to process metadata record for {0} from trail seq# {1,number,0} at RBA {2,number,0}.

Cause: An error occurred when deserializing the metadata record at the specified position in the trail file. This may be due to incorrect encryption key or algorithm provided to the process.

Action: None

OGG-02756: The definition for table {0} is obtained from the trail file.

Cause: The definition for the specified table is obtained from the trail file.

Action: None

OGG-02757: Trail file {0} contains no table definition for {1}.

Cause: Data pump or Replicat encountered a trail file with no table definitions after the definition for the specified table was extracted from a previous file sequence.

Action: If SOURCEDEFS is specified in the parameter file then verify the source definitions file contains the correct definitions for all the tables in the specified trail file then restart the application. If SOURCEDEFS is not specified then add a SOURCEDEFS option with a correct definitions file then restart the application.

OGG-02758: The definition for table {0} is obtained from definitions file {1}.

Cause: The definition for the specified table is obtained from a source definitions file.

Action: None

OGG-02759: The definition for table {0} is obtained from the target database.

Cause: The definition for the specified table is obtained from the target database.

Action: None

OGG-02760: ASSUMETARGETDEFS is ignored because trail file {0} contains table definitions.

Cause: Replicat ignored ASSUMETARGETDEFS because the table definitions from the specified trail file were more reliable.

Action: Perform one of these actions: * Remove the ASSUMETARGETDEFS parameter. * Append OVERRIDE to the ASSUMETARGETDEFS parameter if you want the process to use the table definitions from the target database. Note that doing this may result in data corruption if the target table definitions are not in sync with the trail records.

OGG-02761: Source definitions file, {0}, is ignored because trail file {1} contains table definitions.

Cause: Data pump and Replicat ignored the source definitions files because the table definitions from the specified trail file were more reliable.

Action: Perform one of these actions: * Remove the SOURCEDEFS parameter. * Append OVERRIDE to the SOURCEDEFS parameter if you want the process to use the source definitions file. Note that doing this may result in data corruption if the source definitions file is not in sync with the trail records.

OGG-02762: NO_USE_TRAILDEFS is specified. All table definitions from trail files are ignored.

Cause: The global parameter, NO_USE_TRAILDEFS, was specified when the trail file contains table definitions."

Action: Remove NO_USE_TRAILDEFS from the GLOBALS parameter file to use the table definitions from the trail and avoid this message.

OGG-02763: Unable to retrieve catalog metadata: {0}.

Cause: The query to retrieve catalog metadata did not complete successfully.

Action: Make sure the extract user has privileges to query catalog metadata.

OGG-02764: OBJECTDEFS is ignored when the input trail file does not have full table metadata or NO_USE_TRAILDEFS is specified.

Cause: Pump ignored the OBJECTDEFS option and generated metadata records with no table definition when the table definitions from the input trail file were not available or not used.

Action: None

OGG-02765: Trail format version must be 12.2 or higher to extract changes from multiple catalogs with mixed character sets or timezones.

Cause: The trail format release is prior to Oracle GoldenGate 12c (12.2.1)

Action: None

OGG-02800: Parameter {0} can only be used when Extract is connected to a standby database.

Cause: This parameter was used when Extract was connected to the primary database. It must only be used when Extract connects to a standby database.

Action: Remove the parameter from the parameter file or move Extract to the standby database.

OGG-02801: Parameter MINEFROMACTIVEDG can only be used when the database is in READ ONLY mode.

Cause: The parameter MINEFROMACTIVEDG was used with a database that is not in READ ONLY mode.

Action: Remove the parameter or alter the database to READ ONLY mode.

OGG-02802: Classic Extract failed to retrieve the current system SCN from database.

Cause: The database is in a corrupted or unstable state.

Action: Resolve the database issue.

OGG-02803: Encountered a Data Guard role transition. Alter Extract to SCN {0} and restart Extract, or recreate Extract with the correct number of threads at SCN {0}.

Cause: Extract detected a role transaction.

Action: If the new thread number matches the original thread number after the switch, alter to specified SCN and restart Extract with proper parameter setting. If the old and new thread numbers do not match, recreate Extract from the specified SCN.

OGG-02804: Failed to fetch current resetlogs_id from database view.

Cause: An error occurred when fetching current resetlogs_id from the database view.

Action: Contact Oracle support.

OGG-02805: Resetlogs_id from file header {0} doesn't match expected value of {1}.

Cause: Resetlogs_id from Oracle redo log files does not match expected value.

Action: Make sure old abandoned logs are deleted from system views on logs or archived log.

OGG-02806: Extract is waiting for logs to become available based on time {0} from incarnation with relogs_id of {1}.

Cause: Extract cannot find logs from said incarnation based on timestamp given.

Action: Make sure log transporter is running and logs are being transferred.

OGG-02807: Extract is waiting for logs to become available based on SCN {0} from incarnation with relogs_id of {1}.

Cause: Extract cannot find logs from said incarnation based on scn value given.

Action: Make sure log transporter is running and logs are being transferred.

OGG-02808: Standby database is not running. Start it, then start Extract again.

Cause: The Extract process tried to capture from a standby database that is not running.

Action: Start the standby database.

OGG-02809: Oracle Managed Redo Process(MRP) is not running on the Standby database.

Cause: Oracle Managed Redo Process(MRP) is not running.

Action: Start the Oracle Managed Redo Process (MRP).

OGG-02810: A relative timestamp, such as NOW, was used as starting position for Extract on an Oracle Active Data Guard standby database.

Cause: A relative value was specified as the start position for this Extract.

However, only an SCN or timestamp value can be used when capturing data from an Oracle Active Data Guard standby database.

Action: Start Extract at a specific SCN or timestamp. For help with START EXTRACT syntax, issue the HELP command in GGSCI, or see the Oracle GoldenGate reference documentation.

OGG-02811: Resetlogs change# does not match expected value. Expecting {0} or {1}, retrieved {2}.

Cause: Extract attempted to capture data from a database incarnation that does not match the prior branch. This may be due to multiple role transitions or other database recovery operations.

Action: Contact Oracle Support.

OGG-02812: The USEPREVRESETLOGSID parameter is specified for this process, but the standby database has not been reset.

Cause: The USEPREVRESETLOGSID parameter is specified in the Extract parameter file. However, the standby database was not reset and there is no data from the previous incarnation to capture. This parameter should only be used to capture data from a previous incarnation of the database.

Action: Remove the USEPREVRESETLOGSID parameter from the Extract parameter file.

OGG-02813: Cannot access database {0} to capture table {1}. Verify database name and login privileges.

Cause: The specified container database does not exist or the login user does not have sufficient privileges to access the container database.

Action: Specify the correct container database name or make certain the Oracle GoldenGate user has sufficient privileges to access the container database. Consult the Oracle GoldenGate documentation for Oracle Database. If the problem persists, contact Oracle Support.

OGG-02814: DDLOPTIONS ADDTRANDATA is not supported on read only database

Cause: This parameter leads to an attempt to add TRANDATA on new object and is not allowed.

Action: Delete or comment out the DDLOPTIONS ADDTRANDATA parameter.

OGG-02815: Detecting thread {0} is down at primary database when positioning based on SCN {1}.

Cause: Extract detects that a thread on the primary database is down.

Action: Ensure that this down thread is intended.

OGG-02816: In ADG mode, ADGTIMEOUT value {0} must be greater than ADGAPPLYCHECKFREQ value {1}

Cause: Value for ADGTIMEOUT parameter (default is 30 seconds), must be greater than value for ADGAPPLYCHECKFREQ (default is 3 seconds).

Action: Increase ADGTIMEOUT value, or decrease ADGAPPLYCHECKFREQ value.

OGG-02817: DBOPTIONS FETCHTIMEOUT value {0} must be greater than FETCHCHECKFREQ value {1}

Cause: Value for FETCHTIMEOUT parameter (default is 30 seconds), must be greater than value for FETCHCHECKFREQ (default is 3 seconds).

Action: Increase FETCHTIMEOUT value, or decrease FETCHCHECKFREQ value.

OGG-02900: Replication of UDT and ANYDATA from redo logs is disabled. Trail FORMAT RELEASE must be 12.1 or later. Use fetch instead.

Cause: Trail FORMAT RELEASE must be 12.1 or later.

Action: To support replication of UDT and ANYDATA from redo logs, you must set FORMAT RELEASE to release 12.1 or later.

OGG-02901: Replication of UDT and ANYDATA from redo logs is not supported with the Oracle compatible parameter setting. Using fetch instead.

Cause: Replication of UDT and ANYDATA from redo logs requires Oracle compatible parameter 12.0.0.0.0 or later.

Action: See the Oracle GoldenGate documentation for help with required Oracle database compatible parameter setting requirements.

OGG-02902: Replication of UDT and ANYDATA from redo logs is not supported because the patch required for Oracle database is missing. Use fetch instead.

Cause: The patch that is required to replicate UDT and ANYDATA from redo logs cannot be found.

Action: Apply Oracle Patch 18038108 to the source database.

OGG-02903: Replication of UDT and ANYDATA from redo logs is not supported because the Oracle database version is not release 12.1 or later.

Cause: Replication of UDT and ANYDATA from redo logs requires Oracle 12.1.0.1 or higher version.

Action: Upgrade to Oracle Database release 12.1.0.1 or later. For Oracle Database release 12.1.0.1, apply Oracle Patch 18038108 to the target database.

OGG-02904: Replication of PARTIAL XML containing NCHAR/NVARCHAR/NCLOB data may cause divergence.

Cause: Full support to NCHAR/NVARCHAR/NCLOB in PARTIAL XML requires Oracle Database release 12.1.0.1 or later versions. For Oracle Database release 12.1.0.1, apply Oracle Patch 18038108 to the target database.

Action: The workaround is to use the FETCHPARTIALXML option in Extract so that Replicat does not encounter PARTIAL XML. Contact Oracle support.

OGG-02905: Replication of OID column in object tables may diverge.

Cause: Extract is not configured to capture DML from CREATE TABLE AS SELECT statement.

Action: Configure Extract to capture DML from CREATE TABLE AS SELECT statement, and then restart the process.

OGG-02906: Replication of UDT and ANYDATA from redo logs requires Replicat 12.1.2.1.0 or later.

Cause: Replication of UDT and ANYDATA from redo logs may diverge if Replicat 12.1.2.1.0 or later is not used.

Action: Make sure that Replicat 12.1.2.1.0 or later is used. Ignore this message if you are using the right version.

OGG-02907: User provided parameters conflict.

Cause: _LOGMINER_GET_CTAS_DML and GETCTASDML cannot conflict.

Action: Change _LOGMINER_GET_CTAS_DML or GETCTASDML.

OGG-02908: CTAS not supported with DDL trigger metadata.

Cause: You cannot CTAS parameter while running with DDL metadata trigger.

Action: Remove GETCTASDML from your parameter file or run with no DDL metadata trigger.

OGG-02909: CTAS not supported with replicat versions lower than 12.1.2.1.0.

Cause: CTAS functionality must be used with replicat versions at or above 12.1.2.1.0.

Action: Ensure that the trail files produced with CTAS enabled are not consumed by replicat versions less than 12.1.2.1.0.

OGG-02910: Sequence {0} not processed, sequence values are synchronized at run-time

Cause: SEQUENCE capture is not supported by initial load capture, and is ignored.

Action: None

OGG-02911: Processing table {0}

Cause: Initial load capture is processing the table.

Action: None

OGG-02912: Patch 17030189 is required on your Oracle mining database for trail format RELEASE 12.2 or later.

Cause: The patch that is required by Integrated Dictionary cannot be found.

Action: Either apply Oracle Patch 17030189 to the mining database, or change the trail format to RELEASE 12.1 (or earlier). If neither of these options are viable, as a temporary workaround you may apply script prvtlmpg.plb (included in the Oracle GoldenGate installation directory) to the mining database.

OGG-02913: Metadata format of the definitions file for table {0} does not match trail format.

Cause: The definitions file uses a metadata format that is incompatible with the trail format.

Action: Regenerate the definitions file using the correct metadata format then restart the application.

OGG-02914: Unsupported XML storage option encountered for table {0}, column {1}.

Cause: The specified XML column uses a storage option that is not supported.

Action: Exclude the table from the TABLE or MAP parameter. For supported storage options, see the Oracle GoldenGate documentation.

OGG-02915: Extract is configured with multiple incompatible trail formats.

Cause: Extract is configured with multiple trail formats that are not compatible with each other.

Action: Configure Extract to use compatible trail formats. For compatibility of different trail formats, see the Oracle GoldenGate documentation.

OGG-03000: Table {0} has a lower case ASCII, non-ASCII character or special character such as white space or dot that is not supported when NOEXTATTR option is specified.

Cause: DEFGEN was run with the NOEXTATTR parameter, and the specified table contains a lower case ASCII, non-ASCII or special character.

Action: Exclude the table from the DEFGEN parameter file, or run DEFGEN without the NOEXTATTR parameter.

OGG-03001: Column {0} of table {1} has a lower case ASCII, non-ASCII character or special character that is not supported when NOEXTATTR option is specified.

Cause: DEFGEN was run with the NOEXTATTR parameter, and the column of the specified table contains a lower case ASCII, non-ASCII or special character, such as a white space or dot.

Action: Exclude the table from the DEFGEN parameter file, or run DEFGEN without the NOEXTATTR parameter.

OGG-03002: Target table {0} does not exist. Inexact wildcard match table {1} is being used for target table.

Cause: No table name exactly matches the target wildcard specification. A table with a name that is an inexact match was used as the target.

Action: None required.

OGG-03003: Target table {0} has a lower case ASCII, non-ASCII or special character, such as white space or dot, that is incompatible with trail format level {1}.

Cause: The name of the target table is incompatible with a trail format that is prior to the 11.2.1 release format.

Action: Exclude or rename the table that is in the TARGET clause, or specify 11.2.1 or later for the FORMAT RELEASE option of EXTTRAIL, RMTTRAIL, EXTFILE, or RMTFILE parameters.

OGG-03004: Unknown source column character set. Cannot map source column {0} to target column {1}

Cause: The trail file is written by Extract version 11.1 or earlier, but the _TRAILCHARSET parameter is specified.

Action: Specify the _TRAILCHARSET parameter or do not map a CHAR/VARCHAR column to an NCHAR/NVARCHAR column.

OGG-03005: Unable to find matching parenthesis for token {0} at location {1}.

Cause: There is a syntax error in the parameter file.

Action: Fix the syntax error in the token specification that contains incomplete parentheses.

OGG-03006: Source database character set or Target client character set is missing. OGG character set conversion is disabled.

Cause: Source database character set or Target client character set is missing.

Action: Set up character set or Target client character set.

OGG-03007: Invalid or unsupported character set {0} specified with {1} parameter.

Cause: An invalid or unsupported character set is specified with the _TRAILCHARSET parameter.

Action: Specify a valid character set, and then restart Replicat.

OGG-03010: Performing implicit conversion of column data from character set {0} to {1}.

Cause: Oracle GoldenGate is performing character set conversion because source data character set differs from target data character set.

Action: None required.

OGG-03014: Source column {0} has more characters than target column {1} can hold.

Some source characters will not be mapped during conversion from source character set {2} to target character set {3}.

Cause: The source column has more characters than the target column can hold.

Action: Specify another target column or make the target column size equal to, or greater than, the source column size.

OGG-03015: Character set conversion failure occurred between source column {0} and target column {1} when converting from source character set {2} to target character set {3}. Error code: {4}

Cause: An internal error occurred during character set conversion.

Action: Save the error message and contact Oracle GoldenGate Support.

OGG-03016: Source column {0} length becomes zero when converting from source character set {2} to target column {1} character set {3}.

Cause: An internal error occurred during character set conversion. The trail file may be corrupted. This message is for sanity checking and should not occur in a production environment.

Action: Contact Oracle Support.

OGG-03017: Target column {1} length becomes zero when converting from source column {0} character set {2} to target character set {3}.

Cause: This message is for sanity checking and should not occur in a production environment.

Action: Contact Oracle Support.

OGG-03018: Alternative format data found (code = {0}). Character set conversion was not performed.

Cause: Data of an alternative format was processed. Examples are binary XML, XML diff, or partial LOB.

Action: None

OGG-03019: The column that is being used to evaluate the WHERE clause or FILTER clause is missing in table {0}.

Cause: The column that is being used to evaluate the WHERE clause or FILTER clause is missing, and the process cannot perform the necessary filtering of the data.

Action: Edit the WHERE or FILTER specification in the parameter file to specify a column that cannot contain a missing value.

OGG-03020: Trail character set {0} is specified.

Cause: _TRAILCHARSET parameter is specified.

Action: None

OGG-03021: Trail character set {0} is specified with REPLACEBADCHAR option.

Invalid characters will be replaced by substitute character.

Cause: _TRAILCHARSET parameter is specified with REPLACEBADCHAR option.

Action: None

OGG-03022: Unexpected return code {1} received while attempting to retrieve the {0} CCSID values.

Cause: SQLFetch returned an unexpected return code from select getvariable() for specified CCSID values.

Action: Contact Oracle Support with the details from this message.

OGG-03023: {0} CCSID {1} is not recognized.

Cause: The CCSID value obtained from DB2 is not recognized by Oracle GoldenGate.

Action: Contact Oracle Support with the details from this message.

OGG-03024: Character data marked as MIXED CCSID was encountered, but no TRAILCHARSET option was specified.

Cause: Character data marked as MIXED CCSID was encountered, but no TRAILCHARSET option was specified.

Action: Add either TRAILCHARSETASCII, TRAILCHARSETEBCDIC, or TRAILCHARSETUTF8 in the Extract parameter file.

OGG-03025: The {0} character set specified for the A2E parameter in the GLOBALS file does not match the database CCSID.

Cause: The character set specified for the A2E parameter in the GLOBALS file does not match the database CCSID.

Action: Either correct the charset specification for the A2E parameter in the GLOBALS file or edit the TABLE specification in the Extract parameter file to avoid processing tables with this native encoding.

OGG-03026: Unexpected return code {0} received while attempting to retrieve the APPLICATION ENCODING SCHEME.

Cause: An attempt to select the APPLICATION ENCODING SCHEME failed. This function is not supported prior to DB2 V9.1.

Action: Ensure that the DEFAULT APPLICATION ENCODING SCHEME is EBCDIC.

OGG-03027: The DEFAULT APPLICATION ENCODING SCHEME is {0}. Only EBCDIC is supported.

Cause: The APPLICATION ENCODING SCHEME was determined to be a value other than EBCDIC.

Action: Either change the value specified for CURRENTAPPENSCH in the ODBC initialization file to EBCDIC or remove the CURRENTAPPENSCH parameter.

OGG-03028: Table {0}, with {1} encoding, cannot be processed with {2} parameter specification.

Cause: A table was encountered with encoding that cannot be processed with the specified TRAILCHARSET parameter.

Action: Correct the parameter file to either eliminate this table from processing or change the TRAILCHARSET specification to a value that supports the data in this table.

OGG-03029: Invalid source table name {0} specified.

Cause: An invalid source table name is specified in the TABLE/MAP parameter.

Action: Specify the correct source table name.

OGG-03030: Invalid target table name {0} specified.

Cause: An invalid target table name is specified in the TABLE/MAP parameter.

Action: Specify the correct target table name.

OGG-03031: Character set conversion is not supported in a data pump. Incoming ASCII data will not be converted to EBCDIC.

Cause: The character set of the input file does not match the character set of the platform on which the data pump is running.

Action: Note that column data is ASCII and any attempt to process it as EBCDIC will likely fail.

OGG-03032: Character set conversion is not supported in a data pump. Incoming EBCDIC data will not be converted to ASCII.

Cause: The character set of the input file does not match the character set of the platform on which the data pump is running.

Action: Note that column data is EBCDIC and any attempt to process it as ASCII will likely fail.

OGG-03033: Character set conversion is not supported in a data pump.

Cause: The parameter EBCDICTOASCII was specified in the data pump parameter file.

Action: Remove the parameter EBCDICTOASCII from the data pump parameter file.

OGG-03036: Database character set identified as {0}. Locale: {1}

Cause: The process verified the character set of the database. Informational only.

Action: None

OGG-03037: Session character set identified as {0}.

Cause: The process verified the character set of the database connection. Informational only.

Action: None

OGG-03038: Table {0}, column {1}, data type: {2} supported only for Unicode tables.

Cause: The data type shown is currently only supported for Unicode tables.

Action: Exclude this table from Extract processing, either by removing its explicit specification in the TABLE parameter, or by using the TABLEEXCLUDE parameter if it was included as the result of a wildcard specification.

OGG-03039: Database character set {0} is not supported.

Cause: Database character set is not supported.

Action: Contact Oracle Support.

OGG-03040: Session character set {0} is not supported.

Cause: Session character set is not supported.

Action: Contact Oracle Support.

OGG-03041: Post-DDL command successful: {0}

Cause: Replicat is executing a post-DDL command.

Action: None

OGG-03042: Character set value is not specified for defgen CHARSET parameter.

Cause: No value is specified for the Defgen CHARSET parameter.

Action: Specify a character set for the CHARSET parameter in the Defgen parameter file.

OGG-03043: Character set value {0} specified for defgen CHARSET parameter is ignored.

Cause: The CHARSET parameter and the NOEXTATTR parameter are both specified in the Defgen parameter file. The CHARSET parameter is ignored.

Action: Remove either NOEXTATTR or CHARSET.

OGG-03044: Invalid character set {0} is specified for defgen CHARSET parameter.

Cause: An invalid character set is specified for the Defgen CHARSET parameter.

Action: Specify the correct character set for CHARSET.

OGG-03045: Character set {0} specified for defgen CHARSET parameter is not supported.

Cause: An unsupported character set is specified for the Defgen CHARSET parameter.

Action: Specify a supported character set.

OGG-03046: The definitions file {0} is a version that does not support the extended attributes of character encoding and locale.

Cause: Defgen is in APPEND mode, and the existing contents are of an older format that does not include the extended attributes for character encoding and locale. For consistency, appended definitions will not have extended attributes.

Action: Specify the Defgen parameter NOEXTATTR to cause Defgen to omit the extended attributes, or re-run Defgen for all tables to a new file if you want to include attributes that support character encoding and locale. See the Oracle GoldenGate documentation for more information on globalization support.

OGG-03047: Existing defs file {0} has extended attribute. NOEXTATTR parameter is ignored.

Cause: Defgen is in APPEND mode, and the existing contents are of the format that includes the extended attributes for character encoding and locale. For consistency, appended definitions will have extended attributes, and NOEXTATTR is being ignored.

Action: Remove the NOEXTATTR parameter from the Defgen parameter file.

OGG-03048: Existing definitions file {0} is written in character set {1}. New definitions are being appended in the same character set.

Cause: Defgen APPEND mode is specified. For consistency, the new definitions are being appended in the same character set as those in the existing file.

Action: None

OGG-03049: Existing defs file {0} is written in character set {1}. CHARSET parameter value {2} is ignored.

Cause: Defgen APPEND mode is specified. The character set specified by the CHARSET parameter is different from the one used in the existing definitions file and is being ignored.

Action: None

OGG-03050: Existing definitions file {0} has invalid character set name or the file is corrupted.

Cause: The existing definitions file has an invalid character set. The character set tag may be incorrect, or the file may be corrupted.

Action: Fix the character set tag if it is wrong, or create a new definitions file to replace to corrupt one.

OGG-03051: Invalid character set {0} is specified for defgen UPDATECS parameter.

Cause: An invalid character set is specified for the Defgen UPDATECS parameter.

Action: Specify the correct character set.

OGG-03052: Definitions file is encoded in character set {0}. No character set update is necessary.

Cause: The definitions file is already encoded in the character set specified by the Defgen UPDATECS parameter.

Action: None

OGG-03053: Cannot open the definitions file {0} to update the character set. Check file attributes and user permissions.

Cause: The definitions file may be read-only, or the Defgen user does not have permission to modify the file.

Action: Change the attributes of the file or give the Defgen user write permission.

OGG-03054: The character set of definitions file {0} was updated from {1} to {2}.

Cause: The Defgen parameter UPDATECS is specified, and the character set of the definitions file was updated successfully.

Action: None

OGG-03055: Failed to update character set of definitions file {0} from {1} to {2}. {3}

Cause: The disk may be full or the Defgen user does not have permission to write to the definitions file.

Action: Make sure there is enough disk space for the definitions file, and make sure the Defgen user has full permissions on the file.

OGG-03056: Source table {0} column {1} data size exceeds the maximum target table {2} column {3} size. Automatic truncation is enabled for all tables/columns without further warnings.

Cause: The source column data size exceeds the maximum target column size.

Action: Specify another target column or make the target column size equal to, or greater than, the source column size.

OGG-03057: Unexpected error code {0} while converting column {1} of table {2} from {3} to {4}.

Cause: An unexpected error was encountered during character set conversion.

Action: Contact Oracle Support.

OGG-03058: Cannot identify the character set of the operating system.

Cause: The character set of the operating system is not properly configured.

Action: Check the operating system character set and locale configuration.

OGG-03059: Operating system character set identified as {0}.

Cause: The process verified the character set of the operating system.
Informational only.

Action: None

**OGG-03060: Source column {0} has more characters than target column {1} can hold.
Some source characters will not be mapped during source column character validation of character set {2}.**

Cause: The source column has more characters than the target column can hold.

Action: Specify another target column or make the target column size equal to, or greater than, the source column size.

**OGG-03061: Character validation failure occurred between source column {0} and target column {1} when validating source column data that is in character set {2}.
Error code: {3}**

Cause: An internal error occurred during character validation.

Action: Save the error message and contact Oracle GoldenGate Support.

OGG-03062: Source column {0} contains an invalid character. Cannot write to XML file to convert from source character set {1} to XML encoding {2}.

Cause: The source column contains an invalid character and cannot be converted to XML file encoding.

Action: Do any of the following: Specify another XML encoding, fix the source database data, or use the REPLACEBADCHAR parameter to replace the invalid character.

OGG-03063: Cannot write source column {0} to XML file during conversion from source character set {1} to XML encoding {2}. The source character set is not supported.

Cause: The specified column could not be written to an XML file because Oracle GoldenGate does not support the source character set.

Action: Contact Oracle Support.

OGG-03064: Character set conversion failure occurred between source column {0} and XML file when converting from source character set {1} to XML encoding {2}. Error code: {3}

Cause: An internal error occurred during character set conversion.

Action: Save the error message and contact Oracle GoldenGate Support.

OGG-03065: Source column {0} has more characters than the maximum number of characters that target column {1} can hold. Some source characters will not be mapped during conversion from source character set {2} to target character set {3}.

Cause: The source column has more characters than the target column can hold.

Action: Specify another target column or make the target column size equal to, or greater than, the source column size.

OGG-03066: Source column {0} has more characters than the maximum number of characters that target column {1} can hold. Some source characters will not be mapped during source column character validation of character set {2}.

Cause: The source column has more characters than the target column can hold.

Action: Specify another target column or make the target column size equal to, or greater than, the source column size.

OGG-03067: Source Oracle database character set {0} is not supported.

Cause: The source Oracle database character set is not supported for this database and platform.

Action: Contact Oracle Support.

OGG-03068: Could not initialize large object memory pool.

Cause: This is internal error, failed to initialize memory pool object for large object (LOB).

Action: Contact Oracle Support.

OGG-03069: Unexpected LOB chunk ({0}) found. Expected chunk is 1.

Cause: Unexpected LOB chunk found in the trail file. Trail file may be corrupted.

Action: Check if the trail file has base DML record followed by LOB chunk 1 using logdump. Contact Oracle Support.

OGG-03070: Failed to add LOB chunk in {0}, RBA {1}.

Cause: Failed to add LOB chunk into LOB memory.

Action: Check additional error detail and contact Oracle Support.

OGG-03071: Unexpected LOB record, record fragment or out of row LOB marker in {0}, rba {1}

Cause: Unexpected LOB record found in the trail file. Trail file may be corrupted.

Action: Check additional error detail and contact Oracle Support.

OGG-03506: The source database character set, as determined from the trail file, is {0}.

Cause: The source database character set information in the trail file is being assumed as the source database character set.

Action: None

OGG-03507: The source database character set is {0} as specified by SOURCECHARSET.

Cause: The trail file version is pre-11.2.1, so the character set that is specified with the SOURCECHARSET parameter is assumed as the source database character set.

Action: None

OGG-03508: SOURCECHARSET PASSTHRU is specified. Ignoring the source database character set {1} identified in the trail file.

Cause: The SOURCECHARSET PASSTHRU parameter is specified, which directs the process to pass the data as it exists in the trail record, without performing character set conversion.

Action: None

OGG-03509: Using NLS_LANG character set {0} as the source database character set.

Cause: The version of the trail file is pre-11.2.1 and the SOURCECHARSET parameter is not specified. To assign a character set to the source data, Replicat used the character set that is specified with the NLS_LANG variable.

Action: Specify the source database character set with the SOURCECHARSET parameter.

OGG-03510: The source database character set is unknown, and the SOURCECHARSET parameter is not specified.

Cause: The trail file does not have source character set information and the SOURCECHARSET parameter is not specified. Replicat cannot map the source character data to the target database.

Action: Specify the source database character set with the SOURCECHARSET parameter.

OGG-03511: The _TRAILCHARSET parameter has been deprecated. To specify a source character set, use the SOURCECHARSET parameter.

Cause: The deprecated _TRAILCHARSET parameter is specified in the parameter file.

Action: Remove _TRAILCHARSET and then specify the source database character set with the SOURCECHARSET parameter.

OGG-03512: SOURCECHARSET PASSTHRU in a MAP statement prevents CHAR/VARCHAR/CLOB to/from NCHAR/NVARCHAR/NCLOB mapping.

Cause: The MAP statement contains the SOURCECHARSET parameter with the PASSTHRU option. This parameter specification does not allow CHAR/VARCHAR/CLOB to NCHAR/NVARCHAR/NCLOB mappings. Data must be passed through as-is without conversion.

Action: To map the specified data types, remove SOURCECHARSET with PASSTHRU. To determine how to map between different data types, see the Oracle GoldenGate data integration documentation.

OGG-03514: The SOURCECHARSET and _TRAILCHARSET parameters are both specified in the parameter file. SOURCECHARSET will be used and _TRAILCHARSET will be ignored.

Cause: The deprecated _TRAILCHARSET parameter and the SOURCECHARSET parameter are both specified in the same parameter file.

Action: Remove _TRAILCHARSET and specify the source database character set with SOURCECHARSET.

OGG-03515: Source character set {0} is specified with the SOURCECHARSET parameter.

Cause: The SOURCECHARSET parameter is being used to specify the character set of the source data.

Action: None

OGG-03516: The trail file is version 11.2.1 or later and contains the source character set {1}. The SOURCECHARSET {0} parameter will be ignored.

Cause: Because the trail file is version 11.2.1 or later and contains the source character set, the SOURCECHARSET parameter is unnecessary and is being ignored.

Action: Remove SOURCECHARSET parameter.

OGG-03517: Conversion from character set {2} of source column {0} to character set {3} of target column {1} failed because the source column contains a character that is not available in the target character set.

Cause: The source column contains a character that is not available in the character set of the target column.

Action: Set the target database character set to the same set or a superset of the source database character set.

OGG-03518: Source column {0} cannot be mapped to target column {1} during conversion from source character set {2} to target character set {3}, because the source or the target character set is not supported.

Cause: Either source or target column character set is not supported.

Action: Contact Oracle Support

OGG-03519: Found NCHAR, NVARCHAR2 or NCLOB attribute in user-defined datatype but the required HAVEUDTWITHNCHAR parameter is missing.

Cause: The source database has a user-defined datatype with the NCHAR, NVARCHAR2 or NCLOB attribute, but the HAVEUDTWITHNCHAR parameter is not specified in the Replicat parameter file.

Action: Add the HAVEUDTWITHNCHAR parameter to the Replicat parameter file.

OGG-03520: Connecting to the Oracle database using the AL32UTF8 client character set to support a user-defined type that has an NCHAR, NVARCHAR2 or NCLOB attribute.

Cause: The HAVEUDTWITHNCHAR parameter is specified to support user-defined datatypes that have an NCHAR, NVARCHAR2 or NCLOB attribute.

Action: None

OGG-03521: Invalid character for character set {0} was found while performing character validation of source column {1} maps target column {2}.

Cause: An invalid character was found in the source column.

Action: Fix the source database data or use the REPLACEBADCHAR parameter to replace the invalid character.

OGG-03522: Setting session time zone to source database time zone '{0}'.

Cause: Replicat is setting its session time zone to the source database time zone.

Action: None

OGG-03523: Failed to set session time zone to source database time zone '{0}'.

Cause: Replicat could not set its session to the specified time zone. Either the specified value is invalid or the target database does not support that time zone.

Action: You can do one of the following, depending on the Extract version: If Extract is pre-12.1.2, use the SOURCETIMEZONE parameter to specify a time zone that is supported by the target database. If Extract is 12.1.2 or later, you can use the PRESERVENTARGETTIMEZONE parameter to ignore the source database time zone (the Replicat default) and direct Replicat to use the target time zone in its session, or you can use the SOURCETIMEZONE parameter to direct Replicat to use a specific time zone.

OGG-03524: Invalid or unsupported time zone '{0}' is specified by SOURCETIMEZONE parameter.

Cause: The specified time zone is not valid or is not supported by Replicat.

Action: Specify a valid source database time zone.

OGG-03525: Invalid or unsupported time zone '{0}' in trail file.

Cause: The source database time zone in the trail file is not supported by this release of Replicat.

Action: Specify the source time zone with the SOURCETIMEZONE parameter or use PRESERVENTARGETTIMEZONE to ignore the source time zone and use the target time zone for the Replicat session.

OGG-03526: The source database character set is specified for DB2 z/OS trail version 9.0/9.5 by SOURCECHARSET.

Cause: SOURCECHARSET DB2ZOS is specified, and replicat assumes the trail file version is 9.0/9.5 and is written by an Extract capturing from DB2 z/OS.

Action: None

OGG-03527: Ignoring the invalid source database character set specified for DB2 z/OS trail version 9.0/9.5 by SOURCECHARSET.

Cause: The source database character set is specified for DB2 z/OS trail version 9.0/9.5. However the trail file version is not 9.0/9.5 or not written by an Extract for DB2 z/OS.

Action: Remove the SOURCECHARSET parameter from Replicat parameter file.

OGG-03528: The source database character set, as determined from the table definition file, is {0}.

Cause: The source database character set information in the table definition file is being assumed as the source database character set. The source database character set may be overwritten by the source database character set information in the trail file.

Action: None

OGG-03529: The source character set name is missing for the SOURCECHARSET parameter

Cause: The SOURCECHARSET parameter is specified without requiring character set name.

Action: Specify the character set name.

OGG-03530: The SOURCECHARSET OVERRIDE {0} parameter is specified. The trail file is version 11.2.1 or later and contains the source character set {1} will be ignored.

Cause: Because the SOURCECHARSET parameter is specified with OVERRIDE option, the source character set of the trail file is ignored.

Action: None

OGG-04000: VAM module attempted to retrieve Conflict Detection Resolution column indexes for deletes from GG_ATTR_MD_CDRCOLS_DEL array, but none are available (GG_ATTR_MD_CDRCOLS_COUNT_DEL =0).

Cause: The VAM module failed to retrieve the column array of the indexes that represent the Conflict Detection Resolution columns for deletes in the table. GG_ATTR_MD_CDRCOLS_COUNT_DEL gives the number of delete CDR column indexes in the array; if zero, no indexes exist. In this case, a call to GG_ATTR_

CDRCOLS_DEL should not be made. This is a development error that may require a bug report.

Action: Contact Oracle Support.

OGG-04001: VAM module attempted to retrieve Conflict Detection Resolution column indexes for updates from GG_ATTR_MD_CDRCOLS_UPD array, but none are available (GG_ATTR_MD_CDRCOLS_COUNT_UPD =0).

Cause: The VAM module failed to retrieve the column array of the indexes that represent the Conflict Detection Resolution columns for updates in the table. GG_ATTR_MD_CDRCOLS_COUNT_UPD gives the number of update CDR column indexes in the array; if zero, no indexes exist. In this case, a call to GG_ATTR_CDRCOLS_UPD should not be made. This is a development error that may require a bug report.

Action: Contact Oracle Support.

OGG-04002: VAM module set the three CDR and compression related parameters incorrectly.

Cause: The VAM module set the three CDR and compression related parameters incorrectly. When GG_ATTR_VAMMOD_CDR_SUPPORTED is set to GG_VALUE_TRUE, both GG_ATTR_VAMMOD_CDEL_SUPPORTED and GG_ATTR_VAMMOD_CUPD_SUPPORTED need to be set to GG_VALUE_TRUE. CDR processing in VAM module while delete and update compression in VAM API is not a supported scenario. This is a development error that may require a bug report.

Action: Contact Oracle Support.

OGG-04003: Initialization of user module failed: Callback functions must be implemented

Cause: The VAM module in Extract failed to initialize.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04004: Object {0}.{1}.{2} does not exist in data source

Cause: An invalid table was encountered in the VAM Module Application Framework in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04005: Invalid value encountered in case statement: {0}

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04006: Call to {0} to load {1} failed

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04007: Call to {0} failed to retrieve the address of {1}

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04008: Object {0}: Attribute {1}: Value {2}: Invalid attribute value for CDR settings

Cause: A CDR validation error occurred when checking the CDR processing parameters. Please check the message for details.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04009: Column index {0}: {1} returned with error status {2}

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04010: Object {0}: Attribute {1}: Maximum number of columns exceeded

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04011: Object {0}: Attribute {1}: {2} returned with length {3}

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04012: Object {0}: Attribute {1}: {2} returned with error status {3}

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04013: Object {0}: Attribute {1}: {2} returned with value {3}

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04014: Object {0}: Attribute GG_ATTR_OP_COMPLETE: GGAttrGet returned with missing attribute {1}

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04015: {0}

Cause: An internal logic error occurred in the VAM Simulator Module in Extract.

Action: Review the error message and take appropriate action, or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04016: Object {0}: Column Index {1}: Column Format {2}: {3} returned with error status {4}

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04017: Object {0}: Record Type {1}: Transaction ID {2}: Transaction ID does not exist in transaction lookup table

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04018: Object {0}: Record Type {1}: Transaction ID {2}: Transaction ID already exists in transaction lookup table

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04019: No metadata was found for {0}

Cause: An internal logic error occurred in the VAM module in Extract.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04020: Unexpected condition in {0} at line {1,number,0}

Cause: An internal error occurred.

Action: Contact Oracle Support.

OGG-04021: VAM module must support CDR in order to send unified trail records via the VAM API.

Cause: To support unified trail records, the GG_ATTR_VAMMOD_CDR_SUPPORTED attribute of the VAM must be set. This indicates that the VAM supports CDR handling.

Action: Remove UPDATERECORDFORMAT [FULL/COMPACT] from the Extract parameter file. If this error still occurs, contact Oracle Support or, if you are a developer, contact the VAM module development team.

OGG-04022: VAM module must support CDR in order to send unified trail records via the VAM API.

Cause: To support unified trail records, the GG_ATTR_VAMMOD_CDEL_SUPPORTED attribute of the VAM must be set. This indicates that the VAM supports CDR handling.

Action: Remove UPDATERECORDFORMAT [FULL/COMPACT] from the Extract parameter file. If this error still occurs, contact Oracle Support or, if you are a developer, contact the VAM module development team.

OGG-04023: VAM module must support compressing updates in order to send unified trail records via the VAM API.

Cause: To support unified trail records, the GG_ATTR_VAMMOD_CUPD_SUPPORTED attribute of the VAM must be set. This indicates that the VAM supports CDR handling.

Action: Remove UPDATERECORDFORMAT [FULL/COMPACT] from the Extract parameter file. If this error still occurs, contact Oracle Support or, if you are a developer, contact the VAM module development team.

OGG-04024: GG_OBJ_RECORD: GG_ATTR_BEFORE_AFTER can only be used with GG_OPTYPE_UPDATE_UNIFIED for unified trail records

Cause: The VAM module tried to add a before key column for a record that is not a primary key update.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04025: CHECKOPCOMPLETE: No before columns in a unified update were added for operation type: {0,number,0}

Cause: No before image key fields were sent for a unified update record being passed to the VAM API.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04026: CHECKOPCOMPLETE: Before column(s) in primary key update were added that are not a primary key column: {1}; Operation type: {0,number,0}

Cause: Before image columns were sent for a primary key update record being passed to the VAM API that are not primary key columns.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-04027: Source record exceeds the size of the output buffer used to assemble trail file records. The length required was {0,number,0} but the maximum length allowed is {1,number,0}.

Cause: The size of the output buffer used to hold the internal record written to the trail file is not large enough to contain the record that was sent to the VAM API.

Action: Contact Oracle Support.

OGG-04028: COMPRESSUPDATES is ignored since LOGALLSUPCOLS has been specified.

Cause: LOGALLSUPCOLS parameter takes precedence over COMPRESSUPDATES.

Action: None

OGG-04029: NOCOMPRESSUPDATES is ignored for the before image of the update to table {0} because GETBEFORECOLS has been specified.

Cause: GETBEFORECOLS parameter takes precedence over COMPRESSUPDATES.

Action: None

OGG-04030: NOCOMPRESSUPDATES is ignored for the after image of the update to table {0} because UPDATERECORDFORMAT COMPACT has been specified.

Cause: UPDATERECORDFORMAT COMPACT takes precedence over NOCOMPRESSUPDATES for the after image of the update to the table.

Action: None

OGG-04031: UPDATERECORDFORMAT FULL is ignored since COMPRESSUPDATES has been specified for table {0}.

Cause: COMPRESSUPDATES parameter takes precedence over UPDATERECORDFORMAT FULL.

Action: None

OGG-04032: LOGALLSUPCOLS has set the NOCOMPRESSDELETES, NOCOMPRESSUPDATES and GETUPDATEBEFORERES parameters on.

Cause: The LOGALLSUPCOLS settings take precedence over the previous settings of [NO]COMPRESSDELETES, [NO]COMPRESSUPDATES and [GET/IGNORE]UPDATEBEFORERES.

Action: None

OGG-04033: LOGALLSUPCOLS has set the NOCOMPRESSDELETES and GETUPDATEBEFORES parameters on.

Cause: The LOGALLSUPCOLS settings take precedence over the previous settings of [NO]COMPRESSDELETES and [GET/IGNORE]UPDATEBEFORES.

Action: None

OGG-04034: Column {1} in table {0} has a data type of SYS.ANYDATA with an opaque value and cannot be mapped using column mapping.

Cause: The value of a SYS.ANYDATA column is opaque, which means the data type is held along with the value internally. Because the value is not visible to Oracle GoldenGate, the column cannot be mapped.

Action: Do not use column mapping on tables containing SYS.ANYDATA columns.

OGG-04035: To replicate SYS.ANYDATA columns using fetch requires an Oracle GoldenGate release of 12.1 or higher. The trail file compatibility setting is set to level {0}, a compatibility level of {1} or above is required.

Cause: Using the fetch-based functionality to replicate SYS.ANYDATA columns requires an Oracle GoldenGate release of 12.1 or higher.

Action: Replication of SYS.ANYDATA columns requires Oracle GoldenGate release of 12.1 or higher.

OGG-04036: Positioning sequence ID is out of order, old sequence ID is {0}, new sequence ID is {1}.

Cause: The positioning sequence number should remain the same or increase rather than decrease.

Action: If you are working with an Oracle GoldenGate Developer, contact that person or contact Oracle Support.

OGG-04037: NOLOGALLSUPCOLS has reset the NOCOMPRESSDELETES and GETUPDATEBEFORES parameters.

Cause: The NOLOGALLSUPCOLS settings take precedence over the previous settings of [NO]COMPRESSDELETES and [GET/IGNORE]UPDATEBEFORES.

Action: None

OGG-04501: Charset information: Client charset: [{0}], Database/Server charset: [{1}], CHARSETCONVERT: [{2,choice,0#OFF | 1#ON}].

Cause: Oracle GoldenGate is performing character set conversion. This message shows the source and target character sets, and the conversion set.

Action: None required.

OGG-04502: The client charset: {0} is not supported.

Cause: The character set that is used in the client is deprecated by Sybase or is not supported by Oracle Goldengate.

Action: See the Sybase and Oracle GoldenGate documentation for supported character sets.

OGG-04503: The server charset: {0} is not supported.

Cause: The character set that is used in the database server is deprecated by Sybase or is not supported by Oracle Goldengate.

Action: See the Sybase and Oracle GoldenGate documentation for supported character sets.

OGG-04504: Sybase warning 2401 occurred. Conversion of the character set can not be performed between the client and the server. This may break data integrity. Using default settings for the conversion: Client charset: [{0}], Database/Server charset: [{1}], CHARSETCONVERT: [OFF].

Cause: The process cannot force a conversion between the different client and server character sets because the Sybase server cannot interpret some of the client characters.

Action: Change the client or server character set to one that fixes the Sybase message 2401 and enables conversion.

OGG-04505: Wildcards not supported for database user.

Cause: The wildcard for the specified user is not supported. Check the database login configuration and also make certain _ALLOWWILDCARDSCHEMAS is used in the GLOGALS file.

Action: See the rules for schema wildcarding in the Oracle GoldenGate documentation or contact Oracle Support.

OGG-04506: Failed to convert source data type {2} to target data type {3} for column {1} in table {0}.

Cause: These two data types are not compatible for character set conversion.

Action: Use the following Replicat parameter to ignore this conversion: reperror(error_number, ignore), where error_number is the error number returned from the database. If the problem persists, contact Oracle Support.

OGG-04507: Legacy {0} functionality started at the request of an Oracle GoldenGate user

Cause: The specified functionality was started by the VAM. Informational only.

Action: None

OGG-04508: Oracle GoldenGate is searching the Sybase CS library version that is to be used. Please ignore any error that is reported by Sybase as a part of this search process

Cause: Oracle GoldenGate is searching the Sybase CS library version that it needs to use.

Action: You can ignore any error that is reported by Sybase as a part of this search process.

OGG-04510: {0}

Cause: The specified database error occurred. The cause can be any of the following: Unknown user or invalid password, unknown host machine, server name not in interface file, maximum number of connections already established, sufficient memory not available, or cannot open the interface file. Another cause could be that the Adaptive Server is unavailable, does not exist, or is not configured.

Action: Take any actions based on the problem: Check the user name and password, and make sure the user exists in the database. Make certain the interface file exists and that Oracle GoldenGate can access it. Make certain the server name in the interface file is correct, or try adding another entry for the host machine , but use the IP address instead of the name. Make certain the Adaptive Server is configured in the local machine where Oracle GoldenGate is running. Increase the number of connections permitted to the database. Free up storage in the network layer and free up system memory. If the problem persists, see the instructions in the Oracle GoldenGate report file or contact Oracle Support.

OGG-04511: The current Sybase database version is not supported for the BatchSQL feature; Sybase ASE 15.7 ESD 4 (SP110) or greater is required.

Cause: BatchSQL is not supported with the current version of the Sybase database.

Action: See Installing and Configuring Oracle GoldenGate for Sybase for a list of supported Sybase database versions.

OGG-04512: Sybase database version ASE 15.7 ESD 4 (SP110) and greater is required to support the BatchSQL feature.

Cause: BatchSQL is only supported with Sybase version ASE 15.7 ESD 4 (SP110) and greater.

Action: Ensure that a supported Sybase version is installed. See Installing and Configuring Oracle GoldenGate for Sybase for a list of supported Sybase database versions.

OGG-04514: The log transfer context for the current database({1}) is already reserved by previous instance of Oracle GoldenGate extract process{0}.SQL Error text ({2}).Grant SA_ROLE to Oracle GoldenGate replication user to release the log transfer context.Alternatively, the log transfer context can be released manually with SA_ROLE user by finding spid of the process using sql query (select spid from master..sysprocesses where dbid=db_id('dbName') and program_name = 'GG_SYBLTM') and then killing the process by ASE provided kill command eg 'kill spid'.

Cause: Oracle GoldenGate extract process has reserved the log transfer context of the database and due to abnormalities in ASE like crash, forcefully kill, slow in response etc of the server, the log transfer context reserved during startup is not released by previous instance Oracle GoldenGate extract process, hence the next start of extract will fail with the above error.

Action: Grant the Oracle GoldenGate database replication user with SA_ROLE to kill the extract process that has reserved the log context.

OGG-04521: Stopping at the request of a user exit.

Cause: Stopping at the request of a user exit. Informational only.

Action: None

OGG-04522: Unable to determine user exit compatibility level. {0} running with user exit library {1}, using default compatibility level ({2}).

Cause: The process could not determine the compatibility level of the user exit. The default compatibility level is being used. Informational only.

Action: None

OGG-04523: {0} running with user exit library {1}, compatibility level ({2}) is not current, using compatibility level ({3}).

Cause: The user exit compatibility level is not current. The specified compatibility level will be used.

Action: None

OGG-04524: {0} running with user exit library {1}, compatibility level ({2}) is current.

Cause: The user exit compatibility level is current. Informational only.

Action: None

OGG-04525: {0} running with user exit library {1}, current session character set is {2}.

Cause: The specified user exit library and session character set are in use.
Informational only.

Action: None

OGG-04526: {0} running with user exit library {1}. Current session character set is operating system default character set.

Cause: The user exit session character set is the operating system default character set. Informational only.

Action: None

OGG-04527: The character set of the data source or the session could not be determined. Using ULIB_CS_DEFAULT. No character set conversion is performed for column data.

Cause: The character set of the data source or the session could not be determined. The default operating system character set is being used.

Action: None

OGG-05000: There is no MySQL database character set corresponding to ULibCharset {0}

Cause: A character set is specified in the SOURCEDB or TARGETDB parameter that is not supported by MySQL.

Action: Specify a character set that is supported by MySQL. If the problem persists, contact Oracle GoldenGate Support.

OGG-05001: Invalid sequence identifier length encountered. The current sequence identifier length:{0} must be equal to or greater than the length of its predecessor:{1}

Cause: The length of the new sequence identifier is not equal to or greater than the previous sequence identifier length.

Action: Contact Oracle Support.

OGG-05002: GoldenGate does not support MySQL column character set {0} for column:{1} of table:{2}.

Cause: A character set specified for the column in a MySQL table is not supported by GoldenGate.

Action: If the character set is listed in the MySQL documentation as a supported character set please contact Oracle Support and request that GoldenGate implements its support. As a possible workaround consider using an alternative character set if possible.

OGG-05101: Cannot specify both ETOLDFORMAT and ENCRYPTTRAIL for '{0}'

Cause: The Extract parameter ETOLDFORMAT is specified with the ENCRYPTTRAIL parameter.

Action: Remove ENCRYPTTRAIL from the parameter file.

OGG-05102: Retrying logon to Oracle database after previous attempt failed.

Cause: The process could not log on to the Oracle database because of a database error that showed the database is in the process of starting up or shutting down. The process will try the operation again.

Action: No action needed.

OGG-05200: The schema of table {0} (object id {1}) was altered. {2} If the change affected the physical data layout, you must re-synchronize the source and target databases.

Cause: An unsupported DDL change was done to the the specified object.

Action: Exclude the table from the TABLE parameter or re-synchronize the source and target tables.

OGG-05201: Backup {0} has been overwritten. LSN range {1} to {2} was found, but LSN range {3} to {4} was expected.

Cause: The backup was overwritten by a subsequent backup.

Action: Re-synchronize the source and target tables.

OGG-05202: The server name is reported as NULL by SQL Server. Assign a valid server name with the @@servername variable.

Cause: The SQL Server variable "@@servername" is NULL.

Action: Rename the server to a valid name according to the Microsoft recommended procedure.

OGG-05203: The SQL Server Native Client 11 driver is known to cause a memory leak when used to connect to SQL Server 2012 or later.

Cause: SQL Server Native Client 11 when used with OLE DB causes a memory leak see <http://support.microsoft.com/kb/2894115> and <http://support.microsoft.com/kb/2881661> for more details.

Action: Please switch to ODBC or upgrade to the patch levels as per the referenced KB articles.

OGG-05204: {0} is a third party backup file. Third party backups are not supported.

Cause: Third party backups are not supported.

Action: Convert backup file to native Microsoft tape format.

OGG-05205: {0} is a tape backup. Tape backups are not supported.

Cause: Tape backups are not supported.

Action: Backup to file.

OGG-05206: Backup, {0}, is of an unknown type.

Cause: Backup is of an unknown type.

Action: Backup to a supported format.

OGG-05207: Backup, {0}, is of an unsupported type: {1}.

Cause: Backup is of an unsupported type.

Action: Backup to a supported format.

OGG-05208: Failed to duplicate the SQL Server process handle {0} with Windows system error {1}.

Cause: Extract needed to duplicate the SQL Server process handle but was unable to do so.

Action: Please ensure that the SQL Server process is running.

OGG-05209: Failed to open the SQL Server process, {0}, with Windows system error {1}.

Cause: Extract needed to open the SQL Server process but was unable to do so.

Action: Verify the connection is to a local instance and that permissions are granted for access the SQL Server process.

OGG-05210: {0}: A query to SQL Server has failed: {1} : {2}.

Cause: A query issued against SQL Server has failed.

Action: None. Action depends on error.

OGG-05211: Buffer initialization has failed with a count of {0} and block size of {1}.

Cause: Initialization of an internal log data buffer has returned failure.

Action: Please ensure there exists enough memory for use by Extract.

OGG-05212: Failed to get value for object {0}, attribute {1} from API.

Cause: An internal function returned failure.

Action: Contact Oracle Support.

OGG-05213: Hardware parity failure detected for file id {0} at offset {1}.

Cause: File was incorrectly written to disk.

Action: Verify the integrity of the file using SQL Server.

OGG-05214: Unable to open device {0} with Windows system error {1}.

Cause: Unable to open device.

Action: Action depends on system error.

OGG-05215: Unable to find device {0} with Windows system error {1}.

Cause: Unable to find device.

Action: Action depends on system error.

OGG-05216: Invalid start type: {0}.

Cause: Invalid start type.

Action: Supply a valid start type.

OGG-05217: The starting LSN ({0}) is greater than the flush LSN ({1}) of this database. Positioning not attempted.

Cause: The starting LSN is too high.

Action: Supply a valid starting LSN that is less than or equal to the flush LSN.

OGG-05218: The LSN, {0}, is lower than the first LSN in the online log of this database, {1}, and cannot be found in any backups.

Cause: Extract cannot find the LSN in the logical log span of the database.

Action: Ensure that backups exist, that they are readable, and that they are not currently open.

OGG-05219: The log data provider could not be started.

Cause: The log data provider failed to start.

Action: None

OGG-05220: A read attempt failed on device {0} at offset {1} with Windows system error {2}.

Cause: A device read failed.

Action: Action depends on system error.

OGG-05221: Unable to retrieve virtual log information for LSN {0}.

-
- Cause:** Could not get virtual log information for the specified lsn.
Action: None
- OGG-05222: {0} is not a valid SQL Server backup.**
Cause: The backup device is not a valid native MTF backup.
Action: Supply a valid native MTF backup.
- OGG-05223: LEGACYLOBREADING is no longer supported for SQL Server extract.**
Cause: User supplied LEGACYLOBREADING parameter which is no longer supported.
Action: Remove the parameter from the param file.
- OGG-05224: The LSN, {0}, does not exist in the logical log span of this database.**
Cause: Extract cannot find the LSN in the logical log span of the database.
Action: Ensure that backups exist, that they are readable, and that they are not currently open.
- OGG-05225: SQL Server {0} is not supported. The minimum supported version is SQL Server {1}.**
Cause: The SQL Server version is not supported.
Action: Use a database that is on a supported version of SQL Server.
- OGG-05226: Record processing will begin at LSN {0}.**
Cause: The start LSN has been found.
Action: None
- OGG-05227: Debug backup starting at LSN {0}.**
Cause: Extract is beginning a debug backup run at the specified LSN.
Action: None
- OGG-05228: Debug backup complete.**
Cause: Extract has reached the end of the debug backup.
Action: None
- OGG-05229: An internal LOB Buffer was overrun. Expected {0}, appended {1} to Marker [{2}]**
Cause: More data was appended to an internal LOB buffer than expected.
Action: Contact Oracle Support.
- OGG-05230: An internal LOB Buffer was completed before all of the data was appended. Expected {0}, appended {1} to Marker [{2}]**
Cause: Less data was appended to an internal LOB buffer than expected.
Action: Contact Oracle Support.
- OGG-05231: COM unexpectedly returned a read offset by {0} bytes.**
Cause: Data was not returned to the buffer correctly from COM.
Action: Contact Oracle Support.
- OGG-05232: COM unexpectedly returned {0} bytes more than requested.**
Cause: Data was not returned to the buffer correctly from COM.
Action: Contact Oracle Support.

OGG-05233: An invalid identifier '{0}' was specified for DBOPTIONS TRANSNAME in the Replicat parameter file.

Cause: The value of DBOPTIONS TRANSNAME is not a valid transaction identifier.

Action: Identifier rules:
- Must start with a letter
- Can have up to 32 characters, but no spaces
- Are case insensitive (PART, Part, and part are identical)
- Can include any combination of letters, numbers, and these special characters:
- Dash
- Underscore
- \$ Dollar sign
- # Number sign

OGG-05234: Native backup compression version {0} not supported.

Cause: Extract is trying to decompress a SQL Server backup that was compressed with an algorithm that is not supported. This likely means you are using a version of SQL Server is not supported.

Action: Verify the SQL Server version. If that is a supported version, uncompress the backup and restart Extract. If it fails again, contact Oracle support.

OGG-05235: The current LSN {0} is out of sequence, the previous LSN was {1}.

Cause: The current LSN is out of sequence.

Action: This is an internal failure, contact Oracle support.

OGG-05236: ODBC Warning: The specified DSN '{0}' uses a client driver that may be incompatible with the database server. {1} requires {2} or a more recent version.

Cause: The DSN for the database connection is using a client driver that may be incompatible with the server.

Action: Verify that the client driver is compatible with the database server it connects to.

OGG-05237: Error getting character set for column {1} of table {0}: Database error: {2,number,0} ({3})

Cause: An internal error occurred while fetching column collation information.

Action: Save the error message and contact Oracle GoldenGate Support.

OGG-05238: Unknown character set for column {1} of table {0} : {2}

Cause: An internal error occurred while fetching column character set information.

Action: Save the error message and contact Oracle GoldenGate Support.

OGG-05239: The LSN, {0}, does not exist in the online log of this database. The first LSN of the online log is {1}.

Cause: Extract cannot find the LSN in the online log of the database.

Action: Ensure that the LSN has not already been backed up.

OGG-05240: Waiting for transaction log backups...

Cause: Extract is in ARCHIVEONLY mode and is waiting for a backup.

Action: None

OGG-05241: Table {0} contains both compressed and uncompressed partitions, this configuration is not supported.

Cause: The table has both compressed and uncompressed partitions.

Action: Exclude the table from replication or recreate the table to contain either all compressed or uncompressed partitions.

OGG-05301: Shell command output: '{0}'

Cause: A SHELL Command declared as part of an EVENTACTIONS expression has produced output which was captured for reporting purposes. Informational only.

Action: None

OGG-05302: An error occurred while doing commit handling.

Cause: An error occurred while doing commit handling.

Action: Contact Oracle Support.

OGG-05303: GRAPHIC/VARGRAPHIC/DBCLOB column support requires a UNICODE character set.

Cause: Oracle GoldenGate supports GRAPHIC, VARGRAPHIC and DBCLOB columns only if the character set of the column is UNICODE.

Action: Create the GRAPHIC, VARGRAPHIC or DBCLOB column in a UNICODE database or with a UNICODE character set, if that is not possible, exclude the table from the Oracle GoldenGate configuration.

OGG-05304: Database instance {0} has logarchmeth1 set to off.

Cause: The DB2 configuration parameter LOGARCHMETH1 is set to off.

Action: Set LOGARCHMETH1, LOGRETAIN or USEREXIT configuration parameter appropriately to enable DB2 log retention.

OGG-05305: Process {0} is not in a suspended state. RESUME is ignored.

Cause: A SEND command with RESUME was issued for a process that is not in the SUSPEND state. The RESUME request is being ignored.

Action: None

OGG-05306: Table {0}, column {1}, contains data type: {2,number,0} which is not a supported datatype with COMPRESS SYSTEM DEFAULT ON.

Cause: The specified column is not supported for COMPRESS SYSTEM DEFAULT.

Action: Specify one of the valid COMPRESS SYSTEM DEFAULT data types: numerical, fixed-length character, fixed-length graphic string. For more information on supported data types, see the Oracle GoldenGate documentation for this database.

OGG-05500: Detected database metadata mismatch between current trail file {0} and the previous sequence. {1}

Cause: An inconsistency in database metadata was detected between the current and previous trail file.

Action: Contact Oracle Support.

OGG-05501: Detected trail format inconsistency between current trail file {0} and the previous sequence

Cause: An inconsistency in the trail format was detected between the current and previous trail file.

Action: Contact Oracle Support.

OGG-05502: WARNING: Table {0} is an IOT with Mapping Table. DML replication of this type of table is not supported.

Cause: IOT with Mapping is not supported. DDL for IOT with Mapping will be replicated correctly, but not DML for IOT with Mapping.

Action: Edit the parameter file to remove the table and others of this type from the TABLE statements, and then restart Extract. (If TABLE uses a wildcard, you can exclude those tables with TABLEEXCLUDE.) If DDL support was configured for this table, contact Oracle Support.

OGG-05503: WARNING: Improper VAM Implementation. The LOB data handle is not associated with the same transaction that contains the base row.

Cause: The LOB data handle was associated with a different transaction than the base row that is being replicated at the time the data handle was created. Data handles can only be assigned to columns that belong to base rows that are in the same transaction.

Action: Contact Oracle Support for help with using TRANLOGOPTIONS LEGACYLOBREADING as a temporary workaround.

OGG-05506: Table {0}, column {1}, contains an unsupported data type: {2}.The column will be excluded.

Cause: The specified column contains an unsupported data type. The column will be excluded.

Action: For supported data types, see the Oracle GoldenGate documentation for this database.

OGG-05507: Table {0} column {1} : the fractional part of the captured timestamp will be truncated to {2,number,0} digits.

Cause: The timestamp column has higher granularity than the maximum supported fraction digits. The captured timestamp data will be truncated.

Action: None. Extract will process the timestamp data with less granularity.

OGG-05508: The CSN value {0} given with the ATCSN or AFTERCSN option is less than the CSN value {1} already committed by the previous instance of this process. Only transactions not yet committed will be processed.

Cause: START EXTRACT or START REPLICAT was issued with an ATCSN or AFTERCSN option, but the specified CSN value is lower than the highest CSN that has already been committed to the trail or target database. This would cause duplicate transactions if allowed.

Action: If you issued START EXTRACT or START REPLICAT at the given CSN to confirm that all transactions starting from that CSN got captured to the trail, no action is necessary. However, if it is your intention to start the output of the new process with the transaction at the specified CSN or immediately after it, contact Oracle Support for assistance in determining which output trail is to be affected.

OGG-05509: The CSN value {0} given in the command line was not seen. Processing begins with the first actual CSN value seen above the value in the command line.

Cause: The ATCSN option was used with a CSN value that does not exist in the transaction stream. This CSN value may not be a valid CSN.

Action: Make certain the provided CSN value exists in the input transaction stream. You can use the Logdump utility to examine the input trail file if you issued START REPLICAT, or START EXTRACT for data pump with the ATCSN option. Refer to the Oracle GoldenGate reference documentation for how CSN values are determined for your specific database.

OGG-05510: The CSN value {0} given with the ATCSN or AFTERCSN option is less than a CSN value {1} already committed by the previous instance of this process to at least one output trail file. Some transactions associated with the given CSN might be skipped, but others cannot be skipped because they have already been committed to a trail.

Cause: START EXTRACT was issued with an ATCSN or AFTERCSN option, but the specified CSN value is lower than the highest CSN that has already been committed to at least one of multiple output trails. This same specified CSN value is also higher than the highest CSN already committed to least one of the same set of multiple output trails. Some transactions might be skipped, but other transactions that were already committed to a trail during the previous process run cannot be skipped.

Action: None

OGG-05511: DROP TABLE encountered for {0}, DBID: {1}, OBID: {2}.

Cause: A DROP TABLE was the first log record encountered for the specified table after Extract started. Because WILDCARDRESOLVE IMMEDIATE was not specified, an entry in the definitions file for this table cannot be created, and no truncate record can be created for it.

Action: None

OGG-05512: TRUNCATE cannot be generated for table DBID: {0}, OBID: {1}. Refer to previous message for the name of the table.

Cause: A log record that indicates a DROP TABLE was processed. Because the DB2 catalog no longer contains the table, a TRUNCATE record cannot be captured for it.

Action: Refer to the previous message to get the name of the table. Then, resolve the target table so that it matches the source table, such as deleting or truncating the target table as appropriate.

OGG-05513: An INSERT, UPDATE, or DELETE was encountered for table DBID: {0}, OBID: {1}. A table with the same DBID / OBID was identified as dropped during the current execution of Extract.

Cause: An INSERT, UPDATE, or DELETE was encountered for a table that was identified as dropped during the current run of Extract. Because Extract did not acquire the definition of the dropped table from the DB2 catalog, it is not possible to determine if the table definition has changed.

Action: Refer to the previous message to get the name of the table. Then, resolve the target table so that it matches the source table, such as deleting or truncating the target table as appropriate. If using the SOURCEDEFS parameter, make certain that the data definitions file is current. Then, restart Extract.

OGG-05514: An INSERT, UPDATE, or DELETE was encountered for table {0}, DBID: {1}, OBID: {2}, which was identified as dropped during the current execution of Extract. The current table definition does not match that of the dropped table.

Cause: An INSERT, UPDATE, or DELETE was encountered for a table that was identified as dropped during the current run of Extract. The current table definition does not match that of the dropped table.

Action: Resolve the target table so that it matches the source table, such as deleting or truncating the target table as appropriate. If using the SOURCEDEFS parameter, make certain that the data definitions file is current. Then, restart Extract.

OGG-05515: DATA CAPTURE CHANGES is not enabled for SYS IBM.SYSTABLES.
Processing will be switched from APIFILTER to NOAPIFILTER to allow the capture of data related to SYSIBM.SYSTABLES.

Cause: APIFILTER is enabled and DATA CAPTURE CHANGES is not enabled for SYSIBM.SYSTABLES. NOAPIFILTER will be used to capture data.

Action: To enable DATA CAPTURE CHANGES for SYSIBM.SYSTABLES, use this GGSCI command: ADD TRANSLATE sysibm.systables. This may allow processing to be done with APIFILTER, if no other conditions exist that would force NOAPIFILTER. One such condition is the need to capture change data for any table that includes one or more LOB columns.

OGG-05516: A table with one or more LOB column was encountered. Processing will be switched from APIFILTER to NOAPIFILTER to allow capture of data from the LOB column(s).

Cause: A table with one or more LOB column was encountered and APIFILTER is enabled, which would prevent capture of data from the LOB column(s).

Action: None

OGG-05517: OCI error {{0}-{1}} determining whether to ignore the object.

Cause: The process encountered the specified OCI error when trying to determine whether or not to ignore the object.

Action: Check the OCI error detail and resolve the cause of error.

OGG-05518: No data found when determining whether or not to ignore the object.

Cause: No data was found when determining if the object is to be ignored.

Action: Contact Oracle Support for help.

OGG-05519: Output trail file encryption: {0}

Cause: The ENCRYPTTRAIL parameter was specified or the data pump is sending an encrypted trail file.

Action: None

OGG-05520: Input trail file encryption: {0}

Cause: The input trail is encrypted.

Action: None

OGG-05600: Table {0} has a self-referencing foreign key. Records from this table will be ignored.

Cause: The specified table has a self-referencing foreign key. Oracle GoldenGate does not support this type of table and ignores operations on them.

Action: Undefined

OGG-05601: Error determining whether to ignore the object. OCI error {{0}-{1}} encountered executing SQL query: <{2}>

Cause: The process encountered the specified OCI error when trying to determine whether or not to ignore the object.

Action: Check the OCI error detail and resolve the cause of error. Ensure that the user has privileges to execute the SQL statement.

OGG-05663: CSN-based filtering suppressed a duplicate transaction from trail Seqno {0,number,0}, RBA {1,number,0}, with CSN {2} and transaction ID {3}.

Cause: CSN-based filtering identified a duplicate transaction and filtered it out.

Action: None

OGG-05664: CSN-based filtering suppressed {8,number,0} duplicate transactions, from trail Seqno {0,number,0}, RBA {1,number,0} to Seqno {4,number,0}, RBA {5,number,0}. The first transaction suppressed has CSN {2} and transaction ID {3}, and the last suppressed one has CSN {6} and transaction ID {7}

Cause: CSN-based filtering identified duplicate transactions and filtered them out.

Action: None

OGG-05672: CSN-based duplicate suppression is disabled because there is no checkpoint table for this Replicat.

Cause: There is no checkpoint table for the Replicat group. To store the CSN state, a checkpoint table is required.

Action: To use duplicate suppression, add a checkpoint table for Replicat.

OGG-05673: CSN-based duplicate suppression is disabled because there is no checkpoint table for this Replicat.

Cause: There is no checkpoint table for the Replicat group. To store the CSN state, a checkpoint table is required.

Action: To use duplicate suppression, add a checkpoint table for Replicat.

OGG-05700: WARNING: The ADD TRANDATA command was not issued for table {0}. No records will be processed for this table.

Cause: The ADD TRANDATA command was not issued for the specified table to enable supplemental logging.

Action: Issue the DBLOGIN command in GGSCI, and then issue the ADD TRANDATA command. For more information, see the Oracle GoldenGate reference documentation.

OGG-06000: Replicat Coordinator failed to start Replicat thread {0}. Reason {1}.

Cause: An error occurred when Replicat Coordinator attempted to start a Replicat thread.

Action: Contact Oracle Support.

OGG-06001: Replicat Coordinator failed to send a message to Replicat thread {0}.

Detail: {1}

Cause: An error occurred when Replicat Coordinator attempted to send a message to a Replicat thread.

Action: Contact Oracle Support.

OGG-06002: Coordinated Replicat process received an unsupported message: type {0}

Cause: An unsupported message was received by a Coordinated Replicat process.

Action: None

OGG-06003: All Replicat threads are registered.

Cause: The communication links with all Replicat threads are established.

Action: None

OGG-06004: Coordinated Replicat thread {0} exited unexpectedly. Please check the report file of {0} for more details.

Cause: The coordinator of the coordinated Replicat group received an unexpected thread disconnect event.

Action: Contact Oracle Support if you cannot determine the cause after viewing the report file for the specified thread.

OGG-06005: Replicat Coordinator failed to receive a message from Replicat thread {0}. Detail: {1}

Cause: An error occurred when Replicat Coordinator attempted to receive a message from a Replicat thread.

Action: Contact Oracle Support.

OGG-06006: Replicat thread failed to make a connection to Replicat Coordinator at {0}. Detail: {1}

Cause: An error occurred when Replicat thread attempted to connect to Replicat Coordinator.

Action: Contact Oracle Support.

OGG-06007: Replicat thread failed to register with Replicat Coordinator. Detail: {0}

Cause: An error occurred when Replicat thread attempted to register with Replicat Coordinator.

Action: Contact Oracle Support.

OGG-06008: Replicat thread failed to send a message to Replicat Coordinator. There was a communication error, or Replicat Coordinator may be in the process of stopping. Detail: {0}

Cause: An error occurred when Replicat thread attempted to send a message to Replicat Coordinator.

Action: Contact Oracle Support.

OGG-06009: Replicat thread failed to receive a message from Replicat Coordinator. Detail: {0}

Cause: An error occurred when Replicat thread attempted to receive a message from Replicat Coordinator.

Action: Contact Oracle Support.

OGG-06010: Not the default Partition, not applying DDL record. This is informational only.

Cause: Coordinated Replicat thread is not executing a barrier record. This is expected for all but one of the threads.

Action: None

OGG-06011: Not the default thread, aborting transaction containing PKUPDATE and letting barrier thread apply the transaction.

Cause: Coordinated Replicat thread is not executing a record containing PK Updates. This is expected for all but one of the threads.

Action: None

OGG-06012: The parameter file of a non-coordinated Replicat contains a THREAD, THREADS or THREADRANGE parameter. These parameters are ignored by non-coordinated Replicats.

Cause: The parameter file for a non-coordinated Replicat contains the THREAD, THREADS, or THREADRANGE parameter, which is not supported.

Action: Remove the THREAD, THREADS, or THREADRANGE parameter or run the Replicat as a coordinated Replicat.

OGG-06013: A HANDLECOLLISIONS clause in the parameter file for a non-coordinated Replicat contains a THREAD, THREADS, or THREADRANGE parameter. The THREAD, THREADS, or THREADRANGE parameter will be ignored.

Cause: The parameter file for a non-coordinated Replicat contains a HANDLECOLLISIONS or NOHANDLECOLLISIONS clause with a THREAD, THREADS, or THREADRANGE parameter, which is not supported.

Action: Remove the THREAD, THREADS, or THREADRANGE parameters from the HANDLECOLLISIONS clause or run the replicat as a coordinated Replicat.

OGG-06014: A non-coordinated Replicat received a HANDLECOLLISIONS or NOHANDLECOLLISIONS command with a THREAD, THREADS, or THREADRANGE parameter. The THREAD, THREADS, or THREADRANGE parameter will be ignored.

Cause: A non-coordinated Replicat received a HANDLECOLLISIONS or NOHANDLECOLLISIONS command with a THREAD, THREADS, or THREADRANGE parameter, which is not supported by a non-coordinated Replicat.

Action: Do not send HANDLECOLLISIONS commands with the THREAD, THREADS, or THREADRANGE parameter to a non-coordinated Replicat.

OGG-06015: The last Coordinated Replicat run did not stop at a clean state and the parameter file has changed.

Cause: Changes have been made to the parameter file, and the last run of this Coordinated Replicat group stopped in an inconsistent state.

Action: Make sure the previous configuration stopped in a consistent state, where all the threads are at the same position (synchronized). Use the normal STOP command to stop threads in a synchronized state, or if they are already stopped, use the SYNCHRONIZE command.

OGG-06016: Unable to set the Coordinated thread checkpoint files or checkpoint table to the desired states. Error: {0}

Cause: There was a problem reading or writing a checkpoint file or checkpoint table.

Action: Make sure the checkpoint files exist and have the proper read/write permissions for Replicat to access them and ensure that the state of the checkpoint table is correct. Contact Oracle support if the problem persists.

OGG-06017: MAP statements can only have one THREAD or THREADRANGE parameter: {0}

Cause: A MAP statement contains more than one THREAD or THREADRANGE parameter.

Action: Remove all but one of the THREAD or THREADRANGE parameters from the MAP statement.

OGG-06018: A HANDLECOLLISIONS or NOHANDLECOLLISIONS parameter in a MAP statement does not match the THREAD or THREADRANGE parameter in that MAP statement: {0}

Cause: A HANDLECOLLISIONS or NOHANDLECOLLISIONS parameter within the MAP statement specifies a thread that is not in the THREAD or THREADRANGE clause in that MAP statement.

Action: Modify the parameters so that HANDLECOLLISIONS and NOHANDLECOLLISIONS specify only threads that are within the map's THREAD or THREADRANGE clause.

OGG-06019: The last Coordinated Replicat run did not stop at a clean state, and the threads were changed in the parameter file. Make sure the previous run stopped in a consistent state (synchronized).

Cause: Changes were made to the THREAD or THREADRANGE option in the parameter file, but the last run of this Coordinated Replicat group stopped in an inconsistent state.

Action: Make sure the previous configuration stopped in a consistent state, where all the threads are at the same position (synchronized). Use the normal STOP command to stop threads in a synchronized state, or if they are already stopped, use the SYNCHRONIZE command.

OGG-06020: Register timed out

Cause: A TCP/IP error occurred while the thread was trying to register with the coordinator.

Action: Check for any firewalls that forbid the connection, such as blocking certain ports or processes. Consult your network administrator if you cannot resolve the problem, before contacting Oracle Support, to rule out any other network issues.

OGG-06021: Register timed out

Cause: The Coordinated Replicat thread received an incorrect message from the Coordinator.

Action: Check for any network issues that may be causing the problem, then contact Oracle Support.

OGG-06022: Cannot execute global SQLEXEC because the thread is not in the coordinated Replicat THREAD list.

Cause: The coordinated Replicat thread is not in the list specified in the parameter file. This is expected behavior.

Action: None

OGG-06023: Parameters associated with the THREAD token in {0} are invalid.

Cause: SQLEXEC when used with the THREAD parameter requires valid thread id's.

Action: Modify THREAD parameter associated with SQLEXEC to include valid id's.

OGG-06024: The {0} parameter is not supported for Coordinated Replicat.

Cause: The specified parameter is not supported for Coordinated Replicat.

Action: Remove the parameter from the parameter file or delete the Replicat and add it as a non-coordinated Replicat.

OGG-06025: The THREAD, THREADS, or THREADRANGE options of the TRACE parameter cannot be used for a non-coordinated Replicat.

Cause: A THREAD, THREADS, or THREADRANGE option was detected in the TRACE parameter for a non-coordinated Replicat. These are only supported for Coordinated Replicat.

Action: Remove the THREAD, THREADS, or THREADRANGE specification from the parameter file or delete the Replicat and then add it as a Coordinated Replicat.

OGG-06026: The parameter file has been changed since Coordinated Replicat started. The Coordinator and threads must all be using the same parameter file.

Cause: The parameter file crc value does not match the one recorded when Coordinated Replicat started. This indicates the parameter file was edited and changed during the startup sequence.

Action: Restart Coordinated Replicat to make sure Coordinator and threads are using the same file.

OGG-06027: Coordinator received a message that it was not expecting. Detail: {0}

Cause: A Coordinated Replicat thread belonging to another group (or another program) has sent the Coordinator a message. This can happen if the Coordinator reused a port used by a previous program or if the sending program is using the wrong port number.

Action: Check the process that sent the bad message, or restart Coordinated Replicat.

OGG-06028: Coordinated thread {0} cannot continue because the Coordinator is not running.

Cause: The Coordinator is not running.

Action: Check the Coordinator logs to see why it stopped working before the threads could register.

OGG-06029: Coordinator cannot continue because all Coordinated threads failed to register in the time allowed.

Cause: The Coordinator waits for a period of time before assuming Coordinated threads have died or had problems registering. The reason for the threads not registering could mean the processes died or had issues connecting with the Coordinator.

Action: Check the thread logs to see why they had issues starting and registering.

OGG-06030: The THREADRANGE option is only valid for the MAP statement. Use the THREADS option instead

Cause: It is not valid to specify the THREADRANGE option outside of a MAP statement.

Action: Use the THREADS option instead.

OGG-06031: The THREADS option is not valid for the MAP statement. Use the THREADRANGE option instead

Cause: It is not valid to specify the THREADS option in a MAP statement.

Action: Use the THREADRANGE option instead.

OGG-06032: Coordinator has not received message from thread {0}. Heartbeat timer expired.

Cause: The Coordinator did not receive a statistics response from the specified thread in the time period specified by the heartbeat timer.

Action: Check the logs to see what may have caused the thread to be unresponsive.

OGG-06033: Thread {0} has not received message from Coordinator. Heartbeat timer expired.

Cause: The coordinated thread did not receive a statistics request from the Coordinator in the time period specified by the heartbeat timer.

Action: Check the logs to see what may have caused the Coordinator to be unresponsive.

OGG-06034: This Coordinated Replicat thread matches multiple login specifications. Only the first will be used

Cause: There are multiple login specifications in the Replicat parameter file that match the Coordinated Replicat thread.

Action: Modify the parameter file so that no Coordinated Replicat thread is specified in multiple login specifications.

OGG-06035: The startup line or parameter file contains a Coordinated Replicat specific option (like THREAD or THREADS). This option is incompatible with regular Replicat.

Cause: The parameter file or startup options for a non-coordinated Replicat contains an option such as THREAD, THREADS, or THREADRANGE, which is not supported.

Action: Remove the coordinated specific option or run the Replicat as a Coordinated Replicat.

OGG-06036: Unable to access checkpoint table for thread: {0}. Ignore if this is the first startup of this group.

Cause: A call to access CSN information in the checkpoint table failed.

Action: If this is the first time that you started this group after creating it, ignore this message. Contact Oracle Support if it persists.

OGG-06037: Start parameters SKIPTRANSACTION, ATCSN, AFTERCSN and FORCECURRENTPOSITION are mutually exclusive. Only one may be specified per thread. Thread {0} has multiple specifications

Cause: Two or more mutually exclusive parameters are specified in the START REPLICAT command.

Action: Re-issue the START REPLICAT command with only one of the options per thread. Do not use FORCECURRENTPOSITION. It is not valid for START REPLICAT.

OGG-06038: Thread ID {0} is greater than the MAXTHREADS value specified when the Replicat group was created

Cause: A thread ID was specified that is greater than the maximum number of threads specified when the Replicat was created.

Action: Specify a thread ID less than the specified maximum number of threads or delete the Replicat and then re-create it with a greater maximum.

OGG-06039: Thread ID {0} is not active.

Cause: A thread ID was specified for a thread that is not active.

Action: Specify the ID of an active thread.

OGG-06040: Column {0} specified in the THREADRANGE parameter does not contain a before image. Either use primary key columns for THREADRANGE or specify the GETUPDATEBEFORES parameter for Extract.

Cause: The THREADRANGE parameter contains a column that is not a primary key and that column was updated. The THREADRANGE parameter uses the before image for update operations but cannot find one in this case, because before images are not logged unless the GETUPDATEBEFRES parameter is specified for Extract.

Action: Either use primary key columns for the THREADRANGE clause or add GETUPDATEBEFRES to the Extract parameter file. Contact Oracle Support if the error persists.

OGG-06041: Sequence {0} is specified in a MAP statement containing a THREADRANGE clause. This is not allowed in Coordinated Replicat. Please map sequence to THREAD clause instead.

Cause: THREADRANGE and sequence object type are incompatible in a MAP statement in Coordinated Replicat.

Action: MAP the sequence to a THREAD clause.

OGG-06042: This thread and the Coordinator are connected to different catalogs. All processes of a Coordinated Replicat must be connected to the same catalog.

Cause: All processes of a Coordinated Replicat must connect to the same catalog, but the parameter file specifies different catalogs for some processes.

Action: Modify the parameter file so that all processes connect to the same catalog.

OGG-06043: The coordinator has not received a heartbeat message from thread {0}. ({1} seconds since last stat message received)

Cause: The coordinator did not receive a heartbeat message from the specified thread. If the coordinator does not receive a heartbeat message soon, Replicat may abend.

Action: Check the status of specified thread. It may be hung or in bad state.

OGG-06044: Statements can only have one THREAD, THREADS, or THREADRANGE parameter

Cause: A statement contains more than one THREAD, THREADS, or THREADRANGE parameter.

Action: Remove all but one of the THREAD, THREADS, or THREADRANGE parameters from the statement.

OGG-06045: Could not find column {0} specified in the THREADRANGE parameter

Cause: The process cannot find a column that is specified in a THREADRANGE clause.

Action: Check the THREADRANGE clause to make certain the name of the column is spelled correctly and that it exists in the source data.

OGG-06046: Not the default thread, aborting transaction containing EVENTACTIONS and letting barrier thread apply the transaction.

Cause: Coordinated Replicat thread is not executing a record containing EVENTACTIONS. This is expected for all but one of the threads.

Action: None

OGG-06047: Not the default thread, aborting transaction containing COORDINATED record and letting barrier thread apply the transaction.

Cause: Coordinated Replicat thread is not executing a transaction containing COORDINATED records. This is expected for all but one of the threads.

Action: None

OGG-06048: Error in Replicat communication: {0}

Cause: There was an error in Replicat communication.

Action: If possible, resolve the condition listed in the error message. Otherwise, contact Oracle Support.

OGG-06049: Replicat received an invalid connection

Cause: Replicat received an invalid connection.

Action: Make sure that the ports configured for use by GoldenGate are not used by other processes. Contact Oracle Support if the problem persists.

OGG-06050: Error communicating with thread {0}

Cause: Replicat encountered an error when trying to communicate with a thread.

Action: Fix any problems indicated by other error messages. Contact Oracle Support if the problem persists.

OGG-06051: Connection to Master unexpectedly terminated

Cause: Replicat was disconnected from the Master unexpectedly.

Action: Fix any problems indicated by other error messages. Contact Oracle Support if the problem persists.

OGG-06052: Error communicating with Master

Cause: Replicat encountered an error when trying to communicate with the Master.

Action: Fix any problems indicated by other error messages. Contact Oracle Support if the problem persists.

OGG-06053: Conflict in NUM_MAPPERS or NUM_APPLIERS specification for TARGETCATALOG {0}

Cause: The parameter file contains two TARGETCATALOG specifications for a catalog with conflicting values for NUM_MAPPERS or NUM_APPLIERS.

Action: Remove the conflicting specification from the parameter file.

OGG-06054: TARGETCATALOG specifications require more Appliers than are available

Cause: The TARGETCATALOG specifications in the parameter files specify a number of Appliers greater than the NUM_APPLIERS parameter.

Action: Modify the TARGETCATALOG specifications to reduce the number of Appliers or increase the value specified for NUM_APPLIERS.

OGG-06055: TARGETCATALOG specifications require more Mappers than are available

Cause: The TARGETCATALOG specifications in the parameter files specify a number of Mappers greater than the NUM_MAPPERS parameter.

Action: Modify the TARGETCATALOG specifications to reduce the number of Mappers or increase the value specified for NUM_MAPPERS.

OGG-06056: A THREAD, THREADS, or THREADRANGE option specifies Thread ID {0}, which is greater than the group's MAXTHREADS ({1}).

Cause: A THREAD, THREADS, or THREADRANGE option specifies a Thread ID that is greater than the value of MAXTHREADS, which was specified when the group was created.

Action: Change the option so that the Thread IDs specified are less than or equal to the value of MAXTHREADS or recreate the Replicat with a higher value of MAXTHREADS.

OGG-06057: The value of SPLIT_TRANS_RECS was changed after Replicat ABENDED. Previous value: {0}.

Cause: The value specified for the SPLIT_TRANS_RECS parameter was changed after Replicat abended. Changes to SPLIT_TRANS_RECS should only be made when Replicat is stopped.

Action: Change the value of SPLIT_TRANS_RECS back to the previous value, START and STOP the Replicat, and then change the value of SPLIT_TRANS_RECS as needed.

OGG-06058: The parameter file of a non-Parallel Replicat contains the SPLIT_TRANS_RECS parameter. This parameter is ignored by non-Parallel Replicats.

Cause: The parameter file for a non-Parallel Replicat contains the SPLIT_TRANS_RECS parameter, which is not supported.

Action: Remove the SPLIT_TRANS_RECS parameter or recreate the Replicat as a Parallel Replicat.

OGG-06059: Not the default thread, aborting transaction containing updated source metadata and letting barrier thread apply the transaction.

Cause: Coordinated Replicat thread is not executing a transaction containing updated source metadata. This is expected for all but one of the threads.

Action: None

OGG-06100: Unable to convert an Oracle NUMBER attribute to a CHARACTER string. OCI Error {0}

Cause: A NUMBER attribute of a UDT could not be converted to a CHARACTER string, possibly because the data is corrupted.

Action: Fix the column value in the source database, and then restart Extract so that it captures the corrected data.

OGG-06101: '{0}': This feature is not supported on the current platform

Cause: An option or resource which is not supported on the current platform has been used.

Action: Use a proper option according to your platform.

OGG-06102: Unable to open credential store. Error code {0}.

Cause: The function call to open a credential store returned with an error code.

Action: Contact Oracle Support for help.

OGG-06103: Alias '{0}' not found in credential store.

Cause: The specified alias-credential group are not contained in current credential store.

Action: Verify the alias and credential group were typed correctly.

OGG-06104: Replicat does not support DDL operations for this database. Ignoring this operation.

Cause: Replicat encountered a DDL operation in the trail. DDL is not supported for this database, so this operation will be ignored.

Action: None

OGG-06105: SHELL argument {0} failed with error value {1}.

Cause: The SHELL argument failed due to improper argument specification or an internal expansion processing error.

Action: Verify that the SHELL expression is valid. If it appears valid, contact Oracle Support for further assistance.

OGG-06106: Bad value for source record.

Cause: The source record required to process SHELL arguments is invalid.

Action: Contact Oracle Support.

OGG-06107: Parameter {0} value was adjusted from {1} to {2}.

Cause: The specified parameter value was adjusted by the system.

Action: None

OGG-06108: Error generating encryption key. Error code {0}. Contact Oracle Support.

Cause: Oracle GoldenGate failed to generate an encryption key.

Action: Contact Oracle Support.

OGG-06109: Error encoding encryption key. Contact Oracle Support.

Cause: Trail encryption failed because an encryption key could not be generated.

Action: Contact Oracle Support.

OGG-06110: Error decoding encryption key. Contact Oracle Support.

Cause: An internal error occurred when trying to decode the trail encryption key.

Action: Contact Oracle Support.

OGG-06111: Error trying to use AES for trail encryption. The cipher is not defined properly.

Cause: The process tried to use an AES cipher that is not defined correctly.

Action: Verify that the AES specification is correct in the parameter file. Note that the same AES specification and key must be used to encrypt the trail and also to decrypt it. For example, if the trail is encrypted with AES 256, it must be decrypted with AES 256. If this problem persists, contact Oracle Support.

OGG-06112: AES encryption key length of {0} bytes exceeds the maximum allowed.

Cause: The process tried to use an AES encryption key that is larger than the maximum supported size of 256 bits.

Action: If the AES key is specified in the parameter file, change it to a supported key size. If the key is Oracle GoldenGate-generated, contact Oracle Support.

OGG-06113: Invalid AES encryption key.

Cause: The process attempted to use an AES encryption key with an incorrect value.

Action: If the AES key is specified in the parameter file, change it to a supported AES key value. If the key is Oracle GoldenGate-generated, contact Oracle Support.

OGG-06114: Error retrieving masterkey {0} from wallet at location {1}.

Cause: The process tried to use an encryption key from the master key wallet but could not find either the wallet or the name or version of the master key.

Action: Make certain that the GLOBALS parameter WALLETLOCATION contains the path to the appropriate wallet and that the parameter

MASTERKEYNAME specifies a valid name and version of a masterkey that is stored in the specified wallet.

OGG-06115: Error decrypting trail file. Algorithm not supported on this platform.

Cause: The trail file header specifies that data has been encrypted with an algorithm not supported on this platform.

Action: Make certain that the Oracle GoldenGate source configuration for encryption is supported on the target system. If necessary, recreate and resend the trail file with the new configuration.

OGG-06116: The name of a trace file specified in an EVENTACTIONS clause is too long: {0}

Cause: The name of the specified trace file in the EVENTACTIONS parameter exceeds the length that is supported by Oracle GoldenGate.

Action: Use a shorter file name or file path for the name of the trace file, up to the maximum number of characters supported by the operating system for file names.

OGG-06117: Processed LOG event {0}{1}

Cause: This is a generic Event Marker Infrastructure informational message relating to the use of the EVENTACTIONS parameter. It may be useful for operational, performance, or diagnostic purposes.

Action: None

OGG-06118: Processed LOG event {0}{1}

Cause: This is a generic Event Marker Infrastructure warning message related to the use of the EVENTACTIONS parameter. It may indicate a potential problem and can be used for operational, performance, or diagnostic purposes.

Action: Take action based on the message that is returned. If you cannot resolve the problem, contact Oracle Support.

OGG-06119: Trail file {0} is encrypted but no decryption key was found.

Cause: The trail file header indicates that its content is encrypted, but the reading process could not find the key in the trail metadata. The Oracle GoldenGate source configuration might be using an ENCKEYS file to store an encryption key, but the reading process is not configured to use this method.

Action: Make certain that the source and target configuration for trail encryption matches. If using ENCKEYS in source, target needs this method as well. Contact Oracle Support if assistance is needed.

OGG-06120: Trail file is encrypted with masterkey. Ignoring ENCKEYS configuration

Cause: The trail file header indicates that its content has been encrypted using the master encryption key, but the parameter file contains the ENCKEYS configuration.

Action: Remove the ENCKEYS configuration or specify DECRYPTTRAIL with no options to prevent further warning messages.

OGG-06121: Trail file is not encrypted. Ignoring DECRYPTTRAIL parameter

Cause: The trail file header indicates that its content is not encrypted, but the parameter file contains the DECRYPTTRAIL parameter.

Action: Remove the DECRYPTTRAIL parameter to prevent further warning messages.

OGG-06122: Cannot encrypt a trail file twice with masterkey. Encryption algorithm found in parameter file: {0}

Cause: Encryption with a master key is specified in the parameter file, but the input trail file that the data pump reads is already encrypted with a master key.

Action: Delete the ENCRYPTTRAIL parameter, or specify the DECRYPTTRAIL parameter if you want to keep ENCRYPTTRAIL.

OGG-06123: Cannot encrypt a trail file twice. Encryption algorithm found in parameter file: {0}. Encryption algorithm found in input trail file {1}.

Cause: Encryption is specified in the parameter file, but the input trail file that the data pump reads is already encrypted.

Action: Delete the ENCRYPTTRAIL parameter, or specify the DECRYPTTRAIL parameter if you want to keep ENCRYPTTRAIL.

OGG-06124: Cannot find AES key when attempting to reencrypt data record at trail file {0}, RBA {1,number,0}.

Cause: Added/removed token has forced record reencryption in passthru mode, but the AES key is unavailable in the trail file header.

Action: Copy the ENCKEYS file to the ABENDED pump's Oracle GoldenGate installation directory if not already available. Set the DECRYPTTRAIL and ENCRYPTTRAIL parameters at pump configuration file in order to force reencryption of the affected record. Optionally, revert back to the previous configuration when the affected record has been processed.

OGG-06125: Trail file uses AES encryption, but the AES key cannot be found in the trail header.

Cause: The incoming trail file was originally encrypted using ENCKEYS file enabled key, but the process's parameter file is either missing a DECRYPTTRAIL statement completely, or the DECRYPTTRAIL statement lacks the KEYNAME option needed to identify individual keys in the ENCKEYS file.

Action: Copy the ENCKEYS file to the ABENDED pump's Oracle GoldenGate installation directory if not already available. Set the correct DECRYPTTRAIL and ENCRYPTTRAIL parameters in the process configuration file to force decryption and reencryption of user data.

OGG-06200: A catalog name {0} is specified in an environment where database does not support a catalog.

Cause: A catalog name is specified in a database that does not support a catalog.

Action: Provide a table specification that is valid for your database.

OGG-06201: Parameter {0} is invalid because wildcards in catalog names are not supported.

Cause: A wildcard was used to specify a catalog name. Wildcards in catalog names are not supported.

Action: Change the wildcared names to their exact names.

OGG-06203: Failed to switch to catalog {0}. OCI Error {2} (status = {1,number,1}), SQL <{3}>

Cause: There was a failure when the process attempted to switch catalogs.

Action: Contact Oracle Support

OGG-06204: A catalog name {0} is specified in a parameter file. However, the target database does not support a catalog.

Cause: The database does not support catalogs.

Action: Provide a table specification that is valid for your database.

OGG-06205: Invalid configuration for capturing changes from a container database.

Cause: The Extract configuration does not support container databases.

Action: Use Integrated Capture v2 with Integrated dictionary support.

OGG-06206: The database connection must be to the root level database for user {0}.

Cause: Supply connection information for the root level database.

Action: Supply connection details to the root level database.

OGG-06207: Connection user {0} is not a common user.

Cause: The supplied connection user must be a common user.

Action: Supply a user who has common user privileges.

OGG-06208: DEFGEN was running against catalog {1}. Only tables in the login catalog {0} can be processed by DEFGEN.

Cause: Only tables in the login catalog can be processed by DEFGEN.

Action: Login to the catalog where target tables reside.

OGG-06209: Use either two-part or three-part names in the DEFGEN parameter file, but not both.

Cause: The DEFGEN parameter file contains TABLE specifications that have both two-part names (schema.table) and three-part names (catalog.schema.table). All table names in a given DEFGEN definitions file must be of the same format.

Action: Edit the DEFGEN parameter file to make the table names consistent.

OGG-06210: Replicat cannot apply transactions to catalog {0} while it is logged into catalog {1}.

Cause: Replicat can only apply transactions to its login catalog for the database.

Action: Specify a target catalog in the TARGET clause that is the same as the login catalog specified in the USERID clause or remove the catalog name from the TARGET clause to use the login catalog as the target catalog.

OGG-06211: DEFGEN failed to access catalog {0} to retrieve table definitions.

Cause: DEFGEN was not able to access the specified catalog to retrieve table definitions for the definitions file.

Action: Make certain the USERID user specified in the parameter file has sufficient privileges to access the catalog, and that the catalog is available in the database.

OGG-06212: Wildcarded catalog names is only supported if DEFGEN logs into the database at the root level.

Cause: DEFGEN is configured to log into a specific catalog, but the TABLE specification contains at least one wildcarded catalog specification. To use wildcarded catalog names, DEFGEN must log into the root catalog.

Action: Take either of these actions: To keep the wildcarded catalog specifications, configure DEFGEN to log into the root catalog, or else remove the wildcarded catalog specifications and change them to match the name of the catalog that DEFGEN logs into.

OGG-06213: DEFGEN cannot use the default catalog for table specification {0} while logged into the root level of a database.

Cause: The TABLE parameter does not include a catalog name.

Action: Specify the fully qualified table name, including the catalog name, in the TABLE parameter in the DEFGEN parameter file.

OGG-06214: Invalid version found in DEFGEN file: {0}

Cause: The version number found in DEFGEN's output file is not valid.

Action: Contact Oracle GoldenGate Support.

OGG-06215: Cannot obtain Pluggable Database name for metadata handle {0}.

Cause: Oracle GoldenGate could not determine the name of the Oracle Pluggable Database.

Action: Make certain that Oracle 12.1 was installed correctly. If the problem persists, contact Oracle Support.

OGG-06216: The DDL OBJNAME specification '{0}' does not include a catalog name, and a default source catalog name is not specified for the SOURCECATALOG parameter.

Cause: The object name in the DDL OBJNAME statement does not include a catalog name. If a default source catalog name is not specified with the SOURCECATALOG parameter, DDL OBJNAME requires a catalog name.

Action: Add a catalog name to the DDL OBJNAME object name specification or specify a default source catalog name with the SOURCECATALOG parameter.

OGG-06217: A catalog name {0} is specified in DDL OBJNAME parameter, but the database does not support a catalog.

Cause: The database does not support catalogs.

Action: Provide a DDL OBJNAME specification that is valid for your database.

OGG-06218: The parameter {0} is invalid for a container database.

Cause: The specified parameter is not supported for container databases.

Action: Remove the unsupported parameter.

OGG-06219: Unable to extract data from the Logmining server {0}

Cause: An error occurred while reading the input data stream from the Logmining server.

Action: Query the DBA_CAPTURE view from the mining database to obtain additional information on the specified Logmining server.

OGG-06220: Classic Extract does not support multitenant container databases.

Cause: Classic Extract is configured to capture from a multitenant container database.

Action: Use Integrated Extract for multitenant container database.

OGG-06300: The '{1}' option for the '{0}' parameter is no longer supported.

Cause: The parameter option specified is no longer supported by Oracle GoldenGate.

Action: Fix the syntax. For help with syntax and values, see the Oracle GoldenGate reference documentation.

OGG-06301: Error calling ftok() on file, '{0}'. Error {1,number,0} - {2}.

Cause: An operating system error was returned when attempting to obtain a token for a file.

Action: Check the local file systems for errors.

OGG-06302: File '{0}' is missing the expected token, '{1}'.

Cause: The file specified does not contain the expected contents.

Action: Correct the file contents and try again.

OGG-06303: Unable to read from file '{0}' (error {1,number,0}, {2}).

Cause: An error occurred while the process was reading from an open file.

Action: Check for related errors in the error log of the operating system. If you cannot resolve the problem, contact Oracle Support.

OGG-06304: Unable to write to file '{0}' (error {1,number,0}, {2}).

Cause: An error occurred while the process was writing to an open file.

Action: Check for related errors in the error log of the operating system. If you cannot resolve the problem, contact Oracle Support.

OGG-06305: Invalid option: expecting 'MMAP', 'SHM', or 'SHM ID N', but found '{0}'.

Cause: The datastore was created with an invalid memory specification.

Action: Issue the CREATE DATASTORE command with the correct syntax. For help, see the GGSCI help or the Oracle GoldenGate reference documentation.

OGG-06306: Datastore alter failed.

Cause: The datastore environment cannot be altered.

Action: After stopping all GoldenGate processes, including Manager, issue the ALTER DATASTORE command with the correct syntax. For help, see the GGSCI help or the Oracle GoldenGate reference documentation.

OGG-06307: Datastore does not exist.

Cause: The command failed because the datastore does not exist.

Action: Issue the CREATE DATASTORE command with the correct syntax. For help, see the GGSCI help or the Oracle GoldenGate reference documentation.

OGG-06308: Datastore uses memory mapped (MMAP) environment files.

Cause: The datastore uses memory mapping files for its environment resources.

Action: No action required.

OGG-06309: Datastore uses shared memory (SHM) environment files with a starting ID of 0x{0}.

Cause: The datastore uses System V shared memory for its environment resources.

Action: No action required.

OGG-06310: The {0} DATASTORE command requires that all Oracle GoldenGate processes are stopped, including Manager.

Cause: Modifications to the datastore cannot take place while other local Oracle GoldenGate processes are running.

Action: Stop all GoldenGate processes, including Manager, and try the original command again. For help, see the GGSCI help or the Oracle GoldenGate reference documentation.

OGG-06311: Datastore does not support shared memory on Windows platforms.

Cause: The SHM option was used in the command. This option is not supported on Windows.

Action: Retry the command using the MMAP option.

OGG-06312: '{0}' command unavailable because statistics collection is disabled.

Cause: The 'NOSTATS' parameter in the file, 'GLOBALS', disables all statistics collection. When 'NOSTATS' is present, the 'TRACE' and 'TRACE2' commands cannot be used.

Action: Remove the 'NOSTATS' parameter if statistics collection is desired.

OGG-06313: Collection profiles could not be loaded for this process and are disabled.

Cause: When the Collection Profiles cannot be loaded by EXTRACT or REPLICAT, all statistics collection is disabled.

Action: Enable Activity Logging for additional reasons for the failure.

OGG-06314: Default thread stack size could not be modified.

Cause: The default value of the stack size could not be increased because an internal function failed.

Action: Set PTHREAD_DEFAULT_STACK_SIZE directly in the command shell. If the problem persists, contact Oracle Support.

OGG-06315: Modified the default thread stack size to {0,number,0} bytes.

Cause: putenv function succeeded in changing the PTHREAD_DEFAULT_STACK_SIZE. The value of PTHREAD_DEFAULT_STACK_SIZE was successfully changed.

Action: No action required.

OGG-06316: Table {0} cannot be processed. Capture is not supported for DB2 Catalog tables.

Cause: A DB2 Catalog table was specified for capture.

Action: Remove this table from the TABLE parameter.

OGG-06317: GG_OBJ_METADATA: Catalog name has a length of {0,number,0}, but the maximum allowed is {1,number,0}

Cause: The catalog name of the table contains too many characters to be supported by Oracle GoldenGate.

Action: Contact Oracle Support or, if you are working with an Oracle GoldenGate developer, contact that person.

OGG-06318: File name {0} is too long and caused truncation.

Cause: While formulating the group file name, a truncation error occurred.

Action: Use a fully qualified file name that is shorter than 250 characters.

OGG-06319: Could not retrieve definition for table {0}

Cause: Unable to retrieve definition for table.

Action: Contact Oracle Support.

OGG-06320: Replication of UROWID type is not supported. In table {0}, UROWID at Column {1,number,0} will not be replicated.

Cause: UROWID is not currently a supported data type for Extract in classic capture mode.

Action: UROWID replication support is currently supported by Extract in integrated capture mode. Contact Oracle Support.

OGG-06321: DDL Replication is not supported when the source and target databases are from different vendors.

Cause: Replication is not supported when the source and target are not from the same database vendor

Action: None

OGG-06322: Object {0} is an IBM i native name, which is incompatible with trail format level {1}.

Cause: The name of the IBM i native object is incompatible with trail formats prior to the 11.2.1 release format.

Action: Use a SQL alias for the object name, or specify 11.2.1 or later for the FORMAT RELEASE option of EXTTRAIL, RMTTRAIL, EXTFILE, or RMTFILE parameters.

OGG-06323: {0} is specified. Non ANSI SQL string syntax is used for parameter.

Cause: NOUSEANSISQL parameter is specified. Multi byte and special character can not be used for object name for parameter file compatibility.

Action: None

OGG-06324: Expecting schema name in table name {0}.

Cause: Table name parameter doesn't have required schema name.

Action: Edit the parameter file and supply the schema name.

OGG-06325: Expecting schema name in checkpoint table name {0} in GLOBALS.

Cause: Checkpoint table name parameter doesn't have required schema name.

Action: Edit the GLOBALS parameter file and supply the schema name.

OGG-06326: Extract encountered a snapshot-related error retrieving table {0} during initial load. OCI Error {2} (status = {1,number,0}).

Cause: The initial load session encountered a snapshot-related error.

Action: Refer to the Oracle database documentation for information on the database error code.

OGG-06327: File {0} has invalid byte order specification of 0x{1}.{2,choice,-1#|0#} Error when processing RBA {2}

Cause: Oracle GoldenGate found an unrecognized byte order in the specified trail file.

Action: Contact Oracle Support.

OGG-06328: Invalid byte order found: 0x{0}.{1,choice,-1#|0#} RBA: {1}.

Cause: Oracle GoldenGate found an invalid byte order when processing a record or other type of information.

Action: Contact Oracle Support.

OGG-06329: Trail file {0} using compatibility level {1} is incompatible with byte order specification of {2}. Using default format of {3}.

Cause: Oracle GoldenGate found an incompatible byte order specification for a trail file and is replacing it with the proper format.

Action: Delete the BYTEORDER parameter or specify a compatible format.

OGG-06330: Failed to initialize the parameter file parser.

Cause: The parameter file parser could not be initialized.

Action: Contact Oracle Support.

OGG-06331: Failed to create backup file {0}.

Cause: The backup file could not be created.

Action: Verify that the file doesn't already exist and check the permissions for the parent directory.

OGG-06332: Parameter file {0} has already been converted.

Cause: The parameter file is specified more than once on the command line or is included more than once.

Action: None

OGG-06333: Converting string literals to ANSI SQL while

NOUSEANSISQLQUOTES parameter is specified.

Cause: This will convert string literals to ANSI SQL (single quotes), and ignore the NOUSEANSISQLQUOTES parameter specified in GLOBALS.

Action: Remove NOUSEANSISQLQUOTES parameter from GLOBALS.

OGG-06350: Error adding item to transaction {0} for table={1}, op={2,number,0}, record id={3}, length={4,number,0}, errmsg={5}.

Cause: An internal error occurred in the Cache Object Manager (COM) when the process added an item to a transaction.

Action: Contact Oracle Support.

OGG-06351: The LOB columns in table {0} are not supported by the ALLOWTABLECOMPRESSION parameter.

Cause: The ALLOWTABLECOMPRESSION parameter is being used for tables that contain LOB columns. Compressed tables with LOB columns are not supported by Oracle GoldenGate for DB2 LUW v9.7.

Action: Remove the compressed tables that have LOB columns from the Oracle GoldenGate configuration or remove the ALLOWTABLECOMPRESSION parameter and use uncompressed table.

OGG-06352: cachemgr: filecaching: cm_mf_write_lower comErr: {0} write: {1} (errno {2}, {3})

Cause: An error occurred accessing the CACHEMGR temporary cache file.

Action: Contact Oracle Support.

OGG-06353: cachemgr: filecaching: cm_mf_write_lower WriteFile: {0} error: {1}

Cause: An error occurred accessing the CACHEMGR temporary cache file.

Action: Contact Oracle Support.

OGG-06354: cachemgr: filecaching: cm_mf_write_lower comErr: {0} write: {1}

Cause: An error occurred accessing the CACHEMGR temporary cache file.

Action: Contact Oracle Support.

OGG-06355: A cache file name is too long for an internal buffer

Cause: A cache file name is too long for an internal buffer.

Action: Contact Oracle Support.

OGG-06356: cm_cachedir_cleanup: ggGetFileList: err_code: {0} ({1})

Cause: An error occurred while cleaning up cache filese.

Action: Contact Oracle Support.

OGG-06357: cm_cachedir_cleanup: comErr: {0} remove: file: {1} errno: {2}

Cause: An error occurred while cleaning up cache files.

Action: Contact Oracle Support.

OGG-06358: {1}: Bad Parameter Argument: {0}: invalid size specification

Cause: The CACHEMGR parameter contains invalid syntax.

Action: Correct the syntax and then restart the process. For syntax and usage of CACHEMGR, see the Oracle GoldenGate reference documentation.

OGG-06359: CMDSEC: Failed to retrieve group information ({0}, {1})

Cause: The specified error occurred when the process attempted to get group information from the operating system.

Action: Fix the cause of the error, and then restart the program.

OGG-06360: CMDSEC: Failed to retrieve token information ({0}, {1})

Cause: The specified error occurred when the process attempted to get group information from the operating system.

Action: Fix the cause of the error, and then restart the program.

OGG-06361: CMDSEC: Failed to retrieve token information buffer size ({0}, {1})

Cause: The specified error occurred when the process attempted to get group information from the operating system.

Action: Fix the cause of the error, and then restart the program.

OGG-06362: CMDSEC: Failed to open process token ({0}, {1})

Cause: The specified error occurred when the process attempted to get group information from the operating system.

Action: Fix the cause of the error, and then restart the program.

OGG-06363: CMDSEC: Failed to retrieve user information ({0}, {1})

Cause: The specified error occurred when the process attempted to get group information from the operating system.

Action: Fix the cause of the error, and then restart the program.

OGG-06364: Invalid CMDSEC access specifier (line {0}): {1}

Cause: There is an invalid access specifier in the CMDSEC file.

Action: Fix the CMDSEC file to resolve the cause of the error.

OGG-06365: Invalid CMDSEC uid specifier (line {0}): must be between 0 and {1}

Cause: There is an invalid user ID specifier in the CMDSEC file.

Action: Fix the CMDSEC file to resolve the cause of the error.

OGG-06366: Invalid CMDSEC gid specifier (line {0}): must be between 0 and {1}

Cause: There is an invalid group ID specifier in the CMDSEC file.

Action: Fix the CMDSEC file to resolve the cause of the error.

OGG-06367: Missing CMDSEC entry (line {0}): {1}

Cause: There is a missing entry on the specified line in the CMDSEC file.

Action: Fix the CMDSEC file to resolve the cause of the error.

OGG-06368: The full name of the CMDSEC file is too long

Cause: The name of the CMDSEC file (including the path) exceeds the length that is supported by Oracle GoldenGate.

Action: Use a shorter file path for the CMDSEC file, up to the maximum number of characters supported by the operating system for file names.

OGG-06369: Failed to retrieve user information from the operating system

Cause: An error occurred when the process attempted to get group information from the operating system.

Action: Contact Oracle Support.

OGG-06370: Failed to retrieve user information from the operating system for this process, ({0}, {1})

Cause: The process could not retrieve user information from the operating system.

Action: Fix the cause of the error and then restart the process.

OGG-06371: Failed to retrieve group entry, ({0}, {1})

Cause: There was an error retrieving the user group for the process from the operating system.

Action: Fix the cause of the error and then restart the process.

OGG-06372: Failed to retrieve user entry, ({0}, {1})

Cause: There was an error retrieving the user group for the process from the operating system.

Action: Fix the cause of the error and then restart the process.

OGG-06373: Failed to retrieve primary group entry, ({0}, {1})

Cause: There was an error retrieving the user group for this process from the operating system.

Action: Fix the cause of the error and then restart the process.

OGG-06374: Invalid DDL statement: No INCLUDE

Cause: There is a DDL parameter that does not contain an INCLUDE clause. This parameter will always evaluate to false.

Action: Correct the DDL statement, remove it altogether, or comment the line out.

OGG-06375: Invalid DDL statement: Missing scope specification

Cause: There is a DDL parameter that is missing a scope specification.

Action: Specify a scope (MAPPED, UNMAPPED, OTHER) in the DDL parameter.

OGG-06376: {0} value must be quoted in single quotes (').

Cause: The required single quote marks are missing from a value in the specified parameter.

Action: Correct the parameter value.

OGG-06377: Single quote marks cannot be used to delimit {0}. Use double quotes.

Cause: A value in the specified parameter is enclosed within single quotes, but the correct syntax requires double quotes.

Action: Replace the single quote marks with double quote marks.

OGG-06378: Double quote marks cannot be used to delimit {0}. Use single quotes.

Cause: A value in the specified parameter is enclosed within double quotes, but the correct syntax requires single quotes.

Action: Replace the double quote marks with single quote marks.

OGG-06379: Operating system user group name {0} is too long for an internal buffer.

Maximum supported length is {1}.

Cause: The specified operating system user group name is too long for an internal buffer.

Action: Use a user with a shorter group name.

OGG-06380: Operating system user name {0} is too long for an internal buffer.

Maximum supported length is {1}.

Cause: The specified operating system user name is too long for an internal buffer.

Action: Use a user with a shorter user name.

OGG-06381: Error retrieving OS version ({0},{1})

Cause: The specified error was encountered while retrieving the operating system version.

Action: Fix the cause of the error and then restart the process.

OGG-06382: Unrecognized INCLUDE/EXCLUDE option: [{0}]

Cause: The specified option is not recognized as a valid INCLUDE or EXCLUDE option.

Action: Fix the invalid syntax.

OGG-06383: Error checking command security

Cause: The process could not verify the security of a command when checking the rules in the CMDSEC file.

Action: Contact Oracle Support.

OGG-06384: The syntax for parameter {0} is incorrect.

Cause: The specified parameter contains invalid syntax.

Action: Check for spelling errors, or see the Oracle GoldenGate reference documentation for the correct syntax.

OGG-06385: Upgrade operation was not performed because the checkpoint table {0} is already upgraded.

Cause: The upgrade operation was not performed because the checkpoint table is already upgraded.

Action: None

OGG-06386: Purging log history from {0} older than {1}: {2}

Cause: Manager was not able to purge rows in the log table that were older than the date shown for the reason shown.

Action: None

OGG-06387: Purging log history from {0} older than {1}: {2}

Cause: Manager is purging history from the log table. Informational only.

Action: None

OGG-06388: {0} rows deleted from history table

Cause: Manager is purging history from the log table. Informational only.

Action: None

OGG-06389: Unknown number of rows deleted from history table

Cause: Manager is purging history from the log table. Informational only.

Action: None

OGG-06390: Could not delete rows because no database specified

Cause: Manager failed to purge history from the log table because no database was specified.

Action: Specify a database.

OGG-06391: Error deleting rows because of error: {0}

Cause: Manager failed to purge history from the log table because of the specified error.

Action: Correct the specified error.

OGG-06392: PURGEDDLHISTORY parameter will be ignored because it is not supported with this configuration.

Cause: Either the database does not support it or the DDL history table does not exist.

Action: Remove the PURGEDDLHISTORY parameter.

OGG-06393: The data length of {0} exceeds the maximum allowed record length of {1}.

Cause: The length of the specified record exceeds the maximum length that is allowed for a remote-task Replicat.

Action: Contact Oracle Support.

OGG-06394: BEFORE.<column name> syntax has been deprecated, use @BEFORE(<column name>) instead.

Cause: The BEFORE.<column name> syntax is deprecated.

Action: Use @BEFORE(<column name>) syntax instead.

OGG-06395: Extract is not configured to capture DDL, but a DDL operation has occurred for table {0}, which could adversely affect the integrity of DML capture.

Cause: DDL occurred on a table that is in the Extract configuration, but Extract is not configured to capture DDL.

Action: Configure Extract to capture DDL by adding the appropriate parameters. See the Oracle GoldenGate reference documentation for parameter options.

**OGG-06396: WARNING: SPECIALRUN not supported by Integrated Replicat.
INTEGRATED keyword ignored**

Cause: SPECIALRUN is not supported by Integrated Replicat.

Action: Remove the INTEGRATED keyword.

OGG-06397: The TRANSEXCEPTION option was specified in the REPERROR parameter, but no exceptions mapping was provided for table {0}. The exception cannot be handled.

Cause: The TRANSEXCEPTION option was specified for REPERROR, but a mapping to an exceptions table is missing.

Action: Create an exceptions MAP statement that includes either the MAPEXCEPTION or the EXCEPTIONSONLY option and a mapping of the source table to an exceptions table. For help, see the Oracle GoldenGate administration documentation.

OGG-06398: Unknown encryption type.

Cause: The specified encryption algorithm is unknown.

Action: Specify an encryption algorithm that Oracle GoldenGate supports. See the Oracle GoldenGate security documentation for supported encryption options.

OGG-06399: The specified encryption method is not supported for this platform.

Cause: The specified encryption method is not implemented for this platform.

Action: Specify an encryption method that Oracle GoldenGate supports for this platform. See the Oracle GoldenGate security documentation for supported encryption options.

OGG-06400: The key specified with KEYNAME is not present in the ENCKEYS file.

Cause: The ENCKEYS file does not contain a key name that matches the one in the KEYNAME specification.

Action: Make certain the key name is spelled correctly in the input, or add the key name to the ENCKEYS file.

OGG-06401: No value given for KEYNAME specification.

Cause: No key value was specified for the KEYNAME specification in the parameter file.

Action: Edit the parameter file to specify a key name for the KEYNAME option.

OGG-06402: KEYNAME value exceeds maximum allowed length.

Cause: The key value specified for KEYNAME exceeds the maximum allowed length.

Action: Specify a key value that is compatible with the selected encryption algorithm.

OGG-06403: KEYNAME key value is not a valid hex string.

Cause: The value specified for KEYNAME is not a valid hex string.

Action: Specify a key value that is a valid hex string.

OGG-06404: The key value in KEYNAME does not have a closing quote mark.

Cause: The syntax that specifies the key value in KEYNAME does not contain a closing quote mark.

Action: Add the closing quote mark.

OGG-06405: The length of the key specified in KEYNAME does not match the encryption method of

Cause: The length of the key is not appropriate for the encryption algorithm that is specified.

Action: Specify a key that is appropriate for the algorithm. For supported algorithms and key values, see the Oracle GoldenGate security documentation.

OGG-06406: An error occurred when implementing encryption.

Cause: An error occurred during encryption that Oracle GoldenGate could not identify.

Action: Contact Oracle Support.

OGG-06407: Error (-11) retrieving key for {0} in file ENCKEYS: {1} {2}.

Cause: The specified key could not be retrieved.

Action: Make sure that the key exists in the ENCKEYS file.

OGG-06408: Error initializing encryption context: {0}.

Cause: An error occurred during encryption context initialization.

Action: If the problem persists, contact Oracle Support.

OGG-06409: Error encrypting string.

Cause: The string could not be encrypted.

Action: Make certain that the string is valid or use a different one.

OGG-06410: Error freeing encryption context: {0}.

Cause: An internal error occurred when freeing the encryption context.

Action: If the error persists, contact Oracle Support.

OGG-06411: Error initializing decryption context: {0}.

Cause: An internal error occurred when initializing the decryption context.

Action: If the error persists, contact Oracle Support.

OGG-06412: Error (-12) decrypting string: {0}

Cause: The string could not be decrypted.

Action: Decrypt the string with the same algorithm that was used to encrypt it.

OGG-06413: No encryption key specified. Using default key.

Cause: An encryption key was not specified for the Blowfish encryption algorithm, so the default key is being used.

Action: None if the default key is acceptable. To use a specific key, use the ENCRYPTKEY option with a key name in the ENCRYPT command.

OGG-06414: Missing password specification.

Cause: The ENCRYPT PASSWORD command was issued without a password specification.

Action: Issue the command again and include the password that is to be encrypted. For help with syntax, see the Oracle GoldenGate reference documentation or the ggsci help.

OGG-06415: The specified encryption algorithm requires a key value

Cause: The specified encryption algorithm requires a key value.

Action: Specify an encryption key. For help, see the ggsci help or the Oracle GoldenGate security documentation.

OGG-06416: Default key is not allowed for AES encryption

Cause: An Oracle GoldenGate DEFAULT key was specified for AES encryption. AES requires a user-defined encryption key.

Action: Generate a valid encryption key for use with AES encryption. For more information, see the Oracle GoldenGate security documentation.

OGG-06417: Using Blowfish encryption with DEFAULT key.

Cause: The specified encryption is Blowfish with a DEFAULT key generated by Oracle GoldenGate.

Action: None

OGG-06418: Must include an 'ENCRYPTKEY' clause to specify a key value for AES algorithm.

Cause: AES encryption is specified without an appropriate key value.

Action: Specify a valid encryption key. For more information, see the Oracle GoldenGate security documentation.

OGG-06419: Must have 'ENCRYPTKEY' clause

Cause: The command was issued without an ENCRYPTKEY clause.

Action: Specify the ENCRYPTKEY clause with a valid keyname when executing this command. For help, see the Oracle GoldenGate security documentation.

OGG-06420: Encryption command invalid. Expecting 'ENCRYPTKEY' or an encryption algorithm.

Cause: The encryption command was issued without an ENCRYPTKEY clause or an algorithm specification.

Action: Issue the command again with the correct input. For help, see the Oracle GoldenGate security documentation or the ggsci help.

OGG-06421: Password encryption failed. Error, key must be specified.

Cause: The password could not be encrypted.

Action: Make sure the password is a valid string, and check for spelling errors. If using an encryption key, make certain that the selected algorithm and the key are compatible. See the Oracle GoldenGate security documentation for help.

OGG-06422: The specified password is not long enough to encrypt; size {0}

Cause: The password is too small to be encrypted.

Action: Make sure the password has a valid string length. For supported values, see the Oracle GoldenGate security documentation.

OGG-06423: Error decoding encrypted password for TRANLOGOPTIONS ASM password [{0}].

Cause: The ASM password in TRANLOGOPTIONS could not be decoded.

Action: Correct the problem that caused the error shown in the message.

OGG-06424: Error decoding encrypted password for TRANLOGOPTIONS MININGPASSWORD [{0}].

Cause: The password specified for the mining database user is not valid.

Action: Correct the problem that caused the error shown in the message.

OGG-06425: Error (-12) {0}

Cause: The mining database password could not be decrypted.

Action: Correct the problem that caused the error shown in the message.

OGG-06426: Decryption failed with error {0}.

Cause: The buffer could not be decoded.

Action: Correct the problem that caused the error shown in the message.

OGG-06427: Error decoding key name {0}, {1}.

Cause: The key specified with KEYNAME could not be decrypted.

Action: Correct the problem that caused the error shown in the message.

OGG-06428: The key specified with KEYNAME could not be decrypted {0}, {1}.

Cause: The key specified with the KEYNAME option could not be decrypted.

Action: Correct the problem that caused the error shown in the message.

OGG-06429: Specified key length does not match length of actual key

Cause: The length of the key is not appropriate for the encryption algorithm that is specified.

Action: Specify a key that is appropriate for the algorithm. For supported algorithms and key values, see the Oracle GoldenGate security documentation.

OGG-06430: Encryption algorithm specified without ENCRYPTKEY clause

Cause: The algorithm specified requires a key in the ENCRYPTKEY clause.

Action: Specify a key that is appropriate for the algorithm in the ENCRPYTKEY clause. For supported algorithms and key values, see the Oracle GoldenGate security documentation.

OGG-06431: Auto-encryption and decryption of password failed, passwords do not match

Cause: There was a problem with Auto-encryption and decryption of the password.

Action: Please contact Oracle Support.

OGG-06432: '{0}': This feature is not supported by Oracle GoldenGate Replicat on PostgreSQL. Please refer to the Oracle GoldenGate reference documentation for more details.

Cause: This feature is not supported by Oracle GoldenGate Replicat on PostgreSQL.

Action: Please refer to the Oracle GoldenGate reference documentation for more details.

OGG-06433: No schema is specified for sequence {0} in statement '{1}'. Using default login schema {2}.

Cause: A schema was not explicitly given in the specification for this sequence in the parameter file. The default login schema of the process is being used.

Action: To specify a schema other than the default login schema, edit the parameter file to specify the correct schema.

OGG-06434: Invalid source sequence name {0} specified.

Cause: An invalid source sequence name is specified in the TABLE/MAP parameter.

Action: Specify the correct source sequence name.

OGG-06435: Invalid target sequence name {0} specified.

Cause: An invalid target sequence name is specified in the TABLE/MAP parameter.

Action: Specify the correct target sequence name.

OGG-06436: Missing sequence name specification in TABLE/MAP parameter.

Cause: The name of the source sequence is missing from the TABLE or MAP parameter.

Action: Specify the name of the source sequence.

OGG-06437: No schema is specified for sequence {0} in statement '{1}'. No mapping will be applied.

Cause: The sequence specification does not include a schema name. No mapping can be performed without a schema specification.

Action: Add a schema to the sequence specification, as in schema.sequence. Otherwise, Oracle GoldenGate will assume the login specified in the USERID or USERIDALIAS parameter.

OGG-06438: No schema is specified for table {0} in statement '{1}'. No mapping will be applied.

Cause: A schema was not explicitly given in the specification for this table in the parameter file. No mapping will be applied.

Action: Add a schema to the table specification, as in schema.table. Otherwise, Oracle GoldenGate will assume the login specified in the USERID or USERIDALIAS parameter.

OGG-06439: No unique key is defined for table {0}. All viable columns will be used to represent the key, but may not guarantee uniqueness. KEYCOLS may be used to define the key.

Cause: No unique key is defined for the specified table.

Action: Use a KEYCOLS clause in TABLE or MAP to define a key that contains unique values. Using a defined key ensures uniqueness and improves performance.

OGG-06440: No viable unique key is defined for table {0}. All viable columns will be used to represent the key, but may not guarantee uniqueness. KEYCOLS may be used to define the key.

Cause: The table definition does not contain a unique key of the type that can be used by Oracle GoldenGate.

Action: Use a KEYCOLS clause in TABLE or MAP to define a key that contains unique values. Using a defined key ensures uniqueness and improves performance.

OGG-06442: Little-endian byte order and targetdefs specification found.

Cause: Oracle GoldenGate found a possible misconfiguration in parameters. In case the target system is NSK, little-endian format for trail files is inadequate.

Action: Change byte order for output trails to big-endian format.

OGG-06443: No KEYNAME given for {0} encryption algorithm

Cause: The encryption or decryption method that is being used requires a key specification with the KEYNAME option.

Action: Add the KEYNAME option to the ENCRYPT clause, as in ENCRYPT AES128, KEYNAME key_name. For more information, see the Oracle GoldenGate security documentation.

OGG-06444: Database major/minor version not available.

Cause: Oracle GoldenGate does not have the database version in its database metadata.

Action: Please contact Oracle Support.

OGG-06445: {0} {1} is starting

Cause: The specified process is starting.

Action: None

OGG-06446: Schema name is required for table specification {0}

Cause: The table specification does not include a schema name. A schema name is required when a catalog name is specified.

Action: Add the schema name to the table specification.

OGG-06447: Default schema name is not allowed for table specification {0}

Cause: A default schema name is not allowed to be used in this configuration.

Action: Specify schema names in the table specifications.

OGG-06448: Could not assign a default schema name for table specification {0}

Cause: A default schema name or a wildcard schema name is not supported for this configuration.

Action: Specify a schema name or enable wildcard schemas to be used.

OGG-06449: TARGETDEFS may adversely affect the DDL that is being captured.

Cause: The parameter file contains both TARGETDEFS and DDL parameters. DDL is only supported between like tables.

Action: Remove DDL support for tables affected by TARGETDEFS.

OGG-06450: WARNING: Source column {0} data cannot fit target column {1} buffer.

The data will be truncated..

Cause: The source column has more bytes/characters than the target column can hold.

Action: Contact Oracle Support for workaround.

OGG-06451: Triggers will be suppressed by default

Cause: By default, Replicat suppresses DML triggers.

Action: Use SUPPRESSTRIGGERS or NOSUPPRESSTRIGGERS to explicitly indicate the trigger settings.

OGG-06452: DBOPTIONS NOSUPPRESSTRIGGERS is not supported for the RDBMS version you are using.

Cause: DML trigger firing is not available on the target database.

Action: Do not use DBOPTIONS NOSUPPRESSTRIGGERS in the Replicat parameter file.

OGG-06453: DBOPTIONS SUPPRESSTRIGGERS is not supported for the RDBMS version you are using.

Cause: DML trigger firing suppression is not available on the target database.

Action: Do not use DBOPTIONS SUPPRESSTRIGGERS in the Replicat parameter file.

OGG-06454: DBLINK {0} not supported.

Cause: The object type DBLINKs are not supported in DDL.

Action: Filter out DDL operations that involve DBLINKs. For filtering options, see the Oracle GoldenGate for Oracle documentation or the DDL parameter in the Oracle GoldenGate reference documentation.

OGG-06455: Empty DEFAULT resolution column group for conflict {0}

Cause: The specified conflict has an empty column group for the DEFAULT resolution.

Action: Ensure that DEFAULT column group contains columns.

OGG-06456: Default tracetable name not allowed on CDB.

Cause: A valid tracetable name was not provided in the parameter file.

Action: Include a valid tracetable name with TRACETABLE statement in parameter file.

OGG-06457: One part tracetable name in replicat parameter file.

Cause: One part tracetable name given in replicat parameter file.

Action: Include a valid 2 or 3 part tracetable name in replicat parameter file.

OGG-06458: Wrong number of tracetable name parts in extract parameter file.

Cause: 1 or 3 part tracetable name given in extract parameter file.

Action: Include a valid 2 part tracetable name with TRACETABLE statement in extract parameter file.

OGG-06460: Trail FORMAT {0} or higher is required to support {1} option for table {2}.

Cause: The EXTFILE, EXTTRAIL, RMTFILE, or RMTTRAIL parameter contains the FORMAT option, but the given RELEASE value does not support the specified option.

Action: To support the specified option, set FORMAT RELEASE to at least the version shown in the error message.

OGG-06461: Trail record option {0} is incompatible with {1} for table {2}.

Cause: Two different trail record options {0} and {1} are specified for the same table.

Action: Edit the parameter file so that there is only one trail record format per table.

OGG-06462: The trail file was generated by an Extract that has the UPDATERECORDFORMAT parameter in its parameter file. It is not supported for this database

Cause: The trail file was generated by an Extract that has the UPDATERECORDFORMAT parameter in its parameter file. This type of trail is supported only for Oracle version 12 and above.

Action: Remove the UPDATERECORDFORMAT [FULL | COMPACT] parameter from the Extract parameter file and then restart Extract. Restart the data pump. Stop Replicat and issue the ALTER REPLICAT command with the EXTSEQNO and EXTRBA options to reposition Replicat to the new trail file, and then start Replicat.

OGG-06463: Invalid or incomplete option {0} for UPDATERECORDFORMAT.

Cause: Invalid or incomplete option {0} specified for UPDATERECORDFORMAT.

Action: Edit the parameter file and provide valid UPDATERECORDFORMAT option.

OGG-06464: Duplicate specification of UPDATERECORDFORMAT.

Cause: The parameter file contains more than one UPDATERECORDFORMAT parameter.

Action: Edit the parameter file so that it contains only one UPDATERECORDFORMAT parameter.

OGG-06465: Missing option for UPDATERECORDFORMAT.

Cause: The parameter file contains no option for the UPDATERECORDFORMAT parameter.

Action: Edit the parameter file to add an option for UPDATERECORDFORMAT parameter. Options are FULL or COMPACT.

OGG-06471: Unable to disable trigger firing

Cause: Replicat was unable to disable trigger firing on the target database.

Action: Check if the Replicat user has the required privileges to enable trigger suppression.

OGG-06472: Failed to enable DBOPTIONS SUPPRESSTRIGGERS

Cause: Replicat was unable to disable trigger firing on the target database.

Action: Check if the Replicat user has the required privileges to enable trigger suppression or remove DBOPTIONS SUPPRESSTRIGGERS from the Replicat parameter file.

OGG-06473: The parameter list is too long for {0}.

Cause: The parameter list is too long for the specified parameter.

Action: Reduce the number of values for specified parameter, or see the Oracle GoldenGate reference documentation for the correct syntax.

OGG-06474: Cannot specify parameters {0} and {1} together.

Cause: The specified parameters cannot be used together in the same parameter file.

Action: Specify only one of the parameters. See the Oracle GoldenGate reference documentation for the correct syntax.

OGG-06475: {0} {1} was killed after {2,number,0} seconds

Cause: The specified process was killed because it did not terminate in a timely manner.

Action: None

OGG-06476: {0} {1} could not be stopped after {2,number,0} seconds

Cause: The specified process could not be stopped and is still running.

Action: None

**OGG-06477: After image does not match table definition for {0} at {1}.{2,number,0}.
Restart Extract to acquire the most current table definition.**

Cause: The table may have been altered so that the current definition does not match the log record.

Action: Restart Extract to acquire the most current table definition.

OGG-06478: {2}: Buffer overflow, needed: {1,number,0}, allocated: {0,number,0}.
Table {3}, column {4} at SeqNo {5,number,0} RBA {6,number,0} Transaction {7}.
Cause: A numeric conversion failed because the value in the archive logs has more digits than the specified column can contain.
Action: Verify that the column definitions are correct.

OGG-06479: Schema level supplemental logging, including non-validated keys, is enabled on schema {0}.
Cause: Schema-level supplemental logging, including non-validated keys, is enabled for all objects in the specified schema, as the result of the ADD SCHEMATRANSACTION command. Informational only.
Action: None

OGG-06480: Schema level supplemental logging, excluding non-validated keys, is enabled on schema {0}.
Cause: Schema-level supplemental logging, excluding non-validated keys, is enabled for the specified schema, as the result of the ADD SCHEMATRANSACTION command. Informational only.
Action: None

OGG-06481: The database character set {0} is not English. Use TRAILCHARSETASCII or TRAILCHARSETEBCDIC to ensure correct conversion by Replicat.
Cause: The database character set is not English and the TRAILCHARSETASCII or TRAILCHARSETEBCDIC is not specified. Replicat may not be able to correctly perform any required character set conversion.
Action: Specify either TRAILCHARSETASCII or TRAILCHARSETEBCDIC in the Extract parameter file.

OGG-06482: The parameter _ALLOWTABLECOMPRESSION is deprecated. Use ALLOWTABLECOMPRESSION instead
Cause: The startup parameter _ALLOWTABLECOMPREESION is deprecated.
Action: Use ALLOWTABLECOMPRESSION to capture compressed tables.

OGG-06483: ALLOWTABLECOMPRESSION is set. LOB columns in compressed tables are not supported with this parameter.
Cause: ALLOWTABLECOMPRESSION does not support compressed tables that contain LOB columns.
Action: For DB2LUW version 9.7 and earlier, uncompress tables that contain LOB columns and capture them with a separate Extract group that does not include ALLOWTABLECOMPRESSION in the parameter file.

OGG-06484: ALLOWTABLECOMPRESSION is only valid for DB2LUW versions 9.7 and earlier. Ignoring this parameter.
Cause: ALLOWTABLECOMPRESSION is only valid for DB2LUW versions 9.7 and earlier. For DB2 version 10, Oracle GoldenGate fully supports capturing LOB columns and data from compressed tables simultaneously, without the need for the ALLOWTABLECOMPRESSION parameter.
Action: Remove the ALLOWTABLECOMPRESSION parameter.

OGG-06485: The {0} link is missing or unreadable from the Oracle GoldenGate product directory. Error {1,number,0}: {2}

Cause: The required object link has not been created or may have been deleted. See the previous message for more information.

Action: Re-run the ggos400install installation script to recreate the link.

OGG-06486: Unable to resolve the object {0}. Error {1,number,0}: {2}

Cause: Possible permission issue accessing the object. See the previous message for more information.

Action: Ensure the user profile has permission to access {0}.

OGG-06487: Failure to load the native object {0}. Error {1,number,0}: {2}

Cause: Possible permission issue accessing the object. See the previous message for more information.

Action: Ensure the user profile has permission to access {0}.

OGG-06488: Failure to load symbol {3} from object {0}. Error {1,number,0}: {2}

Cause: The version of the specified Oracle GoldenGate object does not match the version of the installed Oracle GoldenGate build.

Action: Re-run the ggos400install installation script to update the version of the Oracle GoldenGate objects.

OGG-06489: Datastore created

Cause: The datastore was created successfully.

Action: None

OGG-06490: Datastore altered

Cause: The datastore was altered successfully.

Action: None

OGG-06491: Datastore repaired

Cause: The datastore was repaired successfully.

Action: None

OGG-06492: Datastore deleted

Cause: The datastore was deleted successfully.

Action: None

OGG-06493: Extract is ready to use triggerless DDL capture, but first remove _USETRIGGERMETADATA from the DDLOPTIONS parameter.

Cause: The DDL trigger can be safely removed, but the DDLOPTIONS parameter contains the _USETRIGGERMETADATA option, which forces the use of a trigger.

Action: Remove the _USETRIGGERMETADATA option from the DDLOPTIONS parameter and then restart Extract.

OGG-06494: Restart Extract to initiate triggerless DDL capture.

Cause: It is safe for Extract to switch to triggerless DDL capture.

Action: Allow Extract to abend, and then restart Extract.

OGG-06495: OGG created a session pool with SESSIONPOOLMAX {0}, SESSIONPOOLMIN {1} and SESSIONPOOLINCR {2}.

Cause: A session pool was created for Oracle GoldenGate. The default values are SESSIONPOOLMAX-10, SESSIONPOOLMIN-5, SESSIONPOOLINCR-2.

Action: Make certain that SESSIONPOOLMAX is equal to the number of pluggable databases. For more information, refer to the Oracle database documentation for session pooling.

OGG-06496: Conflict detection is enabled for target table {0}, but the before values for the key columns are missing.

Cause: The specified table has a RESOLVECONFLICT parameter, but the before columns required by COMPARECOLS are not specified with GETBEFORECOLS.

Action: Specify GETBEFORECOLS in the Extract parameter file so that before images are captured for COMPARECOLS.

OGG-06497: The sequence number {1,number,0} for output trail file '{0}' is approaching the maximum threshold ({2,number,0}) at which point extract will abend. Please consult Oracle Knowledge Management Doc ID 1559048.1 for further actions.

Cause: The output trail file sequence number is incremented each time the trail file rolls over. The output trail file sequence number is approaching the maximum threshold value. When this threshold has been exceeded, extract will abend.

Action: To avoid this, extract will need to be assigned a new trail. Please consult Oracle Knowledge Management Doc ID 1559048.1 for further actions.

OGG-06498: The sequence number {1,number,0} for output trail file '{0}' has exceeded the maximum threshold ({2,number,0}). Please consult Oracle Knowledge Management Doc ID 1559048.1 for further actions.

Cause: The output trail file sequence number is incremented each time the trail file rolls over. The output trail file sequence number has reached the maximum threshold value.

Action: To continue, extract will need to be assigned a new trail. Please consult Oracle Knowledge Management Doc ID 1559048.1 for further actions.

OGG-06500: DDL of length [{5}], marker sequence [{0}], DDL sequence [{1}] for [{2}].[{3}/{4}] is too large. It will be ignored because _IGNORE_TRUNCATE_DDL parameter is specified.

Cause: The DDL statement is larger than the supported size. It will be truncated and ignored because the _IGNORE_TRUNCATE_DDL is used in the Extract parameter file.

Action: Discarding the DDL may cause metadata inconsistencies and generate errors if subsequent DML is issued for the same object. Apply the original DDL on the target, so that the metadata is consistent for future DDL. You may need to restart processes if the condition caused an error.

OGG-06501: Extract is not configured to run on a snapshot standby database. To enable this mode, add TRANLOGOPTIONS MINEFROMMSNAPSHOTSTBY to the Extract parameter file.

Cause: Oracle GoldenGate is not configured correctly for Extract to run on a snapshot standby database.

Action: To enable Extract to run on a snapshot standby database, use the TRANLOGOPTIONS parameter with the MINEFROMMSNAPSHOTSTBY option in the Extract parameter file.

OGG-06502: Standalone EXCLUDETAG parameter is specified for a primary extract.

Cause: EXCLUDETAG as a standalone parameter is only valid for data pump and replicat.

Action: Specify EXCLUDETAG as a TRANLOGOPTIONS option for primary extract, or use it as a standalone parameter for data pump or replicat.

OGG-06503: Environment variable 'TAG' contains invalid value {0}.

Cause: The environment variable 'TAG' must be in a format that represents the binary byte stream in hexadecimal.

Action: To customize the TAG variable, contact Oracle Support.

OGG-06504: A change record bearing tag {0} is excluded. All following changes with the same tag will also be excluded.

Cause: This tag value is specified in EXCLUDETAG clause in the parameter file.

Action: None

OGG-06510: Using the following key columns for target table {0}: {1}

Cause: Map resolved.

Action: Map resolved.

OGG-06514: Rollback ID {1,number,0} does not match last record ID of {0,number,0} in FM transaction manager. This will be ignored because _ALLOWMISMATCHEDROLLBACKID is set.

Cause: An internal inconsistency was detected in the Extract process while processing a transaction rollback.

Action: Contact Oracle Support.

OGG-06515: Record containing mismatched rollback ID has LSN : {0,number,0} and TID : {1,number,0}.

Cause: An internal inconsistency was detected in the Extract process while processing a transaction rollback.

Action: Contact Oracle Support.

OGG-06516: Could not find definition for {0}, possibly due to insufficient user access privilege.

Cause: The process could not find a definition for the specified table when building the object cache, possibly due to insufficient user privilege to access the table metadata.

Action: Check to make sure the user that is assigned to the process has access privilege to retrieve table metadata from the database. If the user privilege is verified to be sufficient, remove the table from the TABLE and/or MAP parameter. If using wildcards, you can exclude the table with TABLEEXCLUDE or MAPEXCLUDE.

OGG-06517: INFO TRANDATA failed on schema {0} because of the following OCI error: {1}-{2}

Cause: A OCI error prevented Oracle GoldenGate from getting information about schema-level supplemental logging through the INFO TRANDATA command.

Action: Fix the OCI error and retry the INFO TRANDATA command. If the OCI error cannot be resolved, contact Oracle Support.

OGG-06518: INFO TRANDATA failed due to error during select start.

Cause: The SELECT statement that underlies the INFO TRANDATA command failed.

Action: Try the command again. If the problem persists, contact Oracle Support.

OGG-06519: Error ({0,number,0}, no data found) selecting data in {1}. Check all DMLs and DDLs are processed before UDT DDLs are processed.

Cause: An error occurred when fetching data from an internal cursor. Extract did not complete all of the current DML and DDL before processing the DDL of a UDT.

Action: Make sure that all current DML and DDL are processed by Extract before issuing DDL for a UDT.

OGG-06520: BATCHSQL is disabled. An issue exists in IBM i that prevents BATCHSQL from functioning correctly. Once resolved through a PTF, BATCHSQL will require IBM i7.1 or greater.

Cause: The parameter file contains the BATCHSQL parameter, but BATCHSQL is currently not supported on IBM i due to an IBM issue.

Action: Remove BATCHSQL or specify the NOBATCHSQL parameter in the parameter file.

OGG-06521: BATCHSQL is disabled because the database or database version does not support it.

Cause: The parameter file contains the BATCHSQL parameter, but the database or the database version does not support BATCHSQL.

Action: Remove BATCHSQL or specify the NOBATCHSQL parameter in the parameter file.

OGG-06522: Cannot verify existence of table function that is required to {0} schema level supplemental logging, {1}.

Cause: The function that is used to enable/verify/delete schema level supplemental logging (ADD/INFO/DELETE SCHEMATRANSACTION commands) is missing from the database.

Action: All pre-11204 RDBMS releases need be patched with fix for bug-13794550. Apply the Oracle Patch to the source database.

OGG-06523: DDLOPTIONS CAPTUREGLOBALTEMPTABLE is only supported when the Integrated Dictionary is in use.

Cause: DDLOPTIONS CAPTUREGLOBALTEMPTABLE was specified in the parameter file, but trigger-based DDL capture is being used.

Action: Remove DDLOPTION CAPTUREGLOBALTEMPTABLE from the parameter file.

OGG-06524: The trail or file has reached the 2GB size limit. Add a MAXFILES clause to RMTFILE or EXTFILE.

Cause: The RMTFILE or EXTFILE parameter does not have a MAXFILES clause. Extract abends when the size of the file reaches the 2GB size limit unless a MAXFILES clause exists.

Action: Add a MAXFILES clause to the EXTFILE or RMTFILE parameter. MAXFILES permits as many files to be created as needed.

OGG-06525: Fetch failed for DBCLOB data type, column {0} in table {1}.

Cause: DB2 z/OS ODBC fails to correctly fetch data for data type DBCLOB > 2,000 bytes. IBM APAR PM99329 tracks this issue.

Action: Apply the fix for IBM APAR PM99329 if available, or, If possible, change Extract to avoid the fetch for this column.

OGG-06526: Internal error: Column with XMLDiff content does not have LOB data: (table {0}, column {1})

Cause: There was an internal error when the process tried to compose an UPDATE statement for an XMLtype column.

Action: Try using the TRANLOGOPTIONS parameter with the FETCHPARTIALXML option in Extract parameter file so that Replicat does not encounter PARTIAL XML. If the problem persists, contact Oracle support.

OGG-06527: Internal error: XMLDiff rewrite failed: (table {0}, column {1}) OCI Err: {2}

Cause: There was an internal error when the process tried to compose an UPDATE statement for an XMLtype column.

Action: Try using the TRANLOGOPTIONS parameter with the FETCHPARTIALXML option in Extract parameter file so that Replicat does not encounter PARTIAL XML. If the problem persists, contact Oracle support.

OGG-06528: Internal GG error: missing key columns for statement (table {0}, io_type={1})

Cause: The process could not compose a WHERE clause because the key columns are not available in the transaction record.

Action: Contact Oracle Support.

OGG-06529: Table name {0} specified in TABLE/MAP clause '{1}' contains a wildcarded catalog. The database does not support wildcards for those objects.

Cause: Wildcarded catalogs are not supported by this database.

Action: See the rules for catalog wildcarding in the Oracle GoldenGate documentation or contact Oracle Support.

OGG-06530: Berkeley Database encountered a critical error.

Cause: The Berkeley Database cannot be repaired automatically or there is a critical error, such as the system is out of memory.

Action: Repair the Berkeley Database environment and restart the Oracle GoldenGate groups to re-enable Oracle GoldenGate Monitor activity.

OGG-06531: Table {1} not in default catalog '{0}' specified in the ODBC connection. TRUNCATE on this table is not allowed by Informix. A DELETE was performed.

Cause: The specified table could not be truncated because it does not reside in the default catalog that is specified in the ODBC connection. A DELETE was performed on the table instead.

Action: None

OGG-06532: Failed to switch to Edition {0}. OCI Error {2} (status = {1,number,1}), SQL <{3}>

Cause: There was a failure when the process attempted to switch editions.

Action: Contact Oracle Support

OGG-06533: Failed to determine default Edition. OCI Error {1} (status = {0,number,0}), SQL <{2}>

Cause: There was a failure when the process attempted to query the default edition.

Action: Contact Oracle Support

OGG-06534: Reporting diagnostic information for unexpected fetching error. Table Name {0}, Object Type {1,number,0}, Object ID {2,number,0}, Sequence # {3,number,0}, RBA {4,number,0}, SCN {5}, xid {6,number,0}.{7,number,0}.{8,number,0}

Cause: This is an internal error. The process is reporting diagnostic information to troubleshoot the root cause of an unexpected fetching error.

Action: Contact Oracle Support.

OGG-06535: Extract does not support the database compatible setting {0}.

Cause: Oracle GoldenGate Extract does not support the specified database compatible setting.

Action: To view a list of supported versions and compatible settings for this database, log onto <http://support.oracle.com> and select the Certifications tab.

OGG-06536: Extract is not registered for log retention.

Cause: The Extract group was not registered for log retention with the REGISTER EXTRACT command in GGSCI. However, the LOGRETENTION ENABLED parameter is set in the Extract parameter file.

Action: Either register Extract for log retention with REGISTER EXTRACT or remove the LOGRETENTION ENABLED parameter from the Extract parameter file. For more information, see the Oracle GoldenGate documentation.

OGG-06537: SOCKS proxy server replied with error: {0}

Cause: Oracle GoldenGate received an error reply from the SOCKS proxy server.

Action: Verify that the SOCKS proxy is configured adequately to accept requests from your host. If required, make sure the authentication information is correctly specified in the Oracle GoldenGate configuration. Finally, contact the server administrator to look for useful information reported by the proxy.

OGG-06538: An error occurred during network communication with the SOCKS proxy server. {0}

Cause: Oracle GoldenGate received an unexpected message or an error occurred when sending or receiving information from the network.

Action: Verify that the SOCKS proxy server is visible from your host. Next, verify that the proxy is running and that the correct host and port have been specified in the parameter file. Finally, contact the server administrator to look for useful information reported by the proxy.

OGG-06539: The server authentication method {0} is not valid.

Cause: The SOCKS proxy server asked the client to authenticate with an invalid or unexpected authentication method during the handshake.

Action: Contact the server administrator to look for useful information reported by the proxy.

OGG-06540: The SOCKS proxy destination address {0} with size {1} exceeds the maximum length of 255 characters allowed.

Cause: The address specified in the RMTHOST or RMTHOSTOPTIONS parameter, which the proxy tries to connect with your host, is too long to be managed by the SOCKS 5 protocol.

Action: Use a shorter name of the address specifying an IPV4 or IPV6 format.

OGG-06541: The SOCKS proxy username or password with size {0} exceeds the maximum length of 255 characters allowed.

Cause: Either the username or password specified to authenticate with the proxy server is too long to be managed by the SOCKS 5 protocol.

Action: Change the username or password for a shorter one.

OGG-06542: An invalid proxy destination address has been specified: {0}:{1}.

Cause: The target address and port which the application is trying to connect through the proxy is not valid.

Action: Verify that the parameter for proxy address and port number has been specified correctly or contact Oracle Support.

OGG-06543: The parameters FORMATASCII/FORMATXML/FORMATSQL are not supported in PASSTHRU mode.

Cause: When PASSTHRU mode is specified, table metadata is not available to support the FORMATASCII/FORMATXML/FORMATSQL parameters.

Action: Either remove the FORMATASCII/FORMATXML/FORMATSQL parameter or remove the PASSTHRU parameters from the parameter file, depending on your configuration requirement.

OGG-06544: Editioned objects are not supported by this version of the Oracle database.

Cause: A DDL on an editioned object was found. This DDL cannot be applied because this version of the Oracle database does not support editioned objects.

Action: Filter the DDL out of the Oracle GoldenGate configuration.

OGG-06545: Failed to switch to edition {0} before applying the following DDL: {1}.

Cause: There was a failure when the process attempted to switch editions.

Action: Correct the error shown or filter the DDL out of the Oracle GoldenGate configuration.

OGG-06546: Failed to reset edition after applying the following DDL: {0}.

Cause: There was a failure when the process attempted to reset the edition back to the default.

Action: Correct the error shown or filter the DDL out of the Oracle GoldenGate configuration.

OGG-06547: Failed to remove the session tag before applying the DDL. DDLOPTIONS NOTAG will be disabled.

Cause: There was a failure when the process attempted to remove the session tag.

Action: No action necessary. DDLOPTIONS NOTAG will be automatically disabled.

OGG-06548: Failed to restore the session tag to {0}. DDLOPTIONS NOTAG will be disabled.

Cause: There was a failure when the process attempted to restore a session tag.

Action: No action necessary. DDLOPTIONS NOTAG will be automatically disabled.

OGG-06549: Value of column {1} in {0} is out of row and FETCHCOLS is not set for this column. Column value cannot be extracted.

Cause: Extended row size is enabled for this database, but Extract is not configured to fetch the value from the database.

Action: Specify this column with the FETCHCOLUMNS option of the TABLE parameter in the Extract parameter file. See the Oracle GoldenGate reference documentation for syntax.

OGG-06550: Unable to position in log buffer, current size {0}. Use parameter TRANLOGOPTIONS BUFSIZE to increase the size, within the range {1} to {2}.

Cause: An attempt to position in the log buffer failed because the buffer contained only records with duplicate LRSN values.

Action: Increase the buffer size, as indicated, to avoid the problem.

OGG-06551: Could not translate host name {0} into an Internet address.

Cause: There was an error resolving the host name into an IP address.

Action: Make sure the host name in the parameter file is specified correctly.

OGG-06552: TRANLOGOPTIONS parameter MINEFROMSNAPSHOTSTBY is not supported for a database that is not a Snapshot Standby database.

Cause: TRANLOGOPTIONS parameter MINEFROMSNAPSHOTSTBY is specified for a database that is not a Snapshot Standby database.

Action: Remove the parameter from the parameter file.

OGG-06553: DDL Annotation, operation [{0}], Number of Annotations: {1,number,0}

Cause: A DDL operation has annotations for DDL text

Action: None

OGG-06554: Failed to set default edition after applying the following DDL: {0}.

Cause: There was a failure when the process attempted to set the edition to the database default edition.

Action: Correct the error as described or filter the DDL out of the Oracle GoldenGate configuration.

OGG-06555: Set default session edition to [{0}].

Cause: The process set the session edition to the database default edition. This is an informational message.

Action: None

OGG-06556: The following columns will not be considered for CDR :{0}

Cause: This list of columns are not supported by CDR. Extract will not write the before image for these columns. Replicat will not include these columns for conflict detection.

Action: None

OGG-06557: PROCESS_GETINFORLIST_0 failed, Cpu {0}, Pin {1}, err ({2}, {3}).

Cause: Unknown.

Action: Evaluate the error message details and correct.

OGG-06558: FILENAME_TO_PATHNAME_0 failed, for {0}, error {1}.

Cause: Unknown.

Action: Evaluate the error message details and correct.

OGG-06559: FILE_GETINFOBYNAME_0 failed, for {0}, error {1}.

Cause: Unknown.

Action: Evaluate the error message details and correct.

OGG-06560: Invalid device type {0},{1} for Hometerm {2}.

Cause: Hometerm must be either a process or terminal.

Action: Change hometerm option to valid entry for hometerm.

OGG-06561: PATHNAME_TO_FILENAME_0 failed, for {0}, error {1}.

Cause: Unknown.

Action: Evaluate the error message details and correct.

OGG-06562: PROCESS_SPAWN_0 failed result {0}, tcpErr/detail ({1}/{2}).

Cause: Either the CPU, PRI, HOMETERM, or PROCESSNAME parameter is not valid.

Action: Evaluate the error message details and correct.

OGG-06563: Value {0} out of range for {1}, Range is -1, {2} thru {3}.

Cause: Invalid CPU or PRI.

Action: Evaluate the error message details and correct.

OGG-06564: Invalid parameter {0} for PROCESS_SPAWN_0.

Cause: Invalid parameter.

Action: Evaluate the error message details and correct.

OGG-06565: Formatting error on: table name {0}, rowid {1}. Error converting timestamp with timezone from Oracle to ASCII format for column {2}

Cause: An issue occurred during an attempt to convert column data from Oracle to ASCII format.

Action: Use either the INCLUDEREGIONID or the INCLUDEREGIONIDWITHOFFSET options. The INCLUDEREGIONIDWITHOFFSET option is for non-Oracle targets that do not support region ID; it forces conversion to TZH:TZM. Refer to Oracle GoldenGate Reference for Oracle GoldenGate for Windows and UNIX documentation.

OGG-06566: Invalid number {0} for {1}

Cause: Invalid CPU or PRI.

Action: Evaluate the error message details and correct.

OGG-06567: Missing attribute value for {0}

Cause: Invalid CPU or PRI.

Action: Evaluate the error message details and correct.

OGG-06568: DBLOGIN can only be used once on the IBM i platform. To use DBLOGIN again, you must restart the application.

Cause: DBLOGIN can only be used once on the IBM i platform. To use DBLOGIN again, you must restart the application.

Action: Exit from GGSCI then use DBLOGIN again.

OGG-06569: Remote Collector/Server version {0}.{1} receiving data is a different version than this Extract {2}.{3} sending data.

Cause: The version of the collector is different than the version of this installation.

Action: To avoid compatibility issues it is suggested to format to the lowest common version using the 'FORMAT RELEASE' parameter in the primary Extract.

OGG-06570: Unable to resolve the object {0}. OGGJRN not found in the GoldenGate installation library. Run the ggos400install script to create OGGJRN, and then run the ADD CHECKPOINTTABLE command again.

Cause: OGGJRN not found in the GoldenGate installation library.

Action: Run the ggos400install script to create OGGJRN, and then run the ADD CHECKPOINTTABLE command again.

OGG-06571: Unexpected path for GoldenGate Service program {0}. Expected {1} part.

For example, '/QSYS.LIB/INSTALL_LIBRARY.LIB/OGGPRCJRN.SRPGM'.

Run the ggos400install script.

Cause: Unexpected path for GoldenGate Service program.

Action: Run the ggos400install script.

OGG-06572: Add journaling for the checkpoint table failed. Table name: {0}.

Physical file name: {1}. Journal name: {2}. Review the previous error logs and correct the issues. Run the ADD CHECKPOINTTABLE command after correcting the error log issues.

Cause: Review the previous error logs.

Action: Run the ADD CHECKPOINTTABLE command after correcting the issues specified in the previous error logs.

OGG-06573: Attempt to resolve the GoldenGate installation library failed. Review the previous error logs. Run the ggos400install script, and then run the ADD CHECKPOINTTABLE command again

Cause: Review the previous error logs.

Action: Locate the GoldenGate installation library. Run the ggos400install script, and then run the ADD CHECKPOINTTABLE command again.

OGG-06574: Attempt to resolve the native table name from SQL name failed. Verify that the table was created. Table:{0}. Run the ADD CHECKPOINTTABLE command again

Cause: Call to fetch native table name returned zero rows.

Action: Verify that the table exists then run the ADD CHECKPOINTTABLE command again.

OGG-06575: The value of CHECKPOINTSECS must be greater than zero (0).

Cause: The value specified for the CHECKPOINTSECS parameter is invalid.

Action: Supply a positive integer value for the CHECKPOINTSECS parameter.

OGG-06576: Extended Row Size feature in DB2LUW is not supported when UPDATERECORDFORMAT parameter is set in OGG. Table {0} seems to have columns outside the row due to DB2 extended row size feature.

Cause: OGG does not support extended row size when UPDATERECORDFORMAT is set in the extract parameter file.

Action: Either remove the UPDATERECORDFORMAT parameter or move the table to a tablespace with larger page size.

OGG-06577: Invalid TRACETABLE parameter: {0}. Schema is required.

Cause: No schema is specified for the trace table in the TRACETABLE parameter.

Action: Edit the parameter file and specify the schema name for the TRACETABLE parameter.

OGG-06578: Invalid CHECKPOINTTABLE parameter: {0}. Schema is required.

Cause: No schema is specified for the checkpoint table in the CHECKPOINTTABLE parameter.

Action: Edit the parameter file and specify the schema name for the CHECKPOINTTABLE parameter.

OGG-06579: Invalid {0} parameter: {1}. Schema is required.

Cause: The default schema is not allowed for the TABLEEXCLUDE/MAPEXCLUDE parameter.

Action: Edit the parameter file and specify the schema name.

OGG-06580: No schema is specified for the source table {0}. The default schema is not allowed.

Cause: No schema is specified for the source table in the TABLE/MAP parameter.

Action: Edit the parameter file and specify the schema for the source table.

OGG-06581: No schema is specified for the target table {0}. The default schema is not allowed.

Cause: No schema is specified for the target table in the TABLE/MAP parameter.

Action: Edit the parameter file and specify the schema for the target table.

OGG-06582: No schema is specified for the table {0} in the DEFGEN parameter file. The default schema is not allowed.

Cause: No schema is specified for the table in the DEFGEN parameter file.

Action: Edit the DEFGEN parameter file and specify the schema.

OGG-06583: No schema is specified for the source sequence {0}. The default schema is not allowed.

Cause: No schema is specified for the source sequence in the SEQUENCE parameter.

Action: Edit the parameter file and specify the schema for the source sequence.

OGG-06584: No schema is specified for the target sequence {0}. The default schema is not allowed.

Cause: No schema is specified for the target sequence in the SEQUENCE parameter.

Action: Edit the parameter file and specify the schema for the target sequence.

OGG-06585: No schema is specified for the DDL/DDLSUBST/DDLERROR INCLUDE/EXCLUDE object name {0}. The default schema is not allowed.

Cause: No schema is specified for the include/exclude object name in the DDL/DDLSUBST/DDLERROR parameter.

Action: Edit the parameter file and specify the schema for the target sequence.

OGG-06586: Trail {0} has an invalid number of digits for the sequence number {1,number,0}.

Cause: Trail files can have either 6 or 9 digits for the sequence number.

Action: Trail files can have either 6 or 9 digits for the sequence number.

OGG-06587: Seqno {0} is out of range, valid range is from {1} to {2}.

Cause: Sequence number provided is out of range for the trail's sequence length.

Action: Provide a sequence number that is within the range for trail's sequence length.

OGG-06588: The remote peer for remote trail {0} does not support 9 digit sequence number.

Cause: Remote trail is defined to have a 9 digit sequence number, but the remote peer does not support this feature.

Action: Recreate the remote trail with a 6 digit sequence number or upgrade the remote peer.

OGG-06589: The startup input position has been rolled back from trail file {0} seqno {1} RBA {2} to seqno {3} RBA {4}.

Cause: Recovery repositioned the input trail to an earlier position based on checkpoint information and output trail scanning results.

Action: None

OGG-06590: The output trail file {0} is not found, rescan for previous ones.

Cause: The output trail file indicated by checkpoint record is not found. A rescan will be scheduled to try to recover from a previous trail file.

Action: None

OGG-06591: Reading the output trail file {0} encounters an error from position {1}, rescan from the file header to recover.

Cause: Scanning the output trail file encountered an error, when starting from the position indicated by checkpoint record. A rescan will be scheduled to recover from the beginning of this trail file.

Action: None

OGG-06592: Recovering from output trail {0} is failed

Cause: A recovery attempt on corrupt input position failed.

Action: Contact Oracle Support.

OGG-06593: Not enough information from output trail {0} to rollback input position.

Cause: A recovery attempt on corrupt input position failed, not enough information to find a safe rollback point.

Action: Contact Oracle Support.

OGG-06594: Replicat {0} has been altered through GGSCI. Even the start up position might be updated, duplicate suppression remains active in next startup. To override duplicate suppression, start {0} with NOFILTERDUPTRANSACTIONS option.

Cause: The duplicate suppression is active at startup time by default, even the replicat is altered by GGSCI. To skip duplicate suppression at startup time, use the NOFILTERDUPTRANSACTIONS command line option.

Action: None

OGG-06595: The replicat command line option FILTERDUPTRANSACTIONS is already a default. It is not necessary to explicitly specify this option.

Cause: FILTERDUPTRANSACTIONS is a default option for replicat.

Action: None

OGG-06596: Internal error processing Component Failed: {0}. Error Message: {1}.

Error Text: {2}.

Cause: This is an internal processing error.

Action: Contact Oracle Support.

OGG-06597: Unexpected error when mapping from {0} to {1}. Wildcarded member encountered when it was not expected Member Name: {2}.

Cause: This is an internal processing error.

Action: Contact Oracle Support.

OGG-06598: {0} is a compressed table but TRANLOGOPTIONS ALLOWTABLECOMPRESSION parameter is not specified in the extract parameter file.

Cause: OGG can capture compressed tables only when ALLOWTABLECOMPRESSION parameter is specified in the extract parameter file. This applies to DB2 v9.7 and earlier.

Action: Add ALLOWTABLECOMPRESSION in extract parameter file. Tables with LOB columns cannot be captured when this parameter is set.

OGG-06599: Unable to set replication tag due to OCI error {1} (status = {0, number, 0}), SQL <{2}>

Cause: There was an error while setting replication tag in database. This is expected behavior in some RDBMS versions, such as Oracle Database Standard Edition 11.2.0.1.

Action: None

OGG-06600: The remote peer for remote trail {0} does not support 9 digit seqlen feature. Continuing with 6 digit seqlen.

Cause: Remote trail is defined to have a 9 digit sequence number, but the remote peer does not support this feature.

Action: Downgrade the remote trail with a 6 digit sequence number or upgrade the remote peer.

OGG-06601: Mismatch between the length of seqno from checkpoint ({1}) and recovery ({2}) for extract trail {0}.

Cause: The seqlen of trail files returned by recovery process is different from the checkpoint. It's possible that residual trail files from a previous extract process still exist.

Action: Upgrade/downgrade the seqlen of the trail to match existing trail files or remove any residual trail files from a previous extract process.

OGG-08000: Could not create OCI environment.

Cause: Failed to create OCI environment by OCIEnvNslCreate() call.

Action: Ensure that your Oracle Database instance is installed and configured properly.

OGG-08001: Could not retrieve error detail after failed to allocate OCI error handle. OCI status: {0}.

Cause: Failed to create OCI environment by OCIEnvNslCreate() call.

Action: Review the OCI status code in the message and verify that the Oracle Database is properly configured.

OGG-08002: Could not allocate OCI error handle. OCI status: {0}.

Cause: Failed to allocate OCI error handle.

Action: Review the OCI status code in the message and verify that the Oracle Database is properly configured.

OGG-08003: OCI error handle was successfully allocated with the informational message. OCI return code: {0}, Description: {1}.

Cause: OCI error handle was allocated, but OCI returns an informational message.

Action: None

OGG-08004: OCI operation failed. OCI Error Code: {0}, Error Detail: {1}.

Cause: This is an internal OCI error.

Action: Contact Oracle Support.

OGG-08005: OCI SQL operation failed. OCI Error Code: {0}, Error Detail: {1}, SQL: {2}.

Cause: An error occurred in the OCI while executing the SQL.

Action: Resolve the problem based on the error that is shown in this message. If you cannot resolve the problem, contact Oracle Support.

OGG-08006: Failed to retrieve OCI error detail. OCI status: {0}.

Cause: This is an internal OCI error.

Action: Contact Oracle Support.

OGG-08007: Failed to allocate the server context. OCI status: {0}.

Cause: This is an internal OCI error.

Action: Contact Oracle Support.

OGG-08008: Failed to allocate the service context. OCI status: {0}.

Cause: This is an internal OCI error.

Action: Contact Oracle Support.

OGG-08009: Failed to attach the remote server {1}. OCI status: {0}.

Cause: Could not attached to the remote server.

Action: Check if Oracle database configuration and the remote server is accessible.

OGG-08010: Failed to attach the server. OCI status: {0}.

Cause: Could not attached to the server.

Action: Ensure that the Oracle Database configuration and the server is accessible.

OGG-08011: Failed to set the server context attribute. OCI status: {0}.

Cause: This is an internal OCI error.

Action: Contact Oracle Support.

OGG-08012: Failed to set the external name {1} attribute. OCI status: {0}.

Cause: This is an internal OCI error.

Action: Contact Oracle Support.

OGG-08013: Failed to set the internal name {1} attribute. OCI status: {0}.

Cause: This is an internal OCI error.

Action: Contact Oracle Support.

OGG-08014: Failed to allocate the session context. OCI status: {0}.

Cause: This is an internal OCI error.

-
- Action:** Contact Oracle Support.
- OGG-08015: Failed to set the user name {1} attribute. OCI status: {0}.**
- Cause:** This is an internal OCI error.
- Action:** Contact Oracle Support.
- OGG-08016: Failed to set the password attribute. OCI status: {0}.**
- Cause:** This is an internal OCI error.
- Action:** Contact Oracle Support.
- OGG-08017: Failed to set the module {1} attribute. OCI status: {0}.**
- Cause:** This is an internal OCI error.
- Action:** Contact Oracle Support.
- OGG-08018: Module attribute was not set to the OCI session.**
- Cause:** The OCI session module attribute was not set because the module name was not specified by the application.
- Action:** None
- OGG-08019: Failed to allocate describe handle. OCI status: {0}.**
- Cause:** This is an internal OCI error.
- Action:** Contact Oracle Support.
- OGG-08020: Failed to retrieve OCI error detail on OCI session begin failure.**
- Cause:** This is an internal OCI error.
- Action:** Contact Oracle Support.
- OGG-08021: Oracle password may be expired soon. Error code: {0}, Error Detail: {1}.**
- Cause:** Oracle database password for the user may be expired soon.
- Action:** This ignorable error may become critical in future when the password is expired. Update the password before it is expired.
- OGG-08022: Failed to begin the OCI session. Error code: {0}, Error Detail: {1}.**
- Cause:** Could not begin the OCI session.
- Action:** Check the error detail and fix the problem.
- OGG-08023: Failed to set the OCI session attribute. OCI status: {0}.**
- Cause:** This is an internal OCI error.
- Action:** Contact Oracle Support.
- OGG-08024: Failed to end the OCI session. OCI status: {0}.**
- Cause:** This is an internal OCI error.
- Action:** Contact Oracle Support.
- OGG-08025: Failed to detach from the server. OCI status: {0}.**
- Cause:** This is an internal OCI error.
- Action:** Contact Oracle Support.
- OGG-08026: Failed to free the service context. OCI status: {0}.**
- Cause:** This is an internal OCI error.
- Action:** Contact Oracle Support.

OGG-08027: Failed to free the session context. OCI status: {0}.

Cause: This is an internal OCI error.

Action: Contact Oracle Support.

OGG-08028: Failed to free the server context. OCI status: {0}.

Cause: This is an internal OCI error.

Action: Contact Oracle Support.

OGG-08029: Failed to free the describe handle. OCI status: {0}.

Cause: This is an internal OCI error.

Action: Contact Oracle Support.

OGG-08100: {0}

Cause: A generic information message was printed, check the message for more detail.

Action: None

OGG-08101: Invalid TARGETTEXTTRAIL name.

Cause: The name of the trail file specified is not correct.

Action: Verify the correct usage of enclosing quotes.

OGG-08102: Invalid file name.

Cause: The name of the trail file specified is not correct.

Action: Verify the correct specification of path and trail filename.

OGG-08103: file portion must be two characters.

Cause: The name of the trail file specified is larger than two characters.

Action: Specify a filename consisting of only two characters.

OGG-08104: EXTRACT group does not exist.

Cause: The specified extract group has not been added.

Action: Add the extract group first or use an existing one.

OGG-08105: EXTRACT is running, cannot be altered.

Cause: The extract process cannot be modified when running.

Action: Stop the extract process first.

OGG-08106: Trails cannot be used with an EXTRACT task.

Cause: The specified extract group is defined as a task process and do not use trail files.

Action: Alter the extract group or add a new one.

OGG-08107: TARGETTEXTTRAIL already exists.

Cause: The specified trail file was previously added.

Action: Specify a different trail file name.

OGG-08108: TARGETTEXTTRAIL does not exist.

Cause: The specified trail file has not been added.

Action: Add the specified trail file.

OGG-08109: Unable to get current checkpoint data {0}.

Cause: There was an error retrieving the checkpoint information for the specified process.

Action: Verify that options like RBA and SEQNO are correctly specified. Otherwise, contact Oracle Support.

OGG-08110: Login failed. {0}

Cause: There was an error while logging into the database.

Action: Check credentials. Refer the printed message for more details.

OGG-08111: {1} is not a valid value for argument {0}, expected value {2}.

Cause: Such value is not valid for reported argument.

Action: None

OGG-08200: {0} {1} does not exist.

Cause: The specified process does not exist.

Action: Check process type or process name.

OGG-08201: {0} {1} is RUNNING. Stop the process to execute this command.

Cause: The specified process is currently RUNNING. The command cannot be executed unless the process is STOPPED.

Action: Stop the process, and then issue the command.

OGG-08202: Could not delete file {0} ({1,number,0}, {2})

Cause: Moved from ggFragment.

Action: None

OGG-08203: Could not delete DB checkpoint for {0} {1} ({2})

Cause: Moved from ggFragment.

Action: None

OGG-08204: Deleted {0} {1}.

Cause: Moved from ggFragment.

Action: None

OGG-08209: ERROR: {0}.

Cause: Used by GGSCI to print into console, but by Admin Server to log elsewhere.

Action: None

OGG-08210: WARNING: {0}.

Cause: Used by GGSCI to print into console, but by Admin Server to log elsewhere.

Action: None

OGG-08211: {0}.

Cause: Cause is not known before hand, check error message for more detail.

Action: None

OGG-08216: ERROR: Cannot register or unregister EXTRACT {0} because no database login was provided. Use DBLOGIN to establish a connection.

Cause: Undefined

-
- Action: Undefined
- OGG-08217:** A root container connection is required when registering or unregistering Extract for a container database.
- Cause: Undefined
- Action: Undefined
- OGG-08218:** A root container connection to the downstream database is required when registering or unregistering Extract on a container database.
- Cause: Undefined
- Action: Undefined
- OGG-08219:** The user must have common user privileges on the downstream database when registering or unregistering Extract on a container database.
- Cause: Undefined
- Action: Undefined
- OGG-08220:** The user must have common user privileges when registering or unregistering Extract for a container database.
- Cause: Undefined
- Action: Undefined
- OGG-08221:** Cannot register or unregister EXTRACT {0} because of the following SQL error: {1}.
- Cause: Undefined
- Action: Undefined
- OGG-08222:** EXTRACT {0} must be registered with the database to perform this operation.
- Cause: Undefined
- Action: Undefined
- OGG-08223:** ERROR: One or more containers must be specified when registering Extract for a container database.
- Cause: Undefined
- Action: Undefined
- OGG-08224:** ERROR: CONTAINER option was specified though the database does not support containers.
- Cause: Undefined
- Action: Undefined
- OGG-08225:** Extract {0} successfully registered containers with database at SCN {1}.
- Cause: Undefined
- Action: Undefined
- OGG-08226:** Extract {0} successfully dropped containers from database.
- Cause: Undefined
- Action: Undefined
- OGG-08227:** Container list contains too many containers.
- Cause: Undefined

Action: Undefined

OGG-08228: Invalid container name {0}.

Cause: Undefined

Action: Undefined

OGG-08229: ERROR: Database container {0} is not registered.

Cause: Undefined

Action: Undefined

OGG-08230: ERROR: The global name of database container {0} could not be retrieved. Ensure the container is not in restricted mode.

Cause: Undefined

Action: Undefined

OGG-08231: ERROR: Drop container for EXTRACT {0} is already in progress; wait then try again.

Cause: Undefined

Action: Undefined

OGG-08232: ERROR: Database container {0} has already been registered.

Cause: Undefined

Action: Undefined

OGG-08233: ERROR: The global name of the database container {0} is in restricted mode.

Cause: Undefined

Action: Undefined

OGG-08234: ERROR: Database container {0} does not exist.

Cause: Undefined

Action: Undefined

OGG-08235: ERROR: Database container {0} is not open.

Cause: Undefined

Action: Undefined

OGG-08236: Wildcard is not allowed in container name {0}.

Cause: Undefined

Action: Undefined

OGG-08237: ERROR: This EXTRACT {0} cannot be used as a SHARE candidate. Use SHARE AUTOMATIC for finding a valid share candidate.

Cause: Undefined

Action: Undefined

OGG-08238: ERROR: This database does not have the required patch to support a SHARE clause. Remove the SHARE clause.

Cause: Undefined

Action: Undefined

OGG-08239: ERROR: Downstream Integrated Extract requires SCN clause in conjunction with the SHARE clause. See REGISTER with the SHARE clause in the Oracle GoldenGate documentation.

Cause: Undefined

Action: Undefined

OGG-08240: ERROR: The SHARE clause is not supported when registering Extract for a container database.

Cause: Undefined

Action: Undefined

OGG-08241: ERROR: This EXTRACT {0} is already registered with the database.

Cause: Undefined

Action: Undefined

OGG-08242: ERROR: The logmining server failed to locate dictionary for PDB {0}.

Cause: Undefined

Action: Undefined

OGG-08243: WARNING: EXTRACT {0} failed to archive the current logfile on the source database because of the following SQL error: {1}. See Extract user privileges in the Oracle GoldenGate documentation.

Cause: Undefined

Action: Undefined

OGG-08244: Root container {0} can not be specified in any REGISTER CONTAINER command because it is automatically registered.

Cause: Undefined

Action: Undefined

OGG-08245: Container {0} was specified more than once in the container list.

Cause: Undefined

Action: Undefined

OGG-08246: Wrong syntax.

Cause: Undefined

Action: Undefined

OGG-08247: Cannot unregister REPLICAT {0} because no database login was provided. Use DBLOGIN to establish a connection.

Cause: An UNREGISTER REPLICAT command was issued without first issuing a DBLOGIN command.

Action: Issue the DBLOGIN command, and then issue UNREGISTER REPLICAT again.

OGG-08250: {0} is not allowed for {1} {2}

Cause: A command was issued with an invalid option for the given mode.

Action: Use a valid option for the given mode.

OGG-08251: This command is being forced

Cause: A command was issued with the bang[!] option. The user will not be prompted for confirmation.

-
- Action:** None
- OGG-08252: ERROR: Wildcard not allowed for this command.**
- Cause:** Undefined
- Action:** Undefined
- OGG-08253: ERROR: Invalid command.**
- Cause:** Undefined
- Action:** Undefined
- OGG-08254: Could not delete file {0} ({1,number,0}, {2})**
- Cause:** Undefined
- Action:** Undefined
- OGG-08255: {0} {1} not currently running.**
- Cause:** A process that is not currently running was tried to be stopped.
- Action:** None
- OGG-08256: {0} {1} is initializing, please try the command later.**
- Cause:** A command for a process that is in an initialization stage was tried to be executed.
- Action:** Retry the command later.
- OGG-08257: Could not find port information for {0} {1}.**
- Cause:** Oracle GoldenGate could not find the listening port for the specified process.
- Action:** Contact Oracle Support.
- OGG-08258: Data source is required for {0} {1}.**
- Cause:** No data source was specified.
- Action:** Specify a data source.
- OGG-08259: Specified data source is not known.**
- Cause:** An unsupported data source was detected.
- Action:** Specify a supported data source.
- OGG-08260: Apply mode is required for {0} REPLICAT.**
- Cause:** No apply mode was specified.
- Action:** Specify an apply mode.
- OGG-08261: Specified apply mode is not known.**
- Cause:** An unsupported apply mode was detected.
- Action:** Specify a supported apply mode.
- OGG-08262: EXTFILE or EXTTRAIL required for ADD REPLICAT.**
- Cause:** No valid data source was specified.
- Action:** Specify either EXTTRAIL or EXTFILE.
- OGG-08263: Could not find port information for {0}.**
- Cause:** Oracle GoldenGate could not find the listening port for the specified process.

Action: Contact Oracle Support.

OGG-08264: Berkeley DB Repository Version Mismatch Error.

Cause: The Berkeley DB Version used by the repository does not match the dirbdb files.

Action: Delete and recreate the Datastore.

OGG-08500: {0}

Cause: A generic information message was printed, check the message for more detail.

Action: None

OGG-08501: Requested Operation on path {0} failed

Cause: The operation on the specified path failed.

Action: Check the syntax of the path specification in the service request.

OGG-08502: Path {0} not found

Cause: A path specified in the service request cannot be found in the system.

Action: Verify the path name in the service request.

OGG-08503: Path {0} already exists

Cause: The specified path name already exists in the system.

Action: Use a different path name or verify the path name in the service request.

OGG-08504: DistSrvr Shared Context is not initialized

Cause: The shared context for Distribution Server cannot be initialized.

Action: Contact Oracle Support.

OGG-08505: DistSrvr TPC {0} is not valid

Cause: The TPC thread for a distribution path cannot be started with invalid command context.

Action: Contact Oracle Support.

OGG-08506: DistSrvr failed to add path {0}

Cause: Distsrvr failed to add the specified path to the system.

Action: Contact Oracle Support.

OGG-10000: The column data type '{0}' is not supported Oracle GoldenGate.

Cause: The specified data type is not supported by Oracle GoldenGate.

Action: Contact the Oracle GoldenGate administrator or Oracle Support.

OGG-10001: The wildcarded catalog specification is missing from the MAP parameter in the Extract parameter file.

Cause: The wildcarded catalog specification is missing from the MAP parameter in the Extract parameter file.

Action: Specify a wildcarded catalog in the MAP parameter.

OGG-10002: The wildcarded schema specification is missing from the MAP parameter in the Extract parameter file.

Cause: The wildcarded schema specification is missing from the MAP parameter in the Extract parameter file.

Action: Specify a wildcarded schema in the MAP parameter.

OGG-10003: The environment variable INFORMIXSERVER is not set.

Cause: The INFORMIXSERVER environment variable must be set to specify the Informix server.

Action: Set the INFORMIXSERVER variable to the correct Informix server.

OGG-10004: Unable to start capture for columns {1} of table {0}. Verify whether ADD TRANDATA was issued.

Cause: Oracle GoldenGate is unable to capture transaction data for the specified table.

Action: Issue the ADD TRANDATA command for the specified table. If the problem persists, contact Oracle Support.

OGG-10005: Unable to activate CDC session with session id '{0}'.

Cause: The process could not start a CDC session.

Action: Check if the session id value is greater than 0. This indicates that the CDC session was not opened successfully. Contact Oracle Support.

OGG-10006: Unable to reposition CDC session with session id '{0}'.

Cause: The process could not reposition the CDC session.

Action: Check if the session ID value is greater than 0. This indicates that the CDC session was not opened successfully. Contact Oracle Support.

OGG-10007: Unable to allocate '{0}' bytes of heap memory.

Cause: The process could not allocate heap memory.

Action: Verify that the server has sufficient free RAM. If not, add more RAM and then restart the process.

OGG-10009: The CDC reader reached the end of the current CDC record.

Cause: The CDC reader reached the end of the current CDC record.

Action: None

OGG-10010: The CDC session timed out. Start CDC with no timeout value.

Cause: The CDC session being read by the CDC reader timed out.

Action: Check the timeout value used when starting the CDC session. The CDC session must be started with no timeout.

OGG-10011: Unable to read the transaction user name for user id '{0}'. Defaulting to username 'informix'.

Cause: The process is using the default user name of 'Informix' because it could not read the transaction user name for the specified user id.

Action: Check for possible corruption in the /etc/passwd entry for the respective user id.

OGG-10012: Unable to end capture session for the table {0}.

Cause: The process could not end its capture session for the specified table.

Action: None. This will be handled internally.

OGG-10013: Unable to close CDC session with session id '{0}'.

Cause: The process could not close its CDC session.

Action: None. This will be handled internally.

OGG-10014: Resolution column {2} is not part of column group used in conflict resolution {0}:{1}

Cause: The Resolution column is not part of the apply columns list.

Action: Modify the parameter file to include the resolution column in the apply column list.

OGG-10015: The specified decimal column has an unknown scale and cannot be processed. Table: {0} Column: {1}.

Cause: The specified decimal column has an unknown scale and cannot be processed.

Action: Recreate or alter the decimal column with a fixed value of scale.

OGG-10016: The specified decimal column has an unknown scale and cannot be processed. Table: {0} Column: {1}.

Cause: The specified decimal column has an unknown scale and cannot be processed.

Action: Recreate or alter the decimal column with a fixed value of scale.

OGG-10017: The interval column with a length {3} digits will be truncated to {4} digits. Table: {0} Column: {1} Data type: {2}

Cause: The interval column length is greater than the expected value.

Action: Recreate or alter the interval column to a smaller length. See the Oracle GoldenGate reference documentation for more details.

OGG-10018: Metadata property {0} is missing. The default value of {1} is used.

Cause: A value for the specified metadata property is missing.

Action: The upgrade of the Oracle GoldenGate software was not performed correctly. See the Oracle GoldenGate upgrade instructions and the release notes for more details.

OGG-10019: BOUNDED RECOVERY: BR not being used for restore. Extract will revert to normal recovery for this recovery and then turn on Bounded Recovery again.

Cause: Extract was unable to recover from the last Bounded Recovery checkpoint.

Action: Examine the Extract report file for messages related to the bounded recovery failure and then contact Oracle Support. Please report any failure of a bounded recovery to Oracle, even if Extract fully recovers.

OGG-10020: DDL statement succeeded with the following message: {0}.

Cause: The DDL statement succeeded. This message is informational and does not indicate a problem.

Action: None

OGG-10021: The locale of at least one source database does not match the locale of the other databases.

Cause: At least one of the source databases in this configuration has a locale that is different from the locale of the other databases in this configuration.

Action: Stop EXTRACT and set all of the source databases in this configuration to the same locale. To prevent loss of data, re-synchronize the affected data.

OGG-10022: Unable to start capture for {1} columns of table {0}. Verify whether at least a non-LOB column is in the table.

Cause: Oracle GoldenGate is unable to capture transaction data for the specified table. LOB columns are not supported as a key by Oracle GoldenGate.

Action: Include at least one non-LOB column in the table and then run ADD TRANDATA. For column types that are supported as a key, see the Oracle GoldenGate documentation for your database. If the problem persists, contact Oracle Support.

OGG-10023: Unable to activate a CDC session because none of the tables have at least a non-LOB column.

Cause: Oracle GoldenGate is unable to capture transaction data for the specified table. LOB columns are not supported as a key by Oracle GoldenGate.

Action: Include at least one non-LOB column in the table and then run ADD TRANDATA. For column types that are supported as a key, see the Oracle GoldenGate documentation for your database. If the problem persists, contact Oracle Support.

OGG-10024: CREATE/ALTER TABLE statements with encrypted columns that use IDENTIFIED clause are not supported. The DDL statement is ignored: {0}.

Cause: IDENTIFIED clause in encrypted columns is supported only in triggerless Extract.

Action: Remove IDENTIFIED clause.

OGG-10025: Oracle GoldenGate is incompatible with the current Informix Server version {0}. The supported Informix Server versions are {1}.

Cause: Oracle GoldenGate is incompatible with the current Informix Server version.

Action: Make sure you install a compatible Informix Server version.

OGG-10026: CDC error record received with {0}.

Cause: Oracle GoldenGate capture received a CDC record error and so cannot continue.

Action: Refer to the Informix documentation to resolve the error based on the error message, and then restart the capture process.

OGG-10027: An invisible column was encountered in table {0}. Oracle GoldenGate support for invisible columns requires Integrated Capture mode and trail format RELEASE 12.2 or later.

Cause: Invisible columns are supported in Integrated Capture mode only and require trail format RELEASE 12.2 or later.

Action: Exclude the table from the Extract parameter file by using the TABLEEXCLUDE parameter.

OGG-10028: The DELETE TRANDATA command failed for the specified table, error [{1}], operation [{0}]

Cause: The DELETE TRANDATA command failed.

Action: None. This will be handled internally.

OGG-10029: SHOWSYNTAX cannot be used with DBOPTIONS(SKIPTEMPLOB). DBOPTIONS(SKIPTEMPLOB) is disabled.

Cause: The parameter file contains the SHOWSYNTAX parameter, which is not compatible with the DBOPTIONS(SKIPTEMPLOB) parameter.

DBOPTIONS(SKIPTEMPLOB) is disabled.

Action: Remove SHOWSYNTAX to use DBOPTIONS(SKIPTEMPLOB) or remove the DBOPTIONS(SKIPTEMPLOB) parameter to use SHOWSYNTAX.

OGG-10030: The bulk load process encountered unsupported data type {1}-{0} in column {2}.

Cause: The specified data type is not supported by the BULKLOAD initial load method.

Action: Reconfigure Oracle GoldenGate to use a load method that supports the specified data type, or remove the table that contains this data type from the initial load configuration.

OGG-10031: Setting current Edition for DDL operation to [{0}].

Cause: The process is setting the session Edition for the DDL operation. This is an informational message.

Action: None

OGG-10032: Transaction {0} not found. The record at RBA {1} was ignored.

Cause: Extract ignored the record because it could not find the start of the transaction.

Action: Reposition Extract to start capture before the start of the transaction. For more information, see the START EXTRACT command.

OGG-10033: The catalog name is missing in the stored procedure {0}.

Cause: The catalog name is missing in the stored procedure.

Action: Provide the catalog name of the stored procedure to be executed and restart the process.

OGG-10034: The following database error has occurred. {0}.

Cause: A database error has occurred.

Action: Refer to the IBM Informix documentation to correct the database error.

OGG-10035: Error when parsing Informix Server version {0} .

Cause: Error when parsing Informix Server version.

Action: Refer to Oracle GoldenGate Installing and Configuring Oracle GoldenGate for Informix for supported Informix versions.

OGG-10036: The SYSCDC functions required for Oracle GoldenGate capture are not installed in the current database.

Cause: The SYSCDC functions required for Oracle GoldenGate capture are not installed in the current database.

Action: Check the ODBC Datasource configuration. The Database field should point to the CDC database. If the CDC database is not created, run the SQL script \$INFORMIXDIR/etc/syscdcv1.sql as 'informix' user and rerun the capture process.

OGG-10037: A capture process was unable to open a new CDC session due to the error {0}.

Cause: A capture process was unable to open a new CDC session.

Action: Refer to the IBM Informix documentation to correct the CDC error.

OGG-10038: The following generic error has occurred. {0}.

Cause: A generic error has occurred.

Action: Contact Oracle GoldenGate support with the following debug information: 1) Report files. 2) Parameter files. 3) Activity log files. 4) Snapshot of the top active processes on the server with maximum memory usage.

OGG-10039: Invalid input for VAM PARAMS {0} in the capture parameter file.

Cause: Invalid input for VAM PARAMS in the capture parameter file.

Action: Refer to Reference for Oracle GoldenGate for Windows and UNIX.

OGG-10040: Capture process cannot handle CDC record type {0}.

Cause: Capture process cannot handle CDC record type.

Action: Refer to Reference for Oracle GoldenGate for Windows and UNIX for the supported record types.

OGG-10041: CDC session is still valid and the error received {0} can be ignored.

Cause: Oracle GoldenGate capture received a CDC error code which is informational and could be ignored.

Action: None

OGG-10042: Use of your Informix server's current logical log file {0} exceeds the warning threshold of {1}%. Oracle GoldenGate capture is currently positioned at logical log file {2}, indicating a capture lag. Your Informix server may overwrite or archive log file {2} before the capture finishes processing it. Take action to prevent data loss.

Cause: The use of the current logical log file exceeds the warning threshold, but the Oracle GoldenGate capture is positioned at an older log file. This difference indicates a critical capture lag, because the current log could be overwritten or archived before the capture process is able to process it.

Action: If your Informix server overwrites the logical log that the Oracle GoldenGate capture process is reading, then the Oracle GoldenGate capture would fail. Review the following options to prevent the error: 1) If possible, add a new logical log file. 2) If possible, stop any operations on the Informix server, except read-only operations, until this warning message is no longer displayed.. 3) If possible, make the Informix instance read-only using the 'onmode -c block' command. The Informix instance can be unblocked with the 'onmode -c unblock' command. Refer to the Informix documentation before using these commands.

OGG-10100: Invalid read of parameter {0} from definitions file.

Cause: Problem reading from the static repository file for parameter definitions

Action: Contact Oracle Support.

OGG-10101: Incompatible parameter file version {0} for current running version {1}.

Cause: An incompatible version of the parameter repository file is being used.

Action: Contact Oracle Support.

OGG-10102: Error loading parameter with ID# {0} from the repository file.

Cause: Problem reading from the static repository file for parameter definitions

Action: Contact Oracle Support.

OGG-10103: ({0}) line {1}: Parsing error, value "{2}" is out of legal range ({3}) for [{4}].

Cause: Specified parameter value is out of the legal range for that value.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the valid range.

OGG-10104: ({0}) line {1}: Parsing error, value "{2}" is invalid.

Cause: Specified value is not valid.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the legal values.

OGG-10105: ({0}) line {1}: Parsing error, parameter [{2}] is expected to immediately precede [{3}].

Cause: Specified parameter needs to be specified immediately after another.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10106: ({0}) line {1}: Parsing error, parameter [{2}] is expected to precede [{3}].

Cause: Specified parameter needs to be specified after another.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10107: ({0}) line {1}: Parsing error, parameter [{2}] conflicts with parameter [{3}].

Cause: Specified parameter cannot be specified with another.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10108: ({0}) line {1}: Parsing error, parsing encountered an error.

Cause: Issue found while parsing the parameter files.

Action: Contact Oracle Support.

OGG-10109: ({0}) line {1}: Parsing error, parameter with name "{2}" is not defined.

Cause: Referring to a parameter name that has not been defined.

Action: Use the correct name or define the name prior to usage.

OGG-10110: An unexpected error occurred while parsing parameter information.

Cause: An unexpected internal error occurred.

Action: Contact Oracle Support.

OGG-10111: Error opening parameter definition file: {0}. errno: {1,number,0} - {2}

Cause: Problem opening from the static repository file for parameter definitions.

Action: Check the error code to solve the problem. Contact Oracle Support.

OGG-10112: {0} cannot be used with {1}

Cause: The specified parameters are incompatible or mutually exclusive.

Action: Remove one of the parameters, depending on the required Oracle GoldenGate configuration. For help, see the Oracle GoldenGate reference documentation.

OGG-10113: Error creating Parallel Replicat recovery table

Cause: There was an error when Parallel Replicat tried to create its recovery table.

Action: Fix any associated SQL errors and restart Replicat.

OGG-10114: Error reading Parallel Replicat recovery table: {0}

Cause: There was an error when Parallel Replicat tried to read from its recovery table.

Action: Fix the error specified in the message and restart Replicat.

OGG-10115: Error cleaning up Parallel Replicat recovery table

Cause: There was an error when Parallel Replicat tried to cleanup its recovery table.

Action: Fix any associated SQL errors and restart Replicat.

OGG-10116: Parallel Replicat is not supported on this platform

Cause: Parallel Replicat is not supported on this platform.

Action: Drop the Replicat and create a new one that is not a Parallel Replicat.

OGG-10117: Wildcard name {0} not supported for TARGETCATALOG parameter

Cause: The parameter file contains a TARGETCATALOG parameter specifying a wildcard name.

Action: Change the parameter to specify a non-wildcard name.

OGG-10118: Missing catalog name in TARGETCATALOG specification

Cause: The parameter file contains a TARGETCATALOG specification that does not specify a catalog name.

Action: Add a catalog name to the TARGETCATALOG specification.

OGG-10119: Invalid catalog name in TARGETCATALOG specification: {0}

Cause: The parameter file contains a TARGETCATALOG specification that specifies an invalid catalog name.

Action: Specify a valid catalog name for the TARGETCATALOG parameter.

OGG-10120: Use of a default catalog is not supported for Parallel Replicats when applying to multiple target catalogs without a common user login.

Cause: The parameter file contains a MAP with a target table name that does not specify a catalog name. This is not supported for a Parallel Replicat when it is applying to multiple target catalogs unless the login specified is for a common user.

Action: Add a TARGETCATALOG specification for the MAP statement, specify the catalog in the MAP statement, or change the USERID parameter to specify a common user.

OGG-10121: Value not specified for NUM_MAPPERS

Cause: The parameter file contains the NUM_MAPPERS parameter without a value specified.

Action: Specify a value for the NUM_MAPPERS parameter.

OGG-10122: Value not specified for NUM_APPLIERS

Cause: The parameter file contains the NUM_APPLIERS parameter without a value specified.

Action: Specify a value for the NUM_APPLIERS parameter.

OGG-10123: Parallelism greater than 1 is not supported in Standard Edition of Oracle.

Cause: Standard Edition of Oracle only supports a parallelism set to 1.

Action: Set parallelism to 1 or use the Enterprise Edition.

OGG-10124: {{0}} line {1}: Parsing error, value "{2}" is not one of the legal values {3} for [{4}].

Cause: A specified value does not match any value in the accepted list of valid strings.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10125: ({0}): Required parameter [{1}] is missing.

Cause: A parameter is required but has not been specified.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification and include the required parameter.

OGG-10126: The GLOBALS file is missing.

Cause: The GLOBALS file is missing.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification, and then include the required parameter.

OGG-10127: ({0}) line {1}: Parsing error, required parameter option [{2}] is missing.

Cause: A parameter option is required though has not been specified.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification, and then include the required parameter.

OGG-10128: Timestamp {0,date} {0,time} is not found within LRI range {1}.{2} - {3}.{4}.

Cause: The provided timestamp to the position in the LOG does not fall within the provided LRI range.

Action: Extract abends.

OGG-10129: LOOK UP END LRI can not be processed without a LOOK UP BEGIN LRI.

Cause: Only an LOOK UP END LRI was provided and LOOK UP BEGIN LRI is required.

Action: None

OGG-10130: Multiple logins were specified for the same catalog. Only the first will be used

Cause: The parameter file contains multiple logins that connect to the same catalog.

Action: Remove the unnecessary logins.

OGG-10131: A USERID parameter was specified after a MAP or TABLE parameter

Cause: The parameter file contains a USERID specification after a MAP or TABLE parameter. USERID must be specified before any MAP or TABLE parameters.

Action: Move the USERID specification so that it is before all MAP and TABLE parameters.

OGG-10132: No login was specified for catalog {0}

Cause: The parameter file contains a catalog for which it does not specify a login.

Action: Specify a login for the catalog using the USERID parameter.

OGG-10133: Default target catalog name {0} will be used for target table name {1} mapping.

Cause: A default target catalog name is specified with the TARGETCATALOG parameter and will be used when mapping the specified target table.

Action: None

OGG-10134: Ignoring TARGETCATALOG parameter {0} specified for MAP parameter '{1}' which contains a catalog specification.

Cause: The MAP clause already specifies a catalog name for the specified target table.

Action: Remove the TARGETCATALOG parameter or remove the catalog name from the target table name.

OGG-10135: Parallel Replicat requires a CHECKPOINTTABLE with a catalog name when applying to multiple target catalogs.

Cause: The parameter file specifies multiple target catalogs, but Replicat's CHECKPOINTTABLE does not have a catalog name specified.

Action: Modify the parameter file so that there is only one target catalog, or recreate the Replicat with a CHECKPOINTTABLE that has a catalog name.

OGG-10136: Replicat encountered an error and was unable to update the CHECKPOINTTABLE (Error: {0}).

Cause: Replicat encountered an error while updating the CHECKPOINTTABLE.

Action: Resolve the error shown in the message.

OGG-10137: Parallel Replicat does not support TARGET specifications containing wildcard catalogs.

Cause: The parameter file contains a MAP statement that specifies a wildcard catalog.

Action: Modify the parameter file so that there are no TARGET specifications containing wildcard catalogs.

OGG-10138: When Parallel Replicat is applying to multiple target catalogs, EVENTACTIONS options will only affect operations on the same target catalog.

Cause: The parameter file for a Parallel Replicat that is applying to multiple target catalogs contains an EVENTACTIONS specification.

Action: None

OGG-10139: Parameter file {0}: Validity check: {1}

Cause: The specified parameter file has been parsed and validated.

Action: If the validity check failed, check the syntax and values of the parameters.

OGG-10140: {{0}} line {1} column {2}: Parsing error, unexpected value "{3}".

Cause: Parameter parser encountered an unexpected value.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10141: {{0}} line {1} column {2}: Parsing error, value "{3}" syntax error.

Cause: Parameter parser encountered a syntax error.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10142: Attempt to load parameter [{0}] with ID# {1} failed. No parameter with that name matches the current running configuration.

Cause: Parameter parser could not load a specific parameter definition.

Action: Contact Oracle Support.

OGG-10143: ({0}) line {1}: Parameter [{2}] is unrecognized and will be ignored. No parameter definition with that name could be found.

Cause: Parameter parser could not find a specific parameter definition.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10144: ({0}) line {1}: Parameter [{2}] is not valid for this configuration.

Cause: This parameter is not recognized for this running process.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10145: ({0}) line {1}: Parsing error, parameter [{2}] is missing a required value.

Cause: This parameter is missing a required value.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10146: Invalid algorithm: {0} Use AES128 AES192 AES256 or BLOWFISH.

Cause: Invalid encryption algorithm specified.

Action: Resolve the error shown in the message.

OGG-10147: ({0}) line {1}: Parsing error, parameter [{2}] cannot be specified multiple times.

Cause: This parameter cannot be specified more than once.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10148: Original expression [{0}] -- Expanded expression [{1}]

Cause: Comparison of original parameter expression and expression after expansion.

Action: None

OGG-10149: ({0}) line {1}: Parsing error, option [{2}] for parameter [{3}] is missing a required value.

Cause: This option is missing a required value.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10150: ({0}) line {1}: Parsing error, option [{2}] for parameter [{3}] cannot be specified multiple times.

Cause: This option cannot be specified more than once.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10151: ({0}) line {1}: Parsing error, parameter [{3}] has unrecognized keyword or extra value "{2}".

Cause: Specified parameter value is not valid.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the legal values.

OGG-10152: ({0}) line {1}: Parsing error, option [{3}] for parameter [{4}] has unrecognized value "{2}".

Cause: Specified option value is not valid.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the legal values.

OGG-10153: SHELL contains DDL argument {0} is not allowed for DML record.

Cause: The specification of @DDL() as SHELL argument is not allowed for DML records, since the information is not available.

Action: Verify that @DDL() argument for the SHELL expression is removed in the TABLE specification.

OGG-10154: Schema level PREPARECSN set to mode {1} on schema {0}

Cause: Schema-level PREPARECSN command has been processed on the ADD SCHEMATRANSACTION command. Informational only.

Action: None

OGG-10155: Instantiation CSN filtering is enabled on table {0} at CSN {1}

Cause: Instantiation Filtering is enabled and the source table have an instantiation CSN set; replication for this table will begin after the instantiation CSN

Action: None

OGG-10156: Ignoring Instantiation CSN for table {0} as a FILTER clause is specified on mapping configuration for table {0}.

Cause: Instantiation Filtering is enabled and the source table have instantiation information set. However the table already has a FILTER on CSN in the REPLICAT mapping configuration. Manual FILTER rules have precedence, so instantiation CSN is ignored for this table.

Action: None

OGG-10157: Disabling Instantiation filtering as source database global name cannot be resolved.

Cause: Instantiation Filtering is enabled, but the Source Database Global Name cannot be resolved.

Action: Use the DBOPTIONS SOURCE_DB_NAME REPLICAT option or a 12.2 trail format with source metadata information enabled.

OGG-10158: ({0}) line {1}: Parsing error, [{2}] is required to be specified on line {3}.

Cause: Specified parameter is required to be on a specific line.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10159: ({0}) line {1}: Parsing error, parameter [{2}] is missing a required unit value.

Cause: This parameter is missing a required unit value.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10160: ({0}) line {1}: Parsing error, option [{2}] for parameter [{3}] is missing a required unit value.

Cause: This option is missing a required unit value.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10161: Logical end of file reached on {0} at RBA {1,number,0}.

Cause: A logical end of file was reached while reading the trail file.

Action: None

OGG-10162: End of file reached on {0}.

Cause: The end of file was reached while reading the trail file.

Action: None

OGG-10163: An unexpected number of bytes were read from the last block in {0}.

Expected {1}, read {2}.

Cause: While reading from the trail file, the number of bytes read was different than expected.

Action: None

OGG-10164: Trail file {0} has a logical file size.

Cause: The file size of the trail file is a logical file size. This file size can be lower than the physical file size.

Action: None

OGG-10165: The trail file {0} has found to be corrupt after RBA {1,number,0}.

Cause: The trail file has found to be corrupt. The file has been logically shortened in order to be used.

Action: None

OGG-10166: Source database name for instantiation filtering is set both in the Replicat parameter file and in the trail metadata for Table {0}. Value from the parameter file will take precedence: {1}

Cause: Source database name is set both in the Replicat configuration and in the trail file metadata.

Action: Remove the DBOPTIONS SOURCE_DB_NAME from the Replicat configuration, unless you want to override the Source Database Global Name.

OGG-10167: ({0}) line {1}: Parsing error, one of the following parameters or options [{2}] is expected to immediately precede [{3}].

Cause: Parameter or option needs to be specified immediately after one of the parameters or options in the shown list.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10168: ({0}) line {1}: Parsing error, one of the following parameters or options [{2}] is expected to precede [{3}].

Cause: Parameter or option needs to be specified after one of the parameters or options in the shown list.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10169: ({0}): Parsing error, one of the following parameters or options [{1}] is required to be used with [{2}].

Cause: One of the required parameters in the displayed list is missing.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10170: ({0}): Parsing error, one of the following parameters [{1}] is required to be used in this file.

Cause: One of the required parameters in the displayed list is missing.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10171: {{0}} line {1}: Parsing error, parameters or options [{2}] conflict with parameter [{3}].

Cause: Specified parameters cannot be specified with one another.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10172: {{0}} line {1}: Parsing error, [{2}] requires at least one option to be used.

Cause: Specified parameter requires at least one option to be used.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10173: {0}

Cause: A parameter parsing error was detected, but can be ignored.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10174: {{0}} line {1}: Fatal error in parser [{2}].

Cause: A fatal error was found while reading the parameter file.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-10175: {{0}} line {1}: Parsing error, [{2}] is obsolete.

Cause: The specified parameter is obsolete and not valid for the current release of Oracle GoldenGate.

Action: Remove the parameter from the parameter file. Consult the current release notes and documentation for any newer parameters or enhanced functionality that is related to this parameter and for any required migration steps, or contact Oracle Support.

OGG-10176: {{0}} line {1}: Parsing error, [{2}] is deprecated.

Cause: The specified parameter is deprecated and not valid for the current release of Oracle GoldenGate.

Action: Remove the parameter from the parameter file. Consult the current release notes and documentation for any newer parameters or enhanced functionality that is related to this parameter and for any required migration steps, or contact Oracle Support.

OGG-10200: PLSQL operation found [{0}]

Cause: A PLSQL operation was processed. Informational only.

Action: None

OGG-10300: Could not capture the transaction record for table:{0} due to CDC error {1}. Verify whether ADD TRANDATA was issued.

Cause: Oracle GoldenGate is unable to capture transaction data for the specified table.

Action: Issue the ADD TRANDATA command for the specified table.

OGG-10301: The table {0} having column {1} with datatype {2}:{3} is not supported by Oracle GoldenGate.

Cause: The specified column data type is not supported by Oracle GoldenGate.

Action: Refer to the Informix Oracle GoldenGate documentation for the datatypes supported by Oracle GoldenGate. Remove the table from Extract list or alter table for data capture.

OGG-10302: The column {1} in table {0} having datatype {2}:{3} is ignored by CDC capture.

Cause: The specified column is ignored for CDC capture by Oracle GoldenGate.

Action: Refer to the Informix Oracle GoldenGate documentation for the columns ignored for CDC data capture. Verify whether this column is added into fetchcol list in extract param file. Otherwise, data will not be captured for this column.

OGG-10303: Extract VAM PARAMS {0} specified is invalid and unsupported.

Cause: The parameter specified in extract parameter file is invalid.

Action: Refer to the Oracle GoldenGate documentation for the list parameters supported in the extract parameter file. Recify or remove the parameter, if it is not supported.

OGG-10351: Generic error {0} noticed. Error description - {1}.

Cause: Undefined

Action: Undefined

OGG-10402: System-period and Bitemporal tables are not supported with 'INSERTALLRECORDS'

Cause: Replicat parameter file contains either of the temporal table parameters(SUPPRESSTEMPORALUPDATES/NOSUPPRESSTEMPORALUPDATES) along with INSERTALLRECORDS.

Action: Use only one of the parameters at a time.

OGG-10403: Column {1} of Table {0} is an auto generated column and is ignored.

Cause: The column is one among SYS_START, SYS_END and TS_ID columns. These columns are auto filled by DB manager.

Action: Mark such columns as Unused and ignore them.

OGG-10451: DDL operation included [{0}], optype [{1}], objtype [{2}], catalog [{5}], objowner [{3}], objname [{4}]

Cause: The specified DDL operation was included in DDL replication because it meets the criteria of an INCLUDE clause.

Action: None

OGG-10452: DDL operation excluded [{0}], optype [{1}], objtype [{2}], catalog [{5}], objowner [{3}], objname [{4}]

Cause: The specified DDL operation was excluded from DDL replication because it meets the criteria of an EXCLUDE clause or was not included in an INCLUDE clause.

Action: None

OGG-10453: DDL operation excluded by user exit [{0}], optype [{1}], objtype [{2}], catalog [{5}], objowner [{3}], objname [{4}]

Cause: The specified user exit excluded the specified DDL. This is informational only.

Action: None

OGG-10454: DDL operation ignored due to EMI [{0}], optype [{1}], objtype [{2}], catalog [{5}], objowner [{3}], objname [{4}]

Cause: The specified DDL operation was ignored according to the rule specified in EVENTACTIONS.

Action: None required.

OGG-10455: DDL RENAME found, old owner [{0}] object [{1}], new owner [{2}] object [{3}], catalog [{4}]

Cause: A RENAME operation was processed. Informational only.

Action: None

OGG-10456: Metadata not invalidated for [{1},{2}] because of {0} [{3}], catalog [{4}]

Cause: Usually this message is for DDL operations that do not affect metadata, such as TRUNCATE TABLE or ANALYZE TABLE. This message explains why Extract did not clear the metadata (remove it from the DDL cache). It is beneficial not to clear metadata if possible: retaining it improves performance because the process does not need to re-read the metadata for the next DML operation.

Action: None

OGG-10457: DDL RENAME found, old owner [{0}] object [{1}], new owner [{2}] object [{3}], RENAME converted to ALTER TABLE, new operation [{4}], catalog [{5}]

Cause: A RENAME was converted to the equivalent ALTER TABLE RENAME. The reason is that RENAME does not support the use of a schema name, but a schema name is required in case the DDL statement on the target maps to a different schema.

Action: None

OGG-10458: Metadata not invalidated for [{1},{2}] because of {0}, catalog [{3}]

Cause: Usually this message is for DDL operations that do not affect metadata, such as TRUNCATE TABLE or ANALYZE TABLE. This message explains why Extract did not clear the metadata (remove it from the DDL cache). It is beneficial not to clear metadata if possible: retaining it improves performance because the process does not need to re-read the metadata for the next DML operation.

Action: None

OGG-10459: Invalid heartbeat object being added.

Cause: The heartbeat object being added is invalid.

Action: Contact Oracle Support.

OGG-10460: Failed to process operation on tombstone table {0}.

Cause: Extract process failed to process dml LCR on tombstone tables.

Action: Contact Oracle GoldenGate Support.

OGG-10461: Failed to retrieve tombstone timestamp value for table {0}.

Cause: Extract process failed to retrieve tombstone timestamp information in order to generate acdr token.

Action: Contact Oracle GoldenGate Support.

OGG-10462: Schema {0} have {1} prepared tables for instantiation

Cause: Schema contains tables which are prepared for instantiation CSN export. By default, all tables should be prepared.

Action: None

OGG-10463: Instantiation CSN has been set successfully.

Cause: GGSCI command 'SET_INSTANTIATION_CSN' was successfully executed.

Action: None

OGG-10464: Instantiation CSN has been cleared successfully.

Cause: GGSCI command 'CLEAR_INSTANTIATION_CSN' was successfully executed.

Action: None

OGG-10465: Found invalid length of {0} on inline securefile LOB

Cause: Extract detects an invalid length on inline securefile lob data from redo data. Fetching will be used instead to get correct version of lob data.

Action: None

OGG-10466: Found invalid flag of {0} on inline securefile LOB

Cause: Extract detects an invalid flag on inline securefile lob data from redo data. Fetching will be used instead to get correct version of lob data.

Action: None

OGG-10501: Heartbeat object {0} already exists.

Cause: The heartbeat object already exists.

Action: If you want a new object, delete all existing heartbeat objects and recreate them.

OGG-10502: Heartbeat object {0} does not exist.

Cause: The heartbeat object does not exist.

Action: None

OGG-10503: Heartbeat object {0} creation failed.

Cause: The heartbeat object creation failed.

Action: None

OGG-10505: Job schedule [{0}] does not exist.

Cause: Job schedule updating heartbeat tables does not exist.

Action: Use the command 'ADD HEARTBEATABLE' to add the job scheduler.

OGG-10506: Job schedule [{0}] dropped.

Cause: Job schedule for updating the heartbeat tables was dropped. Informational only.

Action: None

OGG-10507: Job [{0}] does not exist.

Cause: Job updating for heartbeat tables does not exist.

Action: Use the command 'ADD HEARTBEATABLE' to add the job.

OGG-10508: Job [{0}] dropped.

Cause: Job for updating the heartbeat tables was dropped. Informational only.

Action: None

OGG-10509: Job schedule [{0}] does not exist.

Cause: Job schedule for purging heartbeat tables does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the job schedule.

OGG-10510: Job schedule [{0}] dropped.

Cause: Job schedule for purging heartbeat tables dropped. Informational only.

Action: None

OGG-10511: Job [{0}] does not exist.

Cause: Job for purging heartbeat tables does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the job.

OGG-10512: Job [{0}] dropped.

Cause: Job for purging the heartbeat tables was dropped. Informational only.

Action: None

OGG-10513: The job scheduler database({0}) does not exist. Configure database {0} and add Oracle GoldenGate replication user with correct role to create and run the heart beat job.

Cause: SYBMGMTDB is not configured to run the heart beat job.

Action: Configure SYBMGMTDB and add Oracle GoldenGate replication user with appropriate role to continue. Follow the SAP/Sybase provided instructions to configure the job scheduler database.

OGG-10515: To create and run heart beat jobs, user({2}) must be created or added in job scheduler database({0}) and it must have ({1}) roles enabled.

Cause: The user is either not added/created in SYBMGMTDB database or user has not proper roles(replication_role, js_admin_role, js_user_role) enabled.

Action: Add/create a Oracle GoldenGate replication user in SYBMGMTDB database and add appropriate role to continue. Follow the SAP/Sybase provided instructions to configure the job scheduler database.

OGG-10520: Table or view ({0}) exists in the database({1}).

Cause: Table or view already exists in the current database.

Action: Execute the DELETE HEARTBEATTABLE command to drop the table.

OGG-10521: Procedure ({0}) exist in the database({1}) .

Cause: Procedure already exist in the current database.

Action: Execute the DELETE HEARTBEATTABLE command to drop the procedure.

OGG-10522: Scheduled job ({0}) already exist.

Cause: The scheduled job exists.

Action: Execute the DELETE HEARTBEATTABLE command to drop the schedule job.

OGG-10523: Cannot alter heartbeat scheduler job, hearttable(s) ({0},{1},{2}) do not exist in the database.

Cause: The heartbeat table and scheduler job does not exist.

Action: Use the ADD HEARTBEATTABLE command to add the heartbeat table and to schedule the job.

OGG-10524: User({2}) must be added in jobs scheduler database({0}) and it must have ({1}) roles enabled to create and run heart beat jobs.

Cause: The user is not the valid user in SYBMGMTDB database to run the job scheduler.

Action: Add an Oracle GoldenGate replication user in the SYBMGMTDB database, and then add an appropriate role to continue. User can follow the SAP/Sybase provided instructions to configure the job scheduler database.

OGG-10525: getSchemaVersion - Unable to obtain schema version for {0},{1}

Cause: The catalog and schema are not valid.

Action: Correct the catalog and schema for the heartbeat table.

OGG-10526: User {0} must have sa_role to create table(s)for user ({1}).

Cause: The user logged in does not have sa_role to create tables for other users of the database.

Action: Add the sa_role to the logged in user.

OGG-10532: Logging of supplemental log data is disabled for table {0}.

Cause: Logging of supplemental log data is disabled. Information only.

Action: None

OGG-10533: Unable to open {0}, err {1} {2}

Cause: A file error was returned when attempting to open/create a required file.

Action: Evaluate the file system error and correct.

OGG-10534: Error {0}, {1} writing to {2}

Cause: A file error was returned when attempting to write to a required file.

Action: Evaluate the file system error and correct.

OGG-10535: Successfully created heartbeat rate table [{0}].

Cause: Heartbeat rate table has been created. Informational only.

Action: None

OGG-10536: Successfully populated heartbeat rate table.

Cause: Heartbeat seed table populated. Informational only.

Action: None

OGG-10538: Unable to stop the heartbeat process.

Cause: Unknown error; Contact Oracle support.

Action: None

OGG-10540: Unable to start the heartbeat process.

Cause: Unknown error; Contact Oracle support.

Action: None

OGG-10541: Manager restarted the heartbeat process.

Cause: Unknown error; If the error persists, contact Oracle support.

Action: None

OGG-10544: The heartbeat process was unable to open \$RECEIVE.

Cause: Unknown error; Contact Oracle support.

Action: None

OGG-10545: The heartbeat process was unable to obtain required rate values.

Cause: Unknown error; Delete and re-add heartbeat configuration using the heartbeattable commands from GGSCI.

Action: None

OGG-10548: Schema.table is required for heartbeattable.

Cause: The heartbeat_table is required in GLOBALS with schema and table name.

Action: Edit the GLOBALS file and specify a fully qualified heartbeat table name (with schema) for the heartbeat_table parameter.

OGG-10549: The current catalog login of {0} is not the same as the configured heartbeat catalog of {1}.

Cause: When using two part names the dblogin (ODBCDSN) will determine the default catalog, the heartbeat table was already set up using another catalog.

Action: Log into the configured catalog.

OGG-10552: Unsupport option is FETCH; No row found. tablename:{0}

Cause: An attempt to fetch the unsupported LCR though the row was not found.

Action: Set UNSUPPORTED_OPTION to IGNORE if the unsupported LCR is irrelevant.

OGG-10553: Unsupport option is FETCH; Cannot fetch by rowid. tablename:{0}

Cause: Try to fetch the unsupported LCR. Either the fetch option disallow fetching by rowid or no valid rowid is received.

Action: Using rowid to fetch or set UNSUPPORTED_OPTION to IGNORE if the unsupported LCR is irrelevant.

OGG-12000: General server error.

Cause: There was some internal problem that prevented proper processing of the request.

Action: Contact Oracle GoldenGate Support.

OGG-12001: Poorly formed service request payload.

Cause: The service request contained a payload what was incorrectly formatted or contained invalid values.

Action: Verify the service request payload specified by the client is correct. See the Reference for Oracle GoldenGate for Windows and UNIX for valid header and attribute names and values.

OGG-12002: Poorly formed request URI.

Cause: The service request contained a URI what was incorrectly formatted or contained invalid values.

Action: Verify the service request URI specified by the client is correct. See the Reference for Oracle GoldenGate for Windows and UNIX for valid header and attribute names and values.

OGG-12003: Poorly formed HTTP request context.

Cause: The service request contained a header or attribute what was incorrectly formatted or contained invalid values.

Action: Verify the service request headers and attributes specified by the client is correct. See the Reference for Oracle GoldenGate for Windows and UNIX for valid header and attribute names and values.

OGG-12004: Service request handler error.

Cause: The service request handler returned an error.

Action: Review the message details and verify the service request was properly and completely formed. See the Reference for Oracle GoldenGate for Windows and UNIX for valid header and attribute names and values.

OGG-12005: No configuration file found at '{0}'. New configuration file created with default settings.

Cause: Named configuration file was not found. A new configuration file with default settings was created.

Action: Verify the configuration specifications in the newly created configuration file is correct for the current environment. See the Reference for Oracle GoldenGate for Windows and UNIX for configuration details.

OGG-12006: Loaded configuration file from '{0}'.

Cause: Report the location from which the configuration was loaded.

Action: None. Informational only.

OGG-12007: Unable to access the configuration file at '{0}'.

Cause: Unable to access the configuration at the specified location.

Action: Verify that the location is accessible and that the file permissions allows read access. See the Reference for Oracle GoldenGate for Windows and UNIX for configuration details.

OGG-12008: Unable to parse the configuration at line {1,number,0} column {2,number,0} in file '{0}'.

Cause: Unable to parse the configuration information in the file at the specified location.

Action: Verify that the configuration information formats are valid. See the Reference for Oracle GoldenGate for Windows and UNIX for configuration details.

OGG-12009: Unable to completely read the configuration file at '{0}'.

Cause: Unable to access the configuration at the specified location.

Action: Verify that the location is accessible and that the file permissions allows read access. See the Reference for Oracle GoldenGate for Windows and UNIX for configuration details.

OGG-12010: The requested service completed successfully but did not return a result.

Cause: Service request was not required to produce results to be returned to the client.

Action: None

OGG-12100: The HTTP Verb '{0}' is invalid for '{0} {1}'.

Cause: The verb provided in the HTTP URI is invalid for this service request.

Action: Verify the HTTP URI specifies a valid verb. See the Reference for Oracle GoldenGate for Windows and UNIX for valid Accept media types.

OGG-12101: Poorly formed HTTP request context for '{0} {1}'.

Cause: The HTTP request context contained a header or attribute what was incorrectly formatted or contained invalid values.

Action: Verify the HTTP context specified by the client is correct. See the Reference for Oracle GoldenGate for Windows and UNIX for valid header and attribute names and values.

OGG-12103: Poorly formed request URI for '{0} {1}'.

Cause: The request URI (Uniform Resource Identifier) incorrectly formatted or references an invalid resource path.

Action: Verify the URI specified by the client is correct. See the Reference for Oracle GoldenGate for Windows and UNIX for valid URI resource paths.

OGG-12104: The HTTP Accept media-type '{0}' is deprecated for '{1} {2}'.

Cause: The media-type value provided in the HTTP Accept header is deprecated.

Action: Update the request to specify an actively support media type. This media type may be treated as an error in future releases. See the Reference for Oracle GoldenGate for Windows and UNIX for valid Accept media types.

OGG-12105: The HTTP Accept value '{0}' is invalid for '{1} {2}'.

Cause: The media-type value provided in the HTTP Accept header is invalid for this service requests. The HTTP Accept header in the service request specifies what response format the client is able to accept.

Action: Verify the HTTP Accept value specified by the client is correct. See the Reference for Oracle GoldenGate for Windows and UNIX for valid Accept media types.

OGG-12106: The request URI template '{3}' placeholder name '{0}' conflicts with the request context names for '{1} {2}'.

Cause: The URI template defines names for dynamic placeholders that conflict with names in the request context.

Action: Resolve Internal.

OGG-12150: Poorly formed HTTP response context for '{0} {1}'.

Cause: The HTTP response context contained a header or attribute what was incorrectly formatted or contained invalid values.

Action: Verify the HTTP context specified by the client is correct. See the Reference for Oracle GoldenGate for Windows and UNIX for valid header and attribute names and values.

OGG-12200: Poorly formed request payload for '{0} {1}'.

Cause: The service request payload was incorrectly formatted or was expressed in an invalid or unsupported format.

Action: Verify the URI specified by the client is correct. See the Reference for Oracle GoldenGate for Windows and UNIX for valid payload formats and structure.

OGG-12201: The request payload for '{0} {1}' defines a root level array. Root level arrays are not currently supported

Cause: The root of the payload document is defined as an array, which is not currently supported.

Action: Change the payload root document from an array to named values or objects. Reference for Oracle GoldenGate for Windows and UNIX for valid service request formats and values.

OGG-12202: The request payload for '{0} {1}' is not defined as an object.

Cause: The root of the JSON payload document is not defined as an object.

Action: Define the JSON payload root document as an object. Reference for Oracle GoldenGate for Windows and UNIX for valid service request formats and values.

OGG-12203: Required JSON element '{0}' is missing

Cause: The JSON item does not validate against the provided JSON schema.

Action: Correct the JSON so that it conforms to the JSON schema.

OGG-12204: JSON element '{0}' is the incorrect type

Cause: The JSON item does not validate against the provided JSON schema.

Action: Correct the JSON so that it conforms to the JSON schema.

OGG-12205: JSON object '{0}' has additional items which are not allowed

Cause: The JSON item does not validate against the provided JSON schema.

Action: Correct the JSON so that it conforms to the JSON schema.

OGG-12206: JSON element '{0}' does not match the expected '{1}' format

Cause: The JSON item does not validate against the provided JSON schema.

Action: Correct the JSON so that it conforms to the JSON schema.

OGG-12207: JSON element '{0}' is missing the required '{1}' property

Cause: The JSON item does not validate against the provided JSON schema.

Action: Correct the JSON so that it conforms to the JSON schema.

OGG-12208: JSON element '{0}' must contain the enum value '{1}'

Cause: The JSON item does not validate against the provided JSON schema.

Action: Correct the JSON so that it conforms to the JSON schema.

OGG-12209: JSON element '{0}' must be one of the enum values

Cause: The JSON item does not validate against the provided JSON schema.

Action: Correct the JSON so that it conforms to the JSON schema.

OGG-12210: JSON element '{0}' dependencies are not met

Cause: The JSON item does not validate against the provided JSON schema.

Action: Correct the JSON so that it conforms to the JSON schema.

OGG-12211: JSON element '{0}' has an invalid additional property, '{1}'

Cause: The JSON item does not validate against the provided JSON schema.

Action: Correct the JSON so that it conforms to the JSON schema.

OGG-12212: JSON element '{0}' matches disallowed schema

Cause: The JSON item does not validate against the provided JSON schema.

Action: Correct the JSON so that it conforms to the JSON schema.

OGG-12213: JSON element '{0}' value does not match the required pattern

Cause: The JSON item does not validate against the provided JSON schema.

Action: Correct the JSON so that it conforms to the JSON schema.

OGG-12214: JSON element '{0}' does not match any schemas

Cause: The JSON item does not validate against the provided JSON schema.

-
- Action:** Correct the JSON so that it conforms to the JSON schema.
- OGG-12215: JSON element '{0}' matches more than one schema**
- Cause:** The JSON item does not validate against the provided JSON schema.
- Action:** Correct the JSON so that it conforms to the JSON schema.
- OGG-12216: JSON element '{0}' value is not an even multiple of {1}**
- Cause:** The JSON item does not validate against the provided JSON schema.
- Action:** Correct the JSON so that it conforms to the JSON schema.
- OGG-12217: JSON object '{0}' exceeds the maximum number of allowed properties of {1,number,0}**
- Cause:** The JSON item does not validate against the provided JSON schema.
- Action:** Correct the JSON so that it conforms to the JSON schema.
- OGG-12218: JSON object '{0}' has less than the minimum number of required properties of {1,number,0}**
- Cause:** The JSON item does not validate against the provided JSON schema.
- Action:** Correct the JSON so that it conforms to the JSON schema.
- OGG-12219: JSON array '{0}' exceeds the maximum number of allowed items of {1,number,0}**
- Cause:** The JSON item does not validate against the provided JSON schema.
- Action:** Correct the JSON so that it conforms to the JSON schema.
- OGG-12220: JSON object '{0}' has less than the minimum number of required properties of {1,number,0}**
- Cause:** The JSON item does not validate against the provided JSON schema.
- Action:** Correct the JSON so that it conforms to the JSON schema.
- OGG-12221: JSON string '{0}' exceeds the maximum allowable length of {1,number,0}**
- Cause:** The JSON item does not validate against the provided JSON schema.
- Action:** Correct the JSON so that it conforms to the JSON schema.
- OGG-12222: JSON string '{0}' does not meet the minimum required length of {1,number,0}**
- Cause:** The JSON item does not validate against the provided JSON schema.
- Action:** Correct the JSON so that it conforms to the JSON schema.
- OGG-12223: JSON element '{0}' is greater than the maximum allowed value of {1,number,0}**
- Cause:** The JSON item does not validate against the provided JSON schema.
- Action:** Correct the JSON so that it conforms to the JSON schema.
- OGG-12224: JSON element '{0}' is less than the minimum allowed value of {1,number,0}**
- Cause:** The JSON item does not validate against the provided JSON schema.
- Action:** Correct the JSON so that it conforms to the JSON schema.
- OGG-12250: Poorly formed response from service handler for '{0} {1}'.**

Cause: The response returned by the service handler registered for this request was poorly formed.

Action: Contact Oracle GoldenGate Support.

OGG-12251: The response payload for '{0} {1}' is empty.

Cause: The service request handler returned an empty response.

Action: Contact Oracle GoldenGate Support.

OGG-12300: Service request handler error.

Cause: The service request handler returned an error. There was some problem processing the request.

Action: Verify that the service request from the client is correct. See the Reference for Oracle GoldenGate for Windows and UNIX for valid header and attribute names and values.

OGG-12301: No service handler registered for '{0} {1}'.

Cause: No service handler is registered for the service request URI.

Action: Contact Oracle GoldenGate Support.

OGG-12302: The handler method registered for '{0} {1}' caused an exception: {2} - {3}.

Cause: The handler method caused an exception. See error messages for details.

Action: Contact Oracle GoldenGate Support.

OGG-12303: Node '{0}' at position {1,number,0} in JsonPath '{2}' is missing.

Cause: Unable to locate the specified node in the JSON document instance specified by the JsonPath.

Action: Verify that the both the JSON document and the JsonPath specification is correct. See the Reference for Oracle GoldenGate for Windows and UNIX for valid JsonPath specifications.

OGG-12304: There is no JsonPath specified. The JsonPath is empty.

Cause: The JsonPath has not been initialize or the specification is empty.

Action: Verify the JsonPath specification describes a valid path. See the Reference for Oracle GoldenGate for Windows and UNIX for valid JsonPath specifications.

OGG-12305: Four or more part table name is not supported.

Cause: Attempting to assign a table name that is four part or more, which is not supported.

Action: Report the error, and then restart the process.

OGG-12400: Failed to prepare fetch on table {0} due to key column {1} being dropped. Use KEYCOLUMNS.

Cause: Unique row data could not be guaranteed to be fetched from the table because one or more key column has been dropped.

Action: Define a key or specify unique columns with the KEYCOLUMNS clause of the TABLE statement.

OGG-12401: OCI error ({0,number,0}-{1}) when validating table {2}, SQL: {3}.

Cause: Validation of the table existance failed.

Action: Contact Oracle Support

OGG-12410: The wrl configuration is missing .

Cause: The Wallet Resource Locator (wrl) was not found in the security configuration.

Action: Verify that the 'wrl' value in the security configuration is present and refers to a valid Oracle Wallet location. See 4 Installing and Configuring Oracle GoldenGate for Oracle Databases.

OGG-12411: The configured communications role '{0}' is not recognized.

Cause: The value configured for the communications role does not describe a recognized role.

Action: Verify that the 'role' value in the security configuration refers to a valid communications role. See 4 Installing and Configuring Oracle GoldenGate for Oracle Databases.

OGG-12412: The communications role configuration is missing.

Cause: The communications role was not found in the security configuration.

Action: Verify that the 'role' value in the security configuration is present and refers to a valid communications role. See 4 Installing and Configuring Oracle GoldenGate for Oracle Databases.

OGG-12413: The communications protocol configuration is missing.

Cause: The communications security protocol was not found in the security configuration.

Action: Verify that the 'protocol' value in the security configuration is present and refers to a valid communications protocol. See 4 Installing and Configuring Oracle GoldenGate for Oracle Databases.

OGG-12414: The communications protocol configuration '{0}' is not recognized.

Cause: The communications security protocol was not recognized.

Action: Verify that the 'protocol' value in the security configuration refers to a valid communications security protocol. See 4 Installing and Configuring Oracle GoldenGate for Oracle Databases.

OGG-12415: Expected communications security configuration id '{1}' but received '{0}'.

Cause: The communications security configuration id did not match the expected value.

Action: Verify that the 'configId' value in the security configuration matches the expected value. See 4 Installing and Configuring Oracle GoldenGate for Oracle Databases.

OGG-12416: Communications security configuration id is missing.

Cause: The communications security configuration id was not found in the security configuration.

Action: Verify that the 'configId' value in the security configuration is present and matches the expected value. See 4 Installing and Configuring Oracle GoldenGate for Oracle Databases.

OGG-13000: With procedural replication, only single output trail is allowed.

Cause: Multiple output trails are not supported if procedural replication is enabled.

Action: Make sure only one trail file is specified in the Extract parameter file.

OGG-14000: Successfully created heartbeat table [{0}].

Cause: Heartbeat table has been created. Information only.

Action: None

OGG-14001: Successfully created heartbeat seed table [{0}].

Cause: Heartbeat seed table has been created. Information only.

Action: None

OGG-14002: Implicit column function heartbeat routing has incorrect format.

Cause: Column function used to parse heartbeat routing is incorrect.

Action: Contact Oracle Support.

OGG-14003: Successfully populated heartbeat seed table with [{0}].

Cause: Heartbeat seed table populated. Information only.

Action: None

OGG-14004: Successfully created procedure [{0}] to update the heartbeat tables.

Cause: Update procedure for heartbeat tables created. Information only.

Action: None

OGG-14005: Successfully created scheduler job [{0}] to update the heartbeat tables.

Cause: Scheduler job for updating heartbeat tables created. Information only.

Action: None

OGG-14006: Heartbeat seed table [{0}] does not exist.

Cause: Heartbeat seed table does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the heartbeat tables.

OGG-14007: Heartbeat seed table [{0}] dropped.

Cause: Heartbeat seed table dropped. Information only.

Action: None

OGG-14008: Heartbeat table [{0}] does not exist.

Cause: Heartbeat table does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the heartbeat tables.

OGG-14009: Heartbeat table [{0}] dropped.

Cause: Heartbeat table dropped. Information only.

Action: None

OGG-14010: Heartbeat history table [{0}] does not exist.

Cause: Heartbeat history table does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the heartbeat tables.

OGG-14011: Heartbeat history table [{0}] dropped.

Cause: Heartbeat history table dropped. Information only.

Action: None

OGG-14012: Procedure [{0}] does not exist.

Cause: Update procedure for heartbeat tables does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the heartbeat tables update procedure.

OGG-14013: Procedure [{0}] dropped.

Cause: Update procedure for heartbeat tables dropped. Information only.

Action: None

OGG-14014: Scheduler job [{0}] does not exist.

Cause: Scheduler job for updating heartbeat tables does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the scheduler job.

OGG-14015: Scheduler job [{0}] dropped.

Cause: Scheduler job for updating heartbeat tables dropped. Information only.

Action: None

OGG-14016: Successfully created heartbeat history table [{0}].

Cause: Heartbeat history table has been created. Information only.

Action: None

OGG-14017: Successfully created procedure [{0}] to purge the heartbeat history table.

Cause: Purge procedure for heartbeat history table created. Information only.

Action: None

OGG-14018: Successfully created scheduler job [{0}] to purge the heartbeat history table.

Cause: Scheduler job for purging heartbeat history table created. Information only.

Action: None

OGG-14019: Procedure [{0}] does not exist.

Cause: Purge procedure for heartbeat history table does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the heartbeat history purge procedure.

OGG-14020: Procedure [{0}] dropped.

Cause: Purge procedure for heartbeat history table dropped. Information only.

Action: None

OGG-14021: Scheduler job [{0}] does not exist.

Cause: Scheduler job for purging heartbeat history table does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the scheduler job.

OGG-14022: Scheduler job [{0}] dropped.

Cause: Scheduler job for purging heartbeat history table dropped. Information only.

Action: None

OGG-14023: Successfully created heartbeat lag view [{0}].

Cause: Heartbeat Lag View has been created. Information only.

Action: None

OGG-14024: Successfully created heartbeat lag history view [{0}].

Cause: Heartbeat Lag History View has been created. Information only.

Action: None

OGG-14025: Heartbeat lag view [{0}] does not exist.

Cause: Heartbeat Lag view does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the heartbeat lag view.

OGG-14026: Heartbeat lag view [{0}] dropped.

Cause: Heartbeat lag view dropped. Information only.

Action: None

OGG-14027: Heartbeat lag history view [{0}] does not exist.

Cause: Heartbeat Lag history view does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the heartbeat lag history view.

OGG-14028: Heartbeat lag history view [{0}] dropped.

Cause: Heartbeat lag history view dropped. Information only.

Action: None

OGG-14029: Frequency of scheduler job [{0}] modified.

Cause: Frequency of scheduler job for updating heartbeat tables has been modified. Information only.

Action: None

OGG-14030: Frequency of purge scheduler job [{0}] modified.

Cause: Frequency of scheduler job for purging heartbeat history table has been modified. Information only.

Action: None

OGG-14031: Retention time of heartbeats modified.

Cause: Retention time of heartbeat records in history table has been modified. Information only.

Action: None

OGG-14032: Successfully added supplemental logging for heartbeat seed table [{0}].

Cause: Added supplemental logging for heartbeat seed table for all columns. Information only.

Action: None

OGG-14033: Successfully added supplemental logging for heartbeat table [{0}].

Cause: Added supplemental logging for heartbeat table for all columns. Information only.

Action: None

OGG-14034: Heartbeat entries with [{0}] deleted.

Cause: Heartbeat entries with given process name deleted from heartbeat table. Information only.

Action: None

OGG-14035: The heartbeat table name cannot contain a wildcard.

Cause: The heartbeat table name specified with HEARTBEATTABLE in the GLOBALS file cannot contain a wildcard.

Action: Specify a non-wildcarded name.

OGG-14036: Schema is required for heartbeattable : {0}.

Cause: Either GGSHEMA should be mentioned in GLOBALS or a schema name must be specified for the heartbeat table in the HEARTBEATTABLE parameter in GLOBALS. Neither available.

Action: Edit the GLOBALS file and specify a fully qualified heartbeattable name (with schema) for the HEARBEATTABLE parameter, or mention GGSHEMA in GLOBALS.

OGG-14037: Catalog login required to add heartbeat tables.

Cause: Catalog login required to add heartbeat tables.

Action: Login to a pdb and retry the command.

OGG-14038: Catalog login required to delete heartbeat tables.

Cause: Catalog login required to delete heartbeat tables.

Action: Login to a pdb and retry the command.

OGG-14039: Catalog login required to alter heartbeattable.

Cause: Catalog login required to alter heartbeattable.

Action: Login to a pdb and retry the command.

OGG-14040: Catalog login required to delete heartbeatentry.

Cause: Catalog login required for command 'delete heartbeatentry'.

Action: Login to a pdb and retry the command.

OGG-14041: [{0}] exists already.

Cause: Heartbeat object exists already.

Action: Rename object and retry the command again.

OGG-14042: Catalog name not supported for heartbeat table [{0}].

Cause: Catalog name not supported for heartbeat table

Action: Use a two part name or a table name along with GGSHEMA.

OGG-14043: Invalid ADD HEARTBEATTABLE specification {0}.

Cause: Invalid ADD HEARTBEATTABLE specification.

Action: None

OGG-14044: Invalid ALTER HEARTBEATTABLE specification {0}.

Cause: Invalid ALTER HEARTBEATTABLE specification.

Action: None

OGG-14045: Invalid DELETE HEARTBEATENTRY specification {0}.

Cause: Invalid DELETE HEARTBEATENTRY specification.

Action: None

OGG-14046: The ADD HEARTBEATTABLE option: {0} is ignored.

Cause: The ADD option of the HEARTBEATTABLE parameter is not valid or supported.

Action: Do not specify the ADD option for the HEARTBEATTABLE parameter.

OGG-14047: Job {0} is currently running. Retry command.

Cause: An attempt was made to drop a job that is currently running.

Action: Reissue the command.

OGG-14048: Invalid DELETE HEARTBEATTABLE specification {0}.

Cause: Invalid DELETE HEARTBEATTABLE specification.

Action: None

OGG-14050: Invalid frequency for scheduler job {0}.

Cause: Invalid input for repeat interval.

Action: Specify a valid frequency.

OGG-14051: Invalid retention time for scheduler job {0}.

Cause: Invalid input for retention time.

Action: Allowed values for retention time are 1 to 999.

OGG-14052: No Heartbeat entries with [{0}], none deleted.

Cause: Heartbeat entries with given process name did not exist and were not deleted from heartbeat table. Information only.

Action: None

OGG-14053: Invalid heartbeat record encountered.

Cause: An invalid heartbeat record was encountered. The trail file may be corrupt. The invalid record will be skipped.

Action: Verify that the trail file is not corrupt.

OGG-14054: Lag from heartbeat table requires DBLOGIN.

Cause: Detailed lag report from heartbeat table requires DBLOGIN.

Action: Log into the database to view detailed lag report.

OGG-14055: Successfully created {0} [{1}].

Cause: Heartbeat object has been created. Informational only.

Action: None

OGG-14056: Successfully deleted {0} [{1}].

Cause: Heartbeat object has been deleted. Informational only.

Action: None

OGG-14057: Could not retrieve heartbeat table frequency interval.

Cause: There was an internal problem retrieving the heartbeat table frequency interval. For instance, the dblogin session login does not have enough privileges to access the relevant database table information, or an internal error occurred.

Action: Execute dblogin command using a login with more privileges or contact Oracle Support.

OGG-14058: Could not retrieve heartbeat table purge frequency interval.

Cause: There was an internal problem retrieving the heartbeat table purge frequency interval. For instance, the dblogin session login does not have enough privileges to access the relevant database table information, or an internal error occurred.

Action: Execute dblogin command using a login with more privileges or contact Oracle Support.

OGG-14059: Could not retrieve heartbeat table retention time interval.

Cause: There was an internal problem retrieving the heartbeat table retention time interval. For instance, the dblogin session login does not have enough privileges to access the relevant database table information, or an internal error occurred.

Action: Execute dblogin command using a login with more privileges or contact Oracle Support.

OGG-14060: Invalid INFO HEARTBEATTABLE specification {0}.

Cause: Invalid INFO HEARTBEATTABLE specification.

Action: None

OGG-14061: Datastore uses LMDB environment files.

Cause: The datastore uses LMDB files for its environment resources.

Action: No action required.

OGG-14062: Dblogin required before exttrail in parameter file to enable heartbeats.

Cause: Heartbeats are disabled if DBLOGIN is not present before the first EXTTRAIL in the parameter file.

Action: Reorder the DBLOGIN details to appear above the first EXTTRAIL in the extract parameter file.

OGG-14063: DDL operations on Heartbeat objects are ignored.

Cause: DDLs on heartbeat objects such as seed, heartbeat and history table, lag view and historical lag view, update and purge procedure are ignored.

Action: None

OGG-14064: Could not delete heartbeat table entries for group name {0}: {{1}}

Cause: Undefined

Action: Undefined

OGG-14065: Heartbeat table [{0}] does not exist in [{1}].

Cause: Heartbeat table does not exist.

Action: Use the command 'ADD HEARTBEATTABLE' to add the heartbeat tables.

OGG-14067: Heartbeat entries with [{0}] deleted from [{1}].

Cause: Heartbeat entries with the given process name were deleted from heartbeat table. Information only.

Action: None

OGG-14500: {{0}} line {1}: Parsing error, parameter [{2}]: {3}

Cause: Parameter specification is invalid.

Action: Refer to the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-14501: Parameter file {0} has unicode byte order mark and CHARSET parameter

Cause: Parameter file is unicode with byte order mark and CHARSET parameter is used.

Action: Remove CHARSET parameter or save using the encoding specified by CHARSET parameter.

OGG-14502: ({0}) line {1}: Unexpected value "{2}", first parameter must be one of: REPLICAT, SPECIALRUN, GENLOADFILES.

Cause: A fatal error was found while reading the parameter file.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-14503: ({0}) line {1}: Unexpected value "{2}", first parameter must be one of: EXTRACT, SOURCEISTABLE, SOURCEISFILE.

Cause: A fatal error was found while reading the parameter file.

Action: See the Reference for Oracle GoldenGate for Windows and UNIX for the proper specification.

OGG-14504: Unable to locate the parameter definitions file.

Cause: Problem locating the static repository file for parameter definitions.

Action: Contact Oracle Support.

OGG-14600: Specifying EXCLUDETAG + in conjunction with EXCLUDETAG NULL is not allowed.

Cause: EXCLUDETAG + and EXCLUDETAG NULL are mutually exclusive.

Action: Verify the EXCLUDETAG option. See the Oracle GoldenGate reference documentation.

OGG-14601: Specifying EXCLUDETAG NULL in conjunction with any other EXCLUDETAG option is not allowed.

Cause: Specifying EXCLUDETAG NULL in conjunction with any other EXCLUDETAG option is not allowed.

Action: Verify the EXCLUDETAG option. See the Oracle GoldenGate reference documentation.

OGG-14602: Specifying EXCLUDETAG + in conjunction with other EXCLUDETAG options.

Cause: EXCLUDETAG + was specified in conjunction with other EXCLUDETAG options.

Action: Verify the EXCLUDETAG option. See the Oracle GoldenGate reference documentation.

OGG-14603: The following generic error has occurred. {0}.

Cause: A generic error has occurred.

Action: Contact Oracle GoldenGate support with the following debug information: 1) Report files. 2) Parameter files. 3) Activity log files. 4) Snapshot of the top active processes on the server with maximum memory usage.

OGG-15000: TRANLOGOPTIONS BUFSIZE should be in the range [{0} - {1}].

Cause: BUFSIZE specified in the parameter file is not within the permissible range.

Action: Specify a number in the specified range for BUFSIZE

OGG-15050: Error loading Java VM runtime library: ({0,number,0} {1})

Cause: The Java VM runtime library can not be found or loaded.

Action: Make sure Java VM runtime library (i.e.:libjvm.so/jvm.dll) is in the search path (LD_LIBRARY_PATH or PATH). In Linux, libjvm.so is located under \$(JAVA_HOME)/lib/amd64/server/libjvm.so. In Windows, jvm.dll is can be found under %JAVA_HOME%\bin\server.

OGG-15051: Java or JNI exception: {0}

Cause: The Java or JNI subsystem returned an exception. Possible causes include an incorrect Java version, lack of memory or disk space to complete the operation, or other internal Java-related errors.

Action: Look for additional information related to this error in the JVM log or dump files, or on the console. The specific resolution is dependent on the type of failure.

OGG-15052: Using Java class path: {0}

Cause: The classpath tells Java where to look in the filesystem for files that contain the classes.

Action: None

OGG-25050: The HANDLEDLFAILOVER option of the TRANLOGOPTIONS parameter cannot be specified when the NOUSERID parameter is specified and there is no Active Data Guard standby database.

Cause: The HANDLEDLFAILOVER option of the TRANLOGOPTIONS parameter cannot be specified when the NOUSERID parameter is specified and there is no Active Data Guard standby database.

Action: Contact Oracle Support.