HTTP请求报文由哪几部分组成?

请求报文是由请求方法、请求URI、协议版本、一些可选的请求首部字段和内容实体构成。

下面是在network截取的一个请求:

General:

Request URL: https://www.baidu.com/home/xman/data/tipspluslist?

 $indextype=manht \&_req_seqid=0x8466e3ac0001093f \& asyn=1 \& t=1552961901647 \& sid=28628_1427_21083_28720_28558_28607_28585_28607_28607_28585_28607_28585_28607_28585_28607_28585_28607_28585_28607_28585_28607_28585_28607_28595_28607_28585_28607_28595_28607_28595_28607_28595_28607_28595_28607_28595_28607_28595_28607_28595_28607_28595_28607_28595_28607_28595_28607_28595_28607_28595_28607_28607_28595_28607_28595_28607_28595_28607_28595_28607_28595-28607_28607_28595-28607_28595-28607_28595-28607_28595-28607_28595-28607_28595-28607_28595-28607-286$

Request Method: GET Status Code: 200 OK

Remote Address: 112.34.112.40:443 Referrer Policy: unsafe-url

Response headers

Cache-Control: private Connection: keep-alive Content-Encoding: gzip Content-Length: 78

Content-Type: text/html; charset=utf-8
Date: Tue, 19 Mar 2019 02:18:22 GMT
Expires: Tue, 19 Mar 2019 02:18:22 GMT

Server: BWS/1.0

Tracecode: 11023798470767062538031910

Vary: Accept-Encoding

Request headers

Accept: text/plain, */*; q=0.01 Accept-Encoding: gzip, deflate, br Accept-Language: zh-CN, zh;q=0.9, en;q=0.8

Cache-Control: no-cache Connection: keep-alive

Cookie: BIDUPSID=18640EC56A0710DC537203C0A89DDE20;

Host: www.baidu.com Pragma: no-cache

Referer: https://www.baidu.com/

User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10 13 1) AppleWebKit/537.36 (KHTML, like Gecko)

Chrome/72.0.3626.121 Safari/537.36 X-Requested-With: XMLHttpRequest

Query String Parameters

indextype: manht

_req_seqid: 0x8466e3ac0001093f

asyn: 1

t: 1552961901647

sid: 28628_1427_21083_28720_28558_28607_28585_26350_28603_28625_28703