

Department of Mathematics and Computer Science

Heidelberg University

Master thesis

in Scientific Computing

submitted by

Yu Xiang

born in November 10, 1989

2022

Numerical methods for optimal control problems, with a case study in state constrained rocket car

This master thesis has been carried out by Yu Xiang

at the

Heidelberg University

under the supervision of

Professor Dr. Ekaterina A. Kostina

Contents

1	Introduction	4
2	Numerical methods	5
2.1	Multiple shooting	7
2.1.1	Mutiple shooting method for OCP	9
2.2	KKT condition	11
2.3	quasi Newton method	13
2.3.1	Newton method	13
2.3.2	quasi Newton method	15
2.4	Sequential quadrative programming	16
3	Optimal control under uncertainty	17
3.1	Classical approach	18
3.2	Training approach	19
4	Numerical solution	21
4.1	Introduction to the rocket car case	21
4.2	Theoretical solution to rocket car case	23
4.3	Apply classical (minmax) approach	23
4.4	Apply training (maxmin) approach	25
4.5	Comparison numerical result of classical and training approach	25
5	Conclusion	26
I	Appendix	28
A	Lists	29
	Bibliography	29

1 Introduction

Many real-life problems can be modeled as an optimal control problem (OCP), for example, launching a rocket to the moon with minimum fuel expenditure as the objective, or maximizing the profit from the factory production, with constraints in resources available and uncertain market demand. This paper focus on solving optimal control problems with numerical approaches, particularly with multiple shooting and (quasi) Newton style method.

In general, optimal control deals with the problem of finding the control over the state for a dynamic system over a period of time such that an objective function is optimized. Generally, an optimal control problem can be formulized as follows:

$$\begin{aligned}
 & \min_{x(t), u(t)} F(x(t), u(t)) \\
 & s.t. \quad \dot{x}(t) = f(x(t), u(t)) \\
 & \quad x(t) \in \Omega \\
 & \quad u(t) \in \mathbb{U} \\
 & \quad t \in [t_0, t_f]
 \end{aligned} \tag{1.1}$$

Here t is the independent variable (generally speaking, time), usually using t_0 and t_f representing the initial and terminal time respectively. $x(t)$ is the state variables, and $u(t)$ is the control variables, $F(\cdot)$ is the objective function, also called the cost function. $\dot{x}(t) = f(x(t), u(t))$ represents the underlying dynamic system, $x(t) \in \Omega$ and $u(t) \in \mathbb{U}$ represents the constraints for which the state variables $x(t)$ and control variable $u(t)$ must satisfy respectively. Sometimes, the constraints are expressed as functions of $x(t)$ and $u(t)$ together.

Generally speaking, there are three basis approaches to address optimal control problems (a) dynamic programming (b) indirect, and (c) direct approaches. (ref [Moritz Diehl \[2005\]](#)). This paper on hand, focus on the direct approaches, which are one of the most widespread and successfully used techniques. Direct approaches transform the original infinite optimal control problem into a finite dimensional nonlinear programming problem (NLP). This NLP is then solved by variants of state-of-the-art numerical optimization methods, and the approach is therefore often sketched as “first discretize, then optimize.”

Mutiple shooting method can be used in the "first discretize" part of the direct approaches. The main idea is to divide the whole interval $t \in [t_0, t_f]$ into multiple subintervals, and introduce initial guess for each subinterval, solve the problem in each subinterval with the initial guess, and impose additional matching conditions at the boundary of each subinterval to form a solution of the whole interval. In each subinterval, with mutiple shooting methods applied, the system of differential equations will be turned into a system of ordinary non-linear algebraic equations. Therefore, the original OCP is transferred into piecewise nonlinear programming problem (NLP). We can use the Karush–Kuhn–Tucker (KKT) approach to combine the constraints and the original objective function into a new Lagrange function.

Minimizing this new Lagrangian function becomes an optimization problem without any constraints, and its optimum value can be determined via derivative methods. To

solve any unconstrained NLP, we can work within an iterative sequential quadratic programming (SQP), or Newton style framework. Newton style methods are second-order derivatives iterative optimization algorithm and generally, but not always, converges faster than first-order derivatives method (e.g. gradient descent). The Newton method needs to calculate the second order derivatives, i.e. the Hessian matrix and its inverse in each iteration, which is very expensive to compute. Quasi Newton methods employs an approximation to the original Hessian matrix and takes an efficient way to update the approximation matrix. Therefore, quasi Newton method is generally faster than Newton method.

Besides the control variables u and state variables x , some optimal control problems may have uncertain parameters whose value are priori unknown, and the optimal objective value depends on the parameter value. This kind of problem is called the parameterized optimal control problems and is of the form

$$\begin{aligned}
& \min_{x(t), u(t)} F(x(t; p), u(t)) \\
& s.t. \quad \dot{x}(t; p) = f(x(t; p), u(t)) \\
& \quad x(t; p) \in \Omega \\
& \quad u(t) \in \mathbb{U} \\
& \quad p \in \mathbb{P} \\
& \quad x = x(\cdot, p^*) \text{ if } p = p^* \\
& \quad t \in [t_0, t_f]
\end{aligned} \tag{1.2}$$

where p^* is a fixed value in the feasible uncertainty set \mathbb{P} , where the parameter p can take value from. Equation 1.2 derives from the equation 1.1, with the parameter p added.

Parameterized optimal control problems are very difficult to solve due to the uncertainty in the parameter p . Since the parameter p can take different values, so does the corresponding objective function $F(\cdot)$. Then, the solution of 1.2, i.e. $\min F(\cdot; p)$ can be regarded as a function of parameter p . One p value corresponds to one solution, if such solution can be found. Since p is priori unknown, in real life problems, it usually makes sense to solve the parameterized optimal control problems in a conservative way, so that a robust solution can be obtained. For example, in the paper [Schlöder \[2022\]](#), when modelling the therapy design of Cerebral Palsy (CP) for the patient, a conservative solution is a desirable result. Two different ways of solving the parameterized optimal control problem will be discussed in details, i.e. the classical approach and the training approach. Both are in the form of a bilevel optimization problem, i.e. an optimization problem in which another optimization problem enters the constraints. Details about these two approaches will be discussed in Chapter 3. The approaches discussed above will be demonstrated with a case study in state constrained rocket car, with the description of the case, and its numerical result given in Chapter 4.

The structure of this paper is as follows. Following this introduction Chapter 1, in next Chapter 2, we focus on explaining in details how to solve optimal control problems with direct approaches using multiple shooting and quasi Newton method. In Chapter 3, we discuss the approaches for solving parameterized optimal control problem, i.e. the classic approach and the training approach. In Chapter 4, we give the description of our case study, i.e. the state constrained rocket car case, and compare the numerical solutions of the classical approach and training approach. In the final Chapter 5, we conclude the analysis with the numerical results.

2 Numerical methods

Optimal control theory deals with systems that can be controlled, i.e whose evolution can be influenced by some external agent. In this paper we only consider the case that the control variable u is a function of only time t , and not function of the state variable x . This type of problem is known as open loop, or controllability problem. The system dynamics of the optimal control problem can be generalized as a system of differential equations

$$\dot{x}(t) = f(x(t), u(t)) \quad (2.1)$$

We would like to have such dynamic system to run in an optimal way, subject to the constraints that are applicable in real life. This indicates that the problem will have a clearly defined objective function, with the dynamic system and the constraints expressed in explicit formula. With the example of launching the rocket to the moon, the objective function can be minimizing the fuel used or minimize the time horizon of the system, subject to the constraints, e.g. gravity, fuel efficiency, speed limitation etc. The trajectories (dynamic system), as well as some of the constraints, are expressed in differential equations.

In Chapter 1, equation 1.1 gives a high-level formulation of an optimal control problem. Here we augment equation 1.1 with mathematical details, with the objective function and the constraints expressed in explicit formulas. For real-life problems, the optimal control formulation can typically be generalized in the following form

$$\min_{x(t), u(t)} F(x(t), u(t)) = \int_{t_0}^{t_f} L(x(t), u(t)) dt + E(x(t_f)) \quad (2.2a)$$

$$s.t. \quad \dot{x}(t) = f(x(t), u(t)), \quad (\text{system dynamics}) \quad (2.2b)$$

$$g(x(t), u(t)) = 0, \quad (\text{path equality constraints}) \quad (2.2c)$$

$$h(x(t), u(t)) \leq 0, \quad (\text{path inequality constraints}) \quad (2.2d)$$

$$x(t_0) = x_0, \quad (\text{initial value}) \quad (2.2e)$$

$$r(x(t_f)) \leq 0, \quad (\text{terminal constraints}) \quad (2.2f)$$

$$x^{lower} \leq x(t) \leq x^{upper} \quad (2.2g)$$

$$u^{lower} \leq u(t) \leq u^{upper} \quad (2.2h)$$

$$t \in [t_0, t_f] \quad (2.2i)$$

Here $L(\cdot)$ and $E(\cdot)$ are called the running cost and end cost, with their sum $F(\cdot)$ the cost/objective function. $g(\cdot)$, $h(\cdot)$ and $r(\cdot)$ are functions representing equality constraints, inequality constraints, and terminal constraints respectively. The time horizon is $[t_0, t_f]$, with the initial value known as x_0 .

Depending on nature of the underlying optimal control problems, the mathematical expression can take a modified form of equation 2.2. For certain problems, some of the constraints defined in equation 2.2 may not play a role, while for other problems,

additional constraints may be needed or existing constraints need to be modified. Nevertheless, Equation 2.2 gives us a general mathematical formulation of the typical optimal control problems in real life, and we do not go further discussion with possible (minor) modification to Equation 2.2.

Various methods exist for solving optimal control problems. The paper [Moritz Diehl \[2005\]](#) summarizes three general approaches to address optimal control problems: (a) dynamic programming, (b) indirect, and (c) direct approaches. Dynamic programming uses the principle of optimality to compute recursively a feedback control for all time t and all x_0 . Indirect methods use the necessary conditions of optimality of the infinite problem to derive a boundary value problem (BVP) in ordinary differential equations.

This paper on hand, focus on the direct approaches, which are one of the most widespread and successfully used techniques. Direct approaches transform the original infinite optimal control problem into a finite dimensional nonlinear programming problem (NLP). This NLP is then solved by variants of state-of-the-art numerical optimization methods, and this approach is therefore often sketched as “first discretize, then optimize.” One of the most important advantages of direct approaches is that they can easily treat inequality constraints, e.g. the inequality path constraints as in equation 2.2d. This is because structural changes in the active constraints during the optimization procedure are treated by well developed NLP methods, which can deal with inequality constraints and active set changes. (ref [Moritz Diehl \[2005\]](#)).

In the text that follows, we first explain the multiple shooting method, which can be used in the “first discretize” part of the direct approaches. Afterwards, we explain the KKT conditions, which can easily treat equality and inequality constraints of the optimal control problems. With the background knowledge of multiple shooting methods and KKT conditions, we continue to explain the Newton-style method and sequential quadratic programming. These methods, together, can serve as the “then optimize” part of the direct approaches, and solve the optimal control problems of the form as in equation 1.1, or in more mathematical details as in equation 2.2.

2.1 Multiple shooting

Multiple shooting method was initially introduced to solve boundary value problem (BVP) in differential equation scope [David Morrison \[1962\]](#). This method, with some adjustment, therefore, is well suited for solving optimal control problem with constraints in differential equations. In the text that follows, we first explain how the multiple shooting can be used for solving BVP in the differential equation scope. After that, we explain how multiple shooting can be applied to a general optimal control problem, and particularly how it can be used for solving optimal control problem of the form as in equation 2.2.

To illustrate the concept of shooting method to solve boundary value problem (BVP), we use the following example.

$$\dot{x} = x(t), t_0 \leq t \leq t_f$$

The analytical solution of above equation is

$$x(t) = x(t_0)e^{t-t_0}$$

where e is the exponential number. Then $x(t_0) = x_0$ will be determined such that it will satisfy $x(t_f) = b$ for a given value b . Therefore, the equation $x(t_f) - b = 0$ or

$x_0 e^{t-t_0} - b = 0$ is obtained. This derivation is called as shooting method. Generally, the shooting method can be summarized as follow

shooting method

- Step 1, choose an initial value $x_0 = x(t_0)$
- Step 2, form a solution of the differential equation from t_0 to t_f
- Step 3, evaluate the error at the boundary, if $x(t_f) - b = 0$, then stop, otherwise continue to Step 4
- Step 4, update the guess for x_0 based on some updating schema, go to Step 2

In multiple shooting method, the "shoot" interval is partitioned into some short subintervals. We define a general differential equation with boundary value of the following form

$$\begin{aligned} \dot{y} &= f(t, y) \\ y(t_f) &= y_f \end{aligned} \quad (2.3)$$

where y denotes the differential variables, $t \in [t_0, t_f]$, y_f is the boundary value at t_f . With multiple shooting method, one chooses a suitable grid of multiple shooting nodes $\tau_j \in [t_0, t_f]$, where $t_0 = \tau_0 < \tau_1 < \dots < \tau_m = t_f$, i.e. m subintervals covering the whole interval. At the beginning of each subinterval, $[\tau_k, \tau_{k+1}]$, $k = 0, 1, \dots, m-1$, we have the initial guess of the starting value \hat{y}_k . Then in each subinterval, we have the initial value problem of the following form:

$$\begin{aligned} \dot{y} &= f(t, y, p), t \in [\tau_k, \tau_{k+1}], k = 0, 1, \dots, m-1 \\ y(\tau_k) &= \hat{y}_k, k = 0, 1, \dots, m-1 \end{aligned} \quad (2.4)$$

In each subinterval, we introduce the new unknown parameter \hat{y}_k , we solve an initial value problem and will get a solution $y(t), t \in [\tau_k, \tau_{k+1}]$. The piecewise solution is not necessary continuous and also not necessarily satisfy the boundary condition $y(t_f) = y_f$. The continuity has to be enforced by additional matching conditions at each subinterval boundary, i.e.

$$\begin{aligned} y(\tau_{k+1}; \hat{y}_k) &= \hat{y}_{k+1}, k = 0, 1, \dots, m-1 \\ \hat{y}_m(i.e. \hat{y}_{\tau_m} = \hat{y}_{t_f}) &= y_f \end{aligned} \quad (2.5)$$

The procedure of multiple shooting method can then be summarized as

Mutiple shooting method

- Step 1, choose multiple shooting nodes $t_0 = \tau_0 < \tau_1 < \dots < \tau_m = t_f$
- Step 2, choose initial guess for $\hat{y}_k, k = 0, 1, \dots, m-1$
- Step 3, form solutions of the differential equation in each subinterval $[\tau_k, \tau_{k+1}], k = 0, 1, \dots, m-1$
- Step 4, evaluate the error at the boundary of each subinterval. If $y(\tau_{k+1}; \hat{y}_k) - \hat{y}_{k+1} = 0, k = 0, 1, \dots, m-1$ and $\hat{y}_m - y_f = 0$, then stop, otherwise continue to Step 5
- Step 5, update the guess for $\hat{y}_k, k = 0, 1, \dots, m-1$ based on some updating schema, go to Step 3

In practice, there are many details to be decided when using (multiple) shooting methods, which we will discuss briefly without giving a comprehensive description. In Step 1 & 2, when choosing the shooting nodes and the initial guess \hat{y}_k , how they are chosen usually depends on nature of the problem as well as a balance between accuracy and computational cost. For example, the nodes can be equally spaced and the \hat{y}_k can be initialized with the same value, or they can be addressed based on our initial knowledge of the problem. In Step 3, polynomial functions can be used as the approximate solutions, leveraging the fact that Taylor expansion can be used to approximate any continuous functions. In Step 4, "evaluate the error" is usually in the form of evaluating an objective function, which, e.g. can be defined as the sum of quadratic errors. In Step 5, the "updating schema" can be defined to so that the \hat{y}_k can move in a direction that decreases the objective function. The (quasi) Newton method, for example, can be used as an updating method in Step 5.

The multiple shooting method can be used for many problems. For example, it can be also applied to the twice differential system of the following form

$$y''(t) = f(t, y(t), y'(t)) \quad y(t_0) = y_0, \quad y(t_f) = y_f, \quad t \in [t_0, t_f] \quad (2.6)$$

The problem 2.6 is similar to the problem 2.3. In each subinterval, a boundary value problem (BVP) is to be solved and matching conditions at the boundary of each subinterval are to be enforced so that the final solution is continuous and applicable to the whole interval.

2.1.1 Mutiple shooting method for OCP

Mutiple shooting method is well suited for solving optimal control problems of the form in equation 2.2, as it can serve as the "first discretize" part of the direct approaches. For problems in the form of equation 2.2, we can discretize the time $t \in [t_0, t_f]$ and the original problem is split into multiple subintervals, with the constraints discretized and applied to each subinterval. We also need to introduce the initial guess for each subinterval and add the matching condition at each boundary. In the end, we turn the original problem in the form of equation 2.2 into piecewise OCPs with augmented parameters and constraints.

The dynamic systems of the OCP in equation 2.2 is defined in the subequation 2.2b, which we show here independently

$$\dot{x}(t) = f(x(t), u(t)), \quad t \in [t_0, t_f] \quad (2.7)$$

If the initial value x_0 for 2.7 is known, then equation 2.7 becomes an initial value problem (IVP) and the solution can be found via numerical method. If analytical solutions exist for equation 2.7, then we can use the analytical solution directly. Nevertheless, for most real-life problems, the analytical solution either does not exist or is very difficult to find, and numerical method is the only practical way to find the solution. Given the initial value x_0 , equation 2.7 will have solution as

$$\begin{aligned} x(t) - x_0 &= \int_{t_0}^t f(x(\tau), u(\tau)) d\tau, \quad t \in [t_0, t_f] \\ x(t) &= x_0 + \int_{t_0}^t f(x(\tau), u(\tau)) d\tau, \quad t \in [t_0, t_f] \end{aligned} \quad (2.8)$$

The integral in equation 2.8 can be approximated by numerical methods, and one simple approximation to the integral in equation 2.8 can be obtained via Euler method.

The Euler method (also called forward Euler method) is a first-order numerical procedure for solving ordinary differential equations (ODEs) with a given initial value. Using a step size equal to 1, the approximation to equation 2.8 via Euler method is of the form

$$x(t) = x_0 + \int_{t_0}^t f(x(\tau), u(\tau)) d\tau \approx x_0 + tf(x(t_0), u(t_0)) \quad (2.9)$$

Euler method is a first order and explicit method for approximating integrals, another widely used method is the trapezoidal rule, which is an implicit second-order method. The trapezoidal rule can approximate equation 2.8 as

$$x(t) = x_0 + \int_{t_0}^t f(x(\tau), u(\tau)) d\tau \approx x_0 + \frac{t}{2}[f(x(t_0), u(t_0)) + f(x(t), u(t))] \quad (2.10)$$

Notice, the solution $x(t)$ becomes an input in the approximation in equation 2.10, and that is why this method is classified as an implicit method. The trapezoidal rule belongs to the family of Runge–Kutta method, which is a family of implicit and explicit iterative methods, with various order of derivatives used.

To solve the OCP as in equation 2.2, we first discretize the time horizon $\in [t_0, t_f]$ into multiple subintervals $t_0 = \tau_0 < \tau_1 < \dots < \tau_m = t_f$, then we introduce the initial guess for x and u in each subinterval, i.e. we have x_0, x_1, \dots, x_{m-1} and u_0, u_1, \dots, u_m . Then in each subinterval $\mathbb{I}_j = [\tau_{j-1}, \tau_j]$, the following step should be taken:

- Solve the dynamic system as in equation 2.7 with the initial guess (x_{j-1}, u_{j-1}) within subinterval \mathbb{I}_j , and obtain a solution $x(\tau; x_{j-1}, u_{j-1})$, $\tau \in \mathbb{I}_j = [\tau_{j-1}, \tau_j]$
- Evaluate the cost function 2.2a within subinterval \mathbb{I}_j with the solution $x(\tau; x_{j-1}, u_{j-1})$. We use the notation F_j as the objective function value that is applicable in subinterval \mathbb{I}_j , with the definition given in equation 2.12.
- Evaluate the error with the constraints 2.2c, 2.2d, 2.2f, 2.2g, and 2.2h, which are applicable in subinterval \mathbb{I}_j .

Within subinterval \mathbb{I}_j , with initial guess $X_j = (x_{j-1}, u_{j-1})$, the result from solving the dynamic system equation 2.7 might be an infeasible solution, i.e. a solution which does not satisfy the constraints 2.2c, 2.2d, 2.2f, 2.2g, and 2.2h. In this case, we can update the initial guess iteratively until feasible solutions are found and one optimal solution is reached. The solution is optimal if a minimum cost function value in the subinterval \mathbb{I}_j is obtained while satisfying all the constraints 2.2c, 2.2d, 2.2f, 2.2g, and 2.2h. In practice, we do not aim to find the optimal solution in each subinterval, instead we aim to find the optimal solution of the whole interval, i.e. $\min \sum_{j=1}^m F_j$. With the matching condition

added, then the original OCP is transferred into NLP of the following form

$$\min_w \sum_{j=1}^m F_j \quad (2.11a)$$

$$s.t. \quad x(\tau_j; x_{j-1}, u_{j-1}) - x_j = 0 \quad j = 1, 2, \dots, m \quad (2.11b)$$

$$g(x_{j-1}, u_{j-1}) = 0 \quad j = 1, 2, \dots, m \quad (2.11c)$$

$$h(x_{j-1}, u_{j-1}) \leq 0, \quad j = 1, 2, \dots, m \quad (2.11d)$$

$$g(x(\tau_m; x_{m-1}, u_{m-1}), u_m) = 0 \quad (\text{the final point } t_m = t_f) \quad (2.11e)$$

$$h(x(\tau_m; x_{m-1}, u_{m-1}), u_m) \leq 0 \quad (\text{the final point } t_m = t_f) \quad (2.11f)$$

$$x(t_0) = x_0, \quad (2.11g)$$

$$x^{lower} \leq x_j \leq x^{upper} \quad j = 0, 1, 2, \dots, m \quad (2.11h)$$

$$u^{lower} \leq u_j \leq u^{upper} \quad j = 0, 1, 2, \dots, m \quad (2.11i)$$

$$t_0 = \tau_0 < \tau_1 < \dots < \tau_m = t_f \quad (2.11j)$$

where $w = (x_0, u_0, x_1, u_1, \dots, x_{m-1}, u_{m-1}, u_m)$, and x_{j-1}, u_{j-1} is the initial guess for interval $\mathbb{I}_j = [\tau_{j-1}, \tau_j]$, the solution $x(\tau_j; x_{j-1}, u_{j-1})$ comes from solving the dynamic system 2.7 numerically for the subinterval $\mathbb{I}_j = [\tau_{j-1}, \tau_j]$, and F_j is defined as in 2.12

$$\begin{aligned} F_j &= \int_{\tau_{j-1}}^{\tau_j} L(x(t), u(t)) dt && \text{if } j = 1, \dots, m-1 \\ F_j &= \int_{\tau_{j-1}}^{\tau_j} L(x(t), u(t)) dt + E(x(t_f)) && \text{if } j = m \text{ (the last subinterval)} \end{aligned} \quad (2.12)$$

2.2 KKT condition

As stated in the introduction Chapter 1, direct approaches transform the original infinite optimal control problem into a finite dimensional nonlinear programming problem (NLP). We have shown in previous section 2.1.1 that an OCP of the form 2.2 can be transferred into NLP of the form 2.11. This NLP is then solved by variants of state-of-the-art numerical optimization methods. KKT condition is one of the widespread and successfully used techniques to address the constraints of NLP. Before we explain the KKT condition, we need to introduce several definitions and theorems first. We consider a general NLP of the following form

$$\begin{aligned} \min_{x \in \mathbb{R}^n} \quad & f(x) \\ \text{s.t.} \quad & g(x) = 0 \\ & h(x) \leq 0 \end{aligned} \quad (2.13)$$

Definition 1 (*Feasible set*) The feasible set Ω is the set

$$\Omega := \{x \in \mathbb{R}^n \mid g(x) = 0, h(x) \leq 0\} \quad (2.14)$$

Definition 2 (*Active Constraints and Active Set*) An inequality constraint $h_i(x) \leq 0$ is called active at $x^* \in \Omega$ iff $h_i(x^*) = 0$ and otherwise inactive. The index set $\mathcal{A}(x^*) \subset \{1, \dots, n_h\}$ of active inequality constraint indices is called the "active set".

Often, the name active set also includes all equality constraint indices, as equalities could be considered to be always active.

Definition 3 (*LICQ*) *The linear independence constraint qualification (LICQ) holds at $x^* \in \Omega$ iff all vectors $\nabla g_i(x^*)$ for $i \in \{1, \dots, n_g\}$ and $\nabla h_i(x^*)$ for $i \in \mathcal{A}(x^*)$ are linearly independent.*

To give further meaning to the LICQ condition, let us combine all active inequalities with all equalities in a map \tilde{g} defined by stacking all functions on top of each other in a column vector as follows:

$$\tilde{g}(x) = \begin{pmatrix} g(x) \\ h_i(x), i \in \mathcal{A}(x^*) \end{pmatrix} \quad (2.15)$$

With the definitions above, we are ready to formulate the famous KKT condition.

Theorem 1 (*KKT Conditions*) *If x^* is a local minimizer of the problem 2.13 and the LICQ holds at x^* , then there exist so called multiplier vectors $\lambda \in \mathbb{R}_g^n$ and $\mu \in \mathbb{R}_h^n$ with*

$$\nabla f(x^*) + \nabla g(x^*)\lambda^* + \nabla h(x^*)\mu^* = 0 \quad (2.16a)$$

$$g(x^*) = 0 \quad (2.16b)$$

$$h(x^*) \leq 0 \quad (2.16c)$$

$$\mu^* \geq 0 \quad (2.16d)$$

$$\mu_i^* h_i(x^*) = 0, \quad i = 1, \dots, n_h \quad (2.16e)$$

The "KKT Conditions" are also known as "First-Order Necessary Conditions".

Definition 4 (*KKT Point*) *We call a triple (x^*, λ^*, μ^*) a "KKT Point" if it satisfies LICQ (Definition 3) and the KKT conditions (Theorem 1).*

Definition 5 (*Lagrangian Function*) *We define the so called "Lagrangian function" to be*

$$\mathcal{L}(x, \lambda, \mu) = f(x) + \lambda^\top g(x) + \mu^\top h(x) \quad (2.17)$$

Here, we have used the so called "Lagrange multipliers" $\lambda \in \mathbb{R}_g^n$ and $\mu \in \mathbb{R}_h^n$. The last three KKT conditions 2.16c - 2.16e are called the complementarity conditions. For each index i , they define an L -shaped set in the (h_i, μ_i) space. This set is not a smooth manifold but has a non-differentiability at the origin, i.e. if $h_i(x^*) = 0$ and also $\mu_i^* = 0$. This case is called a weakly active constraint. Often we want to exclude this case. On the other hand, an active constraint with $\mu_i^* > 0$ is called strictly active.

Definition 6 *Regard a KKT point (x^*, λ^*, μ^*) . We say that strict complementarity holds at this KKT point iff all active constraints are strictly active.*

Theorem 2 (*Second Order Optimality Conditions*) *Let us regard a point x^* at which LICQ holds together with multipliers λ^*, μ^* so that the KKT conditions are satisfied and let strict complementarity hold. Regard a basis matrix $\mathbb{Z} \in \mathbb{R}^{n^*(n-n_g)}$ of the null space of $\frac{\partial \tilde{g}}{\partial x}(x^*) \in \mathbb{R}^{n_g^* \times n}$, i.e., \mathbb{Z} has full column rank and $\frac{\partial \tilde{g}}{\partial x}(x^*)\mathbb{Z} = 0$. Then the following two statements hold:*

- If x^* is a local minimizer, then $\mathbb{Z}^\top \nabla_x^2 \mathcal{L}(x^*, \lambda^*, \mu^*) \mathbb{Z} \succeq 0$. (Second Order Necessary Condition, short : SONC)
- If $\mathbb{Z}^\top \nabla_x^2 \mathcal{L}(x^*, \lambda^*, \mu^*) \mathbb{Z} \succ 0$, then x^* a local minimizer. This minimizer is unique in its neighborhood, i.e., a strict local minimizer, and stable against small differentiable perturbations of the problem data. (Second Order Sufficient Condition, short: SOSOC).

The matrix $\nabla_x^2 \mathcal{L}(x^*, \lambda^*, \mu^*)$ plays an important role in optimization algorithms and is called the Hessian of the Lagrangian, while its projection on the null space of the Jacobian, $\mathbb{Z}^\top \nabla_x^2 \mathcal{L}(x^*, \lambda^*, \mu^*) \mathbb{Z}$, is called the reduced Hessian.

For an optimization problem, if we can start with an initial guess x_0 and find a updating schema which decreases the objective value while maintain the Hessian matrix positive, if such updating schema can converge, it will converge to a local minimizer. If the original problem is convex, the local minimizer is, therefore, the global minimizer. Taking advantage of these properties, we can reformulate the NLP as in equation 2.13 as well as the optimal control problem as in equation 2.2, and then re-write in the Lagrangian form 2.17, optimize the (objective) Lagrangian function with quasi Newton method.

2.3 quasi Newton method

As explained in Section 2.2, KKT condtion can be applied to include the constraints into a Lagrangian function, and we can employ an updating schema with an initial guess to solve NLP as in equation 2.13 and optimal control problem as in equation 2.2. Newton and quasi Netwon method can be used as the updating method to find the optimal solution. For the sake of simplicity, we focus on explaining the Newton and quasi Newton method without constraints in this chapter. How the quasi Newton method, together with multiple shooting, can be used to solve optimal control problem, will be explained in more details in Chapter 4 when we discuss our numerical solutions for the rocket car case.

2.3.1 Newton method

A general optimization problem is typically of the form

$$\begin{aligned} \min \quad & f(x) \\ \text{s.t.} \quad & x \in \Omega \end{aligned} \tag{2.18}$$

Here $x \in \Omega$ represents the constraints for which x must satisfy, it may be in the form of $\{g(x) = 0, h(x) \leq 0\}$ as in the equation 2.13, i.e. the feasible set $\Omega = \underset{x}{\arg} \{g(x) = 0, h(x) \leq 0\}$. Before discussing the optimization problem with constraints, we first focus on the problems without constraints, i.e. problem of the form

$$\min_{x \in \mathbb{R}^n} f(x) \tag{2.19}$$

The problem 2.19 can be solved via Newton's method, which attempts to solve this problem by constructing a sequence $\{x_k\}$ from an initial guess (starting point) x_0 that converges towards a minimizer x^* of $f(x)$ by using a sequence of second-order Taylor

approximations of $f(x)$ around the iterates. The second-order Taylor expansion of $f(x)$ around x_k is

$$f(x_k + \delta_x) \approx h(x_k) := f(x_k) + f'(x_k)\delta(x_k) + \frac{1}{2}f''(x_k)\delta(x_k)^2$$

where δ represents a small change (with respect to x), and f', f'' are the first and second order derivatives of the original function $f(x)$. The notation f', f'' are usually expressed as ∇f and H (the Hessian matrix) respectively when x is a vector of variables. In the text that follows, we will use the symbol ∇f and H directly. Therefore, the Talyor expansion can be written as

$$f(x_k + \delta_x) \approx h(x_k) := f(x_k) + \nabla f(x_k)^T \delta(x_k) + \frac{1}{2}H(x_k)\delta(x_k)^2$$

The next iterate x_{k+1} is defined so as to minimize this quadratic approximation $h(\cdot)$. The function $h(\cdot)$ is a quadratic function of $\delta(x)$, and is minimized by solving $\nabla h(\cdot) = 0$. The gradient of $h(\cdot)$ with respect to $\delta(x_k)$ at point x_k is

$$\nabla h(x_k) = \nabla f(x_k) + H(x_k)\delta(x_k)$$

We are motivated to solve $\nabla h(x_k) = 0$, which turns out to solve a linear system

$$\nabla f(x_k) + H(x_k)\delta(x_k) = 0 \tag{2.20}$$

Therefore, for the next iteration point x_{k+1} , we can just add the small change $\delta(x_k)$ to the current iterate, i.e.

$$x_{k+1} = x_k + \delta(x_k) = x_k - H^{-1}(x_k)\nabla f(x_k),$$

here $H^{-1}(\cdot)$ represents the inverse of the Hessian matrix $H(\cdot)$. The Newton method performs the iteration until the convergence, i.e. x_k and $f(x_k)$ converge to x^* and $f(x^*)$, respectively¹. The details of the Newton method is as follows:

Newton method

- Step 0, $k = 0$, choose an initial value x_0
- Step 1, $\delta(x_k) = -H^{-1}(x_k)\nabla f(x_k)$, if $\delta(x_k) = 0$, then stop
- Step 2, choose a step-size α_k (typically $\alpha_k = 1$)
- Step 3, set $x_{k+1} = x_k + \alpha_k\delta(x_k)$, let $k = k + 1$. Go to Step 1

The parameter α_k is introduced to augment the Newton method such that a line-search of $f(x_k + \alpha_k\delta(x_k))$ is applied to find an optimal value of the step size parameter α_k .

Though the Newton method is straightforward and easy to understand, it has two main limitations. Firstly, it is sensitive to initial conditions. This is especially apparent if the objective function is non-convex. Depending on the choice of the starting point x_0 , the Newton method may converge to a global minimum, a saddle point, a local minimum or may not converge at all. In another word, due to the sensitivity with respect to the initialization, the Newton method may be not able to find the global solution. Secondly, the Newton method can be computationally expensive, with the second-order derivatives, aka, the Hessian matrix $H(\cdot)$ and its inverse very expensive to compute. It may also happen that the Hessian matrix is not positive definite, therefore, Newton method can not be used at all for solving the optimization problem. Due to these limitations of the Newton method, the quasi Newton method is, therefore, usually preferred for solving optimal control or general optimisation problems.

¹In another word, the Newton mehtod has converged when the small change $\delta(x_k) = 0$ or $\delta(x_k)$ is small enough that the change in the objective function is below a pre-defined tolerance level.

2.3.2 quasi Newton method

We have stated that one limitation or the downside of the Newton method, is that Newton method can be computationally expensive when calculating the Hessian (i.e. second-order derivatives) matrix and its inverse, especially when the dimensions get large. The quasi-Newton methods are a class of optimization methods that attempt to address this issue. More specifically, any modification of the Newton methods employing an approximation matrix B to the original Hessian matrix H , can be classified into a quasi-Newton method.

The first quasi Newton algorithm, i.e. the Davidon–Fletcher–Powell (DFP) method, was proposed by William C. Davidon in 1959 [Davidon \[1959\]](#), which was later popularized by Fletcher and Powell in 1963 [Fletcher R. \[1963\]](#). Some of the most common used quasi-Newton algorithms currently are the symmetric rank-one (SR1) method [A. R. Conn \[1991\]](#) and the Broyden–Fletcher–Goldfarb–Shanno(BFGS) method. The family of the quasi Newton algorithms are similar in nature, with most of the difference arising in the part how the approximation Hessian matrix is decided and the updating distance $\delta(x_k)$ is calculated. One of the main advantages of the quasi Newton methods over Newton method is that the approximation Hessian matrix B can be chosen in a way that no matrix needs to be directly inverted. The Hessian approximation B is chosen to satisfy the equation 2.20, with the approximation matrix B replacing the original Hessian matrix H , i.e.

$$\nabla f(x_k) + B_k \delta(x_k) = 0 \quad (2.21)$$

In the text that follows, we explain how the iteration is performed in the BFGS method, as an example illustrating the quasi Newton method. In the BFGS method, instead of computing B_k afresh at every iteration, it has been proposed to update it in a simple manner to account for the curvature measured during the most recent step. To determine an update scheme for B , we will need to impose additional constraints. One such constraint is the symmetry and positive-definiteness of B , which is to be preserved in each update for $k = 1, 2, 3, \dots$. Another desirable property is that B_{k+1} is sufficiently close to B_k at each update $k + 1$, and such closeness can be measured by the matrix norm, i.e. the quantity $\|B_{k+1} - B_k\|$. We can, therefore, formulate our problem during the $k + 1$ update as

$$\begin{aligned} \min_{B_{k+1}} & \|B_{k+1} - B_k\| \\ \text{s.t. } & B_{k+1} = B_{k+1}^T, \quad B_{k+1} \delta(x_k) = y_k \end{aligned} \quad (2.22)$$

where $\delta(x_k) = x_{k+1} - x_k$ and $y_k = \nabla f(x_{k+1}) - \nabla f(x_k)$. In the BFGS method, the norm is chosen to be the Frobenius norm:

$$\|B\|_F = \sqrt{\sum_i^m \sum_j^n |b_{ij}|^2}$$

Solving the problem 2.22 directly is not trivial, but it has been proved (ref [Jorge Nocedal \[2006\]](#)) that problem ends up being equivalent to updating our approximate Hessian B at each iteration by adding two symmetric, rank-one matrices U and V :

$$B_{k+1} = B_k + U_k + V_k$$

where the update matrices can then be chosen of the form $U = auu^T$ and $V = bvv^T$, where u and v are linearly independent non-zero vectors, and a and b are constants. The outer product of any two non-zero vectors is always rank one, i.e. U_k and V_k are rank-one. Since u and v are linearly independent, the sum of U_k and V_k is rank-two, and an update of this form is known as a rank-two update. The rank-two condition guarantees the “closeness” of B_k and B_{k+1} at each iteration.

Besides, the condition $B_{k+1}\delta(x_k) = y_k$ has to be imposed.

$$B_{k+1}\delta(x_k) = B_k\delta(x_k) + auu^T\delta(x_k) + bvv^T\delta(x_k) = y_k$$

Then, a natural choice of u and v would be $u = y_k$ and $v = B_k\delta(x_k)$, we then have

$$\begin{aligned} B_k\delta(x_k) + ay_k y_k^T \delta(x_k) + bB_k\delta(x_k)\delta(x_k)^T B_k^T \delta(x_k) &= y_k \\ y_k(1 - ay_k^T \delta(x_k)) &= B_k\delta(x_k)(1 + b\delta(x_k)^T B_k^T \delta(x_k)) \\ \Rightarrow a &= \frac{1}{y_k^T \delta(x_k)}, \quad b = -\frac{1}{\delta(x_k)^T B_k \delta(x_k)} \end{aligned}$$

Finally, we get the update formula as follows:

$$B_{k+1} = B_k + \frac{y_k y_k^T}{y_k^T \delta(x_k)} - \frac{B_k \delta(x_k) \delta(x_k)^T B_k}{\delta(x_k)^T B_k \delta(x_k)}$$

Since B is positive definite for all $k = 1, 2, 3, \dots$, we can actually minimize the change in the inverse B^{-1} at each iteration, subject to the (inverted) quasi Newton condition and the requirement that it is symmetric. Applying the Woodbury formula (ref [Woodbury \[1950\]](#) for more details), we can show that the updating formula of inverse B^{-1} is as follows

$$B_{k+1}^{-1} = (I - \frac{\delta(x_k) y_k^T}{y_k^T \delta(x_k)}) B_k^{-1} (I - \frac{y_k \delta(x_k)^T}{y_k^T \delta(x_k)}) + \frac{\delta(x_k) \delta(x_k)^T}{y_k^T \delta(x_k)} \quad (2.23)$$

As shown in the formula 2.23, at each iteration, we update B^{-1} by using $\delta(x_k) = x_{k+1} - x_k$ and $y_k = \nabla f(x_{k+1}) - \nabla f(x_k)$. Since an update of B^{-1} depends on the previous value, we need to initialize B^{-1} , either as an identity matrix or as the true Hessian matrix $H(x_0)$, calculated based on the starting point x_0 .

We have shown that with quasi Newton method, with an initial guess x_0 , we can iteratively update x_k until convergence so that an optimal solution to the unconstrained optimization problem as in 2.19 can be obtained. In the next section, we explain how the quasi Newton method can be applied to optimization problems with constraints, as well as the OCP problems of the form 2.2.

2.4 Sequential quadratic programming

With all the background knowledge of multiple shooting, KKT conditions and Newton-style method, now we are ready to explain how we can solve the OCP with the form 2.2 in details, i.e. working within an iterative Sequential Quadratic Programming (SQP) approach.

As explained in section 2.1.1, the original OCP with the form 2.2 can be transferred into a NLP of the form 2.11. Within the NLP 2.11, the independent variables are the initial guess of x and u for each subinterval $\mathbb{I}_j = [\tau_{j-1}, \tau_j]$ and the final control value u_m , i.e. $w = (x_0, u_0, x_1, u_1, \dots, x_{m-1}, u_{m-1}, u_m)$. The constraints in formulation 2.11 are applied to the independent variables $w = (x_0, u_0, x_1, u_1, \dots, x_{m-1}, u_{m-1}, u_m)$ piecewise, and they are in the form as equality constraints or inequality constraints. Together with the matching condition 2.11b, then the NLP problem 2.11 can be re-written as the form in NLP 2.13, with the x in NLP 2.13 replaced by $w = (x_0, u_0, x_1, u_1, \dots, x_{m-1}, u_{m-1}, u_m)$.

To solve NLP of the form 2.13, we can use the KKT approach, i.e. including the constraints and the original objective function into a new objective function, defined as a Lagrangian function as 2.17, which we re-write here

$$\mathcal{L}(w, \lambda, \mu) = f(w) + \lambda^\top g(w) + \mu^\top h(w) \quad (2.24)$$

Based on our discussion regarding Newton-style method, to find the minimum of $\mathcal{L}(w, \lambda, \mu)$, we are motivated to solve a linear system as in equation 2.20, where the first order derivatives and Hessian matrix is calculated for the objective function $\mathcal{L}(w, \lambda, \mu)$. Starting with an initial guess of (w_0, λ_0, μ_0) , then we are motivated to update (w, λ, μ) so as to decrease the objective function $\mathcal{L}(\cdot)$ by solving a subproblem of quadrature programming of the following form

$$\min_{\Delta w} \quad \frac{1}{2} \Delta w^\top \nabla_w^2 \mathcal{L}(\cdot) \Delta w + \nabla_w f(w_i)^\top \Delta w \quad (2.25a)$$

$$\text{s.t.} \quad g(w_i) + \nabla g(w_i)^\top \Delta w = 0 \quad (2.25b)$$

$$h(w_i) + \nabla h(w_i)^\top \Delta w \leq 0 \quad (2.25c)$$

where $\nabla_w^2 \mathcal{L}(\cdot)$ is the Hessian matrix of function $\mathcal{L}(\cdot)$, whose updating can be calculated with quasi Newton method. With a solution $\Delta w_k, \lambda_k^{QP}, \mu_k^{QP}$ found from the subproblem 2.25, we can therefore update the w, λ, μ as

$$w_{k+1} = w_k + \Delta w_k \quad (2.26a)$$

$$\lambda_{k+1} = \lambda_k^{QP} \quad (2.26b)$$

$$\mu_{k+1} = \mu_k^{QP} \quad (2.26c)$$

until convergence.

We have shown that the original OCP of the form 2.2 can be transferred into a NLP of the form 2.11 using multiple shooting method. The NLP 2.11 can then be re-written in the form 2.13, and can be solved using Newton-style framework, i.e. sequential quadrature programming and quasi Newton method. The numerical implementation details to a case study of rocket car will be given in Chapter 4.

3 Optimal control under uncertainty

Besides the OCP as in the formulation 2.2, some OCP may have uncertain parameters whose value are priori unknown, and the optimal objective value depends on the parameter value, as shown in the formulation 1.2 in Chapter 1. This kind of problem is called the

parameterized optimization problems and the formulation 1.2 can be augmented with mathematical details as well, leading to a OCP under uncertainty of the following form

$$\min_{x(t;p), u(t)} F(x(t;p), u(t)) = \int_{t_0}^{t_f} L(x(t;p), u(t)) dt + E(x(t_f;p)) \quad (3.1a)$$

$$s.t. \quad \dot{x}(t;p) = f(x(t;p), u(t)) \quad (\text{system dynamics}) \quad (3.1b)$$

$$g(x(t;p), u(t)) = 0, \quad (\text{path equality constraints}) \quad (3.1c)$$

$$h(x(t;p), u(t)) \leq 0, \quad (\text{path inequality constraints}) \quad (3.1d)$$

$$x(t_0) = x_0, \quad (\text{initial value}) \quad (3.1e)$$

$$r(x(t_f;p)) \leq 0, \quad (\text{terminal constraints}) \quad (3.1f)$$

$$x^{lower} \leq x(t;p) \leq x^{upper} \quad (3.1g)$$

$$u^{lower} \leq u(t) \leq u^{upper} \quad (3.1h)$$

$$p \in \mathbb{P} \quad (3.1i)$$

$$x = x(, p^*) \text{ if } p = p^* \quad (3.1j)$$

$$t \in [t_0, t_f] \quad (3.1k)$$

In other words, the state variables x depend not only on the system dynamics 3.1b, the control variables u , but also an uncertain parameter p . Parameterized optimization problems are very difficult to solve due to the uncertainty in the parameter p . Since different parameter p will lead to different solutions, it makes sense to solve the parameterized optimal control problems in a conservative way. For simplicity and the sake of generalization, we use the more compact formulation 1.2 in Chapter 1 as the representation of a parameterized optimal control problem for our subsequent discussion, which we show here again

$$\begin{aligned} \min_{x(t), u(t)} & F(x(t;p), u(t)) \\ s.t. & \quad \dot{x}(t;p) = f(x(t;p), u(t)) \\ & \quad x(t;p) \in \Omega \\ & \quad u(t) \in \mathbb{U} \\ & \quad p \in \mathbb{P} \\ & \quad x = x(, p^*) \text{ if } p = p^* \\ & \quad t \in [t_0, t_f] \end{aligned} \quad (3.2)$$

In the paper [Schlöder \[2022\]](#), multiple methods of solving the parameterized optimal control problem have been discussed. The main idea of solving the parameterized optimal control problem 3.2 in a conservative way is to transform the problem into another form. Two different ways of solving the parameterized optimal control problem will be discussed in details in the following sections, i.e. the classical approach and the training approach.

3.1 Classical approach

Assuming parameter p^* lies in an uncertainty set \mathbb{P} , we can firstly reach one objective, i.e. identifying a worst possible solution with respect to p^* , i.e. solving a lower level problem. Based on the result of lower level, we can continue to find the best solution with respect

to x , i.e. solving a upper level problem. The "worst-case treatment planning by bilevel optimal control", i.e. a bilevel optimization problem, is an optimization problem in which another optimization problem enters the constraints. Mathematically, the problem 3.2 is transformed into another form, as following

$$\begin{aligned}
& \min_{x(\cdot, p), u(\cdot)} \max_{p \in \mathbb{P}} F(x(t; p), u(t)) \\
& \text{s.t. } \dot{x}(t; p) = f(x(t; p), u(t)) \\
& \quad x(t; p) \in \Omega \\
& \quad u(t) \in \mathbb{U} \\
& \quad p \in \mathbb{P} \\
& \quad x = x(\cdot, p^*) \text{ if } p = p^* \\
& \quad t \in [t_0, t_f]
\end{aligned} \tag{3.3}$$

Due to the *min max* notation, this classical approach of solving the bilevel problem can also be called *minmax* approach. In the classical approach, the set of feasible controllable variables are given by $u(\cdot)$, which yield feasible trajectories $x(\cdot, p)$ for all $p \in \mathbb{P}$. The value of the objective function in the lower level does not depend on p and $x(\cdot, p)$. In other words, in this approach, the dynamic system has no prior knowledge about the value of the parameter p and gets no feedback during the process and has to decide the control strategy in advance.

3.2 Training approach

The paper [Schlöder \[2022\]](#) introduces the "Training Approach". It is based on the idea that in the real world, during the training period, an intervention is introduced and a certain, but a priori unknown, parameter $p \in \mathbb{P}$ is realized. What follows the training period (during which the parameter p is realized), the dynamic system is able to react to it in an optimal manner, i.e. an optimal value $F(\cdot)$ will be obtained given the realized parameter p . The paper [Schlöder \[2022\]](#) call this approach "worst case modeling Training Approach", and it can be written as

$$\begin{aligned}
& \max_{p \in \mathbb{P}} \min_{x(\cdot, p), u(t)} F(x(t; p), u(t)) \\
& \text{s.t. } \dot{x}(t; p) = f(x(t; p), u(t)) \\
& \quad x(t; p) \in \Omega \\
& \quad u(t) \in \mathbb{U} \\
& \quad p \in \mathbb{P} \\
& \quad x = x(\cdot, p^*) \text{ if } p = p^* \\
& \quad t \in [t_0, t_f]
\end{aligned} \tag{3.4}$$

Due to the *max min* notation, this approach of solving the bilevel problem can be also called *maxmin* approach. The solution of the Training Approach in paper [Schlöder \[2022\]](#) is given by a gradient-free method, more precisely, a so-called model-based Derivative-Free Optimization (DFO) approach for box-constrained optimization problems is used. The BOBYQA algorithm is chosen for such approach to solve problems of the form

$$\begin{aligned}
& \min_{x \in \mathbb{R}^n} F(x) \\
& \text{s.t. } a_i \leq x_i \leq b_i, i = 1, \dots, n
\end{aligned} \tag{3.5}$$

The name BOBYQA is an acronym for "Bound Optimization By Quadratic Approximation", and is used to solve lower level problem of 3.4. In the general DFO method, the objective function $F(\cdot)$ is considered a black box. For a given p , the parametric lower level OCP of the Training Approach 3.4 is solved with a direct DFO approach and the resulting (finite dimensional) solution is viewed as dependent variable. Furthermore, the uncertainty set \mathbb{P} is chosen to be box-shaped, and hence the BOBYQA algorithm is applicable to the problem in the Training Approach. The BOBYQA algorithm has been introduced in details in the paper [Powell \[2009\]](#), and we reiterate the main idea in the text that follows.

The method of BOBYQA is iterative, k and n being reserved for the iteration number and the number of variables, respectively. Further, m is reserved for the number of interpolation conditions that are imposed on a quadratic approximation $Q_k(x) \rightarrow F(x)$, $x \in \mathcal{R}^n$, with m is a chosen constant integer from the interval $[n + 2, \frac{1}{2}(n + 1)(n + 2)]$.

The approximation is available at the beginning of the k -th iteration, the interpolation equations have the form

$$Q_k(y_j) = F(y_j), \quad j = 1, 2, \dots, m. \quad (3.6)$$

We let x_k be the point in the set $\{y_j : j = 1, 2, \dots, m\}$ that has the property

$$F(x_k) = \min \{F(y_j), \quad j = 1, 2, \dots, m\}, \quad (3.7)$$

with any ties being broken by giving priority to an earlier evaluation of the least function value $F(x_k)$. A positive number Δ_k , called the "trust region radius", is also available at the beginning of the k -th iteration. If a termination condition¹ is satisfied, then the iteration stops. Otherwise, a step d_k from x_k is constructed such that $\|d_k\| \leq \Delta_k$ holds, $x = x_k + d_k$ is within the bounds of equation 3.5, and $x_k + d_k$ is not one of the interpolation points $y_j : j = 1, 2, \dots, m$. Then the new function value $F(x_k + d_k)$ is calculated, and one of the interpolation points, y_t say, is replaced by $x_k + d_k$, where y_t is different from x_k . It follows that x_{k+1} is defined by the formula

$$x_{k+1} = \begin{cases} x_k, & F(x_k + d_k) \geq F(x_k) \\ x_k + d_k, & F(x_k + d_k) < F(x_k) \end{cases} \quad (3.8)$$

Further, Δ_{k+1} and Q_{k+1} are generated for the next iteration, Q_{k+1} being subject to the constraints

$$Q_{k+1}(\hat{y}_j) = F(\hat{y}_j), \quad j = 1, 2, \dots, m, \quad (3.9)$$

at the new interpolation points

$$\hat{y}_j = \begin{cases} y_j, & j \neq t, \\ x_k + d_k, & j = t \end{cases}, \quad j = 1, 2, \dots, m. \quad (3.10)$$

The operations of BOBYQA algorithm requires the user to provide an initial vector of variables $x_0 \in \mathcal{R}^n$, the initial trust region Δ_1 , and the number m of interpolation conditions where $n + 2 \leq m \leq \frac{1}{2}(n + 1)(n + 2)$. Two different ways have been proposed

¹Typically, a termination condition is satisfied when the objective value can not be improved further after some iterations. For the termination condition of BOBYQA algorithm, please refer the paper [Powell \[2009\]](#) for more details.

for constructing the step d_k from x_k and updating procedures from the k -th iteration to the $k + 1$ -th iteration in the paper [Powell \[2009\]](#), with both methods having utilized the "quadratic" nature of the approximation function $Q(\cdot)$.

The lower level OCP of the Training Approach 3.4 can be solved with the BOBYQA algorithm for a given p , since the lower level problem can be re-written into the form of 3.5 and the uncertainty set \mathbb{P} is chosen to be box-shaped. With the BOBYQA algorithm computing local extrema, the upper level problem still needs to be solved globally. In our rocket car case in Chapter 4, this is straight-forward, i.e. maximizing over all p .

Nevertheless, the BOBYQA algorithm has limitations with several strong assumptions being made. Firstly, it has been assumed the uncertainty set is of moderate size and is box-shaped. Secondly, it has been assumed that there is only one local extrema, i.e. the lower level problem has only one solution for each $p \in \mathbb{P}$. In general, we cannot expect the second assumption to be valid. The BOBYQA algorithm is a gradient-free method with respect to the objective function $F(\cdot)$, it still utilizes the gradient of the approximation function $Q(\cdot)$ while updating the iteration. Therefore, this BOBYQA algorithm, or a general DFO approach, is still subject to the numerical errors and computational costs while calculating the gradients of the approximation function $Q(\cdot)$ and updating them in each iteration.

The paper at hand, instead, is utilizing the gradient of the objective function $F(\cdot)$ directly, with some approximation applied as well. We have used the multiple shooting and Newton-style framework for solving the lower level problem of the Training Approach 3.4. In the next Chapter 4, we discuss in details how our gradient approach to the lower level problem of the Training Approach 3.4 is implemented, with a case study (i.e. state constrained rocket car) as an example for illustration.

4 Numerical solution

In this chapter, we use a case study as an example to illustrate how the numerical methods discussed before can be used for solving OCPs and OCPs under uncertainty. In the next section we first give a description of the case we have chosen, the state constrained rocket car. After that, we present how the numerical methods are implemented for the chosen case and the numeric results.

4.1 Introduction to the rocket car case

The description of the rocket car case is mostly coming from the paper [Schlöder \[2022\]](#), with content either verbatim or in a modified form. We consider the rocket car case with state constraints, i.e. the one-dimensional movement of a mass point under the influence of some constant acceleration/deceleration, e.g. modeling head-wind or sliding friction, which can accelerate and decelerate in order to reach a desired position. The mass of the car is normalized to 1 unit¹ and the constant acceleration/deceleration enters the model in form of an unknown parameter $p \in \mathbb{P} \subset \mathbb{R}$ suffering from uncertainty, with the

¹We do not specify the unit on purpose since the actual unit, either one kilogram or meter, does not play a role in the modeling. We are more concerned about the scale.

uncertainty set \mathbb{P} convex and compact. We consider a problem in which the rocket car shall reach a final feasible position and velocity in a minimum time:

$$\min_{T, u(\cdot), x(\cdot; p)} T \quad (4.1a)$$

$$s.t. \quad x = (x_1, x_2), \quad (4.1b)$$

$$\dot{x} = T \begin{pmatrix} x_2(t; p) \\ u(t) - p \end{pmatrix}, \quad t \in [0, 1], \quad (4.1c)$$

$$x(0, p) = 0, \quad (4.1d)$$

$$x_1(1; p) \geq 10, \quad (4.1e)$$

$$x_2(t; p) \leq 4, \quad t \in [0, 1], \quad (4.1f)$$

$$x_2(1; p) \leq 0, \quad (4.1g)$$

$$T \geq 0, \quad (4.1h)$$

$$u(t) \in [-10, 10], \quad t \in [0, 1]. \quad (4.1i)$$

where x represents the variables of the rocket car, and it has two components $x = (x_1, x_2)$. The first component x_1 is the (time-transformed) position of the rocket car. The second component x_2 is (time-transformed) velocity of the rocket car. The control function $u : [0, 1] \rightarrow \mathbb{R}$ in equation 4.1 represents the acceleration/deceleration value. The condition 4.1d, i.e. $x(0, p) = 0$, indicates that at starting time $t = 0$, both the position and velocity of the car is 0. The condition 4.1e, i.e. $x_1(1; p) \geq 10$, indicates that the position of the car at $t = 1$ must be greater than or equal to 10. The condition 4.1f, i.e. $x_2(t; p) \leq 4$, indicates that the velocity of the car is always smaller or equal to 4 across the whole period. The condition 4.1g, i.e. $x_2(1; p) \leq 0$, indicates that the velocity of the car at ending time $t = 1$ is always smaller or equal to 0. Here, a negative velocity means that the car is moving in a direction that decreases the position. To make the rocket car case even simpler, we can limit the size of the uncertainty set, as following

$$p \in \mathbb{P} = [p_l, p_u] = [0, 9], \quad (4.2)$$

where $p_l < p_u$, with p_l and p_u the lower and upper boundary of the parameter p .

Because our objective is to minimize the time between starting state and ending state, i.e. the variable T , which is unknown, we cannot define a time horizon over which we will discretize and optimize. Therefore, a new variable t , as in the problem 4.1, is defined as follows:

$$t = \frac{\tau}{T} \in [0, 1] \quad \tau \in [0, T] \quad (4.3)$$

where τ is the real time between starting time 0 and ending time T , and t is the relative time between 0 and 1. The equation 4.1c can be also written as

$$\dot{x} = \begin{pmatrix} \dot{x}_1 \\ \dot{x}_2 \end{pmatrix} = T \begin{pmatrix} x_2(t; p) \\ u(t) - p \end{pmatrix} = \begin{pmatrix} T x_2(t; p) \\ T(u(t) - p) \end{pmatrix} \quad (4.4a)$$

$$\begin{pmatrix} \dot{x}_1 \\ \dot{x}_2 \end{pmatrix} = \begin{pmatrix} \frac{\partial x_1}{\partial \tau} \\ \frac{\partial x_2}{\partial \tau} \end{pmatrix} = \begin{pmatrix} \frac{\partial x_1}{\partial \tau} \frac{\partial \tau}{\partial t} \\ \frac{\partial x_2}{\partial \tau} \frac{\partial \tau}{\partial t} \end{pmatrix} = \begin{pmatrix} \frac{\partial x_1}{\partial \tau} T \\ \frac{\partial x_2}{\partial \tau} T \end{pmatrix} = \begin{pmatrix} T x_2(t; p) \\ T(u(t) - p) \end{pmatrix} \quad (4.4b)$$

$$\begin{pmatrix} \frac{\partial x_1}{\partial \tau} \\ \frac{\partial x_2}{\partial \tau} \end{pmatrix} = \begin{pmatrix} x_2(t; p) \\ u(t) - p \end{pmatrix} \quad (4.4c)$$

The equation $\frac{\partial x_1}{\partial \tau} = x_2(t; p)$ means the change in the position in real time is proportional to the speed at that moment. The equation $\frac{\partial x_2}{\partial \tau} = u(t) - p$ means the change in speed is proportional to the acceleration/deceleration value at that moment. The variable $x(t; p)$ is a dependent variable, and is uniquely determined by $T, u(\cdot)$ and p . The goal is to minimize T such that the variable $x(t; p)$ satisfies all the conditions in 4.1.

4.2 Theoretical solution to rocket car case

We have chosen the rocket car case for two main reasons. First, this case is easy to understand, and second a theoretical solution exists, which is useful for evaluating the result of the numerical methods. The optimization problem 4.1 has a unique global solution, and no further local solution exists. The optimal solution based on the uncertain parameter p is given by

$$T^* = T^*(p) = 2.5 + \frac{40}{100 - p^2}, \quad (4.5)$$

and the optimal control function $u^*(\cdot) (= u^*(\cdot; p))$ by

$$u^*(\cdot) = \begin{cases} 10, & \text{for } 0 \leq t < \frac{4}{(10-p)T^*} \\ p & \text{for } \frac{4}{(10-p)T^*} \leq t < 1 - \frac{4}{(10+p)T^*} \\ -10 & \text{for } 1 - \frac{4}{(10+p)T^*} \leq t \leq 1 \end{cases} \quad (4.6)$$

In words, we accelerate as strongly as possible (the acceleration value $u^*(t) = 10$) until the velocity $x_2^*(t; p) = 4$, and then keep the velocity $x_2^*(t; p)$ constant for a certain period of time², and eventually decelerate as as strongly as possible until the velocity reaches the state $x_2(1; p) \leq 0$ and $x_1(1; p) \geq 10$. The first moment that these two conditions have been reached, is the moment that we find the optimal/smallest T .

The proof of the theoretical solution is given in Appendix B of [Schlöder \[2022\]](#). The proof is very tedious, but the idea is straightforward.

Because of the simplicity of the rocket car case, we can find the theoretical solution of the nominal/original problem for our case 4.1. But for many real life problems, it is very difficult to find a direct solution to the original problem, and for some cases not feasible, due to the uncertainty in the parameter p . That is why in the paper [Schlöder \[2022\]](#), a classical (in the form *minmax*) approach and a training (in the form *maxmin*) approach have been discussed, and both approaches will lead to a conservative solution to the original problem. A conservative solution to the problem in the paper [Schlöder \[2022\]](#), or to general problems, is an acceptable (or desired) result since less risk is taken and the result is more robust. In the next chapter, we discuss, in details, the classical approach and training approach for the rocket car problem.

4.3 Apply classical (minmax) approach

We have explained in Section 3.1 about the classical approach. Within this section, we further explain the classical approach in details before we discuss how this approach can be used for the chosen case.

²The acceleration value cancels out with an inherent deceleration value so that the velocity can stay constant. The inherent deceleration value can be the result of a friction or head wind.

The classical approach belongs to the family of robust optimization. Robust optimization is an important subfield of optimization that deals with optimization problems under uncertainty. These uncertainties may influence the satisfaction of constraints but also the objective function value. The aim of robust optimization is to robustify or immunize a solution against uncertainty in terms of feasibility and optimality. In this paper on hand, we focus on problems with deterministic uncertainty, i.e. the uncertain parameters lie in a so-called uncertainty set. For deterministic uncertain problems, robustifying the solution of the considered problem means that the robustified solution yields feasible parameter-dependent variables for all possible realizations of the uncertain parameters, and the robustified solution is optimal with regard to the worst possible value the objective function can take due to uncertainty. Therefore, the robustified solution is conservative. The dominating paradigm in this area of robust optimization is *minmax* model, namely

$$\min_{x \in \mathbb{R}^n} \max_{p \in \mathbb{P}} f(x, p) \quad (4.7)$$

This is the classic format of the generic model, and is often referred to as *minimax* approach, also called classical approach. In this paper on hand, we are particular interested in the robustification of OCPs under uncertainties. In our chosen case, the uncertainty appears in the form of an uncertain parameter which enters the differential equations. Applying the classical approach to the rocket car case, the problem can be solved as follows. Discretize the whole uncertainty set \mathbb{P} into multiple points in an increasing order $[p_0, p_1, \dots, p_n] \subset \mathbb{P}$ so that $p_i, i = 0, 1, \dots, n$ can approximately representing the whole set \mathbb{P} when n is large enough. Here $p_0 = p_l$ and $p_n = p_u$, with $[p_l, p_u] = [0, 9]$, as shown in equation 4.2. For each $p_i \in [p_0, p_1, \dots, p_n] \subset \mathbb{P}$, we solve the *minmax* problem of the following form

$$\min_{\epsilon, u(\cdot), x(\cdot)} \max_{p_i \in \mathbb{P}} \epsilon \quad (4.8a)$$

$$s.t. \quad T \leq \epsilon \quad (4.8b)$$

$$x = (x_1, x_2), \quad (4.8c)$$

$$\dot{x} = T \begin{pmatrix} x_2(t; p_i) \\ u(t) - p_i \end{pmatrix}, \quad t \in [0, 1], \quad (4.8d)$$

$$x(0, p_i) = 0, \quad (4.8e)$$

$$x_1(1; p_i) \geq 10 \quad (4.8f)$$

$$x_2(t; p_i) \leq 4, \quad t \in [0, 1] \quad (4.8g)$$

$$x_2(1; p_i) \leq 0, \quad (4.8h)$$

$$T \geq 0, \quad (4.8i)$$

$$u(t) \in [-10, 10], \quad t \in [0, 1]. \quad (4.8j)$$

where p_i is one of the discretized point p_0, p_1, \dots, p_n from the \mathbb{P} . Therefore, for each $p_i \in \mathbb{P}$, we get a corresponding solution. In the end, we get a robustified parameter-dependent variables for realizations of the uncertain parameters. The bigger the number n , i.e. the more points of p_i , the more precise that the obtained solution can represent the whole uncertain set. In this classical approach, the driver has no prior knowledge about the value of the parameter p and gets no feedback during the process and has to set up the driving strategy in advance. The numerical implementation result of the classical approach is shown in section 4.5 when comparing that of the training approach.

4.4 Apply training (maxmin) approach

Contrast to the classical approach, in the training approach it is assumed that the driver of the rocket car is able to perform optimally for every p because of a preceding training period. We discretize the uncertainty set \mathbb{P} the same as in the classical approach, i.e. we take the discretized points p_0, p_1, \dots, p_n which cover the whole uncertainty set \mathbb{P} . For each $p_i \in [p_0, p_1, \dots, p_n] \subset \mathbb{P}$, we solve the problem

$$\max_{p_i \in \mathbb{P}} \min_{T, u(\cdot), x(\cdot)} T \quad (4.9a)$$

$$s.t. \quad x = (x_1, x_2), \quad (4.9b)$$

$$\dot{x} = T \begin{pmatrix} x_2(t; p_i) \\ u(t) - p_i \end{pmatrix}, \quad t \in [0, 1], \quad (4.9c)$$

$$x(0, p) = 0, \quad (4.9d)$$

$$x_1(1; p_i) \geq 10, \quad (4.9e)$$

$$x_2(t; p_i) \leq 4, \quad t \in [0, 1], \quad (4.9f)$$

$$x_2(1; p_i) \leq 0, \quad (4.9g)$$

$$T \geq 0, \quad (4.9h)$$

$$u(t) \in [-10, 10], \quad t \in [0, 1]. \quad (4.9i)$$

The solution of the training approach in this paper is, therefore, also a function of the realizations of the uncertain parameters. The numerical result will be shown in the next section 4.5.

4.5 Comparison numerical result of classical and training approach

For both the classical approach and the training approach, after the discretization of the uncertainty set, the problem to be solved becomes a normal optimal control problem and we can use the multiple shooting and quasi Newton (in the SQP framework) method to solve. We are leveraging open source package Gekko³ to solve our problem. The Gekko package can let the user choose different underlying nonlinear programming solver (APOPT, BPOPT, IPOPT, MINOS, SNOPT) and as well as different underlying numerical methods. In our case, we have chosen the sequential quadratic programming. Before we discuss the results from the classic approach and training approach, we discuss our primary analysis of the original problem 4.1.

First, we show the theoretical solution of T against different p values across the whole uncertainty set $\subset \mathbb{P} = [0, 9]$, as shown in Figure 4.1. Then, we remove the uncertainty by showing the solution for several chosen p_i values, where $p_i \in [p_0, p_1, \dots, p_n] \subset \mathbb{P} = [0, 9]$, here, we have chosen $p = 0$, $p = 5$, and $p = 9$ as the example for illustration. The T values (rounded to four decimals) and the theoretical $u(t)$ values corresponding to $p = 0$, $p = 5$, and $p = 9$, are shown in Figure 4.2.

³Please refer the website <https://gekko.readthedocs.io/en/latest/> for more information about this open source package




Figure 4.1: The theoretical optimal T values against p values in the uncertainty set, from the formulation 4.5





Figure 4.2: The theoretical $u(t)$ values when $p=0$, $p=5$ and $p=9$, from the formulation 4.6


When p takes fixed values, the OCP under uncertainty becomes a normal OCP problem and we can solve directly with the numerical methods discussed in Chapter 2, and no classical or training approach is needed. With the initial value of $u(t)$ set as $u(t_0) = 10$ and 500 subintervals $\mathbb{I}_j = [\tau_{j-1}, \tau_j]$, from the discretization points $0 = t_0 < t_1 < \dots < t_m = t_f = 1$, and an error tolerance level as $1e-6$, the result from solving a normal OCP with $p = 0$, $p = 5$ and $p = 9$ are shown in Figure 4.3, Figure 4.4 and Figure 4.5 respectively.

Based on these three Figures 4.3, 4.4 and 4.5, the results from $p = 0$, $p = 5$, and $p = 9$ are consistent with that from the theoretical results in formulation 4.5 and 4.6, as shown in Figure 4.1 and Figure 4.2. This confirms two points: first, the theoretical results are correct and second, the numerical methods we have chosen can solve our rocket car case with one fixed p value. These methods can, therefore, be used to solve general OCPs.



The numerical solution ($T= 2.9000100587$) with $p = 0$


Figure 4.3: Original rocket car problem 4.1 solution when $p=0$



The numerical solution ($T= 3.03334618$) with $p = 5$

Figure 4.4: Original rocket car problem 4.1 solution when $p=5$

5 Conclusion



The numerical solution ($T = 4.6053088162$) with $p = 9$

Figure 4.5: Original rocket car problem 4.1 solution when $p=9$

Part I

Appendix

A Lists

Bibliography

Ph. L. Toint A. R. Conn, N. I. M. Gould. Convergence of quasi-newton matrices generated by the symmetric rank one update. 1991.

John F. Zangrando David Morrison, James D. Riley. Multiple shooting method for two-point boundary value problems. 1962.

William C. Davidon. Variable metric method for minimization. 1959.

Powell M.J.D. Fletcher R. A rapid convergent decent method for minimization. 1963.

Stephen J. Wright Jorge Nocedal. Numerical optimization. 2006.

Holger Diedam Pierre-Brice Wieber Moritz Diehl, Hans Georg Bock. Fast direct multiple shooting algorithms for optimal robot control. *Fast Motions in Biomechanics and Robotics*, 2005.

Michael J. D. Powell. The bobyqa algorithm for bound constrained optimization without derivatives. *Technical Report, Department of Applied Mathematics and Theoretical Physics*, 2009.

Matthias Schlöder. Numerical methods for optimal control of constrained biomechanical multi-body systems appearing in therapy design of cerebral palsy. 2022.

Max A. Woodbury. Inverting modified matrices. 1950.
Erklärung:

Ich versichere, dass ich diese Arbeit selbstständig verfasst habe und keine anderen als die angegebenen Quellen und Hilfsmittel benutzt habe.

Heidelberg, den (Datum)