



A1X

Bench scale

Feature

- External Power supply: 230V(115V) AC.
 Internal rechargeable 6V DC Battery
- · Strong iron construction
- · High quality stainless steel plate
- · Built with fence (optional)
- Accumulating function
- · Auto power saving mode and auto off function
- · Selectable automatic power off
- · Suitable for industrial environment
- · Overload protection load cell
- Operating temperature : 0°C to 40°C
 Storage temperature: -25°C to 55°C
- High Resolution (×10) Display
- High bright red LED display
- Relative humidity : ≤ 85% non-condensing
- Built in RS-232 communication
- · Accurate and super stability
- · Easy to calibrate
- · 100% quality guarantee load cell and indicator

Optional:

Fence

RS-485 interface



Spesifikasi

Model Platter size (cm)	A1X Bench Scale						
	24 x 30	24 x 30	40 x 50	50 x 60	60 x 70	60 x 80	70 x 80
Capacity (kg)	6, 15	30, 60, 75	75, 150	150, 300, 500	300, 500, 600	300, 500, 600	300, 500, 600
Readability	0.5g, 1g	2g, 5g, 5g	5g, 10g	20g, 50g, 100g	50g, 100g	50g, 100g	50g, 100g
Dimension (cm)	41(L)x24(W) x38.5(H)	49.5(L)x30(W) x46(H)	40(L)x60(W) x66.5(H)	76.5(L)x60(W) x81.5(H)	70(L)x60(W) x103(H)	80(L)x60(W) x103(H)	80(L)x70(W) x103(H)
Product weight (kg)	6.52	5.42	9.33	17.36	33	36	39