



ACCURATE ELECTRONIC BALANCE



FSR-C

FUJITSU ELECTRIC CO.,LTD



ACCURATE ELECTRONIC BALANCE

FSR-C



This is the Basic Precision balance 0,1g is the with the heavy duty design.

Readability of this model easy to use and accurate

% Percentage Weighing

Easier calculate the percentage of the weighing.



Four Level Anti-Shock Adjustable Function



Very stable with adjustable feet.

AC-DC available

Flexible power supply more than and low energy - consuming, 48 hours operation with dry cells.




17 Units Available : g, ct, lb, oz, ozt, GN, dwt...

A lot of weighing unit, all weighing units available here.



Built with display temperature

Display the temperature area when weighing.



Anti-Radiate, Anti-Static Metal Housing

Anti - electrostatic weighing stable even in radio transmission activity.



Super size LCD display with backlight

Big LCD display, very easy to read, and readable in dark condition.



All aluminium casting house

Heavy duty with aluminium case.



Built in RS232

PC connection available, can connect to external display and also can connect to the external printer directly.



Time & Date setting

Help us to record the weighing time & date. Also can print out the date and time on the print result.



Weighing response time adjustable

user can adjust the speed of weight response



Counting and weighing

Faster counting with zero mistake.



Animal weighing function

User for weigh the animal when moving, the weigh will keep stable.



Dual Range

Depend on user's need. Can weigh more than expectation with the different readability.



Built in under hook

This function is for underweighing, mostly for jewellery and gold



Optional with rechargeable battery

This rechargeable battery is use for long time, suitable for un - electricity location.



Optional with density weighing

The density can be measured in density mode, with under hook function.



FSR-C



Item No.	Max Cap	Readability	Repeatability	Linearity	Work Temp	Pan Size	Housing Size
FSR-C2000	2000g/3000g	0.1g/0.2g	±0.1g/±0.2g	±0.2g/±0.2g	10°C - 35°C	168x168mm	295x208x88mm
FSR-C3000	3000g/5000g	0.1g/0.2g	±0.1g/±0.2g	±0.2g/±0.2g	10°C - 35°C	168x168mm	295x208x88mm
FSR-C4000	6000g/10kg	0.1g/0.2g	±0.1g/±0.2g	±0.2g/±0.2g	10°C - 35°C	168x168mm	295x208x88mm
FSR-C10000	10000g/15kg	0.1g/0.2g	±0.1g/±0.2g	±0.2g/±0.2g	10°C - 35°C	168x168mm	295x208x88mm

- Four level anti-Shock adjustable function
- Dual Range
- Anti-Radiate, Anti-Static Metal Housing
- Weighing Response time Adjustable
- 17 Units available : g, ct, lb, oz, GN, dwt...
- Counting and weighing
- AC-DC Available
- Built in Under Hook

- Super size LCD display with backlight
- Animal weighing function
- All Aluminium Casting Housing
- Built in RS232
- Time and Date Setting
- % Percentage weighing
- Built in display temperature
- Optional with density weighing
- Optional with rechargeable battery