1⃣ PHP Script – Count Number of Page Visits (Session Tracking)

Question

Write a PHP script to keep track of number of times the web page has been accessed (Use Session Tracking).

✅ **Code (session_counter.php)**

```
<?php

session_start();


if (!isset($_SESSION['count'])) {

  $_SESSION['count'] = 1;

} else {

  $_SESSION['count']++;

}


echo "<h2>You have visited this page ".$_SESSION['count']." times.</h2>";

?>
```

2⃣ PHP Script – Create student.xml & Display Students of Specific Course

Question

Write a PHP script to create a student.xml file containing rollno, name, address, college, course. After accepting a course as input, display student details of that course in table format.

(A) create_xml.php – Create XML File

```
<?php

$students = [

  ["1", "Rahul", "Pune", "SP College", "BCA"],

  ["2", "Priya", "Mumbai", "Modern College", "BCS"],

  ["3", "Amit", "Nashik", "SP College", "BCA"],
```

```
    ["4", "Sneha", "Pune", "Modern College", "BCOM"]
];

$xml = new SimpleXMLElement("<students></students>");

foreach ($students as $s) {
    $stu = $xml->addChild("student");
    $stu->addChild("rollno", $s[0]);
    $stu->addChild("name", $s[1]);
    $stu->addChild("address", $s[2]);
    $stu->addChild("college", $s[3]);
    $stu->addChild("course", $s[4]);
}

$xml->asXML("student.xml");

echo "student.xml created successfully!";
?>
```

(B) display_xml.php – Input Course & Display Table

```
<html>
<body>
<form method="post">
    Enter Course: <input type="text" name="course">
    <input type="submit" value="Search">
</form>
</body>
</html>
```

```php
<?php
if ($_POST) {
  $course = $_POST['course'];
  $xml = simplexml_load_file("student.xml");

  echo "<table border='1' cellpadding='5'>
      <tr>
        <th>Roll No</th><th>Name</th><th>Address</th><th>College</th><th>Course</th>
      </tr>";

  foreach ($xml->student as $stu) {
    if (strcasecmp($stu->course, $course) == 0) {
      echo "<tr>
        <td>$stu->rollno</td>
        <td>$stu->name</td>
        <td>$stu->address</td>
        <td>$stu->college</td>
        <td>$stu->course</td>
      </tr>";
    }
  }
  echo "</table>";
}
?>
```

---

3. PHP Script – Change Font Style/Size/Color/Background Using Cookies

Question

Write a PHP script to change preferences of webpage using cookies. 3 pages:

1. Select settings

2. Display chosen settings
3. Apply settings

Page 1: settings.php

```
<html>
<body>
<form method="post" action="save_cookie.php">
  Font Size: <input type="text" name="size"><br>
  Font Color: <input type="text" name="color"><br>
  Background Color: <input type="text" name="bg"><br>
  Font Style: <input type="text" name="style"><br>
  <input type="submit" value="Save Preferences">
</form>
</body>
</html>
```

Page 2: save_cookie.php

```
<?php
setcookie("size", $_POST['size']);
setcookie("color", $_POST['color']);
setcookie("bg", $_POST['bg']);
setcookie("style", $_POST['style']);

echo "<h2>Preferences Saved!</h2>";
echo "<a href='apply.php'>Click to Apply Settings</a>";
?>
```

Page 3: apply.php

```
<?php
```

```
$size = $_COOKIE['size'];
$color = $_COOKIE['color'];
$bg = $_COOKIE['bg'];
$style = $_COOKIE['style'];

echo "<body style='font-size:$size; color:$color; background:$bg; font-family:$style;'>";
echo "<h2>Your Custom Webpage</h2>";
echo "</body>";
?>
```

4⃣ PHP Script – Login with 3 Attempts Using Session

Question

Accept username & password. If correct in first 3 attempts show welcome message, otherwise show error. Use Session.

---

login.php

```
<?php
session_start();

if (!isset($_SESSION['attempts'])) {
  $_SESSION['attempts'] = 0;
}

if ($_SESSION['attempts'] >= 3) {
  echo "<h3>❌ Maximum attempts reached!</h3>";
  exit();
}
?>
```

```
<form method="post" action="check.php">
   Username: <input type="text" name="user"><br>
   Password: <input type="password" name="pass"><br>
   <input type="submit" value="Login">
</form>
```

---

check.php

```
<?php
session_start();

$correct_user = "admin";
$correct_pass = "1234";

$user = $_POST['user'];
$pass = $_POST['pass'];

if ($user == $correct_user && $pass == $correct_pass) {
   echo "<h2>Welcome $user!</h2>";
   session_destroy();
} else {
   $_SESSION['attempts']++;
   echo "<h3>Incorrect Credentials! Attempt: ".$_SESSION['attempts']."</h3>";
   echo "<a href='login.php'>Try Again</a>";
}
?>
```

5⃣ PHP Script – Many–Many Relationship & Show Students with 1st Rank

Question

Entities:
Student(Stud_id, name, class)
Competition(c_no, c_name, type)
Many–many relation → extra attributes(rank, year)

Task:

Accept competition name and display students who secured **1st rank**.

Database Structure (3NF)

Tables:

student

stud_id (PK)

name

class

competition

c_no (PK)

c_name

type

stud_competition

stud_id (FK)

c_no (FK)

rank

year

PRIMARY KEY(stud_id, c_no)

PHP Code

form.php

```
<form method="post" action="result.php">
  Enter Competition Name: <input type="text" name="cname">
  <input type="submit" value="Search">
</form>
```

---

result.php

```
<?php
$con = mysqli_connect("localhost", "root", "", "school");

$cname = $_POST['cname'];

$sql = "SELECT student.stud_id, student.name, student.class
      FROM student
      JOIN stud_competition ON student.stud_id = stud_competition.stud_id
      JOIN competition ON competition.c_no = stud_competition.c_no
      WHERE competition.c_name = '$cname'
      AND stud_competition.rank = 1";

$res = mysqli_query($con, $sql);

echo "<h2>Students with 1st Rank in $cname</h2>";

echo "<table border='1'>
<tr><th>ID</th><th>Name</th><th>Class</th></tr>";

while ($row = mysqli_fetch_assoc($res)) {
   echo "<tr>
         <td>".$row['stud_id']."</td>
         <td>".$row['name']."</td>
         <td>".$row['class']."</td>
       </tr>";
}
```

```
echo "</table>";
?>
```

---

6. Add JavaScript File in CodeIgniter – Check Positive/Negative Number

Question

Add a JavaScript file in Codeigniter. The JavaScript code should check whether a number is positive or negative.

Folder Structure

/application

/assets/js/check.js

/application/views/check_number.php

(A) JavaScript File: assets/js/check.js

```
function checkNumber() {
  let n = document.getElementById("num").value;

  if (n > 0)
    alert("Number is Positive");
  else if (n < 0)
    alert("Number is Negative");
  else
    alert("Number is Zero");
}
```

(B) View File: application/views/check_number.php

```
<html>
<head>
```

```
<script src="<?php echo base_url('assets/js/check.js'); ?>"></script>
</head>
<body>

<h3>Check Positive/Negative Number</h3>

<input type="number" id="num">
<button onclick="checkNumber()">Check</button>

</body>
</html>
```

7⃣ Create Item.xml (5 items) & Display Using PHP

Question

Create XML file Item.xml with item-name, item-rate, item-quantity for 5 items. Display XML records in tabular format using PHP.

(A) Item.xml

```
<items>
  <item>
    <name>Pen</name>
    <rate>10</rate>
    <quantity>50</quantity>
  </item>
  <item>
    <name>Notebook</name>
    <rate>40</rate>
    <quantity>20</quantity>
  </item>
```

```
  <item>
    <name>Bag</name>
    <rate>500</rate>
    <quantity>5</quantity>
  </item>
  <item>
    <name>Pencil</name>
    <rate>5</rate>
    <quantity>100</quantity>
  </item>
  <item>
    <name>Marker</name>
    <rate>25</rate>
    <quantity>30</quantity>
  </item>
</items>
```

(B) PHP Display Code: display_item.php

```
<?php
$xml = simplexml_load_file("Item.xml");

echo "<table border='1' cellpadding='5'>
<tr><th>Item Name</th><th>Rate</th><th>Quantity</th></tr>";

foreach ($xml->item as $i) {
  echo "<tr>
      <td>$i->name</td>
      <td>$i->rate</td>
      <td>$i->quantity</td>
```

```
    </tr>";
}
echo "</table>";
?>
```

---

8. Read book.xml Using simpleXML & Display Attributes + Elements

Question

Write PHP script to read book.xml into SimpleXML object and display attributes and elements.

Sample book.xml

```
<books>
  <book id="B1">
    <title>Java Programming</title>
    <author>Herbert Schildt</author>
    <price>500</price>
  </book>

  <book id="B2">
    <title>PHP Basics</title>
    <author>Rasmus Lerdorf</author>
    <price>350</price>
  </book>
</books>
```

PHP Script: read_book.php

```
<?php
$xml = simplexml_load_file("book.xml");

foreach ($xml->book as $b) {
```

```
  echo "<h3>Book ID: " . $b['id'] . "</h3>";
  echo "Title: " . $b->title . "<br>";
  echo "Author: " . $b->author . "<br>";
  echo "Price: " . $b->price . "<br><hr>";
}
?>
```

---

9. Read Movie.xml Using DOM Parser – Print MovieTitle & ActorName

Question

Read Movie.xml file & print MovieTitle and ActorName using DOM Document Parser (minimum 5 records).

Sample Movie.xml

```
<movies>
  <movie>
    <MovieNo>1</MovieNo>
    <MovieTitle>Leo</MovieTitle>
    <ActorName>Vijay</ActorName>
    <ReleaseYear>2023</ReleaseYear>
  </movie>

  <movie>
    <MovieNo>2</MovieNo>
    <MovieTitle>KGF</MovieTitle>
    <ActorName>Yash</ActorName>
    <ReleaseYear>2018</ReleaseYear>
  </movie>

  <movie>
```

```
    <MovieNo>3</MovieNo>
    <MovieTitle>Pushpa</MovieTitle>
    <ActorName>Allu Arjun</ActorName>
    <ReleaseYear>2021</ReleaseYear>
  </movie>

  <movie>
    <MovieNo>4</MovieNo>
    <MovieTitle>Dangal</MovieTitle>
    <ActorName>Aamir Khan</ActorName>
    <ReleaseYear>2016</ReleaseYear>
  </movie>

  <movie>
    <movie>
    <MovieNo>5</MovieNo>
    <MovieTitle>Pathaan</MovieTitle>
    <ActorName>Shahrukh Khan</ActorName>
    <ReleaseYear>2023</ReleaseYear>
  </movie>
</movies>
```

PHP Script: read_movie_dom.php

```
<?php
$dom = new DOMDocument();
$dom->load("Movie.xml");

$movies = $dom->getElementsByTagName("movie");
```

```
foreach ($movies as $m) {
   $title = $m->getElementsByTagName("MovieTitle")->item(0)->nodeValue;
   $actor = $m->getElementsByTagName("ActorName")->item(0)->nodeValue;

   echo "Movie: $title | Actor: $actor <br>";
}
?>
```

🔟 Display Student Table Records Using CodeIgniter

Question

Create student table (rollno, name, class) with 5 records. Using CodeIgniter, display all records.

(A) MySQL Table

```
CREATE TABLE student(
   rollno INT PRIMARY KEY,
   name VARCHAR(50),
   class VARCHAR(10)
);

INSERT INTO student VALUES
(1,'Rahul','10'),
(2,'Sneha','10'),
(3,'Amit','9'),
(4,'Priya','8'),
(5,'Rohan','9');
```

(B) Model: application/models/Student_model.php

```
<?php
class Student_model extends CI_Model {
```

```
  function getAll() {
    return $this->db->get("student")->result();
  }
}
?>
```

(C) Controller: application/controllers/Student.php

```
<?php
class Student extends CI_Controller {

  public function index() {
    $this->load->model("Student_model");
    $data['students'] = $this->Student_model->getAll();
    $this->load->view("student_view", $data);
  }
}
?>
```

(D) View: application/views/student_view.php

```
<table border="1" cellpadding="5">
<tr><th>Roll No</th><th>Name</th><th>Class</th></tr>

<?php foreach ($students as $s) { ?>
<tr>
  <td><?php echo $s->rollno; ?></td>
  <td><?php echo $s->name; ?></td>
  <td><?php echo $s->class; ?></td>
</tr>
```

```
<?php } ?>


</table>
```

---

11 Create Item.xml with 5 Items

(This is same as Question 7 part A; repeating here as asked)

```
<items>
  <item><name>Pen</name><rate>10</rate><quantity>50</quantity></item>
  <item><name>Notebook</name><rate>40</rate><quantity>20</quantity></item>
  <item><name>Bag</name><rate>500</rate><quantity>5</quantity></item>
  <item><name>Pencil</name><rate>5</rate><quantity>100</quantity></item>
  <item><name>Marker</name><rate>25</rate><quantity>30</quantity></item>
</items>
```

---

12 JavaScript Program Using Alert, Prompt & Confirm

Question

Write JS to display message
“Exams are near, have you started preparing for?” using alert.
Then accept two numbers using prompt & display addition using confirm.

JavaScript Code: exam.js

```
<script>
alert("Exams are near, have you started preparing for?");


var ans = confirm("Do you want to add two numbers?");
if (ans) {
  let a = parseInt(prompt("Enter first number:"));
  let b = parseInt(prompt("Enter second number:"));
  let c = a + b;
```

```
  alert("Addition = " + c);
} else {
  alert("You cancelled the addition.");
}
</script>
```

---

13. PHP Script — Many-to-Many (Event–Committee) & Update Committee Status

Question

Event (eno, title, date)
Committee (cno, name, head, from_time, to_time, status)
Many-to-many relationship.
Write PHP script to accept **title of event** and modify **status of committee = "working"**.

Database Design (3 tables)

event

eno (PK)

title

date

committee

cno (PK)

name

head

from_time

to_time

status

event_committee (junction table)

eno (FK)

cno (FK)

PRIMARY KEY(eno, cno)

Form: event_form.php

```
<form method="post" action="update_status.php">
   Enter Event Title: <input type="text" name="title">
   <input type="submit" value="Update Status">
</form>
```

---

update_status.php

```
<?php
$con = mysqli_connect("localhost", "root", "", "events");

$title = $_POST['title'];

$sql = "UPDATE committee
      SET status='working'
      WHERE cno IN (
         SELECT cno FROM event_committee
         WHERE eno = (SELECT eno FROM event WHERE title='$title')
      )";

if (mysqli_query($con, $sql)) {
   echo "<h3>Status Updated to 'working' Successfully!</h3>";
} else {
   echo "Error updating!";
}
?>
```

---

14. JavaScript Function to Validate Username & Password

Question

Write JS function to validate username and password for membership form.

Code

```
<script>
function validateForm() {
  let u = document.getElementById("user").value;
  let p = document.getElementById("pass").value;

  if (u == "") {
    alert("Username cannot be empty");
    return false;
  }

  if (p.length < 6) {
    alert("Password must be at least 6 characters");
    return false;
  }

  alert("Login Successful!");
  return true;
}
</script>

<form onsubmit="return validateForm()">
  Username: <input type="text" id="user"><br>
  Password: <input type="password" id="pass"><br>
  <input type="submit" value="Submit">
</form>
```

---

15. HTML + jQuery — Insert Text Before & After Paragraph

Question

Create HTML file to insert text before and after a paragraph using jQuery. Use before() and after().

Code: before_after.html

```
<html>
<head>
<script src="https://code.jquery.com/jquery-3.6.0.min.js"></script>
</head>

<body>
<p id="p1">This is a paragraph.</p>

<button id="b1">Insert Before</button>
<button id="b2">Insert After</button>

<script>
$("#b1").click(function() {
  $("#p1").before("<b>Text Inserted BEFORE paragraph<br></b>");
});

$("#b2").click(function() {
  $("#p1").after("<b><br>Text Inserted AFTER paragraph</b>");
});
</script>
</body>
</html>
```

---

16. PHP — Employee Table & Display Records Salary > 50000

Question

Create employee(emp_no, emp_name, address, salary) with 5 records. Display all records where salary > 50000.

MySQL

```
CREATE TABLE employee(
  emp_no INT PRIMARY KEY,
  emp_name VARCHAR(50),
  address VARCHAR(100),
  salary INT
);

INSERT INTO employee VALUES
(1,'Rohan','Pune',45000),
(2,'Sneha','Mumbai',65000),
(3,'Amit','Nashik',55000),
(4,'Priya','Pune',70000),
(5,'Karan','Thane',48000);
```

PHP Display Code: show_emp.php

```
<?php
$con = mysqli_connect("localhost", "root", "", "company");

$sql = "SELECT * FROM employee WHERE salary > 50000";

$res = mysqli_query($con, $sql);

echo "<table border='1'>
<tr><th>No</th><th>Name</th><th>Address</th><th>Salary</th></tr>";
```

```
while ($row = mysqli_fetch_assoc($res)) {
   echo "<tr>
        <td>".$row['emp_no']."</td>
        <td>".$row['emp_name']."</td>
        <td>".$row['address']."</td>
        <td>".$row['salary']."</td>
      </tr>";
}

echo "</table>";
?>
```

17⃣ JavaScript — Student Name Validation + Effects (onblur, onload, hover, click, mouseup)

Question

Accept student name:
✓ If name present → change font colour to **red** + size **18px**
✓ If empty → display image that **changes size** on events
Use **onblur, onload, onmouseover, onclick, onmouseup**

Code: student_effect.html

```
<html>
<body onload="init()">

Enter Student Name:
<input type="text" id="nm" onblur="checkName()">
<br><br>

<img id="img" src="pic.jpg" width="100" height="100"
    style="display:none;"
```

```
    onmouseover="big()"
    onclick="bigger()"
    onmouseup="normal()">

<script>
function init() {
   console.log("Page Loaded");
}

function checkName() {
   let n = document.getElementById("nm").value;

   if (n != "") {
      document.getElementById("nm").style.color = "red";
      document.getElementById("nm").style.fontSize = "18px";
   } else {
      document.getElementById("img").style.display = "block";
   }
}

function big() {
   document.getElementById("img").style.width = "150px";
}

function bigger() {
   document.getElementById("img").style.width = "200px";
}

function normal() {
```

```
  document.getElementById("img").style.width = "100px";
}
</script>


</body>
</html>
```

---

18. AJAX Program — Read contact.dat & Display Table

Question

Write AJAX program to read contact.dat and print data in table format on button click.
(contact.dat contains: srno, name, residence, mobile, address)

---

contact.dat

```
1,Rohan,2345678,9876543210,Pune
2,Priya,2233445,9123456780,Mumbai
3,Amit,4455667,9988776655,Nashik
```

HTML + AJAX File: ajax_contact.html

```
<html>
<head>
<script>
function loadData() {
  var x = new XMLHttpRequest();
  x.onreadystatechange = function() {
    if (this.readyState == 4 && this.status == 200) {
      let lines = this.responseText.split("\n");
      let out = "<table
border='1'><tr><th>SrNo</th><th>Name</th><th>Res</th><th>Mobile</th><th>Address</th></tr
>";
```

```
        for (let i = 0; i < lines.length; i++) {
          let f = lines[i].split(",");
          out += "<tr>";
          for (let j = 0; j < f.length; j++) {
            out += "<td>" + f[j] + "</td>";
          }
          out += "</tr>";
        }
        out += "</table>";

        document.getElementById("result").innerHTML = out;
      }
    };

    x.open("GET", "contact.dat", true);
    x.send();
  }
</script>
</head>

<body>

<button onclick="loadData()">Print Contacts</button>
<br><br>

<div id="result"></div>

</body>
</html>
```

---

19. AJAX – Server Responds While User Types Name

Question

Write AJAX program:

- User types name → server sends responses in real-time
- If empty → “Stranger, please tell me your name!”
- If name = Rohit, Virat, Dhoni, Ashwin, Harbhajan → “Hello, master !”
- Else → “, I don’t know you!”

(A) HTML + AJAX File: name_ajax.html

```
<html>
<head>
<script>
function checkName(str) {
  var x = new XMLHttpRequest();

  x.onreadystatechange = function() {
    if (this.readyState == 4 && this.status == 200) {
      document.getElementById("msg").innerHTML = this.responseText;
    }
  };

  x.open("GET", "server.php?name=" + str, true);
  x.send();
}
</script>
</head>
```

```
<body>

Enter Name:
<input type="text" onkeyup="checkName(this.value)">
<br><br>

<div id="msg" style="font-size:18px;color:blue;"></div>

</body>
</html>
```

(B) server.php

```
<?php
$name = $_GET['name'];

$masters = array("Rohit", "Virat", "Dhoni", "Ashwin", "Harbhajan");

if ($name == "") {
   echo "Stranger, please tell me your name!";
}
else if (in_array($name, $masters)) {
   echo "Hello, master !";
}
else {
   echo $name . ", I don't know you!";
}
?>
```

---

20. JavaScript – Onload Good Morning + Student Registration Form

Question

Show “Hello Good Morning” using alert on page load and display a student registration form.

Code: goodmorning_form.html

```
<html>
<body onload="msg()">

<script>
function msg() {
   alert("Hello Good Morning!");
}
</script>

<h2>Student Registration Form</h2>
<form>
Name: <input type="text"><br><br>
Class: <input type="text"><br><br>
Email: <input type="email"><br><br>
Mobile: <input type="text"><br><br>
<input type="submit" value="Register">
</form>

</body>
</html>
```

---

21 AJAX – Select Teacher & Display Details

Question

Create TEACHER(tno, tname, qualification, salary).
Write AJAX program to select teacher name from dropdown & display details.

(A) teacher table (SQL)

```
CREATE TABLE teacher(
  tno INT PRIMARY KEY,
  tname VARCHAR(50),
  qualification VARCHAR(50),
  salary INT
);

INSERT INTO teacher VALUES
(1,'Ramesh','MSc',45000),
(2,'Sneha','BEd',50000),
(3,'Kiran','MA',47000);
```

(B) HTML + AJAX File: teacher_ajax.html

```
<html>
<head>
<script>
function showTeacher(name) {
   var x = new XMLHttpRequest();

   x.onreadystatechange = function() {
      if (this.readyState == 4 && this.status == 200) {
         document.getElementById("result").innerHTML = this.responseText;
      }
   };

   x.open("GET", "teacher_server.php?tname=" + name, true);
   x.send();
```

```
}
</script>
</head>

<body>

<select onchange="showTeacher(this.value)">
  <option value="">Select Teacher</option>
  <option>Ramesh</option>
  <option>Sneha</option>
  <option>Kiran</option>
</select>

<br><br>
<div id="result"></div>

</body>
</html>
```

(C) teacher_server.php

```
<?php
$con = mysqli_connect("localhost","root","","school");

$name = $_GET['tname'];

$sql = "SELECT * FROM teacher WHERE tname='$name'";
$res = mysqli_query($con,$sql);
$row = mysqli_fetch_assoc($res);
```

```
echo "Teacher No: " . $row['tno'] . "<br>";
echo "Name: " . $row['tname'] . "<br>";
echo "Qualification: " . $row['qualification'] . "<br>";
echo "Salary: " . $row['salary'] . "<br>";
?>
```

---

22 AJAX – Auto Suggestions (Google-like)

Question

When user types in textbox, matching suggestions appear (using array).

HTML + AJAX: suggest.html

```
<html>
<head>
<script>
function showSuggestion(str) {
  var x = new XMLHttpRequest();

  x.onreadystatechange = function() {
    if (this.readyState == 4 && this.status == 200) {
      document.getElementById("sug").innerHTML = this.responseText;
    }
  };

  x.open("GET", "suggest.php?q=" + str, true);
  x.send();
}
</script>

</head>
```

```
<body>

Enter Text: <input type="text" onkeyup="showSuggestion(this.value)">
<br><br>
<div id="sug"></div>

</body>
</html>
```

---

suggest.php

```
<?php
$words = array("apple","banana","bat","car","cat","dog","doll","duster");

$q = $_GET['q'];
$s = "";

foreach ($words as $w) {
   if (strpos($w, $q) === 0) {
      $s .= $w . "<br>";
   }
}

echo $s == "" ? "No suggestions" : $s;
?>
```

---

23. AJAX – Book Details from XML (on selecting book name)

Question

Create XML file with book details.
Using AJAX, when user selects a book, display its details.

---

book.xml

```
<books>
  <book>
    <title>Java</title>
    <author>Schildt</author>
    <year>2021</year>
    <price>500</price>
  </book>

  <book>
    <title>PHP</title>
    <author>Rasmus</author>
    <year>2018</year>
    <price>350</price>
  </book>

  <book>
    <title>Python</title>
    <author>Guido</author>
    <year>2020</year>
    <price>600</price>
  </book>
</books>
```

HTML + AJAX: book_ajax.html

```
<html>
```

```
<head>
<script>
function getBook(title) {
  var x = new XMLHttpRequest();

  x.onreadystatechange = function() {
    if (this.readyState == 4 && this.status == 200) {
      document.getElementById("info").innerHTML = this.responseText;
    }
  };

  x.open("GET","book_server.php?title="+title,true);
  x.send();
}
</script>
</head>

<body>

<select onchange="getBook(this.value)">
  <option>Select Book</option>
  <option>Java</option>
  <option>PHP</option>
  <option>Python</option>
</select>

<br><br>
<div id="info"></div>
```

```
</body>
</html>
```

---

book_server.php

```
<?php
$xml = simplexml_load_file("book.xml");
$title = $_GET['title'];

foreach ($xml->book as $b) {
  if ($b->title == $title) {
    echo "Title: $b->title <br>";
    echo "Author: $b->author <br>";
    echo "Year: $b->year <br>";
    echo "Price: $b->price <br>";
  }
}
?>
```

---

24. jQuery – Insert Text Before & After Paragraph

Question

Use jQuery before() and after() to insert text.

---

insert_before_after.html

```
<html>
<head>
<script src="https://code.jquery.com/jquery-3.6.0.min.js"></script>
</head>

<body>
```

```
<p id="p1">This is a paragraph.</p>

<button id="b1">Insert Before</button>
<button id="b2">Insert After</button>

<script>
$("#b1").click(function(){
  $("#p1").before("<b>Inserted BEFORE<br></b>");
});

$("#b2").click(function(){
  $("#p1").after("<b><br>Inserted AFTER</b>");
});
</script>
</body>
</html>
```

✅ **25. PHP Script – Many-Many Relationship (Student–Competition)**

Tables in 3NF (RDB Design)

1. Student

Student(Stud_id, name, class)

2. Competition

Competition(c_no, c_name, type)

3. Student_Competition (Relationship Table)

Student_Competition(Stud_id, c_no, rank, year)

PHP Script

Form (competition_name.html)

```
<form method="POST" action="search_first_rank.php">
   Enter Competition Name: <input type="text" name="cname">
   <input type="submit" value="Search">
</form>
```

search_first_rank.php

```
<?php
$cn = mysqli_connect("localhost", "root", "", "college");

$cname = $_POST['cname'];

$sql = "SELECT s.Stud_id, s.name, s.class
      FROM Student s
      JOIN Student_Competition sc ON s.Stud_id = sc.Stud_id
      JOIN Competition c ON c.c_no = sc.c_no
      WHERE sc.rank = 1 AND c.c_name = '$cname'";

$result = mysqli_query($cn, $sql);

echo "<h2>Students With 1st Rank in $cname</h2>";
echo "<table border='1'>
<tr><th>ID</th><th>Name</th><th>Class</th></tr>";

while ($row = mysqli_fetch_assoc($result)) {
   echo "<tr>
         <td>".$row['Stud_id']."</td>
         <td>".$row['name']."</td>
         <td>".$row['class']."</td>
        </tr>";
}
```

```
echo "</table>";
?>
```

✅ **26. JavaScript Program – Fibonacci on onclick Event**

```
<html>
<body>
<h3>Fibonacci Series</h3>

<button onclick="printFib()">Click to Print</button>
<p id="result"></p>

<script>
function printFib() {
  let n1 = 0, n2 = 1, next;
  let output = n1 + " " + n2 + " ";

  for (let i = 3; i <= 10; i++) {
    next = n1 + n2;
    output += next + " ";
    n1 = n2;
    n2 = next;
  }
  document.getElementById("result").innerHTML = output;
}
</script>

</body>
</html>
```

✅ **27. CodeIgniter – Insert 5 Student Records**

Model: Student_model.php

```
<?php
class Student_model extends CI_Model {

  public function insert_students() {
    $data = [
      ["rollno"=>1, "name"=>"Amit", "class"=>"10"],
      ["rollno"=>2, "name"=>"Sneha", "class"=>"10"],
      ["rollno"=>3, "name"=>"Ravi", "class"=>"9"],
      ["rollno"=>4, "name"=>"Manoj", "class"=>"9"],
      ["rollno"=>5, "name"=>"Pooja", "class"=>"8"],
    ];

    $this->db->insert_batch("student", $data);
  }
}
?>
```

Controller: StudentController.php

```
<?php
class StudentController extends CI_Controller {

  public function add() {
    $this->load->model('Student_model');
    $this->Student_model->insert_students();
    echo "5 Records Inserted Successfully!";
  }
}
?>
```

✅ 28. PHP Script – Create and Add Elements to cricket.xml

Create cricket.xml (create_cricket.php)

```
<?php
$xml = new SimpleXMLElement("<CricketTeam></CricketTeam>");

$team = $xml->addChild("Team");
$team->addAttribute("country", "Australia");
$team->addChild("player", "David Warner");
$team->addChild("runs", "5000");
$team->addChild("wicket", "0");

$xml->asXML("cricket.xml");

echo "cricket.xml created!";
?>
```

Add India Team Players (add_india_team.php)

```
<?php
$xml = simplexml_load_file("cricket.xml");

$team = $xml->addChild("Team");
$team->addAttribute("country", "India");

$team->addChild("player", "Rohit Sharma");
$team->addChild("runs", "9000");
$team->addChild("wicket", "10");

$team = $xml->addChild("Team");
```

```
$team->addAttribute("country", "India");

$team->addChild("player", "Virat Kohli");
$team->addChild("runs", "12000");
$team->addChild("wicket", "5");

$xml->asXML("cricket.xml");

echo "India players added successfully!";
?>
```