Salesforce Certified Tableau Data Analyst

Practice Examination - Paper 2 (kimi2) - Questions

Questions	60 scored multiple-choice / multiple-select (real exam: 60 scored + 5 unscored)
Time limit	105 minutes
Passing score	65% (aim for 39+ correct here)
Domains	D1 Connect & Transform: 14 | D2 Explore & Analyze: 25 | D3 Create Content: 16 | D4 Publish &
Emphasis	LOD expressions, calculated fields, table calculations (by request)

Instructions: Choose the best answer. Items tagged *(Choose TWO/THREE)* require all correct options - no partial credit, exactly like the real exam. No notes, no Tableau, no internet. Answers with full explanations are in **kimi2-answers.pdf**.

Domain 1: Connect to and Transform Data (24%)

Q1. An analytics team builds dashboards on a production SQL Server that also runs the company's transactional systems. Dashboards take 30+ seconds to load during business hours, the DBA wants query load on the server reduced, and leadership confirms a nightly data refresh is acceptable. Which connection strategy should the analyst recommend?

A. Keep a live connection and add a data source filter to reduce rows
B. Keep a live connection but add an Initial SQL statement to speed up queries
C. Rewrite the connection using New Custom SQL with a WHERE clause
D. Create an extract of the data and schedule it to refresh once every night

Q2. You use Data menu, Replace Data Source to swap an old Excel source for a new database source. The fields are equivalent, but several were renamed in the new source, and many pills in existing sheets now show a red exclamation mark. What is the MOST efficient way to repair the workbook?

A. Rebuild every affected worksheet from scratch against the new source
B. Rename every field in the new data source to match the old names
C. Right-click each broken field and choose Replace References, pointing it to the matching field in the new source
D. Delete the red pills and drag the new fields onto the shelves again one by one

Q3. You connect to an Excel report where the first three rows contain a report title, a generated-on timestamp, blank rows, and merged cells above the real column headers. Tableau shows generic F1, F2, F3 field names. What should you use to fix this at connect time?

A. Connect with New Custom SQL and write a SELECT statement
B. Pivot the columns from the data source page
C. Turn on Use Data Interpreter for the sheet
D. Right-click each field and use Split

Q4. In Tableau Prep, a Sales Rep field contains inconsistent spellings such as 'Stephen', 'Steven', and 'Steve'. You want Prep to AUTOMATICALLY suggest which values to group. Which grouping algorithms are available as automated Group Values options? (Choose THREE) **(Choose THREE)**

A. Pronunciation
B. Common Characters
C. Spelling
D. Regular Expression
E. Fuzzy Clustering

Q5. You drag two tables onto the data source canvas and a noodle appears instead of a join clause. A colleague asks why row counts did not multiply the way a many-to-many join would. Which statement correctly describes relationships as compared with joins?

A. Relationships physically merge the two tables into one fixed table when you connect
B. Relationships preserve each table's native level of detail and combine the data at query time, while joins physically merge rows into a single table up front
C. Relationships require matching field names between tables while joins do not
D. Joins automatically prevent duplicate measures while relationships always duplicate them

Q6. You have twelve monthly CSV files with identical structure, all in the same folder. You want to stack them into one table in Tableau Desktop. Which statement about unions in Tableau Desktop is TRUE?

A. Unions require a WHERE clause to avoid duplicates
B. Unioned tables can come from different connection types (e.g., Excel plus SQL Server)
C. Tables must contain the same number of rows to be unioned
D. Unioned tables must come from the same connection/data source

Q7. Which scenario is the BEST reason to use data blending instead of a relationship or join?

A. Two tables in the same database that share the same grain and keys
B. You want the fastest possible query engine performance
C. Combining aggregated results from a secondary source that lives at a different level of detail and in a different data source than the primary
D. You need unrestricted row-level detail from both tables in every worksheet

Q8. Connected to Microsoft SQL Server, you need only the orders where Region is 'East' or 'West'. What should you do?

A. Double-click New Custom SQL and write: SELECT * FROM Orders WHERE Region = 'East' + Region = 'West'
B. Double-click New Custom SQL and write: SELECT * FROM Orders WHERE Region = 'East' OR Region = 'West'
C. Open the Data Interpreter tab and type the region names
D. Double-click New Custom SQL and write: SELECT * FROM Orders WHERE Region = 'East' AND Region = 'West'

Q9. A Product Key field contains values like 'OF-CA-2019-152156' and you need the four segments as separate columns, without writing any calculation. What is the quickest built-in approach?

A. Right-click the field in the data source page (or Data pane) and choose Split
B. Create aliases for each segment
C. Pivot the field into rows
D. Create four calculated fields using LEFT and FIND

Q10. Your extract is too large and slow to publish. Only data from 2024 onward is ever analyzed. Where should you configure the workbook so the extract physically stores less data?

A. Add Order Date to context on the Filters shelf
B. Create an integer parameter and use it in each worksheet
C. Add a filter on Order Date to the Filters shelf of every worksheet
D. In the Extract Data dialog, add a filter that keeps only Order Date on/after 2024 before creating the extract

Q11. Which of the following are valid OUTPUT types for a Tableau Prep flow? (Choose THREE) **(Choose THREE)**

A. A .hyper extract file
B. A published data source on Tableau Server or Tableau Cloud
C. A table written back to a database
D. A Tableau story
E. A .twb workbook

Q12. In Tableau Prep you must produce an output with exactly one row per Region + Segment and each combination's total sales. Which step and configuration accomplishes this?

A. Aggregate step: put Sales in Grouped Fields and Region + Segment in Aggregated Fields
B. Pivot step: rows to columns on Region
C. Clean step: group Region and Segment, then sum Sales
D. Aggregate step: put Region and Segment in Grouped Fields and Sales (SUM) in Aggregated Fields

Q13. YEAR(Order Date) on Columns gives you four discrete blue headers. You need a single unbroken time axis so that a line chart can display a trend line from the Analytics pane. What should you do?

A. Right-click the date pill and convert it to a continuous date (green pill), e.g., continuous Month
B. Convert the pill from a dimension to a measure
C. Add the date field to context
D. Change the field's data type to string

Q14. Dimension member 'Consumer' must appear as 'Consumer Purchase' in every view, but the underlying database values cannot be modified. What is the right feature?

A. Change the data type of Segment
B. Create a group named 'Consumer Purchase'
C. Write a calculated field with an IF statement for every report
D. Edit Aliases on the Segment dimension and rename the member for display

Domain 2: Explore and Analyze Data (41%)

Q15. Which expression returns each customer's total sales computed at the customer level, independent of the dimensions shown in the view?

A. TOTAL(SUM([Sales]))
B. SUM({FIXED : [Sales]})
C. {FIXED [Customer ID] : SUM([Sales])}
D. {INCLUDE [Customer ID] : SUM([Sales])}

Q16. For a cohort analysis you need, on every order row, the date of THAT CUSTOMER'S first purchase. The view itself is built at the order level. Which calculation gives the first purchase date per customer?

A. {FIXED [Customer ID] : MIN([Order Date])}
B. {INCLUDE [Order ID] : MIN([Order Date])}
C. MIN([Order Date])
D. WINDOW_MIN(MIN([Order Date]))

Q17. A view shows SUM(Sales) by State, plus a field Region Sales = {FIXED [Region] : SUM([Sales])}. You drag Category to the Filters shelf as a normal dimension filter (not context). What happens to Region Sales?

A. It is unchanged, because standard dimension filters are applied after FIXED LOD expressions are evaluated
B. It returns Null for all marks
C. It becomes an error until the filter is added to context
D. It recalculates to include only the selected categories

Q18. The view has one bar per Segment. You need the average ORDER SIZE per segment, meaning each order's total must first be computed at the Order ID level, then averaged. Which field, placed in the view with AVG, does this?

A. {FIXED [Segment] : AVG([Sales])}
B. {INCLUDE [Order ID] : SUM([Sales])}
C. AVG([Sales])
D. {EXCLUDE [Order ID] : SUM([Sales])}

Q19. A view has Region on Rows, then State on Rows (a drill-down to states inside each region), with SUM(Sales) on Text. Which expression gives each state's sales as a percentage of ITS REGION's total?

A. SUM([Sales]) / SUM({INCLUDE [Region] : SUM([Sales])})
B. SUM([Sales]) / TOTAL(SUM([Sales])) computed using Table (down)
C. SUM([Sales]) / SUM({FIXED : SUM([Sales])})
D. SUM([Sales]) / SUM({EXCLUDE [State] : SUM([Sales])})

Q20. What does {FIXED [Region] : MAX({INCLUDE [Customer ID] : SUM([Sales])})} return when used in a view by Region?

A. The grand total of sales per region
B. The average of all customer totals in each region
C. The value of the single largest transaction in each region
D. The total lifetime sales of the highest-spending customer within each region

Q21. Which statement correctly contrasts LOD expressions with table calculations?

A. LOD expressions are computed by the data source as part of the query at a defined granularity, while table calculations are computed locally on the aggregated table of results in the view

B. Table calculations query the underlying data source at row level; LODs only work on data already in the view

C. LOD expressions require at least two tables; table calculations require one

D. They are two names for the same engine

Q22. Which filters are evaluated BEFORE a FIXED LOD expression is computed, and therefore change its result? (Choose TWO) **(Choose TWO)**

A. Extract filters

B. Context filters

C. Standard dimension filters on the Filters shelf

D. Table calculation filters

Q23. Users must pick day, week, month, or year from a parameter and see the elapsed time between Order Date and Ship Date in that unit. The string parameter [Periodicity] holds valid datepart values. Which calculation works?

A. DATEDIFF('parameter', [Order Date], [Ship Date], 'Sunday')

B. DATENAME([Periodicity], [Ship Date])

C. DATEDIFF([Periodicity], [Order Date], [Ship Date])

D. DATEDIFF('Periodicity', [Order Date], [Ship Date])

Q24. Which calculation returns Sales only for dates from January 1 of the current year through today?

A. IF [Order Date] <= TODAY() OR DATETRUNC('year', [Order Date]) = DATETRUNC('year', TODAY()) THEN [Sales] END

B. IF [Order Date] <= TODAY() AND DATETRUNC('year', [Order Date]) = DATETRUNC('year', TODAY()) THEN [Sales] END

C. IF [Order Date] <= TODAY() AND DATETRUNC('month', [Order Date]) = DATETRUNC('year', TODAY()) THEN [Sales] END

D. IF [Order Date] > TODAY() AND DATETRUNC('year', [Order Date]) = DATETRUNC('year', TODAY()) THEN [Sales] END

Q25. An Email field holds values like 'amy@example.com'. Which expression returns 'example.com'?

A. DATENAME('domain', [Email])

B. LEFT([Email], FIND([Email], '@'))

C. SPLIT([Email], '@', 1)

D. RIGHT([Email], LEN([Email]) - FIND([Email], '@'))

Q26. Build a tier label: sales over 1,000 = 'High'; 500 to 1,000 = 'Medium'; everything else = 'Low'. Which calculated field is valid?

A. WHEN [Sales] > 1000 THEN 'High' END

B. CASE [Sales] WHEN > 1000 THEN 'High' WHEN >= 500 THEN 'Medium' ELSE 'Low' END

C. IF [Sales] > 1000 THEN 'High' ELSE [Sales] >= 500 THEN 'Medium' ELSE 'Low' END

D. IF [Sales] > 1000 THEN 'High' ELSEIF [Sales] >= 500 THEN 'Medium' ELSE 'Low' END

Q27. Why does a CASE statement fail for the requirement 'IF SUM(Sales) exceeds the region average THEN flag the customer'?

A. CASE cannot return strings

B. CASE can only compare a single expression for equality against literal values; conditional tests and comparisons against aggregates require IF/THEN

C. CASE requires a context filter first

D. CASE works but runs too slowly to be exam-relevant

Q28. A string field contains values like '15-Mar-2019'. Connected to an extract, which function converts it into a true date?

A. DATEPARSE('dd-MMM-yyyy', [Date String])

B. DATE([Date String])

C. DATENAME('day', [Date String])

D. MAKEDATE([Date String])

Q29. An equipment log lists: Barbell, Dumbbell, Jump Rope, Barbell, Dumbbell, Kettlebell. Which formula returns the number of DISTINCT items (4)?

A. ATTR([Equipment])

B. COUNTD([Equipment])

C. COUNT([Equipment])

D. MAX([Equipment])

Q30. AVG([Amount]) ignores rows where Amount is NULL. The business wants NULL treated as 0 inside the average. Which formula is correct? (Choose TWO - the two equivalent answers apply) **(Choose TWO)**

A. AVG(ZN([Amount]))

B. ZN(AVG([Amount]))

C. AVG(IFNULL([Amount], 0))

D. ZN(AVG(IFNULL([Amount], 0))) alone without changing semantics of ZN placement

Q31. In a crosstab of Sales by Category, what is the FASTEST way to display each category's share of the grand total?

A. Write {FIXED : SUM([Sales])} and divide

B. Add a parameter and a calculated field

C. Right-click SUM(Sales), choose Quick Table Calculation, Percent of Total

D. Add a grand total row from the Analytics pane

Q32. Which table calculation returns a 3-point trailing moving average of monthly sales that INCLUDES the current month?

A. WINDOW_AVG(SUM([Sales]), -2, 0)

B. RUNNING_AVG(SUM([Sales]))

C. WINDOW_AVG(SUM([Sales]), -3, 0)

D. WINDOW_AVG(SUM([Sales]), 0, 2)

Q33. A sorted bar chart shows 10 states by sales; two states tie for 3rd. A colleague is confused why INDEX and RANK differ for a label field. Which explanation is correct?

A. INDEX() works only on dates; RANK() only on strings

B. INDEX() assigns sequential positional numbers (1..N) by order of marks without regard to values and never has ties, while RANK() assigns rank based on the measure's values so tied marks share a rank

C. They are identical - the difference is cosmetic

D. INDEX() detects ties automatically and RANK() never does

Q34. For ascending values 100, 200, 200, 300, you need consecutive ranks with NO GAPS (1, 2, 2, 3). Which function?

A. RANK()

B. RANK_DENSE()

C. RANK_UNIQUE()

D. RANK_MODIFIED()

Q35. A crosstab has Region on Rows and YEAR(Order Date) on Columns, with Percent of Total on SUM(Sales). You want EVERY REGION ROW to sum to 100% across its years. Which addressing do you choose?

A. Compute Using > Table (across)

B. Compute Using > Table (down)

C. Compute Using > Cell

D. Compute Using > Order Date, restarting every Region

Q36. Viewers must choose how many top products, by sales, a chart displays (5, 10, or 20). What is the correct setup?

A. Create a parameter and add it to context on the Filters shelf

B. Write INDEX() <= [Parameter] and place it on Color

C. Type the parameter name into the filter's General tab search box

D. Create an integer parameter with the allowed values, then open the Product Name filter's Top tab, choose By field, and select the parameter instead of typing a fixed number

Q37. A Top 10 customers by sales filter returns unexpected names after users also pick a Region in a quick filter, because the Top-N was computed on ALL customers before the region quick filter applied. What fixes the logic?

A. Apply the Region filter to the Tooltip

B. Right-click the Region filter and choose Add to Context

C. Move the Region filter from Filters to the Marks card

D. Convert the Region filter to a measure filter

Q38. A 'Top 10 Customers' set must automatically update its membership whenever the extract refreshes with new orders. How should you build it?

A. Type ten customer names into a calculated field

B. Group the ten best customers with the paperclip icon

C. Lasso the current top 10 customers in the view and click Create Set from the tooltip

D. Right-click Customer, Create > Set, and define membership on the Top tab (Top 10 by SUM(Sales)) instead of selecting marks manually

Q39. A parameter can be surfaced to dashboard users inside WHICH of the following? (Choose THREE) **(Choose THREE)**

A. Calculated fields

B. Reference lines/bands as their value source

C. Filters such as Top N 'By field' value or measure filter thresholds

D. The stored database connection string of a published data source

E. The file path of a .hyper extract

Domain 3: Create Content (26%)

Q40. Which chart type best reveals the relationship (correlation) between Discount and Profit across hundreds of orders, including outliers?

A. Gantt chart

B. Scatter plot

C. Tree map

D. Pie chart

Q41. You must show monthly Sales as bars and Profit Ratio as a line in ONE chart with independent scales. What is the correct technique?

A. Create a combined axis chart by dragging one measure onto the other measure's axis

B. Place both measures on the same Rows shelf and choose Area

C. Use Measure Names/Measure Values with a single axis automatically

D. Drag Profit Ratio to the opposite edge of the view (or right-click its pill) to create a Dual Axis, then synchronize/adjust axes and set separate mark types on each Marks card

Q42. In a table of Sub-Category rows, business wants sub-categories sorted Descending by total Profit - even though the displayed measure is Sales. How?

A. Right-click the Sub-Category dimension > Sort > Sort By: Field (Profit, Sum), Descending

B. Click the ascending sort toolbar button while Sales is selected

C. Re-alias the sub-categories alphabetically

D. Drag SUM(Sales) to the left of Sub-Category on Rows

Q43. Three KPI sheets on a dashboard must resize proportionally together whenever the dashboard size changes. What should you use?

A. Set every sheet to Floating with fixed pixel positions

B. Place them inside one horizontal (or vertical) layout container, optionally using Distribute Contents Evenly

C. Convert the dashboard to tiled but put nothing in containers

D. Use a story instead of a dashboard

Q44. Which action types can be added from Dashboard > Actions? (Choose THREE) **(Choose THREE)**

A. Filter

B. Highlight

C. Go to URL

D. Send Email

E. Export to PDF

Q45. Users must switch one dashboard zone between a map and a bar chart via a drop-down. Which is the standard pattern?

A. Use a highlight action on the two sheets

B. Create two dashboards and a Go to URL action pointing to itself

C. Create a string parameter listing the view names, hook it to a calculated field placed on each sheet's Filters shelf that keeps the sheet only when the parameter matches that sheet's name, and size both sheets to the same container

D. Right-click the sheet and choose Swap with Sheet

Q46. Which dashboard object takes users to another dashboard or sheet when clicked, with a configurable target and button style?

A. Text object with a URL action

B. A legend set to floating

C. Navigation Button object

D. Image object sized to fit

Q47. Users complain that hovering marks shows 'Keep Only / Exclude' buttons inside the tooltip, causing accidental filtering. How do you remove them while keeping the rest of the tooltip?

A. Turn off tooltips at the Dashboard level

B. Delete the tooltip entirely

C. Set the mark to float

D. In the Edit Tooltip dialog, uncheck Include command buttons

Q48. Which menu path removes grid lines and zero lines from a worksheet, and where do you control alternating row banding?

A. Worksheet menu > Export

B. Format menu > Lines (set Grid Lines/Zero Lines to None) for lines; Format > Shading (Row Banding/Column Banding) for bands

C. Right-click field > Rename

D. Analysis menu > Totals

Q49. A dashboard must be usable on phones by field reps. What is the Tableau-recommended approach in Tableau Desktop?

A. Publish and let Tableau Cloud auto-generate perfect layouts for every device with no authoring

B. Set the worksheet Fit to Standard

C. Add a phone-sized image object

D. Use the Device Preview on the dashboard, add a Phone device layout, and customize it (arrange a phone-friendly subset of views)

Q50. Executives want a guided narrative: three sequential views of the same analysis, each with a caption, that they can page through. Which Tableau feature?

A. A fourth worksheet

B. Story with three story points

C. An extract refresh schedule

D. A nested container

Q51. You must label one spike in a line chart so the note stays attached to that specific data point as the data updates. Which annotation type?

A. Area annotation

B. Point annotation

C. A floating text object

D. Mark annotation

Q52. A map plots 500,000 taxi pickup points and overplotting makes hotspots unreadable. What converts it into an effective concentration heat map?

A. Drag Pickup Count onto Size

B. Right-click the map and choose Convert to Heat Map

C. Add a filled map on top

D. Change the Marks card mark type dropdown to Density

Q53. What does Tableau require/create when you build a histogram from Show Me?

A. Two measures and one date

B. A geographic role

C. A parameter plus three dimensions

D. A single measure; Tableau automatically creates a discrete bin field (with a suggested bin size you can edit) and counts records per bin

Q54. You must permanently merge the five smallest sub-categories into an 'Other' member in EVERY row of every view, while the big ones stay distinct. Which feature, and which if membership must update by a rule later?

A. Create a group on Sub-Category (paperclip); it is static re-labeling - if membership must be rule-driven and refresh-aware, use a set with a Top/Condition rule instead

B. Add a context filter

C. Make it a hierarchy

D. Create an extract refresh

Q55. Why is the Forecast option greyed out for a bar chart of Sales by discrete YEAR(Order Date)?

A. Forecasting requires a scatter plot

B. Forecasting only works on Tableau Cloud

C. Forecasting requires exactly 24 months of data

D. Forecasting requires a view with a continuous date (or continuous integer) field and at least one measure; the discrete year is a header, not a time axis

Domain 4: Publish and Manage Content on Tableau Server and Tableau Cloud (9%)

Q56. Which is a correct step sequence and option set when publishing a finished workbook from Tableau Desktop to a project on Tableau Cloud?

A. Export > PowerPoint, then upload the file

B. Server (or File) > Publish Workbook > sign in to the site > choose the project, name, which sheets to include (optionally Show Sheets as Tabs), and permissions

C. Save the .twb and email it to the site admin

D. File > Save As, choosing .hyper

Q57. A published extract on Tableau Cloud reads from an on-premises SQL Server behind the firewall. It must refresh daily. Which statement is correct?

A. Tableau Cloud always opens a tunnel to private databases automatically

B. Scheduling is impossible for extracts on Tableau Cloud

C. Convert the extract to a live connection first, then schedule

D. A refresh schedule alone cannot reach the on-prem database - you need Tableau Bridge running on a machine inside the network to keep that extract fresh (or make the source cloud-reachable)

Q58. A manager wants an email the moment a dashboard's daily sales drop below 10,000. What is required to create this data-driven alert?

A. Tableau Public

B. A parameter named exactly 'Alert'

C. A view with a continuous numeric axis on which you can set the alert condition/threshold (alert options are unavailable for non-numeric axes such as filled maps or Gantt without numeric axes)

D. A story point in presenter mode

Q59. The sales team must receive an email snapshot of the executive dashboard every Monday at 7 AM without signing in first. Which feature?

A. Subscriptions on a schedule, with recipients who have View permission (admins/owners can subscribe other users/groups)

B. A URL action to the team's inbox

C. Workbook optimizer rules

D. A new dashboard action

Q60. What is required to run a Tableau Prep flow automatically on a schedule on Tableau Server or Tableau Cloud?

A. A .tde file

B. The flow must be published and run via Tableau Prep Conductor, which is part of the Data Management add-on license

C. The desktop task scheduler opening Prep Builder nightly

D. Nothing - every licensed site schedules flows by default at no extra cost

END OF EXAM. Check your work against kimi2-answers.pdf.