SALESFORCE CERTIFIED TABLEAU DATA ANALYST

(ANALYTICS-DA-201)

ADVANCED PRACTICE EXAM 4 - 60 QUESTIONS

Questions	60 (mirrors the real exam's 60 scored items)
Time allowed	105 minutes - same as the real exam
Passing score	65% = 39 / 60 correct (this set is harder - aim for 45+)
Question types	Single choice, [SELECT TWO / THREE] multi-select, and [BUILD LIST] sequencing
Scoring	No partial credit - a multi-select or build-list item counts only when every part is exact
Navigation	Flag and return, as in the real exam; there is no penalty for guessing - answer everything

How to use this paper: this is the FOURTH advanced tier - a fresh 60-question set heavier than the real exam. By request it is weighted hard toward your weak spots: 12 hand-trace calculation questions (dates, strings, numbers, logic), 10 Level-of-Detail questions (FIXED/INCLUDE/EXCLUDE, nested LODs, filter timing), 8 table-calculation traces, plus 9 multi-select items where partial knowledge scores zero. Sections E-G keep the paper realistic with Domain 1/3/4 coverage. Trace every calculation on paper - do not guess.

Conventions: each question has exactly ONE correct answer unless marked otherwise. Items marked [SELECT TWO] need EXACTLY two correct choices. [BUILD LIST] items are correct only when the full letter sequence is right (write it like B-D-C-A). All questions are new - none repeat questions from advanced papers 1-3, the calculations drill, or the glm/kimi/deepseek/cheat-sheet series.

ANSWER EVERYTHING FIRST - THE ANSWER KEY (advanced-answers4.pdf) IS IN THE ANSWERS FOLDER - DO NOT OPEN IT UNTIL YOU FINISH.

SECTION A - CALCULATION TRACES: DATES, STRINGS, NUMBERS, LOGIC (Questions 1-12)

Domain 2.1 - write the result of each function by hand before reading the options. Watch argument order, boundary semantics, case sensitivity, and integer vs decimal math.

Question 1. Using Tableau's default date properties (weeks start on Sunday), what does the following return? (January 15, 2024 is a Monday; March 3, 2024 is a Sunday.)

```
DATEDIFF('week', #2024-01-15#, #2024-03-03#)
```

A. 6
B. 8
C. 7
D. 48

Question 2. What does DATEADD('month', 6, #2024-06-30#) return?

A. #2024-12-31#
B. #2024-06-30#
C. #2025-01-01#
D. #2024-12-30#

Question 3. A data source stores [Order Date] as a date and [Pick Time] as a time. Which expression produces a true datetime such as #2024-10-15 08:30:00#?

A. DATEPARSE([Order Date], [Pick Time])
B. MAKEDATETIME([Order Date], [Pick Time])
C. [Order Date] + [Pick Time]
D. DATE(STR([Order Date]) + STR([Pick Time]))

Question 4. The string field [Code] contains the value " AB " (between the quotes: two leading and three trailing spaces). What does LEN(TRIM([Code])) return?

A. 2
B. 7
C. 5
D. 4

Question 5. What does DATEADD('hour', 13, #2024-10-31 09:00:00#) return?

A. #2024-10-31 22:00:00#
B. #2024-10-31 21:00:00#
C. #2024-11-01 09:00:00#
D. An error - DATEADD does not support the 'hour' date part

Question 6. [Order ID] is stored as the number 12345. What does LEFT(STR([Order ID]), 2) return?

A. "45"
B. An error - LEFT requires a string, not a number
C. The number 12
D. "12"

Question 7. What does FLOOR(-9.4) return in Tableau?

A. -9
B. -9.4
C. -10
D. An error - FLOOR does not accept negative numbers

Question 8. On a row where [Is Loyalty] is TRUE, [Is Coupon] is FALSE, and [Is Clearance] is FALSE, what does this calculation return?

```
IF [Is Loyalty] OR [Is Coupon] AND [Is Clearance] THEN "Keep" ELSE "Drop" END
```

A. "Drop" - the expression is evaluated strictly left to right
B. NULL
C. An error - mixed AND/OR logic is not allowed
D. "Keep"

Question 9. A colleague writes the following calculation. What happens when it is saved?

```
IIF([Sales] > 1000 THEN 'High' ELSE 'Low' END)
```

A. It fails validation - IIF is a function that takes comma-separated arguments, not THEN/ELSE/END keywords
B. It returns "High" for every row
C. It returns "Low" for every row
D. It runs, but returns NULL for every row

Question 10. What does DIV(17, 5) return?

A. 3.4
B. 4
C. 2
D. 3

Question 11. On an extract data source, the field [Name] contains "Tableau Public". What does CONTAINS([Name], "TABLEAU") return?

A. TRUE - text search in Tableau is case-insensitive
B. NULL - CONTAINS cannot evaluate strings with spaces
C. FALSE - CONTAINS is case-sensitive
D. An error - CONTAINS only works on measures

Question 12. You need a sortable numeric period key such as 202410 from [Order Date] = #2024-10-15#. Which expression returns the NUMBER 202410?

A. YEAR([Order Date]) * 100 + MONTH([Order Date])
B. STR(YEAR([Order Date])) + STR(MONTH([Order Date]))
C. YEAR([Order Date]) + MONTH([Order Date])
D. DATENAME('year', [Order Date]) + DATENAME('month', [Order Date])

SECTION B - LEVEL OF DETAIL EXPRESSIONS (Questions 13-22)

Domain 2.8 - FIXED/INCLUDE/EXCLUDE, nesting, and filter interplay. For each trace, first ask: at what grain does the LOD compute, and has any filter stage already run before it?

Question 13. A view shows Region and Category with SUM(Sales) and the field {FIXED [Region] : SUM([Sales])}. The rows are: Alpha | Cat A = 60, Alpha | Cat B = 40, Beta | Cat A = 300. A normal (non-context) dimension filter excludes Category A, so only the Alpha | Cat B mark remains. What does the FIXED field display on that mark?

A. 40
B. 400
C. NULL
D. 100

Question 14. Regions total: East = 1,200 and West = 800. A normal dimension filter keeps only Category A (East Cat A rows = 300, West Cat A rows = 500). A second filter is the boolean calculation {FIXED [Region] : SUM([Sales])} > 1000, keeping True. Which regions appear, and why?

A. Both regions - FIXED expressions ignore all filters
B. Neither - the boolean LOD returns NULL once a dimension filter is present
C. Only East - the FIXED total (1,200) is computed before the Category filter, so East passes and West (800) fails
D. Only West - the dimension filter recomputes the totals to 300 and 500

Question 15. A view shows one mark per Region for Alpha (rows: 100 and 50) and Beta (row: 200). You add {EXCLUDE [Region] : AVG([Sales])}. What does the Alpha mark display?

A. 75
B. 350
C. NULL
D. 116.67

Question 16. At the Region level, East's underlying rows are: NY order 100, NY order 100, NJ order 300. You add AVG({INCLUDE [State] : SUM([Sales])}) to the view. What does the East mark display?

A. 250
B. 166.67
C. 500
D. 200

Question 17. Customer Amy placed orders on 2024-01-10 and 2024-03-05 (2024 is a leap year). A row-level view shows one mark per order, plus the dimension {FIXED [Customer] : MAX([Order Date])}. A second calculation DATEDIFF('day', [Order Date], {FIXED [Customer] : MAX([Order Date])}) evaluates each row. What does the January 10 row display?

A. 54
B. 0
C. -55
D. 55

Question 18. A view is at the Region level. East's underlying rows are: Boston order 100, Boston order 60, Austin order 80. You add AVG({FIXED [City] : SUM([Sales])}). What does the East mark display?

A. 240
B. 120
C. 80
D. 160

Question 19. Match each business requirement to the LOD that satisfies it: I. Show each customer's lifetime sales next to every one of their orders, whatever dimensions or dimension filters are in the view. II. In a view of Region broken down by State, each State row must also show its Region's total. III. In a Region-level view, show the average ORDER value rather than the average line-item value. Which option maps I, II, III correctly?

A. I = {FIXED [Customer] : SUM([Sales])}; II = {EXCLUDE [State] : SUM([Sales])}; III = AVG({INCLUDE [Order ID] : SUM([Sales])})

B. I = {FIXED [Customer] : SUM([Sales])}; II = {INCLUDE [Region] : SUM([Sales])}; III = {EXCLUDE [Order ID] : AVG([Sales])}

C. All three are solved with a FIXED LOD

D. I = {EXCLUDE [Customer] : SUM([Sales])}; II = {FIXED [Region] : SUM([Sales])}; III = {INCLUDE [Order ID] : AVG([Sales])}

Question 20. A view shows one mark per Region. West's cities total 100, 250, 350, and 500. You add the nested LOD {FIXED [Region] : MIN({FIXED [Region], [City] : SUM([Sales])})}. What does the West mark display?

A. 1,200

B. 100

C. 300

D. 250

Question 21. [SELECT TWO] Which TWO statements about nested LOD expressions such as {FIXED [Region] : AVG({FIXED [State] : SUM([Sales])})} are TRUE?

A. The inner expression is evaluated first, as if it were a standalone LOD, producing a value on every row

B. The outer expression then aggregates the inner expression's results

C. The inner expression must always be a FIXED LOD

D. LOD expressions can be nested at most two levels deep

Question 22. The data has three rows: customer A orders 60 and 40 (customer total 100), customer B orders 300 (customer total 300). On any worksheet, what does {FIXED : AVG({FIXED [Customer] : SUM([Sales])})} display?

A. 133.33

B. 400

C. 200

D. 100

SECTION C - TABLE CALCULATIONS (Questions 23-30)

Domain 2.2 - compute each one across the marks already in the view. Check addressing direction and pane boundaries before you touch the numbers.

Question 23. Monthly SUM(Sales) computed Table (across): Jan = 20, Feb = 40, Mar = 70, Apr = 90. You add WINDOW_AVG(SUM([Sales]), -1, 1). What does the April mark display?

A. 55
B. 70
C. 90
D. 80

Question 24. A crosstab has Region on Rows and Month on Columns. East: Jan 10, Feb 20, Mar 40. West: Jan 5, Feb 10, Mar 20. RUNNING_SUM(SUM([Sales])) is set to Compute Using Pane (across). What does the East-Mar cell display?

A. 40
B. 110
C. 70
D. 25

Question 25. [SELECT TWO] A view shows the 12 calendar months sorted descending by SUM(Sales). Which TWO approaches keep only the five highest-sales months on the view?

A. A table calculation filter INDEX() <= 5 computed down the sorted months
B. A distribution band showing the top 5 percentile
C. A filter on the Month dimension configured as Top: By Field: Top 5 by SUM(Sales)
D. A bin field of size 5 on the Sales measure

Question 26. Four products show SUM(Profit): P-A = 50, P-B = -20, P-C = 10, P-D = 80. RANK(SUM([Profit]), 'asc') is applied. Which product displays rank 1?

A. P-A
B. P-C
C. P-D
D. P-B

Question 27. The view has Region, then State nested on Rows. East contains states S1, S2, S3; West contains W1, W2 (five rows total). SIZE() is computed Pane (down). What do East's state rows display?

A. 5
B. 3
C. 1
D. 2

Question 28. [SELECT TWO] Which TWO statements about placing a table calculation on the Filters shelf are TRUE?

A. It hides marks from display without removing their rows from the query results
B. Other computations - like Percent of Total - still see the hidden marks, because table calculation filters run last in the filter pipeline
C. It shrinks the extract, because hidden rows are never read from the data source
D. It behaves identically to a measure filter on the same field

Question 29. A line chart has Region on Rows (one pane for East, one for West) and Month on Columns. East: 10, 20, 30. West: 40, 50, 60. A Moving Average covering the current and previous two values computes Pane (across). What does West's FIRST month display?

A. 40
B. 30
C. 25
D. 35

Question 30. Regions total: East 300, West 500, South 200 (company total 1,000). A normal dimension filter hides South. Management wants each REMAINING region's share of the FULL company total - East must display 30%. Which expression should be used?

A. A Percent of Total quick table calculation on SUM([Sales])
B. SUM([Sales]) / TOTAL(SUM([Sales]))
C. SUM([Sales]) / SUM({FIXED : SUM([Sales])})
D. RUNNING_SUM(SUM([Sales])) / TOTAL(SUM([Sales]))

SECTION D - FILTERS, ORDER OF OPERATIONS, PARAMETERS, SETS & STRUCTURES (Questions 31-36)

Domains 2.3-2.5 - the filter pipeline decides half of Domain 2. Know exactly where sets, Top N and context filters sit in that pipeline.

Question 31. [BUILD LIST] Tableau applies its query pipeline in a strict order. Arrange these six stages from FIRST applied to LAST applied.

A. Dimension filters are applied
B. Context filters are applied
C. Measure filters are applied
D. Sets, conditional filters, and Top N filters are computed
E. Extract filters are applied
F. Table calculation filters are applied

Question 32. A view shows the Top 10 products by SUM(Sales), built with the Product filter's Top tab. Users then flip the Category quick filter to Furniture - and only two products remain, because the Top 10 was computed across ALL categories first. They want the Top 10 within Furniture. What is the fix?

A. Convert the Top 10 filter into a FIXED set
B. Increase the Top count from 10 to 20
C. Drag the Category filter above the Product filter on the Filters shelf, so it runs first
D. Right-click the Category filter and choose Add to Context, so the Top 10 is computed inside the filtered subset

Question 33. [SELECT TWO] A 9,000-row customer list must be filtered to emails containing '@gmail.com'. Which TWO configurations on the Email dimension filter accomplish this?

A. Wildcard tab - match values that Contain "@gmail.com"
B. Condition tab - By Formula: CONTAINS([Email], '@gmail.com')
C. Top tab - By Field: Top 1 by MAX(Email)
D. A measure filter on COUNT([Email])

Question 34. [SELECT TWO] Which TWO statements about hierarchies are TRUE?

A. Tableau can only build hierarchies from geographic fields
B. You create a custom hierarchy by dragging one dimension on top of another in the Data pane (then naming it)
C. In the view, hierarchy fields show +/- controls that let users expand and collapse levels (for example Year to Quarter to Month)
D. Creating a hierarchy writes extra summary tables into the extract

Question 35. Set A = the Top 100 customers by SUM(Sales); Set B = customers whose total profit is negative. You need the customer list that is in BOTH sets. Which combined-set mode do you choose?

A. All members in both sets
B. Shared members in both sets
C. Set A except shared members
D. Combined sets cannot be built from condition-based sets

Question 36. [BUILD LIST] Users must switch a single line chart between Sales, Profit, and Quantity using a dropdown. Arrange the steps in the correct order.

A. Show the parameter control so users can pick a measure

B. Create a string parameter named Choose a Measure with the list: Sales, Profit, Quantity

C. Place the calculated field on Rows with a date on Columns, then test each parameter value and confirm the chart redraws correctly

D. Create a calculated field: CASE [Choose a Measure] WHEN 'Sales' THEN SUM([Sales]) WHEN 'Profit' THEN SUM([Profit]) WHEN 'Quantity' THEN SUM([Quantity]) END

SECTION E - CONNECT TO & TRANSFORM DATA (Questions 37-48)

Domain 1 - connections, extracts, unions/joins/relationships, Prep steps, and field customization.

Question 37. Executive dashboards must never show data more than 5 minutes stale. The source database is fast and lightly loaded, and IT policy forbids storing copies of the data outside the database. Which connection strategy do you choose?

A. An extract with an incremental refresh every 15 minutes
B. A packaged .tdsx snapshot refreshed twice a day
C. A live connection to the database
D. A scheduled .hyper extract refreshed every hour

Question 38. [SELECT TWO] Which TWO capabilities belong to EXTRACT (Hyper) connections and are NOT available on an equivalent live-relational connection?

A. Incremental refresh configured to append only new rows
B. The REGEXP_EXTRACT / REGEXP_MATCH family of string functions
C. Writing Custom SQL as the connection's query
D. Running Initial SQL when the session opens

Question 39. Eleven monthly CSV exports (Jan-Nov) are already stacked into one table. A December file with the identical column structure arrives. What is the correct way to add its rows to the same table?

A. Add the December file to the union (same-structured files stack vertically)
B. Join the December file on row number
C. Create a data blend on the month field
D. Relate the December file to the others on Order ID

Question 40. An Orders table holds many order lines per day. A separate Targets table holds one Sales Target per Month per Region. Analysts must compare monthly actuals to targets without any duplication. Which combining method should be built on the data source page?

A. An inner join on Region and Month - the target joins onto every matching line
B. A union of Targets onto the bottom of Orders
C. Converting the target into a parameter
D. A logical relationship between the two tables on Region and Month, letting each measure aggregate at its own table's grain

Question 41. [SELECT TWO] Which TWO operations can a Tableau Prep Clean step perform directly?

A. Schedule the flow to run every morning
B. Join two input tables on a key field
C. Trim whitespace and other quick text-cleaning operations on a field
D. Change a field's data type (for example String to Date or Number)

Question 42. On the data source page you select the four quarter columns Q1-Q4 of a budget table, right-click and choose Pivot. What does Tableau name the two generated columns by default?

A. "Pivot Field Names" and "Pivot Field Values"
B. "Quarter" and "Budget"
C. The names of the first pivoted column and its measure
D. "Column Name" and "Column Value"

Question 43. A Name column contains strings like "Smith, John, Jr.". You need exactly two columns: Last Name (Smith) and Remainder ("John, Jr."). Which approach works?

A. Automatic Split on the comma - it always produces exactly two fields

B. Custom Split with separator ", ", configured to split off the first 1 column

C. Turn on Data Interpreter

D. Pivot the Name column into rows

Question 44. A Prep flow must output exactly one row per Region per calendar Month with total sales and a distinct order count, aggregated from line-level transactions. Which step does this directly?

A. A Pivot step

B. A Clean step with a group values operation

C. A Join step on Region

D. An Aggregate step grouping by Region and Month of Order Date, aggregating SUM(Sales) and COUNTD(Order ID)

Question 45. In a Prep flow you union two tables. One names its key CustID, the other CustomerID, so the union shows two half-empty columns. What is the built-in way to combine them into one fully populated column?

A. Enable Data Interpreter before the union

B. Pivot the two columns into rows

C. In the Union step, select the two mismatched fields and choose Merge Fields

D. Re-run the union as a wildcard union

Question 46. A cleaned marketing list must be handed to an external media agency that uses no Tableau products. Which Prep Output type should the flow write?

A. A .hyper extract

B. A .csv file

C. A packaged data source (.tdsx)

D. A published data source on Tableau Cloud

Question 47. [SELECT TWO] Which TWO can be set as DEFAULT properties of a field in Tableau Desktop (right-click the field, Default Properties)?

A. The extract refresh schedule for that field

B. Default number format

C. Default aggregation (SUM, AVERAGE, etc.)

D. A list of values users are allowed to type into it

Question 48. A numeric [Employee ID] field is dragged to a view and Tableau shows SUM(Employee ID) and adds up the IDs - meaningless. You want the field to label and group rows instead. What is the correct fix?

A. Create a bin field from Employee ID

B. Change the default number format to remove decimals

C. Right-click the field and choose Convert to Dimension (or drag it to the Dimensions section)

D. Change its default aggregation from SUM to AVERAGE

SECTION F - CREATE CONTENT: CHARTS, DASHBOARDS, FORMATTING (Questions 49-56)

Domain 3 - chart construction, interactivity, device layouts, and formatting.

Question 49. Stakeholders ask: "How are our 80,000 invoice amounts distributed?" - they want the count of invoices falling in each 500-wide band so the shape (skew, clusters) is visible. Which chart answers this?

A. A histogram built on the binned invoice amount
B. A Pareto chart
C. A box plot of invoice amounts by region
D. A scatter plot of amount against customer

Question 50. A crosstab shows SUM(Sales) as text across Region rows and Month columns. Leadership wants the cell backgrounds shaded by value so high and low months pop (a classic highlight table), while keeping the numbers readable. What are the essential changes?

A. Remove SUM(Sales) from Text and leave the cells empty
B. Apply Format > Shading > Row Banding
C. Change the mark type to Pie and put Sales on Angle
D. Change the mark type to Square and put SUM(Sales) on Color (keeping it on Text)

Question 51. A dual-axis chart shows SUM(Sales) as bars and SUM(Profit) as circles, but the two axes auto-scaled independently (0-100K vs 0-40K), making profit look far stronger relative to sales than it is. What corrects the comparison?

A. Set both axes to independent scaling
B. Convert the profit axis to logarithmic
C. Right-click the secondary axis and choose Synchronize Axis
D. Fix only the primary axis range to start at zero

Question 52. A dashboard designed for desktop must also render sensibly on phones - with a DIFFERENT arrangement of its charts (stacked vertically, simplified). How is this accomplished?

A. Set the dashboard Size to Range and hope the tiled items rearrange themselves
B. Use Device Preview, choose Phone, and click 'Add Phone Layout' to design an alternate layout for that dashboard
C. Publish a second workbook sized for phones
D. Set every worksheet's Fit option to Entire View

Question 53. A click on a region's bar must store that region's NAME somewhere both the dashboard title and several calculated fields can read it immediately (for example: 'Details for West'). Which interactivity feature does this?

A. A filter action targeting the detail sheets
B. A highlight action on the Region field
C. A set action adding the region to a set
D. A parameter action that assigns the clicked mark's field value to a parameter

Question 54. On a published dashboard, users must be able to jump to a second dashboard inside the SAME workbook by clicking a labelled button - without leaving Tableau Server/Cloud or opening a browser page. What should the author add?

A. A URL action that pastes the dashboard's web address
B. A Navigation object (button) configured with Navigate To pointing at the target dashboard
C. A web page object displaying the target dashboard
D. A hyperlink typed into a caption

Question 55. Design wants the company's icon set available as mark shapes in Tableau Desktop on every analyst's laptop. Where do the image files go, and how are they picked up?

A. Edit Preferences.tps and register each shape, then restart

B. Copy the image files into the Shapes folder under My Tableau Repository (optionally in a named subfolder), then use Edit Shape > Reload Shapes / choose the palette

C. Drop the icons into Tableau's Program Files folder

D. Upload them to Tableau Cloud and they appear in every Desktop install

Question 56. On a scatter plot of order-level profit ratio, you must shade the region containing the middle 50% of orders - everything between the 25th and 75th percentile - so outliers above and below stand out. Which Analytics pane object and setting do you use?

A. Two stacked reference lines pinned at Q1 and Q3

B. A distribution band of +/- 1 standard deviation

C. A Distribution Band with the Percentile option set to 25 and 75

D. A trend line with a 50% confidence interval

SECTION G - PUBLISH & MANAGE ON SERVER / CLOUD (Questions 57-60)

Domain 4 - publishing, scheduling, governance, and site roles.

Question 57. Forty workbooks across the company all need the same governed definitions of Sales, Margin and Active Customer - maintained centrally and updated once. What should the analytics team do?

A. Email a packaged .tdsx to each workbook author whenever definitions change

B. Publish the data source to Tableau Server/Cloud (and certify it) so every workbook connects to the single governed source

C. Export the KPI formulas as CSV for analysts to re-type

D. Rebuild the definitions separately in each workbook from the workbook's revision history

Question 58. A regional VP wants a picture of the Executive Overview dashboard in her inbox at 08:00 every Monday - the exact view state, no login required. Which Server/Cloud feature does this?

A. A data-driven alert on the dashboard

B. A saved custom view

C. A subscription to the view on a weekly Monday-morning schedule

D. An extract refresh schedule

Question 59. A new analyst must be able to connect to brand-new database tables and flat files, build fully new workbooks in web authoring, and publish new data sources and flows to the site. Which site role is required?

A. Viewer

B. Explorer (can publish)

C. Creator

D. Site Administrator Explorer

Question 60. Each store manager wants the same published dashboard to remember THEIR OWN filter selections (region, date range) every time they open it - without changing what other managers see and without rebuilding views. Which feature provides this?

A. A subscription per manager

B. Duplicate the workbook once per store

C. A data quality warning pinned to the dashboard

D. Each manager saves a custom view of the dashboard

ANSWER SHEET (for self-marking)

Record your answers here while taking the exam, then check against advanced-answers4.pdf. For [BUILD LIST] items write the full sequence.

Q1	_____	**Q13**	_____	**Q25**	_____	**Q37**	_____	**Q49**	_____
Q2	_____	**Q14**	_____	**Q26**	_____	**Q38**	_____	**Q50**	_____
Q3	_____	**Q15**	_____	**Q27**	_____	**Q39**	_____	**Q51**	_____
Q4	_____	**Q16**	_____	**Q28**	_____	**Q40**	_____	**Q52**	_____
Q5	_____	**Q17**	_____	**Q29**	_____	**Q41**	_____	**Q53**	_____
Q6	_____	**Q18**	_____	**Q30**	_____	**Q42**	_____	**Q54**	_____
Q7	_____	**Q19**	_____	**Q31**	_____	**Q43**	_____	**Q55**	_____
Q8	_____	**Q20**	_____	**Q32**	_____	**Q44**	_____	**Q56**	_____
Q9	_____	**Q21**	_____	**Q33**	_____	**Q45**	_____	**Q57**	_____
Q10	_____	**Q22**	_____	**Q34**	_____	**Q46**	_____	**Q58**	_____
Q11	_____	**Q23**	_____	**Q35**	_____	**Q47**	_____	**Q59**	_____
Q12	_____	**Q24**	_____	**Q36**	_____	**Q48**	_____	**Q60**	_____

Score: ____ **/ 60 =** ____ **%** | Passing the REAL exam takes 39/60 (65%). On this harder set, 39+ means you are on track; 45+ means you are exam-ready. Review every explanation in the answer key - especially multi-selects you partially knew and any trace you guessed correctly.