Salesforce Certified Tableau Data Analyst — Practice Exam

Answer Key & Explanations (100 Questions)

Quick Reference Answer Key

Q	Ans	Q	Ans	Q	Ans	Q	Ans	Q	Ans
1	B	21	C	41	C	61	C	81	C
2	B	22	B	42	A	62	D	82	B
3	A, B, C	23	A	43	B	63	A	83	D
4	C	24	D	44	A	64	B	84	A
5	B	25	C	45	C	65	C	85	C
6	A	26	A	46	B	66	A	86	B
7	B	27	B	47	B	67	D	87	A, D
8	A, B	28	D	48	C	68	B	88	B
9	C	29	A	49	A	69	A	89	A
10	C	30	C	50	C	70	C	90	C
11	B	31	B	51	D	71	B	91	D
12	D	32	A	52	A	72	D	92	B
13	B	33	C	53	B	73	C	93	C
14	B, C	34	A	54	C	74	A	94	A
15	A	35	B	55	A	75	B	95	B
16	C	36	D	56	B	76	C	96	C
17	B	37	A	57	C	77	A	97	B
18	D	38	C	58	D	78	B	98	D
19	A, B, C	39	B	59	B	79	D	99	A
20	A	40	A	60	A	80	A	100	A, C

Note on multi-select items: Questions 3, 8, 14, 19, 87, and 100 are "Select TWO/THREE" items. On the real exam there is **no partial credit** — you must select all correct options.

Detailed Explanations

Domain 1: Connect to and Transform Data

Q1 — Answer: B (A live connection) Executives need near real-time data; extracts refresh only on scheduled intervals. A live connection queries the source on every interaction, so flash-sale transactions appear within minutes. Extract schedules (a, c, d) can't beat that latency. Rule of thumb: **live = real-time/low-latency; extract = performance, offline work, snapshots.**

Q2 — Answer: B (Create an extract and schedule a daily refresh) Extracts land in Tableau's high-performance `.hyper` engine, dramatically speeding dashboards over a slow legacy database. Data only needs to be current as of last night, so a daily refresh is enough. Live + filters (a) keeps the speed problem; Custom SQL (c) adds source load; blending (d) doesn't fix slow queries.

Q3 — Answer: A, B, C The extract dialog in Desktop offers: **filters** to limit rows, **aggregation to the level of visible dimensions**, and **incremental refresh** keyed on an identity/date column (plus options like "roll up dates to" and row sampling / Top N rows). Hierarchy auto-creation (d) is not an extract setting — hierarchies are built manually in the Data pane.

Q4 — Answer: C (Fields map only by identical names) Replace Data Source matches old → new fields **by name only**. Renaming `[State]` to `[Province]` breaks every shelf/calc referencing `[State]` (red exclamation errors) until the analyst remaps the field (right-click → Replace References). Tableau does not reconcile by geographic role or rename anything automatically.

Q5 — Answer: B (Data Interpreter) Data Interpreter detects the true header row and data region in **Excel** workbooks, skipping merged banner rows, notes, blank rows, and footers. (It works on Excel/Sheets-style files — not plain CSVs.)

Q6 — Answer: A (Pivot columns to rows) Wide survey data (Q1–Q20 as columns) becomes analyzable when pivoted to tall format: select the question columns, right-click → **Pivot**, producing "Pivot Field Names" (question) and "Pivot Field Values" (response). Data Interpreter cleans layouts but doesn't restructure columns.

Q7 — Answer: B (Split / Custom Split) Right-click the field → **Split** (automatic at the detected delimiter) or **Custom Split** (choose the – delimiter and which token(s) to keep). This creates computed fields (e.g., `US`) without touching the source.

Q8 — Answer: A, B Relationships (the default logical-layer model): **A** — Tableau generates smart join logic **at query time** using only the fields in the viz. **B** — each table keeps its **own level of detail**, avoiding the row duplication/loss a physical join might cause. They do **not** flatten tables at connection time (c describes a physical join) and tables don't need matching granularity (d).

Q9 — Answer: C (1,000 rows) A **left join from Orders to Returns** keeps every left-table row and appends matching right columns (NULLs where no match). All 300 returns match a single order with no fan-out, so the result is exactly the 1,000 order rows. Join cheat-sheet: **Inner = matches only; Left = all left; Right = all right; Full outer = everything.**

Q10 — Answer: C (Wildcard union) A union stacks same-schema files; a **wildcard search** (e.g., `Orders_*.csv`) automatically includes new monthly files dropped in the folder — no rework each month. Joins place columns side-by-side (wrong shape), blending is for cross-source granularity, Data Interpreter doesn't combine files.

Q11 — Answer: B (Data blend) The sources differ in **granularity** (quarterly targets per rep vs. transactional orders) and can't be joined in one data source. A **blend** makes targets primary and aggregates orders to the rep/quarter level via the linking field — the classic "actual vs. target" scenario.

Q12 — Answer: D (Custom SQL) Custom SQL lets the analyst write `SELECT ... WHERE ...` so the relational database filters/selects server-side before Tableau reads the results.

Available for relational connections (SQL Server, Oracle, MySQL, …), not files.

Q13 — Answer: B (Connect pane → Tableau Server) Published data sources are reached from Desktop via **Connect pane → Tableau Server / Tableau Cloud** → sign in → pick the site → select the source. This preserves the certified source's fields, hierarchies, and formats for the whole team.

Q14 — Answer: B, C

- **B — Data source filter** excluding test accounts applies to **every sheet** in the workbook built on that source.
- **C — Extract filter** on `[Order Date]` restricts the rows physically stored in the extract (smaller, faster extract). Context filters (a) and table-calc filters (d) act per view, not across the workbook.

Q15 — Answer: A (Union step) In Prep, a **Union** stacks inputs with matching columns (manual or wildcard union). It's the standard way to combine monthly files, regional exports, or partitions.

Q16 — Answer: C (Left join) `Orders` on the **left**, `Returns` on the **right**; keeping all orders regardless of returns = **Left join**. Inner would drop no-return orders; Right would keep returns without orders; Full outer keeps both sides' unmatched rows.

Q17 — Answer: B (Aggregate step) An **Aggregate step** groups rows by chosen fields (Region + month of Order Date) and computes SUM/AVG/etc., collapsing millions of transactions into a small monthly grain before output. Clean/Union/Pivot steps don't reduce cardinality this way.

Q18 — Answer: D (Pivot step — columns to rows) Months-as-columns (`Jan`…`Dec`) are unpivoted to rows via a **columns-to-rows pivot**, producing Month + Amount columns. (Rows-to-columns pivot is the reverse.)

Q19 — Answer: A, B, C Prep outputs: **file** (.hyper/.csv/.xlsx), **published data source** on Server/Cloud, or **database table** written back to a supported database. A `.twbx` (d) is a Desktop publishing artifact, not a Prep output.

Q20 — Answer: A (Alias) Aliases rename dimension members for display (`CA` → `California`) without touching the source or writing calculations. Limits: discrete dimension members only, no aliases for continuous fields or bins, and aliases can't be referenced in calculations.

Q21 — Answer: C (Convert discrete → continuous) A discrete (blue) date-part creates separate year headers, breaking the trend. Converting to **continuous** (green) draws one unbroken axis across years. Discrete fields make headers; continuous fields make axes — an exam favorite.

Q22 — Answer: B (Convert measure → dimension) Numeric fields like `[Rating]` default to measures and auto-`SUM`. Converting to a **dimension** exposes the distinct values as headers/categories (and lets you aggregate them with COUNTD, AVG, etc., where needed).

Q23 — Answer: A (Default Properties → Aggregation → Average) Right-click the field → **Default Properties → Aggregation → Average** so every *new* use of the field averages instead of summing. (Pill-level changes fix only the current view.)

Q24 — Answer: D (Group and Replace / Group Values) In Prep's profile pane, **Group and**

Replace consolidates variants (`USA`, `US`, `U.S.` → `United States`) via manual selection, common characters, or pronunciation — the cleanest fix for inconsistent member spelling.

Domain 2: Explore and Analyze Data

Q25 — Answer: C (DATEPARSE) `DATEPARSE("yyyyMMdd", [Order Date String])` converts a formatted string into a real date. `DATE()` casts existing date/datetime values only; `DATENAME/DATEPART` extract parts from a date. DATEPARSE works on specific connectors (Excel, text files, extracts, MySQL/Oracle/PostgreSQL, …).

Q26 — Answer: A (DATENAME) `DATENAME('month', date)` → string `"March"`. `DATEPART('month', date)` and `MONTH(date)` return the integer `3`. Need a **name/label** → DATENAME.

Q27 — Answer: B (DATEDIFF) `DATEDIFF('day', [Order Date], [Ship Date])` returns the number of day boundaries between the two dates — the standard date-arithmetic function. `DATEADD` shifts a date; `DATENAME/DATEPART` extract parts.

Q28 — Answer: D (SPLIT) `SPLIT([SKU], "-", 2)` splits on – and returns **token #2** (`1234`). Tokens are 1-indexed left-to-right; negative indexes count from the right. LEFT/MID rely on fixed positions, which SKU segments don't have.

Q29 — Answer: A (CONTAINS + UPPER) `CONTAINS()` is **case-sensitive**, so `CONTAINS(UPPER([Description]), "REFURB")` catches `Refurb`, `refurbished`, `REFURB`… The plain version (b) misses capitalized variants; = (c) requires exact match.

Q30 — Answer: C (IF/ELSEIF with correct thresholds and ordering) `IF [Sales] < 1000 THEN "Small" ELSEIF [Sales] < 10000 THEN "Medium" ELSE "Large" END` matches the defined bands exactly. Option (a) is invalid syntax — CASE tests **equality only**, no < ranges. Option (b) uses strict > on both boundaries, misclassifying exactly 1,000 as Small and exactly 10,000 as Medium. Option (d)'s IIF thresholds (10000/100000) don't match the defined tiers at all.

Q31 — Answer: B (CASE can't do ranges → use IF/THEN) `CASE field WHEN value … END` compares for **equality against a single field**. Range tests (`< 5000`) require `IF [Sales] < 5000 THEN "Low" … END`.

Q32 — Answer: A (ZN) `ZN([Discount])` returns the value if not NULL, else **0** — the go-to NULL-to-zero conversion for numeric arithmetic. `ISNULL()` returns TRUE/FALSE; `IFNULL` returns an *alternative value*; `INT()` truncates.

Q33 — Answer: C (Type conversion with STR) You can't concatenate string + number. `"FY " + STR(YEAR([Order Date]))` casts the number to string and yields `FY 2024`. Type-conversion functions (`STR`, `INT`, `FLOAT`, `DATE`, `DATETIME`) are heavily tested.

Q34 — Answer: A (AVG of a FIXED per-customer SUM) `{FIXED [Customer ID] : SUM([Sales])}` computes one total per customer; wrapping with `AVG()` averages those totals. `AVG([Sales])` (b) averages individual *transactions* — a different number. (d) fixes at Region, not Customer.

Q35 — Answer: B (FIXED LODs run before dimension filters; use a context filter) Order of operations: **extract filters → data source filters → context filters → FIXED LODs → dimension filters → measure filters → table calcs**. FIXED LODs ignore ordinary dimension

filters; adding `[State]` **to context** lifts it above FIXED LODs so the calc respects it.

Q36 — Answer: D (AVG of INCLUDE Customer ID) `{INCLUDE [Customer ID] : SUM([Sales])}` forces per-customer totals into the computation even though Customer isn't on the view; `AVG(...)` then averages them per city. FIXED ignores the view's granularity; EXCLUDE strips dimensions out.

Q37 — Answer: A (EXCLUDE as the denominator) Percent-of-parent: `SUM([Sales]) / SUM({EXCLUDE [Sub-Category] : SUM([Sales])})`. EXCLUDE removes Sub-Category from the denominator so it computes at Category level — the canonical LOD percent-of-parent pattern.

Q38 — Answer: C (Valid nested LOD) `{FIXED [Region] : MAX({INCLUDE [Customer ID] : SUM([Sales])})}` — inner INCLUDE builds per-customer totals, outer FIXED takes the max within each region. The other options are syntactically invalid (`FIXED MAX([Region]) ...`).

Q39 — Answer: B (Running Total, Table Across) Rows = Region, Columns = Months. Computing **Across** accumulates left-to-right within each region's row — a cumulative monthly total per region. Table Down (a) would accumulate down the regions inside each month.

Q40 — Answer: A (Previous 2, Next 0, include current) "Current month plus the two prior months" = trailing window $-2 \rightarrow 0$ with the current mark included (a 3-month moving average). Equivalent calc: `WINDOW_AVG(SUM([Sales]), -2, 0)`.

Q41 — Answer: C (Percent of Total, Table across then down) To make each cell a share of the **entire cross-tab**, use Percent of Total computed over the whole table — **Table (across then down)**. Table Down (a) or Pane-level (b) restrict the denominator to a column/pane, not the whole view.

Q42 — Answer: A (Percent Difference From → Previous) Percent Difference From with **Relative to: Previous** shows each mark as % change versus the prior position along the compute direction — the "+4.2%" month-over-month style.

Q43 — Answer: B (Ranks 1, 1, 3) Default `RANK()` = **competition ranking**: tied values share the rank and the next rank **skips**. 500, 500, 400 → 1, 1, 3. (`RANK_DENSE` → 1, 1, 2; `RANK_UNIQUE` → 1, 2, 3; `RANK_MODIFIED` → 2, 2, 1.)

Q44 — Answer: A (Percentile QTC + filter ≥ 90) The **Percentile** quick table calculation ranks each mark as a 0–100 percentile of the visible data; filtering to ≥ 90 isolates the top 10%. (Sorting + Top 10 (b) takes top 10 *rows*, not the top 10 *percent*.)

Q45 — Answer: C (Compound Growth Rate QTC) Compound Growth Rate computes the steady compounded per-period rate across the visible span — Tableau's native CAGR-style quick table calculation.

Q46 — Answer: B (INDEX() computed Table Down, filtered ≤ 10) `INDEX()` returns a mark's position in its partition; computed **Table Down** it numbers the sorted rows 1–500. Filtering `INDEX() <= 10` keeps the first ten **because table-calc filters apply after the calculation runs** — the numbering isn't recomputed per remaining marks.

Q47 — Answer: B (Filter → Top tab → By field: Top 10 by SUM(Sales)) The Top N **By field** option stays data-driven as data changes. Manual hide (a) and hand-picked sets (c) break on refresh; wildcards (d) match names, not rankings.

Q48 — Answer: C (Add the Region filter to context) Context filters execute *before* Top N in the order of operations, so the Top 10 is computed **within each region**. Without context, Top N is computed globally first, then Region filtering removes members — the classic exam trap.

Q49 — Answer: A (Wildcard → Contains) Dimension filter → **Wildcard** tab offers Contains / Starts with / Ends with / Exactly matches. "Contains Corp" hits the substring anywhere. Conditions (b) use formulas/aggregations; measure filters (c) need numeric fields.

Q50 — Answer: C (Measure filter: At least 0) Drag `[Profit]` to Filters and set **At least 0** — a **measure filter applies after aggregation**, so sub-categories with `SUM(Profit) < 0` drop out. An extract filter (b) shrinks the extract itself; dimension/context filters act on rows, not aggregates.

Q51 — Answer: D (Apply to Worksheets → All Using Related Data Sources) When sources share a matching field (`Region`), the filter's **Apply to Worksheets → All Using Related Data Sources** lets one filter drive sheets on both sources. Filters don't cross sources automatically (they need the shared field), and context/only-this-sheet options don't help.

Q52 — Answer: A (Float parameter × Sales + show the control) Parameters are workbook-global, viewer-adjustable values usable **inside calculations**: `[Sales] * [Exchange Rate]`; show the parameter control for interactivity. Parameters hold **one current value**, not per-row values — they're not filters or sets.

Q53 — Answer: B (Top tab → By field → pick the parameter) In the filter's Top tab, the "By field" value drop-down accepts a **parameter** (list of allowed values 5/10/20) — the standard way to make Top N user-switchable without rebuilding sheets.

Q54 — Answer: C (Reference line Value = parameter) Reference-line **Value** can bind to a parameter: create a numeric parameter with min/max/step (slider), add a reference line, set Value = that parameter. Moving the slider repositions the line — exactly exam objective 2.5.3.

Q55 — Answer: A (Sets must share the same dimension) Combined sets (union/intersection/difference) require both sets to be built on the **same dimension** — otherwise membership can't be meaningfully compared. High-Value Customers ∩ Return Customers works because both sets are on Customer.

Q56 — Answer: B (Create → Bins) Right-click the continuous measure → **Create** → **Bins**, confirm/edit the suggested bin size. The result is a new discrete dimension for histogram bucketing. Notes often tested: bins **can't be used in calculations**, can't be aliased, and bins ≠ groups.

Q57 — Answer: C (Build a hierarchy in the Data pane; drill with +/−) Drag `Sub-Category` onto `Category` in the Data pane → naming the hierarchy; place it on the view → pills show + / − for drill-down/roll-up. Hierarchies define reusable parent-child paths (Category → Sub-Category → Manufacturer).

Q58 — Answer: D (Group with "Include Other") Selecting the top states' headers → **Group**, then checking **Include "Other"** folds the remaining states into one rollup member while totals still cover **all** states. Sets (a) are IN/OUT subsets; bins (b) bucket measures; hierarchies (c) don't relabel anything.

Q59 — Answer: B (Filled map + polygon-capable geography) Filled maps (choropleth) shade **areas**, so the field needs polygon support (Country, State/Province, County, ZIP, …).

City points have no polygon — symbol maps only. Density maps (c) show point concentration, not regional shading.

Q60 — Answer: A (Density mark type + intensity) Set the Marks card type to **Density** and tune intensity on Color — Tableau renders overlapping points as a smooth heat gradient, ideal for huge point clouds. The other options don't visualize concentration.

Q61 — Answer: C (Symbol map: Sales → Size, Profit → Color) A **symbol map** plots a sized circle per location (Sales on **Size**) colored by a second measure (Profit on **Color**) — the standard two-measure store-location pattern.

Q62 — Answer: D (MAKEPOINT + Add a Marks Layer) Raw coordinates → geographic points via `MAKEPOINT([Latitude], [Longitude])`; then drag that field onto the existing map and choose **Add a Marks Layer** so the delivery points render as an independent second layer over the country polygons — two datasets, one map, no blending.

Q63 — Answer: A (Scope: Per Pane) Per Pane computes the aggregation separately inside each pane (per region) so every pane gets *its own* average line. Entire Table draws one global line across all panes; Per Cell computes per cell. Reference-line scope (table/pane/cell) is a frequently tested detail.

Q64 — Answer: B (Analytics pane → Trend Line → Exponential; Describe for stats) Drag **Trend Line** from the Analytics pane, choosing the **Exponential** model for multiplicative growth. Hover the line or right-click → **Describe Trend Line/Model** for **R^2 and p-value**. Models available: Linear, Logarithmic, Exponential, Polynomial (degree selectable), Power.

Q65 — Answer: C (Forecast from the Analytics pane + Forecast Options) Add **Forecast** to a continuous-date + measure view; **Forecast Options** set length (12 months), prediction interval (e.g., 95%), and seasonality/model type. Tableau forecasting uses **exponential smoothing**; you can override automatic seasonality with additive or **multiplicative** when seasonal swing scales with the level.

Domain 3: Create Content

Q66 — Answer: A (Bar chart) Bars compare discrete categories against a common baseline — the clearest choice for ranking fifteen sub-categories. Pies are limited part-to-whole; histograms show one continuous measure's distribution; box plots show spread/quartiles.

Q67 — Answer: D (Dimensions on Rows/Columns, measure on Label + Color, Square marks) The highlight-table recipe = cross-tab grid where the cell squares are colored by the measure value, with the figure displayed on **Label**. Show Me's "highlight table" sets this up automatically.

Q68 — Answer: B (Two continuous measures on opposite axes + row ID on Detail) Scatter plot: one measure on Columns, another on Rows, then **disaggregate** by placing `Order ID` on Detail — otherwise Tableau draws aggregated points. Dimensions can join on Color/Shape.

Q69 — Answer: A (Auto-creates a bin field; plots CNT per bin) A Show Me histogram from one continuous measure creates `[Age (bin)]` (suggested size editable later) and plots the **record count per bin** — no manual bin field needed. (Histogram requires exactly one measure in Show Me.)

Q70 — Answer: C (Tree map: Sales → Size, Profit → Color, dims on Label/Detail) Tree maps encode two measures well: rectangle **Size** (Sales) + rectangle **Color** (Profit), nested by dimensions (Category > Sub-Category) — a hierarchical part-of-whole with an extra metric channel.

Q71 — Answer: B (Gantt Bar + DATEDIFF on Size) Canonical Gantt: continuous date on Columns, tasks on Rows, mark type **Gantt Bar**, duration on **Size** via `DATEDIFF('day', [Start Date],[End Date])` — bars stretch from each task's start to its length.

Q72 — Answer: D (Box-and-whisker from Show Me on disaggregated profit) Box plots need a **disaggregated** measure (Analysis → uncheck Aggregate Measures, or a detail field). The Show Me box plot then draws median, quartile box, and whiskers (default $\pm 1.5\times$ IQR) — the best answer to "how is profit distributed with outliers?".

Q73 — Answer: C (Dual Axis on the second pill + sync decision + independent marks) Both measures on Rows → right-click the **second pill** → **Dual Axis**. Decide whether to **Synchronize Axis** (normally **no** here — bars in currency vs. ratio in % have different scales). Each measure keeps its own Marks card, so bars and lines style independently.

Q74 — Answer: A (Manual sort) Alphabetical order gives Large/Medium/Small. Right-click the pill → **Sort** → **Manual** → arrange Small → Medium → Large. Sort-by-Field (c) orders by a measure's value, which can't express this semantic ordering.

Q75 — Answer: B (Tiled H/V layout containers) Tiled objects snap into a resizing grid; nested **horizontal/vertical containers** keep multi-sheet sections aligned as the window changes. The Layout pane's **item hierarchy** manages nesting. Floating objects overlap and don't reflow.

Q76 — Answer: C (Fixed size 1200 × 800) Fixed size pins exact pixel dimensions — right for a fixed iframe where scroll is unacceptable. Automatic (a) fills the window (risk of awkward scaling); Range (b) flexes between min/max; new dashboards default to Fixed.

Q77 — Answer: A (Update refreshes the story point's snapshot) Story points are **snapshots** of the viz at capture time. Editing the source sheet flags the point with **Update**; clicking it refreshes the snapshot. Stories present sequentially with captions — they don't auto-track source edits.

Q78 — Answer: B (Device Preview → Phone layout) Dashboard tab → **Device Preview**: Tableau auto-generates Phone/Tablet/Desktop layouts; add and customize the **Phone layout** (rearrange/remove items) so viewers' phones get the tailored arrangement.

Q79 — Answer: D (Web Page object, optionally driven by a URL action) Drag a **Web Page object** onto the dashboard with a URL; pair it with a **URL action** so clicks on marks retarget the embedded page. Text/Image objects are static. (On Cloud/Server, the target page must allow framing; HTTPS expected.)

Q80 — Answer: A (Use as Filter) The **Use as Filter** funnel icon (upper-right of a selected dashboard view) wires that sheet to filter all others on selection — no action dialog needed; it creates an automatic filter action.

Q81 — Answer: C (Clearing the selection will: Leave the filter) In **Edit Filter Action**, *Clearing the selection will:* offers **Leave the filter** (keep the last-filtered state), **Show all values** (default reset), or **Exclude all values**. The exam tests knowing these three behaviors cold.

Q82 — Answer: B (URL action with a field-token template) URL action URL templates accept `<Field>` tokens: `https://en.wikipedia.org/wiki/<State>` fills per clicked mark. **Run on: Select** fires on click; **Menu** adds a tooltip hyperlink. A protocol prefix (http/https) is required.

Q83 — Answer: D (Highlight action on Hover) Highlight actions emphasize matching marks across views at full opacity while dimming non-matches — **without removing any rows** (filters remove rows). Run on Hover/Select/Menu; target selected fields vs all fields controls match granularity.

Q84 — Answer: A (Keep set values) Set-action clearing behaviors: **Keep set values** (persist clicked members — cumulative picking), **Add all values to set**, **Remove all values from set**. To accumulate customers across clicks, keep values on clear.

Q85 — Answer: C (Parameter action) Parameter actions write an interacted mark's value into a parameter — clicking a date sets `[Comparison Date]`, which drives the dashboard-wide reference line. Parameter actions can aggregate the source value and keep current value on clear.

Q86 — Answer: B (Param-driven filter per sheet in ONE shared container) Classic sheet-swap: a string parameter lists the chooser options; each candidate sheet filters on a calc like `[Selector] = 'Sales'`. Sheets filtered to nothing show no content and **collapse within the shared container**, letting the selected sheet fill the space. (Modern alternative: Dynamic Zone Visibility.)

Q87 — Answer: A, D

- **A — Dynamic Zone Visibility** (Layout tab → *Control visibility using value*) shows/hides a dashboard object from a **Boolean field/parameter** — e.g., reveal the detail panel only when exactly one category is selected (designer-driven, automatic).
- **D — Show/Hide button** on a **floating object** lets *viewers* toggle visibility (e.g., collapse a filter panel). Trend lines (b) and Data Interpreter (c) are unrelated.

Q88 — Answer: B (Viz in Tooltip) Edit the tooltip → **Insert** → **Sheets** → choose the trend sheet and set **max width/height**. The embedded viz auto-filters to the hovered mark (country) — the prototypical Viz-in-Tooltip scenario. Note the "filter on All Fields" behavior and tooltip command-button options.

Q89 — Answer: A (Mark annotation) Mark annotations attach to a specific mark's value: they move with the mark and become orphaned if the mark disappears on refresh. **Point annotations** pin to coordinates; **Area annotations** shade a region; text objects live on dashboards.

Q90 — Answer: C (Layout tab → Outer/Inner Padding) The dashboard **Layout tab** (per selected item) exposes **Outer Padding** (space around the item) and **Inner Padding** (space between border and content), plus background — the professional spacing toolkit. Worksheet gridlines (a) are separate.

Q91 — Answer: D (My Tableau Repository → Shapes, then Reload Shapes) Custom shape palettes live in **Documents ▸ My Tableau Repository ▸ Shapes ▸** `\<palette folder\` — each subfolder becomes a palette (transparent-background PNGs recommended). Click **Reload Shapes** in the Edit Shape dialog to pick up additions. Assigned shapes embed in the workbook, so they survive publishing. (Custom color palettes are defined separately in `Preferences.tps` — Desktop only.)

Domain 4: Publish and Manage Content on Tableau Server and Tableau Cloud

Q92 — Answer: B (Server → Publish Workbook workflow) Server → Publish Workbook: sign in, choose the **project**, set name/description/**tags**, pick which **sheets** to include, choose **Show sheets as tabs**, set permissions, and include external files if needed. Requires publish permission on the target project.

Q93 — Answer: C (Embed credentials + update the workbook to the published source) Embedding database credentials at publish time lets the server refresh extracts and render subscriptions without interactive sign-in — otherwise scheduled tasks fail on credential prompts. "**Update workbook to use the published data source**" repoints the open workbook at the shared source so everyone builds from one governed copy (which can be **certified** later).

Q94 — Answer: A (Export → Crosstab to Excel) Worksheet → Export → Crosstab to Excel writes the view's aggregated cross-tab into a new Excel file (or **Copy → Crosstab** to the clipboard). Use **Export → Data** for underlying rows. PDF (d) isn't editable.

Q95 — Answer: B (Subscription on a schedule) Subscriptions email a PNG/PDF snapshot of the view/workbook on a server **schedule** (Mondays 8 AM) to named recipients — no login needed to view the image. Requires SMTP configured by the admin plus embedded data credentials. Distinct from **alerts**, which fire on thresholds, not calendars.

Q96 — Answer: C (Incremental extract refresh keyed on Order ID) Incremental refresh appends only rows newer than the refreshed maximum of the identity column (`[Order ID]` here) — far faster than full reloads for append-only tables. Set it in the extract dialog and attach the extract to a server refresh schedule; Full refresh replaces everything.

Q97 — Answer: B (Publish the flow; create a scheduled flow task) Publish the Prep flow to Server/Cloud and link it to a **schedule/task** for unattended nightly runs. On **Tableau Server**, scheduling flows requires the **Data Management** add-on (Tableau Prep Conductor); on **Tableau Cloud**, flow scheduling is built in. Input/output credentials must be embedded so the server can authenticate unattended.

Q98 — Answer: D (Data-driven alert on the numeric axis) Data-driven alerts email recipients when a metric crosses a threshold (below 10,000). Requirements: the view needs a **continuous numeric axis**; the owner sets condition, recipients, and frequency (as often as possible / hourly / daily / weekly). Alerts ≠ subscriptions: alerts are threshold-triggered, subscriptions are schedule-triggered.

Q99 — Answer: A (Web editing: Creator/Explorer (can publish); Save As; Revert) Browser editing requires a **Creator** or **Explorer (can publish)** site role with the right content permissions. **Save** overwrites; **Save As** forks a new workbook; **Revert** returns the view to its last published state. Viewers can't edit (b).

Q100 — Answer: A, C

- **A — Embed the database credentials** with the extract at publish → refresh tasks and subscription snapshots can authenticate (no more credential failures).
- **C — Attach the extract to a server refresh schedule** → data stays current. Converting to live (b) just changes where authentication happens; subscription frequency (d) can't fix stale underlying data.

Score Tracker

Domain	Questions	Your Score	Weight	Comfortable Target
1 — Connect to and Transform Data	Q1–Q24	_ / 24	24%	≥ 18 / 24
2 — Explore and Analyze Data	Q25–Q65	_ / 41	41%	≥ 31 / 41
3 — Create Content	Q66–Q91	_ / 26	26%	≥ 20 / 26
4 — Publish and Manage Content	Q92–Q100	_ / 9	9%	≥ 7 / 9
Total	**100**	**_ / 100**	**100%**	**≥ 65 / 100 to pass**

The real exam uses compensatory scoring — you pass on the total, not per domain. But weak domains here tell you exactly where to focus before exam day. Good luck!