Answer Key & Explanations

Salesforce Certified Tableau Data Analyst - Practice Examination (kimi2)

Score yourself: correct / 60. Passing bar: 39 (65%). Review every explanation - the wrong-option notes are written to train exam-day elimination instincts.

Domain 1: Connect to and Transform Data (24%)

Question 1 - Correct answer: D

Objective 1.1 - Choose between live connection or extract

Correct: D. Create an extract of the data and schedule it to refresh once every night

Rationale: Extracts load data into Tableau's high-performance Hyper engine, which dramatically improves query speed, works offline, and removes query load from the production database. Because the business accepts nightly refresh latency, a scheduled nightly extract refresh is ideal. Initial SQL, data source filters, and custom SQL all still run against the live database and do not solve the performance/load problem.

Question 2 - Correct answer: C

Objective 1.1 - Replace the connected data source

Correct: C. Right-click each broken field and choose Replace References, pointing it to the matching field in the new source

Rationale: When a data source is replaced, Tableau matches fields by name; renamed fields break and show red exclamation marks. Replace References (right-click the invalid field) remaps the broken field to a valid one across every sheet that uses it, which is far faster than rebuilding or re-dragging fields. Renaming in the database is possible but usually not within the analyst's control.

Question 3 - Correct answer: C

Objective 1.2 - Prepare data by using Data Interpreter

Correct: C. Turn on Use Data Interpreter for the sheet

Rationale: Data Interpreter detects and strips out extraneous informational rows (titles, notes, blank rows), resolves merged cells, and correctly promotes the true header row, which is exactly the problem described. Pivot reshapes columns to rows, Split divides string fields, and custom SQL is not available for Excel files in this scenario.

Question 4 - Correct answer: A, B, C

Objective 1.3 - Tableau Prep cleaning: group values

Correct: A. Pronunciation; B. Common Characters; C. Spelling

Rationale: Tableau Prep's automated grouping options are Pronunciation (values that sound alike, e.g., Stephen/Steven), Common Characters (values sharing character sequences), Spelling (one-edit-apart spellings), plus combined modes such as Pronunciation + Spelling. Manual Selection exists but is not automated. Regular Expression and Fuzzy Clustering are not Prep grouping algorithms.

Question 5 - Correct answer: B

Objective 1.2 - Relationships vs joins

Correct: B. Relationships preserve each table's native level of detail and combine the data at query time, while joins physically merge rows into a single table up front

Rationale: Relationships (the default logical-layer model since 2020.2) keep tables separate and let Tableau stitch them together per-worksheet at query time, preserving each table's granularity and avoiding silent duplication. Joins run at the physical layer and produce one fixed denormalized table, which can inflate measures when cardinality is many-to-many.

Question 6 - Correct answer: D

Objective 1.2 - Union tables

Correct: D. Unioned tables must come from the same connection/data source

Rationale: In Tableau Desktop a union stacks rows on top of rows, and all unioned tables must come from the same connection (same Excel file's sheets, same folder of text files via wildcard union, same database). Cross-connection stacking is not a union: that would require data blending or Tableau Prep output. Row counts may differ freely.

Question 7 - Correct answer: C

Objective 1.2 - Blend data

Correct: C. Combining aggregated results from a secondary source that lives at a different level of detail and in a different data source than the primary

Rationale: Blending issues separate queries per data source and combines the already-aggregated results in the view on a shared linked dimension. It is designed for data at different levels of detail or data that cannot be joined directly (e.g., a published source plus a local file). It behaves like a left join on aggregated values and does not expose row-level secondary data.

Question 8 - Correct answer: B

Objective 1.1 - Custom SQL

Correct: B. Double-click New Custom SQL and write: SELECT * FROM Orders WHERE Region = 'East' OR Region = 'West'

Rationale: New Custom SQL is opened by double-clicking it in the data source page's left pane. A row can never be 'East' AND 'West' at once, so the AND version returns zero rows - the classic trap. The '+' operator is not valid logic here. Data Interpreter cleans messy spreadsheets; it does not filter relational data.

Question 9 - Correct answer: A

Objective 1.2 - Split

Correct: A. Right-click the field in the data source page (or Data pane) and choose Split

Rationale: Split uses the common delimiter (the hyphen) automatically and generates one calculated field per segment - no hand-written string parsing needed. LEFT/FIND works but is slower and error-prone; pivot reshapes structure rather than cutting strings; aliases only re-label existing members.

Question 10 - Correct answer: D

Objective 1.2 - Create extract filters

Correct: D. In the Extract Data dialog, add a filter that keeps only Order Date on/after 2024 before creating the extract

Rationale: Extract filters are defined in the Extract Data dialog and determine which rows are ever written into the .hyper file - so the file itself shrinks. Filters on the Filters shelf or in context only hide data in views; the full extract still exists underneath. Parameters by themselves do not filter anything.

Question 11 - Correct answer: A, B, C

Objective 1.3 - Tableau Prep output types

Correct: A. A .hyper extract file; B. A published data source on Tableau Server or Tableau Cloud; C. A table written back to a database

Rationale: A Prep flow's output step can write to a file (.hyper, .csv, .xlsx), publish a data source to Tableau Server/Cloud, or write to a database table. Stories and workbooks are built in Tableau Desktop/Cloud, not emitted by Prep.

Question 12 - Correct answer: D

Objective 1.3 - Shape data by using aggregations (Prep)

Correct: D. Aggregate step: put Region and Segment in Grouped Fields and Sales (SUM) in Aggregated Fields

Rationale: In an Aggregate step, fields placed under Grouped Fields define the output granularity, and measures placed under Aggregated Fields get an aggregation such as SUM. Swapping them inverts the grain, a Clean step performs no aggregation, and pivoting changes shape, not grain.

Question 13 - Correct answer: A

Objective 1.4 - Convert between discrete and continuous

Correct: A. Right-click the date pill and convert it to a continuous date (green pill), e.g., continuous Month

Rationale: Discrete (blue) dates produce separate headers per date part and cannot serve as the continuous axis a trend line requires. Converting the field to continuous (green) creates one unbroken axis over time, which enables trend lines and forecasts. Converting to measure, adding to context, or changing data type achieves none of this.

Question 14 - Correct answer: D

Objective 1.4 - Create aliases

Correct: D. Edit Aliases on the Segment dimension and rename the member for display

Rationale: Aliases change only the display label of a dimension member for the workbook; the stored data and any blend/join keys are untouched. A calculated field works but must be maintained and swapped into every view; a group restructures membership rather than re-labeling; data type changes are irrelevant.

Domain 2: Explore and Analyze Data (41%)

Question 15 - Correct answer: C

Objective 2.9 - FIXED LOD syntax

Correct: C. {FIXED [Customer ID] : SUM([Sales])}

Rationale: {FIXED [Customer ID] : SUM([Sales])} tells Tableau to aggregate sales at exactly the Customer ID grain regardless of what is in the view. INCLUDE adds the dimension to the view's existing grain (so the result still depends on the view), TOTAL() is a table calculation that obeys the view and its addressing, and option C is invalid syntax.

Question 16 - Correct answer: A

Objective 2.9 - FIXED LOD: cohort analysis

Correct: A. {FIXED [Customer ID] : MIN([Order Date])}

Rationale: A plain MIN() evaluates at whichever grain the view is using, so it just returns each order's own date at order level. The FIXED expression scans all rows per customer in the data source and returns their earliest order date, attachable to every order row for cohort bucketing. INCLUDE at Order ID grain again returns the order's own date, and WINDOW_MIN is a table calculation restricted to marks present in the view.

Question 17 - Correct answer: A

Objective 2.9 - FIXED LOD and the order of operations

Correct: A. It is unchanged, because standard dimension filters are applied after FIXED LOD expressions are evaluated

Rationale: Tableau's order of operations computes FIXED LODs (step 4, together with sets/Top N) before ordinary dimension filters (step 5). A non-context dimension filter therefore never reaches the FIXED expression - Region Sales still reflects ALL categories. If you need the filter respected, right-click it and Add to Context (context filters run at step 3, before FIXED).

Question 18 - Correct answer: B

Objective 2.9 - INCLUDE LOD

Correct: B. {INCLUDE [Order ID] : SUM([Sales])}

Rationale: The view's grain is Segment, which is coarser than Order ID. INCLUDE injects Order ID into the computation so SUM(Sales) is evaluated per order; wrapping the field in AVG() in the view then averages those order totals per segment. AVG([Sales]) averages row-level line items, not orders, and FIXED/EXCLUDE do not track the view's grain the way INCLUDE does.

Question 19 - Correct answer: D

Objective 2.9 - EXCLUDE LOD

Correct: D. SUM([Sales]) / SUM({EXCLUDE [State] : SUM([Sales])})

Rationale: The view grain is Region + State. EXCLUDE [State] drops State, so the denominator evaluates one level up - the region - exactly what is wanted. INCLUDE [Region] cannot lower the grain, so the denominator would equal the state's own sales (ratio always 1). TOTAL() with Table (down) sums the whole table, giving % of grand total across ALL regions. {FIXED : SUM(Sales)} is also the company grand total. Equivalent alternative: SUM(Sales) / SUM({FIXED [Region] : SUM(Sales)}), or a Percent of Total table calc computed using State.

Question 20 - Correct answer: D

Objective 2.9 - Nested LOD

Correct: D. The total lifetime sales of the highest-spending customer within each region

Rationale: The inner INCLUDE rolls sales up to the Customer grain (actually Region+Customer, since the outer FIXED declares Region). The outer FIXED then takes the MAX of those per-customer totals for each region - i.e., the best customer's lifetime spend per region. A single transaction would require MAX(Sales) at row level, and MAX is explicitly not SUM or AVG.

Question 21 - Correct answer: A

Objective 2.9 / 2.3 - LOD vs table calculation

Correct: A. LOD expressions are computed by the data source as part of the query at a defined granularity, while table calculations are computed locally on the aggregated table of results in the view

Rationale: LODs (FIXED/INCLUDE/EXCLUDE) translate into subqueries executed by the data source, so they see the underlying rows (respecting extract/context filters as applicable). Table calculations like RUNNING_SUM or LOOKUP execute inside Tableau against the aggregated result table in the view - they can never reach rows that are not in the view. This distinction drives performance and correctness decisions.

Question 22 - Correct answer: A, B

Objective 2.9 - Order of operations with FIXED

Correct: A. Extract filters; B. Context filters

Rationale: Order of operations: (1) extract filters, (2) data source filters, (3) context filters, then (4) FIXED LODs, and only afterwards (5) dimension filters and (7+) measure/table-calc filters. So extract, data-source, and context filters constrain the rows a FIXED LOD sees, while ordinary dimension filters do not.

Question 23 - Correct answer: C

Objective 2.1 - Date calculations with a parameter

Correct: C. DATEDIFF([Periodicity], [Order Date], [Ship Date])

Rationale: DATEDIFF requires the datepart as a string literal or from a field/parameter that evaluates to one - parameter references are used WITHOUT quotes. Quoting the parameter name ('Periodicity' or 'parameter') makes Tableau search for a literal unit called that and fails. DATENAME returns part of a single date, not a difference.

Question 24 - Correct answer: B

Objective 2.1 - Year-to-date calculation

Correct: B. IF [Order Date] <= TODAY() AND DATETRUNC('year', [Order Date]) = DATETRUNC('year', TODAY()) THEN [Sales] END

Rationale: Both tests must hold: the row must be in the current year (DATETRUNC to 'year' equality) AND not in the future (<= TODAY()). OR would admit every past year; '>' inverts the intent; and comparing a month-truncated date to a year-truncated today can never match. Note DATETRUNC keeps both sides at date granularity for a clean comparison.

Question 25 - Correct answer: D

Objective 2.1 - String functions

Correct: D. RIGHT([Email], LEN([Email]) - FIND([Email], '@'))

Rationale: FIND returns the 1-based position of '@'. LEN minus that position is exactly the number of characters after it, so RIGHT pulls the domain. LEFT would return 'amy@' (up to the @). SPLIT with token 1 returns the FIRST piece ('amy') - SPLIT([Email],'@',-1) or 2 would work, but wasn't offered. DATENAME is a date function.

Question 26 - Correct answer: D

Objective 2.1 - Logical expressions (nested IF)

Correct: D. IF [Sales] > 1000 THEN 'High' ELSEIF [Sales] >= 500 THEN 'Medium' ELSE 'Low' END

Rationale: Correct nested syntax is IF cond THEN value, ELSEIF cond THEN value, ELSE value, END. CASE in Tableau only compares one expression for equality against literal values - it cannot evaluate > or >= conditions, so the CASE-based variant is invalid. Writing ELSE followed directly by another condition (skipping ELSEIF) is a syntax error, and there is no WHEN-without-CASE construct.

Question 27 - Correct answer: B

Objective 2.1 - CASE limitations

Correct: B. CASE can only compare a single expression for equality against literal values; conditional tests and comparisons against aggregates require IF/THEN

Rationale: Tableau CASE performs simple switch-style equality matching (e.g., CASE [Segment] WHEN 'Consumer' THEN ...). Ranges, inequalities, boolean logic, and aggregate comparisons all require IF/ELSEIF/THEN/END. CASE returns any data type and has no performance or filter prerequisites.

Question 28 - Correct answer: A

Objective 2.1 - Type conversion with DATEPARSE

Correct: A. DATEPARSE('dd-MMM-yyyy', [Date String])

Rationale: DATEPARSE takes a pattern defining where each part sits in the string and returns a datetime - available for extracts and several database connections. DATE() only recasts values already understood as dates/numbers; DATENAME extracts a part FROM a date; MAKEDATE requires separate integer year, month, day arguments. An alternative valid approach is MAKEDATE(INT(RIGHT(...)), MONTH-part, INT(LEFT(...))), but only DATEPARSE is listed correctly here.

Question 29 - Correct answer: B

Objective 1.x/2.1 - Aggregate functions (COUNT vs COUNTD)

Correct: B. COUNTD([Equipment])

Rationale: COUNT counts rows (6, over-counting repeats). COUNTD counts distinct members (4). MAX on a string returns the alphabetically greatest string, and ATTR is a heterogeneity test returning an asterisk when a dimension has more than one member - none return 4.

Question 30 - Correct answer: A, C

Objective 2.1 - ZN / IFNULL handling of nulls

Correct: A. AVG(ZN([Amount])); C. AVG(IFNULL([Amount], 0))

Rationale: ZN and IFNULL are row-level functions, so they must run BEFORE the aggregation. AVG(ZN([Amount])) and AVG(IFNULL([Amount],0)) both convert null rows to zero first and then average over all rows. ZN(AVG(...)) applies ZN to the already-computed average, which never had null-row exclusion removed - so nothing changes.

Question 31 - Correct answer: C

Objective 2.3 - Quick table calculation: percent of total

Correct: C. Right-click SUM(Sales), choose Quick Table Calculation, Percent of Total

Rationale: Quick Table Calculation > Percent of Total transforms the measure in place with one right-click; the default addressing Table (across)/(down) resolves to share of total for a one-dimension table. The LOD approach is valid but slower to author, parameters add nothing here, and a grand total shows absolute values, not shares.

Question 32 - Correct answer: A

Objective 2.3 - Moving average / WINDOW_AVG

Correct: A. WINDOW_AVG(SUM([Sales]), -2, 0)

Rationale: WINDOW_AVG(expr, start, end) uses offsets relative to the current row: -2 to 0 spans the two previous marks plus the current one - three points in total. (-3, 0) would be four points, (0, 2) looks forward, and RUNNING_AVG averages back to the very first partition row rather than a fixed 3-month window.

Question 33 - Correct answer: B

Objective 2.3 - INDEX vs RANK

Correct: B. INDEX() assigns sequential positional numbers (1..N) by order of marks without regard to values and never has ties, while RANK() assigns rank based on the measure's values so tied marks share a rank

Rationale: INDEX is a positional counter over marks in the partition, so 1,2,3,4... always. RANK evaluates the specified measure, so tied values receive the same rank and (with default competition ranking) the following rank is skipped: 1,2,3,3,5. Neither is type-restricted.

Question 34 - Correct answer: B

Objective 2.3 - Ranking functions

Correct: B. RANK_DENSE()

Rationale: RANK() (competition) yields 1,2,2,4 - the gap after a tie. RANK_DENSE yields 1,2,2,3 with no skipped values. RANK_MODIFIED assigns tied marks the LOWER rank of their group (1,3,3,4), and RANK_UNIQUE forces 1,2,3,4 by breaking ties arbitrarily by row order.

Question 35 - Correct answer: A

Objective 2.3 - Compute using / addressing and partitioning

Correct: A. Compute Using > Table (across)

Rationale: Table (across) addresses the year columns within each region row and makes the row the partition, so each row's percentages add to 100%. Table (down) would make each YEAR COLUMN total 100% instead. Cell evaluates each mark alone (100% everywhere), and 'restarting every' Region is redundant since Region already partitions the table.

Question 36 - Correct answer: D

Objective 2.4/2.5 - Top N filter driven by a parameter

Correct: D. Create an integer parameter with the allowed values, then open the Product Name filter's Top tab, choose By field, and select the parameter instead of typing a fixed number

Rationale: The Top tab of a dimension filter lets you pick Top > By field > SUM(Sales), and the value control accepts a parameter - viewers then drive N from the parameter control. Context filters don't interleave with parameter values that way; INDEX() on Color only colors marks without removing them; the General tab has no such use of parameters.

Question 37 - Correct answer: B

Objective 2.4 - Add filters to context

Correct: B. Right-click the Region filter and choose Add to Context

Rationale: Context filters execute before Top N/conditional/set filters and FIXED LODs. Adding Region to context (its pill turns gray) makes Top 10 compute within the selected region's customers only - an 'inner' pre-filtered pass. Measure filters and Marks-card placement do not change execution order.

Question 38 - Correct answer: D

Objective 2.6 - Dynamic sets

Correct: D. Right-click Customer, Create > Set, and define membership on the Top tab (Top 10 by SUM(Sales)) instead of selecting marks manually

Rationale: A set defined by a computed rule (Top tab by field, or a Condition) re-evaluates on every refresh/query, so membership is dynamic. Lasso-creating and manual name lists freeze the members you picked at authoring time; groups are static re-labelings, not rule-based subsets.

Question 39 - Correct answer: A, B, C

Objective 2.5 - Parameters for interactivity

Correct: A. Calculated fields; B. Reference lines/bands as their value source; C. Filters such as Top N 'By field' value or measure filter thresholds

Rationale: Parameters are workbook-level variables that plug into calculations, reference lines (set the line's Value to the parameter), and filter thresholds (e.g., Top N by field, or a calc placed on Filters). They cannot rewire physical connection details such as credentials or file paths.

Domain 3: Create Content (26%)

Question 40 - Correct answer: B

Objective 3.1 - Choose the right chart

Correct: B. Scatter plot

Rationale: Scatter plots place one continuous measure on each axis and one mark per order, exposing direction, strength, and outliers of the bivariate relationship - and support trend lines. Pies show part-to-whole for a handful of members, tree maps sized hierarchical parts, and Gantt charts durations.

Question 41 - Correct answer: D

Objective 3.1 - Dual axis / combo chart

Correct: D. Drag Profit Ratio to the opposite edge of the view (or right-click its pill) to create a Dual Axis, then synchronize/adjust axes and set separate mark types on each Marks card

Rationale: Dual axis stacks two independent axes and gives each measure its own Marks card so one can be Bar and the other Line; right-click an axis to Synchronize (usually undesirable for mixed units like $ and %, so keep unsynchronized). A combined axis shares one scale - wrong for different units; Measure Values on one axis has the same problem.

Question 42 - Correct answer: A

Objective 3.1 - Custom sort

Correct: A. Right-click the Sub-Category dimension > Sort > Sort By: Field (Profit, Sum), Descending

Rationale: A field-based manual sort on the dimension lets you order members by any field/aggregation/direction, independent of the measure displayed. The toolbar button sorts by the measure in the view (Sales, not Profit), moving pills changes structure not order, and aliases only change labels.

Question 43 - Correct answer: B

Objective 3.2 - Layout containers

Correct: B. Place them inside one horizontal (or vertical) layout container, optionally using Distribute Contents Evenly

Rationale: Containers group tiled objects so they resize and reposition proportionally as one unit - the core of responsive dashboard layout. Floating fixes objects at absolute coordinates and they will overlap or drift when size changes; a story is a narrative sequence, not a resizing strategy.

Question 44 - Correct answer: A, B, C

Objective 3.3 - Dashboard actions

Correct: A. Filter; B. Highlight; C. Go to URL

Rationale: Dashboard actions include Filter, Highlight, Go to URL, Go to Sheet, Change Parameter, and Change Set Values. 'Send Email' and 'Export to PDF' are not action types - subscriptions handle scheduled emails, and export is a viewer menu function.

Question 45 - Correct answer: C

Objective 3.3 - Swap sheets using parameters

Correct: C. Create a string parameter listing the view names, hook it to a calculated field placed on each sheet's Filters shelf that keeps the sheet only when the parameter matches that sheet's name, and size both sheets to the same container

Rationale: The classic sheet-swap uses a parameter + a show/hide calculated filter (e.g., [View Selector] = 'Map') so only the selected sheet renders; both sheets sit in the same layout space. There is no native 'Swap Sheet'; highlight actions don't hide sheets; URL reloads are heavy and unnecessary. (Collapsible show/hide buttons on floating containers are the modern alternative.)

Question 46 - Correct answer: C

Objective 3.3 - Navigation buttons

Correct: C. Navigation Button object

Rationale: The Button/Navigation object (Dashboard pane, Objects) has a Navigate To target (sheet or dashboard) plus image/text styling. Text objects can hold hyperlinks but are not purpose-built navigation controls; images and legends don't navigate natively. (Related: floating containers can also get a Show/Hide toggle button.)

Question 47 - Correct answer: D

Objective 3.4 - Tooltips

Correct: D. In the Edit Tooltip dialog, uncheck Include command buttons

Rationale: The tooltip editor's Include command buttons option controls exactly those interactive Keep Only/Exclude links. The tooltip content itself remains; the other options remove tooltips completely or do nothing relevant.

Question 48 - Correct answer: B

Objective 3.4 - Formatting: grid lines and banding

Correct: B. Format menu > Lines (set Grid Lines/Zero Lines to None) for lines; Format > Shading (Row Banding/Column Banding) for bands

Rationale: Format > Lines governs grid lines, zero lines, trend lines, axis rulers; Format > Shading governs row/column banding and pane/header shading. Other menus have nothing to do with worksheet chrome of this kind.

Question 49 - Correct answer: D

Objective 3.4 - Device layouts

Correct: D. Use the Device Preview on the dashboard, add a Phone device layout, and customize it (arrange a phone-friendly subset of views)

Rationale: Device Preview lets you assign device layouts (Desktop/Tablet/Phone, generic or specific models) to a dashboard; Tableau can generate a default phone layout which you then customize. Items exist per layout - nothing else listed controls device rendering.

Question 50 - Correct answer: B

Objective 3.2 - Stories

Correct: B. Story with three story points

Rationale: Stories are sequences of story points (each holding a sheet or dashboard, with caption text and optional duplication/update behavior) designed exactly for walkthrough narratives. Story points update with data unless you freeze them via description-only snapshots.

Question 51 - Correct answer: D

Objective 3.4 - Annotations

Correct: D. Mark annotation

Rationale: Mark annotations bind to a specific mark (the underlying data point), so they move with it across refreshes. Point annotations anchor to a fixed coordinate in the view, area annotations to a boxed region, and text objects float on dashboards - none track a mark.

Question 52 - Correct answer: D

Objective 2.7 - Density map

Correct: D. Change the Marks card mark type dropdown to Density

Rationale: Selecting Density as the mark type renders a density (heat) map; you can then tune the color palette, intensity, and opacity. There is no right-click 'convert' option; sizing symbols keeps overplotted circles; filled maps shade polygons by a measure value - a different purpose.

Question 53 - Correct answer: D

Objective 3.1 - Histogram

Correct: D. A single measure; Tableau automatically creates a discrete bin field (with a suggested bin size you can edit) and counts records per bin

Rationale: Show Me's histogram takes one measure, generates the suggested bin field, and plots COUNT of rows per equal-width bin. Editing the bin field's size changes bar width. It needs no date, no second measure, and no geography.

Question 54 - Correct answer: A

Objective 2.6 - Groups vs sets

Correct: A. Create a group on Sub-Category (paperclip); it is static re-labeling - if membership must be rule-driven and refresh-aware, use a set with a Top/Condition rule instead

Rationale: Groups physically combine members into a new dimension value that persists across views but are STATIC - 'Other' is fixed until you edit the group. If the definition must re-evaluate per refresh (e.g., bottom 5 by sales), a dynamic set (and optionally an IN/OUT display) is the correct structure. Filters hide data; hierarchies define drill paths.

Question 55 - Correct answer: D

Objective 2.8 - Forecasting prerequisites

Correct: D. Forecasting requires a view with a continuous date (or continuous integer) field and at least one measure; the discrete year is a header, not a time axis

Rationale: Tableau forecasts (exponential smoothing models) extend a continuous time axis; discrete date pills partition the view into headers, so no axis exists to extrapolate. Converting the pill to a continuous month/quarter enables it. It works in Desktop too, on supported chart types, and does not demand a fixed 24 months (though seasonal models need enough history).

Domain 4: Publish and Manage Content on Tableau Server and Tableau Cloud (9%)

Question 56 - Correct answer: B

Objective 4.1 - Publish a workbook

Correct: B. Server (or File) > Publish Workbook > sign in to the site > choose the project, name, which sheets to include (optionally Show Sheets as Tabs), and permissions

Rationale: Publishing is done via Publish Workbook: authenticate, select project, name/description/tags, choose sheets (and tabbed navigation), set permissions and data authentication for sources. Emailing files and exporting to PowerPoint don't publish; .hyper is an extract format, not a workbook.

Question 57 - Correct answer: D

Objective 4.2 - Schedule extract refreshes (Cloud + on-prem)

Correct: D. A refresh schedule alone cannot reach the on-prem database - you need Tableau Bridge running on a machine inside the network to keep that extract fresh (or make the source cloud-reachable)

Rationale: Tableau Cloud cannot initiate connections into private networks. Tableau Bridge (a client behind the firewall) performs refreshes for on-prem/cloud-private sources on a schedule. Live connections to unreachable sources simply fail; extracts refresh fine once Bridge handles connectivity.

Question 58 - Correct answer: C

Objective 4.3 - Data-driven alerts

Correct: C. A view with a continuous numeric axis on which you can set the alert condition/threshold (alert options are unavailable for non-numeric axes such as filled maps or Gantt without numeric axes)

Rationale: Data-driven alerts are created by clicking the numeric axis of a view (Sales over time qualifies) and setting condition + threshold + recipients + frequency. They only exist on continuous numeric axes - no numeric axis, no alert. Check cadence can be hourly/daily/weekly or as data refreshes.

Question 59 - Correct answer: A

Objective 4.3 - Subscriptions

Correct: A. Subscriptions on a schedule, with recipients who have View permission (admins/owners can subscribe other users/groups)

Rationale: Subscriptions email an image or PDF of a view/dashboard to chosen users on a schedule you pick. Subscribing others requires the appropriate site capability; content itself needs no action or optimization to be subscribed.

Question 60 - Correct answer: B

Objective 4.2 / 4.1 - Schedule a Tableau Prep flow

Correct: B. The flow must be published and run via Tableau Prep Conductor, which is part of the Data Management add-on license

Rationale: Flow scheduling is handled by Tableau Prep Conductor, enabled by the Data Management add-on on Server/Cloud. Without Conductor, flows can only be run manually from Prep Builder or via command line; .tde is a legacy extract format unrelated to scheduling.

END OF ANSWER KEY.