Salesforce Certified Tableau Data Analyst (DA-201) — Practice Exam

Answer Key & Explanations

Quick Answer Key

Q	Ans	Q	Ans	Q	Ans	Q	Ans
1	C	26	D	51	B	76	C
2	D	27	B	52	D	77	B, D
3	A	28	A	53	C	78	B
4	B→E→A→D→C	29	C	54	B→C→A→D	79	A
5	B	30	D	55	C	80	D
6	C	31	A	56	B→C→A→D	81	C
7	A, D	32	C	57	B	82	B
8	D	33	B	58	A	83	A
9	B	34	D	59	D	84	D
10	B→D→A→C	35	A, C	60	A	85	C
11	B	36	B, D	61	B	86	B
12	B, D	37	A, C	62	C	87	A
13	C	38	B	63	B	88	D
14	B	39	D	64	D	89	B
15	D	40	A	65	C	90	C
16	B	41	C	66	B	91	D
17	C	42	B	67	A	92	B
18	A	43	D	68	D	93	A
19	D	44	B	69	B	94	C
20	B	45	C	70	C	95	B
21	C	46	A	71	B	96	A, C
22	B	47	D	72	C	97	D
23	A	48	B	73	D	98	A, D
24	C	49	C	74	B	99	B
25	C	50	D→A→B→C→E→F	75	A	100	B, D

Domain 1: Connect to and Transform Data — Answers (Q1–Q24)

Q1 — Correct: C An extract (.hyper) is a snapshot of the data stored in Tableau's fast in-memory engine. It removes query load from the production database, accelerates every interaction, and can be refreshed on a schedule (daily before 7 AM meets the currency requirement). Live connections are only necessary when data must be current in real time — not the case here. *Objective 1.1.2 — Choose between live connection or extract.* · Reference: "Extract Your Data."

Q2 — Correct: D The .hyper format uses Tableau's newer 64-bit data engine and supports very large extracts (billions of rows). You cannot convert a .hyper back to .tde; you cannot use *Export as Version* to downgrade a workbook containing a .hyper extract (downgrades are only possible if the workbook contains a .tde); and Tableau 10.5 (not 10.4 and older) is the first version to create .hyper extracts by default. *Objective 1.1.5 — Connect to .hyper files.* · Reference: "Extract Your Data."

Q3 — Correct: A Published data sources live on the Tableau Server/Cloud site. From Tableau Desktop you use the **Tableau Server** connector (under *Search for Data / Connect to a Server*), sign in, and browse to the published data source. This keeps everyone on the same governed, certified data. *Objective 1.1.8 — Connect to a data source on Tableau Server.* · Reference: "Tableau Server and Tableau Cloud."

Q4 — Correct order: B → E → A → D → C You open the workbook with the original source, add the **new** data source (Data > New Data Source), set it up on the Data Source page, then run **Data > Replace Data Source** from a worksheet, choose the current and replacement sources, and click OK. Replacement works by matching field names/structure, so identical schemas swap cleanly; any broken fields must be fixed manually. *Objective 1.1.9 — Replace the connected data source.* · Reference: "Replace Data Sources."

Q5 — Correct: B Custom SQL is created by double-clicking **New Custom SQL** on the data source page. To include rows from either region you need an `OR` predicate: `WHERE region = 'East' or region = 'West'`. Option A uses + (invalid SQL for this), option C uses `AND` (a row can never be both regions), and option D uses invalid syntax. *Objective 1.1.7 — Pull data from relational databases by using custom SQL queries.* · Reference: "Connect to a Custom SQL Query."

Q6 — Correct: C Data > [data source name] > Create Local Copy downloads the published source (creating a local extract) so you can keep working without a connection to the server. The option does not exist on the File or Worksheet menus. *Objective 1.1.8 / 1.1.3 — Connect to extracts; data sources on Tableau Server.* · Reference: "Create a Local Copy."

Q7 — Correct: A, D Data Interpreter detects and removes extraneous content (titles, notes, footers, subtables) so Tableau correctly locates the actual fields and data values, and it provides a "Review the results" link that opens a document explaining what it changed. It does not create relationships or publish anything to Tableau Server. *Objective 1.2.5 — Prepare data using Data Interpreter.* · Reference: "Use the Data Interpreter to Clean Your Data."

Q8 — Correct: D The automatic **Split** uses spaces as the default delimiter, so it would not work on `Smith;John`. **Custom Split** lets you specify the delimiter (`;`) and which occurrence(s) to extract, creating two new fields without writing a formula. Pivot reshapes

rows/columns and Data Interpreter cleans layout issues — neither splits a string field. *Objective 1.2.5 — Prepare data by using split.* · Reference: "Split a Field into Multiple Fields."

Q9 — Correct: B On the data source page you select the month columns in the grid and choose **Pivot** from the drop-down. Tableau creates `Pivot Field Names` (the month headers — rename to `Date` and set its data type to Date) and `Pivot Field Values` (the numbers — rename to `Sales`). This reshapes wide data into a tall, analyzable structure. Merging columns and custom splitting do not produce the required structure. *Objective 1.2.5 — Prepare data using pivot.* · Reference: "Pivot Column Data from Text Files / Pivot Your Data."

Q10 — Correct order: B → D → A → C First connect to the initial table (which opens the Data Source page), then double-click **New Union**, drag the remaining tables into the union dialog below the first table, and finish with Apply/OK. Unions require matching structure (columns are aligned by position/name) and stack rows. *Objective 1.2.4 — Union tables.* · Reference: "Union Your Data."

Q11 — Correct: B Relationships (the logical layer) are flexible: Tableau generates joins at query time and can **cull** tables not used by the view — Orders-only views never query Returns. A physical left join fixes the join up front and can duplicate rows; blending aggregates per view and isn't needed here since both tables can share a model; a custom SQL view behaves like a fixed join. *Objective 1.2.4 — Use multiple data sources (relationships vs joins).* · Reference: "Relationships, Between Tables."

Q12 — Correct: B, D In a blend, the secondary source is **aggregated first** and then combined with the primary on the linking dimensions (like a left join on the primary). Every member of the primary source appears in the view; missing secondary matches simply show null. Blending is not a row-level merge and cannot be published as a single unified data source — the blend definition lives in each worksheet. *Objective 1.2.4 — Blend data.* · Reference: "Blend Your Data."

Q13 — Correct: C An **extract filter** restricts which rows are written into the extract file itself and runs first in the order of operations — the confidential data never exists in the .hyper. Data source filters hide rows from every worksheet's queries but, on extracts, the rows are still stored in the file. Context and dimension filters are per-worksheet and applied even later. *Objective 1.2.6 — Create extract filters.* · Reference: "Extract Filters / Data Source Filters; Order of Operations."

Q14 — Correct: B The same entity stored in **different formats/spellings** is a **consistency** problem (one value, many representations). Completeness concerns missing values (nulls); accuracy concerns wrong values; timeliness concerns how current the data is. In practice you'd fix consistency with Prep's automatic grouping or Tableau's Group feature. *Objective 1.2.1 — Assess data quality.* · Reference: "Clean and Shape Data / Group Your Data."

Q15 — Correct: D To organize fields into **folders**, select them in the Data pane, right-click, and choose **Folders** > **New Folder**; you can also drag fields into existing folders. Groups combine dimension *members*, hierarchies create drill paths between levels — neither organizes field lists. *Objective 1.2.3 — Organize data into folders.* · Reference: "Organize and

Customize Fields in the Data Pane."

Q16 — Correct: B A **Wildcard Union** in the Prep Input step scans a directory and unions every file matching a name pattern (e.g., `Sales_*.xlsx`). Files added later are picked up automatically on the next run — no manual intervention. Joins combine different tables on keys, and Data Interpreter cleans layout within files. *Objective 1.3.2 — Combine data by using unions.* · Reference: "Add More Data in the Input Step / Wildcard Union."

Q17 — Correct: C Append to table adds the flow's new rows to the existing output (file or table) without removing history — exactly what accumulating monthly data requires. *Create table / Replace data* overwrite the existing output. *Objective 1.3 output — Determine which output type/write option to use.* · Reference: "Save and Share Your Work."

Q18 — Correct: A In a Prep **Aggregate** step, dimensions you group by (Region, Segment) go into **Grouped Fields**, and the measure to aggregate (Sales) goes into **Aggregated Fields** with its function (SUM). Clean, Pivot, and New Rows steps do not change granularity this way. *Objective 1.3.4 — Shape data by using aggregations.* · Reference: "Aggregate, Join, or Union Data."

Q19 — Correct: D To turn row values into **column headers**, you use a Pivot step with **Rows to Columns** and drag the vehicle-type field into the pivot-values area — each distinct value becomes its own column. *Columns to Rows* does the opposite. *Objective 1.3.6 — Shape data by using pivots.* · Reference: "Pivot Your Data."

Q20 — Correct: B Tableau Prep's automatic grouping options are **Pronunciation** (phonetic matching — Metaphone algorithm — catches name variants like *Smith/Smyth*), **Common Characters** (shared substrings), **Spelling** (minor typos), and **Manual Selection**. For phonetic variants of one name, Pronunciation groups all five automatically. *Objective 1.3.1 / 1.2.2 — Cleaning operations.* · Reference: "Clean and Shape Data — Group and Replace Values."

Q21 — Correct: C Publishing the flow to Tableau Server/Cloud (from Prep Builder's *Publish As* or Server menu) lets it run on the server's backgrounder, and you can attach a **schedule** (e.g., weekly Monday 6:00 AM). Task Scheduler and manual CSV exports are not supported automation patterns for flows. *Objective 1.3 output / Domain 4.2 — Schedule a Tableau Prep workflow.* · Reference: "Publish a Flow to Tableau Server or Tableau Cloud."

Q22 — Correct: B Converting a field from discrete to continuous changes it from **headers** (blue) to a **continuous axis** (green). Dates support both: discrete dates make categorical headers; continuous dates produce a smooth axis over time. *Objective 1.4.3 — Choose when to convert between discrete and continuous.* · Reference: "Dimensions and Measures, Blue and Green."

Q23 — Correct: A Drag the field from the **Measures** area of the Data pane into the **Dimensions** area (you can also right-click the field > *Convert to Dimension*). Tableau will treat each postal code as a discrete category rather than a number to aggregate — required for correct geographic matching. *Objective 1.4.4 — Choose when to convert between dimension and measure.* · Reference: "Convert a Measure to a Dimension."

Q24 — Correct: C Aliases rename the *display value* of a dimension member everywhere it appears (right-click the member or field > Aliases > Edit Aliases), without touching the underlying data. They work for discrete dimensions only. Renaming the field changes its name, and groups/calcs are unnecessary workarounds for a simple display rename. *Objective 1.4.5 — Create aliases.* · Reference: "Create Aliases to Rename Members in the View."

Domain 2: Explore and Analyze Data — Answers (Q25–Q65)

Q25 — Correct: C `COUNTD([Equipment])` counts **distinct** equipment values (3: Barbell, Dumbbell, Jump Rope). `COUNT` would over-count (5) because it counts every row; `MAX` on a string returns a string; `ATTR` is a uniqueness test that returns `*` if multiple values exist. *Objective 2.1.6 — Write aggregate functions.* · Reference: "Functions (Aggregate)."

Q26 — Correct: D `{FIXED [Customer Name] : MAX([Order Date])}` computes the max order date per customer **regardless of the view's level of detail**, so Customer Name doesn't need to be in the view. Plain `MAX([Order Date])` only computes at the view's granularity. Options B and C are invalid LOD syntax (the aggregate expression must follow the colon, and the dimension declaration precedes it). *Objective 2.1.7 / 2.9 — Write FIXED LOD calculations.* · Reference: "Create Level of Detail Expressions."

Q27 — Correct: B To get one total per region you fix at Region: `{FIXED [Region] : SUM([Sales])}`; dividing `SUM([Sales])` by this field gives each state's percent of its region's total. Option D is invalid — `TOTAL()` is a *table calculation* and cannot be used inside an LOD expression. *Objective 2.1.7 / 2.9 — Write FIXED LOD calculations.* · Reference: "Create Level of Detail Expressions."

Q28 — Correct: A `{INCLUDE [Sub-Category] : SUM([Sales])}` computes at the view level **plus** Sub-Category (finer detail); aggregating the result with AVG in the view yields the average sub-category sales per category. FIXED ignores the view's dimensions; EXCLUDE removes dimensions; plain SUM stays at Category level. *Objective 2.9 — Write INCLUDE LOD calculations.* · Reference: "Create Level of Detail Expressions — INCLUDE."

Q29 — Correct: C `{EXCLUDE [Category] : SUM([Sales])}` removes Category from the calculation, so it returns the Region total for every row — the LOD equivalent of a total line / "percent of total" denominator. FIXED would ignore Region too; INCLUDE adds detail instead of removing it; `WINDOW_SUM` is a table calculation (a valid alternative but not the LOD the question asks about). *Objective 2.9 — Write EXCLUDE LOD calculations.* · Reference: "Create Level of Detail Expressions — EXCLUDE."

Q30 — Correct: D Per the Tableau order of operations, FIXED LODs compute **after** extract, data source, and context filters, but **before** dimension filters. A standard dimension filter therefore changes what's displayed, but the FIXED values were already computed over the full (context-level) data — the LOD results are unchanged. Add the filter to **context** if it must

affect the FIXED values. *Objective 2.4.3 / 2.9 — Filters + LOD order of operations.* · Reference: "Tableau's Order of Operations."

Q31 — Correct: A `DATEPART('month', [Order Date])` returns the **integer** month number (3). `DATENAME` returns the string name ("March"), `DATETRUNC` truncates a date to the start of the period (a date value), and `DATEPARSE` converts a **string** into a date using a format pattern. *Objective 2.1.1 — Write date calculations.* · Reference: "Date Functions."

Q32 — Correct: C `DATEDIFF(date_part, start_date, end_date)` accepts the date part as its first argument, so passing the **parameter** lets the user switch units dynamically: `DATEDIFF([Date Part], [Order Date], [Ship Date])`, then wrap in `AVG(...)` in the view (grouped by Ship Mode). `DATEADD` adds to a date; `DATENAME` extracts a name. *Objective 2.1.1 — Date calculations + parameters.* · Reference: "Date Functions — DATEDIFF."

Q33 — Correct: B `CONTAINS([Address], "@")` returns **TRUE/FALSE** for every row where an e-mail is present — exactly the row-level test required. `STARTSWITH` checks only the beginning of the string; `REPLACE` modifies the string; `LEN` just measures length. (`FIND([Address],"@") > 0` would also work, but on its own `FIND` returns a position, not a Boolean.) *Objective 2.1.2 — Write string functions.* · Reference: "String Functions."

Q34 — Correct: D `REPLACE([Name], ";", "")` replaces every occurrence of a substring (`;`) with the replacement string (empty), removing the semicolons. `TRIM/LTRIM` remove whitespace only, and `LEFT` extracts characters. *Objective 2.1.2 — Write string functions.* · Reference: "String Functions — REPLACE."

Q35 — Correct: A, C Option A uses a valid `IF/ELSEIF` with `OR` conditions. Option C uses a valid `CASE` that maps **each member individually** (CASE compares one value at a time). Option B is invalid — `WHEN` cannot take `OR` expressions — and Option D uses `AND`, a condition that can never be true for a single record. *Objective 2.1.3 — Write logical and Boolean expressions.* · Reference: "Logical Functions."

Q36 — Correct: B, D `SUM([Sales]) > 50000` evaluates directly to a Boolean, and `IIF(SUM([Sales]) > 50000, TRUE, FALSE)` explicitly returns TRUE/FALSE. Option A returns the **strings** 'TRUE'/'FALSE' rather than Boolean values, and `ISNULL` tests for nulls rather than comparisons. *Objective 2.1.3 — Write logical and Boolean expressions.* · Reference: "Logical Functions — IF, IIF."

Q37 — Correct: A, C `ZN([Amount])` returns the value or **0 if null** (numeric fields), and `IFNULL([Amount], 0)` replaces nulls with the given constant. `ISNULL` returns a Boolean null test (doesn't replace), and `NULLIF` does the opposite (creates nulls when a match occurs). To make nulls count as zero in averages, use `AVG(ZN([Amount]))` or `AVG(IFNULL([Amount],0))` — note `ZN(AVG(...))` would fix the average result, not the inputs. *Objective 2.1.3/2.1.4 — Logical expressions and null handling.* · Reference: "Functions — ZN, IFNULL, ISNULL."

Q38 — Correct: B A 30-point moving average is a **Moving Average quick table calculation**: right-click the measure pill > Quick Table Calculation > Moving Average, then

Edit Table Calculation and set Previous values = 30 (current value included, next = 0). Forecast predicts future values, AVG aggregation doesn't smooth across points, and trend lines show overall direction only. *Objective 2.2.1 — Moving average.* · Reference: "Table Calculation Types."

Q39 — Correct: D After applying **Percent of Total**, you control the partitioning with **Edit Table Calculation** > **Compute Using** > **Specific Dimensions**. Selecting only `Sub-Category` makes the calculation restart for every Category, so percentages within each Category total 100%. Computing using Category (A) partitions by sub-category instead; Table (down) spans everything. *Objective 2.2.2 / 2.3 — Percent of total + customize table calculations.* · Reference: "Transform Values with Table Calculations."

Q40 — Correct: A For a line of cumulative daily sales you need the date at **Exact Date** (continuous) granularity on Columns and the **Running Total** quick table calculation on SUM(Sales). Discrete exact-date headers or YEAR granularity lose the daily level, and Show Me won't add the running total. *Objective 2.2.3 — Running total + building line charts.* · Reference: "Table Calculation Types — Running Total."

Q41 — Correct: C Tableau's "Percent Difference From" is: current − previous, divided by the **absolute value** of the previous value via `LOOKUP` with offset −1. The `ABS` keeps the sign correct when the baseline is negative. Option A is the plain difference, not a percentage. *Objective 2.2.4 — Difference and percent of difference.* · Reference: "Table Calculation Types / Quick Table Calculations."

Q42 — Correct: B CAGR = (End/Start)^(1/n) − 1. Using `LOOKUP(..., -[N Years])` retrieves the value N periods back, raising the ratio to `1/[N Years]` and **subtracting 1** converts growth multiple into growth rate. Option A omits the −1; option C multiplies instead of exponentiating; option D inverts the ratio. *Objective 2.2.6 — Compound growth rate.* · Reference: "Table Calculation Types — YTD Growth, Compound Growth Rate."

Q43 — Correct: D `INDEX()` returns the **physical position** of the row within the partition (1, 2, 3…), regardless of value. `RANK()` orders rows by the **value** of an expression, so the largest value gets rank 1 even if it's the last row physically. *Objective 2.3.4 — Index.* · Reference: "Table Calculation Functions — INDEX, RANK."

Q44 — Correct: B `RANK_DENSE()` gives ties the same rank **without skipping** subsequent ranks (1, 1, 2, 3). `RANK()` (standard competition) skips (1, 1, 3); `RANK_UNIQUE()` never ties (1, 2, 3); `RANK_MODIFIED()` also skips to the last tied position (1, 1, 3). *Objective 2.3.5 — Ranking.* · Reference: "Table Calculation Functions — Rank variants."

Q45 — Correct: C YoY table calcs require the prior year to exist in the query, so a regular dimension filter breaks it. A **table calculation filter** computes last: create `LAST() = 0` (true only on the final column), add it to the Filters shelf computing using the date field, and keep True. The YoY values are computed over all years, then only the latest year displays. (`INDEX()` starts at 1 so `INDEX()=0` is never true; `FIRST()=0` would keep the *first* year.) *Objective 2.3.6 — First/Last + table calc filters.* · Reference: "Table Calculation Functions — FIRST, LAST; Order of Operations."

Q46 — Correct: A Top N (and conditional) filters execute **before** dimension filters. The Top 5 was computed across *all* categories, then the Category filter removed members — leaving 3 bars. Adding the **Category filter to context** makes it run first, so the Top 5 is computed within Office Supplies. Adding the Top filter itself to context would fix the ranking across all data. *Objective 2.4.3 — Add filters to context.* · Reference: "Use Context Filters; Order of Operations."

Q47 — Correct: D The **Wildcard** tab of a dimension filter matches a pattern (Starts with / Contains / Ends with / Exactly matches) with no formula required — typing "The" with "starts with" filters the list. Top ranks by a measure, General selects members, Condition uses a formula or by-field rule. *Objective 2.4.2 — Configure filter settings (wildcard).* · Reference: "Filter Data from Your Views."

Q48 — Correct: B A **Conditional** filter keeps dimension members whose aggregated measure meets a rule: in the Condition tab choose *By field*, Sum of Population, > `1,000,000`. The list of qualifying cities updates dynamically as data changes. Top N limits a count rather than applying a threshold; Wildcard matches strings. *Objective 2.4.2 — Configure filter settings (conditional).* · Reference: "Filter Data from Your Views — Condition tab."

Q49 — Correct: C From the filter card's drop-down menu, **Apply to Worksheets > All Using Related Data Source** propagates the filter to every worksheet that shares the same primary data source (or choose *Selected Worksheets* for specific ones). This is far more maintainable than duplicating filter cards. *Objective 2.4.4 — Apply filters to multiple sheets and data sources.* · Reference: "Apply Filters to Multiple Worksheets."

Q50 — Correct order: D → A → B → C → E → F Tableau's filter order of operations: **Extract filters → Data source filters → Context filters → Dimension filters → Measure filters → Table calculation filters.** (FIXED LODs and Top N/conditional set filters compute after context filters but before dimension filters; INCLUDE/EXCLUDE LODs and blends compute after dimension filters.) *Objective 2.4.3 — Order of operations.* · Reference: "Tableau's Order of Operations."

Q51 — Correct: B Parameters are just workbook variables — they filter nothing on their own. You must reference the parameter in a calculation: create `[Region] = [Choose Region]`, add it to the **Filters** shelf and keep True; then show the parameter control. Pages animate through discrete values; setting the display type alone has no effect on data. *Objective 2.5.2 — Parameters with filters.* · Reference: "Use Parameters to Make Views More Interactive."

Q52 — Correct: D In the dimension filter's **Top** tab, the N value accepts a parameter: create the parameter (integer), then click the drop-down next to the number and choose the parameter — users then change N interactively (e.g., 5, 10, 25). Fixed sets and duplicated filters are not dynamic. *Objective 2.5.2 — Parameters with filters (Top N).* · Reference: "Filter Data from Your Views — Top tab."

Q53 — Correct: C From the Analytics pane, drag **Reference Line** into the view; in the Edit Reference Line dialog, the **Value** drop-down can be set to a parameter. Users change the

parameter (e.g., via slider) and the target line moves — no workbook editing required. *Objective 2.5.3 — Parameters with reference lines.* · Reference: "Reference Lines, Bands, Distributions, and Boxes."

Q54 — Correct order: B → C → A → D Create the parameter first, then the calculated field that branches on it, then place the calculation in the view (replacing the static measure), and finally show the parameter control so users can pick Sales or Profit. *Objective 2.5.1 — Parameters in calculations.* · Reference: "Use Parameters to Make Views More Interactive."

Q55 — Correct: C Right-click the dimension > **Create** > **Set** > **Top** tab defines a *computed* set ("Top 10 by Sum(Sales)") that re-evaluates automatically as data changes. Creating a set from a selection in the view produces a **fixed** (static) set that never auto-updates; groups and parameters are the wrong tools. *Objective 2.6.1 — Sets.* · Reference: "Create Sets."

Q56 — Correct order: B → C → A → D Create the Top 10 by Sales set from the dimension; duplicate it and edit the copy into a **Bottom 10** set; combine the two sets (right-click > **Create Combined Set**) using **All members in both sets** so either membership qualifies; finally drag the combined set to Filters. Combined sets must be based on the same dimension. *Objective 2.6.1 — Sets (combined sets).* · Reference: "Create a Combined Set."

Q57 — Correct: B Right-click the measure > **Create** > **Bins**, enter bin size **3**, then drag `Quantity (bin)` to Columns and `CNT(Quantity)` to Rows (or use Show Me's histogram). Bins convert a continuous measure into a new discrete dimension of equal-width groups; mark type size and groups don't create histograms. *Objective 2.6.2 — Bins.* · Reference: "Build Histograms / Create Bins from a Continuous Measure."

Q58 — Correct: A Create a **hierarchy** (e.g., Category > Sub-Category) in the Data pane, place both fields in the view, and users drill with the +/- buttons. Groups combine members, sets subset data, and parameters swap values — none provide hierarchical drill-down. *Objective 2.6.3 — Hierarchies.* · Reference: "Create Hierarchies."

Q59 — Correct: D Double-clicking `State` auto-generates Latitude/Longitude and the map; adding `Sales` to **Color** encodes total sales; setting the mark type to **Map** fills the states (a choropleth/filled map). Detail + Size produces a symbol map, Angle is only for pie marks, and Density is for point concentration. *Objective 2.7.4 — Create choropleth maps (filled maps).* · Reference: "Build and Analyze Maps in Tableau."

Q60 — Correct: A The **Density** mark type renders many overlapping points as a density/heat visualization; you then tune **Intensity** and **Opacity** from the Color legend. Filled maps shade geographic areas; shrinking circles or a crosstab don't reveal concentration patterns of millions of marks. *Objective 2.7.3 — Create density maps.* · Reference: "Density Maps Using Marks."

Q61 — Correct: B Drag **Distribution Band** from the Analytics pane onto the Profit axis and, in the dialog, set the factor to **Standard Deviation(s)** with Band From = **−1** and Band To = **1** — this shades the area within ±1 standard deviation. Reference bands use explicit min/max lines and box plots summarize distributions. *Objective 2.8.6 — Distribution bands.* ·

Reference: "Reference Lines, Bands, Distributions, and Boxes."

Q62 — Correct: C Right-click any trend line and choose **Edit All Trend Lines**; under **Factors**, clearing **Region** removes Region as a factor so each Sub-Category gets a single trend line computed across all regions. Removing Region from the view would change the analysis scope; changing the model doesn't remove the factor. *Objective 2.8.5 — Trend lines.* · Reference: "Add Trend Lines to a Visualization."

Q63 — Correct: B Drag **Forecast** from the Analytics pane onto the view; Tableau models the seasonal monthly trend and projects forward. Use **Forecast Options** to set the length to exactly 3 years. Trend lines describe fitted history, and clustering groups observations — neither predicts future values. *Objective 2.8.7 / 2.8.8 — Forecast by using default settings; customize a forecasting model.* · Reference: "Forecasting."

Q64 — Correct: D `MODEL_QUANTILE(0.5, SUM([Sales]), …predictors…)` is the predictive-modeling function that returns the **median** (quantile 0.5) of the target given predictors — plot it as a second line on a **dual axis**. `MODEL_PERCENTILE` returns the probability (0–1) that a value is ≤ the target; there is no PREDICT_MEDIAN function. *Objective 2.8.9 — Create a predictive model.* · Reference: "Predictive Modeling Functions (MODEL_QUANTILE, MODEL_PERCENTILE)."

Q65 — Correct: C Grand totals and subtotals are added from the **Analysis** > **Totals** menu (Show Row Grand Totals, Show Column Grand Totals, and optionally All Subtotals). The Marks card and Format menu don't add totals, and there is no "Total" field to drag. *Objective 2.8.1 — Totals and subtotals.* · Reference: "Totals and Subtotals."

Domain 3: Create Content — Answers (Q66–Q91)

Q66 — Correct: B A pie chart needs a **numeric measure on Angle** (Revenue defines each slice's size) with the dimension on **Color** and **Label** (Item). Dimensions are invalid on Angle/Size for pie marks, and putting Revenue on Color/Label with Item on Detail produces evenly split, meaningless slices. *Objective 3.1.1 — Create basic charts (pie).* · Reference: "Build a Pie Chart."

Q67 — Correct: A A heat map uses the **Square** mark type with the measure on **Color**. Choosing a **diverging** palette (Red-Green) distinguishes positive/negative, and **Use Full Color Range** prevents negative values from being clipped — mapping true min-to-max onto the palette. Dimensions on Color would overwrite the measure encoding; Size isn't used in a heat map. *Objective 3.1.1 — Highlight tables / heat maps.* · Reference: "Edit the Color Palette; Use the Full Color Range."

Q68 — Correct: D Synchronize Axis is only available when both continuous axes use the **same data type** — an integer (whole-number) measure paired with a decimal measure

disables the option. Making the data types compatible (e.g., converting the integer measure to a float) re-enables Synchronize Axis, which then aligns the scales and zero baselines. *Objective 3.1.1 — Dual axis charts.* · Reference: "Add Axes for Multiple Measures / Compare Two Measures with Dual Axes."

Q69 — Correct: B To combine two measures with independent axes, place both measures on the same shelf (Rows or Columns), right-click the second axis and choose **Dual Axis**, then assign a mark type per Marks card — Bar for Sales, Line for Profit (a combo chart). Measure Names/Values blends them onto one shared axis instead. *Objective 3.1.1 — Create charts (dual axis, combo).* · Reference: "Compare Two Measures with Dual Axes."

Q70 — Correct: C A Gantt chart places the **continuous** `Start Date` on Columns and `Task Name` on Rows with mark type **Gantt Bar**; each bar starts at the start date and its length comes from `Duration` on **Size**. Duration on Columns or End Date would not position bars on a timeline. *Objective 3.1.1 — Create charts (Gantt).* · Reference: "Build a Gantt Chart."

Q71 — Correct: B A **box plot** (box-and-whisker) shows the distribution of a measure along an axis — median, quartiles, whisker range, and outliers — enabling comparison of variability across categories. Bullet graphs compare actual vs target; scatter shows relationships between two measures; histograms show a single distribution's frequency. *Objective 3.1.1 — Create charts (box plots).* · Reference: "Add a Box Plot."

Q72 — Correct: C A **scatter plot** puts one numeric measure on each axis; each point is a product (add Product to Detail), letting you see correlation/clusters between Sales and Profit. Bars/lines/pies don't reveal correlation between two measures. *Objective 3.1.1 — Create charts (scatter plot).* · Reference: "Build a Scatter Plot."

Q73 — Correct: D Custom sorting lets you order a dimension **by a field that isn't in the view**: right-click `Sub-Category` > Sort > Sort By: **Field**, Descending, Field: `Profit`, Aggregation: `Sum`. Toolbar sorts use the displayed measure, and manual dragging is not reproducible at scale. *Objective 3.1.2 — Sort data (including custom sort).* · Reference: "Sort Data in a Visualization."

Q74 — Correct: B A **treemap** shows part-to-whole relationships for many categories in limited space — rectangles sized by value and colored by an additional encoding. Pie charts become unreadable beyond a handful of slices; Gantt and line charts serve other purposes. *Objective 3.1.1 — Create charts (treemap).* · Reference: "Build a Treemap / Choose the Right Chart Type."

Q75 — Correct: A A **horizontal** layout container arranges objects left-to-right (side by side); a **vertical** container stacks top-to-bottom. Objects inside a container move and resize **together** when the dashboard resizes — the key benefit of containers. *Objective 3.2.1 — Combine sheets into a dashboard using containers and layout options.* · Reference: "Size and Lay Out Your Dashboard."

Q76 — Correct: C Use as Filter (on the sheet's drop-down menu on the dashboard) instantly makes clicking marks in that sheet filter every other sheet on the dashboard — Tableau

creates the filter action for you. Manual actions (Dashboard > Actions) achieve the same but require configuration; highlight actions don't filter. *Objective 3.3.1 — Apply a filter to a view.* · Reference: "Create a Dashboard — Use as Filter."

Q77 — Correct: B, D A story point can contain **either a worksheet or a dashboard**, and story points can be added, duplicated, deleted, reordered, and their captions/titles edited at any time. They are snapshots of a sheet/dashboard state used to build a narrative. *Objective 3.2.3 — Create stories.* · Reference: "Create a Story and Story Points."

Q78 — Correct: B The **Image** object lets you add pictures (logo, watermark) to a dashboard, with options like Fit Image and Center Image. Text objects contain words only, web page objects embed URLs, and blank objects reserve space. *Objective 3.2.2 — Add objects.* · Reference: "Create a Dashboard — Objects."

Q79 — Correct: A A **filter action** (Dashboard > Actions > Add Action > Filter) specifies the Source sheet (map), Target sheet (Products), and how the action runs (on Select), with options for clearing the selection. URL actions open web pages; highlight actions emphasize without filtering; set actions change set membership. *Objective 3.3.2 — Add filter actions.* · Reference: "Filter Actions."

Q80 — Correct: D A **URL action** opens a web address and supports embedding field values into the URL (e.g., `https://<Website>`), so clicking a company mark launches that company's page. A web page object is optional (the URL can open in a new tab). *Objective 3.3.2 — Add URL actions.* · Reference: "URL Actions."

Q81 — Correct: C Highlight actions emphasize the marks in other views that relate to the selection while keeping all other marks visible (data is never removed). Filter actions remove data; URL actions navigate away; go-to-sheet actions switch views. *Objective 3.3.2 — Add highlight actions.* · Reference: "Highlight Actions."

Q82 — Correct: B The standard sheet-swap pattern is a **parameter** + **calculated field**: a parameter holds the view choice, a calculated field (e.g., `IF [P] = 'View 1' THEN 1 ELSE 0 END`) is placed on the Filters shelf of both sheets, so only the selected sheet shows marks. Dashboard actions and show/hide buttons don't switch which visualization is rendered by data. *Objective 3.3.3 — Swap sheets using parameters.* · Reference: "Swap Views Using a Parameter / Sheet Selector."

Q83 — Correct: A The **Navigation** object (button) lets users click to jump to another dashboard or sheet in the same workbook. Download objects export content; image/blank objects are static. *Objective 3.3.4 — Add navigation buttons.* · Reference: "Create a Dashboard — Navigation Object."

Q84 — Correct: D Dynamic Zone Visibility must be driven by a field (or parameter) that is **Boolean** and evaluates to a **single value** in the view — TRUE shows the zone, FALSE hides it (and it can run automatically based on user interaction with the data). *Objective 3.3 (new) — Dynamic zone visibility.* · Reference: "Use Dynamic Zone Visibility."

Q85 — Correct: C A **Show/Hide button** attached to a floating container lets viewers click to toggle that container's visibility on demand — ideal for collapsible filter panels. Dynamic Zone Visibility toggles automatically via a Boolean field (designer-driven), which is a different use case. *Objective 3.3.5 (new) — Show/hide buttons.* · Reference: "Show and Hide Objects by Clicking a Button."

Q86 — Correct: B Annotations attach notes directly to data points: right-click the mark and choose **Annotate** > **Mark** (Area/Point annotate regions). The annotation is a callout tied to the mark. Tooltips only appear on hover and captions are static worksheet subtitles. *Objective 3.4.3 — Add annotations.* · Reference: "Add Annotations."

Q87 — Correct: A Tooltips are driven by the worksheet's Marks card: return to the **worksheet** and drag `Sales` onto **Tooltip** — the value then appears when users hover. (Editing the tooltip text on the dashboard alone cannot add data values, and adding sheets to tooltips — "Viz in Tooltip" — embeds whole visualizations.) *Objective 3.4.4 — Add tooltips.* · Reference: "Format Individual Parts of the View; Views in Tooltips."

Q88 — Correct: D Gridlines and banding are controlled from the **Format** pane (Format menu): use **Lines** to set Grid Lines to None, and **Shading** to remove Row Banding / Column Banding. Formatting applies to the current sheet (Format > Workbook applies default fonts/ lines across the workbook). *Objective 3.4.6 — Remove gridlines, row/column bands, shading.* · Reference: "Format Individual Parts of the View."

Q89 — Correct: B In the Layout pane's padding controls, clear the **all-sides-equal** lock; the padding fields then separate (left/right/top/bottom or outer/inner) so you can set the left side independently. Fit settings and floating mode don't control padding. *Objective 3.4.5 — Apply padding.* · Reference: "Size and Lay Out Your Dashboard — Padding."

Q90 — Correct: C Tableau supports copying sheet-level formatting between worksheets: right-click the formatted sheet tab > **Copy Formatting**, then right-click each target sheet tab > **Paste Formatting**. (Format > Workbook sets workbook-wide defaults but is not a full per-sheet copy of every setting.) *Objective 3.4 — Format workbooks/worksheets.* · Reference: "Copy and Paste Formatting (Worksheet Tabs)."

Q91 — Correct: D The **Device Designer** (Layout pane) lets you create separate layouts for **Phone, Tablet, and Desktop** from one dashboard, rearranging/resizing items per device and previewing each. Multiple workbooks would duplicate maintenance; Automatic sizing alone doesn't adapt layouts. *Objective 3.4.7 — Apply responsive design for specific device layouts.* · Reference: "Create Dashboard Layouts for Different Device Types."

Domain 4: Publish and Manage Content — Answers (Q92–Q100)

Q92 — Correct: B In the **Publish Workbook** dialog (Server > Publish Workbook), the **Sheets** section lists every sheet with check boxes — clear the ones you don't want published. You can also set the project, name, tags, permissions, and data-source options (embedded vs. separate) in the same dialog. Deleting sheets or using permissions is unnecessary. *Objective 4.1.1 — Publish a workbook.* · Reference: "Publish Workbooks."

Q93 — Correct: A On the data source page on Tableau Server/Cloud, use **Extract Refreshes** to create or edit a refresh schedule — including hourly. (Live-connection refreshes to Tableau Cloud, if applicable, are managed separately; extracts on Cloud also support incremental refresh.) *Connected Workbooks*, *New*, and *Connections* do not control schedules. *Objective 4.2.1 — Schedule data extract refreshes.* · Reference: "Refresh Extracts / Schedule Extract Refreshes."

Q94 — Correct: C An incremental refresh reads only new/changed rows identified by the chosen column (Order Date) — rows **after the last refresh timestamp** — and appends them, leaving existing rows untouched. If the source schema changes (new columns) a **full refresh** is required; incremental refresh never duplicates correctly keyed data. *Objective 4.2.1 — Schedule refreshes (incremental).* · Reference: "Refresh Extracts — Incremental Refresh."

Q95 — Correct: B Data-driven alerts are created on a **continuous numeric axis** (e.g., SUM(Sales)) of a view or dashboard on Tableau Server/Cloud — click the axis, then use the Alerts side panel (Create). Gantt charts, maps, numeric bins, and story points are not supported. Alerts require embedded credentials for live connections and are evaluated when related extracts refresh. *Objective 4.3.1 — Create alerts.* · Reference: "Send Data-Driven Alerts from Tableau Cloud and Tableau Server."

Q96 — Correct: A, C An alert owner (or administrator) can resume a suspended alert from the **My Content** area of the Tableau web pages (… > Resume Alert) or by clicking **Resume Alert in the notification email**. (Administrators can also use Tasks > Alerts.) Alerts are not managed from Tableau Desktop's Data Source page or Prep Builder. *Objective 4.3.1 — Create/ manage alerts.* · Reference: "Send Data-Driven Alerts — Resume or Delete Suspended Alerts."

Q97 — Correct: D Group subscriptions are membership-driven: users **added to the group later automatically start receiving** the subscription with no need to re-subscribe, and users removed from the group stop receiving it. There is no need to add users individually or recreate the subscription. *Objective 4.3.2 — Create subscriptions.* · Reference: "Create a Subscription to a View or Workbook."

Q98 — Correct: A, D Two ways to produce an image from a worksheet in Tableau Desktop: **Worksheet** > **Copy** > **Image** (copies to clipboard for pasting into Word) and **Worksheet** > **Export** > **Image** (saves a PNG/JPEG file). (For a whole dashboard, use Dashboard > Export Image.) Printing to PDF and exporting data do not produce an image file. *Objective 4.1.4 — Export content.* · Reference: "Export Views from Tableau Desktop / Download Views and Workbooks."

Q99 — Correct: B A **Custom View** saves a version of the view with the user's selections/ filters applied — she can make it her default view and share the link with others, all without modifying the original published dashboard. Subscriptions email snapshots on a schedule; alerts notify thresholds; downloading is not needed. *Objective 4.3.3 — Create and save custom*

views. · Reference: "Use Custom Views."

Q100 — Correct: B, D Creator and **Explorer (Can Publish)** site roles can publish and manage workbooks/data sources. **Viewer** roles can only consume content (and cannot create data-driven alerts), and **Guest** accounts have no publishing rights. Site roles determine what users can do; permissions determine which content they can do it to. *Objective 4.3.4 — Understand user roles and permissions.* · Reference: "Site Roles, Licenses, and Permissions."

How to Interpret Your Score

Score	Readiness
85–100	Exam-ready — schedule the exam; review the ones you missed
75–84	Strong — revisit missed domains for a week, then re-test
65–74	Borderline — you need targeted study, especially Domain 2 (LODs, table calcs, filter order)
< 65	Not ready yet — spend 2–4 more weeks hands-on in Tableau before attempting

Focus areas if you scored below 80% on any domain:

- **Domain 1:** relationships vs joins vs blends vs unions; Prep steps; extract vs live vs data-source filters.
- **Domain 2 (the biggest trap zone):** FIXED/INCLUDE/EXCLUDE, the filter **order of operations**, table-calc **Compute Using**, RANK variants, and parameter patterns.
- **Domain 3:** which action type (filter/highlight/URL/go-to), show/hide vs dynamic zone visibility, chart-selection logic.
- **Domain 4:** alerts vs subscriptions, refresh schedules, publishing options, site roles.

These questions mirror the published exam-guide objectives and the scenario style of the real DA-201 exam. Good luck! 🎯