SALESFORCE CERTIFIED | ANALYTICS-DA-201

Answer Key and Explanations

DeepSeek 2 practice examination

Exam code	Analytics-DA-201 (formerly TDA-C01)
Format	65 multiple-choice and multiple-select questions
Time limit	105 minutes (about 1.6 minutes per question)
Passing score	65% (published passing threshold)
Product version	Tableau 2024.2
Question mix	58 single-answer + 7 multiple-select
Blueprint	14 / 30 / 16 / 5 questions across the four domains
Delivery	Closed book | no notes | no internet

Domain blueprint used for this paper

Domain	Official weight	Questions here	Share of paper
Connect to and Transform Data	24%	14	22%
Explore and Analyze Data	41%	30	46%
Create Content	26%	16	25%
Publish and Manage Content on Tableau Server and Cloud	9%	5	8%
Total	**100%**	**65**	**100%**

Deliberate emphasis: Domain 2 has 30 questions (46%) instead of the official 41%, for extra practice on LODs, calculations, table calculations, filters, and parameters. The other domains are 14 (22%), 16 (25%), and 5 (8%).

How to use this key

Each entry gives the correct letter, the exact option text, a concise rationale, and the trap that makes the question difficult. Attempt the full paper under timed conditions before reading this section. For multi-select items there is no partial credit: the answer must include every required letter and no extras.

Independent study material aligned to the published Analytics-DA-201 objectives. Not an official Salesforce or Tableau exam; questions are not from a live exam. Behavior reflects Tableau 2024.2.

Quick Answer Grid

Check your responses against the grid, then read the explanation for every item you missed (and for every item you guessed).

Q	Q	Q	Q	Q
1 **D**	14 **A**	27 **C**	40 **A**	53 **C**
2 **B, E**	15 **D**	28 **B**	41 **C**	54 **C**
3 **B**	16 **C**	29 **D**	42 **C**	55 **A**
4 **D**	17 **C**	30 **B**	43 **C**	56 **D**
5 **A**	18 **C**	31 **A**	44 **D**	57 **A**
6 **B**	19 **C**	32 **D**	45 **A**	58 **A**
7 **B**	20 **A**	33 **B**	46 **D**	59 **B**
8 **C, E**	21 **B**	34 **D**	47 **D**	60 **B**
9 **D**	22 **D**	35 **B**	48 **A**	61 **A, E**
10 **D**	23 **A**	36 **B**	49 **C, D**	62 **D**
11 **C**	24 **B**	37 **C**	50 **B**	63 **A**
12 **B**	25 **A**	38 **B**	51 **C**	64 **A**
13 **A, C**	26 **A, B**	39 **B, D**	52 **A**	65 **C**

Detailed Explanations

Explanations are grouped by exam domain. The small label above each answer identifies the objective being tested, which is useful for building a revision list.

Domain 1 | Connect to and Transform Data

14 questions | Official weight 24% | Questions 1-14

Q1 ANSWER D

Relationships vs. physical joins

D. Keep the tables related in the logical layer and let Tableau aggregate at the level of detail required by each sheet.

Why: A physical join combines rows **before** aggregation. Because one order can have several returns, the order row is repeated once per return, so `SUM([Sales])` multiplies. A relationship keeps the tables logically separate and lets Tableau choose the join at query time based on the dimensions in the view, which avoids inflating the order-level measure. This is the recommended approach for tables at different granularities in the same data source.

Exam trap: An inner join removes unmatched rows but does **not** remove the one-to-many duplication. Blending can work across sources, but it is not the best fix for two tables in the same source. Extracts do not de-duplicate data.

Q2 ANSWER B, E

Live connections vs. extracts

B. Use a live connection for Dashboard A.
E. Use an extract for Dashboard B.

Why: Live connections query the source at view time, so Dashboard A sees new transactions almost immediately and the source is sized to handle the load. An extract is a local Hyper snapshot that is fast, portable, and available offline, which matches Dashboard B's historical, performance-sensitive, sometimes-offline use case.

Exam trap: Do not choose an extract merely for speed when the requirement is real-time. Conversely, a live connection cannot provide offline access. A CSV is not an interactive Tableau dashboard.

Q3 ANSWER B

Data Interpreter

B. Data Interpreter

Why: Data Interpreter is a built-in Tableau feature that detects and removes common Excel formatting problems such as title rows, merged cells, blank rows, and subtotal rows. It prepares the sheet so the correct table structure is recognized.

Exam trap: Pivot reshapes columns into rows, Split divides a text field, and Union stacks tables. None of them removes report headers or merged cells.

Q4 ANSWER D

Pivot (columns to rows)

D. Pivot

Why: A pivot converts a wide layout (one column per month) into a tall layout with a Month dimension and a Sales measure. This is the standard way to make month columns usable as a dimension in Tableau.

Exam trap: Split separates delimited text inside a field. Union stacks rows from tables with the same structure. Join combines tables side by side on a key. None of these turns columns into rows.

Q5 ANSWER A

Union

A. Union the files.

Why: A union stacks rows from tables that have the same structure. Twelve identically structured monthly files should be unioned into one table, with a source or month field used to distinguish the files if needed.

Exam trap: A join adds columns side by side and requires a key. A relationship is for related tables, not for appending identical monthly files. Pivot changes columns into rows.

Q6 ANSWER B

Data source filters

B. A data source filter.

Why: A data source filter is stored with the data source and applies to every sheet and every user of that source. It is the correct governance control when the same subset must be enforced consistently across many workbooks.

Exam trap: A worksheet filter affects only that sheet. A context filter also applies to one worksheet (although it changes filter order). A table calculation filter filters marks after calculations and does not remove data from the source.

Q7 ANSWER B

Tableau Prep Group Values

B. Pronunciation

Why: Prep's **Pronunciation** method uses phonetic algorithms (Metaphone 3) to match values that sound alike even when spelled differently. Catherine, Katherine, and Katharine are a classic phonetic match.

Exam trap: Spelling uses edit distance and may not connect all three variants. Common Characters matches on shared character patterns. Manual Selection requires the analyst to pick each value.

Q8 ANSWER C, E

Tableau Prep output types

C. Published data source
E. .csv file

Why: A **published data source** is the governed, reusable output for Tableau Cloud users and can be refreshed on a schedule. A **.csv** file is the appropriate plain-text output for the Python model. A single flow can write multiple outputs.

Exam trap: A .twbx is a packaged workbook, not a reusable data source. A .tds stores connection metadata but no data. A PDF cannot feed a Python model.

Q9 ANSWER D

Aliases

D. An alias

Why: An alias changes only the displayed member name; the underlying value used by calculations and filters stays the same. That satisfies the display requirement without breaking logic that references `E`, `W`, `S`, or `N`.

Exam trap: A group creates a new combined member. A set creates a subset. A calculated field that returns 'East' would change the values used by calculations and could break existing logic.

Q10 ANSWER D

Discrete vs. continuous

D. Values are displayed as separate headers or buckets rather than along a continuous axis.

Why: Discrete fields create headers and divide the view into panes or buckets; continuous fields create an axis. Converting a date from continuous to discrete changes how it is displayed and how marks are laid out, but not the underlying data type.

Exam trap: The data type remains date. The hierarchy may still be available. Changing discrete/continuous does not change the aggregation of a measure.

Q11 ANSWER C

Replace a data source

C. Use Data > Replace Data Source and map the old source to the new source.

Why: Replace Data Source swaps the connection for an existing data source throughout the workbook while preserving worksheets and calculations. It is designed for exactly this development-to-production scenario.

Exam trap: Editing each sheet is slow and error-prone. Creating a new workbook loses workbook-level objects. Changing data types does not change the connection.

Q12 ANSWER B

Join row-count logic

B. 2,050

Why: The 2,000 order rows all match a customer, so they are retained. The 50 customers with no orders are also retained by the left join, with nulls in the Orders columns. Total = 2,000 + 50 = **2,050 rows**.

Exam trap: 1,950 would result if 50 orders lacked a matching customer; that is not this scenario. 2,000 ignores the 50 unmatched customers. 2,500 incorrectly adds all 500 customers to the 2,000 orders.

Q13 ANSWER A, C

Assessing data quality

A. Completeness
C. Consistency

Why: Blank Email values are a **completeness** problem because required values are missing. The three representations of the same country are a **consistency** problem because the same real-world value is encoded differently, which splits groupings and filters.

Exam trap: Granularity concerns the level of detail, lineage concerns the origin of data, and latency concerns delay. None of these describes missing values or varied encodings.

Q14 ANSWER A

Published data sources

A. Connect to the published data source.

Why: Connecting to the published data source reuses the governed connection, standardized fields and calculations, permissions, and row-level security. It also ensures the analyst sees the same definitions as the rest of the organization.

Exam trap: A local extract bypasses centralized updates and permissions. Recreating calculations risks inconsistent definitions. Tableau Public is not appropriate for governed enterprise data.

Domain 2 | Explore and Analyze Data

30 questions | Official weight 41% | Questions 15-44

Q15 ANSWER D

Date calculations

D. `DATETRUNC('month', DATEADD('month', -1, TODAY()))`

Why: `DATEADD('month', -1, TODAY())` moves to the same day one month earlier; `DATETRUNC('month', ...)` then truncates that date to the first day of its month. Together they return the first day of the previous month.

Exam trap: `DATEADD('day', -1, DATETRUNC('month', TODAY()))` returns the **last day of the previous month**, one day before the first of the current month. `DATEDIFF('month', -1, TODAY())` is not a valid date expression and would not produce a date. `DATEPART` returns an integer month number, not a date.

Q16 ANSWER C

String functions

C. `RIGHT([Order ID], 5)`

Why: `RIGHT(string, n)` returns the last *n* characters of the string. The last five characters of `ORD-2024-00457` are `00457`.

Exam trap: `LEFT` returns the first five characters (`ORD-2`). `MID([Order ID], 1, 5)` also starts at position 1. `FIND` returns the position of the hyphen, not the substring. Remember the argument order: the string comes first, then the number.

Q17 ANSWER C

Logical expressions and NULLs

C. Full Price

Why: When `Discount` is NULL, the comparison `NULL > 0` evaluates to unknown/NULL, which is not true, so the ELSE branch runs. The result is **Full Price**. If the expression had no ELSE branch, the result would be NULL.

Exam trap: A common mistake is to assume the result is NULL. Tableau's IF treats an unknown condition as not true and falls through to ELSE. Use `ISNULL()` or `IFNULL()` when NULLs need explicit handling.

Q18 ANSWER C

Type conversion / number functions

C. -9

Why: `INT()` truncates toward zero; it does not round to the nearest integer and does not floor toward negative infinity. Therefore `INT(-9.7)` returns **-9**.

Exam trap: `FLOOR(-9.7)` would return -10. `ROUND(-9.7, 0)` would return -10 as well. Do not confuse INT with FLOOR or ROUND.

Q19 ANSWER C

Aggregate functions

C. `COUNTD([Customer ID])`

Why: `COUNTD()` counts distinct values. Because a customer can appear on many order rows, `COUNT([Customer ID])` would count order lines, not unique customers.

Exam trap: `SUM` on an ID is meaningless. `ATTR` returns a value only if all rows share the same value; otherwise it returns *. Use COUNTD whenever the business question says 'unique' or 'distinct'.

Q20 ANSWER A

Basic spatial calculations

A. `MAKELINE(MAKEPOINT([Warehouse Lat], [Warehouse Lon]), MAKEPOINT([Store Lat], [Store Lon]))`

Why: `MAKEPOINT(lat, lon)` creates a point geometry. `MAKELINE(point1, point2)` connects two point geometries into a line, which is the correct spatial calculation for a route between warehouse and store.

Exam trap: `MAKEPOINT` creates only one point. `DISTANCE` returns a numeric distance, not a line. `BUFFER` creates a polygon around a point at a specified radius.

Q21 ANSWER B

DATEDIFF behavior

B. 2

Why: `DATEDIFF` counts the number of date-part **boundaries** crossed, not the number of complete elapsed months. From January 31 to March 1, the month boundaries for February and March are crossed, so the result is **2**.

Exam trap: Many candidates answer 1 by calculating elapsed full months. Tableau's DATEDIFF counts boundaries; this is a favorite exam trap.

Q22 ANSWER D

FIXED LOD / percent of total

D. `SUM([Sales]) / SUM({FIXED : SUM([Sales])})`

Why: A FIXED LOD with no dimensions computes the grand total at the data-source level and ignores the dimension filter on Region (unless the filter is a context filter). The numerator is the filtered West category sales; the denominator is total company sales, producing the required share.

Exam trap: `TOTAL()` is a table calculation and its denominator changes when the view is filtered, so it gives a share of West sales only. A `{FIXED [Region] ...}` denominator is still the West total under the filter. A `{FIXED [Category] ...}` denominator makes every category equal 100%.

Q23 ANSWER A

INCLUDE LOD

A. `AVG({INCLUDE [Customer ID] : SUM([Sales])})`

Why: The INCLUDE LOD adds Customer ID to the computation even though Customer ID is not in the view, calculating each customer's total sales. The outer `AVG` then averages those customer totals within each region. This is the correct 'average of totals' pattern.

Exam trap: `AVG([Sales])` averages individual order rows, not customer totals. `SUM/COUNT` divides by order lines rather than distinct customers. The EXCLUDE expression removes Customer ID from the view level and does not compute a per-customer total.

Q24 ANSWER B

Nested LOD calculations

B. The highest state-level sales within each region, repeated for rows in that region.

Why: The inner LOD computes sales at Region + State granularity. The outer LOD then takes the maximum of those state values within each region. The result is the top-performing state's sales for that region, available at the region level.

Exam trap: The outer aggregation is MAX, not SUM, so it is not regional total sales. It is scoped by Region, so it is not a global average. Nested LODs are evaluated inside out.

Q25 ANSWER A

FIXED LOD with no dimensions

A. `{SUM([Profit])}`

Why: `{SUM([Profit])}` is shorthand for `{FIXED : SUM([Profit])}`. With no dimension in the LOD, it computes the grand total at the data-source level and repeats that value on every row, independent of the view's dimensions.

Exam trap: `SUM([Profit])` aggregates at the view level, so it changes with the dimensions shown. The Region FIXED expression returns a regional total. `TOTAL()` is a table calculation whose scope depends on the view and filters.

Q26 ANSWER A, B

LOD and filter order of operations

A. Context filter
B. Data source filter

Why: FIXED LODs are computed before ordinary dimension filters but after context filters, data source filters, and extract filters. Therefore context and data source filters change the data that the FIXED calculation sees.

Exam trap: Quick dimension filters and filter actions are applied after FIXED LODs, so they limit displayed marks without changing the LOD values. Table calculation filters are applied last of all.

Q27 ANSWER C

EXCLUDE LOD / percent of total

C. `SUM([Sales]) / SUM({EXCLUDE [Category] : SUM([Sales])})`

Why: EXCLUDE removes Category from the view's level of detail, so the denominator is computed at Region level: the region's total sales. Dividing each category's sales by that regional total gives the category's share of its region.

Exam trap: INCLUDE adds Category even though it is already in the view, so the denominator collapses to the category itself and gives 100%. FIXED on Category also gives 100%. `TOTAL()` gives the grand total across all regions, not the regional total.

Q28 ANSWER B

Aggregate vs. row-level mixing

B. `SUM([Sales]) / {FIXED [Region] : SUM([Sales])}`

Why: Both the numerator and the denominator are aggregate expressions: `SUM([Sales])` and a FIXED LOD, which is also an aggregate. Mixing two aggregates is valid. This is the correct way to compute a region share.

Exam trap: `[Sales] / {FIXED [Region] : SUM([Sales])}` mixes a row-level measure with an aggregate LOD and produces 'Cannot mix aggregate and non-aggregate arguments'. `SUM([Sales]) / [Sales]` mixes an aggregate with a row-level field. `{FIXED [Region] : [Sales]}` puts a row-level field inside a FIXED LOD, which requires an aggregate inside the braces.

Q29 ANSWER D

FIXED LOD vs. dimension filters

D. The LOD values are computed before the dimension filter, so each customer keeps lifetime sales; the filter only limits which customers are displayed.

Why: A FIXED LOD is computed at the data-source level before ordinary dimension filters are applied. The top-100 filter then removes marks from the view, but the LOD value for each displayed customer still reflects that customer's full lifetime sales.

Exam trap: Only a context filter (or data source/extract filter) would reduce the data used by the FIXED calculation. The filter is not ignored; it still controls which customers appear.

Q30 ANSWER B

Table calculation addressing and partitioning

B. Address the calculation by Month and partition by Year.

Why: Addressing controls the direction in which the running total accumulates; partitioning defines the groups that reset it. To accumulate across months but restart for each year, address by Month and partition by Year.

Exam trap: Addressing by Year and partitioning by Month would reset every month and accumulate across years, which is the opposite. A plain `SUM` is not cumulative. A filter does not create a running total.

Q31 ANSWER A

Table calculation filters and denominators

A. Replace the table calculation with `SUM([Sales]) / SUM({FIXED : SUM([Sales])})`.

Why: Table calculations operate on the data remaining after filters, so removing products shrinks the denominator. A FIXED LOD with no dimensions computes the grand total before ordinary dimension filters, keeping the denominator at all-product sales while the filter hides marks from the view.

Exam trap: Putting the filter in context changes the data before the table calculation but still removes the products from the denominator. A table calculation filter is applied after the calculation and has the same denominator problem. Running Total answers a different question.

Q32 ANSWER D

Ranking functions

D. `RANK_DENSE`

Why: `RANK_DENSE` assigns the same rank to ties and leaves no gaps, producing 1, 2, 2, 3. `RANK` produces 1, 2, 2, 4 because it leaves a gap after a tie. `RANK_UNIQUE` and `INDEX` produce 1, 2, 3, 4.

Exam trap: Read the requested sequence carefully. The difference between RANK (1,2,2,4) and RANK_DENSE (1,2,2,3) is a common exam distinction.

Q33 ANSWER B

Window calculations / moving average

B. `WINDOW_AVG(SUM([Sales]), -2, 0)`

Why: `WINDOW_AVG(expression, start, end)` averages a window defined by offsets from the current row. `-2, 0` includes the current month and the two preceding months: three months total.

Exam trap: `-1, 1` spans three rows but includes the next month. `0, 2` includes the current and two future months. A running total divided by 3 is not a moving average.

Q34 ANSWER D

LOOKUP / percent difference

D. `(SUM([Sales]) - LOOKUP(SUM([Sales]), -1)) / LOOKUP(SUM([Sales]), -1)`

Why: `LOOKUP(SUM([Sales]), -1)` retrieves the previous month's value. Subtracting it from the current value and dividing by **the previous month's value** gives the percent change. This is the standard month-over-month formula.

Exam trap: `SUM([Sales]) - LOOKUP(SUM([Sales]), -1)` is only the absolute difference. Dividing by `SUM([Sales])` uses the current value instead of the prior value. `RUNNING_SUM(...) / TOTAL(...)` is a running-total share, not a period-over-period change.

Q35 ANSWER B

Top N filters within a category

B. Add Category to context before the Top 10 filter.

Why: A Top N filter is computed across the whole view unless a higher-level dimension is placed in context. Adding Category to context makes Tableau compute the Top 10 within each category, which is the classic 'Top N within a subset' pattern.

Exam trap: A Top N filter can only rank by a measure/aggregation, not 'by Category'. Converting Product to a measure is meaningless. A table calculation filter could implement a rank, but the context-filter approach is the direct fix for this scenario.

Q36 ANSWER B

Parameters with reference lines

B. Create a parameter, show the parameter control, and add a reference line whose value is the parameter.

Why: A parameter is a workbook-level input. After creating it and showing the control, the analyst can use the parameter as the value of a reference line. Changing the parameter moves the line dynamically.

Exam trap: A filter restricts data; it does not position a reference line. A set action changes set membership. A hard-coded calculation cannot be changed by the user.

Q37 ANSWER C

Parameter-driven Top N

C. Create a calculated field such as `RANK(SUM([Sales])) <= [Top N]` and filter it to True.

Why: Parameters cannot be placed directly on the Filters shelf. They must be referenced inside a calculated field, which is then used as a filter. A rank expression compared to the parameter is a standard dynamic Top N pattern.

Exam trap: Dragging a parameter to Filters is not supported. A parameter on Rows does not filter. Bins created from a parameter do not produce a Top N ranking.

Q38 ANSWER B

Parameter-driven bins

B. Create a numeric parameter and a calculated field `INT([Sales] / [Bin Size]) * [Bin Size]`, then use the calculated field as a dimension.

Why: A standard bin field has a fixed size. To make bin size dynamic, create a numeric parameter and a calculated field that rounds each value down to a multiple of the parameter, then use that field as the dimension for the histogram.

Exam trap: Parameters do not automatically control the Create Bins size. They are not dimensions and cannot be placed on Rows to create a histogram. Sets do not define bin widths.

Q39 ANSWER B, D

Groups vs. sets

B. A group combines dimension members into a new member within the same field and can be created by selecting marks.
D. A set defines a subset of members and can be dynamic, such as the top N customers by a measure.

Why: Groups consolidate members of a dimension into a new member (for example, combining several sub-categories into 'Furniture'). Sets define a subset of dimension members and can be fixed or dynamic, including Top N sets that update with the data.

Exam trap: Neither groups nor sets modify the underlying data source. Groups work on dimensions, not just numeric measures. Groups and sets serve different purposes and are not interchangeable.

Q40 ANSWER A

Forecasting requirements

A. At least one date field and at least one measure.

Why: Forecasting requires a date field to establish the time series and at least one measure to forecast. The data also needs enough historical points and a consistent time granularity for a reliable model.

Exam trap: Two dimensions are not required. Parameters and table calculations are not prerequisites. A geographic field is irrelevant to forecasting.

Q41 ANSWER C

Trend lines per pane

C. Add the trend line, then edit it and set the model to per pane.

Why: Trend lines can be scoped to the whole table or to each pane. With Region creating separate panes, editing the trend line model to 'per pane' draws an independent trend line in each region.

Exam trap: Converting Region to a measure changes the view structure. A reference band is not a trend model. A dual axis layers measures; it does not create per-region regression lines.

Q42 ANSWER C

Reference bands

C. Reference band

Why: A reference band fills the area between two values, such as a lower and upper threshold. It is the correct object for shading an acceptable range around a target.

Exam trap: A reference line marks a single value. A distribution band is based on a statistical distribution (percentiles or standard deviations) of the data, not fixed business thresholds. A box plot summarizes a distribution.

Q43 ANSWER C

Choropleth maps

C. Filled (choropleth) map

Why: A filled map, also called a choropleth map, colors geographic polygons such as states or countries according to a measure. It is ideal for comparing regional intensity.

Exam trap: A symbol map places marks at locations. A density map colors areas by the concentration of points. A heat map is a table-based density view, not a geographic polygon map.

Q44 ANSWER D

Map mark layers

D. Add a Marks Layer and place the city and sales fields on the new layer.

Why: Map mark layers let multiple mark types share the same map. The existing filled state layer remains, and a new marks layer can display city points sized by sales.

Exam trap: Changing the mark type replaces the current marks. A dual axis is for charts with axes, not for layering geographic marks. A reference line does not add another map layer.

Domain 3 | Create Content

16 questions | Official weight 26% | Questions 45-60

Q45 ANSWER A

Choosing chart types

A. Histogram

Why: A histogram groups a continuous measure into bins and shows how many rows fall into each range. It is the standard chart for distribution and frequency.

Exam trap: A line chart shows change over time. A pie chart shows part-to-whole composition of categories. A Gantt chart shows duration and sequencing.

Q46 ANSWER D

Dual-axis and combination charts

D. Place both measures on Rows, use Dual Axis, and leave the axes independent.

Why: A dual-axis view places two measures on separate axes, allowing one to be a bar and the other a line. Because the measures have different scales, the axes can remain independent. Synchronize only when both measures share the same scale.

Exam trap: Dragging two measures onto the same axis creates a combined axis, not a dual axis. Measure Names/Measure Values can create a combined axis but do not automatically create independent dual axes. Synchronizing is not required for independent scales.

Q47 ANSWER D

Pie chart marks

D. Category on Color, `SUM(Sales)` on Angle.

Why: For a pie chart, the dimension that defines the slices goes on Color and the measure that determines each slice's size goes on Angle. This produces proportional slices.

Exam trap: Placing the measure on Text only labels the chart. Category on Rows and Sales on Columns creates a bar chart. Detail and Tooltip do not define pie slice angles.

Q48 ANSWER A

Custom sort by a field not in the view

A. Right-click Product > Sort > By Field, then choose Target and its aggregation.

Why: Tableau's Sort dialog allows sorting a dimension by a field that is not in the view. Choosing 'By Field' lets the analyst select Target and the aggregation used for the sort order.

Exam trap: Adding Target to Rows changes the view layout. A table calculation filter removes marks. A group consolidates members but does not define sort order.

Q49 ANSWER C, D

Dashboard actions

C. A filter action from the map to the bar chart.
D. A highlight action from the map to the bar chart.

Why: A filter action applies the selected region as a filter to the target sheet, so the bar chart shows only that region. A highlight action emphasizes related marks while keeping all marks visible, which matches the hover behavior.

Exam trap: A parameter action changes a parameter value, not the target sheet's filter. A URL action opens an external resource. A set action changes set membership; it does not provide the non-destructive hover highlight.

Q50 ANSWER B

Dynamic zone visibility

B. Dynamic zone visibility controlled by a boolean calculation or parameter.

Why: Dynamic zone visibility shows or hides a dashboard zone based on a parameter or boolean calculated field. It is designer-controlled logic that responds automatically to the control's value.

Exam trap: A filter action filters data in a target sheet. A story point is a saved snapshot in a story. A subscription emails a snapshot; none of these toggles a container's visibility.

Q51 ANSWER C

Parameter actions

C. Parameter action

Why: A parameter action writes a value from the selected mark into a parameter. Because the dashboard's calculated field references that parameter, the displayed measure switches automatically.

Exam trap: A set action changes set membership. A filter action filters a target sheet. A URL action opens a web resource. None of them updates a parameter.

Q52 ANSWER A

Set actions

A. Set action

Why: A set action updates the membership of a set based on the marks a user selects. Other sheets using the set can then compare In versus Out members dynamically.

Exam trap: A parameter action changes a parameter, not a set. A highlight action only emphasizes marks. A navigation action moves to another sheet or dashboard.

Q53 ANSWER C

Dashboard layout

C. Floating objects positioned manually.

Why: Floating objects can be placed anywhere on the dashboard canvas and can overlap other objects, which is necessary for precise layering such as a logo over a chart corner.

Exam trap: Tiled containers arrange objects without overlap. Device preview changes layouts for device sizes. Story points are narrative snapshots, not layout tools.

Q54 ANSWER C

Responsive device layouts

C. Device-specific layouts in the Device Designer for phone and tablet.

Why: The Device Designer lets the designer create phone and tablet layouts with their own arrangement and visibility of dashboard objects, while the desktop layout remains unchanged.

Exam trap: A separate workbook duplicates maintenance. Automatic sizing alone does not rearrange content for small screens. A filter action is unrelated to responsive layout.

Q55 ANSWER A

Viz in Tooltip

A. Viz in Tooltip

Why: Viz in Tooltip embeds a worksheet inside a tooltip. Hovering a mark displays the embedded visualization, which is ideal for showing a state's trend without adding another sheet to the dashboard.

Exam trap: A reference band is an analytics object on a chart. An annotation is static text/markup. Dynamic zone visibility shows or hides dashboard zones, not hover content.

Q56 ANSWER D

Annotations

D. Mark annotation

Why: A mark annotation is attached to a selected mark and moves with it if the view changes. It is the right choice for explaining a specific data point such as a sales spike.

Exam trap: A point annotation is placed at a point in the view rather than attached to a mark. An area annotation highlights a region of the view. A tooltip appears on hover but is not a persistent annotation.

Q57 ANSWER A

Gantt charts

A. Task on Rows, Start Date on Columns, Duration on Size.

Why: A Gantt bar starts at a date and extends for a duration. Place the task dimension on Rows, the start date on Columns, and the duration measure on Size. Tableau draws a bar beginning at the start date with a length equal to the duration.

Exam trap: Duration on Rows creates a bar chart of durations, not a timeline. Start Date on Color and Duration on Label do not position or size bars. Start Date on Detail does not create the time axis.

Q58 ANSWER A

Stories

A. Story

Why: A story is a sequence of story points. Each point captures a worksheet or dashboard state and can include a caption, allowing the author to guide viewers through a narrative.

Exam trap: A dashboard combines views for exploration. A worksheet is a single view. A set is a subset of data, not a presentation format.

Q59 ANSWER B

Custom color palettes

B. `Preferences.tps` in My Tableau Repository.

Why: Custom color palettes are defined in `Preferences.tps` inside the My Tableau Repository folder. After Tableau restarts, the palette is available across workbooks.

Exam trap: A .twbx contains a workbook and its resources, not global preferences. Server settings do not define Desktop palettes. A .tds stores connection and field metadata.

Q60 ANSWER B

Navigation objects

B. Navigation object

Why: A navigation object creates a button or link that moves the user to another dashboard or sheet. It is the standard way to build multi-page dashboard navigation.

Exam trap: A text object displays text. An image object displays a picture. A web page object embeds external web content. None of them navigates between Tableau dashboards.

Domain 4 | Publish and Manage Content on Tableau Server and Cloud

5 questions | Official weight 9% | Questions 61-65

Q61 ANSWER A, E

Alerts vs. subscriptions

A. An alert sends an email when a condition on a view is met.
E. A subscription sends a scheduled snapshot, such as an image or PDF, of a view or workbook.

Why: Alerts are condition-driven: the user defines a threshold on a view and Tableau sends an email when the condition is met. Subscriptions are schedule-driven: Tableau emails a snapshot of a view or workbook at a chosen cadence.

Exam trap: The definitions are reversed in the statements that call an alert a scheduled snapshot and a subscription threshold-triggered. Recipients do not need Creator licenses; viewing and subscribing depend on permissions and site configuration, not on the Creator role.

Q62 ANSWER D

Extract refresh strategy

D. An incremental refresh using a date/time column.

Why: An incremental refresh updates only new or changed rows based on a date/time or numeric column, which is far more efficient than reloading 200 million rows. It requires a supported source and an appropriate incremental column.

Exam trap: Full refreshes reprocess the entire extract and are expensive at this scale. Deleting and recreating is also a full reload. A live connection changes the architecture and may not meet performance needs.

Q63 ANSWER A

Site roles

A. Creator

Why: The Creator role can connect to data, create content, and publish it. Explorer can create and edit content in permitted projects but cannot connect to data sources, and Viewer cannot author content.

Exam trap: Viewer is read/interact only. Explorer lacks the data-connection capability. Server Administrator is far broader than necessary and is not the minimum role.

Q64 ANSWER A

Custom views

A. A custom view

Why: A custom view saves a user's filter, sort, and other view selections on top of a published view. Other users continue to see the original view unless the custom view is shared.

Exam trap: A subscription emails a snapshot. An alert monitors a threshold. An extract is a data snapshot, not a saved personalized view.

Q65 ANSWER C

Publishing and scheduling flows

C. Publish the flow and use Tableau Prep Conductor.

Why: Scheduled flow runs on Tableau Server or Tableau Cloud are handled by Tableau Prep Conductor, which is part of Tableau Data Management. The flow must be published to the site first.

Exam trap: A .twbx is a packaged workbook, not a flow. A PDF is an output format. Subscriptions deliver view snapshots; they do not execute Prep flows.