Salesforce Certified Tableau Data Analyst — Practice Exam

100 Realistic Exam Questions

Exam simulation based on the official Salesforce exam guide (TDA-C01)

Exam Detail	Value
Question formats	Multiple choice, Multiple response
Time limit	120 minutes
Passing score	65%
Domain 1 — Connect to and Transform Data	24%
Domain 2 — Explore and Analyze Data	41%
Domain 3 — Create Content	26%
Domain 4 — Publish and Manage Content on Tableau Server and Tableau Cloud	9%

Instructions:

- Answer every question — unanswered questions receive no credit.
- Questions marked **(Select TWO)** or **(Select THREE)** are multiple-response items; you must select ALL correct options to earn credit (no partial credit).
- Answers with full explanations are in `answer.md`.
- Simulate real conditions: no references, ~70 seconds per question.

Domain 1: Connect to and Transform Data (Questions 1–24)

Question 1

A retail company runs hourly flash promotions and executives need a dashboard showing transactions with no more than a few minutes of latency. The database comfortably supports the query load. Which connection type should the analyst choose?

a) An extract with an hourly refresh schedule

b) A live connection

c) An extract with an incremental refresh

d) A published extract data source refreshed daily

Question 2

An analyst connects to a slow, legacy operational database. Dashboard queries take several minutes, and the analyst only needs data as of the previous night. What is the BEST approach to improve dashboard performance?

a) Keep the live connection and add data source filters

b) Create an extract and schedule it to refresh daily

c) Use Custom SQL against the live database

d) Blend the live database with a spreadsheet

Question 3

When configuring an extract in Tableau Desktop, which settings can the analyst define? **(Select THREE)**

a) Extract filters to limit the rows included

b) Aggregation of data to the level of visible dimensions

c) An incremental refresh keyed on a column such as an ID or a date

d) Automatic detection and creation of hierarchies between fields

---

Question 4

An analyst uses **Replace Data Source**. In the new source, the field `[State]` was renamed to `[Province]`. What happens to worksheets that used `[State]`?

a) Tableau automatically maps `[Province]` to `[State]` because they share a geographic role

b) Tableau renames `[Province]` to `[State]` in the new source

c) Fields map only by identical names, so sheets using `[State]` show errors until the issue is fixed

d) All worksheets using the old data source are deleted

Question 5

You receive an Excel workbook with a merged title banner in row 1, blank rows, explanatory notes, and footer totals. Which Tableau Desktop feature can automatically detect the true column headers and data region?

a) Pivot (multiple columns)

b) Data Interpreter

c) Custom Split

d) Custom SQL

Question 6

A survey dataset stores responses with one column per question (`Q1`, `Q2`, … `Q20`) and one row per respondent. You need one row per respondent per question for analysis. What is the BEST technique?

a) Select the 20 question columns, right-click, and choose Pivot (columns to rows)

b) Enable Data Interpreter on the file

c) Right-click the respondent field and choose Split

d) Create a data blend against a copy of the table

Question 7

The field `[Order Code]` contains values like `US-2024-1186`. You need the region prefix (`US`) as a separate field. What is the fastest way to do this in Tableau Desktop?

a) Use DATEPARSE on the field

b) Right-click the field and use Split (or Custom Split)

c) Pivot the field to rows

d) Replace the data source

Question 8

Which statements correctly describe **relationships** in Tableau's logical layer (the default data model)? **(Select TWO)**

a) Tableau applies join logic at query time based only on the fields used in the visualization

b) Relationships preserve each table's level of detail and avoid unintentionally dropping or duplicating rows

c) Relationships permanently flatten the tables into a single row-level table at connection time

d) Relationships require all tables to share exactly the same granularity

---

Question 9

An `Orders` table contains 1,000 rows. A `Returns` table contains 300 rows, and every return matches exactly one existing `Order ID`. An analyst creates a **left join** from `Orders` to `Returns` on `Order ID`. How many rows does the resulting table contain?

a) 1,300

b) 300

c) 1,000

d) 700

Question 10

An analyst receives a new CSV file every month (`Orders_Jan.csv`, `Orders_Feb.csv`, ...) with an identical schema, and wants new files added to the folder to be included automatically. What is the BEST approach?

a) Create a manual join between each new file and the existing files

b) Use Data Interpreter on each new file as it arrives

c) Use a union with a wildcard search

d) Use data blending across the files

Question 11

Sales targets per rep per quarter live in Excel; transactional orders live in SQL Server. The two sources cannot be joined directly and have different granularity. The analyst must show actual vs. target per rep. Which technique is designed for this?

a) A union of the two sources

b) A data blend on the common field

c) A wildcard union

d) A Custom SQL statement

Question 12

An analyst connecting to a SQL Server database wants the database itself to pre-filter rows with a `WHERE` clause and select only specific columns before Tableau reads the data. Which connection method supports this?

a) Data Interpreter

b) Union

c) Pivot

d) Custom SQL

Question 13

A colleague published a curated, certified data source to the company's Tableau Cloud site. How should an analyst connect to it from Tableau Desktop?

a) File > Open, then browse to the data source on the network

b) In the Connect pane, select Tableau Server, sign in to the site, and choose the published data source

c) Write a Custom SQL query against the published data source

d) Use Data > Replace Data Source

Question 14

An analyst must guarantee that **every** worksheet in a workbook excludes internal "Test" accounts, and also wants the extract itself to contain only the last two years of orders to keep it small. Which actions accomplish both goals? **(Select TWO)**

a) Add a context filter on Account

b) Add a data source filter excluding the test accounts

c) Add an extract filter limiting `[Order Date]` to the last two years

d) Add a table calculation filter on Account

Question 15

In Tableau Prep Builder, an analyst has three input steps with identical columns that need to be stacked into a single dataset. Which step should they add?

a) A Union step

b) An Aggregate step

c) A Pivot step

d) A Clean step

Question 16

In Tableau Prep, the `Orders` table is on the left side of a join step and `Returns` is on the right. The analyst must keep **all** orders, even those with no matching return. Which join type is correct?

a) Inner

b) Right

c) Left

d) Full outer

Question 17

A Tableau Prep flow processes 2 million transactional rows, but the final dashboard only needs monthly totals per region. Which step reduces and reshapes the data appropriately before output?

a) A Clean step with split fields

b) An Aggregate step grouping by Region and by month of Order Date

c) A Union step with a wildcard search

d) An Output step with full refresh only

Question 18

A budget spreadsheet stores months as separate columns (`Jan`, `Feb`, … `Dec`). In Tableau Prep, the analyst needs one row per month instead. Which step accomplishes this?

a) Aggregate

b) Clean

c) Union

d) Pivot (columns to rows)

Question 19

Which output types are available for a Tableau Prep flow? **(Select THREE)**

a) A file (`.hyper`, `.csv`, or `.xlsx`)

b) A published data source to Tableau Server or Tableau Cloud

c) A database table written back to a supported database

d) A packaged workbook (`.twbx`) template

Question 20

An analyst needs the dimension member `CA` to display as `California` on every view, without modifying the source data or writing a calculation. What should they use?

a) Create an alias for the dimension member

b) Create a calculated field with an IF statement

c) Convert the field from discrete to continuous

d) Create a group containing the single member

Question 21

An analyst places `YEAR([Order Date])` as a discrete (blue) field on Columns, and the line chart draws each year as a separate header with a broken axis. They want a single, unbroken time axis across all years. What should they do?

a) Create an alias for each year value

b) Change the field's default aggregation to Year

c) Convert the field from discrete to continuous

d) Replace the data source with a continuous date table

Question 22

The numeric field `[Rating]` (values 1–5) is treated as a measure, so every view automatically shows `SUM(Rating)`. The analyst wants to use the distinct rating values as headers/categories. What should they do?

a) Convert the field from discrete to continuous

b) Convert the field from measure to dimension

c) Create an alias for each rating value

d) Change the field's default sort order

Question 23

The field `[Profit Ratio]` defaults to `SUM` aggregation, which produces meaningless stacked ratios on views. The analyst wants every new view to average it instead. Where should this be configured?

a) Right-click the field > Default Properties > Aggregation > Average

b) Analysis > Totals > Total All Using > Average

c) Right-click the field > Create > Bins

d) Format > Numbers > Percentage on the view only

Question 24

A Tableau Prep profile pane shows the `Country` field contains `United States`, `USA`, `US`, and `U.S.`. What is the most efficient way to standardize these values?

a) Pivot the columns to rows

b) Replace the data source

c) Aggregate by Country

d) Use Group and Replace (Group Values) on the Country field

Domain 2: Explore and Analyze Data (Questions 25–65)

Question 25

A data source stores order dates as the string `20240315`. Which calculation converts these strings into real dates?

a) `DATE([Order Date String])`

b) `DATENAME("yyyyMMdd", [Order Date String])`

c) `DATEPARSE("yyyyMMdd", [Order Date String])`

d) `DATEPART("yyyyMMdd", [Order Date String])`

Question 26

An analyst needs to display the text label "March" on rows from `[Order Date]`. Which function returns the month **name** as a string?

a) `DATENAME('month', [Order Date])`

b) `DATEPART('month', [Order Date])`

c) `MONTH([Order Date])`

d) `DAY([Order Date])`

Question 27

You need to know how many days each order took to ship. Which calculation is correct?

a) `DATEADD('day', [Order Date], [Ship Date])`

b) `DATEDIFF('day', [Order Date], [Ship Date])`

c) `DATENAME('day', [Ship Date] - [Order Date])`

d) `[Ship Date] - [Order Date]` formatted as a number

Question 28

SKU values look like `ABC-1234-XL`. Which calculation returns the middle segment `1234`?

a) `LEFT([SKU], 4)`

b) `MID([SKU], 5, 4)`

c) `FIND([SKU], "-")`

d) `SPLIT([SKU], "-", 2)`

Question 29

The analyst must flag every description containing the word "refurb" regardless of capitalization (`Refurb`, `REFURB`, `refurbished`). Which calculation works reliably?

a) `CONTAINS(UPPER([Description]), "REFURB")`

b) `CONTAINS([Description], "refurb")`

c) `[Description] = "refurb"`

d) `SPLIT([Description], "refurb", 1)`

Question 30

Which calculated field correctly assigns orders to size tiers of "Small" (under 1,000), "Medium" (1,000–9,999), and "Large" (10,000 or more)?

a) `CASE [Sales] WHEN < 1000 THEN "Small" WHEN < 10000 THEN "Medium" ELSE "Large" END`

b) `IF [Sales] > 10000 THEN "Large" ELSEIF [Sales] > 1000 THEN "Medium" ELSE "Small" END`

c) `IF [Sales] < 1000 THEN "Small" ELSEIF [Sales] < 10000 THEN "Medium" ELSE "Large" END`

d) `IIF([Sales] < 10000, "Small", IIF([Sales] < 100000, "Medium", "Large"))`

Question 31

An analyst writes `CASE [Sales] WHEN < 5000 THEN "Low" END` and gets a syntax error. What is the correct fix and why?

a) CASE cannot be used in calculated fields; use ATTR instead

b) CASE only supports equality tests on a single field; rewrite the logic with IF/THEN for range conditions

c) CASE requires the field to be discrete; convert `[Sales]` to discrete first

d) CASE requires an ELSE clause; the error disappears once ELSE is added

---

Question 32

The field `[Discount]` contains NULLs for orders with no discount, which breaks an arithmetic calc. Which function cleanly replaces NULLs with 0 in arithmetic?

a) `ZN([Discount])`

b) `ISNULL([Discount])`

c) `IIF([Discount], 0, 1)`

d) `INT([Discount])`

Question 33

The analyst needs labels like `FY 2024` from `[Order Date]`. "FY" plus the four-digit year. Why does `"FY" + YEAR([Order Date])` fail, and what is the fix?

a) String functions cannot combine; use two separate fields

b) `YEAR()` returns a date; wrap it in `DATEPARSE` first

c) You cannot concatenate a string with a number; convert with `"FY " + STR(YEAR([Order Date]))`

d) Concatenation requires CONCAT(); it only fails on live connections

---

Question 34

A view should show the **average of each customer's total** sales (total each customer's orders first, then average those totals across the region). Which calculation does that?

a) `AVG({FIXED [Customer ID] : SUM([Sales])})`

b) `AVG([Sales])`

c) `SUM([Sales]) / COUNT([Customer ID])`

d) `{FIXED [Region] : AVG([Sales])}`

Question 35

The view contains `{FIXED [Country/Region] : SUM([Sales])}`. When the analyst adds a **dimension filter** on `[State]`, the FIXED result does not change. Why, and how can they make the calc respect that filter?

a) The FIXED calculation is broken; recreate it after adding the filter

b) FIXED LODs execute before dimension filters in the order of operations; add the State filter to context

c) FIXED LODs cannot be filtered at all; replace it with a table calculation

d) The filter is a measure filter; only dimension filters affect FIXED LODs

---

Question 36

At the City level of a view, you want the average **per-customer total** in each city. The view only contains `[City]`. Which LOD expression is correct?

a) `{FIXED [City] : AVG([Sales])}`

b) `{EXCLUDE [City] : SUM([Sales])}`

c) `{FIXED [Customer ID] : AVG([Sales])}`

d) `AVG({INCLUDE [Customer ID] : SUM([Sales])})`

Question 37

A view shows `[Category]` and `[Sub-Category]` on rows with `SUM([Sales])`. The

analyst wants each sub-category shown as a percent of its parent category's total. Which expression is the denominator?

a) `SUM({EXCLUDE [Sub-Category] : SUM([Sales])})`

b) `SUM({INCLUDE [Sub-Category] : SUM([Sales])})`

c) `SUM({FIXED [Sub-Category] : SUM([Sales])})`

d) `TOTAL(SUM([Sales]))` computed Table Down

Question 38

Which of the following is a valid **nested LOD** and correctly computes, for each region, the largest single customer total?

a) `{INCLUDE [Customer ID] : MAX({FIXED [Region] : SUM([Sales])})}`

b) `{FIXED MAX([Region]) : SUM([Sales])}`

c) `{FIXED [Region] : MAX({INCLUDE [Customer ID] : SUM([Sales])})}`

d) `{FIXED [Region] : SUM([Sales])} + {INCLUDE [Customer ID] : MAX([Sales])}`

Question 39

The view has `[Region]` on Rows and continuous `MONTH([Order Date])` on Columns. The analyst wants each cell to show cumulative sales from the start of the year within each region's row. Which setup is correct?

a) Quick table calculation Running Total, compute using Table Down

b) Quick table calculation Running Total, compute using Table Across

c) Quick table calculation Moving Average, compute using Pane Across

d) Calculated field `RUNNING_SUM(AVG([Sales]))`, compute using Cell

Question 40

The analyst wants each mark to show the average of the **current month plus the two previous months** to smooth volatility. Which moving average configuration is correct?

a) Previous values = 2, Next values = 0, with the current value included

b) Previous values = 3, Next values = 0, with the current value excluded

c) Previous values = 1, Next values = 1, with the current value excluded

d) Previous values = 2, Next values = 2, with the current value included

---

Question 41

Each mark in a cross-tab of `[Region] × [Segment]` should display that cell's share of the **entire table total**. Which quick table calculation and compute-using direction achieves this?

a) Percent of Total, compute using Table Down

b) Percent of Total, compute using Pane Across

c) Percent of Total, compute using Table (across then down)

d) Percent Difference From, compute using Table (down then across)

Question 42

The view shows monthly sales, and the analyst wants each month displayed as its percentage change relative to the previous month (for example, "+4.2%"). Which quick table calculation is correct?

a) Percent Difference From, relative to Previous

b) Difference From, relative to Next

c) Compound Growth Rate

d) Running Total, secondary calculation Difference

Question 43

Three products have sales of 500, 500, and 400. Using `RANK(SUM([Sales]))` (descending), what ranks are assigned?

a) 1, 1, 2

b) 1, 1, 3

c) 1, 2, 3

d) 2, 2, 1

Question 44

Management wants a flag on every product that sits in the **top 10% of sales values** across the company. Which approach gives each product a percentile standing for that comparison?

a) Add the Percentile quick table calculation to the sales field and filter for percentile ≥ 90

b) Sort descending and use an INDEX() ≤ 10 filter

c) Add a Running Total and stop at 90%

d) Create a Top 10 conditional filter on Product Name

Question 45

A view on annual revenue needs to display the steady **per-year growth rate** that compounds from the first to the last visible year (like a CAGR). What should the analyst use?

a) Percent Difference From, relative to First

b) A Moving Average table calculation

c) The Compound Growth Rate quick table calculation

d) `YEAR([Order Date]) / SUM([Sales])`

Question 46

An analyst wants to add a simple row-number column (1, 2, 3 …) to a text table of 500 products sorted by sales, then keep only the first 10 rows while keeping the numbering intact. Which function and filter approach is correct?

a) `RANK(SUM([Sales]))` filtered by a Top 10 dimension filter

b) `INDEX()` computed using Table Down, filtered to `INDEX() <= 10`

c) A FIXED LOD that counts rows, filtered by a dimension filter

d) Adding a Measure Values row count on Detail

Question 47

The analyst needs a view that always shows exactly the **ten products with the highest total sales**, updating automatically as data changes. How should they configure it?

a) Sort products descending and manually hide all rows after the tenth

b) Filter `[Product Name]`, open the Top tab, select By Field: Top 10 by Sales, SUM

c) Create a set with the top ten products selected by hand

d) Use a wildcard filter matching the ten product names

Question 48

A workbook has a Top 10 products filter and a `[Region]` dimension filter. The Top 10 is being selected across **all** regions first, and the Region filter then removes some of them, so the view shows fewer than ten products per region. What fixes this so each region keeps its own full top 10?

a) Convert the Top 10 filter to a measure filter

b) Replace the dimension filter with a wildcard filter

c) Right-click the Region filter and choose Add to Context

d) Recompute the quick table calculation using Pane Down

Question 49

An analyst wants to filter to all customers whose names **contain** the text "Corp" anywhere in the string. Which filter configuration is correct?

a) Dimension filter > Wildcard tab > Contains: "Corp"

b) Dimension filter > Condition tab > By formula: `SUM([Sales]) > 0`

c) Measure filter on `[Customer Name]` set to "At least"

d) Top tab > By field Top N containing "Corp"

Question 50

The view lists every sub-category with total profit. The analyst wants to **hide unprofitable sub-categories** (those whose total profit is negative) without touching individual rows. What is the correct approach?

a) Apply a dimension filter on Sub-Category and Exclude the negative ones manually

b) Apply an extract filter on Profit > 0

c) Drag `[Profit]` to Filters and set the measure filter to "At least 0"

d) Apply a context filter on Profit

Question 51

A workbook uses two related data sources: `Orders` and `Targets`, both containing `[Region]`. A Region filter on the Orders sheet should drive sheets built on **both** sources. Which option enables that?

a) Apply to Worksheets > Only This Worksheet

b) Apply to Worksheets > Selected Data Sources is not possible; filters never cross sources

c) Edit the filter to a context filter

d) Apply to Worksheets > All Using Related Data Sources

Question 52

Analysts in different countries must view `[Sales]` converted by an adjustable exchange rate. Users type a rate into a control and the view recalculates. Which design is correct?

a) Create a float parameter `[Exchange Rate]`, use `[Sales] * [Exchange Rate]` in a calculated field, and show the parameter control

b) Create a set on Sales and combine it with a currency field

c) Add an integer filter on Sales using "At least"

d) Use Data Interpreter with a currency translation file

Question 53

Stakeholders want a drop-down that switches a view between Top 5, Top 10, and Top 20 products. How should the analyst connect a parameter to the existing Top N filter?

a) Replace the filter with a FIXED LOD divided by the parameter

b) In the filter's Top tab, choose By Field and select the parameter from the value drop-down

c) Drag the parameter onto the Filters shelf directly

d) Parameters cannot drive filters; use three separate sheets instead

---

Question 54

A line chart needs a horizontal target line whose position managers can adjust with a slider. Which implementation is correct?

a) Draw a constant reference line and manually re-enter the value each time

b) Use a distribution band with a fixed percentile

c) Create a numeric parameter with a range, add a reference line, and set the line's Value to that parameter

d) Add an average line and set confidence to the parameter

Question 55

An analyst defines a dynamic set of "High-Value Customers" using a condition on total sales. They later want to intersect it with a set of "Returned Customers". What must be true to create the combined set?

a) The two sets must be built on the **same dimension**

b) One set must be a FIXED LOD and the other a group

c) Combined sets require both sets to be converted to bins first

d) Sets can never be combined; use a context filter instead

Question 56

For an age-distribution histogram, the analyst needs to bucket the continuous measure `[Age]` into equal-width ranges. What is the correct procedure?

a) Right-click `[Age]` > Create > Set, then choose "By formula"

b) Right-click `[Age]` > Create > Bins, and confirm or adjust the suggested bin size

c) Convert `[Age]` to a dimension, then group its members

d) Create a parameter for bucket width and a Top N filter

Question 57

The analyst wants users to expand `Category` into `Sub-Category`, and further into `Manufacturer`, with plus/minus controls in the view. What should they build?

a) Three separate worksheets placed side by side

b) A set for each level combined into one set

c) A hierarchy by dragging the fields onto each other in the Data pane, then using the `+/−` icons to drill

d) Sort the dimension by field and enable manual sort

Question 58

On a map, fifteen small states should be collapsed into a single "Other" label while the top states keep their names, with **all states still accounted for** in totals. Which feature fits best?

a) A dynamic set with IN/OUT, which hides the non-members

b) A bin with a fixed suggested size

c) A hierarchy with drill-down

d) A group created from the selected state headers (optionally including an "Other" rollup)

Question 59

Management wants a US map in which each **state's area is shaded** according to its return rate. Which map type and requirement apply?

a) Symbol map; requires latitude and longitude generated for each city

b) Filled map (choropleth); requires a geographic field with polygon support such as State

c) Density map; requires the mark type to be set to Shape

d) Heat map from the Show Me panel; requires two measures on the view

---

Question 60

A city-level delivery dataset has thousands of overlapping points. The analyst wants to reveal concentration hotspots rather than plot every point. What should they do?

a) Change the mark type to Density and adjust the intensity on the Color card

b) Create bins on City and build a histogram

c) Add an extract filter sampling 10% of rows

d) Convert City to a group and enable data blending

Question 61

Store locations should appear as **circles** on a map, sized by sales and colored by profit. Which configuration is correct?

a) Filled map with Sales on Size and Profit on Detail

b) Density map with Profit on Color

c) Symbol map with Sales on Size and Profit on Color

d) Choropleth with Profit on Label

Question 62

The analyst needs to overlay **two** datasets on one map: country polygons (sales by country) plus delivery points that exist only as raw `[Latitude]/[Longitude]` numbers. Which approach works?

a) It is impossible to combine two data layers on one map

b) Convert Latitude/Longitude to bins, then create a blend

c) Use Data Interpreter to geocode the points, then union them

d) Create points with `MAKEPOINT([Latitude], [Longitude])` and use "Add a Marks Layer" to render the second dataset as its own layer

---

Question 63

A view is paneled by Region (each region is a pane). A reference line should show **each region's own average** — not one global average across the table. How should the line be scoped?

a) Set the reference line scope to Per Pane using the regional average computation

b) Set the scope to Entire Table so every pane matches

c) Add a grand total using Average instead of a line

d) Use a trend line with the Linear model per cell

Question 64

Monthly active users grow multiplicatively, and the analyst wants to overlay a best-fit **exponential** curve and inspect its quality (R-squared, p-value). What is the correct workflow?

a) Right-click the axis > Add Reference Line > Exponential, then check the legend

b) From the Analytics pane drag Trend Line onto the view choosing the Exponential model; hover the line or right-click > Describe Trend Line to see R-squared and p-value

c) Add a forecast and set seasonality to Exponential

d) Use Data Interpreter with a statistics plug-in

Question 65

A completed time-series view (continuous month + revenue) needs a **12-month forward projection** with 95% prediction intervals, and the analyst suspects multiplicative seasonality. Which is correct?

a) Forecasting is unavailable on continuous months; convert the date to discrete first

b) Add a Moving Average table calculation with 11 previous values

c) Drag Forecast from the Analytics pane, then use Forecast Options to set the length to 12 months, the prediction interval, and multiplicative seasonality (forecasting uses exponential smoothing)

d) Trend lines extend automatically past the data; enable Extend to +12 months

---

Domain 3: Create Content (Questions 66–91)

Question 66

The business asks for the simplest chart to compare total sales across fifteen sub-categories, sorted for instant ranking. Which chart type is the best fit?

a) Bar chart

b) Pie chart

c) Histogram

d) Box plot

Question 67

The analyst wants a "heat-style" cross-tab where each Sub-Category × Region cell is a shaded square with the sales figure inside it. How should a highlight table be constructed?

a) Put Region on Columns, Sub-Category on Rows, Sales on Size, and mark type to Bar

b) Put both dimensions on Detail and Sales on Angle with a Pie mark

c) Put Sales on Filters and use a Top N of 1

d) Put the discrete dimensions on Rows/Columns, then put the measure on both Color and Label with the Square mark type

---

Question 68

Leadership wants to visualize the relationship between `[Discount]` and `[Profit]` for every order, one point per order. Which build creates a proper scatter plot?

a) SUM(Discount) to Columns, SUM(Profit) to Rows, Category to Color only

b) Discount to Columns, Profit to Rows (both continuous measures), and Order ID added to Detail to disaggregate

c) Profit on Color, Discount on Label, mark type Square

d) Order Date on Columns and both measures on Rows using dual axis

---

Question 69

An analyst drops `[Age]` (continuous measure) into an empty view and selects the histogram from Show Me. What does Tableau do automatically?

a) It creates a new bin field from Age and plots CNT(Age) per bin

b) It creates a set of the ten oldest customers

c) It groups ages into a hierarchy for drill-down

d) It converts Age to a string and builds a highlight table

Question 70

Marketing wants a single-part-of-whole chart where rectangle size shows Sales and rectangle color shows Profit across Category and Sub-Category. Which chart and encoding is correct?

a) Tree map with Sales on Angle and Profit on Tooltip

b) Packed bubbles with Sales on Color and Profit on Size

c) Tree map with Sales on Size and Profit on Color, Category/Sub-Category on Label/Detail

d) Pie chart with Profit on Angle and Sales on Color

Question 71

The PMO provides a table of tasks with `[Start Date]` and `[End Date]` and requests a timeline view showing each task's duration as a horizontal bar. Which design produces a Gantt chart?

a) Continuous Start Date on Columns, Task on Rows, mark type Bar, AVG(End Date) on Size

b) Continuous Start Date on Columns, Task on Rows, mark type Gantt Bar, and a calculated field `DATEDIFF('day',[Start Date],[End Date])` on Size

c) End Date on Columns, Start Date on Rows, mark type Line, Duration on Path

d) Start Date on Filters with Top N, Task on Text, mark type Square

---

Question 72

Finance asks: "Show me how profit is **distributed** within each category — median, quartiles, and outliers." Which view answers this best?

a) A highlight table of AVG(Profit) by Category

b) A pie chart of total profit by Category

c) A packed bubble chart sized by profit

d) Category on Columns, disaggregated Profit on Rows, then Box-and-Whisker Plot from Show Me

---

Question 73

A view must show Sales as bars and Profit Ratio as a line on the **same chart with two independent vertical axes**. What is the correct procedure?

a) Drag both measures to a single axis field; Tableau separates them automatically

b) Create a combined field with Measure Values and set mark type to Automatic

c) Place both measures on Rows, right-click the second measure pill, choose Dual Axis, then right-click its axis to Synchronize (or not) and style each Marks card independently

d) Build the line on one sheet and float it over the bars sheet on a dashboard

---

Question 74

A chart shows `[Response]` values "Small", "Medium", and "Large" alphabetically, but the business wants them ordered Small → Medium → Large. Which sort accomplishes this **custom order**?

a) Right-click the Response pill > Sort > Manual, then arrange the values in the desired order

b) Right-click the axis > Clear Sort

c) Sort by Field > Sales descending

d) Right-click the dimension > Create > Set and reorder IN/OUT

Question 75

A dashboard with four worksheets must remain perfectly aligned and resize cleanly when the browser window changes. Which layout practice is recommended?

a) Make every object floating and position them pixel-by-pixel

b) Place the worksheets in an arrangement of tiled horizontal and vertical layout containers

c) Set the dashboard size to Automatic and float all objects

d) Export each sheet as an image and arrange them as floating images

---

Question 76

A dashboard will be embedded into a portal iframe that is exactly 1200 × 800 pixels and must never scroll. Which size setting should be used?

a) Automatic, so it adapts to any browser

b) Range with minimum 800 × 600

c) Fixed size 1200 × 800 (an exact preset/custom size)

d) Fit to the widest worksheet's width

Question 77

The analyst edited a worksheet that feeds an existing story point, and the story point now displays an "Update" notification badge. What does clicking **Update** do?

a) Replaces the story point's snapshot with the worksheet's current saved state

b) Duplicates the story point as a new blank point

c) Publishes the story to Tableau Server

d) Reverts the worksheet to its state when the story was created

---

Question 78

Executives will view a dashboard mostly on phones, but it was designed for desktop. What should the analyst configure in Tableau Desktop?

a) Nothing — dashboards cannot be displayed on phones

b) Use the Device Preview / Layout options to add and customize a Phone layout for the dashboard

c) Republish the workbook with mobile credentials embedded

d) Create a story, which automatically reformats for phones

Question 79

The analyst wants a **live web page** (for example, the company's intranet KPI page) displayed inside the dashboard and update it, optionally, when users click marks. Which object/ technique is correct?

a) A Text object containing a hyperlink

b) An Image object pointing at the URL

c) A floating worksheet with a URL alias

d) A Web Page dashboard object with a URL (optionally driven by a URL action)

Question 80

On a published dashboard, users should be able to click a mark on the Sales map and instantly filter the other three views to that selection — with no separate quick filter. What is the fastest way to enable this?

a) Select the map on the dashboard and click the Use as Filter (funnel) tool

b) Publish the workbook with interactivity enabled

c) Drag the Region field to the Filters shelf on every sheet

d) Add a context filter on Region at the data source

Question 81

A filter action runs when a user selects a bar. When the user clicks empty space (clearing the selection), the dashboard should **keep the last-filtered state** rather than resetting. Which setting controls this?

a) Run action on: Hover

b) Target filters: All Fields

c) Clearing the selection will: Leave the filter

d) Show all values when the action ends

Question 82

Clicking a state in a dashboard should open the state's Wikipedia page in a browser. How should the analyst configure the URL action?

a) URL action with text `Wikipedia` only; Tableau finds the page automatically

b) A URL action run on Select (or Menu) with a URL template embedding the field token, e.g. `https://en.wikipedia.org/wiki/<State>`

c) A highlight action with Target = URL

d) A web page object with no URL action; it guesses context

Question 83

The analyst wants hovering over a product in one view to **visually emphasize** its related marks in all other views — without removing any data from those views. Which action type is correct?

a) Filter action run on Hover

b) Set action with Remove All Values on clear

c) URL action run on Hover

d) Highlight action run on Hover

Question 84

A dashboard uses a set action so users can click customers to add them to a "Focus" set. When the selection is cleared, the chosen customers should **remain** in the set. Which "clearing the selection" behavior is correct?

a) Keep set values

b) Remove all values from set

c) Add all values to set

d) Show all values

Question 85

Analysts should be able to click any date on a seasonal chart to reposition a reference line that marks the "comparison date" throughout the dashboard. Which feature updates a parameter value from a viz interaction?

a) A highlight action using Selected Fields

b) A URL action run on Menu

c) A parameter action that writes the clicked field value into the parameter driving the reference line

d) A context filter placed on Order Date

Question 86

Before dynamic zone visibility existed, a common technique displayed one of several sheets according to a "sheet selector" parameter. Which configuration makes the unused sheets vanish so the chosen one fills the space?

a) Place all sheets in a vertical container; nothing else is required

b) Filter each sheet by a calculated field equal to the parameter value (e.g. `[Sheet Param] = 'Sales'`) and place the sheets in the **same container**; empty-filtered sheets collapse

c) Use a highlight action on text values

d) Publish each sheet as a separate workbook and link them with URL actions

---

Question 87

A dashboard should reveal a detail panel only when exactly one category is selected, and let users collapse a filter panel with a toggle. Which two features implement these behaviors? **(Select TWO)**

a) Dynamic Zone Visibility driven by a Boolean field/parameter ("Control visibility using value")

b) Trend-line models with confidence intervals

c) Data Interpreter with a sheet-detection rule

d) The Show/Hide button on a floating dashboard object

Question 88

Hovering over a country on a map should pop up a compact **line chart of that country's trend** inside the tooltip. Which feature must the analyst use, and how is it configured?

a) An annotation of type Point with an image inserted

b) Viz in Tooltip: Edit the tooltip, Insert > Sheets, choose the trend sheet, and set its max size; the embedded view is filtered to the hovered mark

c) A story point captioned with the country name

d) A reference band set to Per Cell on the country dimension

Question 89

The analyst annotates "Record holiday sales!" on a view. If the underlying data refreshes and the mark moves or disappears, the commentary must follow the **specific mark** it describes (or show the annotation as orphaned so it can be removed). Which annotation type attaches to a specific mark value rather than a fixed coordinate or free-floating area?

a) Mark annotation

b) Point annotation

c) Area annotation

d) Text object on a dashboard

Question 90

A dashboard looks cluttered: the analyst wants consistent **empty space around each view and object**. Where is this padding applied?

a) Format worksheet > Lines > Grid Lines set to None

b) The Size shelf on the Marks card

c) The Layout tab of the dashboard — Outer Padding (and Inner Padding) per item

d) Worksheet > Export > Image with padded margins

Question 91

The design team delivered a set of approved PNG icons (with transparent backgrounds) to encode statuses as marks. Where must the files live for Tableau Desktop to offer them as a custom shape palette, and what refreshes an already-open palette list?

a) Any temp folder; Tableau scans the disk on every open of the Color card

b) Inside the workbook (.twb) as embedded text fields

c) In the server project directory so publish picks them up automatically

d) In the `Shapes` folder inside the My Tableau Repository (each subfolder becomes a palette), then click Reload Shapes in the Edit Shapes dialog

---

Domain 4: Publish and Manage Content on Tableau Server and Tableau Cloud (Questions 92–100)

Question 92

An analyst is ready to share a finished workbook with the Marketing project on Tableau Cloud. What is the correct publish workflow from Desktop?

a) File > Save As > PDF, then upload the PDF to the project

b) Server > Publish Workbook, sign in, choose the Marketing project, set name/tags, choose which sheets to include, and decide on tabbed navigation before publishing

c) Data > Replace Data Source with the published source, which auto-publishes the workbook

d) Copy the .twbx file into the site's document library folder

---

Question 93

The analyst publishes a data source so the whole team can connect to one governed copy. During publishing, which choice ensures scheduled refreshes and subscriptions **do not fail with credential prompts**, and what updates Desktop workbooks to use it?

a) Publish with "Server prompt" authentication; workbooks update automatically overnight

b) Publish as a .twbx with the workbook; nothing else needed

c) Embed the database credentials (authentication) when publishing, and choose "Update workbook to use the published data source"

d) Export the source as CSV; credentials are not required for flat files

---

Question 94

A business user needs the **numbers behind a summary table** in Excel for a one-off audit. Which export path from Tableau Desktop produces a usable crosstab?

a) Worksheet > Export > Crosstab to Excel (or Copy > Crosstab and paste into Excel)

b) Data > Replace Data Source with an Excel extract

c) Server > Publish Workbook with "Include External Files"

d) File > Print to PDF, then convert the PDF to Excel manually

---

Question 95

Sales leadership wants the regional performance dashboard **emailed to the whole team every Monday at 8:00 AM** as an image (PDF optional) without anyone logging in. Which Tableau Server/Cloud feature does this?

a) A data-driven alert on the Sales axis

b) A subscription to the view/workbook scheduled for Mondays, delivered by email to the specified recipients

c) An extract refresh schedule set to weekly

d) A published data source with embedded credentials

Question 96

An extract of a huge orders table must refresh every morning, but a **full reload is too slow**. The table has an ever-increasing `[Order ID]`. What should the analyst configure?

a) A scheduled full refresh with a smaller sample of rows

b) A data source filter limiting order years

c) An incremental extract refresh keyed on Order ID, which appends only rows newer than the last refreshed value

d) A wildcard union with yesterday's CSV only

Question 97

A Tableau Prep flow cleans and appends survey data and must run **unattended every night** so the published data source is fresh by morning. How is this accomplished?

a) Schedule an extract refresh on the workbook; it will run the flow too

b) Publish the flow to Tableau Server/Cloud and create a scheduled task for the flow (on Tableau Server this uses Tableau Prep Conductor; on Tableau Cloud flow scheduling is built in), ensuring credentials for inputs/outputs are embedded

c) Leave Tableau Prep Builder open overnight with the flow loaded

d) Convert the flow to a subscription and add recipients

Question 98

A KPI dashboard shows daily active users on a continuous numeric axis. Management wants an automatic email **whenever the value drops below 10,000**, sent to the distribution list. Which feature and its requirements apply?

a) Subscriptions with a threshold checkbox

b) A highlight action that emails recipients

c) A context filter with the "Notify" condition

d) A data-driven alert set on the continuous numeric axis with condition "below 10,000" and specified recipients (alerts are only available for views with a numeric axis)

Question 99

A colleague wants to fix a title on a published dashboard directly in the browser, save the change as a **new** workbook, and be able to undo back to the last published state. Which statements about web editing are correct?

a) Web editing requires a Creator or Explorer (can publish) site role and edit permissions; use Save As for a new copy and Revert to return to the last published version

b) Anyone with a Viewer role can use Save As on any published workbook

c) Web editing can only overwrite the original; there is no version control or revert

d) Save As is only possible in Tableau Desktop, never on the web

---

Question 100

A published workbook uses an **extract** of a SQL Server database, but the data is never fresh: subscriptions arrive with stale figures and the refresh keeps failing asking for credentials. Which TWO actions fix this? **(Select TWO)**

a) Embed the database credentials with the extract connection when publishing

b) Convert the extract to a live connection so credentials are never needed

c) Assign the published extract to a refresh schedule on the server

d) Increase the subscription frequency to hourly

End of Practice Exam

Check your answers in `answer.md`. Score each domain separately — on the real exam you need 65% overall, but domain-level weakness signals where to study.

Domain → Question map: Domain 1: Q1–Q24 | Domain 2: Q25–Q65 | Domain 3: Q66–Q91 | Domain 4: Q92–Q100