Salesforce Certified Tableau Data Analyst (Analytics DA-201)

Full Practice Exam — 100 Realistic Exam-Style Questions

About the Real Exam (from the official Exam Guide)

Item	Detail
Questions	60 scored multiple-choice / multiple-select items (+ up to 5 unscored)
Time	~105 minutes
Passing Score	65%
Cost	US $200 + applicable taxes
Delivery	Pearson VUE (test center or online proctored)
Prerequisite	None (6+ months hands-on Tableau experience recommended)

Exam Blueprint (question weighting in this paper matches the official guide)

Domain	Weight	Questions in this paper
Domain 1: Connect to and Transform Data	24%	Q1 – Q24
Domain 2: Explore and Analyze Data	41%	Q25 – Q65
Domain 3: Create Content	26%	Q66 – Q91
Domain 4: Publish and Manage Content on Tableau Server and Tableau Cloud	9%	Q92 – Q100

Instructions

- Question types are labeled: **[Single Choice]**, **[Multiple Select – Choose TWO]**, and **[Build List – Order the steps]**.
- Multiple-select questions are scored all-or-nothing on the real exam — partial selections receive **no credit**. Select exactly the number of answers indicated.
- Target completing all 100 questions in one sitting under exam-like conditions (no Tableau, no browser).
- Answers with full explanations are in **answer.md** (same folder).

Domain 1: Connect to and Transform Data (24%)

Q1. [Single Choice] A regional operations dashboard connects **live** to a production SQL

Server database. Users complain that every interaction is slow, and the database administrator reports heavy query load on the server whenever people use the dashboard. The business confirms the data only needs to be current as of 7:00 AM each morning. What should you do?

- A. Keep the live connection and add more filters to reduce the number of returned rows
- B. Create an extract with no scheduled refresh
- C. Create an extract and schedule a daily full refresh that completes before 7:00 AM
- D. Replace the connection with a data blend from a smaller database

---

Q2. [Single Choice] Which statement about `.hyper` extract files is **TRUE**?

- A. You can convert a `.hyper` extract back to a `.tde` extract at any time
- B. In Tableau 10.4 and older versions, extracting data automatically produces a `.hyper` file
- C. You can use **Export as Version** to downgrade a workbook that contains a `.hyper` extract to an older Tableau version
- D. Extracts in the `.hyper` format can contain billions of rows of data

---

Q3. [Single Choice] Your analytics team maintains a certified, governed data source that is published to your company's Tableau Cloud site. You are building a new workbook in Tableau Desktop and must use this same governed data (not the raw database). What should you do?

- A. Use the **Tableau Server / Tableau Cloud** connector, sign in to the site, browse to the published data source, and connect to it
- B. Export the published data source to a CSV file and connect to the CSV
- C. Connect directly to the underlying database using the administrator's credentials
- D. Download any workbook that uses the data source and copy its connection

---

Q4. [Build List – Order the steps] A worksheet was built on an old data source. You must switch the worksheet to a new table that has identical field names and structure by replacing the data source. Put the steps in the correct order (each step is used once):

- A. On the Data Source page, drag the new table to the canvas to set up the data
- B. Open the workbook that connects to the original data source
- C. In the **Replace Data Source** dialog box, select the current data source and the replacement data source, and then click **OK**
- D. Go to a worksheet and select **Data** > **Replace Data Source**
- E. Select **Data** > **New Data Source** and then connect to the new data source

---

Q5. [Single Choice] You connect to a Microsoft SQL Server database. Using **custom SQL**, you need to retrieve rows from a table named `orders`, but only rows where the region is East or West. How should you do this?

- A. Right-click the Orders table and select **Custom SQL Query**, then write: `SELECT * FROM orders WHERE region = 'East' + region = 'West'`
- B. Double-click **New Custom SQL** on the data source page, then write: `SELECT * FROM orders WHERE region = 'East' or region = 'West'`
- C. Double-click **New Custom SQL**, then write: `SELECT * FROM orders WHERE region = 'East' and region = 'West'`

- D. Double-click **New Custom SQL**, then write: `SELECT * FROM orders WHERE region = 'East', WHERE region = 'West'`

Q6. [Single Choice] You connect to a published data source on Tableau Server from Tableau Desktop. Tomorrow you will be traveling and must be able to continue working **offline**. How can you create a local copy of the data source?

- A. On the **File** menu, select **Save As Local Copy**
- B. On the **Worksheet** menu, select the data source and then select **Create Local Copy**
- C. On the **Data** menu, select the data source and then select **Create Local Copy**
- D. It is not possible to create a local copy of a server data source

---

Q7. [Multiple Select – Choose TWO] You connect to an Excel file that contains title rows, footnotes, and an embedded summary subtable. You enable **Data Interpreter**. Which two statements are TRUE?

- A. It interprets your file and determines where the fields and values of your dataset are
- B. It automatically creates relationships between the tables in the file
- C. It automatically publishes the cleaned datasets to Tableau Server
- D. You'll see a **Review the Results** link — clicking it opens a file that explains how the data source was interpreted

---

Q8. [Single Choice] A `Name` field contains values in the format `Smith;John`. You need to create two fields — `Last Name` and `First Name` — without writing a calculation. What should you do?

- A. Use the automatic **Split** option, since it detects the semicolon delimiter automatically
- B. Use the **Data Interpreter** to separate the values
- C. Pivot the field into two rows
- D. Use **Custom Split** and specify `;` as the delimiter

Q9. [Single Choice] You have a spreadsheet with one column per month (`05/2019`, `06/2019`, `07/2019`, `08/2019`, `09/2019`) and one `Position` column. You want to reshape the data so each month becomes a row, producing a `Date` column and a `Sales` column you can analyze over time. What should you do in Tableau Desktop?

- A. Merge the month columns into a single column and change its data type to Date
- B. On the data source page, select the five month columns in the data grid, right-click, and choose **Pivot**; then rename `Pivot Field Names` to `Date`, change its data type to Date, and rename `Pivot Field Values` to `Sales`
- C. Use a wildcard pivot to rearrange the data automatically
- D. Use a custom split on the `/` character

Q10. [Build List – Order the steps] You have three Excel tables with identical column structure that you must stack into a single table using a **union** on the data source page. Put the steps in the correct order (each step is used once):

- A. Drag the second and third tables from the left pane into the **Union** dialog, directly below the first table

- B. Connect to the first table and open the Data Source page
- C. Click **Apply** or **OK**
- D. Double-click **New Union** in the left pane of the data source page

---

Q11. [Single Choice] You are modeling data with an `Orders` table and a `Returns` table. You must be able to analyze **all orders** (whether or not they were returned), and you want Tableau to only query the `Returns` table when a visualization actually uses fields from it, for performance reasons. Which approach should you use?

- A. Create a physical **left join** between Orders and Returns
- B. Establish a logical **relationship** between Orders and Returns
- C. Use **data blending** with Orders as the primary source and Returns as the secondary source
- D. Write a custom SQL view that performs a LEFT OUTER JOIN

Q12. [Multiple Select – Choose TWO] Which two statements correctly describe **data blending** in Tableau?

- A. Blending physically merges rows from the two sources at the row level, exactly like a join
- B. Measures from the secondary data source are aggregated before they are combined with the primary source
- C. A blend can be published as a single, unified data source for others to reuse
- D. All members of the primary data source appear in the view even when the secondary source has no matching value

---

Q13. [Single Choice] Your workbook connects to a sensitive HR database. A set of confidential test rows must **never be stored in the extract file itself** when the extract is created. Which filter type should you use?

- A. A data source filter
- B. A context filter
- C. An **extract filter**, applied when the extract is created
- D. A dimension filter on every worksheet

Q14. [Single Choice] While assessing data quality, you find the same city stored as `New York`, `NY`, and `new york` in a City field. Which data quality trait does this problem affect?

- A. Completeness
- B. Consistency
- C. Accuracy
- D. Timeliness

Q15. [Single Choice] A data source contains 30 fields related to sales that clutter the Data pane. You want to group related fields together so analysts can find them easily. What should you do?

- A. Create a group containing the fields
- B. Create a hierarchy from the fields
- C. Rename every field with a common prefix

- D. Select the fields in the Data pane, right-click, and choose **Folders** > **New Folder**, then drag the fields into it

---

Q16. [Single Choice] A multinational retailer stores regional sales data in separate Excel files (`Sales_North.xlsx`, `Sales_South.xlsx`, `Sales_East.xlsx`, `Sales_West.xlsx`). Each file has the same structure. In Tableau Prep Builder, you need a single table that **automatically includes new regional files** when they are added to the folder in the future. Which step should you take?

- A. Add an Input step for one region and join the other files to it
- B. Configure a **Wildcard Union** in the Input step to match files by name pattern in the directory
- C. Manually drag each file into the Flow pane and connect them with Union steps
- D. Use the Data Interpreter to merge the sheets

Q17. [Single Choice] You have a Tableau Prep flow that processes monthly sales data and outputs a `.hyper` extract used by several dashboards. Each time the flow runs, the **new monthly rows must be added to the existing `.hyper` file** without deleting the historical data. Which write option should you select in the Output step?

- A. Create table
- B. Replace data
- C. **Append to table**
- D. Update table

Q18. [Single Choice] In Tableau Prep Builder, you need to transform an order-level table into one row per `Region` and `Segment`, showing the total `Sales` for each combination. How should you configure the step?

- A. Add an **Aggregate** step; drag `Region` and `Segment` to **Grouped Fields** and `Sales` to **Aggregated Fields** (SUM)
- B. Add a Clean step and drag `Region` and `Segment` to Grouped Fields
- C. Add a Pivot step and aggregate with `Region` and `Segment`
- D. Add a New Rows step with `Region` and `Segment`

Q19. [Single Choice] A vehicle-rental company stores monthly revenue as one row per vehicle type (`SEO`, `PPC`, `Other`, `Intercompany`). They want a **separate column for each vehicle type** instead. Which transformation should you perform in Tableau Prep?

- A. Add a Pivot step, select **Columns to Rows**, and use vehicle type as the pivot value
- B. Add an Aggregate step grouped by vehicle type
- C. Join the flow to a lookup table of vehicle types
- D. Add a Pivot step, select **Rows to Columns**, and drag the vehicle type field so its values become the new column headers

---

Q20. [Single Choice] In Tableau Prep, five records contain variants of the same person's name: `Jon Smith`, `John Smyth`, `Jhon Smith`, `Jon Smyth`, `John Smith`. You must group all five values into one automatically. Which **automatic grouping** option should you use?

- A. Common Characters
- B. Pronunciation
- C. Manual Selection
- D. Spelling

Q21. [Single Choice] Your team runs a Tableau Prep flow every Monday at 6:00 AM. The analyst who built the flow is on leave, and you must ensure the flow keeps running on this schedule without opening Tableau Prep Builder. What should you do?

- A. Save the flow locally and use the Windows Task Scheduler to run Tableau Prep Builder
- B. Output the flow to a CSV and refresh the connected data source manually each week
- C. Publish the flow to Tableau Server or Tableau Cloud and configure a scheduled run
- D. Publish only the flow's output as a data source and schedule an extract refresh

---

Q22. [Single Choice] You drag a date field from the Data pane onto a worksheet and convert it from **discrete to continuous**. What happens?

- A. The dates become text labels on headers
- B. The dates get a continuous (green) axis
- C. Dates cannot be converted to continuous fields
- D. Nothing — dates are always continuous

Q23. [Single Choice] A CSV file loads its `Postal Code` field as a **measure** (numeric). You need it to behave as a geographic **dimension** member. What should you do?

- A. Click and drag the field from the **Measures** area of the Data pane and drop it into the **Dimensions** area
- B. It is not possible to change the role of a loaded field
- C. Convert the field to a string only, which automatically fixes the role
- D. Create a calculated field `FLOAT([Postal Code])` and use it instead

Q24. [Single Choice] Stakeholders want the region member `Central` to display as `Midwest` in every view that uses the Region field, without changing the underlying data. What should you use?

- A. Rename the Region field in the data source
- B. Create a group that combines regions
- C. Create an **alias** for the member (`Central` → `Midwest`) via the field's Aliases settings
- D. Create a calculated field that replaces the string value

---

Domain 2: Explore and Analyze Data (41%)

Q25. [Single Choice] You have a dataset that contains a list of gym equipment and the exercises that use them:

Equipment	Exercise
Barbell	Bench Press
Dumbbell	Bicep Curl
Jump Rope	Double-Under
Barbell	Front Squat
Dumbbell	Overhead Press

Which formula returns the **number of distinct items** in the equipment list?

- A. `MAX([Equipment])`
- B. `COUNT([Equipment])`
- C. `COUNTD([Equipment])`
- D. `ATTR([Equipment])`

Q26. [Single Choice] You have an orders dataset. You need to find the **most recent order date for each customer**, but `Customer Name` is not (and will not be) in the view. Which formula should you use?

- A. `MAX([Order Date])`
- B. `{FIXED [Customer Name] : [Order Date]}`
- C. `{MAX([Order Date]) : FIXED [Customer Name]}`
- D. `{FIXED [Customer Name] : MAX([Order Date])}`

Q27. [Single Choice] A Data Analyst needs to calculate the **percent of regional sales that each state contributes**. As a first step, the analyst needs total sales per region. Which calculation accomplishes this?

- A. `{FIXED [State] : SUM([Sales])}`
- B. `{FIXED [Region] : SUM([Sales])}`
- C. `{FIXED [State], [Region] : SUM([Sales])}`
- D. `{FIXED [Region] : TOTAL(SUM([Sales]))}`

Q28. [Single Choice] Your view shows `SUM(Sales)` by `Category`. Management also wants to see the **average sub-category sales** for each category — a finer level of detail than what is displayed in the view. Which calculation should you use (then aggregate it with AVG in the view)?

- A. `{INCLUDE [Sub-Category] : SUM([Sales])}`
- B. `{FIXED [Sub-Category] : SUM([Sales])}`
- C. `{EXCLUDE [Sub-Category] : SUM([Sales])}`
- D. `SUM([Sales])`

Q29. [Single Choice] Your view shows Sales broken out by `Region` **and** `Category`. You want to display, alongside each category bar, the **total sales of the whole region** (ignoring the category breakout). Which calculation should you use?

- A. `{FIXED [Category] : SUM([Sales])}`
- B. `{INCLUDE [Category] : SUM([Sales])}`
- C. `{EXCLUDE [Category] : SUM([Sales])}`

- D. `WINDOW_SUM(SUM([Sales]))`

Q30. [Single Choice] A worksheet contains a FIXED Level of Detail calculation (`{FIXED [Customer Name] : MIN([Order Date])}`). You then apply a **standard dimension filter** on `Category` to the worksheet. How does the filter affect the view?

- A. The filter changes both the displayed data and the values returned by the FIXED LOD calculation
- B. The FIXED LOD is computed first, so the filter is ignored and the view does not change at all
- C. The view returns an error because filters cannot coexist with FIXED LODs
- D. The filter changes the data displayed in the worksheet, but it does **not** influence the values of the FIXED LOD calculation

---

Q31. [Single Choice] You need to create a calculated field that returns the **number of the month** (for example, `3` for March) from `[Order Date]`. Which calculation should you use?

- A. `DATEPART('month', [Order Date])`
- B. `DATENAME('month', [Order Date])`
- C. `DATETRUNC('month', [Order Date])`
- D. `DATEPARSE('month', [Order Date])`

Q32. [Single Choice] You want to show the **average number of days between Order Date and Ship Date** by Ship Mode, and users must be able to choose whether the difference is measured in days, weeks, months, or years. You create a parameter named `Date Part` whose allowed values are `day`, `week`, `month`, and `year`. Which calculation should you use (then aggregate with AVG)?

- A. `DATEDIFF('day', [Order Date], [Ship Date])`
- B. `DATEADD([Date Part], [Order Date], [Ship Date])`
- C. `DATEDIFF([Date Part], [Order Date], [Ship Date])`
- D. `DATENAME([Date Part], [Order Date])`

Q33. [Single Choice] Your dataset has one `[Address]` field. In some rows the field also contains an e-mail address (for example, `58 Bay Rd. Camel Springs, IL 60122, ann.d235@gmail.com`). You need a calculated field that identifies the rows that contain an e-mail address. Which formula should you use?

- A. `STARTSWITH([Address], "@")`
- B. `CONTAINS([Address], "@")`
- C. `REPLACE([Address], "@", "")`
- D. `LEN([Address])`

Q34. [Single Choice] A string field named `Name` contains unnecessary semicolons (for example, `Smith;;John`). Which function should you use to remove the semicolons from the field?

- A. `TRIM([Name])`
- B. `LTRIM([Name])`
- C. `LEFT([Name], 1)`

- D. `REPLACE([Name], ";", "")`

Q35. [Multiple Select – Choose TWO] You have a `Subject` field with values: `Computer Science`, `Science`, `English`, `Social Studies`. You need a new calculated dimension named `Category` that returns:

- `Sciences` when Subject is Computer Science or Science
- `Humanities` when Subject is English or Social Studies

Which **two** formulas achieve this goal?

- A.

```
IF [Subject] = 'Computer Science' OR [Subject] = 'Science' THEN 'Scienc
ELSEIF [Subject] = 'English' OR [Subject] = 'Social Studies' THEN 'Huma
END
```

- B.

```
CASE [Subject]
WHEN 'Computer Science' OR 'Science' THEN 'Sciences'
WHEN 'English' OR 'Social Studies' THEN 'Humanities'
END
```

- C.

```
CASE [Subject]
WHEN 'Computer Science' THEN 'Sciences'
WHEN 'Science' THEN 'Sciences'
WHEN 'English' THEN 'Humanities'
WHEN 'Social Studies' THEN 'Humanities'
END
```

- D.

```
IF [Subject] = 'Computer Science' AND [Subject] = 'Science' THEN 'Scien
ELSE 'Humanities'
END
```

Q36. [Multiple Select – Choose TWO] You have monthly sales data. You need a calculated field that returns a value of **TRUE** if a month has sales greater than $50,000; otherwise it must return **FALSE**. Which **two** formulas achieve this goal?

- A. `IF SUM([Sales]) > 50000 THEN 'TRUE' ELSE 'FALSE' END`
- B. `SUM([Sales]) > 50000`
- C. `ISNULL(SUM([Sales]) > 50000)`
- D. `IIF(SUM([Sales]) > 50000, TRUE, FALSE)`

Q37. [Multiple Select – Choose TWO] An `Amount` field contains nulls. When you calculate the average, the null values are excluded, but the business requires nulls to be treated as **zero**. Which **two** formulas replace null values with zero?

- A. `ZN([Amount])`
- B. `ISNULL([Amount])`
- C. `IFNULL([Amount], 0)`
- D. `NULLIF([Amount], 0)`

Q38. [Single Choice] You have a line chart of monthly sales for the Consumer segment. You want to smooth the line by showing each point as the average of the **previous 30 data points** including the current one. What should you do?

- A. Right-click anywhere in the graph and select **Forecast** > **Moving Average**
- B. Right-click the `SUM(Sales)` pill, choose **Quick Table Calculation** > **Moving Average**, then choose **Edit Table Calculation** and set **Previous values** to 30
- C. Change the Sales aggregation from Sum to Average
- D. Add a trend line to the chart

Q39. [Single Choice] You have a bar chart showing `SUM(Sales)` for every `Sub-Category`, stacked under each `Category`. You want the bars to show the **percent of sales for each Sub-Category within its Category**, so each Category totals 100%. How should you configure the table calculation?

- A. Apply Percent of Total and set **Compute Using** to `Category`
- B. Apply Percent of Total and set **Compute Using** to `Table (down)` only
- C. Apply Percent of Total and set **Compute Using** to Pane
- D. Apply Percent of Total, then **Edit Table Calculation** > **Compute Using** > **Specific Dimensions** and select `Sub-Category` only, so the calculation restarts for each Category

---

Q40. [Single Choice] You have daily transaction data and need a line chart showing the **cumulative** sales over each individual day. How should you build it?

- A. Drag `Order Date` to Columns, right-click the pill and choose **Exact Date**; drag `Sales` to Rows; right-click `SUM(Sales)` and choose **Quick Table Calculation** > **Running Total**
- B. Drag `YEAR(Order Date)` to Columns and `Sales` to Rows, then apply Running Total
- C. Drag `Order Date` to Columns as a discrete exact date and use a bar chart
- D. Drag `Sales` to Rows and `Order Date` to Detail, then use Show Me

Q41. [Single Choice] You have quarterly sales in a crosstab and want to compute the **percent difference from the previous quarter** using a custom table calculation. Which formula matches how Tableau computes "Percent Difference From"?

- A. `ZN(SUM([Sales])) - LOOKUP(ZN(SUM([Sales])), -1)`
- B. `(ZN(SUM([Sales])) - LOOKUP(ZN(SUM([Sales])), -1)) / ABS(SUM([Sales]))`
- C. `(ZN(SUM([Sales])) - LOOKUP(ZN(SUM([Sales])), -1)) / ABS(LOOKUP(ZN(SUM([Sales])), -1))`
- D. `ZN(SUM([Sales])) / LOOKUP(ZN(SUM([Sales])), 0)`

Q42. [Single Choice] You need a calculated field for the **compound growth rate (CAGR)** of

sales. You have already created a parameter named `N Years`. Which formula should you use?

- A. `POWER(ZN(SUM([Sales]))/LOOKUP(ZN(SUM([Sales])), -[N Years]), ZN(1/[N Years]))`
- B. `POWER(ZN(SUM([Sales]))/LOOKUP(ZN(SUM([Sales])), -[N Years]), ZN(1/[N Years])) - 1`
- C. `(ZN(SUM([Sales]))/LOOKUP(ZN(SUM([Sales])), -[N Years])) * ZN(1/[N Years]) - 1`
- D. `POWER(LOOKUP(ZN(SUM([Sales])), -[N Years])/ZN(SUM([Sales])), ZN(1/[N Years])) - 1`

Q43. [Single Choice] You created a calculated field `Index` with the formula `INDEX()` and used it in a chart. Your audience is confused about the difference between `INDEX()` and `RANK()`. Which explanation is correct?

- A. `INDEX()` ranks a record based on the value it holds
- B. `RANK()` returns the physical position of the row in the partition
- C. They are identical functions with different names
- D. `INDEX()` returns the physical position of the row in the partition, while `RANK()` returns a value based on the value of an expression

---

Q44. [Single Choice] You want to rank products by sales such that ties share the same rank and **no rank values are skipped** (for example: 1, 1, 2, 3), so ranks remain consecutive. Which function should you use?

- A. `RANK()`
- B. `RANK_DENSE()`
- C. `RANK_UNIQUE()`
- D. `RANK_MODIFIED()`

Q45. [Single Choice] You have a crosstab with years as columns (2019–2024) and a **year-over-year percent change** table calculation that requires both years to be present in the query. Management wants to display **only the latest year (2024)** while keeping the YoY calculation intact. What should you do?

- A. Add a `YEAR([Order Date]) = 2024` dimension filter
- B. Add a `FIRST() = 0` filter computed across the date field and keep True
- C. Create a calculated field `LAST() = 0`, add it to the **Filters** shelf, set it to compute using the date field across the table, and keep **True**
- D. Add an `INDEX() = 0` filter to the view

Q46. [Single Choice] You build a view of Sub-Category sales, apply a **Top 5 by SUM(Quantity)** filter on Sub-Category, and also filter Category to **Office Supplies**. The view shows only 3 bars instead of the top 5 office supplies. What should you do?

- A. Right-click the Category filter and select **Add to Context**
- B. Right-click the Top 5 filter and select **Add to Context**
- C. Remove the Category filter and filter with a set instead
- D. Change the Top filter to rank by SUM(Sales)

Q47. [Single Choice] You have a view listing movies. You must filter it to show only records whose movie name **starts with the word "The"**, and you are not allowed to write any formulas. Which type of filter should you use?

- A. Top
- B. General
- C. Condition
- D. Wildcard

Q48. [Single Choice] You have a data source with every city in the United States, including a `Population` measure. Using the `City` dimension, you need a **dynamic filter** that shows only the cities whose population is greater than 1,000,000. Which type of filter should you use?

- A. A General filter with selected cities
- B. A **Conditional** filter (By field: Sum of Population > 1,000,000)
- C. A Wildcard filter
- D. A Top N filter

Q49. [Single Choice] A dashboard contains a Region filter on the "Overview" sheet. The dashboard has 10 other sheets that all use the **same primary data source**, and they must all respond to the Region filter. What is the most efficient way to achieve this?

- A. Rebuild the filter on every sheet
- B. Add the Region filter to context on each sheet
- C. On the Region filter card's drop-down menu, select **Apply to Worksheets > All Using Related Data Source**
- D. Create a copy of the filter card on each sheet

Q50. [Build List – Order the steps] Tableau applies filters in a strict order of operations. Order the following filter types from **first applied** to **last applied** (each is used once):

- A. Data source filters
- B. Context filters
- C. Dimension filters
- D. Extract filters
- E. Measure filters
- F. Table calculation filters

Q51. [Single Choice] You create a parameter named **Choose Region** whose values come from the `Region` field. You want users to toggle between different regions in a chart using this parameter. What should you do next?

- A. Add `Region` to the Filters shelf
- B. Create a calculated field `[Region] = [Choose Region]` and add it to the **Filters** shelf (keeping True)
- C. Add the Choose Region parameter to the Pages shelf
- D. Set the parameter display type to Single Value (list) — nothing else is needed

---

Q52. [Single Choice] Stakeholders want to control **how many top customers** appear in a "Top Customers" view, choosing any number interactively (e.g., 5, 10, 25). How should you configure this?

- A. Create a fixed set with the top 10 customers and let users remove members
- B. Create a Top N filter for each possible value and swap them with a parameter action
- C. Group customers and let users select the group size
- D. Create a parameter `N`, then in the Customer filter's **Top** tab click the number drop-down and select the **parameter** as the value of N (Top N by SUM(Sales))

Q53. [Single Choice] A KPI chart shows monthly revenue. Management wants a horizontal **target line** whose value users can change interactively without editing the workbook. What should you do?

- A. Add a constant line and ask users to edit its value
- B. Add a distribution band around the average
- C. Create a parameter for the target value, then add a **reference line** whose Value is set to the **parameter**
- D. Add an average line from the Analytics pane

Q54. [Build List – Order the steps] You have a worksheet that must display **either Profit or Sales**, based on the user's selection from a `Metric` parameter menu. Order the steps to build this (each step is used once):

- A. Drag the calculated field onto the view, replacing the existing measure
- B. Create a parameter named `Metric` with values `Sales` and `Profit`
- C. Create a calculated field: `IF [Metric] = 'Sales' THEN SUM([Sales]) ELSE SUM([Profit]) END`
- D. Right-click the parameter and select **Show Parameter Control**

Q55. [Single Choice] You need a set of the **top 10 customers by sales** that automatically updates as new data arrives (customers entering or leaving the top 10 as sales change). How should you create the set?

- A. Select the top 10 customers in the view, right-click the selection, and choose **Create Set**
- B. Create a group of the top 10 customers
- C. Right-click the `Customer Name` dimension, choose **Create** > **Set**, open the **Top** tab, and define Top 10 by SUM(Sales)
- D. Create a parameter with the 10 customer names

Q56. [Build List – Order the steps] You must build a view showing the **top 10 AND bottom 10 customers by sales together** (20 rows total). Order the steps to accomplish this (each step is used once):

- A. Right-click one of the two sets, choose **Create Combined Set**, and select **All members in both sets**
- B. Right-click `Customer Name`, choose **Create** > **Set**, and define **Top 10 by Sum(Sales)**
- C. Duplicate the Top 10 set, rename it **Bottom 10**, and edit it to use **Bottom 10 by**

Sum(Sales)
- D. Drag the combined set to the **Filters** shelf

Q57. [Single Choice] You need a histogram of the `Quantity` field using a **bin size of 3**. What should you do?

- A. Drag `Quantity` to Columns, change the mark type to Bar, and set bar size to 3
- B. Right-click `Quantity`, choose **Create** > **Bins**, enter **3** as the size of bins, then drag `Quantity (bin)` to Columns and `CNT(Quantity)` to Rows
- C. Create a group of quantity values in ranges of 3
- D. Create a set of quantity values

Q58. [Single Choice] A view shows total sales by Category. Analysts must be able to **drill down from Category to Sub-Category** directly in the visualization. What should you create?

- A. A hierarchy containing Category and Sub-Category
- B. A group of sub-categories inside each category
- C. A set of sub-categories
- D. A parameter with category and sub-category values

Q59. [Single Choice] Using the Superstore data source, you need a **filled map** that shows the distribution of total Sales by State across the United States (states shaded by sales). How should you build it?

- A. Drag `State` to Detail and `Sales` to Size
- B. Drag `State` to Label and `Sales` to Angle
- C. Change the mark type to Density and add Sales to Color
- D. Double-click `State` (to generate the map), drag `Sales` to **Color**, and set the mark type to **Map**

Q60. [Single Choice] You have a map of taxi pickups in Manhattan containing millions of **overlapping points** that obscure each other. You need to see the concentration patterns of pickups. What should you do?

- A. Change the mark type to **Density** and adjust Intensity and Opacity from the Color legend
- B. Change the mark type to Map (filled)
- C. Make the circle marks smaller and more transparent
- D. Replace the map with a heat-map crosstab of pickup times

---

Q61. [Single Choice] You have a Sales vs. Profit scatter plot and need to add a **distribution band on Profit showing the range from -1 to $+1$ standard deviations**. What should you do?

- A. Add a reference band from MIN(Profit) to MAX(Profit)
- B. From the **Analytics** pane, drag **Distribution Band** onto the Profit axis, select **Standard Deviation** as the factor, and set Band From $= -1$ and Band To $= 1$
- C. Add a box plot to the view
- D. Add a trend line with confidence bands

Q62. [Single Choice] You have a chart showing Profit by Sub-Category across multiple Regions, with trend lines. You want the trend line within each **Sub-Category** to be the **same across all regions**. What should you do?

- A. Remove Region from the view
- B. Change the trend line model to Exponential
- C. Right-click any trend line, select **Edit All Trend Lines**, and under **Factors** clear the check box for **Region**
- D. Create a separate worksheet per region

Q63. [Single Choice] You have monthly historical sales by segment from 2017 to the present. You want to use the historical trend to **predict sales by segment three years into the future**. What should you do?

- A. Add a trend line to the line chart
- B. Drag **Forecast** from the Analytics pane onto the view, then right-click the forecast and use **Forecast Options** to set the forecast length to 3 years
- C. Add a cluster to the view and extrapolate manually
- D. Change the date field to continuous and extend the axis

Q64. [Single Choice] You have a line chart of actual sales, and you want to add a second line that **predicts the median** sales value based on other fields in the data. Which function and configuration should you use?

- A. Use the `MODEL_PERCENTILE` function in a calculated field and a dual-axis configuration
- B. Use the `PREDICT_MEDIAN` function in a calculated field and a dual-axis configuration
- C. Use the Forecast option with the median aggregation setting
- D. Use the `MODEL_QUANTILE` function (with quantile 0.5) in a calculated field and a dual-axis configuration

---

Q65. [Single Choice] You have a crosstab of Sales by Region (rows) and Year (columns). You must add **row grand totals and column grand totals** to the table. Where do you configure this?

- A. On the Marks card, using the Totals drop-down
- B. On the **Format** menu, using the Totals section
- C. On the **Analysis** menu: **Totals** > **Show Row Grand Totals** and **Totals** > **Show Column Grand Totals**
- D. Drag a Total field from the Data pane onto the view

Domain 3: Create Content (26%)

Q66. [Single Choice] You have the following dataset:

Item	Revenue

Candy	18,782
Sodas	36,241
Popcorn	23,987
Nachos	9,483

You want to create a pie chart of revenue by item. How should you configure the marks for the pie chart?

- A. Drag `Revenue` to Color, `Item` to Label, and `Item` to Angle
- B. Drag `Item` to Color, `Item` to Label, and `Revenue` to Angle
- C. Drag `Item` to Size, `Item` to Label, and `Revenue` to Detail
- D. Drag `Revenue` to Color, `Revenue` to Label, and `Item` to Detail

Q67. [Single Choice] You have a highlight table showing Profit by Sub-Category and Region. You want to turn it into a **heat map** where profit magnitude drives color intensity, negative/positive values are visually distinct, and no cells are clipped. How should you configure it?

- A. Keep the mark type as **Square** with Profit on **Color**, click Color > Edit Colors, choose the **Red-Green Diverging** palette, and enable **Use Full Color Range**
- B. Drag `Region` and `Sub-Category` to Color and keep everything else the same
- C. Drag `Profit` to Size and keep Profit on Color
- D. Change the mark type to Density

Q68. [Single Choice] You create a dual-axis chart with `SUM(Sales)` as bars (integer values, axis 0–1,000,000) and `SUM(Profit Ratio)` as a line (decimal values, axis −0.5 to 0.5). The two axes don't share a scale, so the zero baselines don't align. When you right-click the secondary axis, **Synchronize Axis is unavailable (grayed out)**. What is the reason and the fix?

- A. Synchronize Axis only works for two measures with identical names — rename the fields
- B. Dual axes can never be aligned — manually edit the axis ranges instead
- C. The measures have different aggregation functions — change both to SUM and the option appears
- D. The two measures have **different data types** (integer vs. decimal); make the data types compatible (e.g., convert to float), then right-click the secondary axis and select **Synchronize Axis**

Q69. [Single Choice] You need a chart that shows monthly `Sales` as **bars** and monthly `Profit` as a **line** in the same pane, each with its own independent axis. How should you build it?

- A. Place `Measure Names` on Rows and `Measure Values` on Columns
- B. Place both measures on the Rows shelf, right-click the second axis, and choose **Dual Axis**; then set the mark type on each Marks card (Bar for Sales, Line for Profit)
- C. Use Show Me to create a combo chart — it automatically separates mark types
- D. Blend a second data source that contains Profit

Q70. [Single Choice] You have project data with `Task Name`, `Start Date`, and `Duration`

(number of days). You must create a **Gantt chart** showing when each task starts and how long it lasts. How should you build it?

- A. Place `Duration` on Columns and `Start Date` on Size
- B. Place `End Date` on Columns and `Task Name` on Rows
- C. Place `Task Name` on Rows, the **continuous** `Start Date` on Columns, change the mark type to **Gantt Bar**, and place `Duration` on **Size**
- D. Build a bar chart of Duration sorted by Start Date

Q71. [Single Choice] A stakeholder asks for a chart that visualizes the **distribution and variability** of a measure's values (median, quartiles, whiskers, and outliers) along an axis, to compare distributions across categories. Which chart type should you use?

- A. Bullet graph
- B. Box plot
- C. Scatter plot
- D. Histogram

Q72. [Single Choice] You want to explore whether there is a **relationship (correlation) between Sales and Profit** at the product level. Which chart should you create?

- A. A bar chart of Sales colored by Profit
- B. A line chart of Sales and Profit over time
- C. A **scatter plot** with Sales on Columns, Profit on Rows, and Product on Detail
- D. A pie chart of Sales by product

Q73. [Single Choice] A bar chart displays `SUM(Sales)` by Sub-Category. Users want the bars **sorted by Profit (descending)**, but Profit is not displayed in the view. What should you do?

- A. Use the toolbar sort buttons on the Sales axis
- B. Add Profit to Color and sort by the color legend
- C. Sort the bars manually by dragging headers
- D. Right-click `Sub-Category`, choose **Sort**, set Sort By to **Field**, choose `Profit` with aggregation `Sum` and order **Descending**

Q74. [Single Choice] You must show the **part-to-whole contribution** of roughly 50 product categories to total sales, in a limited dashboard space where a pie chart would be unreadable. Which chart type should you use?

- A. Pie chart
- B. Treemap
- C. Gantt chart
- D. Line chart

Q75. [Single Choice] On a dashboard, you want to add a band of four KPI text objects arranged **side by side** so they stay together and resize as a group when the dashboard size changes. Which container should you use?

- A. A **horizontal** layout container

- B. A **vertical** layout container
- C. A blank object
- D. No container — floating objects auto-align

Q76. [Single Choice] A dashboard includes a "Total Sales by Region" sheet. You want users to be able to **click a region bar and filter the other sheets** on the dashboard, with minimal configuration. What is the fastest way?

- A. Open **Dashboard** > **Actions** and add a filter action for every target sheet
- B. Add a highlight action to the dashboard
- C. Open the sheet's drop-down menu on the dashboard and select **Use as Filter**
- D. Add a parameter and a calculated field for each region

Q77. [Multiple Select – Choose TWO] Which two statements about **story points** in Tableau are TRUE?

- A. A story point can only contain a dashboard
- B. A story point can contain either a worksheet or a dashboard
- C. The title of a story point cannot be changed after it is created
- D. You can add, duplicate, delete, or reorder story points, and edit their captions

---

Q78. [Single Choice] You must add your company logo to the top of a dashboard and also a semi-transparent "DRAFT" watermark image over the content. Which dashboard object should you use for the images?

- A. A text object
- B. An **image** object
- C. A web page object
- D. A blank object with background shading

Q79. [Single Choice] On a dashboard, you want users to **click a state on the map sheet** and have the "Products" sheet show only that state's products. How should you configure this?

- A. Open **Dashboard** > **Actions**, add a **Filter action**, set the Source to the map sheet and the Target to the Products sheet, and run the action on Select
- B. Add a URL action that links to the Products sheet
- C. Add a highlight action between the two sheets
- D. Add a set action that filters the state dimension

Q80. [Single Choice] Your data contains a `[Website]` field with each company's URL. When a user clicks a company mark in a dashboard view, the company's website should **open in a browser**. Which action should you configure?

- A. A filter action targeting a web page object only
- B. A highlight action on the company field
- C. A navigation action to a URL dashboard
- D. A **URL action**, inserting the `[Website]` field into the URL (e.g., `https://<Website>`)

Q81. [Single Choice] When a user selects a segment in one dashboard sheet, matching marks in the other sheets should be **emphasized**, but no data should be removed from any view. Which action should you use?

- A. A filter action
- B. A URL action
- C. A **highlight action**
- D. A go-to-sheet action

Q82. [Single Choice] A dashboard contains two visualizations. Users must see **only one visualization at a time** and be able to switch between them. What should you use?

- A. Dashboard actions
- B. A parameter and a calculated field (sheet-swap technique)
- C. Show/hide buttons
- D. Worksheet actions

Q83. [Single Choice] You want to add an object to a dashboard that users can **click to switch to a different dashboard** in the same workbook. Which object should you add?

- A. A **navigation** object
- B. A blank object
- C. A download object
- D. An image object

Q84. [Single Choice] You plan to use **Dynamic Zone Visibility** to automatically show/hide a zone on a dashboard based on a calculated field. Which attributes must the controlling field have?

- A. It must be a string field and a fixed level of detail expression
- B. It must be Boolean and able to return multiple values per view
- C. It must be an integer and depend on the vizLOD
- D. It must be **Boolean** and return a **single value** for the view

---

Q85. [Single Choice] You have a floating layout container holding all filter controls, floating above a chart. Users should be able to **toggle the container open/closed** by clicking a button, to save dashboard space. What should you do?

- A. Configure Dynamic Zone Visibility with a calculated field
- B. Add a URL action that hides the container
- C. Add a **Show/Hide button** to the floating container
- D. Add a navigation button to a duplicate dashboard without filters

---

Q86. [Single Choice] You have a line chart and want to attach a callout note (for example, "Growth rate: 12%") directly to the March 2020 data point. What should you do?

- A. Add the value to the tooltip only
- B. Right-click the March 2020 mark and choose **Annotate** > **Mark**, then type the note
- C. Enable the worksheet caption
- D. Add a text object on the dashboard near the point

Q87. [Single Choice] A published pie chart tooltip currently shows category and profit. Users also want to see **Sales in the tooltip** without changing the chart layout. How should you add it?

- A. On the dashboard, edit the tooltip text and type the sales values manually
- B. In the **worksheet**, drag the `Sales` field to **Tooltip** on the Marks card
- C. Add a Tooltip object to the dashboard
- D. It is not possible to modify a tooltip after the sheet is added to a dashboard

---

Q88. [Single Choice] You must **remove gridlines** and the **row/column banding (shading stripes)** from a worksheet before adding it to a clean, minimal dashboard. Where do you configure this?

- A. Analysis menu > Totals
- B. Right-click each axis and clear the gridline options
- C. The Marks card, under Format
- D. The **Format** pane: use **Lines** to set Grid Lines to **None**, and use **Shading** to remove Row Banding / Column Banding

---

Q89. [Single Choice] In a dashboard, you want to apply padding to only the **left side** of a worksheet object, keeping the other sides at zero. What should you do?

- A. It is not possible — padding applies to all sides equally
- B. In the Layout pane, clear the option that locks **all sides equal** for padding, then set the left padding independently
- C. Change the dashboard fit from Standard to Entire View
- D. Set the object to floating and use pixel offsets

Q90. [Single Choice] You removed gridlines, changed fonts, and updated shading on one worksheet. You must apply the **same formatting to three other worksheets** before adding them to a dashboard. What should you do?

- A. Reformat the other worksheets one at a time
- B. Use Format > Workbook to retroactively apply all sheet-level settings
- C. Right-click the formatted worksheet tab and choose **Copy Formatting**; then right-click each target sheet tab and choose **Paste Formatting**
- D. Save the workbook as a template and reopen it

Q91. [Single Choice] Most users will open your dashboard on phones, others on tablets and desktops. You must make sure the dashboard rearranges itself appropriately for each device type. What should you do?

- A. Build three separate workbooks, one per device
- B. Set the dashboard size to Automatic and assume it works on all devices
- C. Hide the less important sheets when viewed on a phone
- D. Use the **Device Designer** (device layouts) to create separate Phone, Tablet, and Desktop layouts of the same dashboard

---

Domain 4: Publish and Manage Content on Tableau Server and Tableau Cloud (9%)

Q92. [Single Choice] You are publishing a workbook that contains 12 sheets, but only one sheet should be visible to consumers. How should you publish it?

- A. Delete the other 11 sheets, publish, then restore them from a backup
- B. Select **Server** > **Publish Workbook**, and in the Publish Workbook dialog box open the **Sheets** area and clear the check boxes for every sheet except the one you want to publish
- C. Use permissions to hide the other sheets
- D. Add search tags to the sheets you want hidden

Q93. [Single Choice] You have a data source on Tableau Server whose underlying data is in an extract. The business needs the data **updated every hour**. What should you select on the data source page on Tableau Server?

- A. **Extract Refreshes** — add a new refresh schedule set to hourly
- B. Connected Workbooks
- C. New
- D. Connections

Q94. [Single Choice] You configure an **incremental refresh** on an extract based on the `Order Date` column. What happens each time the refresh runs?

- A. All rows in the extract are replaced with a fresh copy of the source data
- B. The refresh creates duplicate rows for records that already exist
- C. The refresh **adds only the rows whose date is after the date/time of the last refresh**
- D. New columns added to the source table are automatically included in the extract

---

Q95. [Single Choice] You want to create a **data-driven alert** that emails you when a measure crosses a threshold. Which view element can you create the alert from?

- A. The duration axis of a Gantt chart
- B. A **continuous numeric axis** (for example, SUM(Sales) on a bar chart)
- C. A map view legend
- D. A numeric-bin axis

Q96. [Multiple Select – Choose TWO] You are the owner of a data-driven alert. You receive an email saying the alert was **suspended** after repeated failures. From which **two** places can you resume the suspended alert?

- A. The **My Content** area of the Tableau web pages (select … > Resume Alert)
- B. The Data Source page in Tableau Desktop
- C. The **Resume Alert** link in the notification email
- D. The notification area of Tableau Prep Builder

Q97. [Single Choice] In Tableau Cloud, you create a **subscription for a group** so all group members receive the emailed view snapshot. What happens if new users are **added to the group later**?

- A. Only the users who were members when the subscription was created receive the emails
- B. You must delete and re-create the subscription so the new users are included
- C. New users must each subscribe themselves individually
- D. The new group members **automatically receive the subscription** — you do not need to re-subscribe the group

---

Q98. [Multiple Select – Choose TWO] You are creating an annual report in Microsoft Word. In Tableau Desktop, you built a chart in a worksheet, and you need an **image of the chart** to insert into the report. Which **two** options create the image?

- A. On the **Worksheet** menu, choose **Copy** > **Image**, then paste it into Word
- B. On the File menu, choose **Print to PDF** and extract the image from the PDF
- C. On the Data menu, choose **Export Data** to Microsoft Access
- D. On the **Worksheet** menu, choose **Export** > **Image** and save the image file

---

Q99. [Single Choice] A colleague wants to always open your published dashboard **with her preferred filters and selections already applied**, without changing the dashboard for everyone else. What should she do?

- A. Create a subscription to the view
- B. Create and save a **custom view** with her selections applied
- C. Create a data-driven alert on the view
- D. Download the workbook and edit it locally

Q100. [Multiple Select – Choose TWO] Which **two** site roles can publish workbooks and data sources to Tableau Cloud?

- A. Viewer
- B. Creator
- C. Guest
- D. Explorer (Can Publish)

---

*End of exam — check your answers against **answer.md**. Score yourself: the real passing score is 65%, but target 80%+ before booking the real exam.*