SALESFORCE CERTIFIED TABLEAU DATA ANALYST (DA-201)

Full-Length Practice Exam — glm2-paper — 60 Challenging Questions

---

Exam facts (real exam):

Questions	60 scored multiple-choice / multiple-select questions (the real exam also includes 5 unscored questions)
Time limit	105 minutes — time yourself without breaks
Passing score	65% — you need at least 39 of 60 correct
Cost / format	USD $200 — proctored at a Pearson VUE center or online; no reference materials allowed

Domain weightings and question ranges in this paper:

Domain	Real exam	This paper	Focus
1. Connect to and Transform Data	24%	13 questions (Q1–Q13)	Connections, joins, Prep, field roles
2. Explore and Analyze Data	41%	30 questions (Q14–Q43)	**LODs, calculations, table calcs — deliberately over-weighted**
3. Create Content	26%	12 questions (Q44–Q55)	Charts, sorting, dashboards, actions
4. Publish and Manage Content	9%	5 questions (Q56–Q60)	Publishing, refreshes, alerts, roles

How to use this paper:

1. Work through all 60 questions in one sitting of 105 minutes — this mirrors the real exam's pace of roughly 100 seconds per question.
2. Most questions have exactly ONE correct answer. Questions with more than one correct answer are explicitly marked "(Choose TWO)" or "(Choose THREE)" and are worth one point only if every selected option is correct.
3. This edition is intentionally heavy on Level of Detail (LOD) expressions, calculated fields, and table calculations — the topics candidates most often miss. Trace every calculation by hand on paper: the real exam expects you to predict results without Tableau open.
4. Write your answers on the answer sheet at the end of the paper, then check yourself against glm2-answers.pdf. Score 39+ (65%) to be in passing range, and revisit any domain where you score below 70%.
5. No Tableau Desktop, notes, or web resources — the real exam is closed-book.

Scenario data note: unless a question provides its own table or values, assume the fields behave like the Sample - Superstore dataset (Sales, Profit, Quantity, Order Date, Ship Date, Region, State, Category, Sub-Category, Customer

Name).

SECTION 1 — Domain 1: Connect to and Transform Data (Q1–Q13)

Topics: live vs. extract, relationships vs. joins vs. unions, Tableau Prep (aggregate, pivot, split, output types), Data Interpreter, data quality, discrete vs. continuous, dimension vs. measure, replacing data sources, file types.

Q1. Your team's dashboards connect **live** to a production SQL Server that also runs the company's transactional systems. During business hours, dashboards take minutes to load and the DBA reports heavy query load. The source data is loaded into the warehouse only once each night, at 2:00 AM. Which approach best resolves the performance problem while keeping the dashboards appropriately current?

- **A.** Keep the live connection and add the same context filter to every worksheet
- **B.** Create an extract of the data and schedule a full extract refresh to run after the nightly load
- **C.** Keep the live connection and create extract filters to reduce the queried rows
- **D.** Create an extract and schedule an incremental refresh to run every hour during business hours

Q2. You connect to a Sales table (one row per order line) and a Quotas table (one row per region per quarter). When you join the tables on Region, sales figures are duplicated and inflated for any region with more than one quota row. Which approach should you use instead?

- **A.** An inner join on Region plus a FIXED LOD calculation to remove the duplicates
- **B.** A union of the two tables
- **C.** A relationship between the two tables on Region
- **D.** A data blend of the two sources on Region

Q3. In a Tableau Prep flow you must produce an output with exactly one row per Region and Segment, showing total Sales for each combination. Which step configuration achieves this?

- **A.** Add an Aggregate step; drag Region and Segment to Grouped Fields and Sales to Aggregated Fields
- **B.** Add an Aggregate step; drag Sales to Grouped Fields and Region and Segment to Aggregated Fields
- **C.** Add a Clean step and group Region and Segment values together
- **D.** Add a Pivot step and use Region and Segment as the pivot values

Q4. A monthly Excel report has a report title in the first two rows, a merged-cell subtitle, a blank spacer column, and three footnote rows beneath the data. When you connect, fields come in named F1, F2, F3 and many values land in the wrong columns. Which feature fixes this without editing the Excel file?

- **A.** Custom SQL
- **B.** Data Interpreter
- **C.** Pivot
- **D.** Split

Q5. A [Product Code] field contains values such as `TV-LG-55-4K`. You need a new field containing only the first segment (for example `TV`). Which option does this?

- **A.** Custom Split, using "-" as the delimiter and keeping only the first token
- **B.** Automatic Split, which asks you which single token to keep
- **C.** Pivot the field from columns to rows
- **D.** Group the values and create an alias for each member

Q6. You receive 12 CSV files (Jan_2024.csv through Dec_2024.csv) with identical column structure. In Tableau Prep you want them combined into a single table whose rows are stacked, with a new field identifying which file each row came from. What should you do?

- **A.** Join the 12 files on the Date column
- **B.** Union the files using a wildcard search, and include the source table name as a new field
- **C.** Pivot the 12 files on the file name
- **D.** Create relationships between the 12 files

Q7. In a Tableau Prep flow you combine a Customers table with an Orders table. The requirement: EVERY customer must appear in the output, even customers who have never placed an order. Which join type should you use, with Customers as the left table?

- **A.** Inner join
- **B.** Right join
- **C.** Left join
- **D.** Full outer join

Q8. While profiling a data source you find that 15% of rows have a blank [Customer Email], and the same country appears as "USA", "U.S.A.", and "United States" in [Country]. Which TWO data-quality dimensions do these issues represent? **[Multiple Select — Choose TWO]**

- **A.** Completeness — blank [Customer Email] values
- **B.** Accuracy — blank [Customer Email] values
- **C.** Consistency — inconsistent [Country] spellings
- **D.** Validity — inconsistent [Country] spellings

Q9. Your Tableau Prep flow cleans sales data consumed by several published dashboards on Tableau Cloud. The flow runs on a schedule, and all dashboards must always use the latest output without anyone re-publishing anything manually. Which output type should the flow write to?

- **A.** A .csv file written to a shared network drive
- **B.** A local .hyper file on the flow author's laptop
- **C.** A published data source on Tableau Cloud
- **D.** A packaged .tdsx file

Q10. You are building a line chart of Sales over time. The business wants ONE unbroken horizontal time axis, so that dates with no sales appear as visible gaps in the trend instead of as separate labeled headers. What should you do with [Order Date]?

- **A.** Keep it as a discrete date part — dates create headers by default
- **B.** Convert it to a continuous (green) exact date
- **C.** Convert it to a string and sort the axis alphabetically
- **D.** Put `DATEPART('day', [Order Date])` on Columns

Q11. [Customer ID] is stored as a number and Tableau places it under Measures. When you drag it into a view, Tableau sums the IDs into meaningless totals. What should you do?

- **A.** Convert [Customer ID] to a discrete field only
- **B.** Convert [Customer ID] to a dimension
- **C.** Create an alias for each ID
- **D.** Format the field as a percentage

Q12. You must re-point an existing workbook from an old data source to a new one that has the same field names. The steps are listed randomly: **1.** Open the workbook connected to the original data source. **2.** On the Data Source page, drag the new table to the canvas to set up the connection. **3.** Select Data > New Data Source and connect to the new data source. **4.** Select Data > Replace Data Source. **5.** In the Replace Data Source dialog, select the current data source and the replacement, then click OK. What is the correct order of steps?

- **A.** 1, 3, 2, 4, 5
- **B.** 1, 4, 5, 3, 2
- **C.** 1, 3, 4, 2, 5
- **D.** 1, 2, 3, 4, 5

Q13. You have cleaned a data source, created calculated fields, renamed columns, and set default number formats and sort order. You want to save all of this metadata for reuse in future workbooks, but you do NOT need to package the underlying data. Which file type should you save?

- **A.** .twb
- **B.** .tds
- **C.** .twbx
- **D.** .hyper n

SECTION 2 — Domain 2: Explore and Analyze Data (Q14–Q43)

Topics: LOD expressions (FIXED, INCLUDE, EXCLUDE, nested), table calculations (RANK, INDEX, LOOKUP, RUNNING_SUM, WINDOW functions, Compute Using), calculated fields (date, string, logical, type conversion, aggregates), parameters, sets and context filters, and the Analytics pane (reference bands, forecasting).

Q14. A view displays SUM(Sales) by [State]. Next to each state's sales, management wants to see the total sales of the region that state belongs to — the same region total repeated on every state row in that region. Which calculation does this?

- **A.** `{FIXED [State] : SUM([Sales])}`
- **B.** `{FIXED [Region] : SUM([Sales])}`
- **C.** `{INCLUDE [Region] : SUM([Sales])}`
- **D.** `{EXCLUDE [Region] : SUM([Sales])}`

Q15. A worksheet displays the calculation `{FIXED [Region] : SUM([Sales])}`. A filter on [Region] sits on the Filters shelf as a normal dimension filter, and you notice the FIXED values do NOT respond to it. Which TWO changes WOULD change the FIXED calculation's results? **[Multiple Select — Choose TWO]**

- **A.** Adding the Region filter to context
- **B.** Defining a data source filter on Region
- **C.** Adding a filter on [Category] to the Filters shelf
- **D.** Adding a measure filter on SUM(Sales)

Q16. A view shows [Region] on Columns. Management wants each region's AVERAGE SALES PER CUSTOMER: first total each customer's sales, then average those customer totals within the region. Which field, placed on Rows with AVG aggregation, does this?

A. `{INCLUDE [Customer Name] : SUM([Sales])}`
B. `{FIXED [Customer Name] : SUM([Sales])}` shown with SUM aggregation
C. `AVG([Sales])` on its own
D. `{EXCLUDE [Region] : SUM([Sales])}`

Q17. A view has [Region] and MONTH([Order Date]) on Rows and SUM(Sales) on Text. A dimension filter keeps only the East and West regions. You want each region-month cell to show that region's share of the month total across the FILTERED regions only. Which calculation is correct?

A. `SUM([Sales]) / {FIXED MONTH([Order Date]) : SUM([Sales])}`
B. `SUM([Sales]) / {EXCLUDE [Region] : SUM([Sales])}`
C. `SUM([Sales]) / TOTAL(SUM([Sales]))` using the default Table (Down) setting
D. `SUM([Sales]) / SUM({FIXED [Region] : SUM([Sales])})`

Q18. Using [Order Date (Months)] (a Month/Year custom date field), you want to show each month's difference from the AVERAGE monthly sales total across the entire period, using a calculation built with LOD expressions. Which calculation is correct?

A. `SUM([Sales]) - AVG(SUM([Sales]))`
B. `SUM([Sales]) - {EXCLUDE [Order Date (Months)] : AVG({FIXED [Order Date (Months)] : SUM([Sales])})}`
C. `{FIXED [Order Date (Months)] : SUM([Sales]) - AVG(SUM([Sales]))}`
D. `SUM([Sales]) - {INCLUDE [Order Date (Months)] : AVG(SUM([Sales]))}`

Q19. For a churn analysis you need each customer's most recent order date, displayed on a view at the customer level. Which calculation returns it?

A. `MAX([Order Date])`
B. `{FIXED [Customer Name] : MAX([Order Date])}`
C. `{MAX([Order Date])}`
D. `{INCLUDE [Order Date] : MAX([Customer Name])}`

Q20. You build a view with [Category] and [Product] on Rows and the calculation `{FIXED [Category] : SUM([Sales])}` on Text. Using the data below, what value appears in the Chair row?

Category	Product	Sales
Furniture	Chair	30
Furniture	Table	70
Office	Lamp	50
Office	Desk	50

A. 30
B. 70
C. 100
D. 200

Q21. Which TWO statements about LOD expressions are TRUE? **[Multiple Select — Choose TWO]**

A. `{FIXED [Region] : SUM([Sales])}` computes one value per region, regardless of any other dimensions in the view

B. `{INCLUDE [State] : SUM([Sales])}` returns the same values whether or not [State] is in the view

C. `{EXCLUDE [Region] : SUM([Sales])}` behaves the same as SUM([Sales]) when [Region] is not in the view

D. Table calculations may be nested inside the aggregate expression of an LOD expression n

Q22. Four products have SUM(Sales) of 200, 150, 150, and 100. You apply a descending RANK table calculation, and a colleague suggests RANK_DENSE instead. What rank does the product with 100 receive under each function?

A. RANK = 3, RANK_DENSE = 3

B. RANK = 4, RANK_DENSE = 4

C. RANK = 3, RANK_DENSE = 4

D. RANK = 4, RANK_DENSE = 3

Q23. A text table shows [Category] members A, B, and C with SUM(Sales) of 100, 250, and 175 respectively. The table is sorted descending by SUM(Sales), and `INDEX()` is computed Table (Down). What INDEX value does category A receive?

A. 1 — INDEX follows alphabetical order

B. 2

C. 3

D. Null — INDEX cannot be used on a sorted view n

Q24. A line view has three monthly marks: January = 100, March = 160, April = 120. February has no row in the view and Show Missing Values is OFF. The calculation `SUM([Sales]) - LOOKUP(SUM([Sales]), -1)` is computed Table (Across). What does March display?

A. 60

B. -60

C. Null — the previous calendar month is missing

D. 160

Q25. Monthly sales are January = 10, February = 20, March = 30, and `RUNNING_SUM(SUM([Sales]))` is displayed. You add a filter `LAST() = 0` (computed Table (Across)) so only March is visible. What does March's running sum display?

A. 30

B. 50

C. 60

D. Null

Q26. A view shows SUM(Sales) by month: January = 10, February = 20, March = 30, April = 40, May = 50. You add `WINDOW_SUM(SUM([Sales]), -2, 0)` computed Table (Across). What does April display?

A. 60

B. 90

C. 120

D. 150

Q27. A crosstab has [Region] on Rows and MONTH([Order Date]) on Columns, with SUM(Sales) on Text and a Percent of Total quick table calculation. You want every region's ROW to sum to exactly 100% — each cell showing its share of that region's total. Which Compute Using setting achieves this?

A. Table (Down)
B. Table (Across)
C. Pane (Down)
D. Cell

Q28. An executive wants a monthly sales line smoothed by a 3-month moving average: each point should average the current month and the TWO previous months. Which steps create this?

A. Right-click the SUM(Sales) pill > Quick Table Calculation > Moving Average, then Edit Table Calculation and set Previous Values = 2 (keeping the current value)
B. Drag Average Line from the Analytics pane onto the view
C. Right-click the MONTH(Order Date) pill > Quick Table Calculation > Moving Average
D. Add a 3-period trend line from the Analytics pane

Q29. Users must see the average elapsed time between [Order Date] and [Ship Date], and must be able to switch the unit among day, week, month, and quarter. A string parameter [Date Unit] holds the selected unit. Which calculation works?

A. `DATEDIFF('day', [Order Date], [Ship Date])`
B. `DATEDIFF([Date Unit], [Order Date], [Ship Date])`
C. `DATEDIFF('parameter', [Order Date], [Ship Date])`
D. `DATEADD([Date Unit], [Order Date], [Ship Date])`

Q30. Which calculation returns year-to-date sales — only sales from January 1 of the current year through today?

A. `IF [Order Date] <= TODAY() OR DATETRUNC('year', [Order Date]) = DATETRUNC('year', TODAY()) THEN [Sales] END`
B. `IF [Order Date] > TODAY() AND DATETRUNC('year', [Order Date]) = DATETRUNC('year', TODAY()) THEN [Sales] END`
C. `IF [Order Date] <= TODAY() AND DATETRUNC('year', [Order Date]) = DATETRUNC('year', TODAY()) THEN [Sales] END`
D. `IF [Order Date] <= TODAY() AND DATETRUNC('month', [Order Date]) = DATETRUNC('year', TODAY()) THEN [Sales] END`

Q31. A payroll cut-off is the first Tuesday of every month. You need a calculated field that returns the first Tuesday of the month for any [Order Date]. Which pair of functions do you need?

A. DATETRUNC and DATEADD
B. DATEDIFF and DATEPART
C. DATENAME and DATEPARSE
D. TODAY and NOW

Q32. [Full Name] contains values like `Doe, Jane`. Which calculation returns the LAST name only ("Doe")?

A. `LEFT([Full Name], FIND([Full Name], ',') - 1)`
B. `RIGHT([Full Name], FIND([Full Name], ',') - 1)`
C. `MID([Full Name], 1, FIND([Full Name], ','))`
D. `SPLIT([Full Name], ',', 2)` n

Q33. `AVG([Amount])` ignores rows where [Amount] is NULL, but management wants those rows counted as ZERO. Which TWO calculations produce the desired average? **[Multiple Select — Choose TWO]**

A. `AVG(ZN([Amount]))`
B. `ZN(AVG([Amount]))`
C. `AVG(IFNULL([Amount], 0))`
D. `IFNULL(AVG([Amount]), 0)` n

Q34. Which of these calculations will throw a "cannot mix aggregate and non-aggregate" error?

A. `SUM([Sales]) - SUM([Cost])`
B. `IF SUM([Sales]) > [Sales Target] THEN 'Over' ELSE 'Under' END`
C. `SUM([Sales]) / SUM([Quantity])`
D. `[Sales] * [Discount]`

Q35. Each product must be labeled 'High' if its profit ratio is at least 0.30, 'Medium' if at least 0.10, and 'Low' otherwise. Which calculation correctly implements this?

A. `CASE [Profit Ratio] WHEN >= 0.30 THEN 'High' WHEN >= 0.10 THEN 'Medium' ELSE 'Low' END`
B. `IF [Profit Ratio] >= 0.30 THEN 'High' ELSEIF [Profit Ratio] >= 0.10 THEN 'Medium' ELSE 'Low' END`
C. `CASE [Profit Ratio] WHEN 0.30 THEN 'High' WHEN 0.10 THEN 'Medium' ELSE 'Low' END`
D. `IIF([Profit Ratio] >= 0.30, 'High', 'Medium')`

Q36. [Order ID] contains values like `ORD-2023-0045`. You need the numeric order sequence (45) as an integer. Which calculation returns it?

A. `INT([Order ID])`
B. `INT(SPLIT([Order ID], '-', 3))`
C. `SPLIT(INT([Order ID]), '-', 3)`
D. `INT(LEFT([Order ID], 3))`

Q37. Which function returns the month NAME — for example "January" — from [Order Date]?

A. `DATEPART('month', [Order Date])`
B. `DATENAME('month', [Order Date])`
C. `DATETRUNC('month', [Order Date])`
D. `STR(DATEPART('month', [Order Date]))`

Q38. [Email] is a string field containing NULLs. You want NULL emails to display as "Unknown". Which calculation does this?

A. `ZN([Email], 'Unknown')`
B. `IFNULL([Email], 'Unknown')`
C. `ISNULL([Email], 'Unknown')`
D. `NULLIF([Email], 'Unknown')`

Q39. Users want one bar chart where a parameter [Measure Selector] switches the displayed measure among Sales, Profit, and Quantity. Which calculated field correctly supports this?

A. `CASE [Measure Selector] WHEN 'Sales' THEN SUM([Sales]) WHEN 'Profit' THEN SUM([Profit]) WHEN 'Quantity' THEN SUM([Quantity]) END`

B. Drag [Measure Selector] directly onto Rows — a parameter is itself a measure

C. `CASE [Sales] WHEN [Measure Selector] = 'Sales' THEN SUM([Sales]) END`

D. `IF [Measure Selector] = TRUE THEN [Sales] END`

Q40. On a dashboard, clicking a region bar should capture that region into a parameter that then drives a dynamic reference line on another sheet. Which dashboard feature does this?

A. A filter action

B. A parameter action

C. A set action

D. A highlight action

Q41. You created a dynamic set of the Top 10 customers by SUM(Sales) and use it as a filter on a view that also has a [Region] quick filter. Users complain that the Top 10 list ignores their region selection — it is being ranked across ALL regions. How do you fix it?

A. Add the [Region] filter to context

B. Convert the set to a fixed set

C. Convert the set to a group

D. Apply the set to more worksheets

Q42. A monthly sales line chart needs a shaded region spanning from the lowest to the highest monthly sales value within each year. Which Analytics pane object should you add?

A. Reference Line

B. Reference Band

C. Distribution Band

D. Box Plot n

Q43. A three-month promotion recently distorted your revenue line chart. You add a forecast, but you want the forecast model to disregard the last 3 months of data while still SHOWING those months in the chart. What should you do?

A. Add a dimension filter excluding the last 3 months

B. In Forecast Options, set "Ignore last" to 3

C. Set the forecast length to 3 months

D. Delete the last 3 months from the extract

SECTION 3 — Domain 3: Create Content (Q44–Q55)

Topics: chart selection (Gantt, histogram, box plot, scatter, dual axis), nested sorting, dashboard interactivity (actions, Use as Filter, dynamic zone visibility, navigation and show/hide buttons), device layouts.

Q44. The PMO wants each project phase drawn as a horizontal bar that starts on its start date and stretches for its length in days. Which chart type and configuration is correct?

A. Gantt chart: continuous [Start Date] on Columns and `DATEDIFF('day', [Start Date], [End Date])` on Size
B. Bar chart: [Phase] on Rows and SUM([Days]) on Columns
C. Line chart: [Start Date] on Columns and [End Date] on Rows
D. Gantt chart: discrete [Start Date] on Columns and [Phase] on Color

Q45. You must visualize the distribution of customer order values in equal-width groups. Which statement about building a histogram in Tableau is TRUE?

A. A histogram requires a continuous measure converted into bins; each bar represents one bin
B. A histogram requires two measures — one per axis
C. A histogram plots every individual order as a point on the chart
D. A histogram requires a dimension on Columns and AVG of the measure on Rows

Q46. A box plot shows the distribution of profit per state, one box per region. Which region shows the LEAST variation in profits?

A. The region whose box (the interquartile range between Q1 and Q3) is narrowest
B. The region with the lowest median
C. The region with the most outliers
D. The region whose whiskers reach the highest value

Q47. A scatter plot shows Sales on Columns and Profit on Rows, one mark per sub-category. You also want a third measure, Quantity, visually encoded in the marks. Which TWO Marks-card properties can do this? **[Multiple Select — Choose TWO]**

A. Color
B. Size
C. Shape
D. Detail

Q48. You create a combo chart with monthly SUM(Sales) as bars and SUM(Profit) as a line on a dual axis. Both measures are in dollars. To ensure both marks align correctly on one shared scale, what should you do after making the chart dual axis?

A. Right-click the secondary axis and select Synchronize Axis
B. Convert SUM(Profit) to a discrete dimension
C. Add Measure Names to the Filters shelf
D. Hide the right-hand axis

Q49. A bar chart of profit by Sub-Category must be sorted descending by SUM(Profit), but where two sub-categories tie, the tie must break alphabetically by name. How do you configure this?

A. In the Sort dialog on the Sub-Category pill, choose Nested: first field SUM(Profit) descending, then Sub-Category ascending
B. Manually drag the bars into the desired order each week
C. Sort alphabetically — Tableau automatically breaks ties by the measure
D. Replace sorting with a RANK table calculation

Q50. On a dashboard, users' clicks on a mark in the Sales sheet should filter the other sheets, and you must not spend time configuring a formal action. Which one-click feature does this?

A. Select the worksheet on the dashboard and enable "Use as Filter"
B. Add all the sheets to a story
C. Enable "Show mark labels" on the source sheet
D. Put the sheets in the same vertical container

Q51. A dashboard has four sheets about customers. When a user hovers over a bar in Sheet 1, you want related marks in the other three sheets emphasized WITHOUT any data being filtered out. Which action type fits?

A. Filter action
B. Highlight action
C. URL action
D. Go to Sheet action

Q52. A detailed table on a dashboard must appear only when a user selects "Show Details" in a parameter, and be hidden otherwise — with no button click required. Which feature does this?

A. Dynamic zone visibility
B. A filter action targeting the table zone
C. A floating text object with a transparent background
D. A swap-sheets parameter

Q53. Users must jump from the Executive Overview dashboard to the Regional Details dashboard in one click. Which dashboard object should you add?

A. A navigation button object
B. A text object containing a URL
C. An image object with no target
D. A blank container

Q54. A floating container holding filter cards takes up dashboard space. You want a small button that toggles the container's visibility whenever users need the filters. Which feature does this?

A. The Show/Hide button on a floating container
B. Dynamic zone visibility driven by a set action
C. A URL action targeting the container
D. This is not possible in Tableau

Q55. Which statement about phone/device layouts is TRUE?

A. A device layout must exactly match the default layout's item positions and sizes
B. A device layout can HIDE items that exist in the default layout, but cannot contain items absent from the default layout
C. Device layouts automatically replace the default layout for desktop users
D. Phone layouts must be built as separate .twbx files

SECTION 4 — Domain 4: Publish and Manage Content on Tableau Server and Tableau Cloud (Q56–Q60)

Topics: publishing workbooks and data sources, Tableau Bridge, scheduled flow runs, data-driven alerts, subscriptions, custom views, and site roles.

Q56. Your team publishes a workbook to Tableau Cloud. Its data comes from an on-premises SQL Server that Tableau Cloud cannot reach directly, and the data must refresh daily. Which approach keeps the data fresh?

- **A.** Publish the workbook with a live connection to SQL Server
- **B.** Publish the workbook/data source as an extract and schedule refreshes through Tableau Bridge
- **C.** Email a refreshed .csv to a Cloud administrator daily for re-upload
- **D.** Publish the extract and add a subscription that refreshes it

Q57. A Tableau Prep flow must run automatically every morning at 6:00 AM, and its published output on Tableau Cloud must refresh accordingly. What should you do?

- **A.** Open Prep Builder every morning at 6:00 AM and click Run
- **B.** Publish the flow to Tableau Cloud and create a schedule for it
- **C.** Create a data-driven alert on the flow
- **D.** Export the flow as .hyper and refresh it in Tableau Desktop

Q58. A regional manager must receive an email the moment daily sales in her dashboard cross 500,000. Which feature does this?

- **A.** A data-driven alert on the relevant mark in the view
- **B.** A subscription to the dashboard
- **C.** An extract refresh notification
- **D.** A performance alert

Q59. Every Monday at 7:00 AM, a stakeholder wants the current state of the executive dashboard delivered to her email as a snapshot, regardless of any data values. Which feature does this?

- **A.** A data-driven alert
- **B.** A subscription
- **C.** A custom view
- **D.** A scheduled export to PowerPoint

Q60. Which THREE are valid Tableau site roles? **[Multiple Select — Choose THREE]**

- **A.** Viewer
- **B.** Explorer
- **C.** Creator
- **D.** Publisher

SELF-MARKING ANSWER SHEET

Record your answers here while taking the exam, then verify against **glm2-answers.pdf**.

Q1 ____	Q2 ____	Q3 ____	Q4 ____	Q5 ____	Q6 ____
Q7 ____	Q8 ____	Q9 ____	Q10 ____	Q11 ____	Q12 ____
Q13 ____	Q14 ____	Q15 ____	Q16 ____	Q17 ____	Q18 ____

Q19 ____	Q20 ____	Q21 ____	Q22 ____	Q23 ____	Q24 ____
Q25 ____	Q26 ____	Q27 ____	Q28 ____	Q29 ____	Q30 ____
Q31 ____	Q32 ____	Q33 ____	Q34 ____	Q35 ____	Q36 ____
Q37 ____	Q38 ____	Q39 ____	Q40 ____	Q41 ____	Q42 ____
Q43 ____	Q44 ____	Q45 ____	Q46 ____	Q47 ____	Q48 ____
Q49 ____	Q50 ____	Q51 ____	Q52 ____	Q53 ____	Q54 ____
Q55 ____	Q56 ____	Q57 ____	Q58 ____	Q59 ____	Q60 ____

Scoring: 39–42 correct = borderline, focus your revision on missed domains; 43–51 = solid pass range; 52+ = distinction territory. Review every explanation in the answer key — especially for questions you guessed correctly.