Practice Exam 3 - Answer Key & Explanations

Attempt the paper first under a 105-minute timer. Multi-select items need ALL correct options - no partial credit, exactly like the real exam.

Quick answer grid

Q1 A	**Q11** A	**Q21** A	**Q31** D	**Q41** A	**Q51** A, C
Q2 B	**Q12** B	**Q22** D	**Q32** C	**Q42** B	**Q52** C
Q3 D	**Q13** A	**Q23** A	**Q33** A	**Q43** B	**Q53** A
Q4 D	**Q14** C	**Q24** D	**Q34** C	**Q44** D	**Q54** A
Q5 C	**Q15** C	**Q25** B	**Q35** B	**Q45** B	**Q55** A
Q6 A, D	**Q16** A, B	**Q26** C	**Q36** B	**Q46** D	**Q56** B
Q7 A	**Q17** A	**Q27** A, C	**Q37** A, B	**Q47** C	**Q57** A
Q8 D	**Q18** D	**Q28** A	**Q38** A	**Q48** B	**Q58** D
Q9 D	**Q19** B	**Q29** B	**Q39** C	**Q49** D	**Q59** B, D
Q10 B	**Q20** D	**Q30** A	**Q40** C	**Q50** C	**Q60** B

How to read your score

Your score	Reading
48 - 60 (80%+)	Exam-ready. Review only the explanations of what you missed, then book the exam.
39 - 47 (65-79%)	Passing zone but not safe - real exam forms vary. Drill every missed Domain-2 topic; retake this paper in 3-4 days.
< 39 (below 65%)	Re-study before re-attempting. Work through the study guide sections for Domain 2 (LODs, calcs, table calcs) and rebuild each wrong answer in Tableau by hand.

Exam-facts reminder: the real test = 60 scored + 5 unscored items, 105 minutes, 65% pass, results immediately. Unanswered questions count as wrong - always guess. You can flag and revisit questions.

Domain 1 - Connect to & Transform Data - Q1-Q14

Q1. A bank's fraud team wants a wall-mounted dashboard that always reflects the current state of suspicious transactions stored in a SQL Server database. Every time the view refreshes, the database itself must be queried. Which connection type should the analyst choose?

A. A live connection to the database **<- correct**
B. A published data source saved as an extract
C. An extract with an incremental refresh every hour
D. An extract with a daily full refresh

Correct answer: A

Topic: Live vs. extract

Why: A live connection sends queries to the source every time the view loads or a user interacts, so values are always current. Extracts are point-in-time snapshots stored in Hyper - no refresh schedule, however frequent, guarantees real-time data.

Why the others fail:

D. A daily refresh leaves data up to 24 hours stale.
C. Even hourly increments are still snapshots, not real time.
B. A published extract has the same staleness problem as a local extract.

Q2. An orders extract holds 40 million rows covering five years, and a full refresh takes three hours - too long for the nightly maintenance window. The source system only appends new rows; historical rows are never updated. What should the analyst configure so refreshes finish quickly?

A. Convert the extract to a live connection with a data source filter
B. An incremental refresh based on Order Date, so only new rows are added **<- correct**
C. Five separate yearly extracts combined with a union in Tableau Desktop
D. An aggregated extract that rolls sales up to the month level

Correct answer: B
Topic: Incremental extract refresh

Why: Incremental refresh adds only rows that are new since the last refresh, keyed on a column such as Order Date or an identity column. It is ideal for append-only data and cuts refresh time dramatically.
Why the others fail:
A. Live changes the performance model entirely and defeats the purpose of the extract.
D. Aggregation loses row-level detail the analysts still need.
C. Each extract would still require a full refresh; unions do not make refreshes incremental.

Q3. An analyst connects to an Excel file that contains a merged company title row, notes under the headers, blank spacer rows, and two sub-tables pasted inside the same sheet. Which Tableau Desktop feature detects the real tables and removes this extraneous information?

A. Custom SQL
B. Wildcard union
C. Data source filter
D. Data Interpreter **<- correct**

Correct answer: D
Topic: Data Interpreter

Why: The Data Interpreter examines Excel (and other) files for formatting artifacts - merged cells, titles, footnotes, empty rows, sub-tables - and surfaces the clean underlying tables. Turn it on from the left pane of the data source page.
Why the others fail:
B. Wildcard union stacks multiple files/sheets; it does not clean formatting.
C. A data source filter removes rows, not layout junk.
A. Custom SQL is for relational sources and cannot repair Excel formatting.

Q4. You have an Orders table (one row per order, including Shipping Cost) and an Order_Items table (many rows per order). The business wants both tables available to every sheet, combined only when needed, and SUM([Shipping Cost]) must not be inflated by the one-to-many match. Which combining method should you choose in Tableau Desktop?

A. Inner join on Order ID
B. Data blending on Order ID
C. Union of the two tables
D. A relationship between the two logical tables **<- correct**

Correct answer: D
Topic: Relationships (logical layer)

Why: Relationships (the default 'noodle') keep each table at its own grain in the logical layer and combine them at query time using only the fields a sheet actually uses. Measure values are not duplicated, so SUM(Shipping Cost) stays correct. A physical join would repeat each order's shipping cost on every item row.
Why the others fail:
A. A join physically merges rows before aggregation, duplicating order-level measures.
B. Blending is a sheet-level technique for separate data sources, not two tables of one source.
C. A union appends rows of similarly structured tables - wrong shape entirely.

Q5. You physically join an Orders table to a Returns table on Order ID. The result must contain every order, including orders that were never returned (with null return columns). Which join type do you need?

A. Right join (Returns on the right)
B. Inner join
C. Left join (Orders on the left) **<- correct**
D. Full outer join

Correct answer: C
Topic: Join types

Why: A left join returns all rows from the left table plus matching rows from the right; unmatched right-side columns become null. An inner join would silently drop never-returned orders, distorting sales analysis.
Why the others fail:
B. Inner keeps only orders that have a matching return.
A. That would keep all returns, not all orders.
D. Full outer also adds returns with no order, which is not requested.

Q6. Twelve monthly CSV exports with identical column structures sit in a folder and must be analysed as one table. Next month's file should be picked up automatically when it is dropped into the same folder. Which TWO statements are correct? [SELECT 2]

A. A union stacks the rows of the files one after another into a single table **<- correct**
B. A union requires a common key field, like a join does
C. Each monthly file becomes its own set of columns in the result
D. A wildcard union in Tableau Desktop automatically includes new files that match the search pattern **<- correct**

Correct answer: A, D
Topic: Union & wildcard union

Why: A union appends rows of same-structure tables. Wildcard union (available on text/Excel files on the data source page) matches a file-name pattern, so new files dropped in the folder are included on refresh. No key field is involved and the schema stays as-is - rows are appended, not pivoted to columns.
Why the others fail:
B. Unions match columns by name/position; there is no join key.
C. Union appends rows; it never adds columns per file.

Q7. Regional sales targets are maintained in a published data source on Tableau Cloud, while transaction-level sales live in a local Excel extract. The two cannot be joined row-by-row (different sources, different grains), and targets must be combined with sales after each side is aggregated to the region level. Which technique should you use?

A. Data blending, with sales as the primary source **<- correct**
B. A union
C. A cross-database join inside the Excel connection
D. A relationship between the two sources

Correct answer: A
Topic: Data blending

Why: Blending is designed for exactly this: separate data sources combined per-sheet, aggregated independently and then linked on a common field (Region). The primary source (blue) drives the view; the secondary (orange) is aggregated and linked. Relationships/joins/unions all require the tables to live in the same data source.
Why the others fail:
D. Relationships exist between logical tables of a single connection, not separate sources.
B. Union stacks same-structure tables of one source.
C. You cannot join a published server data source to a local file in one physical layer.

Q8. In Tableau Prep, a Customer_Name field contains values like 'Cathy', 'Kathy', and 'Kathie', which are pronounced the same but spelled differently. Which Group Values option will cluster these names together automatically?

A. Common Characters
B. Spelling
C. Trim Spaces
D. Pronunciation **<- correct**

Correct answer: D

Topic: Prep - Group Values algorithms

Why: Group Values > Pronunciation uses a pronunciation algorithm (Metaphone 3) to group values that sound alike. 'Spelling' uses edit distance (Levenshtein), and 'Common Characters' (ngram fingerprint) groups values that share unique character sequences. 'Cathy'/'Kathy' sound identical, so Pronunciation is the reliable choice.

Why the others fail:

A. Common Characters keys on shared character patterns - 'Kathy' vs 'Cathy' differ at the first letter and may split.
B. Spelling (edit distance) may still split a K/C swap depending on thresholds.
C. Trim Spaces only removes whitespace; it groups nothing.

Q9. A planning spreadsheet is 'wide': one row per product and twelve separate measure columns (Jan_Sales ... Dec_Sales). In Tableau Prep you must reshape it into rows of Product, Month, and Sales for easy analysis. Which step accomplishes this?

A. Join step with a scaffold table
B. Aggregate step
C. Clean step with a custom split
D. Pivot step - pivot columns to rows **<- correct**

Correct answer: D

Topic: Prep - pivot columns to rows

Why: The Pivot step ('Columns to Rows') converts many measure columns into two fields - a names field and a values field - which is the correct shape for Desktop analysis. Aggregate groups/summarises rows; a split divides string values; a join combines two inputs.

Why the others fail:

B. Aggregate reduces rows by grouping - it cannot unpivot columns.
A. A scaffold join multiplies rows but leaves the wide columns in place.
C. Split cuts one field on a separator; it does not reshape columns to rows.

Q10. A compliance rule states that no analyst may see rows for discontinued products anywhere in a workbook with eight worksheets - not on any current sheet, nor on any sheet added later. Where should the filter be applied?

A. As a context filter on the busiest sheet
B. As a data source filter **<- correct**
C. As a table calculation filter
D. As a dimension quick filter repeated on each sheet

Correct answer: B

Topic: Filter scope - data source filters

Why: A data source filter is defined once on the data source page and automatically constrains every worksheet that uses that source - present and future - making it the governance-grade option. Sheet-level filters (dimension, context, table calc) only affect the sheets where they are configured.

Why the others fail:

A. A context filter is still sheet-scoped (unless manually applied to other sheets).
D. Quick filters per sheet are error-prone and don't automatically cover new sheets.
C. Table calc filters hide marks last in the pipeline and are sheet-scoped.

Q11. A State dimension member 'CA' must display as 'California' in every view, while the underlying column in the database must stay untouched. What should the analyst create in Tableau Desktop?

A. An alias **<- correct**
B. A group
C. A calculated field: IF [State]='CA' THEN 'California' END
D. A set

Correct answer: A

Topic: Aliases

Why: An alias changes only the display label of a dimension member; the stored data and any joins on the raw value are unaffected. Aliases are edited by right-clicking the field > Aliases, or by right-clicking a header in the view.

Why the others fail:

B. A group creates a new grouped field - it doesn't rename individual members for display.
D. A set is a membership subset, unrelated to labels.
C. A calculated field duplicates the field and breaks whenever other members appear; aliases are the intended tool.

Q12. You drag YEAR([Order Date]) to Columns and get four separate blue header pills (2021, 2022, 2023, 2024); your line chart appears as four disconnected segments. You need one continuous time axis with a single unbroken line. What should you do?

A. Move the pill to the Pages shelf
B. Right-click the pill and convert the field to Continuous **<- correct**
C. Change the field's data type to String
D. Add the date field to context

Correct answer: B

Topic: Discrete vs. continuous dates

Why: Blue (discrete) date parts create separate headers/buckets; green (continuous) date values draw one quantitative axis, which is what lines need to be connected. Convert on the pill's right-click menu.

Why the others fail:

C. Strings sort alphabetically and cannot form a time axis.
A. Pages animates through values - one page per year - not a single trend.
D. Context is a filter concept and changes nothing about axes.

Q13. A workbook was built and fully formatted against a test SQL Server database. The production database has an identical schema. All sheets, calculated fields, and formatting must be preserved while pointing the workbook at production. What is the correct approach?

A. Use Data > Replace Data Source and connect to the production database **<- correct**
B. Rebuild the workbook against production
C. Publish the test data source and rename it 'Production'
D. Edit every sheet's fields one by one

Correct answer: A

Topic: Replace data source

Why: Data > Replace Data Source swaps the underlying connection while keeping every worksheet, calculation, axis, and format intact, as long as field names/types match. It is the standard migration path from test to production (or file to server).

Why the others fail:

B. Rebuilding throws away hours of finished work - unnecessary.
D. Manual field edits cannot re-target the connection itself.
C. Renaming a published source never changes what the workbook connects to.

Q14. A cleaning flow in Tableau Prep is finished. The result must be emailed to an external vendor who owns no Tableau software and will load the file into their own tool. Which output type is appropriate?

A. A database table in your company's warehouse
B. Published data source on Tableau Cloud
C. .csv file **<- correct**
D. .hyper extract file

Correct answer: C

Topic: Prep output types

Why: Prep can output to .hyper, .csv, a published data source, or a database table. A .csv is the universal, tool-agnostic choice for a third party with no Tableau access.

Why the others fail:

B. Requires Tableau credentials/licenses on the recipient side.
D. .hyper needs Tableau (or the Hyper API) to read.
A. The vendor has no access to your internal warehouse.

Domain 2 - Explore & Analyze Data (LODs & Calculations Intensive) - Q15-Q39

Q15. You need each customer's lifetime sales as a reusable row-level value - for example, to bucket customers into segments - and the value must stay correct no matter which dimensions are later dragged into the view. Which calculated field delivers this?

A. WINDOW_SUM(SUM([Sales]))
B. TOTAL(SUM([Sales]))
C. {FIXED [Customer ID] : SUM([Sales])} **<- correct**
D. {INCLUDE [Customer ID] : SUM([Sales])}

Correct answer: C

Topic: FIXED LOD

Why: FIXED computes SUM(Sales) at the Customer ID level, independent of the view's dimensions, and returns it to every row of that customer - perfect for segmentation and reuse. INCLUDE only makes sense relative to a view's dimensions; WINDOW_SUM/TOTAL are table calculations that depend on the view layout and break when it changes.

Why the others fail:

D. INCLUDE adds a lower level than the view - with no view defined, behaviour differs per sheet.
A. Table calc: result depends on addressing/partitioning of that particular view.
B. TOTAL is also a table calc over the current partition.

Q16. A {FIXED [Region] : SUM([Sales])} calculation is used on a sheet. Which TWO kinds of filters will change the values this FIXED LOD returns? [SELECT 2]

A. Context filters **<- correct**
B. Extract filters applied when the extract was built **<- correct**
C. Standard dimension quick filters on the Filters shelf
D. Table calculation filters

Correct answer: A, B

Topic: LOD order of operations

Why: FIXED LODs are evaluated BEFORE standard dimension filters, so dimension quick filters do not affect them. Only filters earlier in the pipeline apply: extract filters, data source filters, and context filters. Table calculation filters run last and hide marks without touching LOD values.

Why the others fail:

C. Dimension filters happen after FIXED LODs in the order of operations - the classic exam trap.
D. Table calc filters are the last step and only hide marks.

Q17. A view shows one row per Region. Management wants, for each region, the average of the state-level sales totals within that region (first total each state's sales, then average those totals). Which expression is correct?

A. AVG({INCLUDE [State] : SUM([Sales])}) **<- correct**
B. AVG({FIXED [Region] : SUM([Sales])})
C. AVG({EXCLUDE [State] : SUM([Sales])})
D. WINDOW_AVG(SUM([Sales])) computed Table (down)

Correct answer: A
Topic: INCLUDE LOD

Why: INCLUDE adds State as a lower level of detail than the view (Region), computes SUM(Sales) per state, and the outer AVG then averages those state totals. This is the textbook INCLUDE use case.

Why the others fail:

B. FIXED [Region] returns the region total itself - averaging it just returns the same number.
C. EXCLUDE removes a view dimension; State isn't in the view to remove.
D. A table calc would work by coincidence in this layout but breaks the moment the view changes.

Q18. A view lists Sub-Category rows (within Category) showing SUM([Sales]). On the same rows you also need the sales total of the whole parent Category, so each sub-category can be compared to its category total. Which calculation returns the category total on every sub-category row?

A. LOOKUP(SUM([Sales]), FIRST())
B. {FIXED [Sub-Category] : SUM([Sales])}
C. {INCLUDE [Category] : SUM([Sales])}
D. {EXCLUDE [Sub-Category] : SUM([Sales])} **<- correct**

Correct answer: D
Topic: EXCLUDE LOD

Why: EXCLUDE removes Sub-Category from the view's granularity, so the expression recomputes SUM(Sales) as if the view stopped at Category - the category total repeated per sub-category. ({FIXED [Category] : SUM([Sales])} would also achieve it, but isn't offered.)

Why the others fail:

C. INCLUDE goes to a *lower* level than the view; Category is the *higher* level here.
B. FIXED at Sub-Category simply returns each sub-category's own total.
A. LOOKUP reads other marks in the layout - fragile and layout-dependent.

Q19. What does the calculated field {FIXED : SUM([Sales])} - written with braces but no dimension - return when placed on any sheet?

A. Each row's own sales value
B. The grand total of sales for the entire data set, repeated as the same value on every row **<- correct**
C. A running total of sales down the table
D. An error: a LOD expression requires at least one dimension

Correct answer: B
Topic: Table-scoped FIXED LOD

Why: A FIXED LOD with no dimension declaration is table-scoped: it aggregates over all rows (respecting only extract/data-source/context filters) and returns that single grand total to every row. Classic use: {FIXED : SUM([Profit])} for 'total profit since the company opened', or SUM([Sales]) / SUM({FIXED : SUM([Sales])}) for percent of overall total.

Why the others fail:

D. The dimension list is optional in Tableau.
A. That would require no aggregation at all.
C. Running totals are table calculations (RUNNING_SUM).

Q20. A sheet contains {FIXED [Region] : SUM([Sales])}. A user unticks 'Furniture' in a Category quick filter, but the LOD values stubbornly stay the same. Why, and what is the fix so the LOD responds to the Category selection?

A. Change the LOD to EXCLUDE, which always respects dimension filters
B. Move the Category filter to the Pages shelf so it runs earlier
C. FIXED LODs never respond to any filter - rewrite it as a table calculation
D. FIXED LODs ignore standard dimension filters; right-click the Category filter and 'Add to Context' **<- correct**

Correct answer: D
Topic: FIXED LOD + context filters

Why: In the order of operations, context filters are built into a temp table *before* FIXED LODs run, while standard dimension filters run *after*. Adding the Category filter to context pushes it ahead of the LOD so the LOD computes on the filtered rows only.

Why the others fail:

C. FIXED LODs do respect extract, data source, and context filters.
B. Pages is for animation - irrelevant to the calculation pipeline.
A. EXCLUDE/INCLUDE LODs are computed relative to the view after dimension filters, which changes the *meaning* of the calc, not just its filter behaviour.

Q21. Examine this nested LOD:
{FIXED [Region] : MAX({FIXED [Region], [State] : SUM([Sales])})}
What does it compute?

A. For each region, the sales of its best-performing state (the maximum of that region's state totals) **<- correct**
B. The SUM of sales for each region
C. The maximum of all regional grand totals combined
D. The largest single row-level sales value in the data set

Correct answer: A
Topic: Nested LODs

Why: Evaluate inside-out: the inner {FIXED [Region],[State] : SUM([Sales])} produces one sales total per state. The outer LOD takes the MAX of those totals per region - i.e., the best state within each region, returned to every row of that region. Nested LODs are explicitly on the exam outline (2.9).

Why the others fail:

B. That is just {FIXED [Region] : SUM([Sales])}.
D. Inner aggregation is at state level, never row level.
C. The outer MAX is partitioned per region, not across the whole table.

Q22. You must create 'Days to Ship' as the number of whole days between the order and the shipment, and understand what a negative value means. Which formula is correct, and what does a negative result indicate?

A. DATEDIFF([Ship Date], [Order Date], 'day') - negative means shipping was fast
B. DATEDIFF('day', [Ship Date], [Order Date]) - positive means shipped before ordering
C. [Ship Date] - [Order Date] - negative means the order was cancelled
D. DATEDIFF('day', [Order Date], [Ship Date]) - negative means the ship date is before the order date **<- correct**

Correct answer: D
Topic: DATEDIFF

Why: The correct signature is DATEDIFF(date_part, start_date, end_date) and it returns end - start in the specified unit. Swapping the start and end dates flips the sign - a frequent exam trap. Direct subtraction of dates is not the portable Tableau way; use DATEDIFF.

Why the others fail:

A. The date_part must be the first argument.
C. Date subtraction without DATEDIFF is unreliable/unsupported across sources.
B. With the arguments reversed, positive here would actually mean a *later* ship date.

Q23. A view needs a text column that reads 'August', 'September', ... for labelling a report. Which function returns the month name as a string, rather than the number 8, 9, ...?

A. DATENAME('month', [Order Date]) **<- correct**
B. DATETRUNC('month', [Order Date])
C. MONTH([Order Date])
D. DATEPART('month', [Order Date])

Correct answer: A

Topic: DATENAME vs. DATEPART

Why: DATENAME returns a string ('August'); DATEPART and MONTH return integers (8). DATETRUNC returns a date set to the first day of the month. Choose DATENAME whenever words are needed for labels.

Why the others fail:

D. DATEPART returns integer 8.
B. DATETRUNC returns 8/1/2024 (a date).
C. MONTH returns integer 8.

Q24. A CSV column [Ship Date Text] holds dates like '15/08/2024' (day-first), which Tableau imported as strings. Working with an extract, which expression converts them to real dates?

A. STR([Ship Date Text])
B. MAKEDATE('dd', 'MM', 'yyyy')
C. DATE([Ship Date Text])
D. DATEPARSE('dd/MM/yyyy', [Ship Date Text]) **<- correct**

Correct answer: D

Topic: DATEPARSE

Why: DATEPARSE takes a format pattern describing exactly where day, month, and year appear and returns a date/datetime - built for non-standard date strings (available on extracts and many, but not all, live sources). DATE() alone cannot interpret 'day-first' strings reliably, and MAKEDATE takes numeric year, month, day arguments.

Why the others fail:

C. DATE() relies on locale parsing and misreads day-first strings.
B. MAKEDATE needs three numbers, e.g. MAKEDATE(2024, 8, 15), not format tokens.
A. STR() converts TO string - the opposite direction.

Q25. For Order ID 'CA-2024-115842' you need only the final three characters: '842'. Which expression is correct?

A. RIGHT(3, [Order ID])
B. RIGHT([Order ID], 3) **<- correct**
C. MID([Order ID], 3)
D. LEFT([Order ID], 3)

Correct answer: B

Topic: String functions - RIGHT syntax

Why: Tableau's signature is RIGHT(string, number_of_chars): the string comes first. RIGHT(3, [Order ID]) is invalid. LEFT takes characters from the start; MID(3) would start pulling from position 3 of the string.

Why the others fail:

A. Arguments reversed - classic exam trap.
D. Returns 'CA-'.
C. MID begins at character 3, not 3 from the end.

Q26. A calculated field applies INT() to a margin measure. What does INT(-4.9) return in Tableau?

A. -5
B. 4
C. -4 **<- correct**
D. 5

Correct answer: C

Topic: INT() truncation

Why: INT() truncates toward zero - it simply drops the decimal part, so INT(-4.9) = -4 (and INT(4.9) = 4). This differs from ROUND(-4.9) = -5 and FLOOR(-4.9) = -5. Negative numbers are the standard exam trap for INT.

Why the others fail:

A. -5 would be FLOOR or ROUND.
B. Sign is preserved.
D. ABS would be needed for 5... and ABS(-4.9)=4.9 anyway.

Q27. Which TWO statements about Tableau's logical functions are true? [SELECT 2]

A. CASE tests one expression for equality against each listed WHEN value **<- correct**
B. CASE can evaluate ranges, e.g. WHEN [Sales] > 1000 THEN 'Big'
C. IF ... ELSEIF ... END can evaluate range conditions such as SUM([Sales]) >= 10000 **<- correct**
D. IIF is guaranteed to return only numeric results

Correct answer: A, C

Topic: IF vs. CASE vs. IIF

Why: CASE supports equality tests only - WHEN values must equal the expression; ranges are impossible, which is the reason IF/ELSEIF exists. IF/ELSEIF handles any boolean condition, including aggregates and ranges. IIF returns whatever data type its THEN/ELSE branches define - it is not restricted to numerics.

Why the others fail:

B. CASE cannot evaluate inequalities - use IF/ELSEIF for ranges.
D. IIF(x, 'Yes', 'No') returns strings; type follows the branches.

Q28. Some rows have NULL Profit. For an average computation, the business wants those nulls treated as 0 rather than being skipped. Which is the simplest expression to wrap [Profit] with?

A. ZN([Profit]) **<- correct**
B. NULL([Profit])
C. ATTR([Profit])
D. ISNULL([Profit])

Correct answer: A

Topic: ZN / null handling

Why: ZN (Zero if Null) returns the expression's value when it is not null, otherwise 0 - exactly the requirement. IFNULL([Profit], 0) is the equivalent two-argument form. ISNULL returns a boolean test; ATTR returns the value or an asterisk; 'NULL([Profit])' is not a function.

Why the others fail:

D. ISNULL returns TRUE/FALSE - a test, not a replacement.
C. ATTR checks member uniqueness; unrelated to null replacement.
B. No such function exists.

Q29. An orders table has one row per order line. Management asks: 'How many different customers placed at least one order?' Which aggregation answers this correctly?

A. ATTR([Customer ID])
B. COUNTD([Customer ID]) **<- correct**
C. MAX([Customer ID])
D. COUNT([Customer ID])

Correct answer: B
Topic: COUNT vs. COUNTD

Why: COUNTD counts distinct values - the number of unique customers. COUNT counts every non-null row (order lines), massively over-counting customers who ordered multiple times. This mirrors the official practice question.
Why the others fail:
D. COUNT counts rows, not unique customers.
C. MAX on an ID returns the greatest ID value - meaningless.
A. ATTR returns a value or '*' - not a count.

Q30. Order IDs look like 'CA-2024-115842' (Region-Year-Number). You need the year token '2024' as its own field. Which expression is correct?

A. SPLIT([Order ID], '-', 2) **<- correct**
B. LEFT([Order ID], 2)
C. SPLIT([Order ID], '-', 3)
D. MID([Order ID], '-', 2)

Correct answer: A
Topic: SPLIT token index

Why: SPLIT(string, delimiter, token) uses a 1-based token number: token 1 = 'CA', token 2 = '2024', token 3 = '115842'. Negative indexes count from the end (SPLIT([Order ID], '-', -1) = '115842').
Why the others fail:
C. Token 3 returns the order number, not the year.
D. MID's signature is MID(string, start, [length]) - no delimiter argument.
B. LEFT(...,2) returns 'CA'.

Q31. A month-over-month change calculation reads:
SUM([Sales]) - LOOKUP(SUM([Sales]), -1)
In a continuous-month view computed Table (across), what does LOOKUP(SUM([Sales]), -1) return for each month?

A. Sales of the first month of the data set
B. The average sales of all months
C. Sales of the last month in the partition
D. Sales of the previous mark (the previous month) in the partition **<- correct**

Correct answer: D
Topic: LOOKUP offset

Why: LOOKUP(expression, offset) reaches across the partition: offset -1 = the previous mark relative to the current one. Subtracting it from the current value yields the period-over-period difference. FIRST()/LAST() return positions relative to partition ends; averages need WINDOW_AVG.
Why the others fail:
A. That behaviour comes from FIRST() with an offset, not -1 relative to current row.
C. LAST() points at the partition's end.
B. LOOKUP never averages.

Q32. A crosstab has Region on Rows and continuous MONTH(Order Date) on Columns. A 3-month moving average of sales must accumulate across the year but restart at the first month of each region instead of bleeding across regions. Which 'Compute Using' setting achieves this?

A. Table (down)
B. Specific Dimensions > Region only
C. Table (across) **<- correct**
D. Cell

Correct answer: C
Topic: Addressing & partitioning

Why: Compute Using defines the addressing (direction) of the table calc; everything not addressed becomes the partition in which it restarts. Table (across) walks along each row (through the months) and restarts when a new row (= region) begins - moving the average restarts per region as required.

Why the others fail:

A. Table (down) marches through regions first - the average would jump across regions each step.
D. Cell addresses a single cell - no window to average over.
B. Addressing by Region only would compute one value per region, not a month-by-month window.

Q33. States are ranked by SUM([Sales]) descending. Two states tie for second place. The business wants the ranking 1, 2, 2, 3 - tied states share a rank and no rank numbers are skipped. Which function should the calculated field use?

A. RANK_DENSE(SUM([Sales]), 'desc') **<- correct**
B. INDEX()
C. RANK_UNIQUE(SUM([Sales]), 'desc')
D. RANK(SUM([Sales]), 'desc')

Correct answer: A
Topic: Ranking functions

Why: RANK uses standard competition ranking (1,2,2,4 - skips a number after ties). RANK_DENSE compactly continues (1,2,2,3). RANK_UNIQUE breaks ties arbitrarily (1,2,3,4). RANK_MODIFIED gives ties the higher number (1,3,3,4). INDEX() is a positional counter, not a value rank.

Why the others fail:

D. Competition ranking skips 3 after the tie at 2.
C. RANK_UNIQUE never shares a rank.
B. INDEX numbers rows by position regardless of sales values.

Q34. You place a table-calculation-based field (e.g., 'Rank <= 3') on the Filters shelf to show only the top 3 states. Which statement about the '% of Total' values still visible is TRUE?

A. Table calculation filters execute before dimension filters in the pipeline
B. Hidden states are removed from the data, so % of Total is recalculated against the top 3 only
C. Table calculation filters merely hide marks; the hidden states remain in the computation, so % of Total is still relative to all states **<- correct**
D. Tableau does not allow filtering on table calculations

Correct answer: C
Topic: Table calc filters run last

Why: Table calc filters are the final step of the order of operations. They hide marks from display but do not remove them from the underlying table, so computations (like % of Total) are unchanged - a frequent exam trap. If you need the denominator recalculated, filter with a dimension instead.

Why the others fail:

B. That describes a normal (dimension/measure) filter, not a table calc filter.
A. They run after all other filter types.
D. Filtering on table calcs is allowed and widely used.

Q35. A view should show the Top 10 products by sales within the Technology category only. The analyst adds a Top 10 'by field' filter on Product Name and a Category = Technology quick filter - but the result shows only the Technology products that happen to be in the company's overall top 10. How do you get the top 10 *of Technology*?

A. Replace the filters with an EXCLUDE LOD
B. Right-click the Category filter and select 'Add to Context', then keep the Top 10 filter **<- correct**
C. Sort descending and manually hide everything ranked 11+
D. Convert the Top 10 filter into a table calculation filter

Correct answer: B
Topic: Context filters & Top N

Why: Top-N dimension filters are evaluated on the result left by context filters. Adding Category to context makes Tableau build a Technology-only temp table first, so the Top 10 is computed within Technology. Without context, Top 10 runs against all categories first.

Why the others fail:

D. A table calc filter hides marks last; it changes display, not the Top-N computation.
A. EXCLUDE changes view granularity - unrelated to Top-N filtering.
C. Manual hiding is not a filter and breaks with new data.

Q36. Sales managers want an on-screen control to set a quarterly revenue target that appears as a horizontal reference line on a bar chart, updating live as they type or drag. What is the correct implementation?

A. Use a quick filter on Sales pinned to the target
B. Create a numeric parameter, show its parameter control, and set the reference line's Value to that parameter **<- correct**
C. Create a set from the target value and add it to Colour
D. Create a reference line with a constant value and re-type it each quarter

Correct answer: B
Topic: Parameters with reference lines

Why: Parameters are workbook-wide, single-value variables surfaced via parameter controls; a reference line's value can be bound to a parameter so the line moves as the user changes it. Constants need manual edits; sets and quick filters filter data - they cannot drive a reference line's position.

Why the others fail:

D. Not interactive - requires editing the view each time.
C. Sets classify members; they cannot draw lines.
A. Quick filters subset marks; they cannot position a line.

Q37. Which TWO statements about sets in Tableau are true? [SELECT 2]

A. A combined set can be configured to return the members shared by two existing sets **<- correct**
B. A set defined by a condition or a Top N rule is dynamic - its membership re-evaluates when data refreshes **<- correct**
C. A set writes new rows back into the underlying data source
D. Sets can only be created by manually selecting marks and stay constant forever

Correct answer: A, B
Topic: Sets - dynamic & combined

Why: Sets are subsets of data. Manually picked member lists are fixed; condition/Top-N sets are dynamic and update with the data. Two sets can be merged into a combined set returning shared members (intersection), all members in either, or members of one except the other. Sets never modify the underlying source.

Why the others fail:

D. Condition-based sets update automatically - manual sets are just one flavour.
C. Sets are metadata in the workbook; the source is untouched.

Q38. On a map of thousands of customer geocoded points, overlapping circles visually merge into blobs. Stakeholders want a smooth colour gradient showing concentration of customers - hot zones glowing where points overlap most densely. Which map type best serves this?

A. Density map **<- correct**
B. Heat map with square marks in a crosstab
C. Filled map (choropleth)
D. Symbol map with larger marks

Correct answer: A
Topic: Map types - density

Why: Density maps colour a continuous surface by the concentration of overlapping points and are designed for exactly this overlapping-marks problem. Filled maps need geographic boundaries (polygons) such as states; a 'heat map' in Tableau is a crosstab of square marks, not a geographic technique.

Why the others fail:

D. Bigger symbols make the overlap problem worse.
C. Choropleth shades bounded regions - customer points aren't polygons.
B. Heat maps here are tabular, not geographic.

Q39. An operations team wants a histogram of order values where the bucket width (e.g., $50, $100, $250) can be changed by report consumers without editing the workbook. Which approach delivers this?

A. Write a FIXED LOD that buckets orders by customer
B. Create a manual group of [Sales] values
C. Create bins on [Sales] and set 'Size of bins' to be driven by a parameter **<- correct**
D. Create a set on [Sales] with a Top N condition

Correct answer: C
Topic: Bins + parameters

Why: Bins discretise a continuous measure into equal-width buckets and power histograms. The bin size can be bound to an integer parameter exposed through a parameter control, giving users an interactive bucket width. Groups and sets are for dimension members; the LOD described does nothing about bucketing.

Why the others fail:

B. Groups are manual and static - no equal-width logic, no interactivity.
D. Sets test membership, not equal-size numeric buckets.
A. An LOD aggregates; it cannot create histogram bins.

Domain 3 - Create Content - Q40-Q55

Q40. A sheet shows monthly sales bars and a line for monthly budget (both in currency). After choosing Dual Axis, the two measures use different scales, making the comparison misleading. Which step aligns them?

A. Move one measure to the Pages shelf
B. Add the budget field to context
C. Right-click the secondary axis and select 'Synchronize Axis' **<- correct**
D. Convert both pills to discrete

Correct answer: C
Topic: Dual-axis charts

Why: Tableau never synchronises dual axes automatically - axes are independent until you right-click an axis and Synchronize. Each measure keeps its own Marks card so bar vs. line types remain. (Only sync when the two measures share a unit/meaning.)

Why the others fail:

B. Context is a filter concept - unrelated to axis scaling.
D. Discrete headers can't share a quantitative axis.
A. Pages animates the view; it does not align scales.

Q41. Given fields Item (dimension) and Revenue (measure), how should you configure the marks card to produce a standard pie chart of revenue share per item?

A. Item to Colour, Item to Label, Revenue to Angle **<- correct**
B. Revenue to Colour, Revenue to Label, Item to Detail
C. Item to Size, Item to Label, Revenue to Detail
D. Revenue to Colour, Item to Label, Item to Angle

Correct answer: A

Topic: Pie chart mark configuration

Why: Pie marks need a measure on **Angle** to size the slices and a dimension on Colour (and Label) to distinguish them. Dimensions are invalid on Angle/Size, and putting only the measure on Colour just gradients a single-slice pie. This mirrors the official exam practice question.

Why the others fail:

D. Item (a dimension) is invalid on Angle; Revenue on Colour only tints slices.
C. Item is invalid on Size; no Angle means no slices.
B. Produces an evenly-split gradient, not share-of-revenue slices.

Q42. You need to see the distribution of order values - how many orders fall into each value range. Which is the correct way to build this in Tableau Desktop?

A. Drop [Sales] on Colour and Customer on Rows
B. Select the continuous measure [Sales] and choose Histogram from Show Me (Tableau creates equal-size bins) **<- correct**
C. Create a pie chart with Sales on Angle
D. Add a trend line over [Sales] by Category

Correct answer: B

Topic: Histograms & bins

Why: A histogram visualises the distribution of a single continuous measure. Show Me's Histogram automatically bins the measure on Columns and places CNT(orders) on Rows; bin size is adjustable in the bin field's dialog.

Why the others fail:

A. That yields a coloured list, not a distribution.
C. A pie shows part-to-whole of categories, not value ranges.
D. Trend lines model relationships, not distributions.

Q43. A project plan table lists tasks with [Start Date] and [Duration Days]. To build a timeline where each task is a horizontal bar starting at its start date and stretching for its duration, which configuration is correct?

A. Start Date on Filters, Task on Text
B. Start Date (continuous, exact date) on Columns, Task on Rows, mark type Gantt Bar, Duration on Size **<- correct**
C. Start Date and Duration both on Rows as discrete headers
D. Duration on Columns, Task on Colour, mark type Circle

Correct answer: B

Topic: Gantt charts

Why: A Gantt needs: a continuous date field on Columns (the timeline), tasks on Rows, mark type Gantt Bar, and a duration measure on Size to extend each bar. Duration is often DATEDIFF('day', [Start], [End]) when only dates are stored.

Why the others fail:

D. Circles with duration on columns place points, not spans.
A. No marks are positioned anywhere - nothing to draw.
C. Discrete headers create a crosstab, not a timeline.

Q44. Using Tableau's default box-and-whisker plot, how far do the whiskers extend?

A. Always to the absolute minimum and maximum values
B. Exactly one standard deviation above and below the mean
C. Fixed at the 5th and 95th percentiles
D. To the most extreme data points within 1.5 times the interquartile range (IQR) of the hinges **<- correct**

Correct answer: D

Topic: Box plots

Why: Tableau's box plot shows the median (line), the 25th-75th percentile box (the IQR), and whiskers reaching data points within 1.5x IQR; points beyond are plotted individually as outliers. (Reference-line options can rebase whiskers on percentiles, but 1.5x IQR is the default exam answer.)

Why the others fail:

A. Min/max whiskers are not the default.
B. Standard deviation drives *distribution bands*, not box whiskers.
C. Percentile whiskers are an option, not the default.

Q45. A bar chart shows Category and Sub-Category on Rows with sales bars. Sorting Sub-Category descending by sales currently reorders sub-categories globally, so 'Chairs' pushes other categories around. The business wants sub-categories sorted by sales independently inside each Category. What should you use?

A. Manual sort of sub-category headers
B. A nested sort: right-click Sub-Category > Sort > Sort By Field = Sales (nested) **<- correct**
C. Alphabetical sort on Category
D. A quick table calculation sorted Table (down)

Correct answer: B

Topic: Nested sorting

Why: Nested sorting ranks the inner dimension within each pane/parent independently - each Category gets its own descending Sub-Category order. A field sort without 'nested' reorders members globally across the header.

Why the others fail:

A. Manual sorting breaks the moment data changes and is global.
C. Alphabetical answers the wrong question.
D. Compute Using controls table calcs, not header sort order.

Q46. A dashboard needs a right-hand column holding several filters and a legend that must resize together cleanly as the window size changes. Which layout approach is correct?

A. Fixing absolute pixel positions for each object
B. Floating each filter object over the dashboard
C. Adding many Blank objects at random positions
D. Placing the objects in a vertical layout container (tiled) **<- correct**

Correct answer: D

Topic: Containers - tiled vs. floating

Why: Tiled layout containers snap objects into a shared grid region; a vertical container stacks and resizes its children together, keeping alignment at any size. Floating objects overlap and drift out of position when the dashboard resizes; Blank objects add spacing inside containers - they are not a layout strategy.

Why the others fail:

B. Floating breaks alignment on different screen sizes.
C. Blanks are for padding/spacing inside containers only.
A. Absolute positions defeat responsive behaviour.

Q47. Your executive dashboard must also be usable on phones. Which statement about device layouts in Tableau Desktop is TRUE?

A. Changing the default dashboard never affects any device layout
B. Phone users automatically get a perfect layout with no action by the author
C. You build phone support via Dashboard > Device Preview, then 'Add Phone Layout', arranging a phone-specific layout alongside the default **<- correct**
D. Device layouts require publishing first and are configured only on Tableau Server

Correct answer: C
Topic: Device preview & layouts

Why: Dashboard > Device Preview previews phone/tablet/desktop rendering and lets you add a custom layout per device type, rearranging objects for small screens. The default dashboard drives layouts you haven't customised, but once you customise a layout it becomes independent.

Why the others fail:

B. Auto layouts are generic; real phone support needs an authored layout.
D. Layouts are authored in Desktop before publishing.
A. Edits to the default dashboard do flow into non-customised layouts.

Q48. From a state-level sales bar chart, clicking a state should make its cities stand out on a companion map while all other cities stay visible (dimmed), not disappear. Which interactivity should you configure?

A. A set action
B. A highlight action **<- correct**
C. A filter action
D. A URL action

Correct answer: B
Topic: Highlight vs. filter actions

Why: Highlight actions emphasise related marks (colour/opacity) without removing anything from the view - perfect for visual cross-highlighting. A filter action would remove the non-selected cities entirely; URL actions open web pages; set actions modify set membership.

Why the others fail:

C. Filtering deletes the other cities from the map.
D. URL actions navigate to external content.
A. Set actions change membership - heavier than needed for simple emphasis.

Q49. Executives want to click any customers on a scatter plot to assemble a comparison group; chosen customers should recolour as 'Selected' everywhere on the dashboard, and a summary sheet should compare the selected group against everyone else. Which action type powers this?

A. A parameter action
B. A highlight action
C. A Go to Sheet action
D. A set action that toggles membership of a Customers set **<- correct**

Correct answer: D
Topic: Set actions

Why: Set actions change set membership interactively (keep-only / assign / toggle on selection, with configurable clear-selection behaviour). Because the set is a field, its IN/OUT value can drive colour and calculations on every sheet - exactly the 'selected vs. the rest' pattern.

Why the others fail:

A. Parameter actions store one scalar value, not a membership list.
B. Highlighting doesn't create a reusable group for a summary sheet.
C. Go to Sheet only navigates.

Q50. Clicking a year on a small chart should instantly update a Year Threshold value used by several calculated fields and a reference line across the dashboard. Clicking once must write that year into the shared input. Which feature does this?

A. A context filter on year
B. A data source filter on year
C. A parameter action writing the clicked year into a parameter **<- correct**
D. A set action

Correct answer: C
Topic: Parameter actions

Why: Parameter actions let mark selections (select/hover/menu) set a parameter's value from a field. Since parameters are workbook-wide and can feed calculations, filters, and reference lines, one click updates everything that references the parameter.

Why the others fail:

D. Sets store membership lists, not a single scalar threshold.
A. Context filters subset data; they cannot carry a value into calculations.
B. Data source filters are static, not click-driven.

Q51. Which TWO statements about Dynamic Zone Visibility are true? [SELECT 2]

A. When a tiled object is hidden this way, the space it occupied is reclaimed and neighbouring objects shift to fill it **<- correct**
B. It works only on Text objects
C. An object's visibility can be controlled by a boolean field or a boolean parameter via Layout > 'Control visibility using value' **<- correct**
D. The feature works only on floating objects

Correct answer: A, C
Topic: Dynamic zone visibility

Why: Dynamic zone visibility (Layout pane) shows/hides any dashboard object based on the value of a boolean field or parameter - the standard technique for 'chart appears after the user picks a value'. Hidden tiled objects give their space back, so the layout reflows. It is not restricted to floating or text objects.

Why the others fail:

D. Tiled zones in containers are the primary use case.
B. Works on sheets, images, containers - anything on the dashboard.

Q52. Stakeholders want a single drop-down to switch one dashboard zone between a Sales view, a Profit view, and a Returns view, each occupying the same space. What is the classic implementation?

A. A combined set placed on Colour
B. Three separate dashboards linked with URL actions
C. A string parameter + a calculated filter field compared to the parameter on each sheet, all sheets stacked in one container with titles hidden **<- correct**
D. The Pages shelf with a year field

Correct answer: C
Topic: Sheet swapping

Why: Sheet swap pattern: create a parameter listing the sheet names; build a boolean/string calc field that equals the parameter; filter each sheet to show only when selected; place all sheets in a vertical/horizontal container; hide sheet titles. The parameter control then swaps the visible sheet. (Dynamic zone visibility is the modern alternative.)

Why the others fail:

B. URL navigation reloads separate dashboards - clunky and not one zone.
A. Sets cannot show/hide entire sheets.
D. Pages steps through dimension values, not different worksheets.

Q53. Hovering over a state on a sales map should reveal a small monthly trend line chart for that state inside the tooltip itself. Which feature provides this?

A. Viz in Tooltip (Insert > Sheets in the tooltip editor) **<- correct**
B. A mark annotation
C. A reference band
D. A dashboard URL action

Correct answer: A
Topic: Viz in Tooltip

Why: Viz in Tooltip embeds another worksheet inside a tooltip via the tooltip editor (Insert > Sheets). The embedded viz is automatically filtered to the hovered mark (with a configurable maximum size and filter-all-fields option). Annotations are static call-outs; reference bands shade axes; URL actions leave Tableau.

Why the others fail:

B. Annotations are manually pinned text - not a live chart.
C. Bands shade a numeric range on an axis.
D. URL actions open browser pages on click.

Q54. The company's brand palette must appear as a selectable custom colour palette in the 'Edit Colors' dialog of every workbook you open on your machine. How do you register it with Tableau?

A. Add the palette XML to Preferences.tps in your My Tableau Repository folder **<- correct**
B. Edit the workbook's .twb and Tableau will remember it globally
C. Upload the palette to Tableau Cloud
D. Save a file called colors.json into the Program Files install directory

Correct answer: A
Topic: Custom colour palettes

Why: Custom palettes are defined as <color-palette> entries in Preferences.tps inside 'My Tableau Repository'. After restarting Desktop, they appear in the palette drop-down for all workbooks - the classic exam answer.

Why the others fail:

D. No such mechanism exists.
C. Cloud publishing doesn't inject palettes into Desktop.
B. Editing one .twb affects only that workbook.

Q55. An analyst must present findings as a guided, ordered walkthrough: each step keeps its own frozen view state and a written caption explaining the insight. Which Tableau construct fits best?

A. A story with story points and captions **<- correct**
B. A worksheet with many annotations
C. A single dashboard with floating text boxes
D. A packaged workbook of exported images

Correct answer: A
Topic: Stories

Why: A story is a sequence of story points - each point a snapshot of a sheet/dashboard with its own filter/selection state preserved - plus captions and navigation, designed precisely for narrative walkthroughs.

Why the others fail:

C. One dashboard can't freeze multiple sequential states.
B. Annotations annotate one view; they don't sequence insights.
D. Static images are not interactive Tableau content.

Domain 4 - Publish & Manage Content on Tableau Server / Cloud - Q56-Q60

Q56. A central data team maintains one governed 'Sales' model. Thirty analysts must build workbooks from it, and nobody should ever be prompted for the database password. What is the best publishing approach?

A. Email everyone a .tds file each month
B. Publish the data source to Tableau Server/Cloud and embed the database credentials (optionally certifying it) **<- correct**
C. Publish with 'prompt user' authentication
D. Place a .hyper file on a shared network drive

Correct answer: B
Topic: Publishing data sources

Why: A published data source centralises the model (one definition everywhere, governable, and it can be Certified). When publishing, choosing embedded credentials lets every consumer connect without knowing the password; 'prompt user' would ask each person. Local files by email/shared drive are ungoverned copies that drift.

Why the others fail:

A. Emailed copies fragment the model - 30 versions of the truth.
C. Prompting defeats the requirement and leaks password handling to users.
D. A shared .hyper has no permissions, lineage, or refresh governance.

Q57. A published extract on Tableau Server feeds the morning sales dashboard. The source database gains new rows overnight and historical rows never change. A full refresh of all history is too slow. What should be scheduled?

A. An incremental extract refresh on the server schedule, keyed on Order Date **<- correct**
B. A subscription
C. A full extract refresh every hour
D. A data-driven alert

Correct answer: A
Topic: Scheduling extract refreshes

Why: Server/Cloud schedules support both full and incremental refreshes. Since data is append-only, an incremental refresh keyed on Order Date inserts just the new rows and finishes fast on the weekday schedule.

Why the others fail:

C. Hourly full refreshes are wasteful and still too slow.
B. Subscriptions email images of views - they never refresh data.
D. Alerts watch thresholds; they don't update extracts.

Q58. The VP of Operations must receive an email the moment the daily returns measure on a published dashboard exceeds 500 units - and only in that situation. What should the analyst set up?

A. A highlight action on the returns chart
B. A subscription to the dashboard every morning
C. An incremental extract refresh
D. A data-driven alert on the returns view with a threshold of 500 **<- correct**

Correct answer: D
Topic: Data-driven alerts

Why: Alerts are threshold-based triggers configured on a view's numeric axis: when data crosses the condition, Tableau emails the owner and anyone who has added themselves. They are event-driven (only when breached), unlike subscriptions, which send on a schedule regardless of the numbers.

Why the others fail:

B. A subscription emails every morning whether or not 500 was breached.
C. Refreshing data doesn't notify anyone.
A. Highlight actions are interactive viz behaviour, not notifications.

Q59. Which TWO statements about subscriptions on Tableau Server/Cloud are true? [SELECT 2]

A. A subscription fires only when a measure crosses a threshold
B. A subscription emails an image (and optionally PDF) of a view or workbook to recipients on a defined schedule **<- correct**
C. A subscription refreshes the workbook's extract when it sends
D. Users can subscribe themselves to views they have permission to see, and users with the right permissions can subscribe others **<- correct**

Correct answer: B, D

Topic: Subscriptions

Why: Subscriptions deliver scheduled email snapshots of views/workbooks to entitled users. Threshold-triggered mail describes alerts, and subscriptions have nothing to do with extract refreshes - those run on refresh schedules.

Why the others fail:

A. That's the definition of a data-driven alert.
C. Extract refreshes are scheduled independently.

Q60. A business user needs to: interact with published dashboards, drill and edit existing workbooks in the browser and save copies, but she will never need to connect to a new external database or author content from raw sources. Which site role is the minimum appropriate choice?

A. Viewer
B. Explorer **<- correct**
C. Creator
D. Site Administrator

Correct answer: B

Topic: Site roles - Viewer / Explorer / Creator

Why: Viewer = view and interact only. Explorer adds web-editing of existing workbooks and authoring from published data sources (Explorer 'can publish' can save copies) - exactly this user's needs. Creator is required to connect to brand-new external data and build from scratch. Admin is for managing the site.

Why the others fail:

A. Viewer cannot edit or save anything.
C. Creator is more license than needed - she'd never use new-data connection rights.
D. Admin is about site management, not content editing.

Next steps: rebuild every LOD/calculation question you missed inside Tableau Desktop with the sample Superstore data - typing {FIXED ...}, DATEDIFF, SPLIT, LOOKUP and RANK_DENSE from memory twice is the fastest way to lock Domain 2 (41% of the exam).