ANSWER KEY & EXPLANATIONS

Salesforce Certified Tableau Data Analyst (DA-201) — GLM2 Practice Exam

Quick answer grid

Q1 -> B	**Q2** -> C	**Q3** -> A	**Q4** -> B	**Q5** -> A	**Q6** -> B
Q7 -> C	**Q8** -> A, C	**Q9** -> C	**Q10** -> B	**Q11** -> B	**Q12** -> A
Q13 -> B	**Q14** -> B	**Q15** -> A, B	**Q16** -> A	**Q17** -> B	**Q18** -> B
Q19 -> B	**Q20** -> C	**Q21** -> A, C	**Q22** -> D	**Q23** -> C	**Q24** -> A
Q25 -> C	**Q26** -> B	**Q27** -> B	**Q28** -> A	**Q29** -> B	**Q30** -> C
Q31 -> A	**Q32** -> A	**Q33** -> A, C	**Q34** -> B	**Q35** -> B	**Q36** -> B
Q37 -> B	**Q38** -> B	**Q39** -> A	**Q40** -> B	**Q41** -> A	**Q42** -> B
Q43 -> B	**Q44** -> A	**Q45** -> A	**Q46** -> A	**Q47** -> A, B	**Q48** -> A
Q49 -> A	**Q50** -> A	**Q51** -> B	**Q52** -> A	**Q53** -> A	**Q54** -> A
Q55 -> B	**Q56** -> B	**Q57** -> B	**Q58** -> A	**Q59** -> B	**Q60** -> A, B, C

Passing benchmark: 39 / 60 (65%). Domain score guide: Domain 1 = Q1–13, Domain 2 = Q14–43, Domain 3 = Q44–55, Domain 4 = Q56–60. Any domain under 70% personal accuracy is your next study block.

DOMAIN: CONNECT TO AND TRANSFORM DATA (Q1–Q13)

Q1 — Correct answer: B

Objective: 1.1 Connect to data sources — determine live connection vs. extract

Extracts snapshot the data into Tableau's high-performance Hyper engine, removing query load from the production server. Because the source only changes once per night, a full refresh scheduled after the nightly load keeps the dashboards as current as the source itself (B). (A) Context filters still send every query live to the source. (C) Extract filters only apply once an extract exists — they do nothing for a live connection. (D) Hourly incremental refreshes add no value because the data only changes once per day.

Q2 — Correct answer: C

Objective: 1.2 Prepare data for analysis — use multiple data sources (relationships, joins, unions)

Joins physically merge rows, so a one-to-many link (region-level quotas to order lines) fans out: each order line is repeated once per matching quota row and SUM(Sales) inflates. Relationships (C) preserve each table's native level of detail and Tableau aggregates at the right grain at query time — exactly what they were designed for with tables of different granularity. (B) Unions stack rows of the same schema. (D) Blending links separate published data sources in the view; within a single data source, a relationship is the designed tool.

Q3 — Correct answer: A

Objective: 1.3 Perform data transformation in Tableau Prep — shape data by using aggregations

In a Prep Aggregate step, Grouped Fields define the output grain and Aggregated Fields define the measures and their aggregation. Grouping by Region + Segment and aggregating SUM(Sales) yields exactly one row per combination (A). (B) swaps the roles, grouping by the measure. (C) Cleaning fixes values, not granularity. (D) Pivoting reshapes columns and rows, it does not roll data up.

Q4 — Correct answer: B

Objective: 1.2 Prepare data for analysis — prepare data by using Data Interpreter, pivot, and split

Data Interpreter scans the sheet, detects titles, notes, sub-headers, footers, extra columns and merged cells, and returns a cleanly structured version of the data — leaving the original file untouched (B). (A) Custom SQL requires writing a query and is only for database connections. (C) Pivot restructures wide or tall data. (D) Split breaks a single field into multiple fields.

Q5 — Correct answer: A

Objective: 1.2 Prepare data for analysis — prepare data by using Data Interpreter, pivot, and split

Custom Split lets you choose the delimiter and exactly which token(s) to extract, so you can keep only token 1 (A). Automatic Split uses commonly detected delimiters but always creates fields for ALL tokens — you would then have to remove the extras (so B, as described, is wrong). (C) and (D) do not extract parts of a string.

Q6 — Correct answer: B

Objective: 1.2 Prepare data for analysis — use multiple data sources (union tables)

A union stacks rows from tables with the same schema — the right tool for 12 monthly files. Prep can match files by wildcard (for example `*_2024.csv`) and adds the source table/file name as a field so each row keeps its provenance (B). (A) Joins combine columns, not rows. (C) Pivoting reshapes columns to rows, not files. (D) Relationships link logically distinct tables.

Q7 — Correct answer: C

Objective: 1.3 Perform data transformation in Tableau Prep — combine data by using joins

A left join returns every row from the left (Customers) table plus matching rows from the right (Orders) table; unmatched customers appear with nulls in the order fields (C). (A) An inner join drops customers with no orders. (B) A right join keeps all orders and drops unmatched customers. (D) A full outer join would also keep orders with no customer, which the requirement does not ask for.

Q8 — Correct answer: A, C **(two correct options)**

Objective: 1.2 Prepare data for analysis — assess data quality (completeness, consistency, accuracy)

Completeness measures whether required data is present; blank emails are missing values (A). Consistency measures whether the same fact is represented the same way across the data; the three spellings of one country break consistency (C). Accuracy would mean wrong values (not shown here), and validity would mean values outside an allowed format or domain of values.

Q9 — Correct answer: C

Objective: 1.3 Perform data transformation in Tableau Prep — determine which output type to use

When a flow output is a published data source, every scheduled run refreshes that data source in place, and every workbook connected to it automatically sees the new data (C). (A) and (B) leave the data outside Tableau Cloud, forcing manual re-publishing or reconnection. (D) A .tdsx is a shareable packaged data source file, not a scheduled server output.

Q10 — Correct answer: B

Objective: 1.4 Customize fields — choose when to convert between discrete and continuous

Continuous fields create axes; discrete fields create headers. A continuous exact date produces an unbroken axis on which missing days simply show gaps (B). (A) A discrete date part only creates a header for dates that exist in the data. (C) A string is not chronological. (D) DATEPART returns a discrete number, still giving headers.

Q11 — Correct answer: B

Objective: 1.4 Customize fields — choose when to convert between dimension and measure

Converting the field to a dimension moves it to the categorical side: Tableau stops aggregating it and lists each ID as a member (B). (A) A discrete MEASURE pill still gets aggregated (it just shows one header per group, as AGG(SUM)). (C) Aliases rename displayed members but leave the field a measure. (D) Number formatting does not change aggregation.

Q12 — Correct answer: A

Objective: 1.1 Connect to data sources — replace the connected data source for an existing chart or sheet

You must first create and set up the new connection (Data > New Data Source, then drag the table onto the canvas), and only then swap the workbook onto it via Data > Replace Data Source, confirming the current and replacement sources (A). Tableau maps fields by name, so existing sheets keep working when the names match.

Q13 — Correct answer: B

Objective: 1.1 Connect to data sources — identify data source / file types

A .tds (Tableau Data Source) file stores connection information plus your metadata changes: renamed fields, calculated fields, groups, sets, and default properties such as number formats and sort order (B). (A) A .twb is a workbook of sheets and vizzes. (C) A .twbx zips the workbook with supporting local data — more than you need. (D) A .hyper file is the extract data itself.

DOMAIN: EXPLORE AND ANALYZE DATA (Q14–Q43)

Q14 — Correct answer: B

Objective: 2.9 Create Level of Detail (LOD) calculations — write FIXED LOD calculations

FIXED computes at the dimensions listed in the calculation, independent of the view, so it returns one value per Region and replicates it onto every state in that region (B). (A) returns the state total itself. (C) INCLUDE adds [Region] to the view grain — but Region is already implied by State, so the grain does not change and you still get state totals. (D) Region is not in the view, so excluding it has no effect and you get state totals again.

Q15 — Correct answer: A, B **(two correct options)**

Objective: 2.9 Create Level of Detail (LOD) calculations — FIXED LODs and the order of operations

Tableau's order of operations evaluates extract filters, data source filters and context filters BEFORE FIXED LOD expressions; ordinary dimension filters and measure filters are applied after. Promoting the Region filter to context (A) or defining a data source filter (B) therefore changes what the FIXED calculation sees. (C) and (D) never affect a FIXED LOD.

Q16 — Correct answer: A

Objective: 2.9 Create Level of Detail (LOD) calculations — write INCLUDE LOD calculations

INCLUDE adds [Customer Name] to the view's dimensions, so each customer's total is computed first; re-aggregating with AVG then averages the customer totals per region (A). (B) sums customer totals — you get the region total, not an average. (C) averages transaction rows, which over-weights customers with many orders. (D) returns the grand total replicated across regions.

Q17 — Correct answer: B

Objective: 2.9 Create Level of Detail (LOD) calculations — write EXCLUDE LOD calculations

EXCLUDE removes [Region] from the view grain, so the denominator is each month's total of the remaining (filtered) rows — and EXCLUDE LODs are computed AFTER dimension filters (B). (A) FIXED MONTH is computed before dimension filters, so its denominator still includes Central and South. (C) with Table (Down) the denominator becomes the grand total of the whole table. (D) sums region-level totals, giving a region-scoped denominator, not a month-scoped one.

Q18 — Correct answer: B

Objective: 2.9 Create Level of Detail (LOD) calculations — write nested LOD calculations

The inner FIXED computes each month's sales total; the outer EXCLUDE drops the month dimension and takes the average of those monthly totals; subtracting from the view's SUM(Sales) gives the difference. This is Tableau's canonical nested-LOD example (B). (A) is a window aggregate, not an LOD expression as the requirement states. (C) and (D) try to nest `AVG(SUM(...))` — a table calculation — inside an LOD, which is not permitted.

Q19 — Correct answer: B

Objective: 2.9 Create Level of Detail (LOD) calculations — FIXED application

FIXED computes one value per customer regardless of other dimensions in the view, so each row shows that customer's latest order date (B). (A) MAX in the view returns the single latest date across everything displayed. (C) is a table-scoped LOD — the overall latest date replicated on every row. (D) computes the alphabetically last customer name per date, which is meaningless here.

Q20 — Correct answer: C

Objective: 2.9 Create Level of Detail (LOD) calculations — predict FIXED results at a finer grain

FIXED [Category] computes SUM(Sales) per category: Furniture = 30 + 70 = 100 and Office = 50 + 50 = 100. Because the calculation's grain (Category) is coarser than the view's grain (Category + Product), the same value replicates onto every row of the category — the Chair row shows 100 (C). (A) is the Chair's own sales, (B) the Table's sales, and (D) the grand total.

Q21 — Correct answer: A, C **(two correct options)**

Objective: 2.9 Create Level of Detail (LOD) calculations — LOD behaviors

(A) is the definition of FIXED — its dimension declaration alone sets the grain. (C) EXCLUDE removes dimensions from the view grain; if the dimension is not in the view, nothing is removed and it matches plain SUM. (B) is false: INCLUDE results change as dimensions are added to or removed from the view. (D) is false: table calculations are not allowed inside LOD expressions.

Q22 — Correct answer: D

Objective: 2.2 Create table calculations — ranking

RANK uses competition ranking (like Olympic medals): the two 150s share rank 2, consume positions 2 and 3, so the 100 product gets rank 4. RANK_DENSE never skips: 200 = 1, 150 = 2, 150 = 2, 100 = 3 (D).

Q23 — Correct answer: C

Objective: 2.2 Create table calculations — INDEX

INDEX numbers ROW POSITIONS in the final sorted view. After sorting by sales the display order is B (250), C (175), A (100), so A sits in row 3 (C). INDEX is not alphabetical and does not compare values — value comparison is RANK.

Q24 — Correct answer: A

Objective: 2.2 Create table calculations — LOOKUP with missing data

Table calculations move by MARK POSITION, not by calendar. The mark immediately before March in the view is January, so March computes 160 - 100 = 60 (A). LOOKUP does not know February ever existed — missing rows simply never participate. (B) reverses the subtraction. (C) assumes calendar awareness.

Q25 — Correct answer: C

Objective: 2.2 Create table calculations — table calculation filters

A table-calculation filter hides marks AFTER the calculation is computed — the hidden January and February marks still contribute to the running sum, so March shows 10 + 20 + 30 = 60 (C). If it had been a dimension filter, the earlier months would have been removed before the calculation and March would show 30.

Q26 — Correct answer: B

Objective: 2.2 Create table calculations — window functions

The window (-2, 0) covers the current row and the two rows before it: April = February (20) + March (30) + April (40) = 90 (B). (A) is March's window. (C) is the running total. (D) is the grand total. At partition edges the window simply shrinks — no padding occurs.

Q27 — Correct answer: B

Objective: 2.2 Create table calculations — customize table calculations (Compute Using)

Table (Across) addresses the calculation across the months within each row, partitioning at each region — the denominator is the row total, so each region row sums to 100% (B). (A) Table (Down) makes each COLUMN sum to 100%. (C) With Region on Rows and Month on Columns, panes run horizontally; Pane (Down) restarts within columns. (D) Cell makes every cell 100%.

Q28 — Correct answer: A

Objective: 2.2 Create table calculations — moving average

The quick table calculation applies Moving Average to the measure; Edit Table Calculation then lets you choose Average and set Previous Values = 2 so each point averages the current and two prior months (A). (B) An average line is a single flat line. (C) Quick table calculations apply to measures, not to date pills. (D) Trend lines are regression models, not moving averages.

Q29 — Correct answer: B

Objective: 2.1 Create calculated fields — date calculations

DATEDIFF's date-part argument can be a field — a parameter or dimension containing a valid date-part string such as 'day' or 'week' — so passing the parameter makes the unit user-selectable (B). (A) hard-codes days. (C) passes the literal string 'parameter', which is not a valid date part. (D) DATEADD shifts a date forward; it does not measure the difference between dates.

Q30 — Correct answer: C

Objective: 2.1 Create calculated fields — logical and Boolean expressions (YTD)

Both conditions are needed, joined with AND: the order must fall within the current year (year-truncated dates equal) AND not be in the future (C). (A) uses OR, so any past order — even from previous years — qualifies. (B) reverses the future test, keeping only future dates in this year (usually nothing). (D) compares a month truncation with a year truncation — the logic is wrong.

Q31 — Correct answer: A

Objective: 2.1 Create calculated fields — date calculations

First truncate to the month (`DATETRUNC('month', [Order Date])` returns the first day of the month), then shift forward with `DATEADD('day', ...)` by an offset based on that first day's weekday to land on the Tuesday (A). The other pairs cannot both truncate to a month start and shift a date by days.

Q32 — Correct answer: A

Objective: 2.1 Create calculated fields — string functions

FIND returns the position of the comma (position 4 in `Doe, Jane`); LEFT takes the 3 characters before it, giving "Doe" (A). (B) FIND counts from the left, so RIGHT grabs the wrong characters. (C) MID with that length includes the comma. (D) token 2 is " Jane" — the first name.

Q33 — Correct answer: A, C **(two correct options)**

Objective: 2.1 Create calculated fields — aggregate functions and null handling

The null handling must happen BEFORE the aggregation. ZN and IFNULL replace each null with 0 at the row level, so the average then includes those zeros (A, C). (B) computes AVG first — the nulls are already excluded — and only converts a null final result to 0. (D) likewise only patches a null average; it does not include the missing rows.

Q34 — Correct answer: B

Objective: 2.1 Create calculated fields — aggregation rules

B compares the aggregate SUM([Sales]) with the row-level field [Sales Target]; Tableau cannot mix aggregate and non-aggregate values in one expression unless the field is wrapped in an aggregate such as SUM, AVG, MIN, MAX or ATTR (B). A and C use consistent aggregation; D is purely row-level.

Q35 — Correct answer: B

Objective: 2.1 Create calculated fields — logical expressions (IF vs CASE)

IF / ELSEIF evaluates boolean conditions in order, which is required for range logic like "at least 0.30" (B). CASE compares a single expression for EQUALITY only: (A) is invalid syntax, and (C) matches only ratios of exactly 0.30 or 0.10. (D) IIF supports one condition with only two outcomes, so 'Low' is never reachable.

Q36 — Correct answer: B

Objective: 2.1 Create calculated fields — type conversion functions

SPLIT with '-' and token 3 returns "0045"; INT converts the string to the number 45 (B). (A) The whole value is not numeric, so INT returns null. (C) tries to split a number. (D) grabs "ORD", which cannot convert.

Q37 — Correct answer: B

Objective: 2.1 Create calculated fields — date calculations (DATENAME vs DATEPART)

DATENAME returns the name of the date part as a string ("January") (B). (A) DATEPART returns the number 1. (C) DATETRUNC returns a truncated date value (January 1 of that year). (D) converts the number to the string "1".

Q38 — Correct answer: B

Objective: 2.1 Create calculated fields — logical expressions (null handling on strings)

IFNULL(value, replacement) substitutes a replacement for nulls and works on any data type, including strings (B). (A) ZN takes only ONE argument and is intended for numbers. (C) ISNULL takes one argument and returns a Boolean. (D) NULLIF(a, b) returns NULL when a equals b — the opposite of what you need.

Q39 — Correct answer: A

Objective: 2.5 Create parameters to enable interactivity — in calculations

A parameter is a single placeholder value, not a measure. The CASE maps each parameter string to the correct aggregated measure, and because every branch aggregates consistently the field is valid (A). (B) would display the parameter's text. (C) is malformed CASE syntax. (D) compares a string to TRUE and uses an unaggregated measure.

Q40 — Correct answer: B

Objective: 2.5 Create parameters to enable interactivity — parameter actions

A parameter action changes a parameter's value when the user interacts with marks (click, select, or hover), and everything driven by the parameter — such as a reference line — updates instantly (B). (A) Filter actions filter target sheets. (C) Set actions change set membership. (D) Highlight actions only emphasize marks.

Q41 — Correct answer: A

Objective: 2.4 Create and use filters — sets, Top N and the order of operations

Set conditions (including Top N) are evaluated early in the order of operations — after context filters but before dimension filters. Promoting the Region filter to context makes the Top 10 condition compute within the selected region (A). (B) A fixed set never updates. (C) Groups combine members; they cannot rank. (D) Applying to more sheets does not change how membership is computed.

Q42 — Correct answer: B

Objective: 2.8 Summarize, model, and customize data by using the Analytics pane

A Reference Band shades the area between two values — configure its range from MIN(Sales) to MAX(Sales) with a per-pane (per year) scope (B). (A) A reference line is a single line. (C) Distribution bands show a spread around a center (standard deviations or percentiles). (D) Box plots summarize distributions for a categorical axis, not a time series.

Q43 — Correct answer: B

Objective: 2.8 Summarize, model, and customize data by using the Analytics pane — forecasting

Forecast Options includes an "Ignore last" setting that excludes the trailing periods from the model while keeping them visible in the view (B). (A) A filter would remove the months from the chart too — and filtering also shortens the timeline the forecast builds on. (C) Forecast length controls how far ahead to predict. (D) Deleting data is destructive and unnecessary.

DOMAIN: CREATE CONTENT (Q44–Q55)

Q44 — Correct answer: A

Objective: 3.1 Create charts — create basic charts from scratch (Gantt)

A Gantt chart positions each mark at its start date and stretches the mark's length by a measure — put the duration calculation on Size, with a continuous date so the timeline is proportional (A). (B) A bar chart of total days loses the timeline. (C) A line chart cannot encode durations. (D) Discrete dates create headers, not a proportional time axis.

Q45 — Correct answer: A

Objective: 3.1 Create charts — create basic charts from scratch (histogram)

A histogram shows the distribution of ONE continuous measure sliced into equal-size bins (A) — Tableau even auto-creates the bins when you build one from Show Me. (B) Two measures produce a scatter plot. (C) Points per order is also a scatter plot. (D) An averaged measure by dimension is a bar chart, not a distribution.

Q46 — Correct answer: A

Objective: 3.1 Create charts — box plots

The box spans the interquartile range (Q1 to Q3) — the middle 50% of values — so the narrowest box means the least variation (A). (B) The median shows the center, not the spread. (C) Outliers are extreme points beyond the whiskers. (D) Whisker reach reflects the full min-max range, which is dominated by extremes.

Q47 — Correct answer: A, B **(two correct options)**

Objective: 3.1 Create charts — scatter plots

A continuous measure can be visually encoded with a Color gradient and/or mark Size (A, B). (C) Shape encodes DISCRETE categories only. (D) Detail adds dimension members to the mark's level of detail but does not visually encode a measure.

Q48 — Correct answer: A

Objective: 3.1 Create charts — dual axis and combo charts

When both measures share the same units, synchronizing the axes forces one common scale so the bars and line align on the same grid and comparisons are honest (A). (B) Converting a measure to a discrete dimension destroys the line. (C) Measure Names filters which measures show, not their scales. (D) Hiding an axis changes nothing about the scale.

Q49 — Correct answer: A

Objective: 3.1 Sort data (including custom sort)

The Sort dialog supports Nested sorting: multiple criteria applied in order, so SUM(Profit) descending wins and Sub-Category ascending breaks ties (A). (B) Manual dragging breaks every time the data changes. (C) Alphabetical sorting does not tie-break by a measure. (D) A rank displays a number but does not reorder the bars.

Q50 — Correct answer: A

Objective: 3.3 Add interactivity to dashboards — use filter in a dashboard

"Use as Filter" (from the worksheet's menu on the dashboard) automatically creates a filter action from that sheet to the other dashboard sheets (A). (B) Stories are narrative containers. (C) Mark labels annotate. (D) Containers affect layout only.

Q51 — Correct answer: B

Objective: 3.3 Add interactivity to dashboards — add filter, URL, and highlight actions

Highlight actions emphasize the marks related to the selected/hovered mark across the target sheets — nothing is removed from the view (B). (A) Filter actions remove data from target sheets. (C) URL actions open web pages. (D) Go to Sheet navigates between views.

Q52 — Correct answer: A

Objective: 3.3 Add interactivity to dashboards — dynamic zone visibility

Dynamic zone visibility (available from Tableau 2022.3) shows or hides a zone based on a parameter value or a Boolean field — no button involved (A). (B) Filter actions cannot toggle zone visibility. (C) A transparent object hides nothing. (D) "Swap sheets" is a pattern, not the native feature described.

Q53 — Correct answer: A

Objective: 3.3 Add interactivity to dashboards — add navigation buttons

The navigation button object (Objects panel) links to another dashboard or sheet with a configurable target, style and image (A). (B) A text/URL object opens web pages, not internal dashboards. (C) An image without a target does nothing. (D) A blank container has no click behavior.

Q54 — Correct answer: A

Objective: 3.3 Add interactivity to dashboards — create show/hide buttons for dashboard objects

Floating containers ship with a built-in Show/Hide button option — clicking it collapses or expands the container, ideal for filter panels (A). (B) Dynamic zone visibility is parameter/field-driven rather than a toggle button — and the classic show/hide button is exactly this feature.

Q55 — Correct answer: B

Objective: 3.4 Format workbooks, worksheets, and dashboards — create a responsive design for specific device layouts

Device layouts are variations of the default layout: you can hide, reorder and resize items, but you cannot add objects that do not exist in the default layout (B). (A) Positions/sizes can differ — that is the point. (C) Desktop and unmatched devices keep using the default layout. (D) Device layouts live in the same workbook.

DOMAIN: PUBLISH AND MANAGE CONTENT ON TABLEAU SERVER AND TABLEAU CLOUD (Q56–Q60)

Q56 — Correct answer: B

Objective: 4.2 Schedule data updates — refresh on-premises data for Tableau Cloud

Tableau Bridge is the client that keeps extracts of on-premises data fresh on Tableau Cloud: refresh jobs run behind your firewall on schedule (B). (A) Cloud cannot reach the on-premises database for live queries. (C) Manual CSV uploads are error-prone and don't scale. (D) Subscriptions email snapshots; they never refresh data.

Q57 — Correct answer: B

Objective: 4.1 Publish content — publish a flow

Publishing the flow to the Cloud site (which uses Prep Conductor) and attaching a schedule lets it run unattended, refreshing its published output automatically (B). (A) Manual runs defeat automation. (C) Alerts monitor measure thresholds. (D) Desktop cannot run flows on a schedule.

Q58 — Correct answer: A

Objective: 4.3 Manage published workbooks — create alerts

Data-driven alerts watch a measure on a view against a threshold and email subscribed users when it is crossed — evaluated each time the extract refreshes (A). (B) Subscriptions are sent on a schedule regardless of values. (C) Refresh notifications only report job success/failure. (D) Performance alerts relate to slow dashboards, not thresholds.

Q59 — Correct answer: B

Objective: 4.3 Manage published workbooks — create subscriptions

Subscriptions email a snapshot image of a view or dashboard on a schedule, no threshold required (B). (A) Alerts are value-triggered. (C) Custom views save a personal arrangement of filters. (D) PowerPoint export is a separate manual/extension capability, not the scheduled email described.

Q60 — Correct answer: A, B, C **(three correct options)**

Objective: 4.3 Manage published workbooks — understand user roles and permissions

The three site roles are Creator (full authoring), Explorer (web authoring and publishing, depending on capabilities) and Viewer (interact with content only) (A, B, C). "Publisher" is not a site role — publishing is a capability granted within the Explorer/Creator roles.