Chapter 6.
Parallel Processors

Chulyun Kim

* This material is based on the lecture slides provided by Morgan Kaufmann

Introduction

- Goal: connecting multiple computers to get higher performance
  - Multiprocessors
  - Scalability
- Task-level (process-level) parallelism
  - High throughput for independent jobs
- Parallel processing program
  - Single program run on multiple processors
- Multicore microprocessors
  - Chips with multiple processors (cores)

Hardware and Software

- Hardware
  - Serial: e.g., Pentium 4
  - Parallel: e.g., quad-core Xeon e5345
- Software
  - Sequential: e.g., matrix multiplication
  - Concurrent: e.g., operating system
- Sequential/concurrent software can run on serial/parallel hardware
  - Challenge: making effective use of parallel hardware

Parallel Programming

- Parallel software is the problem
- Need to get significant performance improvement
  - Otherwise, just use a faster uniprocessor, since it's easier!
- Difficulties
  - Partitioning
  - Coordination
  - Communications overhead

Amdahl's Law

- Sequential part can limit speedup
- Example: 100 processors, 90× speedup?
  - $T_{new} = T_{parallelizable}/100 + T_{sequential}$
  - $$\text{Speedup} = \frac{1}{(1 - F_{parallelizable}) + F_{parallelizable}/100} = 90$$
  - Solving: $F_{parallelizable} = 0.999$
- Need sequential part to be 0.1% of original time

Scaling Example

- Workload: sum of 10 scalars, and 10 × 10 matrix sum
  - Speed up from 10 to 100 processors
- Single processor: Time = (10 + 100) × t_{add}
- 10 processors
  - Time = 10 × t_{add} + 100/10 × t_{add} = 20 × t_{add}
  - Speedup = 110/20 = 5.5 (55% of potential)
- 100 processors
  - Time = 10 × t_{add} + 100/100 × t_{add} = 11 × t_{add}
  - Speedup = 110/11 = 10 (10% of potential)
- Assumes load can be balanced across processors

Scaling Example (cont)

- What if matrix size is 100 × 100?
- Single processor: Time = (10 + 10000) × t_{add}
- 10 processors
  - Time = 10 × t_{add} + 10000/10 × t_{add} = 1010 × t_{add}
  - Speedup = 10010/1010 = 9.9 (99% of potential)
- 100 processors
  - Time = 10 × t_{add} + 10000/100 × t_{add} = 110 × t_{add}
  - Speedup = 10010/110 = 91 (91% of potential)
- Assuming load balanced

Instruction and Data Streams

- An alternate classification

		Data Streams	
		Single	Multiple
Instruction Streams	Single	**SISD**: Intel Pentium 4	**SIMD**: SSE instructions of x86
	Multiple	**MISD**: No examples today	**MIMD**: Intel Xeon e5345

- SPMD: Single Program Multiple Data
  - A parallel program on a MIMD computer
  - Conditional code for different processors

Example: (Y = a × X + Y)

- Conventional MIPS code

```
      l.d   $f0,a($sp)      ;load scalar a
      addiu r4,$s0,#512     ;upper bound of what to load
loop: l.d   $f2,0($s0)      ;load x(i)
      mul.d $f2,$f2,$f0     ;a × x(i)
      l.d   $f4,0($s1)      ;load y(i)
      add.d $f4,$f4,$f2     ;a × x(i) + y(i)
      s.d   $f4,0($s1)      ;store into y(i)
      addiu $s0,$s0,#8      ;increment index to x
      addiu $s1,$s1,#8      ;increment index to y
      subu  $t0,r4,$s0      ;compute bound
      bne   $t0,$zero,loop  ;check if done
```

- Vector MIPS code

```
      l.d     $f0,a($sp)    ;load scalar a
      lv      $v1,0($s0)    ;load vector x
      mulvs.d $v2,$v1,$f0   ;vector-scalar multiply
      lv      $v3,0($s1)    ;load vector y
      addv.d  $v4,$v2,$v3   ;add y to product
      sv      $v4,0($s1)    ;store the result
```

Vector Processors

- Stream data from/to vector registers to units
  - Data collected from memory into registers
  - Results stored from registers to memory
- Example: Vector extension to MIPS
  - 32 × 64-element registers (64-bit elements)
  - Vector instructions
    - `lv`, `sv`: load/store vector
    - `addv.d`: add vectors of double
    - `addvs.d`: add scalar to each element of vector of double

Vector vs. Scalar

- Vector architectures and compilers
  - Simplify data-parallel programming
  - Explicit statement of absence of loop-carried dependences
  - Avoid control hazards by avoiding loops



SIMD

- Operate elementwise on vectors of data
  - E.g., MMX and SSE instructions in x86
    - Multiple data elements in 128-bit wide registers
- All processors execute the same instruction at the same time
  - Each with different data address, etc.
- Simplifies synchronization
- Reduced instruction control hardware
- Works best for highly data-parallel applications

Multithreading

- Performing multiple threads of execution in parallel
  - Replicate registers, PC, etc.
  - Fast switching between threads
- Fine-grain multithreading
  - Switch threads after each cycle
  - Interleave instruction execution
  - If one thread stalls, others are executed
- Coarse-grain multithreading
  - Only switch on long stall (e.g., L2-cache miss)
  - Simplifies hardware, but doesn't hide short stalls (eg, data hazards)

Simultaneous Multithreading

- In multiple-issue dynamically scheduled processor
  - Schedule instructions from multiple threads
  - Instructions from independent threads execute when function units are available
  - Within threads, dependencies handled by scheduling and register renaming
- Example: Intel Pentium-4 HT
  - Two threads: duplicated registers, shared function units and caches

Multithreading Example



History of GPUs

- Early video cards
  - Frame buffer memory with address generation for video output
- 3D graphics processing
  - Originally high-end computers (e.g., SGI)
  - Moore's Law ⇒ lower cost, higher density
  - 3D graphics cards for PCs and game consoles
- Graphics Processing Units
  - Processors oriented to 3D graphics tasks
  - Vertex/pixel processing, shading, texture mapping, rasterization

Graphics in the System



GPU Architectures

- Processing is highly data-parallel
  - GPUs are highly multithreaded
  - Use thread switching to hide memory latency
    - Less reliance on multi-level caches
  - Graphics memory is wide and high-bandwidth
- Trend toward general purpose GPUs
  - Heterogeneous CPU/GPU systems
  - CPU for sequential code, GPU for parallel code
- Programming languages/APIs
  - DirectX, OpenGL
  - C for Graphics (Cg), High Level Shader Language (HLSL)
  - Compute Unified Device Architecture (CUDA)

Example: NVIDIA Tesla



Example: NVIDIA Tesla

- Streaming Processors
  - Single-precision FP and integer units
  - Each SP is fine-grained multithreaded
- Warp: group of 32 threads
  - Executed in parallel, SIMD style
    - 8 SPs
      × 4 clock cycles
  - Hardware contexts for 24 warps
    - Registers, PCs, …



Classifying GPUs

- Don't fit nicely into SIMD/MIMD model
  - Conditional execution in a thread allows an illusion of MIMD
    - But with performance degredation
    - Need to write general purpose code with care

	Static: Discovered at Compile Time	Dynamic: Discovered at Runtime
Instruction-Level Parallelism	VLIW	Superscalar
Data-Level Parallelism	SIMD or Vector	**Tesla Multiprocessor**

Putting GPUs into Perspective

Feature	Multicore with SIMD	GPU
SIMD processors	4 to 8	8 to 16
SIMD lanes/processor	2 to 4	8 to 16
Multithreading hardware support for SIMD threads	2 to 4	16 to 32
Typical ratio of single precision to double-precision performance	2:1	2:1
Largest cache size	8 MB	0.75 MB
Size of memory address	64-bit	64-bit
Size of main memory	8 GB to 256 GB	4 GB to 6 GB
Memory protection at level of page	Yes	Yes
Demand paging	Yes	No
Integrated scalar processor/SIMD processor	Yes	No
Cache coherent	Yes	No

Fallacies

- Amdahl's Law doesn't apply to parallel computers
  - Since we can achieve linear speedup
  - But only on applications with weak scaling
- Peak performance tracks observed performance
  - Marketers like this approach!
  - But compare Xeon with others in example
  - Need to be aware of bottlenecks

Pitfalls

- Not developing the software to take account of a multiprocessor architecture
  - Example: using a single lock for a shared composite resource
    - Serializes accesses, even if they could be done in parallel
    - Use finer-granularity locking

Concluding Remarks

- Goal: higher performance by using multiple processors
- Difficulties
  - Developing parallel software
  - Devising appropriate architectures
- SaaS importance is growing and clusters are a good match
- Performance per dollar and performance per Joule drive both mobile and WSC