# Harnessing Greek Textual Resources with Large Language Models and Conversational Al

# Konstantinos Skianis, Ph.D.

https://y3nk0.github.io



Department of Computer Science & Engineering University of Ioannina, Greece

Friday 3/11/2023

About me

About me

- 2 Introduction
- Background
- 4 Project
- 5 Results
- 6 Summary

 About me
 Introduction
 Background
 Project
 Results
 Summa

 0 ● 0 0
 000
 000000
 000000
 0000000
 000

### About me

#### **Education:**

- Ptichion @Informatics, Athens University of Economics and Business, Greece
- Master MVA @École Normale Superieure Paris-Saclay, Paris, France
- Ph.D. @École Polytechnique, Paris, France


### Professional experience:

- Co-founder @BLUAI, PrimeHost
- Researcher @NKUA
- Adjunct Professor @AUEB
- Worked on multiple european projects

### Highlights

- Best paper award at TextGraphs@NAACL 2018: "Fusing Document, Collection and Label Graph-based Representations with Word Embeddings for Text Classification"
- Nature Scientific Reports 2023 journal paper: "Predicting COVID-19 positivity and hospitalization with multi-scale graph neural networks"
- Both startups are members of well-known accelerators

Working for 3 years with the french Agence Numerique Sante in machine translation for medical terminologies



 About me
 Introduction
 Background
 Project
 Results
 Summ

 ○○○
 ○○○
 ○○○○○
 ○○○○○
 ○○○○○○
 ○○○○○○

# PrimeHost

Automate guest conversations with the power of AI

- 1 About me
- 2 Introduction
- Background
- 4 Project
- 5 Results
- 6 Summary

# Greek document repositories

# Have you tried searching information in diavgeia.gov.gr?



# Motivation

### **Project**

Build a pipeline which combines Large Language Models (LLMs) with conversational AI for Greek textual resources

### Why?

- limited applications of cutting-edge NLP approaches in Greek resources
- most of them almost inacessible with old search capabilities

#### Goal

Facilitate extracting knowledge from Greek textual corpora:

- enabling asking questions
- assisting in creating/enhancing existing resources (knowledge graphs, ontologies etc.)
- models and methods can be used in multiple scenarios

- 1 About me
- 2 Introduction
- 3 Background
- 4 Project
- 5 Results
- 6 Summary

# Background

### NLP has been greatly empowered by:

- Neural probabilistic language model (Bengio et al., 2000)
- Word embeddings (Mikolov et al., 2013)
- Transformers (Vaswani et al., 2017)
  - encoder-decoder architecture
  - encoder: multi-head self-attention layers to encode input for creating its latent representations
  - decoder: cross-attention on latent representations and autoregressively generates target
  - BERT: Pre-training of deep bidirectional transformers for language understanding (3TB data, 300M params) (Devlin et al., 2018)
- Large Language Model (LLM)
  - OpenAI GPT: Improving language understanding by generative pre-training (GPT3: 45TB data, 175B params) (Radford et al., 2018)


# Foundational models

- Play a crucial role in forming the basis for more intricate AI and ML models and applications
- LLMs (e.g. BERT, GPT4) are prime examples of foundational models, that acquire knowledge from datasets, allowing them to capture fundamental patterns and relationships
- Initially pre-trained on extensive, general-purpose data and later adapted to specific tasks or domains
- Most commonly used objective to pre-train decoder-only LLMs, e.g. GPT3 and PaLM (Chowdhery et al., 2022), the language modeling task (LM)
- Given a sequence of tokens  $x = \{x_1, \dots, x_n\}$ , the LM task autoregressively predicts the target tokens  $x_i$  based on the preceding tokens  $x_{< i}$  in a sequence, maximize:

$$\mathcal{L}_{LM}(x) = \sum_{i=1}^{n} \log P(x_i | x_{< i})$$
 (1)

# Fine-tuning and scale


- Causal decoder architecture (GPT3) can achieve a superior zero-shot and few-shot generalization capacity
- Full fine-tuning → retraining all model parameters is less feasible (e.g. deploying fine-tuned GPT-3 with 175B params is prohibitively expensive)



Timeline of existing LLMs (having a size larger than 10B) (Zhao et al., 2023)

# LLaMA 2

- Developed by META, open-source (Touvron et al., 2023)
- 70B parameters, 2T tokens, 2000 80G A100
- Grouped-query attention, Ghost Attention, In-Context Temperature re-scaling and Temporal Perception



LLaMA 2-CHAT via supervised fine-tuning, Reinforcement Learning with Human Feedback (RLHF)

# Mistral 7B

- Transformer-based, 7B params (Jiang et al., 2023)
- Outperforms Llama 2 13B on all benchmarks, Llama 1 34B on many, approaches CodeLlama 7B performance on code
- Grouped-query attention, Sliding Window Attention (SWA) to handle longer sequences at smaller cost
- SWA exploits the stacked layers of a transformer to attend in the past beyond the window size

The cat

1

 Higher layers have access to information further in the past than what the attention patterns seems to entail

sat

0

on the


0

0


0


0

1



Vanilla Attention





Sliding Window Attention

**Effective Context Length** 

- 1 About me
- 2 Introduction
- Background
- 4 Project
- 5 Results
- 6 Summary

# Large Greek textual resources

- A Greek Parliament Proceedings Dataset for Computational Linguistics and Political Analysis (Dritsa et al., 2022)
  - 1989 up to 2020
  - >1M speeches with extensive meta-data
  - extracted from 5,355 parliamentary sitting record files
- Corpus of Greek legislation, published by the National Publication Office,
- Corpus of EU legislation (Greek translation), as published in Eur-Lex
- Diavgeia (diavgeia.gov.gr):
  - 58M documents
  - 5260 active organizations/entities
  - 137K users
  - hard to access in a meaningful way

# Related work

#### Models

- Greek-BERT (Koutsikakis et al., 2020)
- 340M params, 29GB, 3.04B tokens
- Greek-BART: denoising auto-encoder (Evdaimon et al., 2023)
  - 181M params, 77GB

### Systems

- A linked data platform for Greek legislation (Angelidis et al., 2018)
- Al-guided chatbots for citizens-government communication (Androutsopoulou et al., 2019)
- Chatbots to provide public service information (Stamatis et al., 2020)
- Chatbot for passport info (Antoniadis and Tambouris, 2021)
- Extracting Structured Information From Diavgeia (Tsironidou, 2021)

No models created by document repos and limited chatbot capabilities

# Proposed work

#### Goal

Incorporate LLMs and conversational AI to exploit Greek textual resources


### Case study

Ask questions to Diavgeia in natural language and extract knowledge

### Proposed pipeline:

- (1) download, preprocess and store documents,
- (2) build a Retrieval-Augmented Generation (RAG) system, incorporating external knowledge into LLMs (Lewis et al., 2020)
- (3) use LLM (e.g. ChatGPT API) and get answers

# Pipeline



A full schematic illustration, based on: https://ubuntu.com/blog/llms-explained

me Introduction Background **Project** Results Summa

000 000000 00000 000000 0000000 000

# Retrieval-Augmented Generation

#### Benefits

- Consistency: more likely to get the same answer from the same question
- Increased factual accuracy: LLM's responses are based on the provided information → model is less likely to hallucinate or mislead
- Decreased cost: building a RAG pipeline is less expensive than fine-tuning. Update only the database instead of training a new model
- Currency: ensure the LLM's responses are based on up-to-date data
- Easily verifiable source: access to the source for cross-checking
- Strong scalability: millions of documents

#### Cons

- Complexity: chunking, quality of search, low-quality data
- Context length limitation: ChatGPT (gpt-3.5-turbo) has a maximum context length of 4096 tokens
- Limited creativity: losing the point of generative Al

- 1 About me
- 2 Introduction
- Background
- 4 Project
- 5 Results
- 6 Summary

# **Implementation**

### Setup:

- 100 documents (1/1/2023 to 2/1/2023)
- BM25 retriever

### Created a docker image with 4 services:

- Redis: open-source, key-value in-memory database to hold history
- Elasticsearch: search engine to look into documents
- Kibana: visualization, data analytics
- Flask API: RESTful API to expose endpoints
  - Response uses OpenAl API (gpt-3.5-turbo)








# Example

# Url: https://diavgeia.gov.gr/decision/view/93AB469H $\Gamma\Upsilon$ -7IZ



# Search in diavgeia.gov.gr



### Frontend

# DiaygeiaBot

καλησπέρα, τι είσαι;

Καλήσπέρα! Είμαι ο Diaygeia Assistant, ένας χρήσιμος bot που απαντά σε ερωτήσεις σχετικά με έγγραφα που ανέβηκαν στο diavgeia.gov.gr. Πώς μπορώ να σας βοηθήσω σήμερα;

Type your message here...

Send

# Extracting info via the chatbot

# DiaygeiaBot

θα ήθελα να μου πεις τι χορηγία έγινε από την εταιρεία Μασούτης προς το Εθνικό Θέατρο

Η εταιρεία Μασούτης παρείχε προϊόντικη χορηγία προς το Εθνικό Θέατρο με το ποσό των 60.000,00 ευρώ.

μπορείς να μου δώσεις τον ΑΔΑ για την παραπάνω χορηγία; Ο αριθμός ΑΔΑ για την παραπάνω χορηγία είναι 93ΑΒ469ΗΓΥ-7ΙΖ.

μπορείς να μου δώσεις και το url για την παραπάνω χορηγία; Το URL για την παραπάνω χορηγία είναι: https://diavgeia.gov.gr/doc/93AB469HΓY-7IZ

Type your message here...

Send

# Key takeaways

# Diavgeia:

- search returns thousands of docs
- not the most relative results

#### LLM-based conversational AI with RAG:

- Prompt engineering can be crucial
- Hallucination (e.g. showing doc with ADA that does not exist)
- Context size affects performance and cost
- Conversation history plays important role
- GPT4 more powerful, but expensive

#### To-do:

- More testing, embeddings, improve UI
- Evaluation: strong LLMs as judges to evaluate on more open-ended questions (Zheng et al., 2023)

# Next improvements: fine-tuning

#### Reminder

Full fine-tuning LLMs remains expensive and slow.

Parameter-efficient fine-tuning (PEFT), cost-efficient, faster, adapting pre-trained models to downstream applications, by fine-tuning a small number of extra model parameters:

- Parameter-efficient prompt tuning (Lester et al., 2021)
- LoRA: Low-rank adaptation of large language models (Hu et al., 2022);(Dettmers et al., 2023)
- P-tuning v2: Prompt tuning comparable to fine-tuning across scales and tasks (Liu et al., 2022)
- GPT understands, too (Liu et al., 2023)




Figure: LoRA reparametrization.
Only A and B are trained.

- 1 About me
- 2 Introduction
- 3 Background
- 4 Project
- 5 Results
- 6 Summary

# Summary

#### Contribution:

- first approach to use an end-to-end NLP approach, combining LLMs, conversational AI and Greek document repos
- real use-case with Diavgeia, access it better

### Why is it important?

- more resources can be added or used for finetuning
- no training required (e.g. with OpenAI API)
- free open-source alternative (e.g. LLaMa 2, Mistral 7B)
- the pipeline can be easily adopted for other documents repos
- highly adjustable for other tasks (e.g. enhance corpora, create new legal documents from scratch fast)

# Future directions?

- Regularization
  - Opt-iml: Scaling language model instruction meta learning through the lens of generalization (lyer et al., 2022)
- Knowledge graphs
  - Temporal Question Answering over KGs (Chen et al., 2023)
  - Graph-Aware Language Model Pre-Training (Xie et al., 2023)
- Graph Neural Networks
  - Graph Neural Prompting with LLMs (Tian et al., 2023)
- Multimodality
  - Palm-e: An embodied multimodal LLM (Driess et al., 2023)
  - Adapted Multimodal Bert with Layer-Wise Fusion for Sentiment Analysis (Chlapanis et al., 2023)

Thank you! Questions?



### References I



Androutsopoulou, Aggeliki et al. (2019). "Transforming the communication between citizens and government through Al-guided chatbots". In: *Government information quarterly* 36.2, pp. 358–367.



Angelidis, Iosif et al. (2018). "Nomothesia: a linked data platform for Greek legislation". In:



Antoniadis, Panteleimon and Efthimios Tambouris (2021). "PassBot: A chatbot for providing information on Getting a Greek Passport". In: Proceedings of the 14th International Conference on Theory and Practice of Electronic Governance, pp. 292–297.



Bengio, Yoshua, Réjean Ducharme, and Pascal Vincent (2000). "A neural probabilistic language model". In: Advances in neural information processing systems 13.



Chen, Ziyang, Jinzhi Liao, and Xiang Zhao (2023). "Multi-granularity Temporal Question Answering over Knowledge Graphs". In: Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp. 11378–11392.



Chlapanis, Odysseas S, Georgios Paraskevopoulos, and Alexandros Potamianos (2023). "Adapted Multimodal Bert with Layer-Wise Fusion for Sentiment Analysis". In: ICASSP 2023-2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, pp. 1–5.



# References II



Chowdhery, Aakanksha et al. (2022). "Palm: Scaling language modeling with pathways". In: arXiv preprint arXiv:2204.02311.



Dettmers, Tim et al. (2023). "Qlora: Efficient finetuning of quantized Ilms". In: arXiv preprint arXiv:2305.14314.



Devlin, Jacob et al. (2018). "Bert: Pre-training of deep bidirectional transformers for language understanding". In: arXiv preprint arXiv:1810.04805.



Driess, Danny et al. (2023). "Palm-e: An embodied multimodal language model". In: arXiv preprint arXiv:2303.03378.



Dritsa, Konstantina et al. (2022). "A Greek Parliament Proceedings Dataset for Computational Linguistics and Political Analysis". In: Advances in Neural Information Processing Systems 35, pp. 28874–28888.



Evdaimon, lakovos et al. (2023). "GreekBART: The First Pretrained Greek Sequence-to-Sequence Model". In: arXiv preprint arXiv:2304.00869.



Hu, Edward J et al. (2022). "Lora: Low-rank adaptation of large language models". In: *ICLR*.



lyer, Srinivasan et al. (2022). "Opt-iml: Scaling language model instruction meta learning through the lens of generalization". In: arXiv preprint arXiv:2212.12017.



Jiang, Albert Q. et al. (2023). Mistral 7B. arXiv: 2310.06825 [cs.CL].



# References III



Koutsikakis, John et al. (2020). "Greek-bert: The greeks visiting sesame street". In: 11th Hellenic conference on artificial intelligence, pp. 110–117.



Lester, Brian, Rami Al-Rfou, and Noah Constant (2021). "The power of scale for parameter-efficient prompt tuning". In: EMNLP.



Lewis, Patrick et al. (2020). "Retrieval-augmented generation for knowledge-intensive nlp tasks". In: Advances in Neural Information Processing Systems 33, pp. 9459–9474.



Liu, Xiao et al. (2022). "P-tuning v2: Prompt tuning can be comparable to fine-tuning universally across scales and tasks". In: ACL.



Liu, Xiao et al. (2023). "GPT understands, too". In: Al Open.



Mikolov, Tomas et al. (2013). "Distributed representations of words and phrases and their compositionality". In: Advances in neural information processing systems 26.



Radford, Alec et al. (2018). Improving language understanding by generative pre-training. OpenAl.



Stamatis, Anestis et al. (2020). "Using chatbots and life events to provide public service information". In: Proceedings of the 13th International Conference on Theory and Practice of Electronic Governance, pp. 54–61.



Tian, Yijun et al. (2023). "Graph Neural Prompting with Large Language Models". In: arXiv preprint arXiv:2309.15427.



# References IV



Touvron, Hugo et al. (2023). Llama 2: Open Foundation and Fine-Tuned Chat Models. arXiv: 2307.09288 [cs.CL].



Tsironidou, Eleni (2021). Extracting Structured Information From Diavgeia Portal.



Vaswani, Ashish et al. (2017). "Attention is all you need". In: Advances in neural information processing systems 30.



Xie, Han et al. (2023). "Graph-Aware Language Model Pre-Training on a Large Graph Corpus Can Help Multiple Graph Applications". In: KDD.



Zhao, Wayne Xin et al. (2023). "A survey of large language models". In: arXiv preprint arXiv:2303.18223.



Zheng, Lianmin et al. (2023). "Judging LLM-as-a-judge with MT-Bench and Chatbot Arena". In: NeurIPS.