

Class 5 data Visualization with ggplot2

Chelsea (PID: A16871799)

Using GGLOT

The ggplot2 package needs to be installed as it does not come with R "out of the box"


We use the 'install.packages()' to do this

```
head(cars)
```

	speed	dist
1	4	2
2	4	10
3	7	4
4	7	22
5	8	16
6	9	10

To use ggplot we first need to load it up before I can call any of functions in the packages. do this with the library() function.

```
library(ggplot2)  
ggplot()
```




All ggplot find at least 3 thing -data (stuff we plot) -aesthetic mapping (aes value) -geoms

```
ggplot(cars)+  
  aes(x=speed, y=dist)+  
  geom_point()+  
  geom_smooth(method="lm", se=FALSE)+  
  labs(title="Speed and stopping distance of Cars",  
        x="Speed (MPH)",  
        y="Stopping Distance (ft)",  
        subtitle = "Your informative subtitle text here",  
        caption="Dataset: 'cars'")+  
  theme_bw()
```

`geom_smooth()` using formula = 'y ~ x'

Speed and stopping distance of Cars


Your informative subtitle text here



Dataset: 'cars'

ggplot is not the only graphing system in R there are more. There is even “base R” graphics.

```
plot(cars)
```



```
url <- "https://bioboot.github.io/bimm143_S20/class-material/up_down_expression.txt"
genes <- read.delim(url)
head(genes)
```

	Gene	Condition1	Condition2	State
1	A4GNT	-3.6808610	-3.4401355	unchanging
2	AAAS	4.5479580	4.3864126	unchanging
3	AASDH	3.7190695	3.4787276	unchanging
4	AATF	5.0784720	5.0151916	unchanging
5	AATK	0.4711421	0.5598642	unchanging
6	AB015752.4	-3.6808610	-3.5921390	unchanging

```
nrow(genes)
```

```
[1] 5196
```

```
ncol(genes)
```

```
[1] 4
```

```
sum(genes$State=="up")
```

```
[1] 127
```


```
table(genes$State)
```

down	unchanging	up
72	4997	127

```
round( table(genes$State)/nrow(genes) * 100, 2 )
```

down	unchanging	up
1.39	96.17	2.44

```
p <- ggplot(genes)+  
  aes(x=Condition1, y=Condition2, col=State)+  
  geom_point()  
  
p+scale_colour_manual(values=c("blue","gray","red"))+  
  labs(title="Gene Expression Changes Upon Drug Treatment",  
        x="Control (no drug)",  
        y="Drug Treatment")
```



File location online

```
library("dplyr")
```

Attaching package: 'dplyr'

The following objects are masked from 'package:stats':

filter, lag


The following objects are masked from 'package:base':

intersect, setdiff, setequal, union

```
url <- "https://raw.githubusercontent.com/jennybc/gapminder/master/inst/extdata/gapminder.  
gapminder <- read.delim(url)  
gapminder_2007 <- gapminder %>% filter(year==2007)
```

```
gapminder_1957 <- gapminder %>% filter(year==1957| year==2007)

ggplot(gapminder_1957) +
  geom_point(aes(x = gdpPercap, y = lifeExp, color=continent,
                 size = pop), alpha=0.7) +
  scale_size_area(max_size = 10) +
  facet_wrap(~year)
```




```
gapminder_top5 <- gapminder %>%
  filter(year==2007) %>%
  arrange(desc(pop)) %>%
  top_n(5, pop)

gapminder_top5
```

	country	continent	year	lifeExp	pop	gdpPercap
1	China	Asia	2007	72.961	1318683096	4959.115
2	India	Asia	2007	64.698	1110396331	2452.210
3	United States	Americas	2007	78.242	301139947	42951.653
4	Indonesia	Asia	2007	70.650	223547000	3540.652
5	Brazil	Americas	2007	72.390	190010647	9065.801

```
ggplot(gapminder_top5) +  
  geom_col(aes(x = country, y = pop, fill = lifeExp))
```



```
ggplot(gapminder_top5) +  
  aes(x=reorder(country, -pop), y=pop, fill=country) +  
  geom_col(col="gray30") +  
  guides(fill="none")
```