# PAPER ANALYSIS



Presented by Yannis He

-

Paper: nuScenes: A multimodal dataset for autonomous driving


Authors: Holger Caesar, Varun Bankiti, Alex H. Lang, Sourabh Vora, Venice Erin Liong,

Qiang Xu, Anush Krishnan, Yu Pan, Giancarlo Baldan, Oscar Beijbom

https://arxiv.org/pdf/1903.11027.pdf

### DATASET INTRODUCTION

- First dataset to carry the full autonomous vehicle sensor suite:
  - o 6 cameras, 5 radars, 1 lidar
  - O All with 360 degree field of view.
- Contents:
  - o 1000 scenes, each 20s long and fully annotated with 3D bounding boxes for 23 classes and 8 attributes
  - 7 times more annotations and 100 times more images than KITTI dataset
- Full released in March 2019
- Purpose of multimodal:
  - O Cameras: accurate measurements of edges, color, light
    - Good at classifications and localization on the image plane
    - Not good at 3D localization
  - O Lidar: less semantic information but highly accurate localization in 3D
    - Data is sparse
      - Range of 50-150m
  - O Radar: measure object velocity through Doppler effect
    - Data sparser than lidar
    - Less precise in terms of localization
    - Range of 200-300m
- Only dataset with radar and night/rain data included
- Recorded at Boston (Seaport and South Boston) and Singapore (SG)



## OTHER DATASET IN THIS FIELD

0

0

0

0

0

0

0

0

11

2

7

0

0

0

152

10

8-35

12

8

6

3

23

15

9

4

14

Global

NY, SF

4x China

5x China

Karlsruhe

China

Seoul

SF

Boston, SG

Miami, PT

Palo Alto

3x USA

SG

3x Germany

Presented by Yannis He

Some other dataset in this field:

2017

2017

2018

2019

2012

2018

2018

2019

2019

2019

2019

2019

2019

2019

n/a

100k

1k†

22

160

1k

113

366

1k

n/a

n/a

1k

100

1.5

2

0.77

5.5

0.6

2.5

5.5

55

Vistas [33]

BDD100K [85]

 $D^2$ -City [11]

KITTI [32]

AS lidar [54]

KAIST [17]

Argoverse [10]

Waymo Open [76]

Lyft L5 [45]

A\*3D [62]

A2D2 [34]

H3D [61]

nuScenes

ApolloScape [41]

| Dataset         | Year | Sce-<br>nes | Size<br>(hr) | RGB<br>imgs | PCs<br>lidar <sup>††</sup> | PCs<br>radar | Ann.<br>frames | 3D<br>boxes | Night /<br>Rain | Map<br>layers | Clas-<br>ses | Locations |
|-----------------|------|-------------|--------------|-------------|----------------------------|--------------|----------------|-------------|-----------------|---------------|--------------|-----------|
| CamVid [8]      | 2008 | 4           | 0.4          | 18k         | 0                          | 0            | 700            | 0           | No/No           | 0             | 32           | Cambridge |
| Cityscapes [19] | 2016 | n/a         | -            | 25k         | 0                          | 0            | 25k            | 0           | No/No           | 0             | 30           | 50 cities |

0

0

0

0

0

0

0

0

1.3M

0

0

0

0

0

25k

100k

144k

700k<sup>†</sup>

15k

20k

8.9k

27k

40k

 $22k^{\dagger}$ 

46k

200k‡

39k

12k

0

0

70k

0

200k

475k

0

1.1M

1.4M

993k†

1.3M

12M‡

230k

Yes/Yes

Yes/Yes

Yes/No

No/Yes

No/No

-/-

Yes/No

No/No

Yes/Yes

Yes/Yes

No/No

Yes/Yes

Yes/Yes

-/-

25k

100M

144k

700k<sup>†</sup>

15k

0

8.9k

83k

1.4M

490k<sup>†</sup>

323k

1M

39k

0

0

0\*\*

0

15k

20k

8.9k

27k

400k

44k


46k


200k

39k

#### SETUP

- Renault Zoe supermini electric cars
- Localization are created with detailed HD map of lidar points in an offline step and collected with Monte Carlo from lidar odometry
  - O Localization errors of < 10cm
- Maps are human-annotated
  - Original rasterized maps: two semantic: roads & sidewalk
  - Vectorized map expansion: Il semantic classes
- 23 categories
- Around 7 pedestrians and 20 vehicles per keyframe on average





Semantic segmentation label

car adult barrier trafficcone truck trailer push/pullable constr. veh. bus.rigid motorcycle bicycle worker debris bicycle racks child bus.bendy stroller animal police police car wheelchair p.mobility ambulance

Annotation categories

### **SOME MEASUREMENTS**

#### Metrics:

- Average Precision (AP)
- True Positive Metrics (TP metrics)
- Average Multi Object Tracking Accuracy (AMOTA)
- Average Multi Object Tracking Precision (AMOTP)
- o nuScences Detection Score (NDS)
- Tracking Initialization Duration (TID)
- Longest Gap Duration (LGD)
- Which sensor is more important
  - PointPillars vs MonoDIS:
    - mAP: 30.5% vs 30.4%
    - NDS: 45.3% vs 38.4%

#### Findings:

- Importance of pre-training
- Better detections gives better tracking

0