Symbols

A	Cross-sectional area of a pile, Equation (4-9) Cross-sectional area of shear wall boundary members or diaphragm chords in.^{2}, Equations (8-2), (8-4), (8-5)
A_b	Gross area of bolt or rivet, Equations (5-18), (5-22), (5-24) Sum of net mortared area of bed joints above and below the test unit, Equation (7-2)
Ac	Area of column, Equation (5-8)
A_e	Effective net area of the horizontal leg, Equation (5-20)
A_g	Gross area of the horizontal leg, Equation (5-19) Gross area of cast iron column, Equation (5-36) Gross area of column, in.^{2}, Equation (6-4)
A_j	Effective cross-sectional area of a beam-column joint, in.^{2}, in a plane parallel to plane of reinforcement generating shear in the joint calculated as specified in Section 6.5.2.3.1, Equation (6-5)
A_n	Area of net mortared/grouted section, Equations (7-1), (7-3), (7-5), (7-7), (7-9), (7-10), (7-11), (7-13)
A_{ni}	Area of net mortared/grouted section of masonry infill, Equation (7-15)
A_s	Area of nonprestressed tension reinforcement, in.^{2}, Tables 6-18, 6-20 Area of reinforcement, Equation (7-13)
$A's$	Area of compression reinforcement, in.^{2}, Tables 6-18, 6-20
A_w	Area of shear reinforcement, Equation (7-12) Nominal area of the web, Equation (5-7) Area of link stiffener web, Equation (5-28), (5-31) Area of the web cross section, = $b_w d$, Chapter 6
A_x	Accidental torsion amplification factor, Equation (3-1)
B	Width of footing, Equations (4-6), (4-7), (4-8)
B_1	Damping coefficient used to adjust one-second period spectral response for the effect of viscous damping, , Equations (1-10), (1-11)
B_{D1}	Numerical damping coefficient taken equal to the value of B_1, as set forth in Table 1-6, at effective damping β equal to the value of β_D, Equation (9-2)
B_{M1}	Numerical damping coefficient taken equal to the value of B_1, as set forth in Table 1-6, at effective damping β equal to the value of β_M, Equation (9-4)
B_S	Coefficient used to adjust short-period spectral response for the effect of viscous damping, Equations (1-8), (1-9), (1-11)
C (or C_j)	Damping coefficient for viscoelastic device (or device j), Equations (9-22), (9-24), (9-29), (9-30), (9-35), (9-37)
C_0	Modification factor to relate spectral displacement of an equivalent SDOF system to the roof displacement of the building MDOF system, Equation (3-15) Damping coefficient for fluid-viscous device, Equation (9-25)
C_1	Modification factor to relate expected maximum inelastic displacements to displacements calculated for linear elastic response, Equations (3-5), (3-6), (3-10), (3-15), (3-19)