

GE23131-Programming Using C-2024

Quiz navigation

1

2

3

Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Saturday, 30 November 2024, 7:37 PM
Duration	22 days 21 hours

Question 1

Correct

Marked out of 3.00

Flag question

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     int b;
6     scanf("%d%d",&a,&b);
7     if(a%10==b%10)
8         printf("true");
9     else
10        printf("false");
11    return 0;
12 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question 2

Correct

Marked out of 5.00

Flag question

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, **n**, perform the following conditional actions:

- If **n** is odd, print **Weird**
- If **n** is even and in the inclusive range of **2** to **5**, print **Not Weird**
- If **n** is even and in the inclusive range of **6** to **20**, print **Weird**
- If **n** is even and greater than **20**, print **Not Weird**

Complete the stub code provided in your editor to print whether or not **n** is weird.

Input Format

A single line containing a positive integer, *n*.

Constraints

$1 \leq n \leq 100$

Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

Sample Input 0

3

Sample Output 0

Weird

Sample Input 1

24

Sample Output 1

Not Weird

Explanation

Sample Case 0: *n* = 3

n is odd and odd numbers are weird, so we print **Weird**.

Sample Case 1: *n* = 24

n > 20 and *n* is even, so it isn't weird. Thus, we print **Not Weird**.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     scanf("%d",&a);
6     if(a%2!=0)
7         printf("Weird");
8     else if(a%2==0&&a>=2&&a<=5)
9         printf("Not Weird");
10    else if(a%2==0&&a>=6&&a<=20)
11        printf("Weird");
12    else if (a%2==0&&a>=20)
13        printf("Not Weird");
14    return 0;
15 }
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question 3

Correct

Marked out of
7.00

Flag question

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d%d%d",&a,&b,&c);
6     if(a*a+b*b==c*c)
7     {
8         printf("yes");
9     }
10    else if(a*a+c*c==b*b)
11    {
12        printf("yes");
13    }
14    else if(b*b+c*c==a*a)
15    {
16        printf("yes");
17    }
18    else
19    {
20        printf("no");
21    }
22    return 0;
23 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

Finish review