

GE23131-Programming Using C-2024

Quiz navigation



Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Saturday, 30 November 2024, 6:23 PM
Duration	22 days 23 hours

Question **1**

Correct

Marked out of 3.00

Flag question

Write a program that prints a simple chessboard.

Input format:

The first line contains the number of inputs T.
The lines after that contain a different values for size of the chessboard

Output format:

Print a chessboard of dimensions size * size. Print a Print W for white spaces and B for black spaces.

Input:

2
3
5

Output:

WBW
BWB
WBW
WBWBW
BWBWB
WBWBW
BWBWB
WBWBW

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int t,d,i=0,i1,i2,o;
5     char c;
6     scanf("%d",&t);
7     while(i<t)
8     {
9         scanf("%d",&d);
10        i1=0;
11        while(i1<d)
12        {
13            o=1;
14            i2=0;
15            if(i1%2==0)
16            {
17                o=0;
18            }
19            while(i2<d)
20            {
21                c='B';
22                if(i2%2==o)
23                {
24                    c='W';
25                }
26                printf("%c",c);
27                i2++;
28            }
29            i1+=1;
30            printf("\n");
31        }
32        i=i+1;
33    }
34 }
```

```

35 return 0;
36 }
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52

```

	Input	Expected	Got	
✓	2	WBW	WBW	✓
	3	BWB	BWB	
	5	WBW	WBW	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	

Passed all tests! ✓

Question 2

Correct

Marked out of 5.00

[Flag question](#)

Let's print a chessboard!

Write a program that takes input:

The first line contains T, the number of test cases

Each test case contains an integer N and also the starting character of the chessboard

Output Format

Print the chessboard as per the given examples

Sample Input / Output

Input:

```

2
2 W
3 B

```

Output:

```

WB
BW
BWB
WBW
BWB

```

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main()
3 {
4     int T,d,i,i1,i2,o,z;
5     char C,s;
6     scanf("%d",&T);
7     for(i=0;i<T;i++)
8     {
9         scanf("%d %c",&d,&s);
10        for(i1=0;i1<d;i1++)
11        {
12            z=(s=='W')?0:1;
13            o=(i1%2==z)?0:1;
14            printf("%c",o==0?'W':'B');
15        }
16        printf("\n");
17    }
18 }

```

```

14         tor(12=0;12<a;12++)
15         {
16             c=(12%2==0)?'W':'B';
17             printf("%c",c);
18         }
19         printf("\n");
20     }
21 }
22 return 0;
23 }
24
25
26
27
28
29
30

```

	Input	Expected	Got	
✓	2	WB	WB	✓
	2 W	BW	BW	
	3 B	BWB	BWB	
		WBW	WBW	
		BWB	BWB	

Passed all tests! ✓

Question 3

Correct

Marked out of
7.00

Flag question

Decode the logic and print the Pattern that corresponds to given input.

If N= 3

then pattern will be :

10203010011012

**4050809

****607

If N= 4, then pattern will be:

1020304017018019020

**50607014015016

****809012013

*****10011

Constraints

2 <= N <= 100

Input Format

First line contains T, the number of test cases

Each test case contains a single integer N

Output

First line print Case #i where i is the test case number

In the subsequent line, print the pattern

Test Case 1

3

3

4

5

Output

Case #1

10203010011012

**4050809

****607

Case #2

1020304017018019020

**50607014015016

****809012013

*****10011

Case #3

102030405026027028029030

**6070809022023024025

****10011012019020021

*****13014017018

*****15016

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,v,p3,c,in,i,i1,i2,t,ti;
5     scanf("%d",&t);
6     for(ti=0;ti<t;ti++)
7     {
8         v=0;
9         scanf("%d",&n);
10        printf("Case #%d\n",ti+1);
11        for(i=0;i<n;i++)
12        {
13            c=0;
14            if(i>0)
15            {
16                for(i1=0;i1<i;i1++) printf(" ");
17            }
18            for(i1=i;i1<n;i1++)
19            {
20                if(i>0)c++;
21                printf("%d0",++v);
22            }
23            if(i==0)
24            {
25                p3=v+(v*(v-1))+1;
26                in=p3;
27            }
28            in=in-c;
29            p3=in;
30            for(i2=i;i2<n;i2++)
31            {
32                printf("%d",p3++);
33                if(i2!=n-1) printf("0");
34            }
35            printf("\n");
36        }
37    }
38    return 0;
39 }
```

	Input	Expected	Got	
✓	3	Case #1	Case #1	✓
	3	10203010011012	10203010011012	
	4	**4050809	**4050809	
	5	****607	****607	
		Case #2	Case #2	
		1020304017018019020	1020304017018019020	
		**50607014015016	**50607014015016	
		****809012013	****809012013	
		*****10011	*****10011	
		Case #3	Case #3	
		102030405026027028029030	102030405026027028029030	
		**6070809022023024025	**6070809022023024025	

		****10011012019020021	****10011012019020021	
		*****13014017018	*****13014017018	
		*****15016	*****15016	

Passed all tests! ✓

Finish review