Name :- Vikas . R. Yadav

Roll No :- 15

10-01-2026 Server Virtualization

Q1. Explain why organizations choose VSphere over other hypervisors, list down at least three features.

⇒ Organizations choose VSphere because it is a stable and widely adopted enterprise virtualization platform that provides high availability, efficient resource management, and centralized administration

Key features:

i) High Availability (HA)

VSphere automatically restarts virtual machines on other hosts in a cluster when a physical host fails, ensuring minimal downtime.

ii) VMotion

VSphere allows live migration of virtual machines from one physical host to another without interrupting services.

iii) Distributed Resource Scheduler (DRS)

DRS automatically balances workloads across hosts by monitoring CPU and memory usage, improving performance and resource utilization

iv) Centralized Management Using VCenter Server

VSphere enables centralized management of multiple hosts and virtual machines from a single interface, simplifying administration and monitoring

These features make VSphere suitable for enterprise environments that require reliability, scalability, and efficient management of virtualized resources.

Q2. What is VCenter Single Sign-on (SSO), and why is it central to VCenter architecture?

⇒ VCenter Single Sign-on (SSO) is a core authentication service of VMware VCenter Server that provides centralized identity management for the VSphere environment.

Explanation In detailed below:..

i) Centralized Authentication Service

VCenter SSO is responsible for authenticating all users and services that access VCenter. Using users log in once, and the authentication is

Sundaram

FOR EDUCATIONAL USE

handled centrally.

ii) Single Login Mechanism

After successful authentication, SSO issues a security token. This token allows users to access multiple vCenter services without re-entering credentials.

iii) Integration with Identity Sources

SSO can be integrated with external identity sources such as Active Directory, LDAP, or local users, enabling enterprise-level user management.

iv) Foundation of vCenter Security

All vCenter components rely on SSO to establish trust. Without SSO, vCenter services cannot communicate securely with each other.

v) Supports Role-Based Access Control (RBAC)

SSO works together with vCenter roles and permissions to enforce that users can only access authorized resources.

v) Service-to-Service Authentication

vCenter SSO enables secure authentication between between internal vCenter services using trusted tokens instead of repeated credential verification.

vi) Scalability and Centralized Management

SSO allows consistent authentication and access policies across large and complex vSphere environments, making it suitable for enterprise deployments.

Thus, vCenter Single Sign-on is central to the vCenter architecture because it acts as the core identity, authentication, and trust mechanism for all vCenter services and users.

Q3. Describe the two-stage deployment process for vCenter Server Appliance (VCSA) 6.7, including prerequisites like DNS.

⇒ The deployment of vCenter Server Appliance (VCSA) 6.7 is performed in two clearly defined stages. This separation ensures that the appliance is

Sundaram
FOR EDUCATIONAL USE

Correctly deployed at the infrastructure level first and then configured at the application level.

i) DNS Configuration.
- A forward DNS record (A record) must exist for the VCSA hostname.
- Reverse DNS (PTR record) is recommended.
- Hostname must resolve correctly before starting deployment.

ii) ESXi Host or VCenter Target.
- An ESXi 6.0 or later host (or an existing vCenter) to deploy the appliance.
- Sufficient CPU, memory, and storage as per VCSA size (Tiny, Small, Medium, etc.).

iii) Network Requirements
- Static IP address for VCSA
- Subnet mask, gateway, and DNS server details
- Network connectivity between ESXi host and deployment machine.

iv) System Time
- Time synchronization between ESXi host and deployment system (NTP recommended).

Stage 1: Deployment of the VCSA Appliance (Infrastructure Setup)
This stage focuses on deploying the virtual appliance.
- The VCSA installer deploys the appliance as a virtual machine on the target ESXi host.
- Task performed in this stage:
  - Selection of deployment target (ESXi host or vCenter)
  - Appliance name and root password configuration
  - Selection of deployment size and storage size
  - Network configuration (IP address, hostnames, DNS)
- At the end of Stage 1:

- The VCSA Virtual machine is Created and powered on.
- Basic OS-level services are installed.
- No vCenter services are Configured yet.

Stage 2: Configuration of vCenter Services (Application Setup)
This Stage Configure vCenter Services Services inside the deployed appliance
- Tasks performed in this Stage:
  - Configuration of Single Sign-on (SSO) domain name
  - Setting SSO administrator password
  - Configuring of NTP Servers and time Synchronization
  - Enabling or disabling SSH access
  - Initial Configuration of vCenter Services
- Database Configuration:
  - Uses the embedded PostgreSQL database (default for VCSA 6.7).
- At the end of Stage 2:
  - All vCenter Services are Started
  - vCenter Server becomes fully Operational and accessible via Vsphere Client.

Why Two-Stage Deployment is Used
- Separates infrastructure deployment from Service Configuration.
- Allows Validation of network and DNS Settings before Configuring Services
- Reduces deployment failures Caused by incorrect prerequisites.
- Improves reliability and troubleshooting during installation.

The two-Stage deployment process of VCSA 6.7 ensures that the appliance is first Correctly deployed at the Virtualization layer (Stage 1) and then fully Configured with identity, time, and management Services (Stage 2). Proper DNS and network Configuration are critical prerequisites for a Successful deployment.

Sundaram
FOR EDUCATIONAL USE

Q4 Describe VSAN fundamentals and its role in hyper-converged infrastructure

⇒ VSAN (Virtual Storage Area Network) is a software-defined storage solution integrated with VMware VSphere that aggregates local storage from ESXi hosts and presents it as a single shared datastore for virtual machines.

VSAN Fundamentals

- Software-Defined Storage
  VSAN eliminates the need for external storage arrays by using local disks (SSD / HDD or NVMe) attached to ESXi hosts.
- Cluster-Based Architecture
  VSAN operates at the cluster level. A minimum of three hosts (or two hosts with a witness) is required to form a VSAN cluster.
- Disk Groups
  Each ESXi host contributes storage through disk groups:
  - One cache device (SSD or NVMe)
  - One or more capacity devices (SSD or HDD)
- Object-Based Storage
  Virtual machine components are stored as objects (VM home, VMDK, snapshots). These objects are managed independently by VSAN.
- Storage Policies (SPBM)
  Storage is controlled using policies such as:
  - Number of failures to tolerate (FTT)
  - Stripe width
  - Cache reservation

  Policies are applied per virtual machine, not per datastore.
- Data Services
  VSAN provides built-in services like:
  - Replication and mirroring
  - Deduplication and compression
  - Checksums and data integrity

Sundaram
FOR EDUCATIONAL USE

- Encryption (at-rest)

Role of VSAN in Hyper-Converged Infrastructure (HCI)

- Combines Compute and Storage
  VSAN integrates storage directly into the ESXi hosts, combining compute and storage into a single platform.
- Simplified Architecture
  HCI with VSAN removes the dependency on separate storage networks (SAN / NAS), reducing complexity.
- Scalability
  Storage and compute scale together by simply adding more ESXi hosts to the cluster.
- Centralized Management
  VSAN is managed directly from vCenter, using the same tools as compute and networking.
- High Availability and Resilience
  VSAN automatically handles disk, host, and network failures based on defined storage policies.
- Cost Efficiency
  Uses commodity hardware, reducing capital and operational costs compared to traditional storage systems.

VSAN transforms local storage into a shared, resilient datastore and plays a critical role in hyper-converged infrastructure by tightly integrating storage with compute and virtualization. This enables simpler management, better scalability, and improved availability in modern data centers.

Q5. Why is storage design critical in vSphere deployments?

⇒ Storage design is critical in vSphere deployments because it directly impacts performance, availability, scalability, and reliability of virtual machines and applications.

i) Performance of Virtual Machines

Storage design determines IOPS, latency, and throughput. Poorly designed storage can cause bottlenecks that slow down databases, applications, and operating systems running inside VMs

ii) Availability and Fault Tolerance

Proper storage design ensures data remains accessible during disk, host, or path failures. Features like multipathing, RAID levels, and storage policies rely on correct design to prevent downtime.

iii) Scalability and Feature Growth

A well-designed storage architecture allows easy expansion as workloads increase. Improper planning can lead to costly redesigns or migration issues later.

iv) Support for vSphere Features

Advanced vSphere features such as vMotion, High Availability (HA), and snapshots depend on shared and consistently accessible storage. Incorrect storage configuration can limit or break these features.

v.) Workload Isolation and Management

Storage design enables separation of workloads using datastores or policies, ensuring that high-I/O applications do not impact other virtual machines.

vi) Data Protection and Recovery

Backup, replication, and disaster recovery strategies rely on storage layout. A good design simplifies snapshot handling, backups, and restores.

vii) Operational Efficiency

Centralized and standardized storage design reduces administrative complexity and makes monitoring and troubleshooting easier.

In VMware vSphere environments, storage is the foundation for virtual machine operations. A well-planned storage design ensures optimal performance, high availability, scalability, and reliable support for enterprise workloads, making it a critical aspect of any vSphere deployment.

Sundaram
FOR EDUCATIONAL USE

Q6. Differentiate Local vs Shared Storage, and explain Common array architecture and RAID levels.

⇒ i) Local Storage vs. Shared Storage

Local Storage

- Storage devices (HDD / SSD / NVMe) are directly attached to a single ESXi host.
- Virtual machines can access storage only from the specific host.
- Does not support advanced features like vMotion or HA across hosts.
- Lower cost and simpler setup.
- Suitable for standalone hosts, labs, or non-critical workloads.

Shared Storage

- Storage is accessible by multiple ESXi hosts simultaneously.
- Enables advanced features such as vMotion, HA, and DRS in VMware vSphere.
- Requires SAN, NAS, or software-defined storage (e.g., vSAN).
- Higher availability and scalability.
- Commonly used in enterprise and production environments.

ii) Common Storage Array Architectures

Directed-Attached Storage (DAS)

- Storage directly connected to a server
- Simple and low latency.
- Limited scalability and sharing

Network-Attached Storage (NAS)

- Storage accessed over a network using file-level protocols (NFS, SMB)
- Easy to manage and deploy
- Suitable for file sharing and VM datastores.

Storage Area Network (SAN)

- Block-level storage accessed using Fibre Channel or iSCSI.
- High performance and reliability.
- Common in enterprise data centers.

Software-Defined Storage (SDS)

- Storage services delivered through software using local disks.
- Integrated with virtualization platforms.
- Enables scalability and policy-based management.

iii) RAID Levels (Redundant Array of Independent Disks)

RAID 0 (Striping)

- Data striped across disks.
- High performance
- No fault tolerance

RAID 1 (Mirroring)

- Data duplicated on two disks.
- High availability.
- 50% storage utilization

RAID 5 (Striping with Parity)

- Data and Parity distributed across disks.
- Tolerates one disk failure.
- Balanced performance and capacity.

RAID 6 (Double Parity)

- Similar to RAID 5 but tolerates two disks failures.
- High fault tolerance.
- Slightly lower write performance.

Sundaram
FOR EDUCATIONAL USE

RAID 10 (1+10)

- Combination of mirroring and striping.
- High performance and high availability.
- Requires more disks and higher cost.

Local storage offers simplicity and low cost but limited functionality, while shared storage enables advanced virtualization features and high availability. Storage array architecture and RAID selection are critical for achieving the desired balance between performance, fault tolerance, and scalability in virtualized environments.

Q7. Outline key vSphere security like RBAC, host lockdown, and VM encryption.

⇒ VMware vSphere provides multiple built-in security mechanisms to protect infrastructure, data, and access to resources.

i) Role Based Access Control (RBAC)

- RBAC controls who can access what within the vSphere environment
- Users are assigned roles that consist of predefined privileges.
- Roles are applied to objects such as:
  - Data centers
  - Clusters
  - Hosts
  - Virtual Machines
- Permission follow a hierarchical inheritance model, reducing administrative complexity.
- Integration with directory services allows centralized user management.

ii) ESXi Host Lockdown Mode

- Lockdown mode restricts direct access to ESXi hosts.
- Prevents unauthorized administrative access using local accounts.
- Forces host management through vCenter Server only.
- Supports different modes:

- Normal Lockdown Mode - limits access while allowing certain service accounts.
- Strict Lockdown Mode - blocks all direct access except via vCenter.

- Enhanced protection against insider threats and misconfigurations.

iii) Virtual Machine Encryption
- VM encryption protects data at rest and in use.
- Encrypts:
  - Virtual disks (VMDKs)
  - VM configuration files
  - Snapshots and swap files
- Uses encryption keys managed by an external key management (KMS)
- Ensures data confidentiality even if storage devices are compromised.

iv) Secure Boot and Trusted Platform Module (TPM)
- Secure Boot ensures that only trusted and signed code runs on ESXi hosts.
- TPM validates host integrity during boot.
- Protects against rootkits and firmware-level attacks.

v) Network Security Features.
- Virtual switch security policies control:
  a) Promiscuous mode b) MAC address changes. c) Forged transmits.
- micro-segmentation limits movement between virtual machines.

vSphere security features such as RBAC, host lockdown mode, and VM encryption work together to enforce strong access control, secure host management, and protect virtual machine data, making vSphere suitable for secure enterprise environments.

17/01/