

Laxmi Charitable Trust's
Sheth L.U.J College of Arts & Sir M.V. College of Science and Commerce
Department of Information Technology (B.Sc.I.T Semester V)
Artificial Intelligence Practical – V Task

Roll No :- T053	Name :- Nidhi Yadav
Class :- TYIT	Batch :- 02
Date of Assignment :- 29-07-2026	Date/Time of Submission :- 29-07-2026

Naïve Bayes' Classification.

A)Using a small dataset (e.g., weather or spam dataset), implement a Naive Bayes classifier using scikit-learn.

Code:-

PEAS Description for an Online Food Delivery Agent

```
PEAS = {  
    "Performance Measure": [  
        "Fast delivery",  
        "Correct order delivered",  
        "Customer satisfaction",  
        "Minimum delivery cost",  
        "Timely delivery"  
    ],  
    "Environment": [  
        "Customers",  
        "Restaurants",  
        "Roads",  
        "Traffic",  
        "Weather"  
    ],  
    "Actuators": [  
        "Assign delivery person",  
        "Send notifications",  
        "Update order status",  
        "Recommend route"  
    ],  
    "Sensors": [  
        "GPS",  
        "Customer order",  
        "Traffic data",  
        "Restaurant status",  
        "Payment confirmation"  
    ]  
}  
print("PEAS Description")  
for key, value in PEAS.items():  
    print(f"\n{key}:")  
    for item in value:  
        print("-", item)
```

```
print("\nEnvironment Classification")
print("Observable    : Partially Observable")
print("Agents        : Multi-Agent")
print("Deterministic   : Stochastic")
print("Episodic        : Sequential")
print("Dynamic          : Dynamic")
print("Discrete/Continuous : Continuous")
print("Nidhi Yadav")
```

Output:-

```
PEAS Description

Performance Measure:
- Fast delivery
- Correct order delivered
- Customer satisfaction
- Minimum delivery cost
- Timely delivery

Environment:
- Customers
- Restaurants
- Roads
- Traffic
- Weather

Actuators:
- Assign delivery person
- Send notifications
- Update order status
- Recommend route

Sensors:
- GPS
- Customer order
...
Episodic      : Sequential
Dynamic       : Dynamic
Discrete/Continuous : Continuous
Nidhi Yadav
```

Code:-

```
from collections import deque

maze = [
    ['S', '!', '!', '#'],
    ['#', '#', '!', '#'],
    ['.', '!', '!', '.'],
    ['#', '#', '!', 'G']
]
```

```

rows = len(maze)
cols = len(maze[0])
start = (0, 0)
goal = (3, 3)
queue = deque([(start, [start])])
visited = {start}
directions = [(1,0),(-1,0),(0,1),(0,-1)]
while queue:
    (x, y), path = queue.popleft()
    if (x, y) == goal:
        print("Shortest Path:")
        print(path)
        break
    for dx, dy in directions:
        nx, ny = x + dx, y + dy
        if 0 <= nx < rows and 0 <= ny < cols:
            if maze[nx][ny] != '#' and (nx, ny) not in visited:
                visited.add((nx, ny))
                queue.append(((nx, ny), path + [(nx, ny)]))
print("Nidhi Yadav")

```

Output:-

```

Shortest Path:
[(0, 0), (0, 1), (0, 2), (1, 2), (2, 2), (3, 2), (3, 3)]
Nidhi Yadav

```

Code:-

```

P_rain = 0.30
P_cloudy_given_rain = 0.80
P_cloudy = 0.50
P_rain_given_cloudy = (P_cloudy_given_rain * P_rain) / P_cloudy
print("Probability of Rain given Cloudy =", round(P_rain_given_cloudy, 2))
print("Nidhi Yadav")

```

Output:-

```

Probability of Rain given Cloudy = 0.48
Nidhi Yadav

```

Code:-

```

from collections import deque

```

```

def is_valid(state):
    m_left, c_left, boat = state
    m_right = 3 - m_left
    c_right = 3 - c_left
    if m_left < 0 or c_left < 0 or m_left > 3 or c_left > 3:
        return False
    if (m_left > 0 and m_left < c_left):
        return False
    if (m_right > 0 and m_right < c_right):
        return False
    return True

def bfs():
    start = (3, 3, 1)
    goal = (0, 0, 0)
    queue = deque([(start, [])])
    visited = set()
    moves = [(1,0),(2,0),(0,1),(0,2),(1,1)]
    while queue:
        state, path = queue.popleft()
        if state == goal:
            return path + [state]
        if state in visited:
            continue
        visited.add(state)
        m, c, boat = state
        for dm, dc in moves:
            if boat:
                new = (m-dm, c-dc, 0)
            else:
                new = (m+dm, c+dc, 1)

            if is_valid(new):
                queue.append((new, path+[state]))

```

```

solution = bfs()
print("Solution:")
for step in solution:
    print(step)
print("Nidhi Yadav")

```

Output:-

```

Solution:
(3, 3, 1)
(3, 1, 0)
(3, 2, 1)
(3, 0, 0)
(3, 1, 1)
(1, 1, 0)
(2, 2, 1)
(0, 2, 0)
(0, 3, 1)
(0, 1, 0)
(1, 1, 1)
(0, 0, 0)
Nidhi Yadav

```

Code:-

```
import heapq

graph = {
    'A': {'B':1,'C':4},
    'B': {'D':2,'E':5},
    'C': {'F':3},
    'D': {'G':5},
    'E': {'G':2},
    'F': {'G':2},
    'G': {}
}

heuristic = {
    'A':7,
    'B':6,
    'C':2,
    'D':4,
    'E':1,
    'F':1,
    'G':0
}


def astar(start, goal):
    pq = [(heuristic[start],0,start,[start])]
    visited = set()
    while pq:
        f,g,node,path = heapq.heappop(pq)
        if node == goal:
            return path,g
        if node in visited:
            continue
        visited.add(node)
        for neighbor,cost in graph[node].items():
            heapq.heappush(
                pq,
                (g+cost+heuristic[neighbor],
```

```

        g+cost,
        neighbor,
        path+[neighbor])
    )
def ucs(start, goal):
    pq = [(0,start,[start])]
    visited = set()
    while pq:
        cost,node,path = heapq.heappop(pq)
        if node == goal:
            return path,cost
        if node in visited:
            continue
        visited.add(node)
        for neighbor,c in graph[node].items():
            heapq.heappush(
                pq,
                (cost+c,
                 neighbor,
                 path+[neighbor])
            )
a_path,a_cost = astar('A','G')
u_path,u_cost = ucs('A','G')
print("A* Search")
print("Path:", a_path)
print("Cost:", a_cost)
print("\nUniform Cost Search")
print("Path:", u_path)
print("Cost:", u_cost)
print("Nidhi Yadav")

```

Output:-



```

A* Search
Path: ['A', 'B', 'D', 'G']
Cost: 8

Uniform Cost Search
Path: ['A', 'B', 'D', 'G']
Cost: 8
Nidhi Yadav

```