Status	Finished
Started	Thursday, 24 September 2026, 1:38 PM
Completed	Thursday, 24 September 2026, 1:44 PM
Duration	5 mins 31 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

The return statement in function is used to _____.

a. returns the control to the calling function
b. None of the mentioned
c. Both return value and returns the control to the calling function ✓
d. return value

Question **2**

Correct

Mark 1.00 out of 1.00

Write the output of : print(max([1, 2, 3, 4], [4, 5, 6], [7]))

a. [4, 5, 6]
b. [1, 2, 3, 4]
c. [7] ✓
d. 7

Question **3**

Correct

Mark 1.00 out of 1.00

cal(n1) : What is n1?

a. Argument ✓
b. Keyword
c. Parameter
d. None of the mentioned

Question **4**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def test(i,j):
    if(i==0):
        return j
    else:
        return test(i-1,i+j)
print(test(4,7))
```

- a. 17 ✓
- b. 13
- c. Infinite loop
- d. 7

Question **5**

Incorrect

Mark 0.00 out of 1.00

Python function always returns a value

Select one:

- True
- False ✗

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the following function call?

```
def outer_fun(a, b):
    def inner_fun(c, d):
        return c + d
        return inner_fun(a, b)
    return a
result = outer_fun(5, 10)
print(result)
```

- a. 5 ✓
- b. Syntax Error
- c. (15,5)
- d. 15

Question **7**

Correct

Mark 1.00 out of 1.00

Which of the following statement is not true regarding functions?

a. A function may or may not have parameters.
b. A function may or may not return value.
c. A function definition begins with "define" ✓
d. Function header always ends with a colon ( ) .

Question **8**

Correct

Mark 1.00 out of 1.00

____ can be defined as a named group of instructions that accomplish a specific task when it is invoked/called.

a. Function ✓
b. Operator
c. Datatype
d. Token

Question **9**

Correct

Mark 1.00 out of 1.00

Which keyword is used for defining a function?

a. def ✓
b. Fun
c. Function
d. Define

Question **10**

Correct

Mark 1.00 out of 1.00

What is the output of the add() function call?

```
def add(a, b):
    return a+5, b+5
result = add(3, 2)
print(result)
```

a. 8

b. 15

c. Syntax Error

d. (8,7) ✓

Question **11**

Correct

Mark 1.00 out of 1.00

Functions which do not return any value is called _____.

a. zero function

b. default function

c. void function ✓

d. null function

Question **12**

Correct

Mark 1.00 out of 1.00

Write the output of : print(min(tuple("computer")))

a. u

b. o

c. t

d. c ✓

Question **13**

Correct

Mark 1.00 out of 1.00

What is the output of the following display() function call?

```
def display(**kwargs):
  for i in kwargs:
    print(i)
display(emp="Kelly", salary=9000)
```

a. ('emp', 'Kelly')
('salary', 9000)

b. emp ✓
salary

c. TypeError

d. Kelly
9000

Question **14**

Correct

Mark 1.00 out of 1.00

Choose the incorrect statement.

a. print(pow(2, 3, 2))
b. None of the mentioned ✓
c. print(pow(2, 3))
d. print(pow(2.3, 3.2))

Question **15**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def maximum(x, y):
    if x > y:
        return x
    elif x == y:
        return 'The numbers are equal'
    else:
        return y
print(maximum(2, 3))
```

a. None of the mentioned

b. 3 ✓

c. The numbers are equal

d. 2

Status	Finished
Started	Thursday, 24 September 2026, 1:31 PM
Completed	Thursday, 24 September 2026, 1:36 PM
Duration	5 mins 16 secs
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 2.00 out of 2.00

Write a function that returns the value of a+aa+aaa+aaaa with a given digit as the value of a.

Suppose the following input is supplied to the program:

9

Then, the output should be:

9+99+999+9999=11106

Sample Input Format:

9

Sample Output format:

11106

For example:

Test	Result
`print(Summation(8))`	`9872`

Answer: (penalty regime: 0 %)

Reset answer

```
def Summation(a):
    return int(str(a)) + int(str(a) * 2) + int(str(a) * 3) + int(str(a) * 4)
```

	Test	Expected	Got	
✓	`print(Summation(8))`	`9872`	`9872`	✓
✓	`print(Summation(10))`	`10203040`	`10203040`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **2**

Correct

Mark 2.00 out of 2.00

complete function to implement coin change making problem i.e. finding the minimum

number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer: (penalty regime: 0 %)

Reset answer

```
def coinChange(n):
    dp = [0] + [float('inf')] * n
    for i in range(1, n + 1):
        dp[i] = min(dp[i - c] + 1 for c in [1, 2, 3, 4] if i - c >= 0)
    return dp[n]

```

	Test	Expected	Got	
✓	print(coinChange(16))	4	4	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **3**

Correct

Mark 2.00 out of 2.00

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all

the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

1 <= orderValue< 10e100000

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
print(christmasDiscount(578))	12

Answer: (penalty regime: 0 %)

Reset answer

```
def christmasDiscount(n):
    primes = {'2', '3', '5', '7'}
    return sum(int(d) for d in str(n) if d in primes)

```

	Test	Expected	Got	
✓	print(christmasDiscount(578))	12	12	✓
✓	print(christmasDiscount(57))	12	12	✓
✓	print(christmasDiscount(222))	6	6	✓
✓	print(christmasDiscount(77777))	35	35	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **4**

Correct

Mark 2.00 out of 2.00

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: U = 2^a * 3^b * 5^c, where a, b and c are nonnegative integers.

For example:

Test	Result
`print(checkUgly(6))`	`ugly`
`print(checkUgly(21))`	`not ugly`

Answer: (penalty regime: 0 %)

Reset answer

```
def checkUgly(n):
    if n <= 0:
        return "not ugly"
    for p in [2, 3, 5]:
        while n % p == 0:
            n //= p
    return "ugly" if n == 1 else "not ugly"
```

	Test	Expected	Got	
✓	`print(checkUgly(6))`	`ugly`	`ugly`	✓
✓	`print(checkUgly(21))`	`not ugly`	`not ugly`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **5**

Correct

Mark 2.00 out of 2.00

A strobogrammatic number is a number that looks the same when rotated 180 degrees (looked at upside down).

Write a program to determine if a number is strobogrammatic. The number is represented as a string.

Example 1:

Input:

69

Output:

true

Example 2:

Input:

88

Output:

true

Example 3:

Input:

962

Output:

false

Example 4:

Input:

1

Output:

true

For example:

Test	Result
`print(Strobogrammatic(69))`	`True`
`print(Strobogrammatic(962))`	`False`

Answer: (penalty regime: 0 %)

Reset answer

```
def Strobogrammatic(num):
    num = str(num)
    mapping = {'0': '0', '1': '1', '6': '9', '8': '8', '9': '6'}
    i, j = 0, len(num) - 1
    while i <= j:
        if num[i] not in mapping or mapping[num[i]] != num[j]:
            return False
        i += 1
        j -= 1
    return True
```

	Test	Expected	Got	
✓	`print(Strobogrammatic(69))`	`True`	`True`	✓
✓	`print(Strobogrammatic(88))`	`True`	`True`	✓
✓	`print(Strobogrammatic(962))`	`False`	`False`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.