Machine Learning Foundations: Geometry, Optimization, and Linear Classification

From vectors and planes to loss functions, feature vectors, and classifiers

Dr. Yael Demedetskaya

Point / Vector

$x=(3,2,2)$

Plane / Separator



$3x_1+x_2-1=0$

Loss / Optimization



$\theta \leftarrow \theta-\gamma\nabla L(\theta)$

Classifier

$h(x)\in\{-1,+1\}$

Geometry gives us representation

Optimization gives us learning

Classification gives us prediction

Foundations for early machine learning concepts and linear classification

Part I — Framing, Notation, and Roadmap

How the course’s mathematical language becomes machine learning language

vector — hyperplane — classifier

Dr. Yael Demedetskaya

Why These Foundations Come First

Linear Algebra / Geometry

Calculus / Optimization

Machine Learning

Probability / Uncertainty

Computation / NumPy

Core idea

Machine learning depends on representation, error measurement, optimization, uncertainty, and computation.

Representation, error, improvement, uncertainty, and computation all arrive before learning can happen.

What Each Prerequisite Contributes

Linear Algebra / Geometry



Geometry: represent and separate

$x \in R^d$

line / plane → classifier boundary

Calculus / Optimization



Optimization: improve parameters

$\nabla L(\theta)$

bowl surface → optimization

Probability / Uncertainty

Probability: model uncertainty

$X \sim N(\mu, \sigma^2)$

Gaussian curve → uncertainty

Computation / NumPy

```
[1, 0, 1]
[0, 1, 1]
```

Computation: make the math executable

Ax

array / vector → NumPy execution

Each prerequisite contributes a distinct part of the machine-learning toolkit.

The Big Story: From Data to Decisions

Machine learning turns real-world objects into numerical representations, places them in a geometric space, and learns rules that predict labels or values.

Raw Object

raw input

Feature Vector



$x \in R^d$

Point in Space

point / vector

Model / Boundary



$\theta \cdot x + \theta_0$

Prediction / Error



$h(x), L(\theta)$

Representation comes first: objects become vectors, vectors enter geometry, and geometry supports prediction.

Example A — From Movie to Feature Vector to Label

A real object becomes a machine-readable representation, then a prediction.

Movie

object / metadata

Encoding



5-feature binary vector

$x=[1,0,1,1,0]$

Representation

point in feature space

Model



score or boundary

$h(x)=\text{sign}(\theta \cdot x+\theta_0)$

Output



like / dislike

object • encoding • representation • prediction

A real object becomes a feature vector before it becomes a prediction.

Example B — From Digit Image to Class Label

Different objects can still enter the same machine-learning pipeline once represented numerically.

Digit

image input

Features



brightness / width

x=[brightness,width]

Representation

point in low-dimensional space

Classifier



class region / boundary

Output



class label

h(x)=7

image • features • point • class

Different data types still pass through the same representation-first pipeline.

Running Examples We Will Reuse

These examples will return throughout the deck as anchors.

Point / Vector

$x=(3,2,2)$

geometry anchor

Plane / Hyperplane



$3x_1+x_2-1=0$

boundary anchor

1D Optimization



$f(x)=\frac{1}{3}x^3-x^2-3x+10$

optimization anchor

Gradient



$f(\theta)=\theta_1^2+\theta_2^2$

descent anchor

Gaussian

$X\sim N(1,2)$

probability anchor

Movie Recommender

5-feature vector + label ±1

supervised-learning anchor

geometry, optimization, probability, computation, supervised learning

Notation You Must Read Fluently

In machine learning, the same letters are reused across different mathematical objects. Context matters.

symbol	meaning	visual example
$\mathbf{x}$	point / feature vector / example	$x=(3,2,2)$
$\mathbf{x_i}$	i-th coordinate	$x_2=2$
$\boldsymbol{\theta}$	parameter vector / normal vector	$\theta\cdot x+\theta_0=0$
$\boldsymbol{\theta_0}$	offset / intercept	boundary shift
$\mathbf{A}$	matrix	A x
$\mathbf{y}$	label	$y\in\{-1,+1\}$
$\mathbf{h}$	classifier / prediction rule	$h(x)=\mathrm{sign}(\theta\cdot x+\theta_0)$
$\mathbf{L}$	loss	$L(\theta)$

$x\in R^d$ • $\theta\in R^d$ • $A\in R^{m\times n}$ • $y\in\{-1,+1\}$

Point, Vector, Feature Vector: Same Shape, Different Role

Point

location in coordinate space

$x=(3,2,2)$

Vector

arrow from the origin

$x \in R^3$

Feature Vector

encoded example for prediction

$x \mapsto$ feature vector

location in space • displacement from origin • encoded example for prediction

$x=(3,2,2)$ • $x \in R^3$ • $x \mapsto$ feature vector

One Object, Three Interpretations

The coordinates did not change. The interpretation changed.

x=(3,2,2)

Point

same coordinates, location in space

same coordinates

Vector

same coordinates, displacement from origin

different role

Feature Vector

same shape, encoded movie example

context changes meaning

x=(3,2,2) • movie → x

The shape of the mathematical object stays the same; only the interpretation changes.