# How to Install JSindo for LINUX

Kiyoshi Yagi kiyoshi.yagi@riken.jp

Theoretical Molecular Science Laboratory RIKEN Pioneering Research Cluster

2018/06/04

# 1. Install Java

Let's check if you have Java installed or not, and the version of Java if you have. In the terminal, type "java -version" and you will see a message like this:

```
>java -version
openjdk version "1.8.0_121"
OpenJDK Runtime Environment (build 1.8.0_121-b13)
OpenJDK 64-Bit Server VM (build 25.121-b13, mixed mode)
```

If your Java is 1.8.xxx (=JDK8), then you can skip the installation and go to Chap. 2.

If your Java is a newer one, 1.9.xxx (=JDK9) and later, it is unfortunately NOT compatible with Java3D library, which JSindo use for visualization. You may either uninstall or switch to JDK8 keeping the current ones. Ask google for details.

To install JDK8, type in the terminal,

```
> yum install java-1.8.0-openjdk (Fedora)
> apt-get install openjdk-8-jre (Debian, Ubuntu)
```

See the OpenJDK website for further details.




http://openjdk.java.net/


Alternately, you may use Oracle Java 1.8.x. It is available from here.

Search "Java SE download" in Google and goto the following website.

http://www.oracle.com/technetwork/java/javase/downloads/index.html




accept



i586 and x64 is 32- and 64-bit, respectively. I think you will normally choose 64-bit.

# 2. Download Java3D

JSindo uses Java3D for visualization. A stable version, 1.6.0, is available from JogAmp. Goto http://jogamp.org



click here and download jogamp-all-platforms.7z

#### Main Page

Welcome to the JogAmp & wiki. It documents JOGL, JOCL and JOAL, the cross-platform bindings to the OpenGL, OpenCL, and OpenAL APIs.

### click here

#### Getting Started Community

- Downloading and installing
   Versioning and Releases
- Setting up a JogAmp project in your favorite IDE
- Source Cod Repositories
- Tracking Reports

- Contribute to JogAmp
- Build JogAmp
- Maintainer and Contacts
- Report a bug
- JogAmp IRC

### Downloading and installing JOGL

Before you can build a project that uses JOGL in your IDE or on the command line &, you'll need to download and install the JOGL JAR files and native JARs or native library files (.dll/.so /.inilib files).

You have a choice of JOGL versions to download. The latest stable version  $\underline{\mathscr{C}}$  is the safest, but lags behind in features. The latest automatic build  $\underline{\mathscr{C}}$  contains all checked-in code, but may be failing some tests.

#### Contents [hide]


- 1 Downloading the latest stable version
  - 1.1 Using the 7z jogamp-all-platforms archive
- 2 Downloading the latest aggregated autobuild
- 3 Downloading the latest automatic build
  - 3.1 Native JARs vs. native library files
- 3.2 Unzipping the files
- 4 Maven
- 5 More information

#### Downloading the latest stable version

Go to this page & and download the all-in-one 7z archive file:

jogamp-all-platforms.7z

### Go back to the Main page and scroll down



Unarchive the two files you've just downloaded. 7z files can be unarchived by,

```
> 7za x jogamp-all-platforms.7z
> 7za x jogamp-java3d.7z
```

If you don't have the command, install p7zip package,

```
> yum install p7zip

(Fedora)

> apt-get install p7zip

(Debian and Ubuntu)
```

You will find jar files in jogamp-all-platforms/jar and in jogamp-java3d. The following jar files are needed for JSindo:

```
jogamp-all-platforms/jar/
    gluegen-rt.jar
    gluegen.jar
    gluegen-rt-natives-linux-XXX.jar
    jogl-all.jar
    jogl-all-natives-linux-XXX.jar
```

```
jogamp-java3d/
j3dcore.jar
j3dutils.jar
vecmath.jar
```

where XXX = amd64 or i586 for 64 or 32-bit, respectively. You can check if your Java is 32- or 64-bit. In the terminal, type "java -version" and you will see a message like this:

```
>java -version
openjdk version "1.8.0_121"
OpenJDK Runtime Environment (build 1.8.0_121-b13)
OpenJDK 64-Bit Server VM (build 25.121-b13, mixed mode)
```

This is an example of 64-bit. If "64-Bit" is absent, then it's 32-bit.

(\* XXX = armv6 and armv6hf are for ARM cpus, which are used for phones.)

# 3. Download JAMA

JAMA is a linear algebra library for JAVA. We use it for matrix multiplications, diagonalization, and so on. It can be downloaded from,

https://math.nist.gov/javanumerics/jama/

### JAMA: A Java Matrix Package

[Background] ..... [The Package] ..... [Request for Comments] ..... [Authors] ..... [Related Links & Libraries]

#### **Background**

JAMA is a basic linear algebra package for Java. It provides user-level classes for constructing and manipulating real, dense matrices. It is meant to provide sufficient functionality for routine problems, packaged in a way that is natural and understandable to non-experts. It is intended to serve as *the* standard matrix class for Java, and will be proposed as such to the <u>Java Grande Forum</u> and then to <u>Sun</u>. A straightforward public-domain reference implementation has been developed by the <u>MathWorks</u> and <u>NIST</u> as a strawman for such a class. We are releasing this version in order to obtain public comment. There is no guarantee that future versions of JAMA will be compatible with this one.

### : Scroll down

### The Package

Version 1.0.3 (November 9, 2012)

- Documentation
- Example
- Source [ Jama-1.0.3.zip ] [ Jama-1.0.3.tar.gz ]
- ChangeLog

click here and download a jarfile.

# 4. Download and test JSindo

Download JSindo-4.x.jar and sample.tar.gz (or sample.zip) from our website: http://www.riken.jp/TMS2012/tms/en/research/software/sindo/index.html

Now, create a new folder (\${HOME}/JSindo/jar in the example below), and copy all jar files in there,

```
> jsindo_jar=${HOME}/JSindo/jar
> mkdir -p $jarfiles

> cp /path/to/jogamp-all-platforms/jar/gluegen.jar $jsindo_jar
> cp /path/to/jogamp-all-platforms/jar/gluegen-rt.jar $jsindo_jar
> cp /path/to/jogamp-all-platforms/jar/jogl-all.jar $jsindo_jar
> cp /path/to/jogamp-all-platforms/jar/gluegen-rt-natives-linux-xxx.jar $jsindo_jar
> cp /path/to/jogamp-all-platforms/jar/jogl-all-natives-linux-xxx.jar $jsindo_jar
> cp /path/to/jogamp-java3d/j3dutils.jar $jsindo_jar
> cp /path/to/jogamp-java3d/j3dcore.jar $jsindo_jar
> cp /path/to/jogamp-java3d/vecmath.jar $jsindo_jar
> cp /path/to/Jama-1.0.3.jar $jsindo_jar
> cp /path/to/Jama-1.0.3.jar $jsindo_jar
```

where xxx = amd64 or i586 for 64-bit or 32-bit, respectively.

Then, type the following command to invoke JSindo:

```
>java -cp "$jsindo_jar/*" JSindo
```


With this command, you should see a control panel of JSindo. If you don't see the panel, you might try to reinstall or update Java. See FAQ for some tips.

Let's open "sample/h2co.minfo", which is included in sample.tar.gz. You can extract the file by,

```
>tar -zxvf sample.tar.gz
```

In JSindo control panel, click File -> Open, choose "h2co.minfo", and click Open. If you see formaldehyde, you're done with the first step!

If this step fails, it is highly likely that JogAmp/Java3D has a problem. Double check if the right jarfiles (xxx = amd64 or i586) are located in the folder.




Finally, goto Tools -> Harmonic Analysis. This should create a panel of "Normal modes".


If you don't see this panel, JAMA isn't working. Check if the jarfile of JAMA is located in the folder.

If the panel appears, you're all set! Congratulations!

Check on "show vibrational coordinates", and choose a mode you want to see. Vibrational motion will be indicated by arrows. You can "Invert the arrows" by a check box, and change the magnitude using a slider.

Thanks for using JSindo! Enjoy!





# FAQ

1. I can not get JSindo start up with the following error:

Could not find or load main class JSindo

You probably don't have JSindo-4.0.jar in the right folder. Review the jar folder.

2. I can not get JSindo start up with the following error:

```
Exception in thread "main" java.awt.HeadlessException at java.awt.GraphicsEnvironment.checkHeadless(GraphicsEnvironment.java:204) ...
```

Some distrubutions have a headless version of Java by default. Try the following command to install a standard Java:

```
> yum install java-1.8.0-openjdk (Fedora)
> apt-get install openjdk-8-jre (Debian, Ubuntu)
```

### 3. How do I make the start up command shorter?

I recommend to create an alias. Edit your ~/.bashrc and add the following two lines,

```
> vi ~/.bashrc
jsindo_jar=${HOME}/JSindo/jar
alias jsindo='java -cp "$jsindo_jar/*" JSindo'
```

After source, you can invoke the program by typing "jsindo" in the command.

```
> . .basrc
> jsindo
```

Alternately, you may want to set CLASSPATH,

```
> export CLASSPATH=${HOME}/JSindo/jar/*
> java JSindo
```

Note, however, that the use of CLASSPATH is discouraged, because it can easily mess things up (the library version, for example).

4. I get JSindo start up, but cannot open minfo file with the following error:

```
Exception in thread "AWT-EventQueue-0" java.lang.NoClassDefFoundError:
javax/media/j3d/Bounds
```

You probably don't have JogAmp/Java3D jarfiles in the jar folder. Review the jar folder.

### 5. I get JSindo start up, but cannot open minfo file with the following error:

```
Exception in thread "AWT-EventQueue-0" java.lang.InternalError: XXX0
profile[1]: GL3bc -> profileImpl GL4bc !!! not mapped
...
```

This error happened to me when I didn't have the right driver installed for my GPU card (Quadro K600). It was solved after installing a nVidia driver. The following website was useful for me to install a driver in my Fedora Core,

https://www.if-not-true-then-false.com/2015/fedora-nvidia-guide