How to Install MakePES

Kiyoshi Yagi
kiyoshi.yagi@chem.tsukuba.ac.jp

Department of Chemistry
Institute of Pure and Applied Sciences
University of Tsukuba

2026/11/11

NOTE

- MakePES is a command line based program. This manual assumes that you are familiar with the commands in UNIX, and that you are working on Bourne Shell (bash).

- “/path/to/sindo” indicates the absolute path of your installation directory. For example,

```
/path/to/sindo -> /home/yagi/pgm/sindo-4.0_220312
```

1. Install Java JDK in your system. For details, see “How to Install JSindo”.

2. Download sindo-4.0_xxxx.zip from our website
   https://tms.riken.jp/en/research/software/sindo

3. Unzip (double click) the file, and find “sindovars.sh” in the top directory,

```
> cd sindo-4.0_xxxx
> ls
FSindo/   JSindo/   LICENSE   README.md   script/   sindovars.sh
```

Edit “sindovars.sh” and set “/path/to/sindo” to the name of install directory.

```
#!/bin/bash

export sindo_dir=/path/to/sindo
export CLASSPATH=${CLASSPATH}:$sindo_dir/JSindo/jar/JSindo-4.0_fat.jar
export PATH=$PATH:$sindo_dir/script:$sindo_dir/FSindo/bin
export SINDO_RSH=ssh
```

4. Open a terminal, source “sindovars.sh”, and then invoke RunMakePES:

```
. /path/to/sindo/sindovars.sh
java RunMakePES -h
```

MakePES is successfully installed if you get the following message,

```
USAGE: java RunMakePES [ -f xmlfile ] [--input-version 1|2]
```

It is useful to source “sindovars.sh” in your ~/.bashrc,

4. Configuration for Gaussian

Note: You can skip this step if you don’t plan to use Gaussian, or if you run Gaussian by yourself.

Proceed to “script”, execute a configure script, and follow the instruction,

```
> cd sindo-4.0_xxxx/script
> ./configure
```

You will be asked to enter a directory where Gaussian is installed, the version of Gaussian, and a local scratch directory. The script creates runGaussian.sh in the same directory.

Note that “sindovars.sh” sets a path to this directory:

```
export PATH=$PATH:$sindo_dir/script:$sindo_dir/FSindo/bin
```