

 > Python > Docker Compose with Flask Apps

Docker Compose with Flask Apps

Docker Compose simplifies multi-container Docker environments on a single host. Let's put together a basic web app with Docker Compose and Flask using Redis (we end up with a Python/Flask container and a Redis container all on one host). We do not need custom networking or to design our own networks to run on; Compose does everything for us!

Set Up Your Host

Install Docker Engine and Docker Compose (unless you have them already); review [Introduction to Docker Compose](#) if you need help.

1. You'll need a directory for your project on your host machine:

```
$ mkdir compose_flask  
$ cd compose_flask
```

2. Add the following to `requirements.txt` in your directory:

```
flask  
redis
```

3. Copy and paste the following code into a new file called `app.py` in your project directory:

```
# compose_flask/app.py
from flask import Flask
from redis import Redis

app = Flask(__name__)
redis = Redis(host='redis', port=6379)

@app.route('/')
def hello():
    redis.incr('hits')
    return 'This Compose/Flask demo has been viewed %s time(s).' % redis.get('hits')

if __name__ == "__main__":
    app.run(host="0.0.0.0", debug=True)
```

Your Docker Image

1. Create your `Dockerfile` in the `compose_flask` directory and add the following:

```
FROM python:2.7
ADD . /code
WORKDIR /code
RUN pip install -r requirements.txt
CMD python app.py
```

2. Build it: `docker build -t compose-flask .`

Define Your Services

Add the following code to a new file, `docker-compose.yml`, in your project directory:

```
version: '2'
services:
  web:
    build: .
    ports:
      - "5000:5000"
    volumes:
      - ./code
```

```
    depends_on:
      - redis
  redis:
    image: redis
```

How to Read the Docker Compose File

- We define two services, `web` and `redis`.
- The `web` service builds from the `Dockerfile` in the current directory...
- Forwards the container's exposed port (5000) to port 5000 on the host...
- Mounts the project directory on the host to `/code` inside the container (allowing you to modify the code without having to rebuild the image)...
- And links the web service to the Redis service.
- The `redis` service uses the latest Redis image from Docker Hub.

Note this composition documents your application's requirements!

Build and Run with Docker Compose

Start the application from your directory:

```
$ docker-compose up
```

If you have localhost access to your host (i.e., you do not use a remote solution to deploy Docker), point your browser to `http://0.0.0.0:5000`, `http://127.0.0.1:5000`, or `http://localhost:5000`. On a Mac, you need to use `docker-machine ip MACHINE_VM` to get your Docker host's IP address (then use that address like `http://MACHINE_IP:5000` to access your web page). If you *do* use a remote host, simply use that IP address and append `:5000` to the end.

You should see:

This Compose/Flask demo has been viewed 1 time(s).

When you refresh, you should see:

```
This Compose/Flask demo has been viewed 2 time(s).
```

Each time you refresh, the number should increment.

Stop the application with `CTRL+C` (read below under “Common Issues” for more information) and refresh the page. You should receive something to the effect of `This site can't be reached`.

Restart the application with `docker-compose up -d`. Redis resets the count and you should see:

```
This Compose/Flask demo has been viewed 1 time(s).
```

Use `docker-compose ps` and you should get similar results:

Name	Command	State	Ports
composeflask_redis_1	docker-entrypoint.sh redis ...	Up	6379/tcp
composeflask_web_1	/bin/sh -c python app.py	Up	0.0.0.0:5000->5000/tcp

Run `docker-compose stop` to stop the containers:

```
$ docker-compose stop
Stopping composeflask_web_1 ... done
Stopping composeflask_redis_1 ... done
```

Common Issues

Starting and Stopping

If you run `docker-compose up -d`, you need to run `docker-compose stop` to stop the services when you finish. If you *did not*, you can stop the service with `CTRL+C` (hit once to gracefully stop and twice to force kill the containers). If you do not run in the background, you can view the calls made to your container.

By Runnable: The service that speeds up development by providing full-stack environments for every code branch.

[Visit Runnable >](#)



[About](#)

[Privacy Policy](#)