



Following \vee

733 Followers

Creating EFS File System And Mount Targets Using Terraform



In this post, we'll see how we can create EFS File System and Mount Targets using Terraform.

Note: We'll run our setup in the us-east-1 region. Terraform and AWS credentials must be configured before proceeding with the execution.

Step 1: Create the following terraform files:

efs.tf

```
resource "aws_efs_file_system" "efs" {
    creation_token = "efs"
    performance_mode = "generalPurpose"
    throughput_mode = "bursting"
    encrypted = "true"

tags = {
        Name = "EFS"
    }
}

resource "aws_efs_mount_target" "efs-mt" {
    count = length(data.aws_availability_zones.available.names)
    file_system_id = aws_efs_file_system.efs.id
    subnet_id = aws_subnet.subnet[count.index].id
    security_groups = [aws_security_group.efs.id]
}
```

network.tf

```
data "aws availability zones" "available" {}
resource "aws vpc" "vpc" {
  cidr block = "10.0.0.0/16"
  enable dns hostnames = true
  enable dns support = true
  tags= {
    Name = "test-env"
}
resource "aws internet gateway" "internet gateway" {
 vpc id = aws vpc.vpc.id
 tags = {
  Name = "Internet Gateway"
}
resource "aws subnet" "subnet" {
  count=length(data.aws availability zones.available.names)
  cidr block = cidrsubnet(aws vpc.vpc.cidr block, 8, count.index)
  vpc id = aws vpc.vpc.id
  availability zone =
data.aws availability zones.available.names[count.index]
}
resource "aws route table" "public" {
 vpc id = aws vpc.vpc.id
 route {
   cidr block = "0.0.0.0/0"
   gateway id = aws internet gateway.internet gateway.id
 tags = {
   Name = "Public Route Table"
 depends on = [aws internet gateway.internet gateway]
resource "aws_route_table_association" "vpc public assoc" {
length(data.aws availability zones.available.names)
 subnet id = aws subnet.subnet.*.id[count.index]
 route table id = aws route table.public.id
}
```

security.tf

```
protocol = "tcp"
  }
 egress {
                  = 0
   from port
  to_port
protocol
                  = 0
                  = "-1"
   cidr blocks
                  = ["0.0.0.0/0"]
 }
 tags = {
   Name = "allow efs"
}
resource "aws security group" "efs" {
  name = "efs-sq"
  description= "Allos inbound efs traffic from ec2"
  vpc id = aws vpc.vpc.id
  ingress {
    security_groups = [aws_security group.ec2.id]
    from port = 2049
    to port = 2049
    protocol = "tcp"
  egress {
    security groups = [aws security group.ec2.id]
    from port = 0
    to port = 0
    protocol = "-1"
  }
 }
```

ec2.tf

```
resource "aws_instance" "testinstance" {
   ami = "ami-087c17d1fe0178315"
   instance_type = "t2.micro"
   subnet_id = aws_subnet.subnet[0].id
   associate_public_ip_address= true
   vpc_security_group_ids = [ aws_security_group.ec2.id ]
   key_name="efs"
   tags= {
      Name = "testinstance"
   }
}
```

This will create a new VPC and launch our EFS and EC2 resources there. You need to change key_name in ec2.tf and it should already be created.

Step 2: Now we have all our terraform resources and it's time to run following Terraform commands

```
terraform init
terraform plan
terraform apply --auto-approve
```

Step 3: Once all the resources are created successfully, you'll see our EFS file system and EC2 instance.



Step 4: Now SSH in to the instance and execute following commands to mount our EFS files:

```
ssh -I <key> ec2-user@<instance_ip>
sudo su -
mkdir /efs
mount -t nfs4 -o
nfsvers=4.1,rsize=1048576,wsize=1048576,hard,timeo=600,retrans=2,nore
svport fs-ed989e59.efs.us-east-1.amazonaws.com:/ /efs
df -h
touch /efs/a
ls /efs
```

As you can see, our EFS file system was successfully mounted and is ready to use. We can also add following entry in /etc/fstab to allow auto mount after reboot.

```
<file_system_id>.us-east-1.amazonaws.com:/ /efs nfs4 defaults,_netdev 0 0
```

Sign up for Best of Towards AWS Monthly

By Towards AWS

A curated list of AWS articles at the end of month. Take a look.



Emails will be sent to yegnasivasai@gmail.com. Not you?

AWS



About Write Help Legal

Get the Medium app



