

Work locally with Git: Open your working directory in Postman to keep your API artifacts in sync with your codebase.

GET Get data GET Get data GET http://localhost:8989/a + No environment

http://localhost:8989/api/products

GET http://localhost:8989/api/products Send

Docs Params Authorization Headers 7 Body Scripts Settings Cookies

Body Cookies Headers 5 Test Results 200 OK · 1.15 s · 416 B

```
{
  "name": "Laptop",
  "description": "Dell XPS 13",
  "price": 1200.0,
  "quantity": 10,
  "id": 1
}, {
  "name": "Smartphone",
  "description": "Samsung Galaxy S21",
  "price": 999.0,
  "quantity": 20,
  "id": 2
}, {
  "name": "Tablet",
  "description": "Apple iPad Pro",
  "price": 799.0,
  "quantity": 15,
  "id": 3
}
```

http://localhost:8989/api/products/1

GET http://localhost:8989/api/products/1

Docs Params Authorization Headers 7 Body Scripts Settings

Body Cookies Headers 5 Test Results

```
{
  "name": "Laptop",
  "description": "Dell XPS 13",
  "price": 1200.0,
  "quantity": 10,
  "id": 1
}
```

http://localhost:8989/api/products/2

GET http://localhost:8989/api/products/2

Docs Params Authorization Headers 7 Body Scripts Settings

Body Cookies Headers 5 Test Results

```
{
  "name": "Smartphone",
  "description": "Samsung Galaxy S21",
  "price": 999.0,
  "quantity": 20,
  "id": 2
}
```

http://localhost:8989/api/products/3

GET http://localhost:8989/api/products/3

Docs Params Authorization Headers 7 Body Scripts Settings

Body Cookies Headers 5 Test Results

```
{
  "name": "Tablet",
  "description": "Apple iPad Pro",
  "price": 799.0,
  "quantity": 15,
  "id": 3
}
```

HTTP client interface showing a POST request to `http://localhost:8989/api/products`. The request body is a JSON object: `{ "name": "Smartphone", "description": "Samsung Galaxy S21", "price": 999.0, "quantity": 20 }`. The response is a 200 OK status with a response time of 292 ms and a body size of 255 B. The response body is a JSON object: `{ "name": "Smartphone", "description": "Samsung Galaxy S21", "price": 999.0, "quantity": 20, "id": 4 }`.

HTTP client interface showing a PUT request to `http://localhost:8989/api/products/1`. The request body is a JSON object: `{ "name": "Laptop", "description": "Dell XPS 13 - Updated", "price": 1100.0, "quantity": 8 }`. The response is a 200 OK status with a response time of 78 ms and a body size of 254 B. The response body is a JSON object: `{ "name": "Laptop", "description": "Dell XPS 13 - Updated", "price": 1100.0, "quantity": 8, "id": 1 }`.

SQL File 4* interface showing SQL commands and the resulting data grid.

```
1 • CREATE DATABASE kluh;  
2 • USE kluh;  
3 • select * from products  
4 • insert INTO products (name, description, price, quantity)
```

Result Grid:

	id	description	name	price	quantity
▶	1	Dell XPS 13 - Updated	Laptop	1100	8
	2	Samsung Galaxy S21	Smartphone	999	20
	3	Apple iPad Pro	Tablet	799	15
	4	Samsung Galaxy S21	Smartphone	999	20
•	NULL	NULL	NULL	NULL	NULL

SQL File 4*

```
1 • CREATE DATABASE k1uh;  
2 • USE k1uh;  
3 • select * from products  
4 ✖ insert INTO products (name, description, price, quantity) VALUES ('Laptop', 'Dell
```

Result Grid

	id	description	name	price	quantity
▶	1	Dell XPS 13 - Updated	Laptop	1100	8
	2	Samsung Galaxy S21	Smartphone	999	20
	3	Apple iPad Pro	Tablet	799	15
*	NULL	NULL	NULL	NULL	NULL

Result Grid
Form Editor

http://localhost:8989/api/products/4

DELETE http://localhost:8989/api/products/4 Send

Docs Params Authorization Headers 9 Body Scripts Settings Cookies

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON Schema Beautify

1

Body Cookies Headers 3 Test Results 204 No Content • 55 ms • 104 B

Raw Preview Visualize

1