Marklume Model Flow

Which AI model Marklume asks, in what order, for each preset with Gemini off and on. Read each row left to right: the first model is asked first, and the next one only if it fails (offline, out of quota, refused, or keeps erroring). Ollama, in amber, is the model on your Mac.

Reading jobs

Copy what is on the page: page layout, a second reading of unclear handwriting, equations, syllabus import. TrOCR on your Mac reads all handwriting first; a model is asked only for what TrOCR is unsure of.

Judgement jobs

Decide what counts: reading the question paper, diagrams, the AI answer key, matching your own key, and marking.

Backup marker

Only with Gemini on. When every Gemini marking model is out of quota, it marks whole scripts instead, and every mark is flagged for your review.

Gemini off the default on a new install

This computer Preset: Ollama on your Mac. Nothing to connect.

READING JOBS	**Ollama** Qwen3-VL 8B
JUDGEMENT JOBS	**Ollama** Qwen3-VL 8B
BACKUP MARKER	*none*

Ollama does everything. There is nothing after it: if the Ollama app is closed, every AI step fails.

Gemini on needs a Gemini key

This computer Preset: Ollama on your Mac. Nothing to connect.

READING JOBS	**Gemini 3.5 Flash** reading model	→ if it fails	**Gemini 3.5 Flash-Lite** reading model	→ if it fails	**Ollama** Qwen3-VL 8B	
JUDGEMENT JOBS	**Gemini 3.6 Flash** marking model	→ if it fails	**Gemini 3.7 Flash** marking model			
BACKUP MARKER	**Ollama** Qwen3-VL 8B					

Ollama is the last reader and the backup marker. It reads when both Gemini reading models fail, and marks whole scripts when Gemini's marking quota runs out.

GPU server

Preset: your Kaggle notebook running vLLM, reached through the Cloudflare tunnel.

READING JOBS	Kaggle GPU Qwen3-VL 8B	if it fails →	Ollama Qwen3-VL 8B
JUDGEMENT JOBS	Kaggle GPU Qwen3-VL 8B	if it fails →	Ollama Qwen3-VL 8B
BACKUP MARKER	*none*		

Ollama is the fallback for every job. It is asked only when Kaggle cannot be reached or keeps failing, which is why the pop-up at 74% named Ollama.

READING JOBS	Gemini 3.5 Flash reading model	if it fails →	Gemini 3.5 Flash-Lite reading model	if it fails →	Kaggle GPU Qwen3-VL 8B
JUDGEMENT JOBS	Gemini 3.6 Flash marking model	if it fails →	Gemini 3.7 Flash marking model		
BACKUP MARKER	Kaggle GPU Qwen3-VL 8B	if it fails →	Ollama Qwen3-VL 8B		

Ollama only backs up the backup marker. It marks only if Gemini is out of quota and Kaggle is also down. It is never used for reading here.

Hugging Face

Preset: Hugging Face's hosted models, paid for with your free monthly credits.

READING JOBS	Hugging Face Qwen3-VL 30B-A3B	if it fails →	Ollama Qwen3-VL 8B
JUDGEMENT JOBS	Hugging Face Qwen3-VL 30B-A3B	if it fails →	Ollama Qwen3-VL 8B
BACKUP MARKER	*none*		

Ollama is the fallback for every job. It is asked when Hugging Face is unreachable or out of credits.

READING JOBS	Gemini 3.5 Flash reading model	if it fails →	Gemini 3.5 Flash-Lite reading model	if it fails →	Hugging Face Qwen3-VL 30B-A3B
JUDGEMENT JOBS	Gemini 3.6 Flash marking model	if it fails →	Gemini 3.7 Flash marking model		
BACKUP MARKER	Hugging Face Qwen3-VL 30B-A3B	if it fails →	Ollama Qwen3-VL 8B		

Ollama only backs up the backup marker. It marks only if Gemini is out of quota and Hugging Face also fails. It is never used for reading here.

One marker per script

The first model that answers a marking request marks that whole script. If it fails halfway, the script stops or waits; it does not switch to the next model mid-script.

Gemini off means nothing goes to Google

Even with a key saved. With Gemini on but no key, marking fails instead of falling to the open model.

Ollama must be open to help

Ollama is only a fallback if the Ollama app is running with qwen3-vl:8b-instruct pulled. If it is not, the error you see names Ollama, even when the real problem was Kaggle or Hugging Face.

From Marklume's source, 1 October 2026 (app_config.dart: openChain, chainForTask, backupMarkingModels). Model names are the defaults, except the GPU server, which shows the 8B model you run on Kaggle.