

Gateway Specifications Response Form (TesPro TG-424 Pro)

Item	Descriptions	Specifications	TesPro TG-424 Pro
1	CPU	Dual Core 1 Ghz	ARM Cortex-A53 Dual Core , 1.6Ghz
2	RAM	2GB DDR3	DDR4 2GB
3	Memory (eMMC)	min 32GB free for custom applicaton	32GB eMMC
4	GPS receiver		4G Modem built-in GNSS
5	4G LTE modem		4G CAT1 or 4G CAT4, Optional
6	Ethernet	min 2, better 4 (isolated)	1*WAN 1~3 *LAN (isolated), 10/100/1000 Mbps
7	USB	> 2x	USB-A *1 or USB-C * 1, Optional
8	Serial ports	2x RS-485 (isolated)	RS485 *2 , Industrial Terminal Connector (A/B/GND)
9	TPM 2.0		Onboard TPM 2.0 Security Coprocessor
10	Power Supply	12Vdc	12–36V DC Wide-range Input, Reverse Polarity Protection
11	Can run C++ software or not		OS: OpenWRT, OpenWrt supports execution of C/C++ applications natively.
12	Protocol		Multi-protocol support: Modbus RTU (RS485), Modbus TCP, OPC UA, DLMS, IEC 61850