Tree Power Notes

author[*]   author[*]

February 26, 2020

ABSTRACT.

Key words:

Introduction

Literature review:

1 Assumptions

1. We assume all trees we consider are roughly the same. That means same height, same radius

2. With the previous assumption, we place all devices at the same height, and same depth

2 To do (Feb 7)

Our goal is to write Python scripts that would simulate the temperature distribution in the trunk of the tree and the ambient environment. We will use the heat model for both. See the following reference for more detail:

1. Within a tree stem: see [3]
   heat

2. Ambient temperature: see [5] and [6]
   airtempforestgreen

3 PDE model of temperature within a tree stem

3.1 Parameters to collect and verify. Nick

Notations:

1. T: temperature (K)

2. ρ: density (kg/m^3)

---

[*]University of Washington, WA

3. c: specific heat (J/(kgK))

4. t: time (s)

5. k: thermal conductivity (W/(mK))

6. r: distance from center of the tree (m)

7. ϕ: azimuth angle, measured clockwise with south being $\phi = 0$ (radian/degree), [3] assumes $\partial k / \partial \phi = 0$

8. α: albedo of the surface

3.2 The heat equation in cylindircal coordinates

The basic heat equation for temperature distribution is

$$\rho c \frac{\partial T}{\partial t} = \nabla \cdot (k \nabla T) = \frac{1}{r} \frac{\partial}{\partial r} \left(kr \frac{\partial T}{\partial r} \right) + \frac{1}{r} \frac{\partial}{\partial \phi} \left(\frac{k}{r} \frac{\partial T}{\partial \phi} \right) \tag{1}$$

We add source terms for the diffusion equation to obtain

$$\rho c \frac{\partial T}{\partial t} = \nabla \cdot (k \nabla T) - \frac{1}{\Delta r} [H + (1 - \alpha)(S_{dir} + S_{dif}) + (IR_{in} - IR_{out})] \tag{2}$$

In the following, we explain the source terms:

1. Free convective heat loss/gain happens when the tree surface temp is different from the ambient temp. Forced convection happens when there is wind. We denote the heat loss/gain by H, and

$$H = h(T_{sfc} - T_{air}), \tag{3}$$

with h (W/(m^2K)) being the convective heat transfer coefficient. Here

$$h = h_{free} - h_{forced}, \tag{4}$$

more details in 3.

2. $S_{dir} + S_{dif}$ represents direct solar radiation, plus diffusion solar radiation.

3. $IR_{in} - IR_{out}$ represents wave radiation from and to the tree. More details see [3].

Our goal now is to solve this 2D differential equation with FD scheme.
https://pycav.readthedocs.io/en/latest/api/pde/crank_nicolson.html

3.3 FD scheme for the heat equation

A detailed discussion about polar heat equation is in [7]. However, the equation presented there was axi-symmetric, and our equation depends on the azimuth angle ϕ. Our goal is to modify the equation, therefore method presented. pg.251, section 3.5.6

3.4 Implementation in Python and numerical results

ReferenceBAD FORMAT. FOR convience only

1. Yan. D. et al, Time-Dependent Finite-Volume Model of Thermoelectric Devices, IEEE, Transactions on industry applications, Vol. 50, No.1, Jan/Feb 2014

2. MIT notes online

3. Potter, A., Andresen, J., A finite-difference model of temperatures and heat flow within a tree stem, Can. J. For. Res. **32**, 548-555 (2002)

4. Bownman, W. et al, Sapwood temperature gradients between lower stems and the crown do not influence estimate of stand-level stem CO_2 efflux, Tree Physiology, 28, 1553-1559

5. Chen, J., et al, An empirical model for predictin diurnal air-temperature gradients from edge into old-growth Douglas-fir forest, Ecological Modeling, Vol. 67, Issues 2-4, pg 179-198, June 1993

6. Tanja, S. et al., Air temperature triggers the recovery of evergreen boreal forest photosynthesis in spring, Global Change Biology, vol 9, issue 10, pg 1410-1426, Oct 2003

7. Linge S., Langtangen H.P. (2017) Diffusion Equations. In: Finite Difference Computing with PDEs. Texts in Computational Science and Engineering, vol 16. Springer, Cham

ectric

mit

heat

sapwood

forest

ergreen

017book