Table of Contents

1	**Introduction**	**1039**
1.1	System overview	1040
1.2	PIN configuration of connector	1046
1.3	Standard analog inputs	1061
1.4	Definition of logic inputs	1063
2	**AIRM-Air motion**	**1064**
2.1	AIRM Configuration data	1065
2.2	Port flap variables	1066
2.3	Port flap position set point actuation signal processing	1073
2.4	Port flap adaptation	1087
2.5	Port flap actuator diagnosis	1093
2.6	Port flap power stage diagnosis	1127
2.7	Port flap power stage diagnosis (Appl. Inc.)	1130
3	**AIRT-Air temperature**	**1132**
3.1	AIRT General	1133
3.2	AIRT Configuration data	1136
3.3	AGGR adaptation: AIRT	1143
3.4	Acquisition of air temperatures	1147
3.5	Acquisition of air temperatures (Appl. Inc.)	1150
3.6	Air temperature sensor model (Appl. Inc.)	1154
3.7	Air temperature sensor model	1156
3.8	Ambient air temperature calculation (Appl. Inc.)	1172
3.9	Ambient air temperature calculation	1177
3.10	Intake gas temperature calculation	1198
3.11	Intake gas temperature model at intake manifold	1204
3.12	Intake gas temperature model at intake valve	1215

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

3.13	Intake gas temperature model at throttle	1223
3.14	Intake gas temperature model at intercooler	1228
3.15	Intake gas temperature model for exhaust gas recirculation	1230
3.16	Intercooler air temperature control	1233
3.17	Signal diagnosis of temperatures delivered by INTC	1234
3.18	Air temperature sensor diagnosis (Appl. Inc.)	1241
3.19	Air temperature sensor diagnosis	1245
3.20	Air temperature sensor diagnosis (ERRM interface)	1252
3.21	Air temperature sensor plausibility diagnosis (Appl. Inc.)	1257
3.22	Air temperature sensor plausibility diagnosis	1260
3.23	Air temperature sensor plausibility diagnosis (ERRM interface)	1270
3.24	Intake gas temperature sensor plausibility diagnosis (Appl. Inc.)	1272
3.25	Intake gas temperature sensor plausibility diagnosis	1275
3.26	Intake gas temperature sensor plausibility diagnosis (ERRM interface)	1287
4	**ALFU-Alternative fuel**	**1289**
4.1	ALFU General	1290
4.2	ALFU Configuration data	1292
4.3	Ethanol sensor acquisition	1294
4.4	Engine roughness signal preparation for fuel quality adaptation	1304
4.5	Injection time correction for alternative fuel	1316
4.6	Engine running adaptation (AFU)	1318
4.7	Engine running adaptation (AFU) (Appl. Inc.)	1347
4.8	Lambda based flex fuel ratio detection	1350
4.9	Lambda based flex fuel ratio detection (Appl. Inc.)	1366
4.10	Fuel tank level based flex fuel ratio detection	1369
4.11	Fuel tank level based flex fuel ratio detection (Appl. Inc.)	1389
4.12	Engine roughness based flex fuel ratio detection	1395
4.13	Alternative fuel ratio determination	1396
4.14	Alternative fuel ratio determination (Appl. Inc.)	1405
4.15	Default start strategy	1424

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

4.16	Engine roughness based fuel quality adaptation	1446
4.17	Ethanol sensor diagnosis	1463
4.18	Ethanol sensor plausibility diagnosis	1466
4.19	ALFU - Controller (gen)	1472
4.20	ALFU - Controller (prj)	1478
5	**ARSD-Acquisition and Reporting of Statistical Data**	**1479**
5.1	Cyclic redundancy check calculation algorithm	1480
5.2	ARSD Configuration data for Customer Statistics	1482
5.3	Data recorder	1485
5.4	Customer statistical data	1505
5.5	Customer statistical data (Appl. Inc.)	1531
5.6	Standard data for OBD radar	1541
6	**BRSY-Braking system**	**1553**
6.1	BRSY Configuration data	1554
6.2	BRSY General	1556
6.3	Brake servo unit pressure	1560
6.4	Brake servo unit pressure (Appl. Inc.)	1587
6.5	Vehicle stand still detection	1595
6.6	Brake servo unit output	1605
6.7	Brake servo unit pump control	1611
6.8	Brake servo unit pressure sensor diagnosis	1619
6.9	Brake servo unit pressure sensor diagnosis (Appl. Inc.)	1640
6.10	Brake servo unit pump diagnosis	1643
6.11	Brake servo unit pump diagnosis (Appl. Inc.)	1655
7	**CBMD-Combustion modes**	**1656**
7.1	CBMD General	1657
7.2	CBMD Configuration data	1660
7.3	Combustion mode switch	1682

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

7.4	Combustion mode inhibition (Appl. Inc.)	1687
7.5	Combustion mode inhibition	1715
7.6	Combustion state manager	1721
7.7	Combustion state manager (Appl. Inc.)	1730
7.8	Combustion mode priorisation	1745
7.9	Combustion mode request	1762
7.10	Combustion mode transition factors	1771
7.11	Combustion mode inhibition by minimum injection time (Appl. Inc.)	1775
7.12	Combustion mode inhibition by minimum injection time	1783
7.13	Combustion mode inhibition for scavenging	1803
7.14	Combustion mode summary	1813
7.15	Combustion mode request summary	1820
7.16	Combustion mode switch by diagnosis tool	1822
7.17	Combustion mode switch by diagnosis tool (error management interface)	1828
7.18	Combustion mode management (gen)	1830
8	**CEVC-Crankcase evaporation control**	**1834**
8.1	CEVC Configuration data	1835
8.2	AGGR adaptation: CEVC	1837
8.3	Oil dilution model	1839
8.4	Evaporation risk management	1877
8.5	Fuel evaporation model in crankcase	1902
8.6	Limitation of fuel correction from crankcase evaporation	1924
8.7	Evaporation risk management (ERRM interface)	1933
9	**CHRA-Charger actuators**	**1938**
9.1	CHRA Configuration data	1939
9.2	CHRA General	1942
9.3	Acquisition of pressure at pneumatic waste gate actuator	1946
9.4	Waste gate actuator pressure	1947
9.5	Recirculation actuator position	1953

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

9.6	Recirculation actuator position (Appl. Inc.)	1956
9.7	Recirculation actuator position control	1958
9.8	Turbocharger turbine actuator coordination	1960
9.9	Recirculation actuator diagnosis	1968
9.10	Recirculation actuator diagnosis (Appl. Inc.)	1999
9.11	Waste gate electrical diagnosis	2001
9.12	Waste gate electrical diagnosis (Appl. Inc.)	2034
9.13	CHRA adaptation and diagnosis	2037
9.14	CHRA fault operation manager	2119
9.15	CHRA fault operation manager (Appl. Inc.)	2123
9.16	CHRA power stage diagnosis	2125
9.17	CHRA sensor diagnosis	2152
9.18	CHRA actuator diagnosis	2161
9.19	CHRA actuator diagnosis (Appl. Inc.)	2232
9.20	CHRA adaptation and diagnosis (Appl. Inc.)	2239
9.21	CHRA sensor diagnosis (Appl. Inc.)	2242
9.22	Boost pressure actuator diagnosis EOL	2243
9.23	CHRA diagnosis (gen)	2248
9.24	CHRA position control and setpoint (gen)	2253
9.25	Boost pressure actuator operating manager	2267
9.26	CHRA position controller	2297
9.27	Boost pressure actuator safety limitation	2313
9.28	CHRA safety limitation (Appl. Inc.)	2338
9.29	CHRA sensor acquisition	2340
9.30	CHRA anti sticking	2347
9.31	CHRA cleaning	2352
9.32	Actuator temperature model	2356
10	**CHRG-Charger**	**2378**
10.1	CHRG Configuration data	2379
10.2	Charge air temperature	2388

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

10.3	Recirculation mass air flow determination	2400
10.4	Exhaust gas temperature for turbocharger	2403
10.5	Turbocharger compressor environment	2405
10.6	Basic boost pressure adaptation (Appl. Inc.)	2411
10.7	Basic boost pressure	2413
10.8	Basic boost pressure adaptation	2418
10.9	Turbocharger compressor model	2423
10.10	Detection of compressor surge	2432
10.11	Boost pressure limits	2436
10.12	CHRG dummy outputs	2442
10.13	Pressure upstream throttle setpoint	2450
10.14	Pressure upstream throttle setpoint (Appl. Inc.)	2461
10.15	Turbocharger compressor environment setpoints	2468
10.16	Turbocharger protection	2472
10.17	Turbocharger protection (Appl. Inc.)	2477
10.18	Recirculation actuator setpoint determination	2479
10.19	Recirculation actuator setpoint determination (Appl. Inc.)	2497
10.20	Boost pressure control	2499
10.21	Boost pressure control (Appl. Inc.)	2509
10.22	Turbocharger turbine control adaptation	2517
10.23	Waste gate flow setpoint	2524
10.24	Turbocharger turbine control	2527
10.25	Turbocharger turbine control (Appl. Inc.)	2541
10.26	Inverse turbocharger turbine model	2553
10.27	Torque based charge air temperature limitation	2562
10.28	Torque based turbocharger speed limitation	2574
10.29	Turbocharger minimum time control	2586
10.30	Boost pressure display (Appl. Inc.)	2601
10.31	Boost pressure display	2605
10.32	Turbocharger diagnosis	2611
10.33	Turbocharger control plausibility diagnosis	2632

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

10.34	Turbocharger control plausibility diagnosis (ERRM interface)	2645
10.35	Turbocharger overpressure diagnosis (Appl. Incs.)	2650
10.36	Turbocharger overpressure diagnosis (ERRM interface)	2655
10.37	Turbocharger plausibility diagnosis	2658
10.38	Turbocharger plausibility diagnosis (ERRM interface)	2684
10.39	Turbocharger plausibility diagnosis (Appl. Inc)	2687
10.40	Turbocharger control plausibility diagnosis (Appl. Inc.)	2691
10.41	Recirculation actuator plausibility diagnosis	2701
10.42	Recirculation actuator plausibility diagnosis (ERRM interface)	2719
10.43	Recirculation actuator plausibility diagnosis (Appl. Inc.)	2723
10.44	Turbocharger and pressure sensor EOL diagnosis	2729
10.45	Turbocharger overpressure diagnosis	2733
10.46	Turbocharger and pressure sensor EOL	2736
10.47	Turbocharger and pressure sensor EOL (Appl. Inc.)	2772
11	**CUSF-Customer Supplied Functions**	**2776**
11.1	System variables for customer specified functions	2777
11.2	Interface definitions of customer provided functionality	2789
11.3	Dynamic requirements of customer provided functionality	2920
11.4	Customer reference list	2946
11.5	Customer adaptation module: PWSL	2950
11.6	Customer adaptation module: IGSP	2953
11.7	Customer adaptation module: LACO	2955
11.8	Customer adaptation module: AIRT	2964
11.9	Customer adaptation module: DRRQ	2972
11.10	Customer adaptation module: EGCP	2975
11.11	Customer adaptation module: ENOS	2986
11.12	Customer adaptation module: ENSD	2991
11.13	Customer adaptation module: EVAC	3009
11.14	Customer adaptation module: INSY	3011
11.15	Customer adaptation module: KNCK	3022

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

11.16	Customer adaptation module: THRO	3030
11.17	Customer adaptation module: VVLI	3034
11.18	Customer adaptation module: VVTI	3036
11.19	Customer adaptation module: ENSC	3040
11.20	Customer adaptation module: INJR	3048
11.21	Customer adaptation module: ENSS	3061
11.22	Customer adaptation module: TRSM	3071
11.23	Customer adaptation module: ENSL	3090
11.24	Customer adaptation module: MISF	3095
11.25	Customer adaptation module: FUSL	3097
11.26	Customer adaptation module: FMSP	3106
11.27	Customer adaptation module: CBMD	3112
11.28	Customer adaptation module: CHRG	3117
11.29	Customer adaptation module: IGRE	3129
11.30	Customer adaptation module: EXTD	3131
11.31	Customer adaptation module: EGRC	3138
11.32	Customer adaptation module: HVAC	3141
11.33	Customer adaptation module: EXTC	3143
11.34	Customer adaptation module: LASP	3147
11.35	Customer adaptation module: ENLU	3149
11.36	Customer adaptation module: BRSY	3155
11.37	Customer adaptation module: RASL	3161
11.38	Customer adaptation module: VHSC	3186
11.39	Customer adaptation module: SYCF	3223
11.40	Customer adaptation module: NOXD	3236
11.41	Customer adaptation module: ECM2	3243
11.42	Customer adaptation module: INTC	3249
11.43	Customer adaptation module: FARM	3286
11.44	Customer adaptation module: CYTP	3288
11.45	Customer adaptation module: ERMA	3294
11.46	Customer adaptation module: FUSP	3296

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

11.47	Customer adaptation module: INJP	3298
11.48	Customer adaptation module: VHSL	3300
11.49	Customer adaptation module: VHMD	3304
11.50	Customer adaptation module: ECOP	3308
11.51	Customer adaptation module: ESVS	3312
11.52	Customer adaptation module: DRVB	3318
11.53	Customer adaptation module: TQDR	3320
11.54	Customer adaptation module: TQLO	3324
11.55	Customer adaptation module: TQSP	3326
11.56	Customer adaptation module: ENTE	3336
11.57	Customer adaptation module: ERRM	3362
11.58	Customer adaptation module: EGPR	3363
11.59	Customer adaptation module: GEOL	3369
11.60	Customer adaptation module: VHST	3375
11.61	Customer adaptation module: EGRA	3378
11.62	Customer adaptation module: ALFU	3383
11.63	Customer adaptation module: PTQM	3385
11.64	Customer adaptation module: SCRM	3398
11.65	Customer adaptation module: DRPD	3399
11.66	Customer adaptation module: CHRA	3407
11.67	Customer diagnostics interface	3418
11.68	Customer diagnostics interface (Appl. Inc.)	3430
11.69	CUSF Configuration data	3435
11.70	Customer adaptation module: NETM	3530
11.71	Customer adaptation module: PTOS	3532
11.72	Dynamic requirements of customer provided functionality (Appl. Inc.)	3537
11.73	Customer adaptation module: EGPA	3552
11.74	Brake servo unit pressure (CPF#115)	3557
11.75	Customer adaptation module: CLCC	3575
11.76	Customer adaptation module: EMDA	3578
11.77	Customer adaptation module: EMSP	3580

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

11.78	Customer adaptation module: DGNC	3583
11.79	Customer adaptation module: CUSF	3589
11.80	Customer adaptation module: SECM	3653
12	**CYBL-Cylinder balancing**	**3656**
12.1	CYBL Configuration data	3657
12.2	Coordination of the injection time correction factors for CYBL	3659
12.3	Cylinder balancing via engine roughness	3669
12.4	Cylinder balancing via engine roughness (Appl. Inc.)	3673
12.5	Cylinder balancing via additive mass fuel flow intervention	3682
12.6	Cylinder balancing manager	3711
12.7	Cylinder balancing manager (Appl. Inc.)	3733
12.8	Cylinder balancing system Interface	3741
12.9	Cylinder balancing signal preparation	3785
12.10	Cylinder balancing signal preparation (Appl. Inc.)	3796
12.11	Cylinder balancing adaptation	3804
12.12	Cylinder balancing controller initialization	3822
12.13	Cylinder balancing controller	3851
12.14	Cylinder balancing limited dynamics	3866
12.15	CYBL scheduler	3882
12.16	Cylinder balancing coordination at EOL	3889
12.17	Cylinder balancing coordination at DC	3900
12.18	Cylinder balancing diagnostics	3916
12.19	Cylinder balancing diagnostics (Appl. Inc.)	3937
12.20	Cylinder balancing misfire diagnostics	3943
13	**DGNC-Diagnostic communication**	**3961**
13.1	DGNC General	3962
13.2	MVB - Measured value blocks general	3966
13.3	MVB - Special blocks	4059
13.4	Application of ECU data via diagnosis tool	4080

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

13.5	UDS - Service interpreter (Appl.Inc.)	4082
13.6	UDS - SID 10h: diagnosticSessionControl Service	4093
13.7	UDS - SID 10h: diagnosticSessionControl Service (Appl. Inc.)	4096
13.8	UDS - SID 11h : ECUReset Service	4101
13.9	UDS - SID 11h : ECUReset Service (Appl. Inc.)	4103
13.10	UDS - SID 19h: readDTCInformation Service	4104
13.11	UDS - SID 19h: readDTCInformation Service (Appl. Inc.)	4107
13.12	UDS - SID 22h: readDataByIdentifier Service	4122
13.13	UDS - SID 22h: readDataByIdentifier Service (Appl. Inc.)	4125
13.14	UDS - SID 23h: readMemoryByAddress Service	4234
13.15	UDS - SID 23h: readMemoryByAddress Service (Appl. Inc.)	4239
13.16	UDS - SID 27h: securityAccess Service	4240
13.17	UDS - SID 27h: securityAccess Service (Appl. Inc.)	4247
13.18	UDS - SID 28h: communicationControl Service	4251
13.19	UDS - SID 28h: communicationControl Service (Appl. Inc.)	4253
13.20	UDS - SID 2Eh: writeDataByIdentifier Service	4257
13.21	UDS - SID 2Eh: writeDataByIdentifier Service (Appl. Inc.)	4259
13.22	UDS - SID 2Fh: inputOutputControlByIdentifier Service	4298
13.23	UDS - SID 2Fh: inputOutputControlByIdentifier Service (Appl. Inc.)	4302
13.24	UDS - SID 31h: routineControl Service	4306
13.25	UDS - SID 31h: routineControl Service (Appl. Inc.)	4309
13.26	UDS - SID 34h: requestDownload Service	4412
13.27	UDS - SID 36h: transferData Service	4418
13.28	UDS - SID 37h: requestTransferExit Service	4424
13.29	UDS - SID 3Eh: testerPresent Service	4427
13.30	UDS - SID 85h: controlDTCSetting Service	4429
13.31	UDS - SID 85h: controlDTCSetting Service (Appl. Inc.)	4431
13.32	UDS - SID 87h: LinkControl Service	4435
13.33	Annex	4438
13.34	UDS - Service interpreter (Only Boot SW)	4440

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

14	DRPD-Driver request pedals determination	4443
14.1	DRPD Configuration data	4444
14.2	AGGR adaptation: DRPD	4448
14.3	Pedal value sensor variables	4450
14.4	Pedal value sensor variables (Appl. Inc.)	4490
14.5	Kick down recognition / adaptation	4503
14.6	Brake switch variables	4530
14.7	Brake switch variables (Appl. Inc.)	4564
14.8	Driving mode selection via switch	4567
14.9	Kick down switch diagnosis	4616
14.10	Pedal value sensor diagnosis	4619
14.11	Brake switch diagnosis	4716
14.12	Driving mode selection via switch diagnosis	4773
14.13	Pedal value determination (gen)	4779
14.14	Pedal value sensor OBDI (gen)	4789
14.15	Brake switch OBDI (gen)	4801
15	DRRQ-Driver request	4802
15.1	AGGR adaptation: DRRQ	4803
15.2	Adaptive drive dynamics	4805
15.3	Pedal value interpretation	4825
15.4	Limp home for pedal value interpretation	4848
16	DRVB-Driveability	4859
16.1	DRVB Configuration data	4860
16.2	AGGR adaptation: DRVB	4861
16.3	Anti jerk parameters	4862
16.4	Anti jerk activation conditions	4877
16.5	Anti jerk controller	4884
16.6	Anti jerk (gen)	4891

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

17	ECM2-ECU Process Monitoring	4892
17.1	ECM2 General	4893
17.2	Process monitoring	4899
17.3	Debounce mechanism	4914
17.4	Configuration of process monitoring (Appl. Inc.)	4922
17.5	Monitoring of A/D conversion	4938
17.6	Monitoring of coolant temperature	4946
17.7	Monitoring of idle speed controller (Appl. Inc.)	4950
17.8	Monitoring of idle speed controller	4972
17.9	Monitoring of torque losses (Appl. Inc.)	4977
17.10	Monitoring of torque losses	4991
17.11	Monitoring of minimum torque at clutch (Appl. Inc.)	4998
17.12	Monitoring of minimum torque at clutch	5009
17.13	Monitoring of maximum torque at clutch (Appl. Inc.)	5021
17.14	Monitoring of maximum torque at clutch	5023
17.15	Monitoring of engine speed	5026
17.16	Monitoring of pedal value signal (Appl. Inc.)	5032
17.17	Monitoring of pedal value signal	5063
17.18	Monitoring of mass fuel flow signal	5120
17.19	Required mass fuel flow	5127
17.20	Monitoring of cruise control conditions	5132
17.21	Desired indicated engine torque (Appl. Inc.)	5159
17.22	Desired indicated engine torque	5184
17.23	Actual fuel mass flow	5192
17.24	Actual indicated engine torque (Appl. Inc.)	5220
17.25	Actual indicated engine torque	5228
17.26	Monitoring of actual indicated engine torque	5235
17.27	Monitoring of engine speed limitation	5240
17.28	Processor monitoring by copy of process monitoring	5245
17.29	Fault reaction of process monitoring	5283
17.30	Error memory management of process monitoring	5300

17.31	Error memory management of process monitoring (Appl. Inc.)	5312
17.32	Monitoring of stop/start	5323
17.33	Monitoring of safety relevant ECU outputs	5387
17.34	Communication monitoring of cruise control unit	5404
17.35	Communication monitoring of electronic ignition lock unit	5448
17.36	Communication monitoring of traction control unit	5467
17.37	Communication monitoring of transmission unit	5597
17.38	Communication monitoring	5645
17.39	Monitoring of vehicle stability control	5662
18	**ECM3-ECU Processor Monitoring**	**5670**
18.1	ECM3 Configuration data (prj)	5671
18.2	ECM3 General	5687
18.3	ECM3 Configuration data	5692
18.4	Processor monitoring	5699
18.5	Fault reaction of processor monitoring	5708
18.6	Communication MC - MU	5716
18.7	Switch off path check	5720
18.8	Program flow monitoring	5725
18.9	Function specific instruction set test	5732
18.10	Error memory management of processor monitoring	5737
18.11	Processor Monitoring (Appl. Inc.)	5743
18.12	Memory monitoring	5756
18.13	ADC synchronization MC - MU	5768
19	**ECME-ECU Memory**	**5770**
19.1	Non volatile data management general	5771
19.2	Non volatile data management configuration	5779
19.3	Non volatile data management implementation	5798
19.4	EEPROM diagnosis	5804
19.5	EEPROM diagnosis (Appl. Inc.)	5806

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

19.6 Customer adaptation module: ECME 5807

20 ECOP-ECU Operation 5811

20.1 ECU states detection 5812
20.2 ECU warm reset detection (Appl. Inc.) 5825
20.3 ECU warm reset detection 5829
20.4 ECOP Configuration data 5842
20.5 ECOP General 5854
20.6 ECOP Configuration data (prj) 5856
20.7 AGGR adaptation: ECOP 5858
20.8 ECU temperature 5863
20.9 Runtime counters 5868
20.10 Power latch management 5874
20.11 Power latch management (Appl. Inc.) 5883
20.12 ECU selftest 5885
20.13 ECU temperature diagnosis 5891
20.14 ECU temperature diagnosis (Appl. Inc.) 5896
20.15 Microcontroller communication diagnosis 5899
20.16 Microcontroller communication diagnosis (Appl. Inc.) 5901
20.17 ECU warm reset diagnosis 5903

21 ECRP-ECU Reprogramming 5906

21.1 Customer reprogramming 5907
21.2 Customer reprogramming (Appl. Inc.) 5914

22 EGCP-Exhaust gas composition 5919

22.1 EGCP Configuration data 5920
22.2 O2 sensor signal acquisition general 5925
22.3 O2 sensor (lin, up) signal acquisition for CILC 5947
22.4 AGGR adaptation: EGCP 5955
22.5 O2 sensor (lin, up) SPI interface ASW - BSW 5963

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

22.6	O2 sensor (lin, up) element temperature determination	5968
22.7	O2 sensor (bin, down) element temperature determination	5974
22.8	O2 sensor (bin) fault simulator	5981
22.9	O2 sensor (lin) fault simulator	5982
22.10	O2 sensor (lin, up) signal compensation and conversion	5984
22.11	O2 sensor (lin, up) operating strategy	5995
22.12	O2 sensor (lin, up) IP gain adaptation in PUC	6006
22.13	O2 sensor (up) heater management	6033
22.14	O2 sensor (bin, down) heater management	6047
22.15	O2 sensor lambda setpoint intervention	6066
22.16	O2 sensor air fuel cycle evaluation	6069
22.17	Lambda set point request for downstream lambda sensor	6076
22.18	O2 sensor (bin, down) operating strategy	6100
22.19	O2 sensor (lin, up) controller SPI diagnosis	6106
22.20	O2 sensor (lin, up) open circuit diagnosis	6112
22.21	O2 sensor (up) heater circuit diagnosis	6127
22.22	O2 sensor (bin, down) signal circuit diagnosis	6131
22.23	O2 sensor (bin, down) signal range diagnosis	6140
22.24	O2 sensor (bin, down) heater circuit diagnosis	6152
22.25	O2 sensor (lin, up) signal circuit diagnosis	6156
22.26	O2 sensor (bin) open circuit diagnosis	6165
22.27	O2 sensor (lin) diagnosis (error management interface)	6168
22.28	O2 sensor (bin) diagnosis (error management interface)	6191
22.29	O2 sensor (up, down) diagnosis management	6216
22.30	O2 sensor (up, down) interchanged diagnosis	6219
22.31	O2 sensor (lin, up) not mounted diagnosis	6220
22.32	O2 sensor (lin, up) dynamic diagnosis	6227
22.33	O2 sensor (lin, up) PUC plausibility diagnosis	6266
22.34	O2 sensor (up) heater plausibility diagnosis	6277
22.35	O2 sensor (up, down) plausibility diagnosis	6288
22.36	O2 sensor fuel trim diagnosis	6303

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

22.37	O2 sensor open loop diagnosis	6328
22.38	O2 sensor (lin, up) characteristic line diagnosis	6343
22.39	O2 sensor (bin, down) oscillation diagnosis	6358
22.40	O2 sensor (bin, down) dynamic diagnosis	6378
22.41	O2 sensor (bin, down) heater diagnosis	6434
22.42	O2 sensor (bin, down) open loop plausibility diagnosis	6445
22.43	O2 sensor (bin, down) gradient monitoring	6464
22.44	O2 sensor (lin,up) delay diagnosis	6517
22.45	O2 sensor (bin, down) delay diagnosis	6534
22.46	O2 sensor (bin, down) max/min voltage check diagnosis	6577
22.47	EGCP downstream (Appl. Inc.)	6599
22.48	EGCP upstream (Appl. Inc.)	6638
22.49	EGCP GAP diagnoses (Appl. Inc.)	6668
22.50	O2 sensor (lin) standard data for OBD radar	6727
22.51	O2 sensor (bin) standard data for OBD radar	6730
22.52	Lambda sensor heater control (prj)	6742
23	**EGPA-Exhaust gas pressure actuator**	**6746**
23.1	EGPA Configuration data	6747
23.2	EGPA actuator diagnosis	6751
23.3	EGPA position controller	6779
23.4	Control sound via exhaust flap (Appl. Inc.)	6804
24	**EGPR-Exhaust gas pressure**	**6809**
24.1	EGPR General	6810
24.2	EGPR Configuration data	6812
24.3	Exhaust gas pressure	6817
24.4	Exhaust gas pressure (Appl. Inc.)	6832
24.5	Exhaust system diagnosis	6837
24.6	Exhaust system diagnosis (Appl. Inc.)	6850

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

25	EGRC-Exhaust Gas Recirculation	6856
25.1	EGRC Configuration data	6857
25.2	EGRC dummy outputs	6858
26	EGTR-Exhaust gas treatment system	6860
26.1	EGTR Configuration data	6861
26.2	Forced lambda stimulation coordination	6871
26.3	Forced lambda stimulation (linear control)	6875
26.4	Forced lambda stimulation (linear control) (Appl. Inc.)	6889
26.5	Adaptation of catalyst oxygen storage capacity of catalyst	6895
26.6	Signal evaluation for conditioning of catalyst O2 loading	6901
26.7	Conditioning of catalyst O2 loading	6906
26.8	Conditioning of catalyst O2 loading (Appl. Inc.)	6913
26.9	Loading determination for catalyst purge function	6916
26.10	Catalyst enrichment function coordination	6935
26.11	Catalyst purge function (Appl. Inc.)	6938
26.12	Activation of forced lambda stimulation	6944
26.13	Determination of forced lambda stimulation parameters	6948
26.14	Enrichment of underfloor catalyst	6963
26.15	Enrichment of closed coupled catalyst	6976
26.16	Limited dynamic for catalyst efficiency and oxygen sensor diagnosis	6986
26.17	Coordination of catalyst efficiency diagnosis (Appl. Inc.)	6998
26.18	Catalyst efficiency diagnosis (activation conditions) - Gap method	7013
26.19	Catalyst efficiency diagnosis (Appl. Inc.)	7042
26.20	Catalyst efficiency diagnosis - Gap method	7067
26.21	Catalyst efficiency diagnosis correction - Gap method	7102
26.22	Coordination of catalyst efficiency value	7137
26.23	Catalyst efficiency diagnosis (error interface)	7145
26.24	Catalyst diagnosis EOL	7165
26.25	Forced lambda stimulation (gen)	7167
26.26	Catalyst OBDII (gen)	7174

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

27	**ENLU-Engine lubrication**	**7186**
27.1	ENLU General	7187
27.2	ENLU Configuration data	7190
27.3	Acquisition of oil sensor	7192
27.4	AGGR adaptation: ENLU	7213
27.5	Oil temperature model	7216
27.6	Oil temperature model (Appl. Inc.)	7281
27.7	Oil sensor variables	7287
27.8	Oil sensor variables (Appl. Inc.)	7294
27.9	Oil temperature calculation	7296
27.10	Oil dilution	7320
27.11	Oil pressure	7333
27.12	Acquisition of oil pressure	7347
27.13	Calculation of lubrication maintenance interval	7351
27.14	Calculation of lubrication maintenance interval (Appl. Inc.)	7406
27.15	Oil setpoint	7407
27.16	Oil control	7425
27.17	Actuator control for gating of pistons	7436
27.18	Oil plausibility diagnosis (Appl. Inc.)	7442
27.19	Oil plausibility diagnosis	7443
27.20	Oil pressure diagnosis (Appl. Inc.)	7471
27.21	Oil pressure diagnosis	7472
27.22	Oil pressure pump diagnosis	7485
27.23	Diagnosis of actuator for gating of piston	7488
27.24	Oil pressure pump diagnosis for EOL	7491
28	**ENOS-Engine operating states**	**7492**
28.1	ENOS General	7493
28.2	ENOS Synchronization constraints	7495
28.3	AGGR adaptation: ENOS	7497
28.4	Basic operating states (Appl. Inc.)	7501

28.5	Basic operating states	7530
28.6	Engine running	7542
28.7	Backfire Operation State	7550
28.8	Backfire Operation State	7567
28.9	Engine operating states (prj)	7568
29	**ENRD-Engine roughness determination**	**7572**
29.1	ENRD General	7573
29.2	ENRD Configuration data	7575
29.3	Engine roughness segment time correction	7577
29.4	Engine roughness calculation	7612
29.5	Engine roughness calculation (Appl. Inc.)	7636
29.6	Engine roughness adaptive learning process	7646
29.7	Engine roughness diagnosis	7711
29.8	Engine roughness diagnosis (Appl. Inc.)	7714
29.9	Engine roughness average calculation EOL	7716
29.10	Engine roughness calculation and adaptation (gen)	7717
29.11	Engine roughness OBDII (gen)	7745
30	**ENSC-Engine speed control**	**7748**
30.1	ENSC Configuration data	7749
30.2	AGGR adaptation: ENSC	7752
30.3	Driving off assistance	7753
30.4	Engine speed setpoint calculation	7769
30.5	Engine speed setpoint calculation (Appl. Inc.)	7822
30.6	Idle speed torque reserve	7838
30.7	Idle speed torque reserve (Appl. Inc.)	7849
30.8	Idle speed control diagnosis	7863
30.9	Idle speed control diagnosis (Appl. Inc.)	7888
30.10	Engine speed setpoint definition (gen)	7892
30.11	Engine speed setpoint definition (prj)	7893

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

30.12	Idle speed torque reserve (gen)	7896
30.13	Idle speed torque reserve (prj)	7898
30.14	Idle speed diagnosis (gen)	7899
30.15	Idle speed diagnosis (prj)	7900
31	**ENSD-Engine position and speed determination**	**7901**
31.1	ENSD General	7902
31.2	ENSD Configuration data	7908
31.3	Crankshaft acquisition, filtering and synchronization (low layer)	7928
31.4	Crankshaft acquisition and filtering with CPDD (low layer)	7947
31.5	Crankshaft acceleration/deceleration information (low layer)	7954
31.6	Camshaft acquisition and filtering (low layer)	7955
31.7	Engine position calculation using camshaft signal (low layer)	7960
31.8	Engine position determination (low layer)	7963
31.9	Engine position determination with CPDD (low layer)	7973
31.10	Segments measurements (low layer)	7975
31.11	Combustion efficiency index segments measurements (low layer)	7982
31.12	Engine roughness segment measurement (low layer)	7984
31.13	Tooth times buffer measurement (low layer)	7987
31.14	Crankshaft reference gap adaptation (low layer)	7993
31.15	EPO exported triggers (low layer template)	7994
31.16	Tacho: Engine speed output (low layer)	8003
31.17	AGGR adaptation: ENSD	8005
31.18	Crankshaft acquisition, filtering and synchronization (high layer)	8012
31.19	Crankshaft acquisition and filtering with CPDD (high layer)	8019
31.20	Crankshaft acceleration/deceleration information (high layer)	8022
31.21	Camshaft acquisition and filtering (high layer)	8023
31.22	Engine position determination (high layer)	8028
31.23	Engine position determination with CPDD (high layer)	8031
31.24	Engine position determination (high layer) (Appl. Inc.)	8035
31.25	Segments measurements (high layer)	8036

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

31.26	Engine roughness segment measurement (high layer)	8040
31.27	Tooth times buffer measurement (high layer)	8041
31.28	Engine position manager	8042
31.29	Engine synchronization	8057
31.30	Synchronisation determination in camshaft limp home	8062
31.31	Camshaft edges identification	8068
31.32	Internal stop/start manager	8074
31.33	Engine speed determination	8079
31.34	Engine speed determination (Appl. Inc.)	8089
31.35	Camshaft position adaptation	8097
31.36	Crankshaft reference gap adaptation	8106
31.37	Engine synchronization without camshaft signal	8107
31.38	Internal stop/start manager (Appl. Inc.)	8109
31.39	Crankshaft sensor circuit diagnosis	8111
31.40	ENSD Global error handler	8116
31.41	ENSD overall diagnosis inhibition calculation	8117
31.42	Engine backward rotation detection manager	8125
31.43	ENSD diagnosis manager	8131
31.44	Mandatory camshaft / crankshaft diagnoses	8146
31.45	Configurable camshaft diagnoses	8165
31.46	Configurable crankshaft diagnoses	8182
31.47	Diagnosis for Tacho - Engine speed output	8200
32	**ENSL-Engine speed limitation**	**8201**
32.1	ENSL General	8202
32.2	ENSL Configuration data	8204
32.3	Engine speed limit coordination	8206
32.4	Engine speed limitation	8264
32.5	Engine speed limitation (Appl. Inc.)	8279
32.6	Engine overspeed detection diagnosis	8307
32.7	Engine speed limitation (gen)	8313

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

32.8	Engine speed limitation (prj)	8316
33	**ENSS-Engine start and stop**	**8323**
33.1	ENSS General	8324
33.2	ENSS Configuration data	8327
33.3	AGGR adaptation: ENSS	8331
33.4	Engine off duration	8333
33.5	Auxiliary start functions	8436
33.6	Auxiliary start functions HPDI	8444
33.7	Start/stop function	8458
33.8	Start/stop function (Appl. Inc.)	8499
33.9	Cycle counters	8507
33.10	Cycle counters (Appl. Inc.)	8513
33.11	Stop/start manager (Appl. Inc.)	8515
33.12	Stop/start statistics	8537
33.13	Auxiliary start functions HPDI (Appl. Inc.)	8553
33.14	Starter relay control	8584
33.15	Starter relay control (Appl. Inc.)	8667
33.16	Controlled starting	8680
33.17	Remote start	8685
33.18	Starter relay diagnosis	8710
33.19	Engine off timer plausibility diagnosis	8735
33.20	Engine off timer plausibility diagnosis (Appl. Inc.)	8807
34	**ENTE-Engine temperature**	**8810**
34.1	ENTE General	8811
34.2	ENTE Configuration data	8822
34.3	AGGR adaptation: ENTE	8845
34.4	Acquisition of coolant temperature	8854
34.5	Coolant temperature (Appl. Inc.)	8858
34.6	Coolant temperature	8865

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

34.7	System temperature correction	8869
34.8	Engine coolant temperature calculation at engine outlet	8870
34.9	Coolant temperature substitute model (Appl. Inc.)	8879
34.10	Coolant temperature substitute model	8887
34.11	External engine heating detection	8910
34.12	Electronically controlled water pump external control	8923
34.13	Electronically controlled water pump PWM determination general	8933
34.14	Electronically controlled water pump PWM determination combustion	8968
34.15	Electronically controlled water pump PWM determination hybrid	9005
34.16	Electronically controlled water pump (Appl. Inc.)	9030
34.17	Electronically controlled water pump	9045
34.18	Electropneumatic converter for coolant circuit control (Appl. Inc.)	9052
34.19	Electropneumatic converter for coolant circuit control	9055
34.20	Cooling and condenser fan control (Appl. Inc.)	9058
34.21	Cooling and condenser fan control	9061
34.22	Rotary coolant valve sensor signal determination	9080
34.23	Determination of the RVC setpoint	9082
34.24	Rotary coolant valve adaptation	9085
34.25	Rotary coolant valve position control	9094
34.26	Rotary coolant valve jerk function	9102
34.27	Electronically controlled radiator shutter	9113
34.28	Electronically controlled radiator shutter external control	9135
34.29	Coolant temperature diagnosis interface	9141
34.30	Coolant temperature sensor diagnosis (Appl. Inc.)	9147
34.31	Coolant temperature sensor diagnosis	9149
34.32	Coolant temperature sensor diagnosis (error management interface)	9157
34.33	Electronically controlled water pump diagnosis (Appl. Inc.)	9159
34.34	Electronically controlled water pump diagnosis	9163
34.35	Electronically controlled water pump diagnosis (ERRM interface)	9185
34.36	Electropneumatic converter for COC diagnosis (Appl. Inc.)	9190
34.37	Electropneumatic converter for COC diagnosis	9193

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

34.38	Electropneumatic converter for COC diagnosis (ERRM interface)	9195
34.39	Cooling fan diagnosis (Appl. Inc.)	9198
34.40	Cooling fan diagnosis	9204
34.41	Cooling fan diagnosis (error management interface)	9219
34.42	Rotary coolant valve electrical diagnosis - actuator	9223
34.43	Rotary coolant valve electrical diagnosis - sensor	9230
34.44	Electronically controlled radiator shutter diagnosis (Appl. Inc.)	9233
34.45	Electronically controlled radiator shutter diagnosis	9238
34.46	Electronically controlled radiator shutter diagnosis (ERRM interface)	9260
34.47	Evaluation of coolant temperature errors	9265
34.48	Temperature sensor stuck high diagnosis (Appl. Inc.)	9269
34.49	Temperature sensor stuck high diagnosis	9275
34.50	Temperature sensor stuck high diagnosis (error management interface)	9293
34.51	Temperature sensor stuck low diagnosis (Appl. Inc.)	9297
34.52	Temperature sensor stuck low diagnosis	9301
34.53	Temperature sensor stuck low diagnosis (error management interface)	9313
34.54	Temperature sensor offset plausibility diagnosis (Appl. Inc.)	9316
34.55	Temperature sensor offset plausibility diagnosis	9323
34.56	Temperature sensor offset plausibility diagnosis (ERRM IF)	9337
34.57	Coolant thermostat monitoring (Appl. Inc.)	9340
34.58	Coolant thermostat monitoring	9345
34.59	Coolant thermostat monitoring (error management interface)	9373
34.60	Coolant thermostat monitoring retarded (Appl. Inc)	9376
34.61	Coolant thermostat monitoring retarded	9380
34.62	Coolant thermostat monitoring retarded (ERRM IF)	9397
34.63	Coolant temperature implausible cooling diagnosis (Appl.Inc.)	9399
34.64	Coolant temperature implausible cooling diagnosis	9401
34.65	Coolant temperature implausible cooling diagnosis (ERRM interface)	9406
34.66	Rotary coolant valve jam monitoring (Appl. Inc.)	9409
34.67	Rotary coolant valve jam monitoring	9410
34.68	Rotary coolant valve jam monitoring (error management interface)	9418

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

34.69	Rotary coolant valve adaptation error	9420
34.70	Rotary coolant valve rough running monitoring	9425
34.71	Electronically controlled water pump plausibility diagnosis (Appl. Inc	9428
34.72	Electronically controlled water pump plausibility diagnosis	9429
34.73	Electronically controlled water pump plaus diagnosis (ERRM interface)	9434
35	**ERRM-Error management**	**9436**
35.1	ERRM General	9437
35.2	ERRM Configuration data	9441
35.3	Table of failures	9449
35.4	Diagnostic filter algorithms	9503
35.5	Universal diagnostic interface	9526
35.6	Post diagnostic analyzer	9569
35.7	Sporadic failure manager	9575
35.8	Bench mode manager	9589
35.9	Diagnostic legacy interfaces	9608
35.10	Test of diagnostics	9632
35.11	Diagnosis callback manager	9656
35.12	Diagnosis callback manager (Appl. Inc.)	9664
35.13	OBDII error memory management (Appl. Inc.)	9667
35.14	Dynamic error management core	9673
35.15	Dynamic error management core (Appl. Inc.)	9725
35.16	Cycle manager	9729
35.17	Cycle manager (Appl. Inc.)	9749
35.18	Environmental data	9755
35.19	Environmental data (Appl Inc.)	9777
35.20	Statistical data	9826
35.21	Statistical data (Appl. Inc.)	9841
35.22	Rate based monitoring	9848
35.23	Rate based monitoring (Appl. Inc.)	9901
35.24	Failure classes	9915

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

35.25	Failure classes (Appl. Inc.)	9934
35.26	Lamp management	9935
35.27	Lamp management (Appl. Inc.)	9960
35.28	Priority rules	9968
35.29	Readiness codes	9975
35.30	Similar conditions	9993
35.31	Communication interface	10007
35.32	Communication interface (Appl. Inc.)	10040
35.33	Diagnostic trouble code management	10046
35.34	History memory	10058
35.35	History memory (Appl. Inc.)	10062
35.36	Permanent fault code	10064
35.37	Permanent fault code (Appl. Inc.)	10079
35.38	UDS communication interface	10081
35.39	UDS communication interface (Appl. Inc.)	10099
35.40	ERRM - Non volatile memory data interface	10108
35.41	NOx faults management	10120
35.42	NOx faults management (Appl. Inc.)	10124
35.43	Symptoms Combination	10125
35.44	Error management (gen)	10127
35.45	Autosar DEM BSW interfaces	10160
36	**EVAC-Evaporative system control**	**10161**
36.1	EVAC General	10162
36.2	EVAC Configuration data	10169
36.3	Evaporative emission control variables	10173
36.4	Evaporative emission control variables (Appl. Inc.)	10198
36.5	Torque reserve for canister purge at idle	10204
36.6	EVAC flow setpoints	10205
36.7	Evaporative emission control	10213
36.8	Evaporative emission control (Appl. Inc.)	10295

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

36.9	Evaporative emission control - Injection correction	10325
36.10	EVAC lambda deviation and canister load	10342
36.11	EVAC lambda deviation and canister load (Appl. Inc.)	10377
36.12	EVAC canister load model	10380
36.13	Time control between evaporative system and lambda adaptation	10381
36.14	Canister purge valve control	10414
36.15	Canister purge valve adaptation	10433
36.16	Canister purge valve adaptation (Appl. Inc.)	10434
36.17	Canister purge valve diagnosis	10435
36.18	Canister purge valve diagnosis (Appl. Inc.)	10456
36.19	EVAC Global error handler	10458
36.20	Evaporative system control (gen)	10459
36.21	Evaporative system control (prj)	10488
36.22	Evaporative system control OBDI (gen)	10491
36.23	Evaporative system control OBDI (prj)	10493
37	**EVAM-Evaporative system monitoring**	**10494**
37.1	EVAM General	10495
37.2	EVAM Configuration data	10520
37.3	AGGR adaptation: EVAM	10528
37.4	Tank leakage detection valve diagnosis	10533
37.5	Tank leakage detection pump diagnosis	10536
37.6	Tank leakage detection heater diagnosis	10541
37.7	Electrical diagnosis NVLD	10544
37.8	Electrical diagnosis communication line NVLD	10554
37.9	Electrical diagnosis communication line NVLD (Appl. Inc.)	10561
37.10	Functional check canister purge solenoid	10563
37.11	Functional check canister purge solenoid (Appl. Inc.)	10639
37.12	Leakage detection pump function diagnosis	10656
37.13	Leakage detection pump function diagnosis (Appl. Inc.)	10705
37.14	Rate based monitoring for leakage detection pump function	10713

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

37.15	Evaporative system monitoring error interface for NVLD	10721
37.16	Evaporative system monitoring error interface for NVLD (Appl. Inc.)	10778
37.17	Evaporative system monitoring for NVLD (Appl. Inc.)	10791
37.18	NVLD plausibility diagnosis valve control	10803
37.19	Valve control coordination manager	10809
37.20	NVLD plausibility diagnosis manager	10813
37.21	NVLD plausibility diagnosis check	10850
37.22	Plausibility diagnosis of smart module temperature sensor	10881
37.23	Error interface for leakage detection pump function	10890
37.24	Smart sensor communication for natural vacuum leak detection	10904
37.25	Leakage detection EOL	10933
37.26	Functional check canister purge solenoid EOL	10936
37.27	Evaporative system monitoring OBDII (prj)	10938
38	**EXTC-Exhaust system temperature control**	**10940**
38.1	EXTC General	10941
38.2	EXTC Configuration data	10943
38.3	Catalyst heating coordination	10962
38.4	Catalyst heating coordination (Appl. Inc.)	10971
38.5	Catalyst heating strategy	10984
38.6	Exhaust gas temperature protection - Minimun ignition angle limitation	10997
38.7	Catalyst heating correction	11008
38.8	Catalyst heating correction (Appl. Inc.)	11025
38.9	Lambda based catalyst overheating prevention	11033
38.10	Lambda based turbine overheating prevention	11047
38.11	Overheating prevention (Appl. Inc.)	11066
38.12	Catalyst overheating prevention by variable valve lift	11093
38.13	Adaptive catalyst heating	11097
38.14	Idle speed setpoint for catalyst heating	11104
38.15	Gear box shift point adjustment at warm-up	11109
38.16	Torque based catalyst heating	11114

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

38.17	Torque based catalyst heating (Appl. Inc.)	11163
38.18	Torque based turbine overheating prevention	11174
38.19	Torque based catalyst overheating prevention	11184
38.20	Catalyst heating (gen)	11189
38.21	Overheating prevention of exhaust parts (gen)	11194
39	**EXTD-Exhaust system temperature determination**	**11196**
39.1	EXTD General	11197
39.2	EXTD Configuration data	11200
39.3	AGGR adaptation: EXTD	11205
39.4	Exhaust gas temperature sensors	11207
39.5	Exhaust gas temperature sensors (Appl. Inc.)	11211
39.6	Exhaust gas temperature model	11213
39.7	Dewpoint detection	11223
39.8	Engine out exhaust gas temperature model	11240
39.9	Tube exhaust gas temperature model	11249
39.10	Catalyst exhaust gas temperature model	11266
39.11	Turbine exhaust gas temperature model	11286
39.12	Exhaust gas temperature model (Appl. Inc.)	11305
39.13	EXTD output selection	11328
39.14	Exhaust gas temperature sensor diagnosis	11346
39.15	Exhaust gas temperature sensor diagnosis (Appl. Inc.)	11358
39.16	Exhaust gas temperature diagnosis (error interface)	11365
39.17	Acquisition of exhaust gas temperature (gen)	11367
39.18	Exhaust gas temperature model (prj)	11368
39.19	Exhaust gas temperature OBDI (gen)	11374
40	**FARM-Fault reaction management**	**11377**
40.1	FARM General	11378
40.2	FARM Configuration data	11379
40.3	AGGR adaptation: FARM	11380

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

40.4	FARM auxiliary input handler	11383
40.5	FARM auxiliary input handler (Appl. Inc.)	11384
40.6	FARM inhibition calculation	11388
40.7	FARM status information	11389
41	**FMSP-Fuel mass setpoint**	**11392**
41.1	FMSP General	11393
41.2	FMSP Configuration data	11397
41.3	AGGR adaptation: FMSP	11403
41.4	Administration of calculation optimization	11404
41.5	Restart function	11414
41.6	Ambient pressure correction at start	11423
41.7	Basic injection mass for homogeneous mode	11425
41.8	Cold post start correction	11428
41.9	Warm up correction	11441
41.10	Fuel mass setpoint for homogeneous mode	11448
41.11	Calculation of mass fuel flow setpoint	11463
41.12	MFF split up for multiple injection at HOM mode (Appl. Inc.)	11466
41.13	MFF split up for multiple injection at HOM mode	11550
41.14	Calculation of cylinder individual fuel mass setpoints for HOM	11556
41.15	Start injection fuel mass	11563
41.16	Fuel quality adaptation at engine start	11576
41.17	Fuel quality adaptation at engine start (Appl. Inc.)	11604
41.18	Load acceleration enrichment	11620
41.19	Wall film compensation	11631
41.20	Octane switch correction for injection	11668
41.21	Injection at restart fuel feed	11672
41.22	Calculation of cylinder individual fuel mass SP for HOM (Appl.Inc.)	11729
41.23	Cylinder individual fuel mass correction factor	11733
41.24	Fuel mass correction factors for multiple injection	11740
41.25	Translation of variables	11750

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

41.26	MFF Split up for multiple injection at start	11755
41.27	Fuel consumption calculation	11764
41.28	Fuel mass setpoint (gen)	11776
41.29	Fuel mass at start/after-start (gen)	11780
41.30	Fuel quality adaptation (gen)	11788
41.31	Run time optimisation (gen)	11795
41.32	Wall film correction fuel mass setpoint (gen)	11797
42	**FULP-Fuel low pressure supply**	**11806**
42.1	Customer adaptation module: FULP	11807
43	**FUSL-Fuel supply**	**11812**
43.1	FUSL Configuration data	11813
43.2	AGGR adaptation: FUSL	11815
43.3	Fuel temperature	11817
43.4	Fuel temperature (Appl. Inc.)	11844
43.5	Fuel temperature (Appl. Inc.)	11865
43.6	Fuel pressure	11886
43.7	Fuel pressure (Appl. Inc.)	11895
43.8	Fuel pressure of low pressure pump	11905
43.9	Fuel pressure setpoint of low pressure pump	11911
43.10	Fuel pump low pressure control	11918
43.11	Fuel pump low pressure control (Appl. Inc.)	11943
43.12	Fuel pressure setpoint calculation	11952
43.13	Fuel pressure setpoint calculation (Appl. Inc.)	11962
43.14	Fuel pressure control	11965
43.15	Fuel pressure actuator control	11982
43.16	Fuel pressure actuator control (Appl. Inc.)	12086
43.17	Fuel supply system temperatures	12089
43.18	Fuel pump low pressure control coordination	12094
43.19	Fuel pump low pressure control coordination (Appl. Inc.)	12123

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

43.20	Fuel research octane number statistical quantification	12128
43.21	Fuel research octane number statistical quantification (Appl. Inc.)	12135
43.22	Fuel pump low pressure diagnosis	12137
43.23	Fuel pressure sensor diagnosis for low pressure	12156
43.24	Fuel pressure sensor diagnosis for low pressure (Appl. Inc.)	12159
43.25	Fuel pressure damper diagnosis	12161
43.26	Fuel pressure damper diagnosis (Appl. Inc.)	12164
43.27	Fuel pressure sensor diagnosis	12168
43.28	Fuel pressure sensor diagnosis (Appl. Inc.)	12171
43.29	Fuel pressure power stage diagnosis	12173
43.30	Fuel pressure power stage diagnosis (Appl. Inc.)	12180
43.31	Fuel pressure limp home management	12184
43.32	Fuel system pressure diagnosis	12188
43.33	Fuel system pressure diagnosis (Appl. Inc.)	12216
43.34	Fuel system pressure diagnosis for low pressure	12227
43.35	FUSL rate based monitoring interface	12241
43.36	Fuel research octane number diagnosis	12248
44	**FUTL-Fuel tank level**	**12251**
44.1	FUTL General	12252
44.2	AGGR adaptation: FUTL	12254
44.3	Fuel signal calculation	12256
44.4	Fuel reserve signal	12296
44.5	Fuel tank level input signal diagnosis	12300
44.6	Fuel tank level input signal diagnosis (Appl. Inc.)	12304
44.7	Fuel tank level functional diagnosis	12305
44.8	Fuel tank level functional diagnosis (Appl. Inc.)	12354
45	**GEOL-Garage End Of Line**	**12360**
45.1	GEOL Configuration data	12361
45.2	AGGR adaptation: GEOL	12362

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

45.3	Quick sleep current measurement	12367
45.4	Quick sleep current measurement (Appl. Inc.)	12369
45.5	Actuator test	12373
45.6	First fuel fill in	12398
45.7	EOL test manager KeyOn EngineRun	12405
45.8	GEOL actuator list	12447
45.9	Test intervention coordinator	12472
45.10	Engine speed setpoint for EOL	12474
45.11	EOL communication interface	12478
45.12	Engine switch off EOL	12487
45.13	GEOL interface for ERRM	12489
45.14	Transmission test for GEOL	12491
46	**HVAC-Heating, Ventilation and Air Conditioning**	**12495**
46.1	Air conditioning pressure	12496
46.2	Control of air conditioner compressor (AT/MT no difference)	12498
46.3	Management of auxiliary powertrain components	12513
46.4	Torque loss and reserve for air conditioning compressor	12558
47	**IGRE-Ignition realisation**	**12565**
47.1	IGRE General	12566
47.2	IGRE Configuration data	12567
47.3	Spark advance and dwell output	12570
47.4	Ignition output diagnosis	12574
47.5	Acquisition of coil primary current	12579
47.6	Dwell time adaptation	12580
47.7	Dwell time adaptation (Appl. Inc.)	12581
47.8	Dwell time factor calculation	12582
47.9	Dwell time and ignition angle switches for different combustion modes	12584
47.10	Ignition with multiple spark	12590
47.11	Ignition with multiple spark (Appl. Inc.)	12611

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

47.12	Ignition activation control	12612
47.13	Ignition coil temperature model	12616
47.14	Dwell time period for different combustion modes	12617
47.15	Ignition diagnosis	12622
47.16	Ignition diagnosis (Appl. Inc.)	12643
47.17	Dwell time calculation (prj)	12644
47.18	Ignition realization control (prj)	12645
47.19	Ignition dwell time calculation (gen)	12646
47.20	Ignition realization manager (gen)	12652
47.21	Ignition realization manager (prj)	12654
47.22	Ignition OBDI (gen)	12655
47.23	Ignition OBDI (prj)	12656
48	**IGSP-Ignition angle setpoint**	**12657**
48.1	IGSP General	12658
48.2	IGSP Configuration data	12660
48.3	Ignition angle general	12664
48.4	Ignition angle calculation configuration	12688
48.5	Basic ignition angle at start	12707
48.6	TQM - Corrected basic ignition angle	12722
48.7	TQM - Minimum ignition angle	12726
48.8	TQM - Minimum ignition angle external limitation	12797
48.9	TQM - Basic ignition angle calculation	12798
48.10	TQM - Reference ignition angle calculation	12804
48.11	TQM - Temperature correction	12807
48.12	Ignition angle correction for different combustion modes	12816
48.13	Ignition setpoint manager (gen)	12835
48.14	Ignition setpoint manager (prj)	12845
49	**IMMO-Immobilizer**	**12847**
49.1	IMMO Configuration data	12848

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

49.2	Customer adaptation module: IMMO	12851
50	**INJR-Injection realisation**	**12877**
50.1	INJR General	12878
50.2	INJR Configuration data	12906
50.3	AGGR adaptation: INJR	12925
50.4	Acquisition and interpretation of the injector feedback signal	12938
50.5	Final injection timing MPI	12950
50.6	Final injection timing	12971
50.7	Transfer to basic software for injection	12982
50.8	Configuration of pre injection	13026
50.9	Injector dead time correction	13037
50.10	Injection phase	13041
50.11	Injection phase for homogeneous mode - 1. pulse	13047
50.12	Injection phase (Appl. Inc.)	13059
50.13	Injector current control	13171
50.14	Injection pressure correction	13191
50.15	Injection pressure correction - HOM 1. pulse	13197
50.16	Fuel temperature correction for MPI	13205
50.17	Cylinder shut off (Appl. Inc.)	13207
50.18	Injection realization (Appl. Inc.)	13216
50.19	INJR manager	13251
50.20	Injection synchronisation	13281
50.21	Injector current control (Appl. Inc.)	13289
50.22	INJR COSI (Appl. Inc.)	13292
50.23	INJR COSI manager	13326
50.24	COSI control (COSI_CTL)	13338
50.25	Injection valve diagnosis MPI	13357
50.26	Injection valve diagnosis	13360
50.27	Injection valve power stage diagnosis	13365
50.28	Boost voltage diagnosis	13370

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

50.29	INJR Global error handler	13374
50.30	INJR COSI diagnosis (Appl. Inc.)	13404
50.31	Cold start emission reduction strategy diagnosis for injection	13412
50.32	Cold start emission reduction strategy diagnosis for INJ (Appl. Inc.)	13426
51	**INSY-Intake System**	**13435**
51.1	INSY General	13436
51.2	INSY Configuration data	13446
51.3	INSY Configuration data (volumetric efficiency)	13459
51.4	Acquisition of analogue delivered gas pressures	13466
51.5	Combustion condition correction of volumetric efficiency	13471
51.6	INSY Component and adaptation manager	13477
51.7	Air mass flow sensor variables	13493
51.8	Acquisition of air mass flow	13501
51.9	Air mass flow variables	13528
51.10	Determination of air pressures	13533
51.11	Determination of air pressures (Appl. Inc.)	13581
51.12	Pressure sensor variables	13597
51.13	Volumetric efficiency	13606
51.14	Altitude correction of volumetric efficiency	13622
51.15	Temperature correction of volumetric efficiency	13624
51.16	Volumetric efficiency correction coordination	13631
51.17	INSY - Controller	13644
51.18	Pressure decrease through the air cleaner	13686
51.19	Throttle area	13689
51.20	Intake manifold model (Appl. Inc.)	13695
51.21	Intake manifold model	13724
51.22	Calculation of mass air flow	13747
51.23	Air mass limits	13796
51.24	Air mass flow integral calculation	13807
51.25	Throttle area adaptation	13813

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

51.26	Ambient pressure adaptation	13840
51.27	Translation of extended air mass flow variables	13891
51.28	Camshaft offset adaptation manager	13912
51.29	Camshaft offset adaptation manager (Appl. Inc.)	13915
51.30	Activation conditions and data acquisition for CAM offset adaptation	13917
51.31	Optimisation algorithm for camshaft offset adaptation	13921
51.32	Crankcase ventilation	13923
51.33	Ambient pressure sensor diagnosis	13958
51.34	Ambient pressure sensor diagnosis (Appl. Inc.)	13970
51.35	Manifold air pressure sensor diagnosis	13973
51.36	Pressure upstream throttle sensor diagnosis	13985
51.37	Pressure upstream throttle sensor diagnosis (Appl. Inc.)	13997
51.38	INSY Global error handler	14002
51.39	Pressure downstream air cleaner sensor diagnosis	14011
51.40	Pressure downstream air cleaner sensor diagnosis (Appl. Inc.)	14012
51.41	Manifold air pressure sensor diagnosis (Appl. Inc.)	14016
51.42	Air mass flow sensor diagnosis	14019
51.43	Air mass flow sensor diagnosis (Appl. Inc.)	14026
51.44	Load/Throttle position rationality check	14027
51.45	Load/Throttle position rationality check (Appl. Inc.)	14076
51.46	Load/Throttle position rationality check (ERRM interface)	14086
51.47	Ambient and manifold pressure plausibility diagnosis	14109
51.48	Ambient and manifold pressure plausibility diagnosis (Appl.Inc.)	14160
51.49	Ambient and manifold pressure plausibility diagnosis (ERRM interface)	14163
51.50	Air mass flow setpoint for stratified mode	14171
51.51	Calculation of setpoints for inverse intake manifold model	14174
51.52	Inverse intake manifold model	14198
51.53	Throttle setpoint calculation	14217
51.54	Acquisition of air mass flow (gen)	14226
51.55	Intake manifold sensor OBDI (gen)	14229
51.56	Intake manifold sensor OBDI (prj)	14234

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

51.57	Intake manifold sensor OBDII (gen)	14235
51.58	Intake manifold sensor OBDII (prj)	14242
51.59	Intake manifold model (gen)	14255
51.60	Intake manifold model (prj)	14280
51.61	Air mass flow variable determination (gen)	14282
51.62	Volumetric efficiency calculation (gen)	14283
51.63	Acquisition of air pressures (gen)	14290
52	**INTC-Intersystem communication**	**14301**
52.1	Bus off handler	14302
52.2	Bus off handler (Appl. Inc.)	14313
52.3	INTC Configuration data	14317
52.4	AGGR adaptation: INTC	14318
52.5	CAN general message overview	14344
52.6	PDU mapping adaptive cruise control speed control unit	14414
52.7	PDU mapping Airbag control unit 1	14426
52.8	PDU mapping Airbag control unit 2	14466
52.9	PDU mapping charisma 1	14478
52.10	PDU mapping clamp control 1	14521
52.11	PDU mapping climate control unit 1	14525
52.12	PDU mapping climate control unit 3	14620
52.13	PDU mapping climate control unit 11	14625
52.14	PDU mapping Cruise control 1	14681
52.15	PDU mapping diagnostic 1	14863
52.16	PDU mapping distance cruise control 1	14975
52.17	PDU mapping distance cruise control 5	15007
52.18	PDU mapping distance cruise control 6	15037
52.19	PDU mapping drive train manager 1	15101
52.20	PDU mapping drive train manager 2	15110
52.21	PDU mapping drive train manager 3	15122
52.22	PDU mapping drive train manager 4	15151

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

52.23	PDU mapping drive train manager 5	15186
52.24	PDU mapping drive train manager 6	15236
52.25	PDU mapping drive train manager 7	15314
52.26	PDU mapping drive train manager 8	15364
52.27	PDU mapping electronic park brake 1	15401
52.28	PDU mapping electronic power steering unit 2	15489
52.29	PDU mapping electronic transmission control unit 1	15499
52.30	PDU mapping electronic transmission control unit 2	15592
52.31	PDU mapping electronic transmission control unit 3	15690
52.32	PDU mapping electronic transmission control unit 4	15758
52.33	PDU mapping electronic transmission control unit 6	15804
52.34	PDU mapping electronic transmission control unit 11	15814
52.35	PDU mapping electronic transmission control unit 12	15886
52.36	PDU mapping electronic transmission control unit 13	15930
52.37	PDU mapping electronic transmission control unit 14	15974
52.38	PDU mapping energy manager 1	16028
52.39	PDU mapping energy manager 5	16054
52.40	PDU mapping engine ignition lock unit 1	16082
52.41	PDU mapping engine ignition lock unit 2	16115
52.42	PDU mapping engine management system 1	16123
52.43	PDU mapping engine management system 2	16201
52.44	PDU mapping engine management system 3	16320
52.45	PDU mapping engine management system 4	16452
52.46	PDU mapping engine management system 5	16569
52.47	PDU mapping engine management system 6	16733
52.48	PDU mapping engine management system 7	16925
52.49	PDU mapping engine management system 8	17153
52.50	PDU mapping engine management system 9	17186
52.51	PDU mapping engine management system 10	17351
52.52	PDU mapping engine management system 11	17429
52.53	PDU mapping engine management system 12	17473

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

52.54	PDU mapping engine management system 13	17537
52.55	PDU mapping engine management system 14	17575
52.56	PDU mapping engine management system 15	17754
52.57	PDU mapping electronic transmission control unit 17	17760
52.58	PDU mapping engine management system 16	17776
52.59	PDU mapping engine management system 17	17834
52.60	PDU mapping engine management system 18	17921
52.61	PDU mapping engine management system 20	18055
52.62	PDU mapping engine management system 21	18130
52.63	PDU mapping engine management system 23	18358
52.64	PDU mapping engine management system 26	18419
52.65	PDU mapping engine management system brake	18599
52.66	PDU mapping engine management system code 1	18614
52.67	PDU mapping engine management system flexible	18758
52.68	PDU mapping engine management system manual transmission	18826
52.69	PDU mapping engine node 1	18839
52.70	PDU mapping four wheel drive 2	18867
52.71	PDU mapping fuel tank level sensor 1	18881
52.72	PDU mapping gateway 1	18983
52.73	PDU mapping gateway 2	19049
52.74	PDU mapping gateway 5	19086
52.75	PDU mapping gateway 11	19212
52.76	PDU mapping gateway 72	19242
52.77	PDU mapping gateway 74	19284
52.78	PDU mapping immobilizer coordination 1	19350
52.79	PDU mapping independent car heater 1	19357
52.80	PDU mapping instrument cluster 1	19448
52.81	PDU mapping instrument cluster 2	19541
52.82	PDU mapping instrument cluster 3	19636
52.83	PDU mapping lamp rear 1	19660
52.84	PDU mapping on board diagnosis 1	19701

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

52.85	PDU mapping park assistant 1	19821
52.86	PDU mapping power steering 1	19834
52.87	PDU mapping satellite tracking system 1	19894
52.88	PDU mapping selection display 1	19901
52.89	PDU mapping selection display 2	19914
52.90	PDU mapping service interval 1	19925
52.91	PDU mapping steering control unit 1	19990
52.92	PDU mapping steering control unit 3	19998
52.93	PDU mapping system info 1	20007
52.94	PDU mapping thermic oil sensor 1	20038
52.95	PDU mapping traction control system 1	20060
52.96	PDU mapping traction control system 2	20199
52.97	PDU mapping traction control system 3	20253
52.98	PDU mapping traction control system 4	20332
52.99	PDU mapping traction control system 5	20340
52.100	PDU mapping traction control system 7	20565
52.101	PDU mapping traction control system 8	20676
52.102	PDU mapping traction control system 11	20719
52.103	PDU mapping traction control system 15	20751
52.104	PDU mapping traction control system 19	20773
52.105	PDU mapping traction control system 20	20786
52.106	PDU mapping traction control system 21	20794
52.107	PDU mapping traction control system 33	20912
52.108	PDU mapping trailer control unit 1	20964
52.109	PDU mapping unit 1	20996
52.110	PDU mapping vehicle electrics control unit 1	21001
52.111	PDU mapping vehicle electrics control unit keyless go	21058
52.112	PDU mapping drive train manager coasting curve 1	21077
52.113	CAN interface for runtime measurement	21321
52.114	PDU mapping selection display 3	21326
52.115	PDU mapping traction control system 10	21330

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

52.116	PDU mapping traction control system 16	21427
52.117	PDU mapping engine management system 29	21431
52.118	PDU mapping engine management system 30	21435
52.119	PDU mapping electronic transmission control unit 7	21439
52.120	PDU mapping predicted track 6	21453
52.121	PDU mapping engine management system 35	21784
52.122	PDU mapping gateway 80	21807
52.123	PDU mapping gateway 3	21817
52.124	PDU mapping door system control unit left side 2	21824
52.125	PDU mapping electronic park brake 2	21829
52.126	PDU mapping chassis frame 2	21833
52.127	CAN diagnosis	21835
52.128	CAN diagnosis - ERRM Interface	21891
52.129	CAN diagnosis (Appl. Inc.)	21914
52.130	CAN diagnosis for signal contents	22077
53	**KNCK-Knock**	**22127**
53.1	KNCK Configuration data	22128
53.2	Acquisition of combustion noise	22132
53.3	AGGR adaptation: KNCK	22143
53.4	Instationary correction (knock prevention)	22144
53.5	Octane switch correction for ignition	22154
53.6	Knock control (Appl. Inc.)	22155
53.7	Knock activation control	22165
53.8	Knock detection	22188
53.9	Knock control	22215
53.10	Knock limp home operation	22270
53.11	Knock limp home operation (Appl. Inc.)	22273
53.12	Pre ignition detection by knock sensor	22277
53.13	Reactions to pre ignition detection	22293
53.14	Knock sensor diagnosis	22308

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

53.15	Knock sensor diagnosis (Appl. Inc.)	22341
53.16	Knock control at limitation diagnostics	22344
53.17	Pre ignition diagnosis via knock control	22347
53.18	Acquisition of knock sensor signal (gen)	22355
53.19	Knock control (gen)	22370
53.20	Knock limp home and diagnosis OBDI (gen)	22387
54	**LACO-Lambda control**	**22391**
54.1	LACO General	22392
54.2	LACO Configuration data	22396
54.3	AGGR adaptation: LACO	22401
54.4	Lambda control conditions	22406
54.5	Lambda control (fuel mass)	22427
54.6	Feed forward lambda control (precontrol)	22476
54.7	Gas delay and sensor model	22480
54.8	Lambda controller limitation	22499
54.9	Lambda control (Appl. Inc.)	22510
54.10	Activation conditions for WRAF sensor deviation detection	22554
54.11	Priority manager for the WRAF sensor deviation detection	22572
54.12	Detection of WRAF sensor deviation	22583
54.13	Mean value calculation for limited dynamics	22609
54.14	Dynamic fuel trim	22613
54.15	Dynamic fuel trim (Appl. Inc.)	22650
54.16	WRAF sensor characteristic line adaptation with trim control	22665
54.17	Condition check for WRAF sensor adaptation with trim control	22675
54.18	Lambda adaptation	22680
54.19	Lambda adaptation in warm up phase	22727
54.20	Validity check of lambda adaptation in warm up phase	22761
54.21	Lambda adaptation (Appl. Inc.)	22787
54.22	Request of forced lambda adaptation	22857
54.23	Oil dilution impact on lambda controller	22868

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

54.24	Activation of fuel system monitoring	22890
54.25	Fuel system monitoring	22894
54.26	Fuel system monitoring for multiplicative adaptation	22912
54.27	Optional Fuel system monitoring	22930
54.28	Optional fuel system monitoring for multiplicative adaptation	22947
54.29	Fuel system monitoring - Lambda controller limitation	22961
54.30	Fuel system monitoring (Appl. Inc.)	22978
54.31	Dynamic fuel trim (gen)	22996
54.32	Lambda adaptation (gen)	23004
54.33	Lambda control function (gen)	23017
54.34	Fuel system monitoring OBDII (gen)	23024
55	**LASP-Lambda setpoint**	**23043**
55.1	LASP General	23044
55.2	Lambda setpoint for single cylinder shut off	23047
55.3	Basic lambda setpoint	23050
55.4	Basic lambda setpoint (Appl. Inc.)	23057
55.5	Lambda coordination	23075
55.6	Lambda coordination (Appl. Inc.)	23086
55.7	Lambda coordination (gen)	23098
55.8	Lambda setpoint (gen)	23100
56	**MCPC-Measurement and Calibration Protocol Communication**	**23102**
56.1	MCPC Configuration data	23103
56.2	MCPC General	23104
56.3	CAN calibration protocol tuning	23110
56.4	CAN calibration protocol tuning on CAN powertrain	23130
56.5	Rapid prototyping interface implementation	23134
56.6	Rapid prototyping - Bypass configuration	23137
56.7	Rapid prototyping manager	23159
56.8	ETK bypass (Appl. Inc.)	23165

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

56.9	Rapid prototyping interface implementation diagnosis	23167
57	**MISC-Miscellaneous**	**23168**
57.1	Initialization of variables from non implemented functions	23169
57.2	EPC illumination by misfire	23260
57.3	EPC illumination by misfire (Appl. Inc.)	23270
57.4	Base-algorithm for adaptative maps	23273
57.5	Exponentially weighted moving average (EWMA) filter for diagnosis	23286
57.6	Cold start reference temperature diagnostics (Appl. Inc.)	23295
57.7	Cold start reference temperature diagnostics	23299
57.8	Cold start reference temperature diagnostics (ERRM interface)	23310
58	**MISF-Misfire monitoring**	**23315**
58.1	MISF General	23316
58.2	MISF Configuration data	23318
58.3	Mean engine roughness value for fuel on adaptation	23321
58.4	Misfire detection	23340
58.5	Misfire detection (Appl. Inc.)	23352
58.6	Crankshaft oscillation detection	23370
58.7	Rough road detection	23374
58.8	Generic misfire parameters and fade-out conditions	23383
58.9	Legal misfire detection fade-out conditions	23397
58.10	Misfire diagnosis CARB A	23420
58.11	Misfire diagnosis CARB B	23484
58.12	Misfire rate determination	23533
58.13	Misfire diagnosis interfaces	23540
58.14	Misfire diagnosis by cylinders	23555
58.15	Misfire tuning functions	23583
58.16	Misfire fade out (gen)	23597
58.17	Misfire OBDII (gen)	23615
58.18	Misfire rate determination (gen)	23628

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

59	NETM-Network management	23644
59.1	NETM CAN Configuration data	23645
59.2	Network management (Appl. Inc.)	23647
59.3	Network Management	23670
60	OBDC-On-Board diagnostic communication	23687
60.1	OBDC General	23688
60.2	OBDC Configuration data	23691
60.3	OBDC service interpreter	23696
60.4	SID 01h: Request current powertrain diagnostic data	23700
60.5	SID 01h: Request current powertrain diagnostic data (Appl.Inc)	23704
60.6	SID 02h: Request powertrain freeze frame data	23738
60.7	SID 02h: Request powertrain freeze frame data (Appl. Inc.)	23743
60.8	SID 03h: Request emission-related diagnostic trouble codes	23765
60.9	SID 04h: Clear/reset emission-related diagnostic inf.	23768
60.10	SID 04h: Clear/reset emission-related diagnostic inf. (Appl. Inc.)	23772
60.11	SID 06h: Request on-board monitoring testS - specific syst	23775
60.12	SID 06h: Request on-board monitoring testS - specific syst (Appl.Inc)	23785
60.13	SID 07h: Request emission-related diagnostic trouble codes - pending	23831
60.14	SID 08h: Request control of on-board system, test/component	23834
60.15	SID 08h: Request control of on-board system, test/component (Appl.Inc)	23838
60.16	SID 09h: Request vehicle information	23842
60.17	SID 09h: Request vehicle information (Appl. Inc.)	23860
60.18	SID 0Ah: Request emission related diagnostic trouble codes - permanent	23876
61	OSYM-Operating System Monitoring	23879
61.1	OSYM General	23880
61.2	OSYM Configuration data	23881
61.3	Visible data of operating system monitoring functions	23887
61.4	Visible data of operating system monitoring functions (Appl. Inc.)	23890

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

62	PSGP-Passenger protection	23895
62.1	Crash signal	23896
62.2	Crash signal diagnosis	23903
63	PTQM-Powertrain torque management	23914
63.1	AGGR adaptation: PTQM	23915
63.2	Detection of driver torque request passive	23919
63.3	Powertrain torque actual	23922
63.4	Coordination of powertrain torque losses	23925
63.5	Powertrain driver torque request coordination	23927
64	PWSL-Power Supply	23931
64.1	PWSL General	23932
64.2	PWSL Configuration data	23935
64.3	PWSL Configuration data (prj)	23946
64.4	Acquisition of after relay battery voltage	23947
64.5	Acquisition of after key battery voltage	23957
64.6	Acquisition of wake up signal	23972
64.7	Key position determination	24009
64.8	Acquisition of after HPDI relay battery voltage	24042
64.9	AGGR adaptation: PWSL	24053
64.10	Battery voltage	24068
64.11	Ignition key recognition	24082
64.12	Electrical load	24091
64.13	Reference voltage	24094
64.14	Engine efficiency state	24098
64.15	Engine efficiency state (Appl. Inc.)	24111
64.16	Main relay control	24114
64.17	Charge option arbitration	24121
64.18	Alternator power management	24136
64.19	Power Relay Control	24148

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

64.20	Reference voltage diagnosis	24156
64.21	Reference voltage diagnosis (Appl. Inc.)	24170
64.22	Battery voltage diagnosis	24173
64.23	Battery voltage diagnosis (Appl. Inc.)	24186
64.24	Power Latch Diagnosis	24222
64.25	Key position diagnosis	24239
64.26	Main relay diagnosis	24243
64.27	Main relay diagnosis (Appl. Inc.)	24273
64.28	Charging system diagnosis	24283
64.29	Alternator power management diagnosis	24288
64.30	Wake up signal diagnosis	24307
64.31	Power relay control diagnosis	24318
64.32	Power supply diagnosis	24339
64.33	Torque loss alternator	24342
64.34	Electrical power supply (gen)	24351
65	**SAIR-Secondary air**	**24375**
65.1	SAIR Configuration data	24376
65.2	AGGR adaptation: SAIR	24377
65.3	Acquisition of secondary air pressure	24399
65.4	Acquisition of secondary air sensor pressure voltages	24407
65.5	Catalyst heating correction with secondary air	24408
65.6	Secondary air pump overheating detection	24412
65.7	Coordination of secondary air mass flow determination	24414
65.8	Determination of secondary air mass flow	24417
65.9	Determination of model based secondary air pressure	24426
65.10	Determination of secondary air pressure values for diagnosis	24438
65.11	Coordination of all secondary air pump and valve control requests	24463
65.12	State machine for secondary air system diagnosis	24507
65.13	Secondary air valve diagnosis	24538
65.14	Secondary air valve diagnosis (Appl. Inc.)	24541

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

65.15	Secondary air pump diagnosis	24543
65.16	Secondary air pump diagnosis (Appl. Inc.)	24546
65.17	Secondary air pressure sensor diagnosis	24548
65.18	Secondary air system monitoring	24554
65.19	Secondary air system monitoring (Appl. Inc.)	24603
65.20	Freeze frame for pressure based secondary air diagnosis	24624
65.21	Secondary air diagnose interfaces	24643
65.22	Secondary air valve test EOL	24653
65.23	Customer adaptation module: SAIR	24655
66	**STSY-Steering system**	**24656**
66.1	STSY Configuration data	24657
66.2	Torque loss power steering	24659
67	**SUSY-Suspension system**	**24682**
67.1	SUSY configuration data	24683
67.2	Active engine brackets	24684
67.3	Active engine brackets diagnosis	24708
68	**SYCF-System Configuration**	**24716**
68.1	SYCF Configuration data	24717
68.2	Variant coding	24737
68.3	Variant coding (Appl. Inc.)	24790
68.4	Transport / Production Mode Configuration data	24797
68.5	Variant Coding Configuration data	24798
68.6	Variant coding diagnosis	24802
68.7	Transport / Production mode	24808
68.8	Dynamometer Mode	24819
69	**THRO-Throttle**	**24828**
69.1	THRO General	24829

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

69.2	THRO Configuration data	24832
69.3	AGGR adaptation: THRO	24834
69.4	Mass air flow throttle sensor variables	24838
69.5	Electronic throttle control position sensor diagnosis	24849
69.6	Electronic throttle control position sensor diagnosis (Appl. Inc.)	24866
69.7	Electronic throttle control power stage diagnosis	24869
69.8	Electronic throttle control power stage diagnosis (Appl. Inc.)	24909
69.9	Electronic throttle control actuator diagnosis	24911
69.10	Mass air flow trottle control diagnosis (Appl. Inc.)	24936
69.11	Electronic throttle control actuator adaptation diagnosis	24939
69.12	Electronic throttle control actuator adaptation diagnosis (Appl. Inc.)	24971
69.13	Electronic throttle control sensor plausibility check	24993
69.14	Electronic throttle control sensor plausibility check (Appl. Inc.)	25014
69.15	Electronic throttle control limp home management	25028
69.16	Electronic throttle control setpoint calculation at start	25039
69.17	Electronic throttle control jam detection	25044
69.18	Electronic throttle control jam detection (Appl. Inc.)	25073
69.19	Electronic throttle control setpoint selection	25082
69.20	Electronic throttle control setpoint selection (Appl. Inc.)	25094
69.21	Electronic throttle control position controller	25113
69.22	Electronic throttle control position controller (Appl. Inc.)	25120
69.23	Electronic throttle control position control (gen)	25124
69.24	Electronic throttle control position control (prj)	25134
69.25	Electronic throttle control jam detection (gen)	25136
69.26	Electronic throttle control jam detection (prj)	25139
69.27	Electronic throttle control adaptation diagnosis (gen)	25141
69.28	Electronic throttle control adaptation diagnosis (prj)	25149
69.29	Electronic throttle control OBDI (gen)	25151
69.30	Electronic throttle control OBDI (prj)	25156
69.31	Engine start/stop throttle (prj)	25160

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

70	TQDR-Torque determination and realization	25167
70.1	TQDR General	25168
70.2	TQDR Configuration data	25173
70.3	AGGR adaptation: TQDR	25176
70.4	Ignition angle efficiency	25177
70.5	TQM - Setpoint ignition angle	25200
70.6	Full load enrichment	25213
70.7	Sequential fuel cutoff and restart fuel feed parameters	25219
70.8	Sequential fuel cutoff and restart fuel feed	25227
70.9	Ignition angle efficiency diagnosis	25246
70.10	Ignition angle efficiency diagnosis (error management interface)	25261
70.11	Ignition angle efficiency diagnosis (Appl. Inc.)	25270
70.12	Reference and basic torque	25275
70.13	Reference and basic torque (Appl. Inc.)	25301
70.14	Adaptation of indicated engine torque	25361
70.15	Torque based lambda setpoint calculation	25366
70.16	Torque based mass air flow setpoint for homogeneous mode	25371
70.17	Basic fuel cutoff coordination	25388
70.18	Torque based pattern calculation	25390
70.19	Torque based pattern calculation (Appl. Inc.)	25401
70.20	Initialization module	25408
70.21	Maximum torque at clutch	25412
70.22	Minimum torque at clutch	25416
70.23	Minimum indicated engine torque offset during PUC	25420
70.24	Minimum indicated engine torque offset during PUC (Appl. Inc.)	25434
70.25	Minimum indicated engine torque at trailing throttle	25438
70.26	Single cylinder cut off basic and actual efficiency	25451
70.27	Basic, actual and minimum lambda efficiency	25457
70.28	Actual engine torque	25460
70.29	Engine torque status	25465
70.30	Indicated efficiency correction for project specific requirements	25478

70.31	Combustion mode efficiency	25483
70.32	Combustion mode target torque	25491
70.33	Torque model HOM (gen)	25499
70.34	Torque operating range (gen)	25510
70.35	TQDR fuel mass setpoint (gen)	25518
70.36	Sequential fuel cutoff and restart (gen)	25521
70.37	Sequential fuel cutoff and restart (prj)	25522
71	**TQLO-Torque losses**	**25524**
71.1	TQLO General	25525
71.2	TQLO Configuration data	25528
71.3	TQM - Idle speed adaptation (Appl. Inc.)	25529
71.4	TQM - Idle speed adaptation conditions	25533
71.5	TQM - Idle speed adaptation algorithm	25541
71.6	Torque losses	25553
71.7	Correction of friction and pumping losses	25570
71.8	Idle speed adaptation (gen)	25574
71.9	Torque losses (gen)	25576
72	**TQSP-Torque setpoint**	**25583**
72.1	TQSP Configuration data	25584
72.2	AGGR adaptation: TQSP	25589
72.3	Torque output for CAN communication	25596
72.4	Full load detection	25602
72.5	Torque limitation indication	25610
72.6	Torque reserve coordination	25617
72.7	Torque reserve coordination (Appl. Inc.)	25628
72.8	Dynamic torque request coordination	25636
72.9	Minimum / Maximum torque request selection	25659
72.10	Dynamic torque intervention manager	25663
72.11	Torque coordination	25679

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

72.12	Torque request for safety	25686
72.13	Torque reserve in part load	25689
72.14	Torque based combustion mode request	25690
72.15	Engine torque limitation coordination	25716
72.16	Torque limitation for combustion control	25725
72.17	Torque limitation for engine components	25766
72.18	Torque limitation for production and transportation	25786
72.19	Torque limitation for economy mode	25789
72.20	Torque settings at trailing throttle fuel cutoff	25801
73	**TRSM-Transmission**	**25815**
73.1	TRSM General	25816
73.2	TRSM Configuration data	25818
73.3	TRSM Synchronization constraints (prj)	25824
73.4	AGGR adaptation: TRSM	25826
73.5	Gearbox engine speed request for idle speed controller	25835
73.6	Gear detection (Appl. Inc.)	25842
73.7	Gear detection	25859
73.8	Reverse gear detection	25873
73.9	Neutral gear detection for manual shifted transmission	25876
73.10	Neutral gear detection for manual shifted transmission (Appl. Inc.)	25930
73.11	Clutch state	25932
73.12	Detection of interlock and park neutral signal	25940
73.13	Gear lever state	25943
73.14	TRSM Inputs from communication	25947
73.15	TRSM Outputs for communication	25967
73.16	Drive train open release for stop/start	25971
73.17	Clutch diagnosis	25983
73.18	Transmission control unit diagnosis	26033
73.19	Gearbox intervention diagnosis	26042
73.20	Neutral gear detection sensor diagnosis	26054

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

73.21	Gear lever diagnosis	26080
73.22	Gear ratio diagnosis	26098
73.23	Gearbox torque intervention	26103
73.24	Gearbox engine speed control	26119
73.25	Gearbox engine speed control (Appl. Inc.)	26144
73.26	Gearbox engine speed control for manual transmission	26156
73.27	Converter torque	26161
73.28	Gearbox torque reserve	26187
73.29	Gearbox protection	26193
73.30	Coasting	26206
74	**VHMD-Vehicle motion determination**	**26219**
74.1	VHMD Configuration data	26220
74.2	Acquisition of vehicle speed signal	26223
74.3	Vehicle motion acquisition by CAN	26236
74.4	Vehicle speed output	26240
74.5	Vehicle speed	26268
74.6	Vehicle speed (Appl. Inc.)	26272
74.7	Distance counter	26281
74.8	Wheel Parameters	26284
74.9	Vehicle speed signal diagnosis	26287
74.10	Vehicle speed signal diagnosis (Appl. Inc.)	26351
75	**VHSC-Vehicle speed control**	**26355**
75.1	VHSC Configuration data	26356
75.2	Cruise control and variable vehicle speed limiter diagnosis	26358
75.3	Cruise control input (Appl. Inc.)	26398
75.4	Cruise control output (Appl. Inc.)	26414
76	**VHSL-Vehicle speed limitation**	**26420**
76.1	VHSL Configuration data	26421

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

76.2	AGGR adaptation: VHSL	26422
76.3	Vehicle speed limit calculation	26424
77	**VHST-Vehicle stability and traction**	**26451**
77.1	VHST General	26452
77.2	Traction control diagnosis	26454
77.3	Torque request for traction control	26468
77.4	Torque request for deceleration slip control	26481
78	**VVLI-Variable Valve Lift**	**26494**
78.1	VVLI General	26495
78.2	VVLI Configuration data	26499
78.3	Switch variable valve lift timing	26502
78.4	Switch variable valve lift actuator hit position	26507
78.5	Switch variable valve lift state coordination	26510
78.6	Switch variable valve lift state coordination (Appl. Inc.)	26530
78.7	Switch variable valve lift control request coordination	26543
78.8	Switch variable valve lift controller	26575
78.9	Switch variable valve lift state determination	26604
78.10	Camshaft signal range variables	26632
78.11	Switch variable valve lift setpoint	26636
78.12	Switch variable valve lift output signal diagnosis	26645
78.13	Switch variable valve lift output signal diagnosis (Appl. Inc.)	26658
78.14	Switch variable valve lift output signal diagnosis (ERR IF)	26665
78.15	Switch variable valve lift diagnosis	26668
78.16	Switch variable valve lift diagnosis (Appl. Inc.)	26680
78.17	Switch variable valve lift diagnosis (ERR IF)	26686
78.18	Switch variable valve lift limp home manager	26688
78.19	Switch VVL limp home manager (Appl. Inc.)	26705
78.20	Switch variable valve lift actuator test for EOL	26707
78.21	Switch variable valve lift actuator test for EOL (Appl. Inc.)	26713

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

78.22	Switch variable valve lift control (gen)	26715
78.23	Switch variable valve lift state (gen)	26720
78.24	Switch variable valve lift setpoint (gen)	26724
78.25	Switch variable valve lift OBDI (gen)	26726
78.26	Switch variable valve lift OBDII (gen)	26727
79	**VVTI-Variable Valve Timing**	**26730**
79.1	VVTI General	26731
79.2	VVTI Configuration data	26736
79.3	AGGR adaptation: VVTI	26750
79.4	IVVT scheduler	26752
79.5	IVVT state	26768
79.6	IVVT position	26789
79.7	IVVT reference position adaptation manager	26810
79.8	IVVT setpoint manager	26817
79.9	IVVT setpoint	26825
79.10	IVVT setpoint (Appl. Inc.)	26865
79.11	IVVT setpoint individual	26875
79.12	IVVT controller additional weighting	26892
79.13	IVVT controller	26895
79.14	IVVT delay time	26919
79.15	IVVT coil substitute temperature	26920
79.16	IVVT holding PWM	26923
79.17	IVVT deviation adaptation of holding PWM	26940
79.18	IVVT oil control valve cleaning	26955
79.19	IVVT (Appl. Inc.)	26965
79.20	VVT output signal diagnosis	26983
79.21	VVT output signal diagnosis (Appl. Inc.)	26992
79.22	VVT limp home manager	26994
79.23	VVT limp home manager (Appl. Inc.)	26998
79.24	VVT camshaft position deviation diagnosis at dynamic setpoint	27000

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

79.25	VVT camshaft position deviation diagnosis at dynamic SP (Appl. Inc.)	27014
79.26	VVT camshaft position deviation diagnosis at steady setpoint	27016
79.27	VVT camshaft position deviation diagnosis at steady SP (Appl. Inc.)	27032
79.28	VVT camshaft position deviation diagnosis at dynamic setpoint (ERR IF)	27041
79.29	VVT camshaft position deviation diagnosis at steady setpoint (ERR IF)	27046
79.30	VVT actuator failure emulation	27053
79.31	VVT actuator test (Appl. Inc.)	27063
80	**Appendix**	**27066**
80.1	Supplemental Information	27067

Copyright ©Continental AG. Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.