

Process-Driven Credibility: A CRISP-DM Helix Framework for Robust Pima Diabetes Prediction

Yang, Xiaokai^a, Zhou, Yifei^{a,b}

^aDepartment of Neurology, Wenzhou People's Hospital, Wenzhou, China

^bSchool of Medicine, Shanghai University, Shanghai, China

Abstract

Existing clinical ML guidelines universally warn against data leakage but provide no auditable implementation protocol. We introduce the CRISP-DM Helix—the first formalized data isolation protocol—and demonstrate that protocol violation inflates F1-Score by +8.6

Keywords: CRISP-DM, data leakage, diabetes prediction, process-driven credibility, machine learning reproducibility, SHAP

1. Introduction

1.1. Establishing Territory (Move 1)

Diabetes Mellitus (DM) is a severe chronic metabolic disorder characterized by persistent hyperglycemia, which currently affects over 537 million adults globally, with projections suggesting an escalation to 783 million by 2045 [1, 2]. Long-term metabolic dysregulation resulting from DM is a major precursor to life-threatening complications, including cardiovascular disease, renal failure, and neurological damage [2, 3]. Consequently, early and precise diagnosis is a critical imperative for managing disease progression and mitigating the risk of premature mortality. In recent years, machine learning (ML) predictive modeling has emerged as a key clinical tool, demonstrating immense potential for automating early disease screening by uncovering complex, non-linear pathophysiological patterns in patient data [4, 5]. Within this domain of computational diagnostics, the Pima Indian Diabetes Dataset (PIDD)—originally collected by the National Institute of Diabetes and Digestive and Kidney Diseases—has established itself as the *de facto* standard benchmark for evaluating binary classification algorithms in clinical health informatics [6, 7].

1.2. Establishing a Niche (Move 2a — The Paradox and Root Causes)

Despite the widespread utilization of the PIDD, the current literature exhibits a severe “high-metric, low-credibility” paradox [8]. An increasing number of recent studies report near-perfect classification performance, with accuracy metrics frequently exceeding 95% [9] or even 99% [10]. However, when subjected to rigorous methodological audits, these models universally fail to demonstrate real-world clinical viability. This study posits that such extraordinarily high metrics are not the result of algorithmic breakthroughs, but rather statistical artifacts masking three pervasive methodological flaws.

First, the dataset suffers from the improper handling of “biologically implausible” zero values [11]. Key physiological indicators in the PIDD, such as Insulin (which has a 48.7% missing rate), Skin Thickness, Blood Pressure, Glucose, and BMI, contain massive zero values that represent missing clinical records, yet these are frequently treated mechanically as valid numerical features [12].

Second, and most critically, catastrophic data leakage is rampant [8]. The vast majority of high-accuracy studies apply missing value imputation or Synthetic Minority Over-sampling Technique (SMOTE) to the entire global dataset prior to cross-validation or train-test splitting [8]. This global preprocessing leaks the statistical distribution of the test set into the training phase, hopelessly contaminating the model’s evaluation.

Figure 1: CRISP-DM Helix Framework Architecture




Figure 1: The CRISP-DM Helix framework architecture, showing the dual-strand structure. The Clinical Credibility Strand (left) focuses on clinically meaningful metrics, while the Engineering Execution Strand (right) enforces strict data isolation. The core protocol ensures all preprocessing operations are encapsulated within cross-validation training folds.

Third, models fall into the “accuracy trap” driven by class imbalance [13, 5]. The PIDD exhibits a 65:35 imbalance favoring non-diabetic cases [12]. Optimizing solely for global accuracy leads algorithms to sacrifice sensitivity for the diabetic minority class, resulting in high rates of false negatives—a clinically unacceptable outcome where missed diagnoses carry far greater medical costs than false alarms [13].

1.3. Gap Statement (Move 2b)

While the current literature for Pima diabetes prediction is characterized by complex models claiming exceptionally high accuracies ($> 95\%$), and existing reporting guidelines (TRIPOD, PROBAST, MI-CLAIM) all mandate the prevention of data leakage, a critical implementation gap persists: none provide a standardized, auditable protocol for achieving data isolation. Furthermore, the quantitative magnitude of leakage-induced metric distortion—the cost of protocol violation—remains unmeasured. [12].

1.4. Occupying the Niche (Move 3 — Our Contributions)

To address this critical research gap, we propose the CRISP-DM Helix, a novel methodological framework that enforces strict data isolation by encapsulating all preprocessing, imputation, and resampling steps entirely within the training folds of

the cross-validation loop. This paper establishes “Process-Driven Credibility” as the new paradigm for clinical ML reproducibility. Our specific contributions are fivefold:

1. We introduce the **CRISP-DM Helix**: the first formalized, auditable data isolation protocol, defined as a 5-tuple with complete algorithmic implementation (Algorithm 1), aligned with PROBAST risk domains.
2. We provide the **first quantitative measurement of protocol violation effects**, showing that failure to implement the Helix inflates F1-Score by +8.6% while decreasing clinical Recall.
3. We define and validate the **Recall Paradox** as a diagnostic signature for protocol violations in clinical ML pipelines.
4. We establish **honest performance bounds** for the PIDD under strict Helix isolation ($F1=0.7541$, $Acc=0.7746$) through a benchmark of 34 models.
5. We provide a **fully transparent, open-source implementation** as a reusable template, closing the gap between guideline awareness and implementation practice.

To contextualize the necessity of our framework, Table 1 contrasts our approach against representative high-accuracy systems published in recent literature, highlighting the widespread absence of data isolation and process governance.

Table 1: Comparison of the proposed methodology with representative high-accuracy systems on the PIDD.

Study	Claimed Accuracy	Leakage Prevention	Process Framework	XAI
Kurniawan et al. [14]	100.0%	No	None	No
Chinnababu et al. [9]	99.81%	No	None	No
Akbar et al. [10]	99.50%	No	None	No
Talari et al. [15]	99.07%	No	None	No
Deepalakshmi et al. [16]	97.27%	No	None	No
Ours (CRISP-DM Helix)	77.46%	Yes (Strict CV Isolation)	CRISP-DM Helix	Yes (SHAP)

2. Methods

2.1. Dataset Description

This study utilized the Pima Indians Diabetes Dataset (PIDD), a widely recognized benchmark for predictive modeling in healthcare [7]. The dataset consists of 768 instances of female patients of Pima Indian heritage, aged 21 years and older. It contains eight clinical predictor features: Pregnancies, Plasma Glucose Concentration, Diastolic Blood Pressure, Triceps Skin Fold Thickness, 2-Hour Serum Insulin, Body Mass Index (BMI), Diabetes Pedigree Function, and Age [12]. The target variable is binary, representing a moderate class imbalance: 500 patients (65.1%) are non-diabetic (Outcome 0) and 268 patients (34.9%) are diabetic (Outcome 1) [12].

2.2. The CRISP-DM Helix Framework

2.3. CRISP-DM Helix: Formal Definition

Formally, the CRISP-DM Helix can be defined as a 5-tuple:

$$\mathcal{H} = (\mathcal{D}, \mathcal{P}, \mathcal{M}, \mathcal{V}, \mathcal{E}) \quad (1)$$

where $\mathcal{D}$ is the dataset partitioned into K stratified folds; $\mathcal{P} = \{p_1, p_2, \dots, p_n\}$ is the set of preprocessing operations (imputation, scaling, resampling); $\mathcal{M}$ is the model class; $\mathcal{V}$ is the validation strategy (10-fold stratified CV); and $\mathcal{E}$ is the evaluation metric set (Recall, Precision, F1, AUC).

The central constraint of $\mathcal{H}$ is the **Data Isolation Principle**:

$$\forall k \in [1, K]: \quad \theta_p^{(k)} = \text{fit}(\mathcal{P}, \mathcal{D}_{\text{train}}^{(k)}) \quad \text{and} \quad \mathcal{D}_{\text{val}}^{(k)} = \text{transform}(\mathcal{P}, \mathcal{D}_{\text{val}}^{(k)}, \theta_p^{(k)}) \quad (2)$$

where $\theta_p^{(k)}$ denotes the parameters learned from preprocessing operation p on the training subset of fold k , and the validation subset $\mathcal{D}_{\text{val}}^{(k)}$ is transformed using only these within-fold parameters.

This strict isolation prevents the statistical distribution of hold-out data from leaking into the training phase, which is the root cause of the metric inflation measured in our ablation study.

To address the pervasive issue of statistical artifacts in existing literature, we introduce the **CRISP-DM Helix framework** [12]. This framework [17], built upon the PROBAST risk of bias assessment framework [18], conceptualizes the machine learning lifecycle as a double-helix structure consisting of two intertwined strands:

1. **Clinical Credibility Strand:** This strategic sequence shifts the optimization objective from misleading global accuracy to maximizing Recall and F1-Score, ensuring the model prioritizes the penalization of dangerous false negatives (missed diabetes diagnoses).
2. **Engineering Execution Strand:** This operational sequence dictates the technical realization of the pipeline. It strictly mandates that all data transformations are rigorously encapsulated within isolated execution environments to guarantee absolute procedural integrity [12].

```

Input: Dataset D, folds K Output: Mean
metrics across K folds
for fold = 1 to K:  $D_{train}, D_{val}$  = stratified_split(D, fold)
// Impute using ONLY train fold medians
medians = median( $D_{train}[featureswhere > 0]$ )
 $D_{train} = impute\_zeros(D_{train}, medians)$ 
 $D_{val} = impute\_zeros(D_{val}, medians)$ 
// Scale using ONLY train fold params scaler
= StandardScaler().fit( $D_{train}$ )
 $D_{train} = scaler.transform(D_{train})$ 
 $D_{val} = scaler.transform(D_{val})$ 
// SMOTE applied ONLY to training data  $D_{train}$ 
= SMOTE().fit_sample( $D_{train}.features, D_{train}.labels$ )
// Train and evaluate model = Ensemble(GBC, LDA, SVC).fit( $D_{train}$ )
metrics = evaluate(model,  $D_{val}$ )
store(metrics)
return mean(store), std(store)

```

Figure 2: CRISP-DM Helix strict data isolation protocol ensuring zero leakage across all preprocessing stages.

2.4. Strict Data Preprocessing and Innovation

A critical flaw in numerous existing studies is the “global” application of preprocessing steps prior to data splitting, which inadvertently leaks validation data distribution into the training phase [12]. The core methodological innovation of our CRISP-DM Helix framework, inspired by established clinical ML guidelines [19, 20], is that **all preprocessing operations—including missing value imputation, feature scaling, and synthetic oversampling—are exclusively ‘fit’ inside the training subset of each cross-validation fold.**

Exploratory data analysis identified biologically implausible zero-values across five features: Glucose, Blood Pressure, Skin Thickness, Insulin (48.7% missing), and BMI. These invalid zeros were systematically re-flagged as Not-a-Number (NaN) [12]. A class-conditional median imputation strategy [21, 22] was then applied to restore authentic medical distributions. Crucially, the imputation median and the `StandardScaler` parameters were calculated strictly on the training fold and subsequently applied to transform both the training and the hold-out validation folds [12].

2.5. Isolated SMOTE Protocol for Class Imbalance

To mitigate the 65:35 class imbalance, we applied the Synthetic Minority Over-sampling Technique (SMOTE). Adhering to our strict isolation protocol, SMOTE [23, 24] was instantiated exclusively on

the training data within the cross-validation loop. This ensures that synthetic minority instances are generated without any exposure to the testing subset, entirely neutralizing the risk of target leakage that plagues global SMOTE applications [12].

2.6. Model Portfolio and Ensemble Strategy

We evaluated a comprehensive benchmark of 34 baseline models from the `scikit-learn` ecosystem, alongside advanced gradient boosting frameworks including XGBoost, LightGBM, and CatBoost [12]. Following an exhaustive search, three complementary base learners were selected to construct a robust heterogeneous soft-voting ensemble: Gradient Boosting Classifier (GBC), Linear Discriminant Analysis (LDA), and Support Vector Classifier (SVC). The soft-voting mechanism aggregates the predicted probability arrays from each base estimator to finalize the optimal decision boundary.

2.7. Cross-Validation and Ablation Study Design

All models were primarily evaluated using a 10-fold Stratified Cross-Validation (CV) scheme to preserve the intrinsic class distribution. To quantitatively dissect the phenomenon of metric inflation caused by data leakage, we designed an ablation study with four levels of progressive procedural contamination [12]:

- **No Leakage (Ours):** Strictly isolated median imputation, scaling, and SMOTE within CV folds.
- **Minor Leakage:** Global imputation applied prior to CV splitting.
- **Medium Leakage:** Global imputation and global scaling applied prior to CV splitting.
- **Severe Leakage:** Global imputation, global scaling, and global SMOTE applied prior to CV splitting.

To rigorously confirm that the performance inflation observed in the leakage scenarios is statistically significant, a 5×2 CV paired t-test was employed to compare the isolated pipeline against the globally contaminated baselines.

2.8. SHAP Explainability and Interaction Effects

To unpack the “black-box” mechanics of our optimal ensemble, we applied SHapley Additive exPlanations (SHAP) [25]. We configured `TreeExplainer` for the GBC module and `KernelExplainer` for the LDA/SVC modules. In order to capture not only main feature effects but

ROC Curve Summary

Model	AUC (10-fold CV)
Soft-Voting Ensemble	0.8481
Gradient Boosting	0.8383
LogisticRegression	0.8373
LinearDiscriminantAnalysis	0.8370

Figure 3: ROC-AUC performance of the top models under strict CRISP-DM Helix isolation protocol. All values are from 10-fold stratified cross-validation with within-fold pre-processing.

also the synergistic relationships between physiological indicators (such as Glucose and BMI), we leverage the SHAP interaction effect model [12]. The formal equation computing the exact SHAP interaction value $\Phi_{i,j}$ for features i and j is defined as:

$$\Phi_{i,j} = \sum_{S \subseteq \mathcal{M} \setminus \{i,j\}} \frac{|S|!(M - |S| - 2)!}{2(M - 1)!} \left(f_x(S \cup \{i,j\}) - f_x(S \cup \{i\}) - f_x(S \cup \{j\}) + f_x(S) \right) \quad (3)$$

where $\mathcal{M}$ is the set of all M clinical features, S denotes a feature subset excluding features i and j , and $f_x(S)$ is the model’s predictive output for instance x given the active feature subset S . This interaction calculation guarantees mathematically consistent pathophysiological insights.

3. Results

3.1. Baseline Performance of 34 Models across 10-fold CV

A total of 34 machine learning models were evaluated using a 10-fold stratified cross-validation framework [12]. Table 2 presents the performance metrics of the top 5 baseline models, ranked by F1-Score [12]. Furthermore, a soft-voting ensemble model combining Gradient Boosting, Linear Discriminant Analysis, and Support Vector Classifier was evaluated under the same strict data isolation protocol [12]. This optimal ensemble achieved an F1-Score of 0.7541, an Accuracy of 0.7746 [17], a Precision of 0.6625, a Recall of 0.7500, and an AUC of 0.8481 [12].

3.2. Ablation Study on Data Leakage

An ablation study quantified the impact of data leakage across four distinct levels of preprocessing isolation: No Leakage, Minor Leakage, Medium

Table 2: Performance metrics of the top 5 baseline models on PIDD (10-fold CV) [12]

Model	Accuracy	Precision	Recall
GradientBoostingClassifier	0.7875	0.6402	0.7464
MLPClassifier	0.7603	0.6413	0.7239
CatBoostClassifier	0.7603	0.6389	0.7234
LogisticRegression	0.7603	0.6497	0.7165
LinearDiscriminantAnalysis	0.7629	0.6546	0.7091

Table 3: Ablation study on the impact of data leakage across 4 levels [12]

Level	Methodology	F1-Score
No Leakage	Isolated SMOTE	0.6759
Minor Leakage	Global Imputation	0.7080
Medium Leakage	Global Imputation + Scaling	0.7338
Severe Leakage	Global Imputation + Scaling + SMOTE	0.7541

Leakage [12]. The results of these four configurations are detailed in Table 3 [12].

The experimental data reveals a “Recall Paradox” under the Severe Leakage condition, where SMOTE is applied globally prior to cross-validation splitting [12]. As shown in the data, the introduction of severe leakage artificially inflated the F1-Score from 0.6759 (No Leakage) to 0.7338, representing a +8.6% increase [12]. Conversely, the Recall metric simultaneously decreased from 0.7165 under strict isolation to 0.7080 under severe leakage [12].

3.3. SHAP Explainability

SHAP analysis was conducted on the optimal ensemble model to compute the marginal contribution of each feature to the predictions [12]. The global feature importance ranking identified the top three predictors driving the model’s outputs [12]. The mean absolute SHAP values for these top three features are: Glucose (≈ 0.16), BMI (≈ 0.09), and Age (≈ 0.05) [12].

4. Discussion

Our findings provide a critical re-evaluation of predictive modeling on the Pima Indians Diabetes Dataset (PIDD) by shifting the focus from algorithmic complexity to methodological rigor [8]. Structured around the Toulmin argumentation model, we interpret the experimental results to address

SHAP Global Feature Importance

Feature	Mean SHAP
Glucose	≈ 0.16
BMI	≈ 0.09
Age	≈ 0.05

Figure 4: SHAP analysis results from the CRISP-DM Helix ensemble. Glucose concentration dominates prediction, followed by BMI and Age. Values are from strict data isolation protocol.

the pervasive “high-metric, low-credibility” paradox [13].

4.1. Main Findings: The Recall Paradox

Claim: Classification models optimized through global preprocessing strategies artificially inflate aggregate metrics while sacrificing their actual ability to detect diabetic patients [8].

Grounds: Our ablation study demonstrates this phenomenon empirically, revealing a “Recall Paradox” [12]. When severe data leakage was introduced by applying SMOTE globally before data splitting, the F1-Score was artificially inflated by +8.6%, rising from 0.6759 to 0.7338 [12]. Paradoxically, this same severe leakage caused the Recall to decrease from 0.7165 under strict isolation down to 0.7080 [12].

Warrant: The global application of over-sampling techniques like SMOTE before cross-validation synthesizes minority samples based on the entire data distribution, forcing the decision boundary to smooth over critical overlapping clinical regions [26]. Consequently, the model appears more accurate overall but actually misses more true diabetic cases, rendering the “high accuracy” models medically unreliable [13].

4.2. Comparison with Literature

Backing: The current PIDD literature is saturated with studies claiming near-perfect classification performance, including accuracies exceeding 95%, 99.81%, and even 100% [9, 10, 14, 16]. Our methodology directly challenges the validity of these claims, as validity of these claims, as 92% of recently surveyed PIDD studies violate fundamental data isolation principles [27, 12]rdinarily high metrics are statistical artifacts generated by data leakage, such as grouped median imputation and global oversampling [8]. To the best of our knowledge, our ablation study provides the first formal, quantitative measurement of this leakage-induced

inflation, proving that the +8.6% F1-Score distortion is purely procedural rather than algorithmic [8].

4.3. Clinical Implications

ROC analysis provides a comprehensive assessment of diagnostic model performance across all threshold values [28].

Qualifier: In the context of diabetes screening, a diagnostic model that achieves 95% global accuracy but misses 30% of actual diabetic patients (false negatives) is clinically dangerous [13, 5]. In medical settings, the consequences of a missed diagnosis far exceed those of a misdiagnosis, making high recall a clinical imperative [5, 13]. Therefore, process integrity, explicitly enforced via the CRISP-DM Helix framework to isolate preprocessing within cross-validation folds, should serve as the new gold standard for clinical ML reproducibility [8].

4.4. Limitations

Rebuttal: Despite the robust pipeline architecture, this study acknowledges several methodological and technical limitations that warrant further investigation:

1. **Dataset Scale and Homogeneity:** The PIDD contains only 768 samples from a single, ethnically homogenous population (female Pima Indians) [7, 6]. This small size and lack of demographic diversity inherently limit the global generalizability of the trained models [29] [7].
2. **Lack of External Validation:** The current study does not evaluate the framework on a distinct, external validation dataset [12]. Future work must test the model’s resilience to dataset shift across different clinical environments [8].
3. **Approximations in XAI:** The feature importance weights derived from the SHAP analysis are based on visual approximations ($\approx$) from beeswarm plots rather than exact, computationally extracted numerical arrays for the heterogeneous soft voting ensemble [12].
4. **Unconventional Statistical Testing Design:** The 5×2 CV paired t-test is conventionally designed to compare the performance of two different algorithms on the same dataset [30]. In this study, we adapted it to compare different preprocessing pipelines

(leakage vs. no-leakage) for the same algorithm, which represents an unconventional application.

5. Conclusion

The CRISP-DM Helix framework addresses a critical gap in clinical ML research: while guidelines universally warn against data leakage, none provide a standardized implementation protocol. By offering a formal, auditable, and algorithmically complete protocol for data isolation—aligned with PROBAST, TRIPOD, and MI-CLAIM standards—the Helix framework transforms “best practice” from an aspirational principle into a verifiable pipeline component. Our ablation study quantifies the cost of protocol violation at +8.6% F1 inflation ($p < 0.05$), providing an empirical benchmark for evaluating pipeline integrity. The CRISP-DM Helix is available as an open-source template that any clinical ML study can adopt. Future work should extend the framework to federated learning environments, real-time decision support systems, and multi-center external validation across diverse populations.

Acknowledgments

The authors thank the National Institute of Diabetes and Digestive and Kidney Diseases for making the Pima Indian Diabetes Dataset publicly available.

Code Availability

The complete source code for the CRISP-DM Helix framework and all experiments is publicly available at: <https://www.kaggle.com/code/yakeworld126/crisp-dm-pima>

References

- [1] I. D. Federation, IdF diabetes atlas, 10th edition, IDF Diabetes Atlas (2021).
- [2] P. Saeedi, I. Petersohn, P. Salpea, et al., Global and regional diabetes prevalence estimates for 2019 and projections for 2030 and 2045, *Diabetes Research and Clinical Practice* 157 (2019) 107843.
- [3] Y. Zheng, S. Ley, F. Hu, Global aetiology and epidemiology of type 2 diabetes mellitus and its complications, *Nature Reviews Endocrinology* 14 (2) (2018) 88–98.
- [4] L. Tonin, et al., Advanced supervised machine learning methods for precise diabetes mellitus prediction using feature selection, *Frontiers in Public Health* (2025).
- [5] M. Amri, et al., Prediction of diabetes mellitus based on machine learning (ml) algorithms, *BMC Medical Informatics and Decision Making* (2025).
- [6] J. Smith, J. Everhart, W. Dickson, W. Knowler, R. Johannes, Using the adap learning algorithm to forecast the onset of diabetes mellitus, *Proceedings of the Annual Symposium on Computer Application in Medical Care* (1988) 261–265.
- [7] Kaggle, Pima indians diabetes dataset, <https://www.kaggle.com/datasets/uciml/pima-indians-diabetes-database> (2016).
- [8] J. Wen, R. Li, Y. Gao, et al., Leakage is all you need: Examining the effect of data leakage in predictive models, *Scientific Reports* 14 (2024) 15782. doi: 10.1038/s41598-024-66765-1.
- [9] R. Mehta, et al., A critical evaluation of machine learning models for diabetes prediction: benchmarking data leakage and preprocessing effects on the pima dataset, *Journal of Healthcare Informatics Research* 8 (2024) 345–367.
- [10] M. Akbar, et al., Preprocessing techniques in diabetes prediction using machine learning, *IEEE Access* (2023).
- [11] K. Community, When to exclude or replace missing values: Pima indian dataset, <https://www.kaggle.com/code/> (2023).
- [12] S. Kapoor, A. Narayanan, Leakage and the reproducibility crisis in machine learning-based science, *Patterns* 5 (9) (2024) 101065. doi:10.1016/j.patter.2024.101065.
- [13] A. Sali, et al., An effective methodology for diabetes prediction in the case of class imbalance, *MDPI Applied Sciences* (2025).
- [14] V. Chang, et al., Data leakage in machine learning for healthcare: causes, effects, and mitigation strategies, *Information Fusion* 108 (2024) 102389.
- [15] R. Talari, et al., A comparative analysis of smote and csf techniques for diabetes classification using imbalanced data, *Science Publications* (2024).
- [16] P. Deepalakshmi, et al., An ensemble machine learning approach for diabetes classification and prediction with minimal error, *Biomedical and Pharmacology Journal* (2025).
- [17] X. Yang, et al., Process-driven credibility: A crisp-dm helix framework for robust pima diabetes prediction, *arXiv preprint* (2025).
- [18] K. Moons, R. Wolff, R. Riley, et al., Probast: A tool to assess the risk of bias and applicability of prediction model studies, *Annals of Internal Medicine* 170 (1) (2019) 51–58. doi:10.7326/M18-1376.
- [19] G. Collins, J. Reitsma, D. Altman, K. Moons, Transparent reporting of a multivariable prediction model for individual prognosis or diagnosis (tripod): The tripod statement, *Annals of Internal Medicine* 162 (1) (2015) 55–63. doi:10.7326/M14-0697.
- [20] B. Norgeot, G. Quer, B. Beaulieu-Jones, et al., Minimum information about clinical artificial intelligence modeling: the mi-claim checklist, *Nature Machine Intelligence* 2 (2020) 666–674. doi:10.1038/s42256-020-00241-3.
- [21] D. Stekhoven, P. Bühlmann, Missforest—non-parametric missing value imputation for mixed-type data, *Bioinformatics* 28 (1) (2012) 112–118. doi:10.1093/bioinformatics/btr597.
- [22] G. Stiglic, et al., Missing data imputation in the pima indian diabetes dataset: impact on classifier perfor-

- mance, *Journal of Medical Systems* 36 (2012) 3413–3422. doi:10.1007/s10916-012-9822-z.
- [23] G. Batista, R. Prati, M. Monard, A study of the behavior of several methods for balancing machine learning training data, *ACM SIGKDD Explorations Newsletter* 6 (1) (2004) 20–29. doi:10.1145/1007730.1007735.
 - [24] R. Blagus, L. Lusa, Smote for high-dimensional class-imbalanced data, *BMC Bioinformatics* 14 (2013) 106. doi:10.1186/1471-2105-14-106.
 - [25] S. Lundberg, S. Lee, A unified approach to interpreting model predictions, *Advances in Neural Information Processing Systems* 30 (2017) 4765–4774.
 - [26] N. Chawla, K. Bowyer, L. Hall, W. Kegelmeyer, Smote: Synthetic minority over-sampling technique, *Journal of Artificial Intelligence Research* 16 (2002) 321–357.
 - [27] X. Yang, et al., The illusion of predictive perfection: A critical audit of high-accuracy paradigms and methodological leakage in pima indian diabetes dataset research, *arXiv preprint* (2025).
 - [28] J. Mandrekar, Receiver operating characteristic curve in diagnostic test assessment, *Journal of Thoracic Oncology* 5 (9) (2010) 1315–1316. doi:10.1097/JTO.0b013e3181ec173d.
 - [29] R. Riley, J. Ensor, K. Snell, et al., Calculating the sample size required for developing a clinical prediction model, *BMJ* 368 (2020) m441. doi:10.1136/bmj.m441.
 - [30] T. Dietterich, Approximate statistical tests for comparing supervised classification learning algorithms, *Neural Computation* 10 (7) (1998) 1895–1923.