Tutorial - Week 2

Objectives: To practice with

- user defined functions

- 1. Considering the general structure of a C program. Indicate an appropriate place for:
 - -function prototypes
 - -function definitions
 - -function calls

```
#include <stdio.h>
#define PI 3.141

Function prototypes

int main(void)
{

Function calls

return 0;
}
```

2. Find and correct errors in the following function definitions

```
a. void add2Numbers( int num1, int num2)
{
    int num1; int sum;

    sum = num1 + num2;
    return sum;
}

b. int sum2Num( int num1, int num2 );
{
    int sum;

    sum = num1 * num2;
    return ;
}
```

- a. 1) Wrong re-declaration of the formal parameter num1; a variable can be declared only ONCE within its own scope and C supports five variable scopes, see slide 16 of lecture 2
 - 2) The return type of the function should be int.
- b. 1) The semicolon at the end of the function header should be omitted.
 - 2) The function does not return an integer result as its return type indicates.
 - 3) The function name does not match its purpose (not an error but not a good practice).

See further remarks at the end of this document.

3. Find errors in the following function prototypes:

```
a. int sum (int x, y, z);
b. int sum (int, int, int);
c. int sum (void, int y, int z);
```

- a. Error, data types for variables y and z are missing
- b. No error
- c. Error, void cannot be a formal parameter among more; it is used, it should be the only function parameter.

4. Considering the following function prototype:

```
int findMax(int num1, int num2, int num3);
```

Write a function call to find the maximum value among three numbers inputA, inputB and 1000.

```
int inputA, inputB, maxValue;
.....
maxValue = findMax (inputA, inputB, 1000);
```

5. Sound level is commonly measured in decibels (dB)

```
Sound level = 20*log_{10}(sp/rp)
```

where:

sp is a measured sound pressure

rp is a reference pressure (the sensitivity of human ear 20*10⁻⁶ Pa)

Provide a function prototype and its definition that calculates the sound level based on the sound pressure measured. Provide an example of the function call.

```
#define REF_PRES 20.0e-6

float getDbLevel ( float sountPressure );
```

```
soundLevel = getDbLevel( measuredSdPress );

float getDbLevel ( float sountPressure )

float soundLev;

soundLev = 20.0*log10( soundPressure / REF_PRES );

return soundLev;
}
```

Math.h library should be used

6. Write statements that compute and display the absolute difference of two type double variables, x and y (|x-y|).

7. Write a complete C program that prompts the user for the coordinates of two 3-D points (x_1, y_1, z_1) and (x_2, y_2, z_2) and displays the distance between them computed using the following formula:

```
#include <math.h>
int
main (void)
   double x1, y1, z1, x2, y2, z2, distance;
   /* Get the coordinates. */
   printf("Enter the first set of x y z coordinates> ");
   scanf("%lf%lf%lf", &x1, &y1, &z1);
   printf("Enter the second set of x y z coordinates> ");
   scanf("%lf%lf%lf", &x2, &y2, &z2);
   /* Compute the distance. */
   distance = sqrt(pow(x1 - x2, 2) + pow(y1 - y2, 2) + pow(z1 - y2, 2)
   z2, 2));
   /* Display the result. */
   printf("The distance between (%.2f, %.2f, %.2f) and (%.2f, %.2f)
   \$.2f) is \$.2f.\n", x1, y1, z1, x2, y2, z2, distance);
  return (0);
}
```

8. If an actual argument of -35.7 is passed to a type int formal parameter, what will happen? If an actual argument of 17 is passed to a type double formal parameter, what will happen?

The formal parameter's value will be -35. The formal parameter's value will be 17.0.

9. Write the prototype for a function called script that has three input parameters. The first parameter will be the number of spaces to display at the beginning of a line. The second parameter will be the character to display after the spaces, and the third parameter will be the number of times to display the second parameter on the same line.

```
int script(int num spaces, char char to display, int num of chars);
```

10. Write a function that computes the time one must leave in order to reach a certain destination by a designated time. You need to deal only with arrivals occurring later in the same day as the departure. Function inputs include the arrival time as an integer on a 24-hour clock (8:30 P.M. = 2030), the distance to the destination in kilometers, and the speed you plan to average in km/h. The function result should be the required departure time (rounded to the nearest minute) as an integer on a 24-hour clock. Also, write a driver program to test your function.

```
* Computes the departure time required to reach a destination that
* is a given (positive) distance away, based on supplied arrival
* time and estimated average speed. Arrival must be on same day
  * as departure.
#include <stdio.h>
/* function prototype */
int find departure time (int arr time, float distance, float speed);
int main(void)
  float distance, /* input--distance traveled (km) */
        avg speed; /* input--anticipated average speed (km/hr) */
   int dep time; /* output--required departure time */
  /* Get arrival time */
  printf("Enter arrival time as integer on a 24 hour clock. For
          example,");
  printf("\n8:30 PM would be entered as 2030\n");
  printf("Arrival time> ");
  scanf("%d", &arr time);
  /* Now get the distance to travel and anticipated average speed*/
  printf("Enter the distance in km> ");
  scanf("%f", &distance);
  printf("Enter anticipated average speed (including stops) in
          km/hr> ");
  scanf("%f", &avg speed);
  /* Compute and display the required departure time. */
  dep time = find departure time(arr time, distance, avg speed);
  printf("You need to leave at %d.\n", dep time );
  return (0);
```

```
}
/*
* Returns the departure time required to travel distance
* given arrival time (arr_time) and speed.
* Pre: dist/speed <= arr time converted to hours since midnight
 * (i.e., arrival is same day as departure)
*/
int
find departure time (int arr time, float distance, float speed)
  int journey_min,
                   /* travel time in minutes (rounded) */
  arr min,
                /* total minutes to arrival time */
  /* hour of departure (24-hr clock) */
  dep hr,
           /* minutes of departure time */
  dep min,
  dep_time; /* departure time (24-hr clock) */
  journey = 60*distance / speed;
  journey min = (int)(journey + 0.5); /* rounding */
  arr min = arr time / 100 * 60 + arr time % 100;
  dep time min = arr min - journey min;
  dep hr = dep time min / 60;
  dep min = dep time min % 60;
  dep time = dep hr * 100 + dep min;
   return (dep time);
 }
```