Class 10: Structural Bioinformatics (pt.1)

Yasmeen Al Shakarchi (PID: A18116120)

Table of contents

The PDB database 1
Using Molstar 2
The Bio3D package for structural bioinformatiocs 4
Quick viewing of PDBs 6
Predicition of Protein flexibliy 6
Comparative protein structure analysis with PCA 7

The PDB database

The Protein Data Bank (PDB) is the main repository of biomolecular structure data. Let's see what is in it:

> Q1: What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy.

Answer: X-ray is 80.9%/ 81%, where EM is 12.8%/ 13%.

> Q2: What proportion of structures in the PDB are protein?

Answer: 214078

```
stats <- read.csv("pdbstats26", row.names =1)
stats
```

```
                        X.ray    EM   NMR Integrative Multiple.methods Neutron
Protein (only)         178795 21825 12773         343              226      84
Protein/Oligosaccharide  10363  3564    34           8               11       1
Protein/NA                9106  6335   287          24                7       0
Nucleic acid (only)       3132   221  1566           3               15       3
```

```
Other                       175    25    33           4                 0       0
Oligosaccharide (only)       11     0     6           0                 1       0
                         Other  Total
Protein (only)              32 214078
Protein/Oligosaccharide      0  13981
Protein/NA                   0  15759
Nucleic acid (only)          1   4941
Other                        0    237
Oligosaccharide (only)       4     22
```

```r
n.sums <- colSums(stats)
n <- n.sums/n.sums["Total"]
round(n, digits = 2)
```

```
           X.ray               EM              NMR      Integrative
            0.81             0.13             0.06             0.00
Multiple.methods          Neutron            Other            Total
            0.00             0.00             0.00             1.00
```

What is the total number of entries in the PDB?

```r
n.sums["Total"]
```

```
 Total
249018
```

Answer: There is 249018.

Using Molstar

We can use the main Molstar viewer online:



Figure 1: First view of HIV-Pr dimer with bound inhibitor

Q. Generate and insert an image of the HIV-Pr cartoon colored by secondary structure, showing the inhibitor (ligand) in ball and stick.

Q. One final image showing catalytic APS 25 and the all-important active site water molecule.



(Both of these questions is answered from this picture, made sure with the TA)

The Bio3D package for structural bioinformatiocs

```
library(bio3d)

hiv <- read.pdb("1hsg")
```

```
  Note: Accessing on-line PDB file
```

```
hiv
```

```
 Call:  read.pdb(file = "1hsg")

   Total Models#: 1
     Total Atoms#: 1686,  XYZs#: 5058  Chains#: 2  (values: A B)
```

```
     Protein Atoms#: 1514  (residues/Calpha atoms#: 198)
     Nucleic acid Atoms#: 0  (residues/phosphate atoms#: 0)

     Non-protein/nucleic Atoms#: 172  (residues: 128)
     Non-protein/nucleic resid values: [ HOH (127), MK1 (1) ]

   Protein sequence:
      PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD
      QILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFPQITLWQRPLVTIKIGGQLKE
      ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP
      VNIIGRNLLTQIGCTLNF

+ attr: atom, xyz, seqres, helix, sheet,
        calpha, remark, call
```

```r
head(hiv$atom)
```

```
  type eleno elety  alt resid chain resno insert      x      y     z o     b
1 ATOM     1     N <NA>   PRO     A     1   <NA> 29.361 39.686 5.862 1 38.10
2 ATOM     2    CA <NA>   PRO     A     1   <NA> 30.307 38.663 5.319 1 40.62
3 ATOM     3     C <NA>   PRO     A     1   <NA> 29.760 38.071 4.022 1 42.64
4 ATOM     4     O <NA>   PRO     A     1   <NA> 28.600 38.302 3.676 1 43.40
5 ATOM     5    CB <NA>   PRO     A     1   <NA> 30.508 37.541 6.342 1 37.87
6 ATOM     6    CG <NA>   PRO     A     1   <NA> 29.296 37.591 7.162 1 38.40
  segid elesy charge
1  <NA>     N   <NA>
2  <NA>     C   <NA>
3  <NA>     C   <NA>
4  <NA>     O   <NA>
5  <NA>     C   <NA>
6  <NA>     C   <NA>
```

```r
pdbseq(hiv)
```

```
  1   2   3   4   5   6   7   8   9  10  11  12  13  14  15  16  17  18  19  20
"P" "Q" "I" "T" "L" "W" "Q" "R" "P" "L" "V" "T" "I" "K" "I" "G" "G" "Q" "L" "K"
 21  22  23  24  25  26  27  28  29  30  31  32  33  34  35  36  37  38  39  40
"E" "A" "L" "L" "D" "T" "G" "A" "D" "D" "T" "V" "L" "E" "E" "M" "S" "L" "P" "G"
 41  42  43  44  45  46  47  48  49  50  51  52  53  54  55  56  57  58  59  60
"R" "W" "K" "P" "K" "M" "I" "G" "G" "I" "G" "G" "F" "I" "K" "V" "R" "Q" "Y" "D"
 61  62  63  64  65  66  67  68  69  70  71  72  73  74  75  76  77  78  79  80
```

```
"Q" "I" "L" "I" "E" "I" "C" "G" "H" "K" "A" "I" "G" "T" "V" "L" "V" "G" "P" "T"
 81  82  83  84  85  86  87  88  89  90  91  92  93  94  95  96  97  98  99   1
"P" "V" "N" "I" "I" "G" "R" "N" "L" "L" "T" "Q" "I" "G" "C" "T" "L" "N" "F" "P"
  2   3   4   5   6   7   8   9  10  11  12  13  14  15  16  17  18  19  20  21
"Q" "I" "T" "L" "W" "Q" "R" "P" "L" "V" "T" "I" "K" "I" "G" "G" "Q" "L" "K" "E"
 22  23  24  25  26  27  28  29  30  31  32  33  34  35  36  37  38  39  40  41
"A" "L" "L" "D" "T" "G" "A" "D" "D" "T" "V" "L" "E" "E" "M" "S" "L" "P" "G" "R"
 42  43  44  45  46  47  48  49  50  51  52  53  54  55  56  57  58  59  60  61
"W" "K" "P" "K" "M" "I" "G" "G" "I" "G" "G" "F" "I" "K" "V" "R" "Q" "Y" "D" "Q"
 62  63  64  65  66  67  68  69  70  71  72  73  74  75  76  77  78  79  80  81
"I" "L" "I" "E" "I" "C" "G" "H" "K" "A" "I" "G" "T" "V" "L" "V" "G" "P" "T" "P"
 82  83  84  85  86  87  88  89  90  91  92  93  94  95  96  97  98  99
"V" "N" "I" "I" "G" "R" "N" "L" "L" "T" "Q" "I" "G" "C" "T" "L" "N" "F"
```

Let's try out the new **bio3dview** package that is not yet in CRAN We can use the **remotes** package to install any R package from GitHub.

Quick viewing of PDBs

```r
library(bio3dview)

#view.pdb(hiv, backgroundColor = "pink")
```

```r
library(bio3dview)

sele <- atom.select(hiv, resno=25)

#view.pdb(hiv, backgroundColor = "pink",
 #        highlight =sele,
 #        highlight.style = "spacefill")
```

Predicition of Protein flexibliy

```r
adk <- read.pdb("6s36")
```

```
  Note: Accessing on-line PDB file
   PDB has ALT records, taking A only, rm.alt=TRUE
```

```r
m <- nma(adk)
```

```
 Building Hessian...        Done in 0.012 seconds.
 Diagonalizing Hessian...   Done in 0.053 seconds.
```

```r
plot(m)
```



In the last plot the highest point sis the most flexible areas.

Write out our results as a wee trajectory movie:

```r
mktrj(m, file="results.pdb")
```

```r
#view.nma(m)
```

Comparative protein structure analysis with PCA

we start with a data base id "1ake_A"

```r
library(bio3d)

id <- "1ake_A"
aa <- get.seq("1ake_A")
```

```
Warning in get.seq("1ake_A"): Removing existing file: seqs.fasta

Fetching... Please wait. Done.
```

```r
aa
```

```
              1        .         .         .         .         .         60
pdb|1AKE|A   MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMLRAAVKSGSELGKQAKDIMDAGKLVT
              1        .         .         .         .         .         60

             61        .         .         .         .         .         120
pdb|1AKE|A   DELVIALVKERIAQEDCRNGFLLDGFPRTIPQADAMKEAGINVDYVLEFDVPDELIVDRI
             61        .         .         .         .         .         120

            121        .         .         .         .         .         180
pdb|1AKE|A   VGRRVHAPSGRVYHVKFNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQMTAPLIG
            121        .         .         .         .         .         180

            181        .         .         .   214
pdb|1AKE|A   YYSKEAEAGNTKYAKVDGTKPVAEVRADLEKILG
            181        .         .         .   214

Call:
  read.fasta(file = outfile)

Class:
  fasta

Alignment dimensions:
  1 sequence rows; 214 position columns (214 non-gap, 0 gap)

+ attr: id, ali, call
```

```r
blast <- blast.pdb(aa)
```

```
 Searching ... please wait (updates every 5 seconds) RID = STT64FCE014
 .
 Reporting 96 hits
```

Have a wee peak:

```r
head( blast$hit.tbl)
```

```
        queryid subjectids identity alignmentlength mismatches gapopens q.start
1 Query_1901899     1AKE_A  100.000             214          0        0       1
2 Query_1901899     8BQF_A   99.533             214          1        0       1
3 Query_1901899     4X8M_A   99.533             214          1        0       1
4 Query_1901899     6S36_A   99.533             214          1        0       1
5 Query_1901899     9R6U_A   99.533             214          1        0       1
6 Query_1901899     9R71_A   99.533             214          1        0       1
  q.end s.start s.end    evalue bitscore positives mlog.evalue pdb.id    acc
1   214       1   214 1.78e-156      432    100.00    358.6267 1AKE_A 1AKE_A
2   214      21   234 2.91e-156      433    100.00    358.1351 8BQF_A 8BQF_A
3   214       1   214 3.18e-156      432    100.00    358.0464 4X8M_A 4X8M_A
4   214       1   214 4.67e-156      432    100.00    357.6621 6S36_A 6S36_A
5   214       1   214 1.04e-155      431     99.53    356.8615 9R6U_A 9R6U_A
6   214       1   214 1.23e-155      431     99.53    356.6937 9R71_A 9R71_A
```

```r
hits <- plot(blast)
```

```
  * Possible cutoff values:    260 3
            Yielding Nhits:    20 96

  * Chosen cutoff value of:    260
            Yielding Nhits:    20
```



Peak at our "top hits"

```
head(hits$pdb.id)
```

```
[1] "1AKE_A" "8BQF_A" "4X8M_A" "6S36_A" "9R6U_A" "9R71_A"
```

Now we can download these "top hits" these will all be ADK steuctures in the PDB database.

```
files <- get.pdb(hits$pdb.id, path="pdbs", split = TRUE, gzip = TRUE)
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1AKE.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/8BQF.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4X8M.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6S36.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/9R6U.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/9R71.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/8Q2B.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/8RJ9.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6RZE.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4X8H.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3HPR.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4V.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/5EJE.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4Y.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3X2S.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAP.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAM.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/8PVW.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4K46.pdb.gz exists. Skipping download

Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4NP6.pdb.gz exists. Skipping download


  |
  |                                                                      |   0%
  |
  |====                                                                  |   5%
  |
  |=======                                                               |  10%
  |
  |==========                                                            |  15%
  |
  |==============                                                        |  20%
  |
  |==================                                                    |  25%
  |
  |======================                                                |  30%
  |
  |========================                                              |  35%
  |
  |============================                                          |  40%
  |
  |================================                                      |  45%
  |
  |====================================                                  |  50%
  |
  |========================================                              |  55%
  |
  |============================================                          |  60%
  |
  |================================================                      |  65%
  |
  |====================================================                  |  70%
  |
  |========================================================              |  75%
```

```
  |
  |=========================================================             |  80%
  |
  |==============================================================        |  85%
  |
  |=================================================================     |  90%
  |
  |====================================================================  |  95%
  |
  |======================================================================| 100%
```

We need one package from BioConductor. To set this up we need to first install a package called **Biocmanager** from CRAN.

Now we can use the `install()` function from this package like this: `BiocManager::install("msa")`

```r
pdbs <- pdbaln(files, fit = TRUE, exefile="msa")
```

```
Reading PDB files:
pdbs/split_chain/1AKE_A.pdb
pdbs/split_chain/8BQF_A.pdb
pdbs/split_chain/4X8M_A.pdb
pdbs/split_chain/6S36_A.pdb
pdbs/split_chain/9R6U_A.pdb
pdbs/split_chain/9R71_A.pdb
pdbs/split_chain/8Q2B_A.pdb
pdbs/split_chain/8RJ9_A.pdb
pdbs/split_chain/6RZE_A.pdb
pdbs/split_chain/4X8H_A.pdb
pdbs/split_chain/3HPR_A.pdb
pdbs/split_chain/1E4V_A.pdb
pdbs/split_chain/5EJE_A.pdb
pdbs/split_chain/1E4Y_A.pdb
pdbs/split_chain/3X2S_A.pdb
pdbs/split_chain/6HAP_A.pdb
pdbs/split_chain/6HAM_A.pdb
pdbs/split_chain/8PVW_A.pdb
pdbs/split_chain/4K46_A.pdb
pdbs/split_chain/4NP6_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..   PDB has ALT records, taking A only, rm.alt=TRUE
```

```
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..   PDB has ALT records, taking A only, rm.alt=TRUE
..   PDB has ALT records, taking A only, rm.alt=TRUE
....   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..

Extracting sequences

pdb/seq: 1   name: pdbs/split_chain/1AKE_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 2   name: pdbs/split_chain/8BQF_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 3   name: pdbs/split_chain/4X8M_A.pdb
pdb/seq: 4   name: pdbs/split_chain/6S36_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 5   name: pdbs/split_chain/9R6U_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 6   name: pdbs/split_chain/9R71_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 7   name: pdbs/split_chain/8Q2B_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 8   name: pdbs/split_chain/8RJ9_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 9   name: pdbs/split_chain/6RZE_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 10   name: pdbs/split_chain/4X8H_A.pdb
pdb/seq: 11   name: pdbs/split_chain/3HPR_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 12   name: pdbs/split_chain/1E4V_A.pdb
pdb/seq: 13   name: pdbs/split_chain/5EJE_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 14   name: pdbs/split_chain/1E4Y_A.pdb
pdb/seq: 15   name: pdbs/split_chain/3X2S_A.pdb
pdb/seq: 16   name: pdbs/split_chain/6HAP_A.pdb
pdb/seq: 17   name: pdbs/split_chain/6HAM_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 18   name: pdbs/split_chain/8PVW_A.pdb
```

```
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 19   name: pdbs/split_chain/4K46_A.pdb
   PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 20   name: pdbs/split_chain/4NP6_A.pdb
```

Let's have a wee peak at our stuctures after "fitting" or superposing:

```
#library(bio3dview)
#view.pdbs(pdbs)
```

```
#view.pdbs(pdbs, colorScheme = "residue")
```

we can run functions like `rmsd()`, `rmsf()` and the best `pca()`

```
pc.xray <- pca(pdbs)
plot(pc.xray)
```




```
plot(pc.xray, 1:2)
```



Finally, let's make a wee movie of the major "motion" or stuructural diffrenece in the dataset- we call this a "trajectory"

```
mktrj(pc.xray, file="results.pdb")
```