Class 08: Breast Cancer Mini Project

Yasmeen Al Shakarchi (PID: A18116120)

Table of contents

Background 1
Data Import 1
Principal Component Analysis (PCA) 4
Scree plot 7
4. Hierarchial clustering 11
Combining methods 14
Prediction 16

Background

In today's class we will be employing all the R techniques for data analysis that we have learned thus far for - inlcuding the machine learning methods of clustering and PCA - to analyze real breast cancer biopsy

Data Import

The data is in CSV format:

```
wisc.df <- read.csv("WisconsinCancer.csv", row.names = 1)
```

wee peak at the data

```
head(wisc.df, 3)
```

```
         diagnosis radius_mean texture_mean perimeter_mean area_mean
842302           M       17.99        10.38          122.8      1001
842517           M       20.57        17.77          132.9      1326
84300903         M       19.69        21.25          130.0      1203
         smoothness_mean compactness_mean concavity_mean concave.points_mean
842302           0.11840          0.27760         0.3001             0.14710
842517           0.08474          0.07864         0.0869             0.07017
84300903         0.10960          0.15990         0.1974             0.12790
         symmetry_mean fractal_dimension_mean radius_se texture_se perimeter_se
842302          0.2419                0.07871    1.0950     0.9053        8.589
842517          0.1812                0.05667    0.5435     0.7339        3.398
84300903        0.2069                0.05999    0.7456     0.7869        4.585
         area_se smoothness_se compactness_se concavity_se concave.points_se
842302    153.40      0.006399        0.04904      0.05373           0.01587
842517     74.08      0.005225        0.01308      0.01860           0.01340
84300903   94.03      0.006150        0.04006      0.03832           0.02058
         symmetry_se fractal_dimension_se radius_worst texture_worst
842302       0.03003             0.006193        25.38         17.33
842517       0.01389             0.003532        24.99         23.41
84300903     0.02250             0.004571        23.57         25.53
         perimeter_worst area_worst smoothness_worst compactness_worst
842302             184.6       2019           0.1622            0.6656
842517             158.8       1956           0.1238            0.1866
84300903           152.5       1709           0.1444            0.4245
         concavity_worst concave.points_worst symmetry_worst
842302            0.7119               0.2654         0.4601
842517            0.2416               0.1860         0.2750
84300903          0.4504               0.2430         0.3613
         fractal_dimension_worst
842302                   0.11890
842517                   0.08902
84300903                 0.08758
```

Q1. How many obervations are in this dataset?

```
wisc.data <- wisc.df[,-1]
diagnosis <- wisc.df$diagnosis
```

```
nrow(wisc.df)
```

```
[1] 569
```

Q2. How many of the observations have a malignant diagnosis?

```r
sum(wisc.df$diagnosis == "M")
```

```
[1] 212
```

```r
table(wisc.df$diagnosis)
```

```
  B   M 
357 212 
```

Q3. How many variables/features in the data are suffixed with _mean?

```r
length(grep("_mean",colnames(wisc.df)))
```

```
[1] 10
```

```r
colnames(wisc.df)
```

```
 [1] "diagnosis"               "radius_mean"            
 [3] "texture_mean"            "perimeter_mean"         
 [5] "area_mean"               "smoothness_mean"        
 [7] "compactness_mean"        "concavity_mean"         
 [9] "concave.points_mean"     "symmetry_mean"          
[11] "fractal_dimension_mean"  "radius_se"              
[13] "texture_se"              "perimeter_se"           
[15] "area_se"                 "smoothness_se"          
[17] "compactness_se"          "concavity_se"           
[19] "concave.points_se"       "symmetry_se"            
[21] "fractal_dimension_se"    "radius_worst"           
[23] "texture_worst"           "perimeter_worst"        
[25] "area_worst"              "smoothness_worst"       
[27] "compactness_worst"       "concavity_worst"        
[29] "concave.points_worst"    "symmetry_worst"         
[31] "fractal_dimension_worst"
```

We need to remove the `dignosis` column before we do any further analysis of this dataset- we don't want to pass this to PCA etc. We will save it as a separate wee vector that we can use later to compare our findings to those of experts.

```r
wisc.data <- wisc.df[,-1]
diagnosis <- wisc.df$diagnosis
```

Principal Component Analysis (PCA)

The main function in base R is called `prcomp()` we will use the optional argument `scale = TRUE` here as the data columns/features/dimensions are on very different scales in the original data set.

```r
wisc.pr <- prcomp(wisc.data, scale= T)
```

```r
head(wisc.pr$x)
```

```
               PC1        PC2        PC3       PC4        PC5         PC6
842302   -9.184755  -1.946870 -1.1221788 3.6305364  1.1940595  1.41018364
842517   -2.385703   3.764859 -0.5288274 1.1172808 -0.6212284  0.02863116
84300903 -5.728855   1.074229 -0.5512625 0.9112808  0.1769302  0.54097615
84348301 -7.116691 -10.266556 -3.2299475 0.1524129  2.9582754  3.05073750
84358402 -3.931842   1.946359  1.3885450 2.9380542 -0.5462667 -1.22541641
843786   -2.378155  -3.946456 -2.9322967 0.9402096  1.0551135 -0.45064213
                 PC7         PC8         PC9       PC10       PC11       PC12
842302    2.15747152  0.39805698 -0.15698023 -0.8766305 -0.2627243 -0.8582593
842517    0.01334635 -0.24077660 -0.71127897  1.1060218 -0.8124048  0.1577838
84300903 -0.66757908 -0.09728813  0.02404449  0.4538760  0.6050715  0.1242777
84348301  1.42865363 -1.05863376 -1.40420412 -1.1159933  1.1505012  1.0104267
84358402 -0.93538950 -0.63581661 -0.26357355  0.3773724 -0.6507870 -0.1104183
843786    0.49001396  0.16529843 -0.13335576 -0.5299649 -0.1096698  0.0813699
                PC13         PC14         PC15        PC16        PC17
842302    0.10329677 -0.690196797  0.601264078  0.74446075 -0.26523740
842517   -0.94269981 -0.652900844 -0.008966977 -0.64823831 -0.01719707
84300903 -0.41026561  0.016665095 -0.482994760  0.32482472  0.19075064
84348301 -0.93245070 -0.486988399  0.168699395  0.05132509  0.48220960
84358402  0.38760691 -0.538706543 -0.310046684 -0.15247165  0.13302526
843786   -0.02625135  0.003133944 -0.178447576 -0.01270566  0.19671335
                PC18       PC19        PC20         PC21        PC22
842302   -0.54907956  0.1336499  0.34526111  0.096430045 -0.06878939
842517    0.31801756 -0.2473470 -0.11403274 -0.077259494  0.09449530
84300903 -0.08789759 -0.3922812 -0.20435242  0.310793246  0.06025601
84348301 -0.03584323 -0.0267241 -0.46432511  0.433811661  0.20308706
84358402 -0.01869779  0.4610302  0.06543782 -0.116442469  0.01763433
```

```
843786   -0.29727706 -0.1297265 -0.07117453 -0.002400178  0.10108043
                PC23         PC24         PC25         PC26        PC27
842302    0.08444429  0.175102213  0.150887294 -0.201326305 -0.25236294
842517   -0.21752666 -0.011280193  0.170360355 -0.041092627  0.18111081
84300903 -0.07422581 -0.102671419 -0.171007656  0.004731249  0.04952586
84348301 -0.12399554 -0.153294780 -0.077427574 -0.274982822  0.18330078
84358402  0.13933105  0.005327110 -0.003059371  0.039219780  0.03213957
843786    0.03344819 -0.002837749 -0.122282765 -0.030272333 -0.08438081
                  PC28         PC29          PC30
842302   -0.0338846387  0.045607590  0.0471277407
842517    0.0325955021 -0.005682424  0.0018662342
84300903  0.0469844833  0.003143131 -0.0007498749
84348301  0.0424469831 -0.069233868  0.0199198881
84358402 -0.0347556386  0.005033481 -0.0211951203
843786    0.0007296587 -0.019703996 -0.0034564331
```

```r
library(ggplot2)

ggplot(wisc.pr$x) +
  aes(PC1, PC2, col=diagnosis) +
  geom_point()
```



```r
summary(wisc.pr)
```

```
Importance of components:
                          PC1    PC2     PC3     PC4     PC5     PC6     PC7
Standard deviation     3.6444 2.3857 1.67867 1.40735 1.28403 1.09880 0.82172
Proportion of Variance 0.4427 0.1897 0.09393 0.06602 0.05496 0.04025 0.02251
Cumulative Proportion  0.4427 0.6324 0.72636 0.79239 0.84734 0.88759 0.91010
                           PC8    PC9    PC10   PC11    PC12    PC13    PC14
Standard deviation     0.69037 0.6457 0.59219 0.5421 0.51104 0.49128 0.39624
Proportion of Variance 0.01589 0.0139 0.01169 0.0098 0.00871 0.00805 0.00523
Cumulative Proportion  0.92598 0.9399 0.95157 0.9614 0.97007 0.97812 0.98335
                          PC15    PC16    PC17    PC18    PC19    PC20   PC21
Standard deviation     0.30681 0.28260 0.24372 0.22939 0.22244 0.17652 0.1731
Proportion of Variance 0.00314 0.00266 0.00198 0.00175 0.00165 0.00104 0.0010
Cumulative Proportion  0.98649 0.98915 0.99113 0.99288 0.99453 0.99557 0.9966
                          PC22    PC23   PC24    PC25    PC26    PC27    PC28
Standard deviation     0.16565 0.15602 0.1344 0.12442 0.09043 0.08307 0.03987
Proportion of Variance 0.00091 0.00081 0.0006 0.00052 0.00027 0.00023 0.00005
Cumulative Proportion  0.99749 0.99830 0.9989 0.99942 0.99969 0.99992 0.99997
                          PC29    PC30
Standard deviation     0.02736 0.01153
Proportion of Variance 0.00002 0.00000
Cumulative Proportion  1.00000 1.00000
```

> Q4. From your results, what proportion of the original variance is captured by the first principal component (PC1)?

Answer: 0.4427

> Q5. How many principal components (PCs) are required to describe at least 70% of the original variance in the data?

Answer: PC3

> Q6. How many principal components (PCs) are required to describe at least 90% of the original variance in the data?

Answer: PC7

> Q7. What stands out to you about this plot? Is it easy or difficult to understand? Why?

```r
biplot(wisc.pr)
```



Answer: This plot is very messy and not easy to read at all. The lines overlap and it is not comprehensible.

Scree plot

```r
pr.var <- wisc.pr$sdev^2
```

```r
pve <- pr.var / sum(pr.var)

plot(c(1, pve),
     xlab = "Principal Component",
     ylab = "Proportion of Variance Explained",
     ylim = c(0, 1),
     type = "o")
```




```
barplot(pve, ylab = "Percent of Variance Explained",
     names.arg=paste0("PC",1:length(pve)), las=2, axes = FALSE)
axis(2, at=pve, labels=round(pve,2)*100 )
```



```r
library(factoextra)
```

```
Welcome! Want to learn more? See two factoextra-related books at https://goo.gl/ve3WBa
```

```r
fviz_eig(wisc.pr, addlabels = TRUE)
```

```
Warning in geom_bar(stat = "identity", fill = barfill, color = barcolor, :
Ignoring empty aesthetic: `width`.
```



Q8. Generate a similar plot for principal components 1 and 3. What do you notice about these plots?

```r
library(ggplot2)

ggplot(wisc.pr$x) +
  aes(PC1, PC3, col=diagnosis) +
  geom_point()
```



Answer: The plot is tighter and PC3 explains less variance than PC2 (Less variation).

> Q9. For the first principal component, what is the component of the loading vector (i.e. wisc.pr$rotation[,1]) for the feature concave.points_mean? This tells us how much this original feature contributes to the first PC. Are there any features with larger contributions than this one?

```
wisc.pr$rotation["concave.points_mean", "PC1"]
```

```
[1] -0.2608538
```

```
abs(wisc.pr$rotation[,1])
```

```
            radius_mean           texture_mean         perimeter_mean
             0.21890244             0.10372458             0.22753729
              area_mean        smoothness_mean       compactness_mean
             0.22099499             0.14258969             0.23928535
         concavity_mean     concave.points_mean          symmetry_mean
             0.25840048             0.26085376             0.13816696
 fractal_dimension_mean              radius_se             texture_se
             0.06436335             0.20597878             0.01742803
           perimeter_se                 area_se          smoothness_se
```

```
          0.21132592              0.20286964              0.01453145
      compactness_se            concavity_se       concave.points_se
          0.17039345              0.15358979              0.18341740
         symmetry_se    fractal_dimension_se            radius_worst
          0.04249842              0.10256832              0.22799663
       texture_worst         perimeter_worst              area_worst
          0.10446933              0.23663968              0.22487053
    smoothness_worst       compactness_worst         concavity_worst
          0.12795256              0.21009588              0.22876753
 concave.points_worst          symmetry_worst fractal_dimension_worst
          0.25088597              0.12290456              0.13178394
```

Answer: concave.points_mean contributes fairly strongly to PC1 (neg (-)), the answer here was –0.2608. Yes lots of others have larger absolute loadings.

4. Hierarchial clustering

The goal of this section is to do heierarchical clustering of the original data to see if there is any obvious grouping into malignant and benign clusters.

In short, these results are not good!

First we will scale our `wisc.data` then calculate a distance matrix, then pass to `hclust()`:

```
wisc.dist <- dist( scale(wisc.data))
wisc.hclust <- hclust(wisc.dist)
plot(wisc.hclust)
```




```
plot(wisc.hclust)
abline(h = 19, col="red", lty=2)
```



Q10. Using the plot() and abline() functions, what is the height at which the clustering model has 4 clusters?

```
plot(wisc.hclust, labels = FALSE, hang = -1, cex = 0.3)
abline(h = 7, col = "red", lty = 2)
```



Answer: At h = 19.

Q12. Which method gives your favorite results for the same data.dist dataset? Explain your reasoning.

Answer: My favorite results come from "average" because

```
wisc.hclust.clusters <- cutree(wisc.hclust, k=2)
table(wisc.hclust.clusters)
```

```
wisc.hclust.clusters
  1   2
567   2
```

Combining methods

The idea here is that I can take my new variables (i.e. the scores on the pCs `wisc.pr$x`) that are better descriptions of the data-set than the original features (i.e. the 30 columns in `wisc.data`) and use these as a basis for clustering.

```
pc.dist <- dist(wisc.pr$x[, 1:3])
wisc.pr.hclust <- hclust(pc.dist, method= "ward.D2")
plot(wisc.pr.hclust)
```




```
grps <- cutree(wisc.pr.hclust, k=2)
table(grps)
```

```
grps
  1   2
203 366
```

```
table(diagnosis)
```

```
diagnosis
  B   M
357 212
```

```r
wisc.pr.hclust.clusters <- cutree(wisc.pr.hclust, k=2)
```

> Q13. How well does the newly created hclust model with two clusters separate out the two "M" and "B" diagnoses?

```r
table(wisc.pr.hclust.clusters, diagnosis)
```

```
                       diagnosis
wisc.pr.hclust.clusters   B   M
                      1  24 179
                      2 333  33
```

Answer: It clusters it better because there is two clusters separates the diagnoses (one fouces on B and other on M).

I can now run `table()` with both my clustering `grps` and the expertn `diagnosis`

```r
table(grps, diagnosis)
```

```
    diagnosis
grps   B   M
   1  24 179
   2 333  33
```

Our clustering "1" has 179 "M" diagnosis or cluster "2" has 333 "B" diagnosis

179 TP 24 FP 333 TN 33 FN

> Q14. How well do the hierarchical clustering models you created in the previous sections (i.e. without first doing PCA) do in terms of separating the diagnoses? Again, use the table() function to compare the output of each model (wisc.hclust.clusters and wisc.pr.hclust.clusters) with the vector containing the actual diagnoses.

```r
table(wisc.hclust.clusters, diagnosis)
```

```
                    diagnosis
wisc.hclust.clusters   B   M
                   1 357 210
                   2   0   2
```

```r
table(wisc.pr.hclust.clusters, diagnosis)
```

```
                       diagnosis
wisc.pr.hclust.clusters   B   M
                      1  24 179
                      2 333  33
```

Answer: The hierarchical clustering model without pr did a poor job separating the diagnoses ebc ause it mixed both diagnoses toghther. Where the hierarchical clustering model with pr did a poor job separating the diagnoses to create two clusters that more clearly separated benign and malignant samples (better diagnostic separation).

> Q15. OPTIONAL: Which of your analysis procedures resulted in a clustering model with the best specificity? How about sensitivity?

Sensitivity: TP/(TP+FN)

```r
179/(179+33)
```

```
[1] 0.8443396
```

Specificity: TN/(TN+FP)

```r
333/(333+24)
```

```
[1] 0.9327731
```

Prediction

We can use our PCA model for predicition of new un-seen cases:

```r
url <- "https://tinyurl.com/new-samples-CSV"
new <- read.csv(url)
npc <- predict(wisc.pr, newdata=new)
npc
```

```
           PC1       PC2        PC3        PC4       PC5        PC6        PC7
[1,]  2.576616 -3.135913  1.3990492 -0.7631950  2.781648 -0.8150185 -0.3959098
[2,] -4.754928 -3.009033 -0.1660946 -0.6052952 -1.140698 -1.2189945  0.8193031
            PC8       PC9       PC10      PC11      PC12      PC13     PC14
[1,] -0.2307350 0.1029569 -0.9272861 0.3411457  0.375921 0.1610764 1.187882
[2,] -0.3307423 0.5281896 -0.4855301 0.7173233 -1.185917 0.5893856 0.303029
          PC15       PC16        PC17        PC18        PC19       PC20
[1,] 0.3216974 -0.1743616 -0.07875393 -0.11207028 -0.08802955 -0.2495216
[2,] 0.1299153  0.1448061 -0.40509706  0.06565549  0.25591230 -0.4289500
           PC21       PC22       PC23       PC24        PC25         PC26
[1,]  0.1228233 0.09358453 0.08347651  0.1223396  0.02124121  0.078884581
[2,] -0.1224776 0.01732146 0.06316631 -0.2338618 -0.20755948 -0.009833238
             PC27        PC28         PC29         PC30
[1,]  0.220199544 -0.02946023 -0.015620933  0.005269029
[2,] -0.001134152  0.09638361  0.002795349 -0.019015820
```

```r
plot(wisc.pr$x[,1:2], col=grps)
points(npc[,1], npc[,2], col="blue", pch=16, cex=3)
text(npc[,1], npc[,2], c(1,2), col="white")
```



Q16. Which of these new patients should we prioritize for follow up based on your results

Answer: Based on these results the patient that we should prioritize is patient 2. This is because it is near the black cluster (malignant samples).