

Prop-5 Build

Instructions (How to Build)

This document is a guide for developers and users who wish to compile and build the Prop-5 source code themselves.

[NOTE] If you want to use the pre-built plug-ins (VST3) or the standalone app without compiling them yourself, please follow the installation instructions in `README` `Install.txt` included in the package.

1. Prerequisites

To build this project, the following tools must be installed on your system in advance:

- **C++17 Compatible Compiler**
 - **Windows:** Visual Studio 2022 (with "Desktop development with C++" workload)
 - **macOS:** Xcode 15 or higher (including Command Line Tools)
 - **Linux:** Clang or GCC
 - **CMake** (version 3.22 or higher)
 - **Git** (used for cloning the repository and retrieving JUCE)
-

2. Setup Instructions

This repository does not include the JUCE framework source code itself. Before building, you need to place JUCE in the root directory of the project.

① Clone the Repository

First, open your terminal or command prompt and clone this repository:

```
git clone https://github.com/yamatech/Prop-5.git Prop-5
cd Prop-5
```

② Place the JUCE Framework

Place the JUCE framework directly under the project root with the folder name **JUCE**.

[Method A] Get using Git (Recommended)

Clone the official JUCE repository and check out the version verified to work with this project (7.0.12):

```
git clone https://github.com/juce-framework/JUCE.git JUCE
cd JUCE
git checkout tags/7.0.12
cd ..
```

[Method B] Download Manually

1. Download the zip file from the JUCE Official Website.
 2. Extract the file and place the **JUCE** folder directly in the root of this project. *(Make sure `Prop-5/JUCE/CMakeLists.txt` exists in this layout)*
-

3. How to Build

Use CMake for building. Execute the following commands in the root directory of the project.

① Create and Configure Build Directory

Run CMake to generate the build environment:

```
mkdir build
cd build
cmake ..
```

② Run the Compilation (Build)

Build the plugin and standalone app:

To perform a Release Build (Recommended):

```
cmake --build . --config Release
```

To perform a Debug Build (for development):

```
cmake --build . --config Debug
```

4. About Build Artifacts

Upon a successful build, the plugin files for each format will be generated in the following directory:

- **Output Path:**
 - `build/Prop-5_artefacts/Release/` (or `Debug/`)

Convenient Setting: Copy Plugin After Build

On Windows, if you want to automatically copy the VST3 plug-in to a specific folder (e.g., `C:\Program Files\Common Files\VST3`) after a successful build, change the following line in `CMakeLists.txt` (located in the project root) from `FALSE` to `TRUE`:

```
set(COPY_PLUGIN_AFTER_BUILD FALSE)
```

↓↓↓

```
set(COPY_PLUGIN_AFTER_BUILD TRUE)
```

5. License & Disclaimer

- **License:** This project is licensed under the **GNU General Public License v3 (GPLv3)**. See the `LICENSE` file for details.
- **Disclaimer & Trademarks:**
 - **Prophet-5** and **Sequential** are registered trademarks of **Sequential LLC**.
 - This software is an unofficial, independent fan-made clone/emulator and is **not affiliated with, endorsed by, sponsored by, or associated with Sequential LLC or its affiliates in any way**.