

# CISCO ISE API



# Cisco ISE (Identity Service Engine)

- ▶ ISE is not just **RADIUS/TACACS** server but **total authentication solution** including device the profiling, the endpoint posture service and more.
- ▶ MAB (MAC Auth. Bypass) or 802.1X for the endpoint, PC
- ▶ Q: How can I add and delete **every MAC of every PC** ???
- ▶ A: **API !!! Especially for SDA.**

# Useful Link

- ▶ <https://community.cisco.com/t5/security-documents/ise-ers-api-examples/ta-p/3622623#toc-hld--1848670580>
- ▶ <https://developer.cisco.com/docs/identity-services-engine/#!setting-up/cisco-ise>
- ▶ [https:// IP\\_ADDRESS:9060/ers/SDK](https://IP_ADDRESS:9060/ers/SDK)

# what is cURL?

- ▶ cURL = Client URL
  - ▶ multi protocol
  - ▶ command in line tool
  - ▶ Free

# #00 - test api

▶ `curl -k -X GET -H 'ACCEPT: application/json' --user admin:1234Qwer 'https://10.72.80.186:9060/ers/config/node'`

==> Converted Python Code

```
import requests
```

```
headers = {
```

```
    'ACCEPT': 'application/json',
```

```
}
```

```
response = requests.get('https://10.72.80.186:9060/ers/config/node', headers=headers, verify=False,  
auth=('admin', '1234Qwer'))
```

# cURL to Python

▶ `curl -k -X GET -H 'ACCEPT: application/json' --user admin:1234Qwer 'https://10.72.80.186:9060/ers/config/node'`

==> **Converted Python Code**

```
import requests
```

```
headers = {
```

```
    'ACCEPT': 'application/json',
```

```
}
```

```
response = requests.get('https://10.72.80.186:9060/ers/config/node', headers=headers, verify=False,  
auth=('admin', '1234Qwer'))
```

# MAC

- ▶ MAC creation
  - ▶ step1) GROUP (VLAN) ID
  - ▶ step2) MAC insert
- ▶ GROUP MOVE
  - ▶ step1) group ID and end point ID
  - ▶ step2) move
- ▶ MAC delete
  - ▶ step1) MAC ID
  - ▶ step2) delete MAC



# #1-1 MAC insert : GROUP ID {yame1}

- ▶ **curl -k --header 'Accept: application/json' --user admin:1234Qwer https://10.72.80.186:9060/ers/config/endpointgroup/name/{yame1}**
- ▶ {
- ▶ "EndPointGroup" : {
- ▶ "id" : "690e3550-c9d4-11ea-892d-8a9574f231bf",
- ▶ "name" : "yame1",
- ▶ "description" : "yame1",
- ▶ "systemDefined" : false,
- ▶ "link" : {
- ▶ "rel" : "self",
- ▶ "href" : "https://10.72.80.186:9060/ers/config/endpointgroup/name/yame1",
- ▶ "type" : "application/json"
- ▶ }
- ▶ }



# #1-1 MAC insert : GROUP ID {yame2}

```
▶ curl -k --header 'Accept: application/json' --user admin:1234Qwer https://10.72.80.186:9060/ers/
  config/endpointgroup/name/{yame}
▶ {
▶   "EndPointGroup" : {
▶     "id" : "6f4034f0-c9d4-11ea-892d-8a9574f231bf",
▶     "name" : "yame2",
▶     "description" : "yame2",
▶     "systemDefined" : false,
▶     "link" : {
▶       "rel" : "self",
▶       "href" : "https://10.72.80.186:9060/ers/config/endpointgroup/name/yame2",
▶       "type" : "application/json"
▶     }
▶   }
▶ }
```

# #1-2 MAC insert : Insert MAC

```
curl -k --include --header 'Content-Type:application/json' --header 'Accept: application/json' --user admin:1234Qwer --request POST https://10.72.80.186:9060/ers/config/endpoint --data '{
  "ERSEndPoint" : {
    "name" : "00:00:00:00:11:11",
    "description" : "API-INPUT",
    "mac" : "00:00:00:00:11:11",
    "groupId" : "690e3550-c9d4-11ea-892d-8a9574f231bf",
    "staticGroupAssignment" : true
  }
}'
```

## HTTP/1.1 201 Created

```
Set-Cookie: JSESSIONIDSSO=ADC450ABB6500E8B02E4CFC7352DEFE8; Path=/; Secure; HttpOnly
Set-Cookie: APPSESSIONID=51166A0122ADE9E27B1B419CB6FB337E; Path=/ers; Secure; HttpOnly
Cache-Control: no-cache, no-store, must-revalidate
Pragma: no-cache
Expires: Thu, 01 Jan 1970 00:00:00 GMT
X-Frame-Options: SAMEORIGIN
Strict-Transport-Security: max-age=31536000; includeSubDomains
X-Content-Type-Options: nosniff
X-Content-Security-Policy: default-src 'self'; script-src 'self' 'unsafe-inline' 'unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data:;
X-WebKit-CSP: default-src 'self'; script-src 'self' 'unsafe-inline' 'unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data:;
Content-Security-Policy: default-src 'self'; script-src 'self' 'unsafe-inline' 'unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data:;
X-XSS-Protection: 1; mode=block
Location: https://10.72.80.186:9060/ers/config/endpoint/4f3a0180-c9d5-11ea-892d-8a9574f231bf
Date: Sun, 19 Jul 2020 15:34:18 GMT
Content-Type: application/json;charset=utf-8
Content-Length: 0
Server:
```

# MAC

- ▶ MAC creation
  - ▶ step1) GROUP (VLAN) ID
  - ▶ step2) MAC insert
- ▶ GROUP MOVE
  - ▶ step1) group ID and end point ID
  - ▶ step2) move
- ▶ MAC delete
  - ▶ step1) MAC ID
  - ▶ step2) delete MAC



## #2-1 MAC move : MAC ID

```
curl -k -X GET -H 'ACCEPT: application/json' --user admin:1234Qwer 'https://10.72.80.186:9060/ers/
config/endpoint?filter=mac.EQ.00:00:00:00:11:11'
{
  "SearchResult" : {
    "total" : 1,
    "resources" : [ {
      "id" : "da4c8f20-c9dc-11ea-892d-8a9574f231bf",
      "name" : "00:00:00:00:11:11",
      "link" : {
        "rel" : "self",
        "href" : "https://10.72.80.186:9060/ers/config/endpoint/4f3a0180-c9d5-11ea-892d-8a9574f231bf",
        "type" : "application/json"
      }
    }
  ]
}
```

## #2-2 MAC move yame1 to yame2

```
curl -k --include --header 'Content-Type:application/json' --header 'Accept: application/json' --user admin:1234Qwer --request PUT https://10.72.80.186:9060/ers/config/endpoint/{da4c8f20-c9dc-11ea-892d-8a9574f231bf} --data '
```

```
{
  "ERSEndPoint" : {
    "name" : "00:00:00:00:11:11",
    "description" : "API-INPUT",
    "mac" : "00:00:00:00:11:11",
    "groupId" : "6f4034f0-c9d4-11ea-892d-8a9574f231bf",
    "staticGroupAssignment" : true
  }
}

{
  "UpdatedFieldsList" : {
    "updatedField" : [ {
      "field" : "groupId",
      "oldValue" : "690e3550-c9d4-11ea-892d-8a9574f231bf",
      "newValue" : "6f4034f0-c9d4-11ea-892d-8a9574f231bf"
    } ]
  }
}
```

# MAC

- ▶ MAC creation
  - ▶ step1) GROUP (VLAN) ID
  - ▶ step2) MAC insert
- ▶ GROUP MOVE
  - ▶ step1) group ID and end point ID
  - ▶ step2) move
- ▶ MAC delete
  - ▶ step1) MAC ID
  - ▶ step2) delete MAC



## #3 delete MAC

```
curl -k --include --header 'Content-Type:application/json' --header 'Accept: application/json' --user admin:1234Qwer --request DELETE https://10.72.80.186:9060/ers/config/endpoint/{da4c8f20-c9dc-11ea-892d-8a9574f231bf}
```

### HTTP/1.1 204 No Content

Cache-Control: no-cache, no-store, must-revalidate

Expires: Thu, 01 Jan 1970 00:00:00 GMT

Set-Cookie: JSESSIONIDSSO=6CF7B14558E64AF78C50C0CD80A0D3E5; Path=/; Secure; HttpOnly

Set-Cookie: APPSESSIONID=9A83568DEB1EE9A7BD800A4E14DC0BAF; Path=/ers; Secure; HttpOnly

Pragma: no-cache

X-Frame-Options: SAMEORIGIN

Strict-Transport-Security: max-age=31536000; includeSubDomains

X-Content-Type-Options: nosniff

X-Content-Security-Policy: default-src 'self'; script-src 'self' 'unsafe-inline' 'unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data;;

X-WebKit-CSP: default-src 'self'; script-src 'self' 'unsafe-inline' 'unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data;;

Content-Security-Policy: default-src 'self'; script-src 'self' 'unsafe-inline' 'unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data;;

X-XSS-Protection: 1; mode=block

Date: Sun, 19 Jul 2020 15:59:33 GMT

Content-Type: application/json;charset=utf-8

Server:



# CISCO ISE API

