

CineLog – Domain Model Specification

1. User

A user is a registered account on CineLog.

A user has: unique username, unique email, hashed password, account status (unverified | verified | locked), failed login attempt counter, lockout expiry timestamp, created-at timestamp.

A user can have one active verification token, one active password reset token, many watchlist entries, watch logs, ratings, reviews, and one derived stats profile.

Rules:

- Only verified accounts may log in
- Passwords must be hashed before storage
- No duplicate movie/show entries per user across watchlist or logs
- Users may only access their own data
- After 5 failed logins the account is locked for 60 minutes
- Failed login count resets after successful login
- Locked accounts may still request password resets

2. Verification Token

Short-lived email verification token linked to a user.

Fields: user reference, hashed token value, expiry timestamp (5 min), created-at timestamp.

Rules: One active token per user, new requests invalidate old tokens, 2-minute wait between requests, max 3 requests before 1-hour cooldown, hashed storage required.

3. Password Reset Token

Short-lived password reset token linked to a user.

Fields: user reference, hashed token value, expiry timestamp (5 min), created-at timestamp.

Rules: One active token per user, new requests invalidate old tokens, 2-minute wait between requests, max 3 requests before 1-hour cooldown, account remains verified after reset, hashed storage required.

4. Movie / Show (TMDB Reference)

Cached TMDB record used by CineLog.

Fields: TMDB ID, type, title, poster URL, release year, overview, genre list, cached-at timestamp.

Rules: Read-only in CineLog, cached locally, refreshed periodically, referenced by all user content.

5. Watchlist Entry

Fields: user reference, TMDB item reference, status, created-at, updated-at.

Rules: One entry per item per user, defaults to “want to watch”, updates to “watched” when logged, removable by owner only.

6. Watch Log

Fields: user reference, TMDB item reference, date watched, created-at timestamp.

Rules: One watch log per item, automatically updates watchlist status, creates watchlist entry if absent, date watched is automatic, required for ratings and reviews.

7. Rating

Fields: user reference, TMDB item reference, score (1–10), created-at, updated-at.

Rules: Only watched items may be rated, one rating per item, score must be 1–10, ratings may be updated, rating required for reviews.

8. Review

Fields: user reference, TMDB item reference, rating reference, review body, created-at, updated-at.

Rules: Requires an existing rating, optional, one review per item, may be updated or deleted, no minimum length in MVP.

9. Audit Log

Fields: optional user reference, action type, metadata/context, created-at timestamp.

Rules: Append-only, tracks verification requests, login attempts, lockouts, and password resets, not exposed to users in MVP.

10. Stats (Derived)

Computed from watch logs and ratings.

Includes: total watched items, average rating, most watched genre, recent watches.

Rules: Based only on requesting user's data, read-only, genres derived from cached TMDB records.