

Comment	Description	Designator	Footprint	LibRef	Quantity
Cap Pol1	Polarized Capacitor (Radial)	C1, C2, C15	CAPPR2.5-6.3x5	Cap Pol1	3
Cap For	Polarized Capacitor	C1, C2, C13	CAFFIX2.5-0.5X5	Cap For	3
Cap Pol	(Surface Mount)	C3	TC6032-2412	Cap Pol	1
Сар	Capacitor	C4, C8	RESC2012N	Сар	2
0	0	C5, C6, C9, C13,	0.4.00004014/	0	
Cap	Capacitor Polarized Capacitor	C14	CAPC2012W	Cap	5
Cap Pol	(Surface Mount)	C7	С	Cap Pol	1
Сар	Capacitor	C10	CAPC2012N	Сар	1
Сар	Capacitor	C11, C12	CAPC1608N	Сар	2
3V6	Zener Diode	D1, D2, D4	DIO6.35-3.1x1.6	D Zener	3
2V7	Zener Diode	D3	DIO6.35-3.1x1.6	D Zener	1
Diode	Default Diode	D7	MELF-D5023-2009	Diode	1
J3	Jumper 1:2	J1, J2, J3	J3 SMT 60	J3	3
USB B HEADER	Connector, USB B Type, Right Angle, Thru Hole, White	P1	HDR1X4	USB_B	1
LCD	Header, 16-Pin	P2	HDR2X8	Header 16	1
TMP1	Header, 3-Pin	P3	HDR1X3	Header 3	1
TMP2	Header, 3-Pin	P4	HDR1X3	Header 3	1
DHT11	Header, 4-Pin	P5	HDR1X4	Header 4	1
UART	Header, 4-Pin	P6	HDR1X4	Header 4	1
BMP085	Header, 6-Pin	P7	HDR1X6	Header 6	1
-DE04	Header, 4-Pin, Dual	DO	LIDDOVA	Handar AVO	
nRF24	row	P9	HDR2X4	Header 4X2	1
REL1	Header, 2-Pin NPN General-	P10	HDR1X2	Header 2	1
BC817-16	purpose Transistor	Q1, Q2	SOT23_N	BC817-16	2
Decistor	Decistor	R1, R2, R3, R4, R5, R6, R7, R8, R9, R10 R11, R12, R13, R14 R15, R16, R17, R18 R19, R20, R21, R22 R23, R24, R25, R26 R27, R28, R29, R30 R31, R32, R33, R34 R35, R37, R38, R39		Decistor	40
Resistor	Resistor	R40, R41	RESC2012W	Resistor	40
Resistor	Resistor	R36 SW1, SW2, SW3,	AXIAL-0.3 SW 1P4C	Resistor	1
SW-PB	Switch	SW4	200x300mil	SW-PB	4
LM1117MP-3.3	800mA Low-Dropou Linear Regulator 8-Bit AVR Microcontroller with 8K Bytes of In-	U1	MP04A_M	LM1117MP-3.3	1
	System Programmable Flasl				
ATmega8-16AI	Programmable Flasi Memory	U2	32A_N	ATmega8-16AI	1
LED	,	VD1, VD2	LED2.54x3	LED	2
12MHz	Crystal Oscillator	Y1	HC49U	XTAL	1
	S. John Coomator			, , the	<u>'</u>