



Mastering f-Strings in Python



Cahya Alkahfi

Table of contents

- ✓ What are f-Strings
- ✓ Basic Usage
- ✓ Formatting Numbers
- ✓ Aligning Strings
- ✓ Padding Strings
- ✓ Date and Time Formatting
- ✓ Special Characters & Escape Sequences
- ✓ Multiline f-Strings
- ✓ Nested f-Strings
- ✓ Bonus (Star Patterns using f-Strings)



What are f-Strings?

f-Strings, short for formatted string literals, were introduced in Python 3.6. They provide a concise and readable way to embed expressions inside string literals using curly braces `{}`.

f-Strings are designed to be more readable and less error-prone compared to previous string formatting methods. They allow embedding of Python expressions directly within strings, making the code cleaner and easier to understand.

Benefits of Using f-Strings

Readability: improve code readability by reducing the verbosity associated with other formatting methods. Embedding expressions directly within strings makes the intent of the code clearer.

Efficiency: more efficient than both the `%` operator and `str.format()` method. They are faster because they are evaluated at runtime, reducing the overhead of additional function calls.

Flexibility: provide great flexibility in embedding various types of expressions, including variables, arithmetic operations, and even function calls. They also support advanced formatting options like alignment, padding, and precision control.

Ease of Use: simplify string formatting tasks and reduce the likelihood of errors. They eliminate the need for placeholders and explicit argument indexing, making the code more intuitive and less prone to mistakes.

Creating an f-String

f-Strings provide a simple and intuitive way to embed expressions inside string literals. To create an f-String, prefix a string with the letter **f** or **F**, followed by the string in either single, double, or triple quotes, with every expression or operation enclosed in curly braces **{}**.

```
name = "John Doe"
greeting = f"Hello, I am {name}"
print(greeting)
```

```
Hello, I am John Doe
```

```
first_name = "John"
last_name = "Doe"
age = 50
full_name = f"{first_name} {last_name}"
greeting = f"Hello, my name is {full_name} and I am {age} years old"
print(greeting)
```

```
Hello, my name is John Doe and I am 50 years old
```

```
radius = 5
area = f"The area of the circle is {3.14 * radius ** 2:.2f} square units."
print(area)
```

```
The area of the circle is 78.50 square units.
```

In Python 3.8 and later, we can use "**self-documenting expressions**" to display expressions and their results directly by using the equals sign (**=**) within the f-String expression.

```
a = 10
b = 0.125

print(f"{a + b = :.2f}, {a - b = :.2f}, {a * b = }")

a + b = 10.12, a - b = 9.88, a * b = 1.25
```

Formatting Numbers

```
rate = 0.84579

# 4 decimal places
fmt_rate_1 = f"Rate to 4 decimal places is {rate:.4f}"
print(fmt_rate_1)

# 2 decimal places percentage
fmt_rate_2 = f"Rate as a percentage to 2 decimal places is {rate:.2%}"
print(fmt_rate_2)
```

Rate to 4 decimal places is 0.8458
Rate as a percentage to 2 decimal places is 84.58%

```
distance = 1384400000
fmt_distance_1 = f"Distance: {distance:,.0f}" # comma separator
print(fmt_distance_1)

fmt_distance_2 = f"Distance: {distance:_.0f}" # underscore separator
print(fmt_distance_2)
```

Distance: 1,384,400,000
Distance: 1_384_400_000

```
speed = 299_792_458

# Format with standard scientific notation (lowercase 'e')
fmt_speed_1 = f"Speed of light is {speed:.2e} m/s"
print(fmt_speed_1)

# Format with uppercase scientific notation (uppercase 'E')
fmt_speed_2 = f"Speed of light is {speed:.4E} m/s"
print(fmt_speed_2)
```

Speed of light is 3.00e+08 m/s
Speed of light is 2.9979E+08 m/s

Aligning Strings

```
data = [225000, 5000, 15000000]

print("Left-aligned:")
for dt in data:
    print(f"{dt:<8}")    # Left-align 8 characters (<8)

print("\nRight-aligned (by 10 chars):")
for dt in data:
    print(f"{dt:>10}")    # Right-align 10 characters (>10)
print("-----")

print("\nCenter-aligned (by 13 chars):")
for dt in data:
    print(f"{dt:^13}")    # Center-align 13 characters (^13)
print("-----")
```

Left-aligned:

225000

5000

15000000

Right-aligned (by 10 chars):

225000

5000

15000000

Center-aligned (by 13 chars):

225000

5000

15000000

Padding Strings

As before, but we can fill the empty space with any character.

```
data = [225000, 5000, 15000000]

print("Right padding with '*' (8 chars):\n")
for dt in data:
    print(f"{dt:*<8}")

print("\nLeft padding with 'X' (10 chars):\n")
for dt in data:
    print(f"{dt:X>10}")

print("\nLeft and right padding with '_' (12 chars):\n")
for dt in data:
    print(f"{dt:_^12}")
```

Right padding with '*' (8 chars):

```
225000**
5000****
15000000
```

Left padding with 'X' (10 chars):

```
XXXX225000
XXXXXX5000
XX15000000
```

Left and right padding with '_' (12 chars):

```
___225000___
___5000___
__15000000__
```


Date and Time Formatting

Using **f-Strings** along with the **datetime** module allows us to format dates and times flexibly and conveniently.

```
from datetime import datetime

# Get the current date and time
now = datetime.now()

# Example 1: Full date and time
formatted_now_1 = f"{now:%Y-%m-%d %H:%M:%S}"
print(f"Full date and time: {formatted_now_1}")

# Example 2: Date only
formatted_now_2 = f"{now:%Y-%m-%d}"
print(f"Date only: {formatted_now_2}")

# Example 3: Time only
formatted_now_3 = f"{now:%H:%M:%S}"
print(f"Time only: {formatted_now_3}")

# Example 4: Custom format
formatted_now_4 = f"{now:%A, %B %d, %Y at %I:%M %p}"
print(f"Cust. format: {formatted_now_4}")
```

```
Full date and time: 2024-08-04 19:31:45
Date only: 2024-08-04
Time only: 19:31:45
Cust. format: Sunday, August 04, 2024 at 07:31 PM
```


Special Characters & Escape Sequences

Although these are not exclusive features of f-Strings, f-Strings make it easy to include special characters like **quotes**, **backslashes**, and **newline** characters by using escape sequences or raw string literals.

```
item = "Laptop"
specs = ["15\" screen", "16GB RAM", "512GB SSD"]

output = f"Product: {item}\nSpecs:\n\t{specs[0]}\n\t{specs[1]}\n\t{specs[2]}"
print(output)
```

```
Product: Laptop
Specs:
    15" screen
    16GB RAM
    512GB SSD
```

```
# using raw string
path1 = r"C:\Users\SainsData\Documents\Report1.txt"

# using escape character (\ and \\)
path2 = "\"C:\\Users\\SainsData\\Documents\\Report2.txt\""

output = f"The file path is:\n > {path1}\n > {path2}"
print(output)
```

```
The file path is:
> "C:\Users\SainsData\Documents\Report1.txt"
> "C:\Users\SainsData\Documents\Report2.txt"
```

Multiline f-Strings (1/3)

Multiline f-Strings use triple quotes (''' or ''') to enclose the string, and we can include expressions inside curly braces {} just like with single-line f-Strings. We can also use `join` Method to create a list of items separated by newline characters.

```
width = 10
height = 5

area = f"""
The dimensions of the rectangle are:
> Width: {width} units
> Height: {height} units
> Area: {width * height} square units
"""

print(area)
```

```
The dimensions of the rectangle are:
> Width: 10 units
> Height: 5 units
> Area: 50 square units
```

```
items = ["apple", "banana", "cherry"]

shopping_list = f"""
Shopping List:
{'- ' + '\n- '.join(items)}
"""

print(shopping_list)
```

```
Shopping List:
- apple
- banana
- cherry
```

Multiline f-Strings (2/3)

```
items = {
    "Laptop": 999.99,
    "Smartphone": 499.99,
    "Tablet": 299.99,
    "Headphones": 199.99,
    "Charger": 29.99
}

output = f"""
{"-"*24}
{"Product":<12} | {"Price":>7}
{"-"*24}
"""

for item, price in items.items():
    output += f"{item:<12} | ${price:>7.2f}\n"

output+=f"{'-'*24}"

print(output)
```

```
-----
Product      | Price
-----
Laptop       | $ 999.99
Smartphone   | $ 499.99
Tablet       | $ 299.99
Headphones   | $ 199.99
Charger      | $  29.99
-----
```

Multiline f-Strings (3/3)

```
send_email = lambda info: f"""
To: {info['recipient']}
Subject: {info['subject']}

Dear {info['username']},

Welcome to our service! We are thrilled to have you on board.

Best regards,
The Team
"""

my_info = {
    'recipient': "johndoe@example.com",
    'subject': "Welcome to Our Service",
    'username': "John Doe"}

print(send_email(my_info))
```

```
To: johndoe@example.com
Subject: Welcome to Our Service

Dear John Doe,

Welcome to our service! We are thrilled to have you on board.

Best regards,
The Team
```

Nested f-Strings

If necessary, we can also use nested f-Strings, where an f-String contains another f-String within its expression.

```
a, b, c, d = 1, 2, 3, 4

output = f'''Data {a = }, {b = }, {c = }, {d = }
| {f'''1) {a + b = }
|   {f"1.1) {c + d = }"}'''
| {f'''1) {a * d = }
|   {f"1.2) {c * d = }"}'''
| ...

print(output)
```

```
Data a = 1, b = 2, c = 3, d = 4
  1) a + b = 3
    1.1) c + d = 7
  1) a * d = 4
    1.2) c * d = 12
```

Bonus (Star Patterns using f-Strings)

```
start = 1; stop = 14; step = 2

for i in range(start, stop, step):
    print(f"{'* ' * i:^{2*stop}}")
```

```

      *
    * * *
  * * * * *
* * * * * * *
* * * * * * * *
* * * * * * * * *
* * * * * * * * * *
* * * * * * * * * *
```

```
start = 1; stop = 14; step = 2

for i in range(start, stop, step):
    print(f"{'* ' * (stop - i):^{2*stop}}")
```

```
* * * * * * * * * *
* * * * * * * * *
* * * * * * * *
* * * * * * *
* * * * *
* * *
*
```

Bonus (Star Patterns using f-Strings)

```
start = 1; stop = 8; step = 1
```

```
for i in range(start, stop, step):  
    print(f"{'x ' * i:<{2*stop}}")
```

```
x  
x x  
x x x  
x x x x  
x x x x x  
x x x x x x  
x x x x x x x
```

```
start = 1; stop = 8; step = 1
```

```
for i in range(start, stop, step):  
    print(f"{'x ' * (stop - i):<{2*stop}}")
```

```
x x x x x x x  
x x x x x x  
x x x x x  
x x x x  
x x x  
x x  
x
```


Bonus (Star Patterns using f-Strings)

```
start = 1; stop = 18; step = 2

for i in range(start, stop, step):
    print(f"{'+ ' * (stop//2 - abs(i - stop//2))}^{2*stop}")
```

```
      +
    + + +
  + + + + +
+ + + + + + +
+ + + + + + +
  + + + + +
    + + +
      +
```

```
start = 1; stop = 17; step = 2

for i in range(start, stop, step):
    print(f"{'+ ' * abs(i - stop//2)}^{2*stop}")
```

```
+ + + + + + +
  + + + + +
    + + +
      +
      +
    + + +
  + + + + +
+ + + + + + +
```

Bonus (Star Patterns using f-Strings)

```
start=1; stop=9; step=2

for i in range(start, 2*stop, step):
    spaces = abs(stop - i)
    x = stop - spaces
    print(f"{' ' * spaces}x{' '*(2*x - 3)}{'x' if x > 1 else ''}")
```

```
      x
     x x
    x   x
   x     x
  x       x
 x         x
x          x
 x         x
  x       x
   x     x
    x   x
     x x
      x
```

THANK YOU

