

## 5-3: Basic Decision Support Metrics

Introduction to Recommender Systems

## Goals for Today

- To understand the concept of “decision support” metrics
- To learn a set of decision-support metrics, including:
  - Error rate and Reversals
  - Precision, Recall, MAP
  - Receiver operating characteristic
- To understand the usefulness and limitations of these metrics

Introduction to Recommender Systems

## What is “Decision Support”

- Measure how well a recommender helps users *make good decisions*
  - Good decisions are about choosing “good” items and avoiding “bad” ones
- For predictions: 4\* vs. 2.5\* worse than 2.5\* vs. 1\*
- For recommendations, top of list is what matters most.

Introduction to Recommender Systems

## Errors and Reversals

- What is an “error?”
  - Ad hoc measure of wrong predictions
  - E.g., determine that 3.5-5\* = good, 1-2.5\* = bad
    - Error is when a good movie (for a user) gets a bad prediction (or vice versa)
  - Can also be used for top-n – every time a bad movie appears in the top-n, it is an error.
  - Usually reported as total number (compared between algorithms), average error rate per user, etc.
  - Not widely used in research
- Reversals are large mistakes – e.g., off by 3 points on a 5-point scale
  - Intuition is that these are likely really bad – lead to loss of confidence
  - Again, reported as total or average rate

Introduction to Recommender Systems

## Precision and Recall

- Information Retrieval Metrics

- Precision is the percentage of selected items that are “relevant”

- $P = \frac{N_{rs}}{N_s}$

- Recall is the percentage of relevant items that are selected

- $R = \frac{N_{rs}}{N_r}$

## Precision and Recall (2)

- Different Goals

- Precision is about returning mostly useful stuff

- Not wasting user time
  - Assumption is that there is more useful stuff than you want

- Recall is about not missing useful stuff

- Not making a bad oversight
  - Assumption is that you have time to filter through results to find the key result you need

- When these two goals are in balance, F-metrics

- $F_1 = \frac{2PR}{P+R}$

## Precision and Recall (3)

- Problem #1 with precision/recall

- Need ground truth for all items

- But if we had ground truth, why bother with a recommender

- Ways this is addressed

- Fake precision/recall by limiting to rated items
    - Common – results in interesting biases
  - Human-rating experiments that compute precision/recall over some random subset

## Precision and Recall (4)

- Problem #2 with precision/recall

- Covers entire data set – not targeted on top-recommended items

- precision/recall inherently about “full query”

- Addressed through P@n, R@n

- Precision@n is the percentage of the top-n items that are “good”:  $P@n = \frac{N_{r@n}}{n}$
  - Some have proposed computing this as an average over a set of experiments with 1 “hit” and a large number of presumed misses
  - Recall@n is effectively the same

## Mean Average Precision (MAP)

- In IR, MAP averages over both multiple queries and over position in top-n retrieval
  - $MAP = \frac{\sum_{q=1}^Q AveP(q)}{Q}$  where  $AveP = \frac{\sum_{k=1}^n P(k) * rel(k)}{\# \text{ relevant docs}}$
  - More intuitively, this is computing an estimate of the area under the precision-recall curve, and then averaging across queries
- In recommender systems, this has been adapted in several ways, most commonly across users. Unfortunately, not standardized.
  - Useful comparing algorithm variants; for other comparisons, need to be really careful ...

Introduction to Recommender Systems

## Receiver Operating Characteristic

- The ROC curve is a plot of the performance of a classifier or filter at different thresholds. It plots true-positives against false positives:
  - [http://en.wikipedia.org/wiki/Receiver\\_operating\\_characteristic](http://en.wikipedia.org/wiki/Receiver_operating_characteristic)
- In recommender systems, the curve reflects trade-offs as you vary the prediction cut-off for recommending (vs. not).
- Area under the curve is often used as a measure of recommender effectiveness

Introduction to Recommender Systems

## Reflections ...

- Once again, all of these metrics tend to correlate highly with each other (good replacements for each other)
- Precision@n and overall precision are perhaps the most widely used (and easily understood)
- ROC provides insight if the goal is to tune the recommender's use as a filter, or identify "sweet spots" in its performance
- None of these metrics overcome the problem of being based on rated items only (and the inherent variation that comes from this limitation)

Introduction to Recommender Systems

## Looking forward ...

- Next, we look at rank metrics, then a bit of a rant on hidden-data evaluation, and then a broader set of metrics to look at business relevance ...

Introduction to Recommender Systems

## 5-3: Basic Decision Support Metrics

Introduction to Recommender Systems

