

Oracle® Text

Reference

12c Release 1 (12.1)

E41399-12

June 2017

Provides reference information for building applications with Oracle Text.

Oracle Text Reference, 12c Release 1 (12.1)

E41399-12

Copyright © 2001, 2017, Oracle and/or its affiliates. All rights reserved.

Primary Author: Roopesh Ashok Kumar

Contributors: Drew Adams, Cathy Shea, Edwin Balthes, Eric Belden, Rajesh Bhatiya, Mohammad Faisal, Roger Ford, Rahul Kadwe, George Krupka, Paul Lane, Colin McGregor, Padmaja Potineni, Yiming Qi, Sanoop Sethumadhavan, Asha Tarachandani, Gaurav Yadav

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface	xix
Audience	xix
Documentation Accessibility	xix
Related Documents.....	xix
Conventions.....	xx
Changes in This Release for Oracle Text Reference.....	xxi
Changes in Oracle Text 12c Release 1 (12.1)	xxi
New Features	xxi
Deprecated Features.....	xxi
Desupported Features	xxi
1 Oracle Text SQL Statements and Operators	
1.1 ALTER INDEX	1-1
1.2 ALTER TABLE: Supported Partitioning Statements	1-18
1.3 CATSEARCH	1-23
1.4 CONTAINS.....	1-29
1.5 CREATE INDEX	1-40
1.6 DROP INDEX	1-63
1.7 MATCHES	1-63
1.8 MATCH_SCORE.....	1-65
1.9 SCORE	1-65
2 Oracle Text Indexing Elements	
2.1 Overview.....	2-1
2.2 Creating Preferences.....	2-2
2.3 Datastore Types	2-2
2.3.1 DIRECT_DATASTORE	2-3
2.3.2 MULTI_COLUMN_DATASTORE.....	2-3
2.3.3 DETAIL_DATASTORE	2-7
2.3.4 FILE_DATASTORE.....	2-9

2.3.5	URL_DATASTORE	2-11
2.3.6	USER_DATASTORE	2-14
2.3.7	NESTED_DATASTORE	2-16
2.4	Filter Types	2-19
2.4.1	AUTO_FILTER	2-19
2.4.2	NULL_FILTER	2-22
2.4.3	MAIL_FILTER.....	2-22
2.4.4	USER_FILTER.....	2-26
2.4.5	PROCEDURE_FILTER	2-29
2.5	Lexer Types.....	2-32
2.5.1	AUTO_LEXER	2-33
2.5.2	BASIC_LEXER	2-41
2.5.3	MULTI_LEXER.....	2-49
2.5.4	CHINESE_VGRAM_LEXER.....	2-52
2.5.5	CHINESE_LEXER	2-52
2.5.6	JAPANESE_VGRAM_LEXER	2-53
2.5.7	JAPANESE_LEXER.....	2-54
2.5.8	KOREAN_MORPH_LEXER	2-55
2.5.9	USER_LEXER.....	2-59
2.5.10	WORLD_LEXER.....	2-71
2.6	Wordlist Type.....	2-72
2.6.1	BASIC_WORDLIST.....	2-72
2.6.2	BASIC_WORDLIST Example	2-79
2.7	Storage Types	2-80
2.7.1	BASIC_STORAGE	2-81
2.8	Section Group Types	2-86
2.8.1	Section Group Types for Creating a Section Group	2-86
2.8.2	Section Group Examples for HTML, XML, and JSON Enabled Documents.....	2-88
2.9	Classifier Types	2-89
2.9.1	RULE_CLASSIFIER.....	2-90
2.9.2	SVM_CLASSIFIER.....	2-91
2.10	Cluster Types.....	2-92
2.10.1	KMEAN_CLUSTERING.....	2-92
2.11	Stoplists	2-93
2.11.1	Multi-Language Stoplists	2-94
2.11.2	Creating Stoplists.....	2-94
2.11.3	Modifying the Default Stoplist.....	2-94
2.12	System-Defined Preferences.....	2-95
2.12.1	Data Storage Preferences.....	2-95
2.12.2	Filter Preferences	2-96
2.12.3	Lexer Preferences.....	2-96
2.12.4	Section Group Preferences	2-97
2.12.5	Stoplist Preferences	2-98

2.12.6	Storage Preferences	2-98
2.12.7	Wordlist Preferences	2-98
2.13	System Parameters.....	2-98
2.13.1	General System Parameters	2-98
2.13.2	Default Index Parameters.....	2-99
2.13.3	Default Policy Parameters.....	2-102

3 Oracle Text CONTAINS Query Operators

3.1	Operator Precedence	3-2
3.1.1	Group 1 Operators	3-2
3.1.2	Group 2 Operators and Characters.....	3-3
3.1.3	Procedural Operators.....	3-3
3.1.4	Precedence Examples	3-3
3.1.5	Altering Precedence	3-4
3.2	ABOUT	3-4
3.3	ACCUMulate (,)	3-7
3.4	AND (&).....	3-8
3.5	Broader Term (BT, BTG, BTP, BTI).....	3-9
3.6	CTXFILTERCACHE	3-11
3.7	DEFINEMERGE	3-14
3.8	DEFINESCORE	3-15
3.9	EQUIvalence (=)	3-19
3.10	Fuzzy	3-20
3.11	HASPATH	3-21
3.12	INPATH	3-23
3.13	MDATA.....	3-29
3.14	MINUS (-).....	3-31
3.15	MNOT	3-31
3.16	Narrower Term (NT, NTG, NTP, NTI).....	3-32
3.17	NDATA	3-34
3.18	NEAR (;)	3-36
3.19	NOT (~)	3-39
3.20	OR ()	3-40
3.21	Preferred Term (PT).....	3-41
3.22	Related Term (RT).....	3-41
3.23	SDATA	3-42
3.24	soundex (!)	3-45
3.25	stem (\$)	3-45
3.26	Stored Query Expression (SQE).....	3-46
3.27	SYNonym (SYN)	3-47
3.28	threshold (>)	3-48
3.29	Translation Term (TR).....	3-48
3.30	Translation Term Synonym (TRSYN).....	3-49

3.31	Top Term (TT)	3-50
3.32	weight (*).....	3-51
3.33	wildcards (% _).....	3-52
3.34	WITHIN.....	3-54
4	Special Characters in Oracle Text Queries	
4.1	Grouping Characters	4-1
4.2	Escape Characters	4-1
4.3	Reserved Words and Characters	4-2
5	CTX_ADM Package	
5.1	About CTX_ADM Package Procedures.....	5-1
5.2	MARK_FAILED	5-1
5.3	RECOVER	5-2
5.4	RESET_AUTO_OPTIMIZE_STATUS	5-2
5.5	SET_PARAMETER	5-3
6	CTX_ANL Package	
6.1	About CTX_ANL Package Procedures.....	6-1
6.2	ADD_DICTIONARY	6-1
6.3	DROP_DICTIONARY	6-4
7	CTX_CLS Package	
7.1	About CTX_CLS Package Procedures	7-1
7.2	TRAIN	7-1
7.3	CLUSTERING.....	7-4
8	CTX_DDL Package	
8.1	ADD_ATTR_SECTION.....	8-3
8.2	ADD_AUTO_OPTIMIZE.....	8-4
8.3	ADD_FIELD_SECTION.....	8-5
8.4	ADD_INDEX	8-8
8.5	ADD_MDATA	8-9
8.6	ADD_MDATA_COLUMN	8-11
8.7	ADD_MDATA_SECTION.....	8-12
8.8	ADD_NDATA_SECTION	8-13
8.9	ADD_SDATA_COLUMN	8-14
8.10	ADD_SDATA_SECTION	8-16
8.11	ADD_SEC_GRP_ATTR_VAL	8-17
8.12	ADD_SPECIAL_SECTION	8-18
8.13	ADD_STOPCLASS	8-19
8.14	ADD_STOP_SECTION	8-21
8.15	ADD_STOPTHEME	8-22

8.16	ADD_STOPWORD	8-23
8.17	ADD_SUB_LEXER	8-24
8.18	ADD_ZONE_SECTION	8-26
8.19	COPY_POLICY	8-29
8.20	CREATE_INDEX_SET	8-29
8.21	CREATE_POLICY	8-30
8.22	CREATE_PREFERENCE	8-31
8.23	CREATE_SECTION_GROUP	8-34
8.24	CREATE_SHADOW_INDEX.....	8-37
8.25	CREATE_STOPLIST	8-39
8.26	DROP_INDEX_SET	8-40
8.27	DROP_POLICY	8-40
8.28	DROP_PREFERENCE	8-41
8.29	DROP_SECTION_GROUP	8-41
8.30	DROP_SHADOW_INDEX	8-42
8.31	DROP_STOPLIST	8-42
8.32	EXCHANGE_SHADOW_INDEX	8-43
8.33	OPTIMIZE_INDEX.....	8-44
8.34	POPULATE_PENDING.....	8-50
8.35	PREFERENCE_IMPLICIT_COMMIT	8-50
8.36	RECREATE_INDEX_ONLINE	8-51
8.37	REM_SEC_GRP_ATTR_VAL.....	8-58
8.38	REMOVE_AUTO_OPTIMIZE.....	8-58
8.39	REMOVE_INDEX	8-59
8.40	REMOVE_MDATA	8-59
8.41	REMOVE_SECTION	8-60
8.42	REMOVE_STOPCLASS	8-61
8.43	REMOVE_STOPTHEME	8-61
8.44	REMOVE_STOPWORD	8-62
8.45	REMOVE_SUB_LEXER.....	8-63
8.46	REPLACE_INDEX_METADATA	8-63
8.47	SET_ATTRIBUTE	8-64
8.48	SET_SEC_GRP_ATTR	8-65
8.49	SET_SECTION_ATTRIBUTE	8-66
8.50	SYNC_INDEX	8-68
8.51	UNSET_ATTRIBUTE	8-70
8.52	UNSET_SEC_GRP_ATTR	8-71
8.53	UPDATE_SUB_LEXER	8-71
8.54	UPDATE_POLICY.....	8-72
8.55	UPDATE_SDATA.....	8-73

9 CTX_DOC Package

9.1	About CTX_DOC Package Procedures.....	9-2
-----	---------------------------------------	-----

9.2	FILTER	9-2
9.3	GIST	9-5
9.4	HIGHLIGHT	9-9
9.5	IFILTER	9-12
9.6	MARKUP	9-13
9.7	PKENCODE	9-19
9.8	POLICY_FILTER.....	9-20
9.9	POLICY_GIST	9-21
9.10	POLICY_HIGHLIGHT.....	9-23
9.11	POLICY_LANGUAGES.....	9-24
9.12	POLICY_MARKUP	9-26
9.13	POLICY_NOUN_PHRASES	9-29
9.14	POLICY_PART_OF_SPEECH.....	9-32
9.15	POLICY_SNIPPET	9-34
9.16	POLICY_STEMS.....	9-36
9.17	POLICY_THEMES.....	9-37
9.18	POLICY_TOKENS	9-39
9.19	SET_KEY_TYPE	9-40
9.20	SNIPPET	9-40
9.21	THEMES.....	9-44
9.22	TOKENS.....	9-47

10 CTX_ENTITY Package

10.1	ADD_EXTRACT_RULE.....	10-1
10.2	ADD_STOP_ENTITY	10-4
10.3	COMPILE	10-6
10.4	CREATE_EXTRACT_POLICY	10-7
10.5	DROP_EXTRACT_POLICY	10-8
10.6	EXTRACT.....	10-8
10.7	REMOVE_EXTRACT_RULE.....	10-10
10.8	REMOVE_STOP_ENTITY	10-10

11 CTX_OUTPUT Package

11.1	ADD_EVENT	11-1
11.2	ADD_TRACE	11-2
11.3	DISABLE_QUERY_STATS.....	11-4
11.4	ENABLE_QUERY_STATS.....	11-4
11.5	END_LOG.....	11-5
11.6	END_QUERY_LOG.....	11-5
11.7	GET_TRACE_VALUE.....	11-6
11.8	LOG_TRACES.....	11-6
11.9	LOGFILENAME.....	11-7
11.10	REMOVE_EVENT	11-7

11.11	REMOVE_TRACE	11-8
11.12	RESET_TRACE.....	11-8
11.13	START_LOG.....	11-9
11.14	START_QUERY_LOG.....	11-9
12	CTX_QUERY Package	
12.1	BROWSE_WORDS	12-1
12.2	COUNT_HITS	12-4
12.3	EXPLAIN.....	12-4
12.4	HFEEDBACK	12-7
12.5	REMOVE_SQE	12-10
12.6	RESULT_SET	12-11
12.7	RESULT_SET_DOCUMENT	12-17
12.8	STORE_SQE.....	12-18
13	CTX_REPORT Package	
13.1	Description of Procedures in CTX_REPORT	13-1
13.2	Using the Function Versions	13-2
13.3	DESCRIBE_INDEX	13-2
13.4	DESCRIBE_POLICY	13-3
13.5	CREATE_INDEX_SCRIPT.....	13-4
13.6	CREATE_POLICY_SCRIPT.....	13-5
13.7	INDEX_SIZE.....	13-5
13.8	INDEX_STATS	13-6
13.9	QUERY_LOG_SUMMARY	13-10
13.10	TOKEN_INFO	13-14
13.11	TOKEN_TYPE	13-15
13.12	VALIDATE_INDEX.....	13-17
14	CTX_THES Package	
14.1	ALTER_PHRASE	14-2
14.2	ALTER_THESAURUS.....	14-4
14.3	BT	14-4
14.4	BTG	14-6
14.5	BTI	14-7
14.6	BTP	14-9
14.7	CREATE_PHRASE	14-10
14.8	CREATE_RELATION	14-11
14.9	CREATE_THESAURUS	14-12
14.10	CREATE_TRANSLATION	14-13
14.11	DROP_PHRASE.....	14-13
14.12	DROP_RELATION	14-14
14.13	DROP_THESAURUS	14-16

14.14	DROP_TRANSLATION	14-16
14.15	EXPORT_THESAURUS.....	14-17
14.16	HAS_RELATION.....	14-18
14.17	IMPORT_THESAURUS.....	14-18
14.18	NT	14-19
14.19	NTG	14-21
14.20	NTI	14-22
14.21	NTP	14-24
14.22	OUTPUT_STYLE	14-25
14.23	PT	14-25
14.24	RT	14-27
14.25	SN.....	14-28
14.26	SYN	14-28
14.27	THES_TT	14-30
14.28	TR	14-31
14.29	TRSYN	14-32
14.30	TT	14-34
14.31	UPDATE_TRANSLATION	14-35

15 CTX_ULEXER Package

15.1	WILDCARD_TAB.....	15-1
------	-------------------	------

16 Oracle Text Utilities

16.1	Thesaurus Loader (ctxload).....	16-1
16.1.1	ctxload Text Loading	16-1
16.1.2	ctxload Syntax.....	16-2
16.1.3	ctxload Examples.....	16-3
16.2	Entity Extraction User Dictionary Loader (ctxload)	16-3
16.2.1	ctxload Syntax.....	16-4
16.2.2	Considerations When Creating a User Dictionary	16-4
16.2.3	XML Schema	16-5
16.2.4	ctxload Example	16-6
16.3	Knowledge Base Extension Compiler (ctxkbt)	16-6
16.3.1	Knowledge Base Character Set.....	16-7
16.3.2	ctxkbt Syntax	16-7
16.3.3	ctxkbt Usage Notes.....	16-8
16.3.4	ctxkbt Limitations	16-8
16.3.5	ctxkbt Constraints on Thesaurus Terms.....	16-9
16.3.6	ctxkbt Constraints on Thesaurus Relations	16-9
16.3.7	Extending the Knowledge Base.....	16-10
16.3.8	Example for Extending the Knowledge Base	16-10
16.3.9	Adding a Language-Specific Knowledge Base	16-11
16.3.10	Limitations for Adding a Knowledge Base	16-11

16.3.11	Order of Precedence for Multiple Thesauri	16-11
16.3.12	Size Limits for Extended Knowledge Base	16-12
16.4	Lexical Compiler (ctxlc)	16-12
16.4.1	Syntax of ctxlc	16-12
16.4.2	ctxlc Performance Considerations	16-13
16.4.3	ctxlc Usage Notes	16-13
16.4.4	ctxlc Example	16-13
17	Oracle Text Alternative Spelling	
17.1	Overview of Alternative Spelling Features.....	17-1
17.1.1	Alternate Spelling.....	17-2
17.1.2	Base-Letter Conversion.....	17-2
17.1.3	New German Spelling	17-3
17.2	Overriding Alternative Spelling Features	17-3
17.3	Alternative Spelling Conventions	17-4
17.3.1	German Alternate Spelling Conventions.....	17-4
17.3.2	Danish Alternate Spelling Conventions.....	17-4
17.3.3	Swedish Alternate Spelling Conventions	17-5
A	Oracle Text Result Tables	
A.1	CTX_QUERY Result Tables.....	A-1
A.1.1	EXPLAIN Table	A-1
A.1.2	HFEEDBACK Table	A-3
A.2	CTX_DOC Result Tables.....	A-6
A.2.1	Filter Table.....	A-7
A.2.2	Gist Table.....	A-7
A.2.3	Highlight Table.....	A-7
A.2.4	Markup Table.....	A-8
A.2.5	Theme Table	A-8
A.2.6	Token Table.....	A-9
A.3	CTX_THES Result Tables and Data Types	A-9
A.3.1	EXP_TAB Table Type.....	A-9
B	Oracle Text Supported Document Formats	
B.1	About Document Filtering Technology	B-1
B.1.1	Latest Updates for Patch Releases	B-1
B.1.2	Restrictions on Format Support	B-2
B.1.3	Supported Platforms for AUTO_FILTER Document Filtering Technology.....	B-2
B.1.4	Filtering on PDF Documents and Security Settings.....	B-3
B.1.5	PDF Filtering Limitations	B-4
B.1.6	Environment Variables	B-4
B.1.7	General Limitations	B-4
B.2	Supported Document Formats	B-4

B.2.1	Archive File Format	B-5
B.2.2	Database Formats	B-6
B.2.3	Email Formats	B-7
B.2.4	Graphic Formats (Raster and Vector Image)	B-8
B.2.5	Multimedia Formats	B-11
B.2.6	Other Formats	B-12
B.2.7	Presentation Formats	B-13
B.2.8	Spreadsheet Formats	B-14
B.2.9	Text and Markup Formats	B-15
B.2.10	Word Processing and Desktop Publishing Formats	B-15
C	Text Loading Examples for Oracle Text	
C.1	SQL INSERT Example	C-1
C.2	SQL*Loader Example	C-1
C.2.1	Creating the Table	C-1
C.2.2	Issuing the SQL*Loader Command	C-2
C.3	Structure of ctxload Thesaurus Import File	C-3
C.3.1	Import File Format	C-3
C.3.2	Alternate Hierarchy Structure	C-6
C.3.3	Usage Notes for Terms in Import Files	C-6
C.3.4	Usage Notes for Relationships in Import Files	C-7
C.3.5	Examples of Import Files	C-7
D	Oracle Text Multilingual Features	
D.1	Introduction	D-1
D.2	Indexing	D-1
D.2.1	Multilingual Features for Text Index Types	D-1
D.2.2	Lexer Types	D-3
D.2.3	Basic Lexer Features	D-3
D.2.4	Multi Lexer Features	D-5
D.2.5	World Lexer Features	D-5
D.3	Querying	D-7
D.4	Supplied Stop Lists	D-7
D.5	Knowledge Base	D-8
D.6	Multilingual Features Matrix	D-8
E	Oracle Text Supplied Stoplists	
E.1	English Default Stoplist	E-1
E.2	Chinese Stoplist (Traditional)	E-5
E.3	Chinese Stoplist (Simplified)	E-5
E.4	Danish (dk) Default Stoplist	E-6
E.5	Dutch (nl) Default Stoplist	E-8
E.6	Finnish (sf) Default Stoplist	E-16

E.7	French (f) Default Stoplist	E-22
E.8	German (d) Default Stoplist	E-28
E.9	Italian (i) Default Stoplist	E-35
E.10	Portuguese (pt) Default Stoplist	E-40
E.11	Spanish (e) Default Stoplist	E-42
E.12	Swedish (s) Default Stoplist	E-47
F	The Oracle Text Scoring Algorithm	
F.1	Scoring Algorithm for Word Queries	F-1
F.2	Word Scoring Example	F-2
F.3	DML and Scoring Algorithm	F-2
G	Oracle Text Views	
G.1	CTX_ALEXER_DICTS	G-3
G.2	CTX_AUTO_OPTIMIZE_INDEXES	G-3
G.3	CTX_AUTO_OPTIMIZE_STATUS	G-3
G.4	CTX_CLASSES	G-3
G.5	CTX_FILTER_BY_COLUMNS	G-4
G.6	CTX_FILTER_CACHE_STATISTICS	G-4
G.7	CTX_INDEXES	G-5
G.8	CTX_INDEX_ERRORS	G-6
G.9	CTX_INDEX_OBJECTS	G-6
G.10	CTX_INDEX_PARTITIONS	G-6
G.11	CTX_INDEX_SETS	G-7
G.12	CTX_INDEX_SET_INDEXES	G-7
G.13	CTX_INDEX_SUB_LEXERS	G-7
G.14	CTX_INDEX_SUB_LEXER_VALUES	G-7
G.15	CTX_INDEX_VALUES	G-8
G.16	CTX_OBJECTS	G-8
G.17	CTX_OBJECT_ATTRIBUTES	G-8
G.18	CTX_OBJECT_ATTRIBUTE_LOV	G-9
G.19	CTX_ORDER_BY_COLUMNS	G-9
G.20	CTX_PARAMETERS	G-10
G.21	CTX_PENDING	G-11
G.22	CTX_PREFERENCES	G-12
G.23	CTX_PREFERENCE_VALUES	G-12
G.24	CTX_SECTIONS	G-12
G.25	CTX_SECTION_GROUPS	G-13
G.26	CTX_SQES	G-13
G.27	CTX_STOPLISTS	G-13
G.28	CTX_STOPWORDS	G-14
G.29	CTX_SUB_LEXERS	G-14
G.30	CTX_THESAURI	G-14

G.31	CTX_THES_PHRASES.....	G-15
G.32	CTX_TRACE_VALUES.....	G-15
G.33	CTX_USER_ALEXER_DICTS	G-15
G.34	CTX_USER_AUTO_OPTIMIZE_INDEXES	G-15
G.35	CTX_USER_EXTRACT_POLICIES	G-16
G.36	CTX_USER_EXTRACT_POLICY_VALUES	G-16
G.37	CTX_USER_EXTRACT_RULES.....	G-16
G.38	CTX_USER_EXTRACT_STOP_ENTITIES	G-17
G.39	CTX_USER_FILTER_BY_COLUMNS.....	G-17
G.40	CTX_USER_INDEXES.....	G-17
G.41	CTX_USER_INDEX_ERRORS	G-18
G.42	CTX_USER_INDEX_OBJECTS	G-19
G.43	CTX_USER_INDEX_PARTITIONS.....	G-19
G.44	CTX_USER_INDEX_SETS	G-20
G.45	CTX_USER_INDEX_SET_INDEXES.....	G-20
G.46	CTX_USER_INDEX_SUB_LEXERS.....	G-20
G.47	CTX_USER_INDEX_SUB_LEXER_VALS	G-21
G.48	CTX_USER_INDEX_VALUES.....	G-21
G.49	CTX_USER_ORDER_BY_COLUMNS	G-21
G.50	CTX_USER_PENDING	G-22
G.51	CTX_USER_PREFERENCES.....	G-22
G.52	CTX_USER_PREFERENCE_VALUES	G-22
G.53	CTX_USER_SECTIONS	G-23
G.54	CTX_USER_SECTION_GROUPS.....	G-23
G.55	CTX_USER_SESSION_SQES.....	G-23
G.56	CTX_USER_SQES	G-23
G.57	CTX_USER_STOPLISTS	G-24
G.58	CTX_USER_STOPWORDS.....	G-24
G.59	CTX_USER_SUB_LEXERS	G-24
G.60	CTX_USER_THESAURI	G-25
G.61	CTX_USER_THES_PHRASES	G-25
G.62	CTX_VERSION	G-25

H Stopword Transformations in Oracle Text

H.1	Understanding Stopword Transformations	H-1
H.2	About Stopwords in Phrase Queries	H-2
H.3	Word Transformations	H-2
H.4	AND Transformations	H-3
H.5	OR Transformations	H-3
H.6	ACCUMulate Transformations	H-3
H.7	MINUS Transformations.....	H-4
H.8	MNOT Transformations.....	H-4
H.9	NOT Transformations	H-4

H.10	EQUIValence Transformations	H-5
H.11	NEAR Transformations	H-5
H.12	Weight Transformations	H-6
H.13	Threshold Transformations	H-6
H.14	WITHIN Transformations	H-6

Index

List of Tables

1-1	ALTER INDEX SYNC Methods.....	1-8
1-2	CATSEARCH Query Operators.....	1-24
1-3	TRANSFORM Parameters.....	1-31
1-4	Template Attribute Values.....	1-35
1-5	SYNC Types.....	1-52
1-6	Supported CTXCAT Index Preferences.....	1-60
2-1	Datastore Types.....	2-2
2-2	MULTI_COLUMN_DATASTORE Attributes.....	2-4
2-3	DETAIL_DATASTORE Attributes.....	2-7
2-4	FILE_DATASTORE Attributes.....	2-10
2-5	URL_DATASTORE Attributes.....	2-12
2-6	USER_DATASTORE Attributes.....	2-14
2-7	NESTED_DATASTORE Attributes.....	2-17
2-8	Filter Types.....	2-19
2-9	AUTO_FILTER Attributes.....	2-20
2-10	MAIL_FILTER Attributes.....	2-23
2-11	USER_FILTER Attribute.....	2-26
2-12	PROCEDURE_FILTER Attributes.....	2-29
2-13	Lexer Types.....	2-32
2-14	Languages Supported for AUTO_LEXER.....	2-33
2-15	AUTO_LEXER Language-Independent Attributes.....	2-35
2-16	AUTO_LEXER Language-Dependent Attributes.....	2-38
2-17	Default Values for AUTO_LEXER Language-Dependent Attributes.....	2-38
2-18	Supported Languages for AUTO_LEXER Dictionary Attribute.....	2-40
2-19	BASIC_LEXER Attributes.....	2-41
2-20	Stemming User-Dictionaries.....	2-47
2-21	Languages Supported for MULTI_LEXER Auto-detection.....	2-51
2-22	CHINESE_VGRAM_LEXER Attributes.....	2-52
2-23	CHINESE_LEXER Attributes.....	2-53
2-24	JAPANESE_VGRAM_LEXER Attributes.....	2-53
2-25	JAPANESE_LEXER Attributes.....	2-55
2-26	KOREAN_MORPH_LEXER Dictionaries.....	2-56
2-27	KOREAN_MORPH_LEXER Attributes.....	2-57
2-28	User-Defined Routines for USER_LEXER.....	2-59
2-29	USER_LEXER Attributes.....	2-60
2-30	VARCHAR2 Interface for INDEX_PROCEEDURES.....	2-61
2-31	CLOB Interface for INDEX_PROCEDURE.....	2-62
2-32	User-defined Lexer Query Procedure XML Schema Attributes.....	2-63
2-33	User-defined Lexer Indexing Procedure XML Schema Element Names.....	2-65
2-34	User-defined Lexer Indexing Procedure XML Schema Attributes.....	2-68
2-35	User-defined Lexer Query Procedure XML Schema Attributes.....	2-70
2-36	WORLD_LEXER Attribute.....	2-72
2-37	BASIC_WORDLIST Attributes.....	2-73
2-38	Storage Types.....	2-81
2-39	BASIC_STORAGE Attributes.....	2-81
2-40	Section Group Types.....	2-86
2-41	RULE_CLASSIFIER Attributes.....	2-90
2-42	SVM_CLASSIFIER Attributes.....	2-91
2-43	KMEAN_CLUSTERING Attributes.....	2-92
2-44	General System Parameters.....	2-99
2-45	Default CONTEXT Index Parameters.....	2-99

2-46	Default CTXCAT Index Parameters.....	2-101
2-47	Default CTXRULE Index Parameters.....	2-101
2-48	Default Policy Parameters for CTX_DDL.CREATE_POLICY.....	2-102
3-1	Query Expression Precedence Examples.....	3-3
3-2	MDATA and Other Query Operators.....	3-30
3-3	Score Samples.....	3-52
4-1	Characters for Grouping Query Terms.....	4-1
4-2	Characters for Escaping Query Terms.....	4-2
4-3	Reserved Words and Characters.....	4-3
6-1	Custom Dictionary Valid Parts-of-Speech (case sensitive).....	6-3
6-2	Custom Dictionary Valid Features.....	6-3
8-1	Paragraph and Sentence Section Boundaries.....	8-18
9-1	Part of Speech Abbreviations.....	9-30
9-2	Required Columns for Token Tables.....	9-48
10-1	Supplied Entity Types.....	10-2
11-1	Available Traces.....	11-3
16-1	Size Limit for the Extended Knowledge Base.....	16-12
17-1	German Alternate Spelling Conventions.....	17-4
17-2	Danish Alternate Spelling Conventions.....	17-4
17-3	Swedish Alternate Spelling Conventions.....	17-5
A-1	EXPLAIN Result Table.....	A-1
A-2	EXPLAIN Table OPERATION Column.....	A-2
A-3	EXPLAIN Table OPTIONS Column.....	A-3
A-4	HFEEDBACK Results Table.....	A-4
A-5	HFEEDBACK Results Table OPERATION Column.....	A-5
A-6	HFEEDBACK Results Table OPTIONS Column.....	A-5
A-7	CTX_FEEDBACK_ITEM_TYPE.....	A-6
A-8	FILTER Result Table.....	A-7
A-9	Gist Table.....	A-7
A-10	Highlight Table.....	A-8
A-11	Markup Table.....	A-8
A-12	Theme Table.....	A-8
A-13	Token Table.....	A-9
A-14	EXP_TAB Table Type (EXP_REC).....	A-9
B-1	AUTO_FILTER Behavior with PDF Security Settings.....	B-3
B-2	Supported Archive File Formats.....	B-5
B-3	Supported Raster Image Formats for AUTO_FILTER Filter.....	B-9
B-4	Supported Vector Image Formats for AUTO_FILTER Filter.....	B-10
D-1	Oracle Text Lexer Types.....	D-3
D-2	Languages Supported by the World Lexer (Space-separated).....	D-5
D-3	Languages Supported by the World Lexer (Non-space-separated).....	D-6
D-4	Languages Not Supported by the World Lexer.....	D-6
D-5	Multilingual Features for Supported Languages.....	D-8

Preface

Welcome to *Oracle Text Reference*. This document provides reference information for building applications with Oracle Text. This preface contains the following topics:

- [Audience](#) (page xix)
- [Documentation Accessibility](#) (page xix)
- [Related Documents](#) (page xix)
- [Conventions](#) (page xx)

Audience

This document is intended for application developers and system administrators who maintain an Oracle Text system in an Oracle environment. To use this document, you need experience with Oracle Database, SQL, SQL*Plus, and PL/SQL.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documents

For more information about Oracle Text, see:

- *Oracle Text Application Developer's Guide*

For more information about Oracle Database, see:

- *Oracle Database Concepts*
- *Oracle Database Administrator's Guide*
- *Oracle Database Utilities*
- *Oracle Database Performance Tuning Guide*
- *Oracle Database SQL Tuning Guide*
- *Oracle Database SQL Language Reference*
- *Oracle Database Reference*
- *Oracle Database Development Guide*
- *Oracle Database Sample Schemas*

For more information about PL/SQL, see:

- *Oracle Database PL/SQL Language Reference*

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Changes in This Release for Oracle Text Reference

This preface points you to changes in Oracle Text for this release.

- [Changes in Oracle Text 12c Release 1 \(12.1\)](#) (page xxi)

Changes in Oracle Text 12c Release 1 (12.1)

The changes in Oracle Text for Oracle Database 12c Release 1 (12.1) are described in the following topics.

- [New Features](#) (page xxi)
- [Deprecated Features](#) (page xxi)
- [Desupported Features](#) (page xxi)

New Features

The new features introduced in this release for Oracle Text are listed and described in the New Features section of *Oracle Text Application Developer's Guide*. For a complete list of new features for Oracle Database 12c, see *Oracle Database New Features Guide*.

Deprecated Features

Some features that are deprecated in this release for Oracle XML Database may affect Oracle Text XML applications. See *Oracle Database Upgrade Guide* for information on Oracle XML Database deprecations and changes.

Desupported Features

The following Oracle Text features are desupported in this release:

- CTXXPATH is desupported in Oracle Database 12c Release 1 (12.1). This does not affect the CTXCAT index type. Use XMLIndex indexes instead. See *Oracle XML DB Developer's Guide* for information about XMLIndex.
- ALTER INDEX OPTIMIZE for Text Indexes is desupported in Oracle Database 12c Release 1 (12.1). The ALTER INDEX OPTIMIZE [token index_token | fast | full [maxtime (time | unlimited)]] operation is not supported for Oracle Database 12c. To optimize your index, use CTX_DDL.OPTIMIZE_INDEX. See "[OPTIMIZE_INDEX](#) (page 8-44)" for information about OPTIMIZE_INDEX.

- SYNC [MEMORY memsize] for Text Indexes is desupported in Oracle Database 12c Release 1 (12.1). To synchronize your index, use CTX_DDL.SYNC_INDEX. See "[SYNC_INDEX](#) (page 8-68)" for information about SYNC_INDEX.
- The CHARSET_FILTER filter type is desupported in Oracle Database 12c Release 1 (12.1).

See *Oracle Database Upgrade Guide* for a complete list of desupported features for Oracle Database 12c.

Oracle Text SQL Statements and Operators

This chapter describes the SQL statements and Oracle Text operators for creating and managing Oracle Text indexes and performing Oracle Text queries.

The following statements are described in this chapter:

- [ALTER INDEX](#) (page 1-1)
- [ALTER TABLE: Supported Partitioning Statements](#) (page 1-18)
- [CATSEARCH](#) (page 1-23)
- [CONTAINS](#) (page 1-29)
- [CREATE INDEX](#) (page 1-40)
- [DROP INDEX](#) (page 1-63)
- [MATCHES](#) (page 1-63)
- [MATCH_SCORE](#) (page 1-65)
- [SCORE](#) (page 1-65)

1.1 ALTER INDEX

Note:

This section describes the `ALTER INDEX` statement as it pertains to managing an Oracle Text domain index.

For a complete description of the `ALTER INDEX` statement, see *Oracle Database SQL Language Reference*.

ALTER INDEX Purpose

Use `ALTER INDEX` to make changes to, or perform maintenance tasks for a `CONTEXT`, `CTXCAT`, or `CTXRULE` index.

All Index Types

Use `ALTER INDEX` to perform the following tasks on all Oracle Text index types:

- Rename the index or index partition. See "[ALTER INDEX RENAME Syntax](#) (page 1-4)".
- Rebuild the index using different preferences. Some restrictions apply for the `CTXCAT` index type. See "[ALTER INDEX REBUILD Syntax](#) (page 1-4)".

- Add stopwords to the index. See "[ALTER INDEX REBUILD Syntax](#) (page 1-4)".
- Add or remove a sub_lexer, and remove a stopword or set of stopwords for a given symbol (language or language-independent). See "[ALTER INDEX Sub_Lexer Syntax](#) (page 1-12)"

CONTEXT and CTXRULE Index Types

Use ALTER INDEX to perform the following tasks on CONTEXT and CTXRULE index types:

- Resume a failed index operation (creation/optimization).
- Add sections and stop sections to the index.
- Replace index metadata.

See Also:

"[ALTER INDEX REBUILD Syntax](#) (page 1-4)" to learn more about performing these tasks

Overview of ALTER INDEX Syntax

The syntax for ALTER INDEX is fairly complex. The major divisions are covered in the following sections:

- "[ALTER INDEX MODIFY PARTITION Syntax](#) (page 1-2)"—use this to modify an index partition's metadata.
- "[ALTER INDEX PARAMETERS Syntax](#) (page 1-3)"—use this to modify the parameters of a nonpartitioned index, or to modify all partitions of a local partitioned index, without rebuilding the index.
- "[ALTER INDEX RENAME Syntax](#) (page 1-4)"—use this to rename an index or index partition.
- "[ALTER INDEX REBUILD Syntax](#) (page 1-4)"—use this to rebuild an index or index partition. With this statement, you can also replace index metadata; add stopwords, sections, and stop sections to an index; and resume a failed operation.

The parameters for ALTER INDEX REBUILD have their own syntax, which is a subset of the syntax for ALTER INDEX. For example, the ALTER INDEX REBUILD PARAMETERS statement can take either REPLACE or RESUME as an argument, and ALTER INDEX REBUILD PARAMETERS ('REPLACE') can take several arguments. Valid examples of ALTER INDEX REBUILD include the following statements:

```
ALTER INDEX REBUILD PARALLEL n
ALTER INDEX REBUILD PARAMETERS ( 'REPLACE DATASTORE datastore_pref' )
ALTER INDEX REBUILD PARAMETERS ( 'REPLACE WORDLIST wordlist_pref' )
```

ALTER INDEX MODIFY PARTITION Syntax

Use the following syntax to modify the metadata of an index partition:

```
ALTER INDEX index_name MODIFY PARTITION partition_name PARAMETER (paramstring)
```


index_name

Specify the name of the index whose partition metadata you want to modify.

partition_name

Specify the name of the index partition whose metadata you want to modify.

paramstring

The only valid argument here is 'REPLACE METADATA'. This follows the same syntax as ALTER INDEX REBUILD PARTITION PARAMETERS ('REPLACE METADATA'); see the REPLACE METADATA subsection of the "[ALTER INDEX REBUILD Syntax](#) (page 1-4)" section for more information. (The two statements are equivalent. ALTER INDEX MODIFY PARTITION is offered for ease of use, and is the recommended syntax.)

ALTER INDEX PARAMETERS Syntax

Use the following syntax to modify the parameters either of nonpartitioned or local partitioned indexes, without rebuilding the index. For partitioned indexes, this statement works at the index level, not at the partition level. This statement changes information for the entire index, including all partitions.

```
ALTER INDEX index_name PARAMETERS (paramstring)
```

paramstring

ALTER INDEX PARAMETERS accepts the following arguments for *paramstring*:

- 'REPLACE METADATA'
Replaces current metadata. See the REPLACE METADATA subsection of the "[ALTER INDEX REBUILD Syntax](#) (page 1-4)" section for more information.
- 'ADD STOPWORD'
Dynamically adds a stopword to an index. See the ADD STOPWORD subsection of the "[ALTER INDEX REBUILD Syntax](#) (page 1-4)" section for more information.
- 'ADD FIELD SECTION'
Dynamically adds a field section to an index. See the ADD FIELD subsection of the "[ALTER INDEX REBUILD Syntax](#) (page 1-4)" section for more information. You can add an unlimited number of field sections.
- 'ADD ZONE SECTION'
Dynamically adds a zone section to an index. See the ADD ZONE subsection of the "[ALTER INDEX REBUILD Syntax](#) (page 1-4)" section for more information.
- 'ADD ATTR SECTION'
Dynamically adds an attribute section to an index. See the ADD ATTR subsection of the "[ALTER INDEX REBUILD Syntax](#) (page 1-4)" section for more information.
- 'ADD SDATA SECTION'
Dynamically adds an SDATA section to an index, without rebuilding the index. An SDATA section can only be added to BASIC, HTML, XML, and NEWS section groups. It supports both global as well as local indexes. The syntax is:

```
ALTER INDEX index_name PARAMETERS (ADD SDATA SECTION sdata_section_name TAG
sdata_section_tag DATATYPE sdata_section_datatype);
```

The datatype can be VARCHAR2, CHAR, NUMBER, DATE, or RAW.

See "[Adding an SDATA Section](#) (page 1-17)" for more information.

Each of the above described parameters has an equivalent ALTER INDEX REBUILD PARAMETERS version, except ADD SDATA SECTION.

For example, ALTER INDEX PARAMETERS ('REPLACE METADATA') is equivalent to ALTER INDEX REBUILD PARAMETERS ('REPLACE METADATA'). However, the ALTER INDEX PARAMETERS versions work on either partitioned or nonpartitioned indexes, whereas the ALTER INDEX REBUILD PARAMETERS versions work only on nonpartitioned indexes.

ALTER INDEX RENAME Syntax

Use the following syntax to rename an index or index partition:

```
ALTER INDEX [schema.]index_name RENAME TO new_index_name;
```

```
ALTER INDEX [schema.]index_name RENAME PARTITION part_name TO new_part_name;
```

[*schema.*]*index_name*

Specify the name of the index to rename.

new_index_name

Specify the new name for *schema.index*. The *new_index_name* parameter can be no more than 25 bytes, and 21 bytes for a partitioned index. If you specify a name longer than 25 bytes (or longer than 21 bytes for a partitioned index), then Oracle Text returns an error and the renamed index is no longer valid.

Note:

When *new_index_name* is more than 25 bytes (21 for local partitioned index) and less than 30 bytes, Oracle Text renames the index, even though the system returns an error. To drop the index and associated tables, you must drop *new_index_name* with the DROP INDEX statement and then re-create and drop *index_name*.

part_name

Specify the name of the index partition to rename.

new_part_name

Specify the new name for partition.

ALTER INDEX REBUILD Syntax

Use ALTER INDEX REBUILD to rebuild an index, rebuild an index partition, resume a failed operation, replace index metadata, add stopwords to an index, or add sections and stop sections to an index.

The ALTER INDEX REBUILD syntax has its own subsyntax. That is, its parameters have their own syntax. For example, the ALTER INDEX REBUILD PARAMETERS statement can take either REPLACE or RESUME as an argument, and ALTER INDEX REBUILD PARAMETERS ('REPLACE') has several arguments it can take.

Valid examples of ALTER INDEX REBUILD include the following statements:

```
ALTER INDEX REBUILD PARALLEL n
ALTER INDEX REBUILD PARAMETERS (REPLACE DATASTORE datastore_pref)
ALTER INDEX REBUILD PARAMETERS (REPLACE WORDLIST wordlist_pref)
```

This is the syntax for ALTER INDEX REBUILD:

```
ALTER INDEX [schema.]index [REBUILD] [PARTITION partname] [ONLINE] [PARAMETERS
(paramstring)] [PARALLEL N];
```

PARTITION *partname*

Rebuilds the index partition *partname*. Only one index partition can be built at a time.

When you rebuild a partition you can specify only RESUME or REPLACE in *paramstring*. These operations work only on the *partname* you specify.

With the REPLACE operation, you can specify MEMORY, STORAGE, and SYNC for each index partition.

Adding Partitions To add a partition to the base table, use the ALTER TABLE SQL statement. When you add a partition to an indexed table, Oracle Text automatically creates the metadata for the new index partition. The new index partition has the same name as the new table partition. Change the index partition name with ALTER INDEX RENAME.

Splitting or Merging Partitions Splitting or merging a table partition with ALTER TABLE renders the index partitions invalid. You must rebuild them with ALTER INDEX REBUILD.

ONLINE

Enables you to continue to perform updates, insertions, and deletions on a base table. It does not enable you to query the base table. The ONLINE keyword can only be used with the Enterprise Edition of Oracle Database.

Note:

You can specify REPLACE or RESUME when rebuilding an index or an index partition ONLINE.

PARAMETERS (*paramstring*)

Optionally specify *paramstring*. If you do not specify *paramstring*, then Oracle Text rebuilds the index with existing preference settings.

The syntax for *paramstring* is as follows:

```
paramstring =
'REPLACE
  [DATASTORE datastore_pref]
  [FILTER filter_pref]
  [LEXER lexer_pref]
  [WORDLIST wordlist_pref]
  [STORAGE storage_pref]
  [STOPLIST stoplist]
  [SECTION GROUP section_group]
  [MEMORY memsize]
```

```
[[POPULATE | NOPOPULATE]
[INDEX SET index_set]

[METADATA preference new_preference]
[METADATA FORMAT COLUMN format_column_name]
[[METADATA] SYNC (MANUAL | EVERY "interval-string" | ON COMMIT)]
[[METADATA] TRANSACTIONAL|NONTRANSACTIONAL

| RESUME [memory memsize]
| OPTIMIZE [token index_token | fast | full [maxtime (time | unlimited)]]
| ADD STOPWORD word [language language]
| ADD ZONE SECTION section_name tag tag
| ADD FIELD SECTION section_name tag tag [(VISIBLE | INVISIBLE)]
| ADD ATTR SECTION section_name tag tag@attr
| ADD STOP SECTION tag'
```

REPLACE [*optional_preference_list*]

Rebuilds an index. You can optionally specify your own preferences, or system-defined preferences.

You can replace only preferences that are supported for that index type. For instance, you cannot replace index set for a CONTEXT or CTXRULE index. Similarly, for the CTXCAT index type, you can replace lexer, wordlist, storage index set, and memory preferences.

The POPULATE parameter is the default and need not be specified. If you want to empty the index of its contents, then specify NOPOPULATE. Clear an index of its contents when you must rebuild your index incrementally. The NOPOPULATE choice is available for a specific partition of the index, and not just for the entire index.

If you are rebuilding a partitioned index using the REPLACE parameter, then you can specify only STORAGE, MEMORY, and NOPOPULATE.

A new wordlist preference SEPARATE_OFFSETS specifies that the *token_info* in the index is stored as *docids* only in one place, and *offsets* is stored only in another place. Refer to *Oracle Text Application Developer's Guide* for information on improved response time using the SEPARATE_OFFSETS option of CONTEXT index.

Note:

If this procedure modifies the existing index tables for only the following storage attributes of the BASIC_STORAGE type (any one of them), then it will not result in re-indexing of data:

- BIG_IO
 - I_INDEX_CLAUSE
 - I_TABLE_CLAUSE
 - SEPARATE_OFFSETS
-

See Also:

- [Oracle Text Indexing Elements](#) (page 2-1) for more information about creating and setting preferences, including information about system-defined preferences
 - *Oracle Text Application Developer's Guide* for information on improved response time using the SEPARATE_OFFSETS option of CONTEXT index
-

REPLACE METADATA *preference new_preference*

Replaces the existing preference class settings, including SYNC parameters, of the index with the settings from *new_preference*. Only index preferences and attributes are replaced. The index is not rebuilt.

This statement is useful when you want to replace a preference and its attribute settings after the index is built, without re-indexing all data. re-indexing data can require significant time and computing resources.

This statement is also useful for changing the SYNC parameter type, which can be automatic, manual, or on-commit.

The ALTER INDEX REBUILD PARAMETER ('REPLACE METADATA') statement does not work for a local partitioned index at the global level for the index. You cannot, for example, use this syntax to change a global preference, such as filter or lexer type, without rebuilding the index. Use ALTER INDEX PARAMETERS instead to change the metadata of an index at the global level, including all partitions. See "[ALTER INDEX PARAMETERS Syntax](#) (page 1-3)".

When should I use the METADATA keyword? REPLACE METADATA should be used only when the change in index metadata will not lead to an inconsistent index, which can lead to incorrect query results.

For example, use this statement in the following instances:

- To go from a single-language lexer to a multilexer in anticipation of multilingual data. For an example, see "[Replacing Index Metadata: Changing Single-Lexer to Multilexer](#) (page 1-15)".
- To change the WILDCARD_MAXTERMS setting in [BASIC_WORDLIST](#) (page 2-72).
- To change the SYNC parameter type, which can be automatic, manual, or on-commit.

These changes are safe and will not lead to an inconsistent index that might adversely affect your query results.

WARNING:

The REPLACE METADATA statement can result in inconsistent index data, which can lead to incorrect query results. As such, Oracle does not recommend using this statement, unless you carefully consider the effect it will have on the consistency of your index data and subsequent queries.

There can be many instances when changing metadata can result in inconsistent index data. For example, Oracle recommends *against* using the METADATA keyword after performing the following procedures:

- Changing the [USER_DATASTORE](#) (page 2-14) procedure to a new PL/SQL stored procedure that has different output.
- Changing the [BASIC_WORDLIST](#) (page 2-72) attribute PREFIX_INDEX from NO to YES because no prefixes have been generated for existing documents. Changing it from YES to NO is safe.
- Adding or changing BASIC_LEXER printjoin and skipjoin characters, because new queries with these characters would be lexed differently from how these characters were lexed at index time.
- Do not use REPLACE METADATA with FORWARD_INDEX. Instead use REPLACE STORAGE.

In these unsafe cases, Oracle recommends rebuilding the index.

REPLACE [METADATA] SYNC (MANUAL | EVERY "*interval-string*" | ON COMMIT)

Specifies SYNC for automatic synchronization of the CONTEXT index when a DML change has occurred to the base table. You can specify one of the SYNC methods shown in [Table 1-1](#) (page 1-8).

SYNC Type	Description
MANUAL	Means no automatic synchronization. This is the default. You must manually synchronize the index using CTX_DDL.SYNC_INDEX. Use MANUAL to disable ON COMMIT and EVERY synchronization.
EVERY <i>interval-string</i>	Automatically synchronize the index at a regular interval specified by the value of <i>interval-string</i> , which takes the same syntax as that for scheduler jobs. Automatic synchronization using EVERY requires that the index creator have CREATE JOB privileges. Ensure that <i>interval-string</i> is set to a long enough period so that any previous synchronization jobs will have completed. Otherwise, the synchronization job may hang. The <i>interval-string</i> argument must be enclosed in double quotation marks (" "). See " Enabling Automatic Index Synchronization (page 1-55)" for an example of automatic synchronization syntax.

SYNC Type	Description
ON COMMIT	<p>Synchronize the index immediately after a commit. The commit does not return until the sync is complete. (Because the synchronization is performed as a separate transaction, there may be a time period, usually small, when the data is committed but index changes are not.)</p> <p>The operation uses the memory specified with the <i>memory</i> parameter.</p> <p>Note that the sync operation has its own transaction context. If this operation fails, the data transaction still commits. Index synchronization errors are logged in the CTX_USER_INDEX_ERRORS view. See "Viewing Index Errors (page 1-58)" under CREATE INDEX.</p> <p>ON COMMIT sync works best when the STAGE_ITAB index option is enabled, because otherwise it causes significant fragmentation of the main index, requiring frequent OPTIMIZE calls. See "Enabling Automatic Index Synchronization (page 1-55)" for an example of ON COMMIT syntax. Refer to <i>Oracle Text Application Developer's Guide</i> for more information about the STAGE_ITAB option of the CONTEXT index.</p>

Each partition of a locally partitioned index can have its own type of sync: (ON COMMIT, EVERY, or MANUAL). The type of sync specified in master parameter strings applies to all index partitions unless a partition specifies its own type.

With automatic (EVERY) synchronization, you can specify memory size and parallel synchronization. The syntax is:

```
... EVERY interval_string MEMORY mem_size PARALLEL paralegree ...
```

ON COMMIT synchronizations can only be executed serially and at the same memory size as what was specified at index creation.

Note:

This command rebuilds the index. When you want to change the SYNC setting without rebuilding the index, use the REBUILD REPLACE METADATA SYNC (MANUAL | ON COMMIT) operation.

REPLACE [METADATA] TRANSACTIONAL | NONTRANSACTIONAL

This parameter enables you to turn the TRANSACTIONAL property on or off. For more information, see ["TRANSACTIONAL \(page 1-53\)"](#).

Using this parameter only succeeds if there are no rows in the DML pending queue. Therefore, you may need to sync the index before issuing this command.

To turn on the TRANSACTIONAL index property:

```
ALTER INDEX myidx REBUILD PARAMETERS('replace metadata transactional');
```

or

```
ALTER INDEX myidx REBUILD PARAMETERS('replace transactional');
```

To turn off the TRANSACTIONAL index property:

```
ALTER INDEX myidx REBUILD PARAMETERS('replace metadata nontransactional');
```

or

```
ALTER INDEX myidx REBUILD PARAMETERS('replace nontransactional');
```

RESUME [MEMORY *memsize*]

Resumes a failed index operation. You can optionally specify the amount of memory to use with *memsize*.

Note:

This ALTER INDEX operation applies only to CONTEXT and CTXRULE indexes. It does not apply to CTXCAT indexes.

ADD STOPWORD *word* [language *language*]

Dynamically adds a stopword *word* to the index.

Index entries for *word* that existed before this operation are not deleted. However, subsequent queries on *word* are treated as though it has always been a stopword.

When your stoplist is a multilanguage stoplist, you must specify *language*.

The index is *not* rebuilt by this statement.

ADD ZONE SECTION *section_name* tag *tag*

Dynamically adds the zone section *section_name* identified by *tag* to the existing index.

The added section *section_name* applies only to documents indexed after this operation. For the change to take effect, you must manually re-index any existing documents that contain the tag.

The index is *not* rebuilt by this statement.

Note:

This ALTER INDEX operation applies only to CONTEXT and CTXRULE indexes. It does not apply to CTXCAT indexes.

See Also:

["Notes \(page 1-17\)"](#)

ADD FIELD SECTION *section_name* tag *tag* [(VISIBLE | INVISIBLE)]

Dynamically adds the field section *section_name* identified by *tag* to the existing index. There is no limit to the number of field sections that can be added.

Optionally specify VISIBLE to make the field sections visible. The default is INVISIBLE.

See Also:

CTX_DDL.[ADD_FIELD_SECTION](#) (page 8-5) for more information on visible and invisible field sections

The added section *section_name* applies only to documents indexed after this operation. For the change to affect previously indexed documents, you must explicitly re-index the documents that contain the tag.

This statement does not rebuild the index.

Note:

This ALTER INDEX operation applies only to CONTEXT CTXRULE indexes. It does not apply to CTXCAT indexes.

See Also:

["Notes](#) (page 1-17)"

ADD ATTR SECTION *section_name* tag *tag@attr*

Dynamically adds an attribute section *section_name* to the existing index. You must specify the XML tag and attribute in the form *tag@attr*. You can add attribute sections only to XML section groups.

The added attribute section *section_name* applies only to documents indexed after this operation. For the change to take effect, you must manually re-index any existing documents that contain the tag.

The index is *not* rebuilt by this statement.

Note:

This ALTER INDEX operation applies only to CONTEXT CTXRULE indexes. It does not apply to CTXCAT indexes.

See Also:

["Notes](#) (page 1-17)"

ADD STOP SECTION *tag*

Dynamically adds the stop section identified by *tag* to the existing index. As stop sections apply only to automatic sectioning of XML documents, the index must use the AUTO_SECTION_GROUP section group. The tag you specify must be case sensitive and unique within the automatic section group or else ALTER INDEX raises an error.

The added stop section *tag* applies only to documents indexed after this operation. For the change to affect previously indexed documents, you must explicitly re-index the documents that contain the tag.

The text within a stop section can always be searched.

The number of stop sections you can add is unlimited.

The index is *not* rebuilt by this statement.

See Also:["Notes \(page 1-17\)"](#)

Note:

This ALTER INDEX operation applies only to CONTEXT indexes. It does not apply to CTXCAT indexes.

PARALLEL *n*

Using *n*, you can optionally specify the parallel degree for parallel indexing. This parameter is supported only when you use SYNC, REPLACE, and RESUME in paramstring. The actual degree of parallelism might be smaller depending on your resources.

Parallel indexing can speed up indexing when you have large amounts of data to index and when your operating system supports multiple CPUs.

ALTER INDEX Sub_Lexer Syntax

Use the following syntax.

See Also:

["ALTER INDEX Purpose \(page 1-1\)"](#) for list of types of indexes and syntax for ALTER INDEX

```
New paramstring =
'REPLACE
    [DATASTORE datastore_pref]
    [FILTER filter_pref]
    [LEXER lexer_pref]
    [WORDLIST wordlist_pref]
    [STORAGE storage_pref]
    [STOPLIST stoplist]
    [SECTION GROUP section_group]
    [MEMORY memsize]
    [[POPULATE | NOPOPULATE]]
    [INDEX SET index_set]

    [METADATA preference new_preference]
    [[METADATA] SYNC (MANUAL | EVERY "interval-string" | ON COMMIT)]
    [[METADATA] TRANSACTIONAL|NONTRANSACTIONAL

| RESUME [memory memsize]
| OPTIMIZE [token index_token | fast | full [maxtime (time | unlimited)]]
| SYNC [memory memsize]
| ADD STOPWORD word [language language][LANGUAGE_DEPENDENT(TRUE|FALSE)]
| ADD ZONE SECTION section_name tag tag
| ADD FIELD SECTION section_name tag tag [(VISIBLE | INVISIBLE)]
| ADD ATTR SECTION section_name tag tag@attr
| ADD STOP SECTION tag
| ADD SUB_LEXER sub_lexer_name LANGUAGE language [ALT_VALUE
alternate_value_for_language] [LANGUAGE_DEPENDENT (TRUE|FALSE)]
| REMOVE SUB_LEXER LANGUAGE language
| REMOVE STOPWORD word [LANGUAGE language]
```

```

| REMOVE STOPWORDS FOR LANGUAGE language
| MIGRATE to MULTI_STOPLIST [LANGUAGE COLUMN lang]
| MIGRATE FIELD SECTION field_section_name to [READ ONLY] MDATA
| UPDATE SUB_LEXER LANGUAGE language TO sub_lexer_preference
| ADD MDATA SECTION secname TAG sectag

```

Sub_Lexer Example

```
ALTER INDEX myidx PARAMETERS('ADD SUB_LEXER mycompany_lexer LANGUAGE mycompany
LANGUAGE_DEPENDENT FALSE');
```

```
ALTER INDEX myidx PARAMETERS('REMOVE STOPWORDS FOR LANGUAGE mycompany');
```

Sub_Lexer Notes

The language can be Oracle predefined language symbols (globalization support name or abbreviation of an Oracle Text-supported language), or user-defined symbols for language independent sub_lexer or stopword.

ADD SUB_LEXER

The following conditions apply:

- If LANGUAGE_DEPENDENT clause is not provided, it will default TRUE.
- Sync will be blocked (or it will be blocked by sync).
- If adding first language independent sub_lexer, then base table will also be locked.
- Adding first language independent sub_lexer or stopword will take longer to complete. Otherwise, it should take fraction of a second to complete unless it's being blocked by ongoing sync process on the same index.

REMOVE SUB_LEXER

Will succeed only if there are no documents with language column set to the symbol for the sub_lexer being removed.

REMOVE STOPWORD

The following conditions apply:

- If LANGUAGE clause is not specified, it is assumed that the index is using basic_stoplist. If the index is not using basic_stoplist, an error will be raised.
- If the index is using basic_stoplist (instead of multi_stoplist), then it will succeed only if the base table is empty.
- If the index is using multi_stoplist, and user specifies "ALL" for LANGUAGE clause, then it will succeed only if the base table is empty.
- If the index is using multi_stoplist, and user specifies a symbol for LANGUAGE clause, then it will succeed only if there are no documents with language column set to the symbol for the stopword being removed.

See Also:

["ALTER INDEX REBUILD Syntax \(page 1-4\)"](#)

MIGRATE TO MULTI_STOPLIST [LANGUAGE COLUMN lang]

The following conditions apply:

- Migrate the stoplist of an existing Text index to Multi_stoplist. The language of the existing stopwords will have the value of ALL.
- If LANGUAGE column has already been defined for the index:
 - LANGUAGE COLUMN can be skipped (old language column is retained for the index).
 - If LANGUAGE COLUMN is specified and there is a mismatch between index language column and the one specified, an error will be raised.
- LANGUAGE COLUMN must be specified for the index; otherwise, an error is raised.

MIGRATE FIELD SECTION TO MDATA SECTION

The following conditions apply:

- Allow user to convert a field section to MDATA section. Specify READ ONLY if the MDATA section is meant to be a READ_ONLY MDATA section (ADD and REMOVE not allowed).
- Limitation: Tokens in migrated MDATA sections will not have typical MDATA characteristics - case information, tokens being stored as it is in the document, etc. To retain these, those documents need to be reindexed.

UPDATE SUB_LEXER LANGUAGE SUB_LEXER_SYMBOL TO SUB_LEXER_PREFERENCE

The following conditions apply:

- Allows user to update sublexer dynamically.
- Language, alt_value, language dependency should remain same for the old and new sublexer preference.
- For updating the default sublexer, the syntax is:

```
UPDATE SUB_LEXER DEFAULT TO SUB_LEXER_PREFERENCE
```

ADD MDATA SECTION secname TAG sectag

The following conditions apply:

- Allows users to add MDATA section to the index.
- Cannot be used with NULL/AUTO/PATH section groups.

ALTER INDEX Examples**Resuming Failed Index**

The following statement resumes the indexing operation on newsindex with 2 megabytes of memory:

```
ALTER INDEX newsindex REBUILD PARAMETERS('resume memory 2M');
```

Rebuilding an Index

The following statement rebuilds the index, replacing the stoplist preference with `new_stop`.

```
ALTER INDEX newsindex REBUILD PARAMETERS('replace stoplist new_stop');
```

Rebuilding a Partitioned Index

The following example creates a partitioned text table, populates it, and creates a partitioned index. It then adds a new partition to the table and rebuilds the index with `ALTER INDEX` as follows:

PROMPT create partitioned table and populate it

```
create table part_tab (a int, b varchar2(40)) partition by range(a)
(partition p_tab1 values less than (10),
 partition p_tab2 values less than (20),
 partition p_tab3 values less than (30));
```

```
insert into part_tab values (1,'Actinidia deliciosa');
insert into part_tab values (8,'Distictis buccinatoria');
insert into part_tab values (12,'Actinidia quinata');
insert into part_tab values (18,'Distictis Rivers');
insert into part_tab values (21,'pandorea jasminoides Lady Di');
insert into part_tab values (28,'pandorea rosea');
```

```
commit;
```

PROMPT create partitioned index

```
create index part_idx on part_tab(b) indextype is ctxsys.context
local (partition p_idx1, partition p_idx2, partition p_idx3);
```

PROMPT add a partition and populate it

```
alter table part_tab add partition p_tab4 values less than (40);
insert into part_tab values (32, 'passiflora citrina');
insert into part_tab values (33, 'passiflora alatocaerulea');
commit;
```

The following statement rebuilds the index in the newly populated partition. In general, the index partition name for a newly added partition is the same as the table partition name, unless the name has already been used. In this case, Oracle Text generates a new name.

```
alter index part_idx rebuild partition p_tab4;
```

The following statement queries the table for the two hits in the newly added partition:

```
select * from part_tab where contains(b,'passiflora') >0;
```

The following statement queries the newly added partition directly:

```
select * from part_tab partition (p_tab4) where contains(b,'passiflora') >;
```

Replacing Index Metadata: Changing Single-Lexer to Multilexer

The following example demonstrates how an application can migrate from single-language documents (English) to multilanguage documents (English and Spanish) by replacing the index metadata for the lexer.

```
REM creates a simple table, which stores only English (American) text

create table simple (text varchar2(80));
insert into simple values ('the quick brown fox');
commit;

REM create a simple lexer to lex this English text

begin
  ctx_ddl.create_preference('us_lexer','basic_lexer');
end;
/

REM create a text index on the simple table
create index simple_idx on simple(text)
indextype is ctxsys.context parameters ('lexer us_lexer');

REM we can query easily
select * from simple where contains(text, 'fox')>0;

REM now suppose we want to start accepting Spanish documents.
REM first we have to extend the table with a language column
alter table simple add (lang varchar2(10) default 'us');

REM now let's create a Spanish lexer,
begin
  ctx_ddl.create_preference('e_lexer','basic_lexer');
  ctx_ddl.set_attribute('e_lexer','base_letter','yes');
end;
/
REM Then create a multilexer incorporating our English and Spanish lexers.
REM Note that the DEFAULT lexer is the exact same lexer, with which we have
REM have already indexed all the documents.
begin
  ctx_ddl.create_preference('m_lexer','multi_lexer');
  ctx_ddl.add_sub_lexer('m_lexer','default','us_lexer');
  ctx_ddl.add_sub_lexer('m_lexer','spanish','e_lexer');
end;
/
REM next replace our metadata
alter index simple_idx rebuild
parameters ('replace metadata language column lang lexer m_lexer');

REM We are ready for some Spanish data. Note that we could have inserted
REM this BEFORE the alter index, as long as we did not SYNC.
insert into simple values ('el zorro marr&oacute;n r&aacute;pido', 'e');
commit;
exec ctx_ddl.sync_index('simple_idx');
REM now query the Spanish data with base lettering:
select * from simple where contains(text, 'rapido')>0;
```

Optimizing the Index

To optimize your index, use `CTX_DDL.OPTIMIZE_INDEX` (page 8-44).

Synchronizing the Index

To synchronize your index, use `CTX_DDL.SYNC_INDEX` (page 8-68).

Adding a Zone Section

To add to the index the zone section author identified by the tag `<author>`, enter the following statement:

```
ALTER INDEX myindex REBUILD PARAMETERS('add zone section author tag author');
```

Adding a Stop Section

To add a stop section identified by tag <fluff> to the index that uses the AUTO_SECTION_GROUP, enter the following statement:

```
ALTER INDEX myindex REBUILD PARAMETERS('add stop section fluff');
```

Adding an Attribute Section

Assume that the following text appears in an XML document:

```
<book title="Tale of Two Cities">It was the best of times.</book>
```

Assume also that you want to create a separate section for the title attribute and you want to name the new attribute section booktitle. To do so, enter the following statement:

```
ALTER INDEX myindex REBUILD PARAMETERS('add attr section booktitle tag title@book');
```

Adding an SDATA Section

To add an SDATA section S1 of NUMBER data type and identified by tag T1, to the index, enter the following statement:

```
ALTER INDEX myindex PARAMETERS('add sdata section S1 tag T1 datatype NUMBER);
```

Using Flashback Queries

If a Text query is flashed back to a point before an ALTER INDEX statement was issued on the Text index for which the query is being run, then:

- The query optimizer will not choose the index access path for that given index because the index is treated according to its creation time with ALTER INDEX. Therefore, to the query optimizer, the index is perceived not to exist.
- The functional processing of the Text operator will fail with ORA-01466 or ORA-08176 errors if the ALTER INDEX statement involves re-creation of DR\$ index tables.

To work around this issue, use the DBMS_FLASHBACK package. For example:

```
EXEC dbms_flashback.enable_at_system_change_number(:scn);
SELECT id from documents WHERE CONTAINS(text, 'oracle')>0;
EXEC dbms_flashback.disable;
```

See Also:

"Using DBMS_FLASHBACK Package" in *Oracle Database Development Guide*

Notes

Add Section Constraints

Before altering the index section information, Oracle Text checks the new section against the existing sections to ensure that all validity constraints are met. These constraints are the same for adding a section to a section group with the CTX_DDL PL/SQL package and are as follows:

- You cannot add zone, field, or stop sections to a NULL_SECTION_GROUP.
- You cannot add zone, field, or attribute sections to an automatic section group.
- You cannot add attribute sections to anything other than XML section groups.
- You cannot have the same tag for two different sections.
- Section names for zone, field, and attribute sections cannot intersect.
- You cannot exceed 64 fields per section.
- You cannot add stop sections to basic, HTML, XML, or news section groups.
- SENTENCE and PARAGRAPH are reserved section names.

Related Topics

CTX_DDL.[SYNC_INDEX](#) (page 8-68) in [CTX_DDL Package](#) (page 8-1)

CTX_DDL.[OPTIMIZE_INDEX](#) (page 8-44) in [CTX_DDL Package](#) (page 8-1)

[CREATE INDEX](#) (page 1-40)

1.2 ALTER TABLE: Supported Partitioning Statements

Note:

This section describes the ALTER TABLE statement as it pertains to adding and modifying a partitioned text table with a context domain index.

For a complete description of the ALTER TABLE statement, see *Oracle Database SQL Language Reference*.

Purpose

Use the ALTER TABLE statement to add, modify, split, merge, exchange, or drop a partitioned text table with a context domain index. The following sections describe some of the ALTER TABLE operations.

Modify Partition Syntax**Unusable Local Indexes**

```
ALTER TABLE [schema.]table MODIFY PARTITION partition UNUSABLE LOCAL INDEXES
```

Marks the index partition corresponding to the given table partition UNUSABLE. You might mark an index partition unusable before you rebuild the index partition as described in "[Rebuild Unusable Local Indexes](#) (page 1-18)".

If the index partition is not marked unusable, then the statement returns without actually rebuilding the local index partition.

Rebuild Unusable Local Indexes

```
ALTER TABLE [schema.]table MODIFY PARTITION partition REBUILD UNUSABLE LOCAL INDEXES
```

Rebuilds the index partition corresponding to the specified table partition that has an UNUSABLE status.

Note:

If the index partition status is already `VALID` before you enter this statement, then this statement does *not* rebuild the index partition. Do not depend on this statement to rebuild the index partition unless the index partition status is `UNUSABLE`.

Add Partition Syntax

```
ALTER TABLE [schema.]table ADD PARTITION [partition]
VALUES LESS THAN (value_list) [partition_description]
```

Adds a new partition to the high end of a range-partitioned table.

To add a partition to the beginning or to the middle of the table, use the `ALTER TABLE SPLIT PARTITION` statement.

The newly added table partition is always empty, and the context domain index (if any) status for this partition is always `VALID`. After issuing DML, if you want to synchronize or optimize this newly added index partition, then you must look up the index partition name and enter the `ALTER INDEX REBUILD PARTITION` statement. For this newly added partition, the index partition name is usually the same as the table partition name, but if the table partition name is already used by another index partition, the system assigns a name in the form of `SYS_Pn`.

By querying the `USER_IND_PARTITIONS` view and comparing the `HIGH_VALUE` field, you can determine the index partition name for the newly added partition.

Merge Partition Syntax

```
ALTER TABLE [schema.]table
MERGE PARTITIONS partition1, partition2
[INTO PARTITION [new_partition] [partition_description]]
[UPDATE GLOBAL INDEXES]
```

Applies only to a range partition. This statement merges the contents of two adjacent partitions into a new partition and then drops the original two partitions. If the resulting partition is non-empty, then the corresponding local domain index partition is marked `UNUSABLE`. You can use `ALTER TABLE MODIFY PARTITION` to rebuild the partition index.

For a global, nonpartitioned index, if you perform the merge operation without an `UPDATE GLOBAL INDEXES` clause, then the resulting index (if not `NULL`) will be invalid and must be rebuilt. If you specify the `UPDATE GLOBAL INDEXES` clause after the operation and the `SYNC` type is `MANUAL`, then the index will be valid, but you still must synchronize the index with `CTX_DDL.SYNC_INDEX` (page 8-68) for the update to take place.

The naming convention for the resulting index partition is the same as in the `ALTER TABLE ADD PARTITION` statement.

Split Partition Syntax

```
ALTER TABLE [schema.]table
SPLIT PARTITION partition_name_old
AT (value_list)
[into (partition_description, partition_description)]
```

```
[parallel_clause]
[UPDATE GLOBAL INDEXES]
```

Applies only to range partitions. This statement divides a table partition into two partitions, thus adding a new partition to the table. The local corresponding index partitions will be marked UNUSABLE if the corresponding table partitions are non-empty. Use the `ALTER TABLE MODIFY PARTITION` statement to rebuild the partition indexes.

For a global, nonpartitioned index, if you perform the split operation without an `UPDATE GLOBAL INDEXES` clause, then the resulting index (if not NULL) will be invalid and must be rebuilt. If you specify the `UPDATE GLOBAL INDEXES` clause after the operation and the `SYNC` type is `MANUAL`, then the index will be valid, but you still must synchronize the index with `CTX_DDL.SYNC_INDEX` (page 8-68) for the update to take place.

The naming convention for the two resulting index partition is the same as in the `ALTER TABLE ADD PARTITION` statement.

Exchange Partition Syntax

```
ALTER TABLE [schema.]table EXCHANGE PARTITION partition WITH TABLE table
[INCLUDING|EXCLUDING INDEXES}
[WITH|WITHOUT VALIDATION]
[EXCEPTIONS INTO [schema.]table]
[UPDATE GLOBAL INDEXES]
```

Converts a partition to a nonpartitioned table, and converts a table to a partition of a partitioned table by exchanging their data segments. Rowids are preserved.

If `EXCLUDING INDEXES` is specified, all the context indexes corresponding to the partition and all the indexes on the exchanged table are marked as UNUSABLE. To rebuild the new index partition in this case, issue an `ALTER TABLE MODIFY PARTITION` statement.

If `INCLUDING INDEXES` is specified, then for every local domain index on the partitioned table, there must be a nonpartitioned domain index on the nonpartitioned table. The local index partitions are exchanged with the corresponding regular indexes.

For a global, nonpartitioned index, if you perform the exchange operation without an `UPDATE GLOBAL INDEXES` clause, then the resulting index (if not NULL) will be invalid and must be rebuilt. If you specify the `UPDATE GLOBAL INDEXES` clause after the operation and the `SYNC` type is `MANUAL`, then the index will be valid, but you still must synchronize the index with `CTX_DDL.SYNC_INDEX` (page 8-68) for the update to take place.

Field Sections

Field section queries might not work the same way if the nonpartitioned index and local index use different section IDs for the same field section.

Storage

Storage is not changed. So if the index on the nonpartitioned table `$I` table was in tablespace `XYZ`, then after the exchange partition, it will still be in tablespace `XYZ`, but now it is the `$I` table for an index partition.

Storage preferences are not switched, so if you switch and then rebuild the index, then the table may be created in a different location.

Restrictions

Both indexes must be equivalent. They must use the same objects and the same settings for each object. Note that Oracle Text checks only that the indexes are using the same object. But they should use the same exact everything.

No index object can be partitioned, that is, when the user has used the storage object to partition the \$I, \$N tables.

If either index or index partition does not meet all these restrictions an error is raised and both the index and index partition will be `INVALID`. You must manually rebuild both index and index partition using the `ALTER INDEX REBUILD` statement.

Truncate Partition Syntax

```
ALTER TABLE [schema.]table TRUNCATE PARTITION [DROP|REUSE STORAGE] [UPDATE GLOBAL INDEXES]
```

Removes all rows from a partition in a table. Corresponding `CONTEXT` index partitions are also removed.

For a global, nonpartitioned index, if you perform the truncate operation without an `UPDATE GLOBAL INDEXES` clause, then the resulting index (if not `NULL`) will be invalid and must be rebuilt. If you specify the `UPDATE GLOBAL INDEXES` clause after the operation, the index will be valid.

ALTER TABLE Examples

Global Index on Partitioned Table Examples

The following example creates a range-partitioned table with three partitions. Each partition is populated with two rows. A global, nonpartitioned `CONTEXT` index is then created. To demonstrate the `UPDATE GLOBAL INDEXES` clause, the partitions are split and merged with an index synchronization.

```
create table tdrexglb_part(a int, b varchar2(40)) partition by range(a)
(partition p1 values less than (10),
 partition p2 values less than (20),
 partition p3 values less than (30));

insert into tdrexglb_part values (1,'row1');
insert into tdrexglb_part values (8,'row2');
insert into tdrexglb_part values (11,'row11');
insert into tdrexglb_part values (18,'row18');
insert into tdrexglb_part values (21,'row21');
insert into tdrexglb_part values (28,'row28');

commit;
create index tdrexglb_parti on tdrexglb_part(b) indextype is ctxsys.context;

create table tdrexglb(a int, b varchar2(40));

insert into tdrexglb values(20,'newrow20');
commit;

PROMPT make sure query works
select * from tdrexglb_part where contains(b,'row18') >0;

PROMPT split partition
alter table tdrexglb_part split partition p2 at (15) into
(partition p21, partition p22) update global indexes;
```

```
PROMPT before sync
select * from tdrexglb_part where contains(b,'row11') >0;
select * from tdrexglb_part where contains(b,'row18') >0;

exec ctx_ddl.sync_index('tdrexglb_parti')

PROMPT after sync
select * from tdrexglb_part where contains(b,'row11') >0;
select * from tdrexglb_part where contains(b,'row18') >0;

PROMPT merge partition
alter table tdrexglb_part merge partitions p22, p3
into partition pnw3 update global indexes;

PROMPT before sync
select * from tdrexglb_part where contains(b,'row18') >0;
select * from tdrexglb_part where contains(b,'row28') >0;
exec ctx_ddl.sync_index('tdrexglb_parti');

PROMPT after sync
select * from tdrexglb_part where contains(b,'row18') >0;
select * from tdrexglb_part where contains(b,'row28') >0;

PROMPT drop partition
alter table tdrexglb_part drop partition p1 update global indexes;

PROMPT before sync
select * from tdrexglb_part where contains(b,'row1') >0;
exec ctx_ddl.sync_index('tdrexglb_parti');

PROMPT after sync
select * from tdrexglb_part where contains(b,'row1') >0;

PROMPT exchange partition
alter table tdrexglb_part exchange partition pnw3 with table
tdrexglb update global indexes;

PROMPT before sync
select * from tdrexglb_part where contains(b,'newrow20') >0;
select * from tdrexglb_part where contains(b,'row28') >0;

exec ctx_ddl.sync_index('tdrexglb_parti');
PROMPT after sync
select * from tdrexglb_part where contains(b,'newrow20') >0;
select * from tdrexglb_part where contains(b,'row28') >0;

PROMPT move table partition
alter table tdrexglb_part move partition p21 update global indexes;
PROMPT before sync
select * from tdrexglb_part where contains(b,'row11') >0;

exec ctx_ddl.sync_index('tdrexglb_parti');
PROMPT after sync
select * from tdrexglb_part where contains(b,'row11') >0;

PROMPT truncate table partition
alter table tdrexglb_part truncate partition p21 update global indexes;

update global indexes;
```

1.3 CATSEARCH

Use the CATSEARCH operator to search [CTXCAT](#) (page 1-41) indexes. Use this operator in the WHERE clause of a SELECT statement.

The CATSEARCH operator also supports database links. You can identify a remote table or materialized view by appending @dblink to the end of its name. The dblink must be a complete or partial name for a database link to the database containing the remote table or materialized view. (Indexing of remote views is not supported.)

The grammar of this operator is called CTXCAT. You can also use the CONTEXT grammar if your search criteria require special functionality, such as thesaurus, fuzzy matching, proximity searching, or stemming. To utilize the CONTEXT grammar, use the "[Query Template Specification](#) (page 1-25)" in the [text_query](#) (page 1-23) parameter as described in this section.

About Performance

Use the CATSEARCH operator with a [CTXCAT](#) (page 1-41) index mainly to improve mixed-query performance. Specify your text query condition with `text_query` and your structured condition with the `structured_query` argument.

Internally, Oracle Text uses a combined B-tree index on text and structured columns to quickly produce results satisfying the query.

Limitations

If the optimizer chooses to use the functional query invocation, then your query will fail. The optimizer might choose functional invocation when your structured clause is highly selective.

The `structured_query` argument of the CATSEARCH operator must reference columns used during CREATE INDEX sets; otherwise, error DRG-10845 will be raised. For example, the error will be raised if you issue a CATSEARCH query on a view created on top of a table with the CTXCAT index on it, and the name of the logical column on the view is different from the actual column name on the physical table. The columns referenced by the `structured_query` argument of the CATSEARCH operator must be the physical column name used during CREATE INDEX sets, not the logical column on the view.

Syntax

```
CATSEARCH(

[schema.]column,
text_query      [VARCHAR2|CLOB],
structured_query VARCHAR2,

RETURN NUMBER;
```

[*schema*.]*column*

Specifies the text column to be searched on. This column must have a CTXCAT index associated with it.

text_query

Specify one of the following to define your search in `column`:

- [CATSEARCH Query Operations](#) (page 1-24)
- [Query Template Specification](#) (page 1-25) (for using CONTEXT grammar)

CATSEARCH Query Operations

The CATSEARCH operator supports only the following query operations:

- Logical AND
- Logical OR (|)
- Logical NOT (-)
- " " (quoted phrases)
- Wildcarding

[Table 1-2](#) (page 1-24) provides the syntax for these operators.

Table 1-2 CATSEARCH Query Operators

Operation	Syntax	Description of Operation
Logical AND	a b c	Returns rows that contain a, b, and c.
Logical OR	a b c	Returns rows that contain a, b, or c.
Logical NOT	a - b	Returns rows that contain a and not b.
Hyphen with no space	a-b	Hyphen treated as a regular character. For example, if the hyphen is defined as skipjoin, words such as <i>web-site</i> are treated as the single query term <i>website</i> . Likewise, if the hyphen is defined as a printjoin, words such as <i>web-site</i> are treated as <i>web-site</i> in the CTXCAT query language.
" "	"a b c"	Returns rows that contain the phrase "a b c". For example, entering "Sony CD Player" means return all rows that contain this sequence of words.
()	(A B) C	Parentheses group operations. This query is equivalent to the CONTAINS query (A &B) C.
Wildcard (right and double truncated)	term* a*b	The wildcard character matches zero or more characters. For example, <i>do*</i> matches <i>dog</i> , and <i>gl*s</i> matches <i>glass</i> . Left truncation not supported. Note: Oracle recommends that you create a prefix index if your application uses wildcard searching. Set prefix indexing with the BASIC_WORDLIST (page 2-72) preference.

The following limitations apply to these operators:

- The left-hand side (the column name) must be a column named in at least one of the indexes of the index set.

- The left-hand side must be a plain column name. Functions and expressions are not allowed.
- The right-hand side must be composed of literal values. Functions, expressions, other columns, and subselects are not allowed.
- Multiple criteria can be combined with AND. Note that OR is not supported.
- When querying a remote table through a database link, the database link must be specified for CATSEARCH as well as for the table being queried.

For example, these expressions are supported:

```
catsearch(text, 'dog', 'foo > 15')
catsearch(text, 'dog', 'bar = ''SMITH''')
catsearch(text, 'dog', 'foo between 1 and 15')
catsearch(text, 'dog', 'foo = 1 and abc = 123')
catsearch@remote(text, 'dog', 'foo = 1 and abc = 123')
```

These expressions are not supported:

```
catsearch(text, 'dog', 'upper(bar) = ''A''')
catsearch(text, 'dog', 'bar LIKE ''A%''')
catsearch(text, 'dog', 'foo = abc')
catsearch(text, 'dog', 'foo = 1 or abc = 3')
```

Query Template Specification

Specifies a marked-up string that specifies a query template. Specify one of the following templates:

- Query rewrite, used to expand a query string into different versions
- Progressive relaxation, used to progressively enter less restrictive versions of a query to increase recall
- Alternate grammar, used to specify CONTAINS operators (See "[CONTEXT Query Grammar Examples](#) (page 1-27)")
- Alternate language, used to specify alternate query language
- Alternate scoring, used to specify alternate scoring algorithms

See Also:

The [text_query](#) (page 1-30) parameter description for CONTAINS for more information about the syntax for these query templates

structured_query

Specifies the structured conditions and the ORDER BY clause. There must exist an index for any column you specify. For example, if you specify 'category_id=1 order by bid_close', you must have an index for 'category_id, bid_close' as specified with the CTX_DDL.ADD_INDEX package.

With structured_query, you can use standard SQL syntax only with the following operators:

- =

- <=
- >=
- >
- <
- IN
- BETWEEN
- AND (to combine two or more clauses)

Note:

You cannot use parentheses () in the `structured_query` parameter.

Examples

1. Create the table.

The following statement creates the table to be indexed:

```
CREATE TABLE auction (category_id number primary key, title varchar2(20),
bid_close date);
```

The following statements insert the values into the table:

```
INSERT INTO auction values(1, 'Sony DVD Player', '20-FEB-2012');
INSERT INTO auction values(2, 'Sony DVD Player', '24-FEB-2012');
INSERT INTO auction values(3, 'Pioneer DVD Player', '25-FEB-2012');
INSERT INTO auction values(4, 'Sony DVD Player', '25-FEB-2012');
INSERT INTO auction values(5, 'Bose Speaker', '22-FEB-2012');
INSERT INTO auction values(6, 'Tascam CD Burner', '25-FEB-2012');
INSERT INTO auction values(7, 'Nikon digital camera', '22-FEB-2012');
INSERT INTO auction values(8, 'Canon digital camera', '26-FEB-2012');
```

2. Create the CTXCAT index.

The following statements create the CTXCAT index:

```
begin

ctx_ddl.create_index_set('auction_iset');
ctx_ddl.add_index('auction_iset','bid_close');

end;
/
CREATE INDEX auction_titlex ON auction(title) INDEXTYPE IS CTXSYS.CTXCAT
PARAMETERS ('index set auction_iset');
```

3. Query the table.

A typical query with CATSEARCH might include a structured clause as follows to find all rows that contain the word *camera* ordered by *bid_close*:

```
SELECT * FROM auction WHERE CATSEARCH(title, 'camera', 'order by bid_close
desc')>
0;
```


CATEGORY_ID	TITLE	BID_CLOSE
8	Canon digital camera	26-FEB-12
7	Nikon digital camera	22-FEB-12

The following query finds all rows that contain the phrase *Sony DVD Player* and that have a bid close date of February 20, 2012:

```
SELECT * FROM auction WHERE CATSEARCH(title, 'Sony DVD Player',
'bid_close='20-FEB-00')> 0;
```

CATEGORY_ID	TITLE	BID_CLOSE
1	Sony DVD Player	20-FEB-12

The following query finds all rows with the terms *Sony* and *DVD* and *Player*:

```
SELECT * FROM auction WHERE CATSEARCH(title, 'Sony DVD Player',
'order by bid_close
desc')> 0;
```

CATEGORY_ID	TITLE	BID_CLOSE
4	Sony DVD Player	25-FEB-12
2	Sony DVD Player	24-FEB-12
1	Sony DVD Player	20-FEB-12

The following query finds all rows with the term *DVD* and not *Player*:

```
SELECT * FROM auction WHERE CATSEARCH(title, 'DVD - Player', 'order by bid_close
desc')> 0;
```

CATEGORY_ID	TITLE	BID_CLOSE
6	Tascam CD Burner	25-FEB-12

The following query finds all rows with the terms *CD* or *DVD* or *Speaker*:

```
SELECT * FROM auction WHERE CATSEARCH(title, 'CD | DVD | Speaker', 'order by
bid_close desc')> 0;
```

CATEGORY_ID	TITLE	BID_CLOSE
3	Pioneer DVD Player	25-FEB-12
4	Sony DVD Player	25-FEB-12
6	Tascam CD Burner	25-FEB-12
2	Sony DVD Player	24-FEB-12
5	Bose Speaker	22-FEB-12
1	Sony DVD Player	20-FEB-12

The following query finds all rows that are about *audio equipment*:

```
SELECT * FROM auction WHERE CATSEARCH(title, 'ABOUT(audio equipment)',
NULL)> 0;
```

CONTEXT Query Grammar Examples

The following examples show how to specify the CONTEXT grammar in CATSEARCH queries using the template feature:

```
PROMPT
PROMPT fuzzy: query = ?test
PROMPT should match all fuzzy variations of test (for example, text)
select pk||' ==> '||text from test
```

```
where catsearch(text,
'<query>
  <textquery grammar="context">
    ?test
  </textquery>
</query>', '')>0
order by pk;

PROMPT
PROMPT fuzzy: query = !sail
PROMPT should match all soundex variations of bot (for example, sell)
select pk||' ==> '||text from test
where catsearch(text,
'<query>
  <textquery grammar="context">
    !sail
  </textquery>
</query>', '')>0
order by pk;

PROMPT
PROMPT theme (ABOUT) query
PROMPT query: about(California)
select pk||' ==> '||text from test
where catsearch(text,
'<query>
  <textquery grammar="context">
    about(California)
  </textquery>
</query>', '')>0
order by pk;
```

The following example shows a field section search against a CTXCAT index using CONTEXT grammar by means of a query template in a CATSEARCH query:

```
-- Create and populate table
create table BOOKS (ID number, INFO varchar2(200), PUBDATE DATE);

insert into BOOKS values(1, '<author>NOAM CHOMSKY</author><subject>CIVIL
  RIGHTS</subject><language>ENGLISH</language><publisher>MIT
  PRESS</publisher>', '01-NOV-2003');

insert into BOOKS values(2, '<author>NICANOR PARRA</author><subject>POEMS
  AND ANTIPOEMS</subject><language>SPANISH</language>
  <publisher>VASQUEZ</publisher>', '01-JAN-2001');

insert into BOOKS values(1, '<author>LUC SANTE</author><subject>XML
  DATABASE</subject><language>FRENCH</language><publisher>FREE
  PRESS</publisher>', '15-MAY-2002');

commit;

-- Create index set and section group
exec ctx_ddl.create_index_set('BOOK_INDEX_SET');
exec ctx_ddl.add_index('BOOKSET', 'PUBDATE');

exec ctx_ddl.create_section_group('BOOK_SECTION_GROUP',
  'BASIC_SECTION_GROUP');
exec ctx_ddl.add_field_section('BOOK_SECTION_GROUP', 'AUTHOR', 'AUTHOR');
exec ctx_ddl.add_field_section('BOOK_SECTION_GROUP', 'SUBJECT', 'SUBJECT');
exec ctx_ddl.add_field_section('BOOK_SECTION_GROUP', 'LANGUAGE', 'LANGUAGE');
```

```

exec ctx_ddl.add_field_section('BOOK_SECTION_GROUP','PUBLISHER','PUBLISHER');

-- Create index
create index books_index on books(info) indextype is ctxsys.ctxcat
  parameters('index set book_index_set section group book_section_group');

-- Use the index
-- Note that: even though CTXCAT index can be created with field sections, it
-- cannot be accessed using CTXCAT grammar (default for CATSEARCH).
-- We need to use query template with CONTEXT grammar to access field
-- sections with CATSEARCH.

select id, info from books
where catsearch(info,
'<query>
  <textquery grammar="context">
    NOAM within author and english within language
  </textquery>
</query>',
'order by pubdate')>0;

```

Related Topics

["Syntax for CTXCAT Index Type \(page 1-58\)"](#)

Oracle Text Application Developer's Guide

1.4 CONTAINS

Use the CONTAINS operator in the WHERE clause of a SELECT statement to specify the query expression for a Text query.

The CONTAINS operator also supports database links. You can identify a remote table or materialized view by appending @dblink to the end of its name. The dblink must be a complete or partial name for a database link to the database containing the remote table or materialized view (querying of remote views is not supported).

CONTAINS returns a relevance score for every row selected. Obtain this score with the [SCORE \(page 1-65\)](#) operator.

The grammar for this operator is called the CONTEXT grammar. You can also use CTXCAT grammar if your application works better with simpler syntax. To do so, use the ["Query Template Specification \(page 1-25\)"](#) in the [text_query \(page 1-30\)](#) parameter as described in this section.

See Also:

- ["Query Rewrite Template \(page 1-30\)"](#)
 - ["Query Result Set Descriptor Template \(page 1-31\)"](#)
 - ["Query Relaxation Template \(page 1-32\)"](#)
 - ["Alternate Grammar Template \(page 1-32\)"](#)
 - ["Language Independent Template \(page 1-33\)"](#)
 - ["Alternate Language Template \(page 1-34\)"](#)
 - ["Alternative Scoring Template \(page 1-34\)"](#)
 - The CONTEXT Grammar" topic in *Oracle Text Application Developer's Guide*
-

Syntax

```
CONTAINS(  
    [schema.]column,  
    text_query    [VARCHAR2|CLOB]  
    [,label      NUMBER])  
RETURN NUMBER;
```

[schema.]column

Specify the text column to be searched on. This column must have a Text index associated with it.

text_query

Specify one of the following (limited to 4000 bytes for a VARCHAR2 or 64000 bytes for a CLOB):

- The query expression that defines your search in column.
- A marked-up document that specifies a query template.

Use one of the following query templates:

- [Query Rewrite Template \(page 1-30\)](#)
- [Query Result Set Descriptor Template \(page 1-31\)](#)
- [Query Relaxation Template \(page 1-32\)](#)
- [Alternate Grammar Template \(page 1-32\)](#)
- [Language Independent Template \(page 1-33\)](#)
- [Alternate Language Template \(page 1-34\)](#)
- [Alternative Scoring Template \(page 1-34\)](#)

Query Rewrite Template

Use this template to automatically write different versions of a query before you submit the query to Oracle Text. This is useful when you need to maximize the recall

of a user query. For example, you can program your application to expand a single phrase query of 'cat dog' into the following queries:

```
{cat} {dog}
{cat} ; {dog}
{cat} AND {dog}
{cat} ACCUM {dog}
```

These queries are submitted as one query and results are returned with no duplication. In this example, the query returns documents that contain the phrase *cat dog* as well as documents in which *cat* is near *dog*, and documents that have *cat* and *dog*.

This is done with the following template:

```
<query>
  <textquery lang="ENGLISH" grammar="CONTEXT"> cat dog
    <progression>
      <seq><rewrite>transform((TOKENS, "{", " ", " "})</rewrite></seq>
      <seq><rewrite>transform((TOKENS, "{", " ", " ; "})</rewrite></seq>
      <seq><rewrite>transform((TOKENS, "{", " ", "AND")</rewrite></seq>
      <seq><rewrite>transform((TOKENS, "{", " ", "ACCUM")</rewrite></seq>
    </progression>
  </textquery>
  <score datatype="INTEGER" algorithm="COUNT"/>
</query>
```

The operator TRANSFORM is used to specify the rewrite rules and has the following syntax (note that it uses double parentheses). The parameters are described in [Table 1-3](#) (page 1-31).

```
TRANSFORM((terms, prefix, suffix, connector))
```

Table 1-3 TRANSFORM Parameters

Parameter	Description
term	Specifies the type of terms to be produced from the original query. Specify either TOKENS or THEMES.
prefix	Specifies the literal string to be prepended to all terms.
suffix	Specifies the literal string to be appended to all terms.
connector	Specifies the literal string to connect all terms after applying the prefix and suffix.

Note:

An error will be raised if the input Text query string specified in the Query Rewrite Template with TRANSFORM rules contains any Oracle Text query operators (such as AND, OR, or SOUNDEx). Also, any special characters (such as % or \$) in the input Text query string must be preceded by an escape character, or an error is raised.

Query Result Set Descriptor Template

Use this template to take in a Result Set Descriptor. The element `ctx_result_set_descriptor` is added to the query template. This enables the CONTAINS query cursor to take in a group count query.

The Result Set Interface document is placed in a public variable in the `ctx_query` package. (`ctx_query.result_set_document`.)

The CONTAINS query cursor behavior remains unchanged and the Result Set Document is available right after closing the cursor

For example, the following query of *kukui nut* returns a result set with the following template.

```
<query>
  <textquery lang="ENGLISH" grammar="CONTEXT">
    <progression>
      <seq><rewrite>transform((TOKENS, "{", "}", " "))</rewrite></seq>
      <seq><rewrite>transform((TOKENS, "{", "}", " ; "))</rewrite></seq>
      <seq><rewrite>transform((TOKENS, "{", "}", "AND"))</rewrite></seq>
      <seq><rewrite>transform((TOKENS, "{", "}", "ACCUM"))</rewrite></seq>
    </progression>
  </textquery>
  <score datatype="INTEGER" algorithm="COUNT"/>
<ctx_result_set_descriptor>
  <group>
    <group_values>
      <value id="2"/>
      <value id="3"/>
      <value id="4"/>
    </group_values>
    <count/>
  </group>
</ctx_result_set_descriptor>
</query>
```

Query Relaxation Template

Use this template to progressively relax your query. **Progressive relaxation** is when you increase recall by progressively issuing less restrictive versions of a query, so that your application can return an appropriate number of hits to the user.

For example, the query of *black pen* can be progressively relaxed to:

```
black pen
black NEAR pen
black AND pen
black ACCUM pen
```

This is done with the following template

```
<query>
  <textquery lang="ENGLISH" grammar="CONTEXT">
    <progression>
      <seq>black pen</seq>
      <seq>black NEAR pen</seq>
      <seq>black AND pen</seq>
      <seq>black ACCUM pen</seq>
    </progression>
  </textquery>
  <score datatype="INTEGER" algorithm="COUNT"/>
</query>
```

Alternate Grammar Template

Use this template to specify an alternate grammar, such as CONTEXT or CATSEARCH. Specifying an alternate grammar enables you to enter queries using different syntax and operators.

For example, with CATSEARCH, enter ABOUT queries using the CONTEXT grammar. Likewise with CONTAINS, enter logical queries using the simplified CATSEARCH syntax.

The phrase *'dog cat mouse'* is interpreted as a phrase in CONTAINS. However, with CATSEARCH, this is equivalent to an AND query of *'dog AND cat AND mouse'*. Specify that CONTAINS use the alternate grammar with the following template:

```
<query>
  <textquery grammar="CTXCAT">dog cat mouse</textquery>
  <score datatype="integer"/>
</query>
```

Language Independent Template

Use this template to specify a lexer that uses user-defined symbols (or abbreviations) and does not depend on any language.

The following example specifies that the query take a list of language-independent sublexers.

```
<query>
  <textquery grammar="CONTEXT" lang="ENGLISH">
    Oracle
  </textquery>
  <score datatype="INTEGER" algorithm="COUNT"/>
  <sublexers>
    <sublexer_label> SESSION_LANG </sublexer_label>
    <sublexer_label> MAIL </sublexer_label>
    <sublexer_label> CALENDER </sublexer_label>
  </sublexers>
</query>
```

The following conditions apply:

- The `sublexers` element consists of one or more `sublexer_label` elements.
- Each `sublexer_label` element contains the symbol for the language independent sub_lexer.
- When the `sublexers` element is specified, the query will be processed with the stopwords and sub_lexers for each of the symbols specified in the `sublexers` element, and query will return only the documents indexed by the specified sub_lexers.
- A special reserved symbol called `SESSION_LANG` can be used for the system to pick a language-dependent sub_lexer based on the language specified in `lang` attribute of the `textquery` element in the query template. If `lang` attribute is not specified, then the `lang` attribute will be based on session language. Query parsed by the chosen sub_lexer will only return documents indexed by that language-dependent sub_lexer. If both `SESSION_LANG` and `lang` attribute are specified, the `lang` attribute will take priority.
- If `sublexers` element is specified without `SESSION_LANG`, then `lang` attribute of `textquery` element will be ignored.

- Default Behavior:

If `sublexers` element is not present in the query template, then `query` will be parsed with one language-dependent sub-lexer (if any), which is chosen based on the specified `lang` attribute value or the session language AND all language independent sub-lexers.

Alternate Language Template

Use this template to specify an alternate language:

```
<query><textquery lang="french">bon soir</textquery></query>
```

Alternative Scoring Template

Use this template to specify an alternative scoring algorithm.

The following example specifies that the query use the `CONTEXT` grammar and return integer scores using the `COUNT` algorithm. This algorithm returns a score as the number of query occurrences in the document.

```
<query>
  <textquery grammar="CONTEXT" lang="english"> mustang
  </textquery>
  <score datatype="INTEGER" algorithm="COUNT"/>
</query>
```

The following example uses the `normalization_expr` attribute to add `SDATA(price)` into the score returned by the query, and uses it as the final score:

```
<query>
  <textquery grammar="CONTEXT" lang="english">
    DEFINESCORE(dog, RELEVANCE) and cat
  </textquery>
  <score algorithm="COUNT" normalization_expr ="doc_score+ SDATA(price)"/>
</query>
```

The `normalization_expr` attribute is used only with the alternate scoring template, and is an arithmetic expression that consists of:

- Arithmetic operators: `+` `-` `*` `/`. The operator precedence is the same as that for SQL operator precedence.
- Grouping operators: `()`. Parentheses can be used to alter the precedence of the arithmetic operators.
- Absolute function: `ABS(n)` returns the absolute value of *n*; where *n* is any expression that returns a number.
- Logarithmic function: `LOG(n)`: returns the base-10 logarithmic value of *n*; where *n* is any expression that returns a number.
- Predefined components: The `doc_score` predefined component can be used to return the initial query score of a particular document.
- `SDATA` component: `SDATA(name)` returns the value of the `SDATA` with the specified name as the score.
 - Only `SDATA` with a `NUMBER` or `DATE` data type is allowed. An error is raised otherwise.
 - The *sdata* string and the `SDATA` name are case-insensitive.

- Because an SDATA section value can be NULL, any expression with NULL SDATA section value is evaluated as 0. For example: the `normalization_expr "doc_score + SDATA(price)"` will be evaluated to 0 if `SDATA(price)` for a given document has a NULL value.
- Numeric literals: There are any number literal that conforms to the SQL pattern of NUMBER literal and is within the range of the double-precision floating-point ($-3.4e38$ to $3.4e38$).
- Date literals: Date literals must be enclosed with `DATE ()`. Only the following format is allowed: YYYY-MM-DD or YYYY-MM-DD HH24:MI:SS. For example: `DATE (2005-11-08)`.

Consistent with SQL, if no time is specified, then 00:00:00 is assumed.

The `normalization_expr` attribute overrides the `algorithm` attribute. That is, if `algorithm` is set to `COUNT`, and the user also specifies `normalization_expr`, then the score will not be count, but the calculated score based on the `normalization_expr`.

If the score (either from `algorithm = COUNT` or `normalization_expr = ...`) is internally calculated to be greater than 100, then it will be set to 100.

If the query relaxation template is used, the score will be further normalized in such a way that documents returned from higher sequences will always have higher scores than documents returned from sequence(s) below.

DATE Literal Restrictions

Only the minus (-) operator is allowed between date-type data (DATE literals and date-type SDATA). Using other operators will result in an error. Subtracting two date-type data will produce a number (float) that represents the difference in number of days between the two dates. For example, the following expression is allowed:

```
SDATA(dob) - DATE(2005-11-08)
```

The following expression is not allowed:

```
SDATA(dob) + DATE(2005-11-08)
```

The plus (+) and minus (-) operators are allowed between numeric data and date type of data. The number operand is interpreted as the number or fraction of days. For example, the following expression is allowed:

```
DATE(2005-11-08) + 1           = 9 NOV 2005
```

The following expression is not allowed:

```
DATE(2005-11-08)* 3           = ERROR
```

Template Attribute Values

[Table 1-4](#) (page 1-35) gives the possible values for template attributes.

Table 1-4 Template Attribute Values

Tag Attribute	Description	Possible Values	Meaning
grammar=	Specifies the grammar of the query.	CONTEXT CTXCAT	The grammar of the query.

Table 1-4 (Cont.) Template Attribute Values

Tag Attribute	Description	Possible Values	Meaning
datatype=	Specifies the type of number returned as score.	INTEGER FLOAT	Returns score as integer between 0 and 100. Returns score as its high-precision floating-point number between 0 and 100.
algorithm=	Specifies the scoring algorithm to use.	DEFAULT COUNT	Returns the default. Returns scores as the number of occurrences in the document.
lang=	Specifies the language name.	Any language supported by Oracle Database. See <i>Oracle Database Globalization Support Guide</i> .	The language name.

Template Grammar Definition

The query template interface is an XML document. Its grammar is defined with the following XML DTD:

```
<!ELEMENT query (textquery, score?, order?)>
<!ELEMENT textquery (#PCDATA|progression)*>
<!ELEMENT progression (seq)+>
<!ELEMENT seq (#PCDATA|rewrite)*>
<!ELEMENT rewrite (#PCDATA)>
<!ELEMENT score EMPTY>
<!ELEMENT order (orderkey+)>
<!ELEMENT orderkey (#PCDATA)>
<ATTLIST textquery grammar (context | ctxcat) #IMPLIED>
<ATTLIST textquery lang CDATA #IMPLIED>
<ATTLIST score datatype (integer | float) "integer">
<ATTLIST score algorithm (default | count) "default">
```

Values are case insensitive: integer | float, default | count, context | ctxcat .

See Also:

[Oracle Text CONTAINS Query Operators](#) (page 3-1) for more information about the operators in query expressions

label

Optionally, specifies the label that identifies the score generated by the CONTAINS operator.

Returns

For each row selected, the CONTAINS operator returns a number between 0 and 100 that indicates how relevant the document row is to the query. The number 0 means that Oracle Text found no matches in the row.

Note:

You must use the SCORE operator with a label to obtain this number.

Example

The following example searches for all documents in the text column that contain the word *oracle*. The score for each row is selected with the SCORE operator using a label of 1:

```
SELECT SCORE(1), title from newsindex
WHERE CONTAINS(text, 'oracle', 1) > 0;
```

The CONTAINS operator must be followed by an expression such as > 0, which specifies that the score value calculated must be greater than zero for the row to be selected.

When the SCORE operator is called (for example, in a SELECT clause), the CONTAINS clause must reference the score label value as in the following example:

```
SELECT SCORE(1), title from newsindex
WHERE CONTAINS(text, 'oracle', 1) > 0 ORDER BY SCORE(1) DESC;
```

The following example specifies that the query be parsed using the CATSEARCH grammar:

```
SELECT id FROM test WHERE CONTAINS (text,
'<query>
<textquery lang="ENGLISH" grammar="CATSEARCH">
cheap pokemon
</textquery>
<score datatype="INTEGER"/>
</query>' ) > 0;
```

Grammar Template Example

The following example shows how to use the CTXCAT grammar in a CONTAINS query. The example creates a CTXCAT and a CONTEXT index on the same table, and compares the query results.

```
PROMPT create context and ctxcat indexes, both using theme indexing
PROMPT
create index tdrbqcq101x on test(text) indextype is ctxsys.context
parameters ('lexer theme_lexer');

create index tdrbqcq101cx on test(text) indextype is ctxsys.ctxcat
parameters ('lexer theme_lexer');

PROMPT ***** San Diego *****
PROMPT ***** CONTEXT grammar *****
PROMPT ** should be interpreted as phrase query **
select pk||' ==> '||text from test
where contains(text,'San Diego')>0
order by pk;
```

```
PROMPT ***** San Diego *****
PROMPT ***** CTXCAT grammar *****
PROMPT ** should be interpreted as AND query ***
select pk||' ==> '||text from test
where contains(text,
'<query>
  <textquery grammar="CTXCAT">San Diego</textquery>
  <score datatype="integer"/>
</query>')>0
order by pk;

PROMPT ***** Hitlist from CTXCAT index *****
select pk||' ==> '||text from test
where catsearch(text, 'San Diego', '')>0
order by pk;
```

Alternate Scoring Query Template Example

The following query template adds price SDATA section (or SDATA filter-by column) value into the score returned by the query and uses it as the final score:

```
<query>
  <textquery grammar="CONTEXT" lang="english">
    DEFINESCORE(dog, RELEVANCE) and cat
  </textquery>
  <score algorithm="COUNT" normalization_expr ="doc_score+SDATA(price)"/>
</query>
```

Query Relaxation Template Example

The following query template defines a query relaxation sequence. The query of *black pen* is entered in sequence as *black pen*, then *black NEAR pen*, then *black AND pen*, and then *black ACCUM pen*. Query hits are returned in this sequence with no duplication as long as the application requires results.

```
select id from docs where CONTAINS (text, '
<query>
  <textquery lang="ENGLISH" grammar="CONTEXT">
    <progression>
      <seq>black pen</seq>
      <seq>black NEAR pen</seq>
      <seq>black AND pen</seq>
      <seq>black ACCUM pen</seq>
    </progression>
  </textquery>
  <score datatype="INTEGER" algorithm="COUNT"/>
</query>')>0;
```

Query relaxation is most effective when your application requires the top *n* hits to a query, which you can obtain with the DOMAIN_INDEX_SORT or FIRST_ROWS hint, which is being deprecated, in a PL/SQL cursor.

Query Rewrite Template Example

The following template defines a query rewrite sequence. The query of *kukui nut* is rewritten as follows:

```
{kukui} {nut}
{kukui} ; {nut}
{kukui} AND {nut}
```

{kukui} ACCUM {nut}

```
select id from docs where CONTAINS (text, '
<query>
  <textquery lang="ENGLISH" grammar="CONTEXT"> kukui nut
  <progression>
    <seq><rewrite>transform((TOKENS, "{", "}", " "))</rewrite></seq>
    <seq><rewrite>transform((TOKENS, "{", "}", " ; "))</rewrite></seq>
    <seq><rewrite>transform((TOKENS, "{", "}", "AND"))</rewrite></seq>
    <seq><rewrite>transform((TOKENS, "{", "}", "ACCUM"))</rewrite></seq>
  </progression>
</textquery>
<score datatype="INTEGER" algorithm="COUNT"/>
</query>')>0;
```

Order By SDATA Sections Template Example

The following query template defines a query sequence for ordering by SDATA section values using the `<order>` and `<orderkey>` elements. The first level of ordering is done on the SDATA section `price`, which is sorted in the ascending order. The second and third level of ordering is done by the SDATA section `pub_date` and `score`, both of which are sorted in the descending order.

```
select id from docs where CONTAINS (text, '
<query>
  <textquery lang="ENGLISH" grammar="CONTEXT"> Oracle </textquery>
  <score datatype="INTEGER" algorithm="COUNT"/>
  <order>
    <orderkey> SDATA(price) ASC </orderkey>
    <orderkey> SDATA(pub_date) DESC </orderkey>
    <orderkey> Score DESC </orderkey>
  </order>
</query>', 1)>0;
```

The `<orderkey>` element value must have the following format:

```
<orderkey> SDATA(sdata_section_name) | score [DESC|ASC] </orderkey>
```

The sort order is ascending by default, if not specified as either DESC or ASC.

The `<orderkey>` element will be ignored in the following cases:

- when the Oracle Cost-Based Optimizer (CBO) pushes the SQL query level ordering into the Text index
- when the `CONTAINS ()` predicate is processed functionally
- when the ordering is already specified by the ORDER BY clause in the SQL query statement

Notes

Querying Multilanguage Tables

With the multilexer preference, you can create indexes from multilanguage tables. At query time, the multilexer examines the session's language setting and uses the sublexer preference for that language to parse the query. If the language setting is not mapped, then the default lexer is used.

When the language setting is mapped, the query is parsed and run as usual. The index contains tokens from multiple languages, so such a query can return documents in several languages.

To limit your query to returning documents of a given language, use a structured clause on the language column.

Query Performance Limitation with a Partitioned Index

Oracle Text supports the CONTEXT indexing and querying of a partitioned text table.

However, for optimal performance when querying a partitioned table with an ORDER BY SCORE clause, query the partition. If you query the entire table and use an ORDER BY SCORE clause, the query might not perform optimally unless you include a range predicate that can limit the query to a single partition.

For example, the following statement queries the partition p_tab4 partition directly:

```
select * from part_tab partition (p_tab4) where contains(b,'oracle') > 0 ORDER BY  
SCORE DESC;
```

Limitation with Remote Execution of CONTAINS Query

Oracle Text supports the remote execution of the CONTAINS operator, but with some limitations. You can invoke the CONTAINS operator in a remote query only if the query is executed completely in the remote database. You cannot use the CONTAINS operator in a subquery of a query, which causes the query to run partly on the remote database and partly on the local database. Doing so will raise the error "ORA-00949: illegal reference to remote database." However, CONTAINS, when invoked remotely from an inner query might run successfully sometimes if view merging is enabled and possible on this query, as in this case the query will be transformed into a single query and, hence, no error will occur.

For example, the following query is correct:

```
select id from remtab@rdb  
where contains@rdb(text,'hello') > 0;
```

Related Topics

["Syntax for CONTEXT Index Type \(page 1-41\)"](#)

[Oracle Text CONTAINS Query Operators \(page 3-1\)](#)

"The CONTEXT Grammar" topic in *Oracle Text Application Developer's Guide*

["SCORE \(page 1-65\)"](#)

1.5 CREATE INDEX

This section describes the CREATE INDEX statement as it pertains to creating an Oracle Text domain index and composite domain index.

See Also:

"Oracle Database SQL Language Reference for a complete description of the CREATE INDEX statement

Purpose

Use CREATE INDEX to create an Oracle Text index. An Oracle Text index is an Oracle Database domain index or composite domain index of type CONTEXT, CTXCAT, or CTXRULE. A domain index is an application-specific index. A **composite domain index** (CDI) is an Oracle Text index that not only indexes and processes a specified

text column, but also indexes and processes `FILTER BY` and `ORDER BY` structured columns, which are specified during index creation.

You must create an appropriate Oracle Text index to enter `CONTAINS`, `CATSEARCH`, or `MATCHES` queries.

You cannot create an Oracle Text index on an index-organized table.

You can create the following types of Oracle Text indexes.

CONTEXT

A `CONTEXT` index is the basic type of Oracle Text index. This is an index on a text column. A `CONTEXT` index is useful when your source text consists of many large, coherent documents. Query this index with the `CONTAINS` operator in the `WHERE` clause of a `SELECT` statement. This index requires manual synchronization after DML. See "[Syntax for CONTEXT Index Type](#) (page 1-41)".

CTXCAT

The `CTXCAT` index is a combined index on a text column and one or more other columns. The `CTXCAT` type is typically used to index small documents or text fragments, such as item names, prices, and descriptions found in catalogs. Query this index with the `CATSEARCH` operator in the `WHERE` clause of a `SELECT` statement. This type of index is optimized for mixed queries. This index is transactional, automatically updating itself with DML to the base table. See "[Syntax for CTXCAT Index Type](#) (page 1-58)".

CTXRULE

A `CTXRULE` index is used to build a document classification application. The `CTXRULE` index is an index created on a table of queries or a column containing a set of queries, where the queries serve as rules to define the classification criteria. Query this index with the `MATCHES` operator in the `WHERE` clause of a `SELECT` statement. See "[Syntax for CTXRULE Index Type](#) (page 1-61)".

Required Privileges

You do not need the `CTXAPP` role to create an Oracle Text index. If you have Oracle Database grants to create a B-tree index on the text column, you have sufficient privilege to create a text index. The issuing owner, table owner, and index owner can all be different users, which is consistent with Oracle standards for creating regular B-tree indexes.

Syntax for CONTEXT Index Type

Uses a `CONTEXT` index to create an index on a text column. Query this index with the `CONTAINS` operator in the `WHERE` clause of a `SELECT` statement. This index requires manual synchronization after DML.

```
CREATE INDEX [schema.]index ON [schema.]table(txt_column)
  INDEXTYPE IS ctxsys.context [ONLINE]
  [FILTER BY filter_column[, filter_column]...]
  [ORDER BY oby_column[desc|asc][, oby_column[desc|asc]]...]
  [LOCAL [PARTITION [partition] [PARAMETERS('paramstring')]]]
  [, PARTITION [partition] [PARAMETERS('paramstring')]]]
  [PARAMETERS(paramstring)] [PARALLEL n] [UNUSABLE];
```

[schema.]index

Specifies the name of the Text index to create.

[*schema*.]*table*(*txt_column*)

Specifies the name of the table and column to index. *txt_column* is the name of the domain index column on which the `CONTAINS ()` operator will be invoked.

Your table can optionally contain a primary key if you prefer to identify your rows as such when you use procedures in `CTX_DOC`. When your table has no primary key, document services identifies your documents by `ROWID`.

Note:

Primary keys of the following type are supported: `NUMBER`, `VARCHAR2`, `DATE`, `CHAR`, `VARCHAR`, and `RAW`.

The column that you specify must be one of the following types: `CHAR`, `VARCHAR`, `VARCHAR2`, `BLOB`, `CLOB`, `BFILE`, `XMLType`, or `URIType`.

The table that you specify can be a partitioned table. If you do not specify the `LOCAL` clause, then a global, nonpartitioned index is created.

The `DATE`, `NUMBER`, and nested table columns cannot be indexed. Object columns also cannot be indexed, but their attributes can be indexed, provided that they are atomic data types.

Attempting to create an index on a Virtual Private Database (VPD) protected table will fail unless one of the following criteria is true:

- The VPD policy is created such that it does not apply to the `INDEX` statement type.
- The policy function returns a `NULL` predicate for the current user.
- The user (or index owner) is `SYS`.
- The user has the `EXEMPT ACCESS POLICY` privilege.

Indexes on multiple columns are not supported with the `CONTEXT` index type. You must specify only one column in the column list.

Note:

With the `CTXCAT` index type, you can create indexes on text and structured columns. See "[Syntax for CTXCAT Index Type](#) (page 1-58)"

Note:

Because a Transparent Data Encryption-enabled column does not support domain indexes, it cannot be used with Oracle Text. However, you can create an Oracle Text index on a column in a table stored in a Transparent Data Encryption-enabled tablespace.

ONLINE

Creates the index while enabling DML insertions/updates/deletions on the base table.

During indexing, Oracle Text enqueues DML requests in a pending queue. At the end of the index creation, Oracle Text locks the base table. During this time, DML is blocked. You must synchronize the index in order for DML changes to be available.

Limitations

The following limitations apply to using `ONLINE`:

- At the very beginning or very end of the `ONLINE` process, DML might fail.
- `ONLINE` is supported for `CONTEXT` indexes only.

FILTER BY *filter_column*

This is the structured indexed column on which a range or equality predicate in the `WHERE` clause of a mixed query will operate. You can specify one or more structured columns for *filter_column*, on which the relational predicates are expected to be specified along with the `CONTAINS()` predicate in a query.

The Cost-based Optimizer (CBO) will consider pushing down the structured predicates on these `FILTER BY` columns with the following relational operators: `<`, `<=`, `=`, `>=`, `>`, `between`, and `LIKE` (for `VARCHAR2`).

These columns can only be of `CHAR`, `NUMBER`, `DATE`, `VARCHAR2`, or `RAW` type. Additionally, `VARCHAR2` and `RAW` types are supported only if the maximum length is specified and is limited to no more than 249. The ADT attributes of supported types (`CHAR`, `NUMBER`, `DATE`, `VARCHAR2`, or `RAW`) are also allowed. An error is raised for all other data types. Expressions, for example, `func(col1)`, and virtual columns are not allowed.

txt_column is allowed in the `FILTER BY` column list.

DML operations on `FILTER BY` columns are always transactional.

ORDER BY *oby_column*

This is the structured indexed column on which a structured `ORDER BY` mixed query will be based. A list of structured *oby_columns* can be specified in the `ORDER BY` clause of a `CONTAINS()` query.

These columns can only be of `CHAR`, `NUMBER`, `DATE`, `VARCHAR2`, or `RAW` type. Additionally, `VARCHAR2` and `RAW` types are supported only if the maximum length is specified and is limited to no more than 249. Expressions, for example, `func(col1)`, and virtual columns are not allowed.

The order of the specified columns matters. The Cost-based Optimizer (CBO) will consider pushing the sort into the composite domain index only if the `ORDER BY` clause in the text query contains:

- Entire ordered `ORDER BY` columns declared by the `ORDER BY` clause during the `CREATE INDEX` statement
- Only the prefix of the ordered `ORDER BY` columns declared by the `ORDER BY` clause during the `CREATE INDEX` statement
- The score followed by the prefix of the ordered `ORDER BY` columns declared by the `ORDER BY` clause during the `CREATE INDEX` statement
- The score following the prefix of the ordered `ORDER BY` columns declared by the `ORDER BY` clause during the `CREATE INDEX` statement

The following example illustrates Cost-based Optimizer (CBO) behavior with regard to `ORDER BY` columns:

```
CREATE INDEX foox ON foo(D) INDEXTYPE IS CTXSYS.CONTEXT
FILTER BY B, C
ORDER BY A, B desc;
```

Consider the following query:

```
SELECT A, SCORE(1) FROM foo WHERE CONTAINS(D, 'oracle',1)>0
AND C>100 ORDER BY col_list;
```

Note:

If you set NLS_SORT or NLS_COMP parameters (that is, alter session set NLS_SORT = <some lang>;), then CBO will not push the sort or related structured predicate into the CDI. This behavior is consistent with regular B-tree indexes.

The Cost-based Optimizer (CBO) will consider pushing the sort into the composite domain index (CDI) if col_list has the following values:

```
A
A,B
SCORE(1), A
SCORE(1), A, B
A, SCORE(1)
A, B, SCORE(1)
```

The CBO will not consider to push the sort into the CDI if col_list has the following values:

```
B
B,A
SCORE(1), B
B, SCORE(1)
A, B, C
A, B asc
```

(or simply A, B)

- The SCORE followed by the prefix of the ordered ORDER BY columns declared by the ORDER BY clause during the CREATE INDEX statement.
- The SCORE following the prefix of the ordered ORDER BY columns declared by the ORDER BY clause during the CREATE INDEX statement.

Expressions, for example, func(col_a), are not allowed.

txt_column appearing in the ORDER BY column list is allowed.

DML operations on ORDER BY columns are always transactional.

Limitations

The following limitations apply to FILTER BY and ORDER BY:

- A structured column is allowed in FILTER BY and ORDER BY clauses. However, a column that is mapped to MDATA in a FILTER BY clause cannot also appear in the ORDER BY clause. An error will be raised in this case.
- The maximum length for CHAR, VARCHAR2, and RAW columns cannot be greater than 249. Additionally, if the VARCHAR2 or RAW column is mapped to an MDATA column, then the specified maximum length cannot exceed 64 and 32 bytes,

respectively. (Note that MDATA does not support CHAR data types. If a FILTER BY column of CHAR data type is mapped to an MDATA section, then an error will be raised during the CREATE INDEX statement.)

- The sum of the numbers for INDEXED_COLUMN, FILTER BY columns, and ORDER BY columns cannot be greater than 99.

Note:

- As with concatenated B-tree indexes or bitmap indexes, performance degradation may occur in DML as the number of FILTER BY and ORDER BY columns increases.
 - Mapping a FILTER BY column to MDATA is not recommended if the FILTER BY column contains sequential values or has very high cardinality. Doing so can result in a very long and narrow \$I table and reduced \$X performance. An example is a column of type DATE. For columns of this type, mapping to SDATA is recommended.
-
-

Note:

An index table with the name DR\$*indextable*\$S is created to store FILTER BY and ORDER BY columns that are mapped to SDATA sections. If nothing is mapped to an SDATA section, then the \$S table will not be created.

\$S table contains the following columns:

- SDATA_ID *number* is the internal SDATA section ID.
- SDATA_LAST *number*, the last document ID, which is analogous to token_last.
- SDATA_DATA RAW(2000), the compressed SDATA values. Note that if \$S is created on a tablespace with 4K database block size, then it will be defined as RAW(1500).

Restriction: For performance reasons, \$S table must be created on a tablespace with db block size >= 4K without overflow segment and without PCTTHRESHOLD clause. If \$S is created on a tablespace with db block size < 4K, or is created with an overflow segment or with a PCTTHRESHOLD clause, then appropriate errors will be raised during the CREATE INDEX statement.

Restrictions on exporting and importing text tables with composite domain index created with FILTER BY and/or ORDER BY clauses are as follows:

- Regular exp and imp will not support exporting and importing of composite domain index. Doing so will lead to the following error: EXP-00113: Feature Composite Domain Index is unsupported.
- To export a text table with composite domain index, you must use Data Pump Export and Import utilities (invoked with the expdp and impdp commands, respectively), or DBMS_DATAPUMP PL/SQL package.

See Also:

[ADD_SDATA_COLUMN](#) (page 8-14) in [CTX_DDL Package](#) (page 8-1)

Limitations of using ALTER INDEX and ALTER TABLE with FILTER BY and ORDER BY columns of the composite domain index, which are imposed by Extensible Indexing Framework in Oracle Database:

(These limitations are imposed by Extensible Indexing Framework in Oracle Database.)

- Using ALTER INDEX to add or drop FILTER BY and ORDER BY columns is currently not supported. You must re-create the index to add or drop FILTER BY or ORDER BY columns.
- To use ALTER TABLE MODIFY COLUMN to modify the datatype of a column that has the composite domain index built on it, you must first drop the composite domain index before modifying the column.
- To use ALTER TABLE DROP COLUMN to drop a column that is part of the composite domain index, you must first drop the composite domain index before dropping the index column.

The following limitations apply to FILTER BY and ORDER BY when used with PL/SQL packages:

- Mapping FILTER BY columns to sections is optional. If section mapping does not exist for a FILTER BY column, then it is mapped to an SDATA section by default. The section name assumes the name of the FILTER BY column.
- If a section group is not specified during the CREATE INDEX clause of a composite domain index, then system default section group settings are used. An SDATA section is created for each of the FILTER BY and ORDER BY columns.

Note:

Because a section name does not allow certain special characters and is case-insensitive, if the column name is case-sensitive or contains special characters, then an error will be raised. To work around this problem, you must map the column to an MDATA or SDATA section before creating the index. See [CTX_DDL.ADD_MDATA_COLUMN](#) (page 8-11) or [CTX_DDL.ADD_SDATA_COLUMN](#) (page 8-14).

- An error is raised if a column that is mapped to an MDATA section also appears in the ORDER BY column clause.
- Column section names are unique to their section group. That is, you cannot have an MDATA column section named FOO if you already have an MDATA column section named FOO. Nor can you have a field section named FOO if you already have an SDATA column section named FOO. This is true whether it is implicitly created (by CREATE INDEX for FILTER BY or ORDER BY clauses) or explicitly created (by CTX_DDL.ADD_SDATA_COLUMN).
- One section name can be mapped to only one FILTER BY column, and vice versa. Mapping a section to more than one column, or mapping a column to more than one section is not allowed.

- Column sections can be added to any type of section group, including the NULL section group.
- If a section group with sections added by the `CTX_DDL.ADD_MDATA_COLUMN` or `CTX_DDL.ADD_SDATA_COLUMN` packages is specified for a `CREATE INDEX` statement without a `FILTER BY` clause, then the mapped column sections will be ignored. However, the index will still get created without those column sections. The same is true for a `FILTER BY` clause that does not contain mapped columns in the specified section group.

See Also:

[CTX_DDL.ADD_SDATA_COLUMN](#) (page 8-14)

LOCAL [PARTITION [partition] [PARAMETERS('paramstring')]

Specifies a local partitioned context index on a partitioned table. The partitioned table must be partitioned by range. Hash, composite, and list partitions are not supported.

You can specify the list of index partition names with *partition_name*. If you do not specify a partition name, then the system assigns one. The order of the index partition list must correspond to the table partition order.

The `PARAMETERS` clause associated with each partition specifies the parameters string specific to that partition. You can only specify *sync (manual | every | on commit)*, *memory* and *storage* for each index partition.

The `PARAMETERS` clause also supports the `POPULATE` and `NOPOPULATE` arguments. See "[POPULATE | NOPOPULATE](#) (page 1-52)".

Query the views [CTX_INDEX_PARTITIONS](#) (page G-6) or [CTX_USER_INDEX_PARTITIONS](#) (page G-19) to find out index partition information, such as index partition name, and index partition status.

See Also:

"[Creating a Local Partitioned Index](#) (page 1-55)"

Query Performance Limitation with Partitioned Index

For optimal performance when querying a partitioned index with an `ORDER BY SCORE` clause, query the partition. If you query the entire table and use an `ORDER BY SCORE` clause, the query might not perform optimally unless you include a range predicate that can limit the query to the fewest number of partitions, which is optimally a single partition.

See Also:

"[Query Performance Limitation with a Partitioned Index](#) (page 1-40)"

PARALLEL n

Optionally specifies the parallel degree for parallel indexing. The actual degree of parallelism might be smaller depending on your resources. You can use this parameter on nonpartitioned tables. However, creating a nonpartitioned index in

parallel does not turn on parallel query processing. Parallel indexing is supported for creating a local partitioned index.

The indexing memory size specified in the parameter clause applies to each parallel slave. For example, if indexing memory size is specified in the parameter clause as 500M and parallel degree is specified as 2, then you must ensure that there is at least 1GB of memory available for indexing.

See Also:

- ["Parallel Indexing" \(page 1-56\)](#)
 - ["Creating a Local Partitioned Index in Parallel" \(page 1-56\)](#)
 - The "Performance Tuning" chapter in *Oracle Text Application Developer's Guide*
-
-

Performance

Parallel indexing can speed up indexing when you have large amounts of data to index and when your operating system supports multiple CPUs.

Note:

Using PARALLEL to create a local partitioned index that enables parallel queries. (Creating a nonpartitioned index in parallel does not turn on parallel query processing.)

Parallel querying degrades query throughput especially on heavily loaded systems. Because of this, Oracle recommends that you disable parallel querying after creating a local index. To do so, use the ALTER INDEX NOPARALLEL statement.

For more information on parallel querying, see the "Performance Tuning" chapter in *Oracle Text Application Developer's Guide*.

Limitations

Parallel indexing is supported only for the CONTEXT index type.

UNUSABLE

Creates an unusable index. This creates index metadata only and exits immediately.

You might create an unusable index when you need to create a local partitioned index in parallel.

See Also:

["Creating a Local Partitioned Index in Parallel" \(page 1-56\)](#)

PARAMETERS(*paramstring*)

Optionally specify indexing parameters in *paramstring*. You can specify preferences owned by another user using the *user.preference* notation.

The syntax for *paramstring* is as follows:

```

paramstring =
'[DATASTORE datastore_pref]
[FILTER filter_pref]
[CHARSET COLUMN charset_column_name]
[FORMAT COLUMN format_column_name]
[SAVE_COPY COLUMN save_copy_column_name]

[LEXER lexer_pref]
[LANGUAGE COLUMN language_column_name]

[WORDLIST wordlist_pref]
[STORAGE storage_pref]
[STOPLIST stoplist]
[SECTION GROUP section_group]
[MEMORY memsize]
[POPULATE | NOPOPULATE]
[SYNC (MANUAL | EVERY "interval-string" | ON COMMIT)]
[TRANSACTIONAL]'

```

Create datastore, filter, lexer, wordlist, and storage preferences with CTX_DDL.[CREATE_PREFERENCE](#) (page 8-31) and then specify them in the paramstring.

Note:

When you specify no paramstring, Oracle Text uses the system defaults.

For more information about these defaults, see "[Default Index Parameters](#) (page 2-99)".

DATASTORE *datastore_pref*

Specifies the name of your datastore preference. Use the datastore preference to specify where your text is stored. See "[Datastore Types](#) (page 2-2)".

FILTER *filter_pref*

Specifies the name of your filter preference. Use the filter preference to specify how to filter formatted documents to plain text or HTML. See "[Filter Types](#) (page 2-19)".

CHARSET COLUMN *charset_column_name*

Specifies the name of the character set column. This column must be in the same table as the text column, and it must be of type CHAR, VARCHAR, or VARCHAR2. Use this column to specify the document character set for conversion to the database character set. The value is case-insensitive. You must specify a globalization support character set string, such as JA16EUC.

When the document is plain text or HTML, the AUTO_FILTER and CHARSET filters use this column to convert the document character set to the database character set for indexing.

Use this column when you have plain text or HTML documents with different character sets or in a character set different from the database character set.

Setting NLS_LENGTH_SEMANTICS parameter to CHAR is not supported at the database level. This parameter is supported for the following columns:

- The CHARSET COLUMN, for example:

```

VARCHAR2 <size> CHAR
CHAR <size> CHAR

```

- An index created on a VARCHAR2 and CHAR column
- VARCHAR2 and CHAR columns for FILTER BY and ORDER BY clauses of CREATE INDEX
- FORMAT COLUMN

Note:

- Documents are not marked for re-indexing when only the character set column changes. The indexed column must be updated to flag the re-index.
 - The NLS_LENGTH_SEMANTICS = CHAR parameter is supported at the column level only, and is not supported at the database level, as described in this section.
-

FORMAT COLUMN *format_column_name*

Specifies the name of the format column. The format column must be in the same table as the text column and it must be CHAR, VARCHAR, or VARCHAR2 type.

FORMAT COLUMN determines how a document is filtered, or, in the case of the IGNORE value, if it is to be indexed.

AUTO_FILTER uses the format column when filtering documents. Use this column with heterogeneous document sets to optionally bypass filtering for plain text or HTML documents.

In the format column, you can specify one of the following options:

- TEXT
- BINARY
- IGNORE

The TEXT option indicates that the document is either plain text or HTML. When TEXT is specified, the document is not filtered, but may have the character set converted.

The BINARY option indicates that the document is a format supported by the AUTO_FILTER object other than plain text or HTML, for example PDF. BINARY is the default, if the format column entry cannot be mapped.

The IGNORE option indicates that the row is to be ignored during indexing. Use this value when you need to bypass rows that contain data incompatible with text indexing such as image data, or rows in languages that you do not want to process. The difference between documents with TEXT and IGNORE format column types is that the former are indexed but ignored by the filter, while the latter are not indexed at all. Thus, IGNORE can be used with any filter type.

Note:

Documents are not marked for re-indexing when only the format column changes. The indexed column must be updated to flag the re-index.

SAVE_COPY COLUMN *save_copy_column_name*

Specifies the name of the column that contains the preference of whether to save a copy of a document into the \$D index table during a search operation.

You can specify one of the following three options in the SAVE_COPY column: PLAINTEXT, FILTERED, or NONE.

The PLAINTEXT option indicates that the document should be stored as a plain text in the \$D index table. Specify this value when using the SNIPPET procedure.

The FILTERED option indicates that a filter preference should be applied on the text present in the document before storing it into the \$D index table. Specify this value when using the MARKUP procedure or the HIGHLIGHT procedure.

The NONE option indicates that a copy of the document should not be saved in the \$D index table. Specify this value for any of the following scenarios:

- when SNIPPET, MARKUP, or HIGHLIGHT procedure is not used.
- when the indexed column is either VARCHAR2 or CLOB.

LEXER *lexer_pref*

Specifies the name of your lexer or multilexer preference. Use the lexer preference to identify the language of your text and how text is tokenized for indexing. See "[Lexer Types](#) (page 2-32)".

LANGUAGE COLUMN *language_column_name*

Specifies the name of the language column when using a multi-lexer preference. See "[MULTI_LEXER](#) (page 2-49)".

This column must exist in the base table. It cannot be the same column as the indexed column. Only the first 30 bytes of the language column are examined for language identification.

Note:

Documents are not marked for re-indexing when only the language column changes. The indexed column must be updated to flag the re-index.

WORDLIST *wordlist_pref*

Specifies the name of your wordlist preference. Use the wordlist preference to enable features such as fuzzy, stemming, and prefix indexing for better wildcard searching. See "[Wordlist Type](#) (page 2-72)".

STORAGE *storage_pref*

Specifies the name of your storage preference for the Text index. Use the storage preference to specify how the index tables are stored. See "[Storage Types](#) (page 2-80)".

STOPLIST *stoplist*

Specifies the name of your stoplist. Use stoplist to identify words that are not to be indexed. See CTX_DDL.[CREATE_STOPLIST](#) (page 8-39).

SECTION GROUP *section_group*

Specifies the name of your section group. Use section groups to create searchable sections in structured documents. See CTX_DDL.[CREATE_SECTION_GROUP](#) (page 8-34).

MEMORY *memsize*

Specifies the amount of run-time memory to use for indexing. The syntax for `memsize` is as follows:

```
memsize = number[K|M|G]
```

K stands for kilobytes, M stands for megabytes, and G stands for gigabytes.

The value you specify for `memsize` must be between 1M and the value of `MAX_INDEX_MEMORY` in the [CTX_PARAMETERS](#) (page G-10) view. To specify a memory size larger than the `MAX_INDEX_MEMORY`, you must reset this parameter with `CTX_ADM.SET_PARAMETER` (page 5-3) to be larger than or equal to `memsize`.

The default is the value specified for `DEFAULT_INDEX_MEMORY` in `CTX_PARAMETERS`.

The `memsize` parameter specifies the amount of memory Oracle Text uses for indexing before flushing the index to disk. Specifying a large amount memory improves indexing performance because there are fewer I/O operations and improves query performance and maintenance, because there is less fragmentation.

Specifying smaller amounts of memory increases disk I/O and index fragmentation, but might be useful when run-time memory is scarce.

POPULATE | NOPOPULATE

Specifies whether an index should be empty or populated. The default is `POPULATE`.

Note:

`POPULATE | NOPOPULATE` is the only option whose default value cannot be set with `CTX_ADM.SET_PARAMETER` (page 5-3).

Empty indexes are populated by updates or inserts to the base table. You might create an empty index when you need to create your index incrementally or to selectively index documents in the base table. You might also create an empty index when you require only theme and Gist output from a document set.

SYNC (MANUAL | EVERY "*interval-string*" | ON COMMIT)

Specifies `SYNC` for automatic synchronization of the `CONTEXT` index when there are inserts, updates or deletes to the base table. You can specify one of the following `SYNC` methods:

SYNC Type	Description
MANUAL	Provides no automatic synchronization. This is the default. You must manually synchronize the index with <code>CTX_DDL.SYNC_INDEX</code> .

SYNC Type	Description
EVERY " <i>interval-string</i> "	<p>Automatically synchronizes the index at a regular interval specified by the value of <i>interval-string</i>, which takes the same syntax as that for scheduler jobs. Automatic synchronization using EVERY requires that the index creator have CREATE JOB privileges.</p> <p>Ensure that <i>interval-string</i> is set to a long enough period that any previous sync jobs will have completed; otherwise, the sync job might hang. <i>interval-string</i> must be enclosed in double quotes, and any single quote within <i>interval-string</i> must be preceded by the escape character with another single quote.</p> <p>See "Enabling Automatic Index Synchronization (page 1-55)" for an example of automatic sync syntax.</p>
ON COMMIT	<p>Synchronizes the index immediately after a commit transaction. The commit transaction does not return until the sync is complete. (Because the synchronization is performed as a separate transaction, there may be a period, usually small, when the data is committed but index changes are not.)</p> <p>The operation uses the memory specified with the <i>memory</i> parameter.</p> <p>Note that the sync operation has its own transaction context. If this operation fails, the data transaction is still committed. Index synchronization errors are logged in the CTX_USER_INDEX_ERRORS view. See "Viewing Index Errors (page 1-58)".</p> <p>See "Enabling Automatic Index Synchronization (page 1-55)" for an example of ON COMMIT syntax.</p>

Each partition of a locally partitioned index can have its own type of sync (ON COMMIT, EVERY, or MANUAL). The type of sync specified in master parameter strings applies to all index partitions unless a partition specifies its own type.

With automatic (EVERY) synchronization, users can specify memory size and parallel synchronization. That syntax is:

```
... EVERY interval_string MEMORY mem_size PARALLEL pardegree ...
```

The ON COMMIT synchronizations can be run only serially and must use the same memory size that was specified at index creation.

See Also:

Oracle Database Administrator's Guide for information about job scheduling

TRANSACTIONAL

Specifies that documents can be searched immediately after they are inserted or updated. If a text index is created with TRANSACTIONAL enabled, then, in addition to

processing the synchronized rowids already in the index, the CONTAINS operator will process unsynchronized rowids as well. Oracle Text does in-memory indexing of unsynchronized rowids and processes the query against the in-memory index.

TRANSACTIONAL is an index-level parameter and does not apply at the partition level.

You must still synchronize your text indexes from time to time (with CTX_DDL.SYNC_INDEX) to bring pending rowids into the index. Query performance degrades as the number of unsynchronized rowids increases. For that reason, Oracle recommends setting up your index to use automatic synchronization with the EVERY or ON COMMIT parameter. (See "[SYNC \(MANUAL | EVERY \"interval-string\" | ON COMMIT\)](#) (page 1-52)".)

Transactional querying for indexes that have been created with the TRANSACTIONAL parameter can be turned on and off (for the duration of a user session) with the PL/SQL variable CTX_QUERY.disable_transactional_query. This is useful, for example, if you find that querying is slow due to the presence of too many pending rowids. Here is an example of setting this session variable:

```
exec ctx_query.disable_transactional_query := TRUE;
```

If the index uses AUTO_FILTER, queries involving unsynchronized rowids will require filtering of unsynchronized documents.

CREATE INDEX: CONTEXT Index Examples

The following sections give examples of creating a CONTEXT index.

Creating CONTEXT Index Using Default Preferences

The following example creates a CONTEXT index called myindex on the docs column in mytable. Default preferences are used.

```
CREATE INDEX myindex ON mytable(docs) INDEXTYPE IS ctxsys.context;
```

See Also:

- *Oracle Text Application Developer's Guide*
 - For more information about default settings, see "[Default Index Parameters](#) (page 2-99)"
-

Creating CONTEXT Index with Custom Preferences

The following example creates a CONTEXT index called myindex on the docs column in mytable. The index is created with a custom lexer preference called my_lexer and a custom stoplist called my_stop.

This example also assumes that the preference and stoplist were previously created with CTX_DDL.[CREATE_PREFERENCE](#) (page 8-31) for my_lexer, and CTX_DDL.[CREATE_STOPLIST](#) (page 8-39) for my_stop. Default preferences are used for the unspecified preferences.

```
CREATE INDEX myindex ON mytable(docs) INDEXTYPE IS ctxsys.context  
PARAMETERS('LEXER my_lexer STOPLIST my_stop');
```

Any user can use any preference. To specify preferences that exist in another user's schema, add the user name to the preference name. The following example assumes

that the preferences `my_lexer` and `my_stop` exist in the schema that belongs to user `kenny`:

```
CREATE INDEX myindex ON mytable(docs) INDEXTYPE IS ctxsys.context
  PARAMETERS('LEXER kenny.my_lexer STOPLIST kenny.my_stop');
```

Enabling Automatic Index Synchronization

You can create your index and specify that the index be synchronized at regular intervals for insertions, updates and deletions to the base table. To do so, create the index with the `SYNC (EVERY "interval-string")` parameter.

To use job scheduling, you must log in as a user who has DBA privileges and then grant `CREATE JOB` privileges.

The following example creates an index and schedules three synchronization jobs for three index partitions. The first partition uses `ON COMMIT` synchronization. The other two partitions are synchronized by jobs that are scheduled to be executed every Monday at 3 P.M.

```
CONNECT system/password
GRANT CREATE JOB TO dr_test

CREATE INDEX tdrmauto02x ON tdrmauto02(text)
  INDEXTYPE IS CTXSYS.CONTEXT local
  (PARTITION tdrm02x_i1 PARAMETERS('
    MEMORY 20m SYNC(ON COMMIT)'),
  PARTITION tdrm02x_i2,
  PARTITION tdrm02x_i3) PARAMETERS('
    SYNC (EVERY "NEXT_DAY(TRUNC(SYSDATE), 'MONDAY') + 15/24"
  ');
```

See *Oracle Database Administrator's Guide* for information about job scheduling syntax.

Creating CONTEXT Index with Multilexer Preference

The multilexer preference decides which lexer to use for each row based on a language column. This is a character column in the table that stores the language of the document in the text column. For example, create the table `globaldoc` to hold documents of different languages:

```
CREATE TABLE globaldoc (
  doc_id NUMBER PRIMARY KEY,
  lang VARCHAR2(10),
  text CLOB
);
```

Assume that `global_lexer` is a multilexer preference you created. To index the `global_doc` table, specify the multilexer preference and the name of the language column as follows:

```
CREATE INDEX globalx ON globaldoc(text) INDEXTYPE IS ctxsys.context PARAMETERS
('LEXER global_lexer LANGUAGE COLUMN lang');
```

See Also:

["MULTI_LEXER \(page 2-49\)"](#) for more information about creating multilexer preferences

Creating a Local Partitioned Index

The following example creates a text table that is partitioned into three, populates it, and then creates a partitioned index:

PROMPT create partitioned table and populate it

```
CREATE TABLE part_tab (a int, b varchar2(40)) PARTITION BY RANGE(a)
(partition p_tab1 values less than (10),
 partition p_tab2 values less than (20),
 partition p_tab3 values less than (30));
```

PROMPT create partitioned index

```
CREATE INDEX part_idx on part_tab(b) INDEXTYPE IS CTXSYS.CONTEXT
LOCAL (partition p_idx1, partition p_idx2, partition p_idx3);
```

Note:

The limit for the number of partitions in Oracle Text is the same as the maximum number of partitions per table in Oracle Database.

Using FILTER BY and ORDER BY Clauses

The following example creates an index on table *docs* and orders the documents by author's publishing date.

First, create the table:

```
CREATE TABLE docs (
  docid    NUMBER,
  pub_date DATE,
  author   VARCHAR2(30),
  category VARCHAR2(30),
  document CLOB
);
```

Create the index with **FILTER BY** and **ORDER BY** clauses:

```
CREATE INDEX doc_idx on docs(document) indextype is ctxsys.context
  FILTER BY category, author
  ORDER BY pub_date desc, docid
  PARAMETERS ('memory 500M');
```

Parallel Indexing

Parallel indexing can improve index performance when you have multiple CPUs.

To create an index in parallel, use the **PARALLEL** clause with a parallel degree. This example uses a parallel degree of 3:

```
CREATE INDEX myindex ON mytab(pk) INDEXTYPE IS ctxsys.context PARALLEL 3;
```

Creating a Local Partitioned Index in Parallel

Creating a local partitioned index in parallel can improve performance when you have multiple CPUs. With partitioned tables, you can divide the work. You can create a local partitioned index in parallel in two ways:

- Use the **PARALLEL** clause with the **LOCAL** clause in the **CREATE INDEX** statement. In this case, the maximum parallel degree is limited to the number of partitions you have. See "[Parallelism with CREATE INDEX](#) (page 1-57)".

- Create an unusable index first, then run the DBMS_PCLUTIL.BUILD_PART_INDEX utility. This method can result in a higher degree of parallelism, especially if you have more CPUs than partitions. See "[Parallelism with DBMS_PCLUTIL.BUILD_PART_INDEX](#) (page 1-57)".

If you attempt to create a local partitioned index in parallel, and the attempt fails, you may see the following error message:

```
ORA-29953: error in the execution of the ODCIIndexCreate routine for one or more
of the index partitions
```

To determine the specific reason why the index creation failed, query the [CTX_USER_INDEX_ERRORS](#) (page G-18) view.

Parallelism with CREATE INDEX

You can achieve local index parallelism by using the PARALLEL and LOCAL clauses in the CREATE INDEX statement. In this case, the maximum parallel degree is limited to the number of partitions that you have.

The following example creates a table with three partitions, populates them, and then creates the local indexes in parallel with a degree of 2:

```
create table part_tab3(id number primary key, text varchar2(100))
partition by range(id)
(partition p1 values less than (1000),
 partition p2 values less than (2000),
 partition p3 values less than (3000));

begin
  for i in 0..2999
  loop
    insert into part_tab3 values (i,'oracle');
  end loop;
end;
/

create index part_tab3x on part_tab3(text)
indextype is ctxsys.context local (partition part_tabx1,
                                  partition part_tabx2,
                                  partition part_tabx3)

parallel 2;
```

Parallelism with DBMS_PCLUTIL.BUILD_PART_INDEX

You can achieve local index parallelism by first creating an unusable CONTEXT index, and then running the DBMS_PCLUTIL.BUILD_PART_INDEX utility. This method can result in a higher degree of parallelism, especially when you have more CPUs than partitions.

In this example, the base table has three partitions. We create a local partitioned unusable index first, then run DBMS_PCLUTIL.BUILD_PART_INDEX, which builds the 3 partitions in parallel (referred to as inter-partition parallelism). Also, inside each partition, index creation proceeds in parallel (called intra-partition parallelism) with a parallel degree of 2. Therefore, the total parallel degree is 6 (3 times 2).

```
create table part_tab3(id number primary key, text varchar2(100))
partition by range(id)
(partition p1 values less than (1000),
 partition p2 values less than (2000),
 partition p3 values less than (3000));
```

```
begin
  for i in 0..2999
    loop
      insert into part_tab3 values (i,'oracle');
    end loop;
end;
/

create index part_tab3x on part_tab3(text)
indextype is ctxsys.context local (partition part_tabx1,
                                   partition part_tabx2,
                                   partition part_tabx3)

unusable;

exec dbms_pclxutil.build_part_index(jobs_per_batch=>3,
  procs_per_job=>2,
  tab_name=>'PART_TAB3',
  idx_name=>'PART_TAB3X',
  force_opt=>TRUE);
```

Viewing Index Errors

After a CREATE INDEX or ALTER INDEX operation, you can view index errors with Oracle Text views. To view errors on your indexes, query the [CTX_USER_INDEX_ERRORS](#) (page G-18) view. To view errors on all indexes as CTXSYS, query the [CTX_INDEX_ERRORS](#) (page G-6) view.

For example, to view the most recent errors on your indexes, enter the following statement:

```
SELECT err_timestamp, err_text FROM ctx_user_index_errors
ORDER BY err_timestamp DESC;
```

Deleting Index Errors

To clear the index error view, enter the following statement:

```
DELETE FROM ctx_user_index_errors;
```

Syntax for CTXCAT Index Type

Combines an index on a text column and one or more other columns. Query this index with the CATSEARCH operator in the WHERE clause of a SELECT statement. This type of index is optimized for mixed queries. This index is transactional, automatically updating itself with DML to the base table.

```
CREATE INDEX [schema.]index on [schema.]table(column) INDEXTYPE IS ctxsys.ctxcat
[PARAMETERS('['index set index_set
[lexer lexer_pref
[storage storage_pref
[stoplist stoplist
[section group sectiongroup_pref
[wordlist wordlist_pref
[memory memsize']');
```

[*schema.*]*table*(*column*)

Specifies the name of the table and column to index.

The column that you specify when you create a CTXCAT index must be of type CHAR or VARCHAR2. No other types are supported for CTXCAT.

Attempting to create an index on a Virtual Private Database (VPD) protected table will fail unless one of the following options is true:

- The VPD policy is created such that it does not apply to `INDEX` statement type, which is the default
- The policy function returns a null predicate for the current user.
- The user (index owner) is `SYS`.
- The user has the `EXEMPT ACCESS POLICY` privilege.

Supported CTXCAT Preferences

index set *index_set*

Specifies the index set preference to create the CTXCAT index. Index set preferences name the columns that make up your subindexes. Any column that is named in an index set column list cannot have a `NULL` value in any row of the base table, or else you get an error.

Always ensure that your columns have non-null values before and after indexing.

See "[Creating a CTXCAT Index](#) (page 1-60)".

Index Performance and Size Considerations

Although a CTXCAT index offers query performance benefits, creating this type of index has its costs. The time that it takes Oracle Text to create a CTXCAT index depends on the total size of the index.

The total size of a CTXCAT index is directly related to:

- Total text to be indexed
- Number of component indexes in the index set
- Number of columns in the base table that make up the component indexes

Having many component indexes in your index set also degrades DML performance because more indexes must be updated.

Because of these added costs in creating a CTXCAT index, you should carefully consider the query performance benefit that each component index gives your application before adding it to your index set.

See Also:

Oracle Text Application Developer's Guide for more information about creating CTXCAT indexes and the benefits

Other CTXCAT Preferences

When you create an index of type CTXCAT, you can use the supported index preferences listed in [Table 1-6](#) (page 1-60) in the `parameters` string.

Table 1-6 Supported CTXCAT Index Preferences

Preference Class	Supported Types
Datastore	This preference class is not supported for CTXCAT.
Filter	This preference class is not supported for CTXCAT.
Lexer	BASIC_LEXER (page 2-41) (<code>index_themes</code> attribute not supported) CHINESE_LEXER (page 2-52) CHINESE_VGRAM_LEXER (page 2-52) JAPANESE_LEXER (page 2-54) JAPANESE_VGRAM_LEXER (page 2-53) KOREAN_MORPH_LEXER (page 2-55)
Wordlist	BASIC_WORDLIST (page 2-72)
Storage	BASIC_STORAGE (page 2-81)
Stoplist	Supports single language stoplists only (<code>BASIC_STOPLIST</code> type).
Section Group	Only Field Section is supported for CTXCAT.

Unsupported Preferences and Parameters

When you create a CTXCAT index, you cannot specify datastore and filter preferences. For section group preferences, only the field section preference is supported. You also cannot specify language, format, or charset columns as with a CONTEXT index.

Creating a CTXCAT Index

This section gives a brief example for creating a CTXCAT index. For a more complete example, see *Oracle Text Application Developer's Guide*.

Consider a table called AUCTION with the following schema:

```
create table auction(item_id number,
title varchar2(100),
category_id number,
price number,
bid_close date);
```

Assume that queries on the table involve a mandatory text query clause and optional structured conditions on `price`. Results must be sorted based on `bid_close`. This means that an index to support good response time for the structured and sorting criteria is required.

You can create a catalog index to support the different types of structured queries a user might enter. For structured queries, a CTXCAT index improves query performance over a context index.

To create the indexes, first, create the index set preference, next, optionally, add the storage preference, and, finally, add the required indexes to it:

```
begin
ctx_ddl.create_index_set('auction_iset');
```

```
ctx_ddl.add_index('auction_iset','bid_close');
ctx_ddl.add_index('auction_iset','price, bid_close');
end;
```

Optionally, create the storage preference:

```
begin
ctx_ddl.create_preference('auction_st_pref', 'BASIC_STORAGE');
ctx_ddl.set_attribute('auction_st_pref', 'I_TABLE_CLAUSE',
                    'tablespace TEXT storage (initial 5M)');
ctx_ddl.set_attribute('auction_st_pref', 'I_ROWID_INDEX_CLAUSE',
                    'tablespace TEXT storage (initial 5M)');
ctx_ddl.set_attribute('auction_st_pref', 'I_INDEX_CLAUSE',
                    'tablespace TEXT storage (initial 5M) compress 2');
end;
/
```

Then, create the CTXCAT index with the CREATE INDEX statement as follows:

```
create index auction_titlex on AUCTION(title) indextype is CTXSYS.CTXCAT
parameters ('index set auction_iset storage auction_st_pref');
```

Querying a CTXCAT Index

To query the title column for the word *pokemon*, enter regular and mixed queries as follows:

```
select * from AUCTION where CATSEARCH(title, 'pokemon',NULL)> 0;
select * from AUCTION where CATSEARCH(title, 'pokemon', 'price < 50 order by
bid_close desc')> 0;
```

See Also:

Oracle Text Application Developer's Guide for a complete CTXCAT example

Syntax for CTXRULE Index Type

The CTXRULE type is an index on a column containing a set of queries. Query this index with the MATCHES operator in the WHERE clause of a SELECT statement.

```
CREATE INDEX [schema.]index on [schema.]table(rule_col) INDEXTYPE IS
ctxsys.ctxrule
[PARAMETERS ('[lexer lexer_pref] [storage storage_pref]
[section group section_pref] [wordlist wordlist_pref]
[classifier classifier_pref]');

[PARALLEL n];
```

[schema.]table(column)

Specifies the name of the table and rule column to index. The rules can be query compatible strings, query template strings, or binary Support Vector Machine rules.

The column you specify when you create a CTXRULE index must be VARCHAR2, CLOB or BLOB. No other types are supported for the CTXRULE type.

Attempting to create an index on a Virtual Private Database (VPD) protected table will fail unless one of the following is true:

- The VPD policy does not have the INDEX statement type turned on (which is the default).

- The policy function returns a null predicate for the current user.
- The user (index owner) is SYS.
- The user has the EXEMPT ACCESS POLICY privilege.

lexer_pref

Specifies the lexer preference to be used for processing queries and later for the documents to be classified with the MATCHES function.

With both classifiers SVN_CLASSIFIER and RULE_CLASSIFIER, you can use the BASIC_LEXER, CHINESE_LEXER, JAPANESE_LEXER, or KOREAN_MORPH_LEXER lexer. (See "[Classifier Types](#) (page 2-89)" and "[Lexer Types](#) (page 2-32)".)

For processing queries, these lexers support the following operators: ABOUT, STEM, AND, NEAR, NOT, OR, and WITHIN.

The thesaural operators (BT*, NT*, PT, RT, SYN, TR, TRSYS, TT, and so on) are supported. However, these operators are expanded using a snapshot of the thesaurus at index time, not when the MATCHES function is entered. This means that if you change your thesaurus after you index, you must re-index your query set.

storage_pref

Specify the storage preference for the index on the queries. Use the storage preference to specify how the index tables are stored. See "[Storage Types](#) (page 2-80)".

section_group

Specify the section group. This parameter does not affect the queries. It applies to sections in the documents to be classified. The following section groups are supported for the CTXRULE index type:

- BASIC_SECTION_GROUP
- HTML_SECTION_GROUP
- XML_SECTION_GROUP
- AUTO_SECTION_GROUP

See "[Section Group Types](#) (page 2-86)".

CTXRULE does not support special sections. It also does not support NDATA sections.

wordlist_pref

Specifies the wordlist preferences. This is used to enable stemming operations on query terms. See [Wordlist Type](#) (page 2-72).

classifier_pref

Specifies the classifier preference. See "[Classifier Types](#) (page 2-89)". You must use the same preference name you specify with CTX_CLS . TRAIN.

Example for Creating a CTXRULE Index

See *Oracle Text Application Developer's Guide* for a complete example of using the CTXRULE index type in a document routing application.

Related Topics

CTX_DDL.[CREATE_PREFERENCE](#) (page 8-31)

[CTX_DDL.CREATE_STOPLIST](#) (page 8-39)

[CTX_DDL.CREATE_SECTION_GROUP](#) (page 8-34)

["ALTER INDEX](#) (page 1-1)"

["CATSEARCH](#) (page 1-23)"

1.6 DROP INDEX

Note:

This section describes the `DROP INDEX` statement as it pertains to dropping a Text domain index.

For a complete description of the `DROP INDEX` statement, see *Oracle Database SQL Language Reference*.

Purpose

Use `DROP INDEX` to drop a specified Text index.

Syntax

```
DROP INDEX [schema.]index [force];
```

[force]

Optionally forces the index to be dropped. Use the `force` option when Oracle Text cannot determine the state of the index, such as when an indexing operation fails.

Oracle recommends against using this option by default. Use it only when a regular call to `DROP INDEX` fails.

Example

The following example drops an index named `doc_index` in the current user's database schema:

```
DROP INDEX doc_index;
```

Related Topics

["ALTER INDEX](#) (page 1-1)"

["CREATE INDEX](#) (page 1-40)"

1.7 MATCHES

Use the `MATCHES` operator to find all rows in a query table that match a given document. The document must be a plain text, HTML, or XML document.

The `MATCHES` operator also supports database links. You can identify a remote table or materialized view by appending `@dblink` to the end of its name. The `dblink` must be a complete or partial name for a database link to the database containing the remote table or materialized view. (Querying of remote views is not supported.)

This operator requires a `CTXRULE` index on your set of queries.

When the [SVM_CLASSIFIER](#) (page 2-91) classifier type is used, MATCHES returns a score in the range 0 to 100; a higher number indicates a greater confidence in the match. Use the `label` parameter and `MATCH_SCORE` to obtain this number. Then use the matching score to apply a category-specific threshold to a particular category.

If the `SVM_CLASSIFIER` type is not used, then this operator returns either 100 (the document matches the criteria) or 0 (the document does not match).

Limitation

If the optimizer chooses to use the functional query invocation with a MATCHES query, your query will fail.

Syntax

```
MATCHES(  
  
[schema.]column,  
document VARCHAR2 or CLOB  
[,label INTEGER])  
  
RETURN NUMBER;
```

column

Specifies the column containing the indexed query set.

document

Specifies the document to be classified. The document can be plain text, HTML, or XML. Binary formats are not supported.

label

Optionally specifies the label that identifies the score generated by the MATCHES operator. Use this label with [MATCH_SCORE](#) (page 1-65).

Matches Example

The following example creates a table `querytable`, and populates it with classification names and associated rules. It then creates a `CTXRULE` index.

The example enters the MATCHES query with a document string to be classified. The `SELECT` statement returns all rows (queries) that are satisfied by the document:

```
create table querytable (classification varchar2(64), text varchar2(4000));  
insert into querytable values ('common names', 'smith OR jones OR brown');  
insert into querytable values ('countries', 'United States OR Great Britain OR  
France');  
insert into querytable values ('Oracle DB', 'oracle NEAR database');  
  
create index query_rule on querytable(text) indextype is ctxsys.ctxrule;  
  
SELECT classification FROM querytable WHERE MATCHES(text, 'Smith is a common name  
in the United States') > 0;  
  
CLASSIFICATION  
-----  
common names  
countries
```

Related Topics

["MATCH_SCORE \(page 1-65\)"](#)

["Syntax for CTXRULE Index Type \(page 1-61\)"](#)

[CTX_CLS.TRAIN \(page 7-1\)](#)

Oracle Text Application Developer's Guide contains extended examples of simple and supervised classification, which make use of the MATCHES operator.

1.8 MATCH_SCORE

Use the MATCH_SCORE operator in a statement to return scores produced by a MATCHES query.

The MATCH_SCORE operator also supports database links. You can identify a remote table or materialized view by appending @dblink to the end of its name. The dblink must be a complete or partial name for a database link to the database containing the remote table or materialized view. (Querying of remote views is not supported.)

When the SVM_CLASSIFIER classifier type is used, this operator returns a score in the range 0 to 100. Use the matching score to apply a category-specific threshold to a particular category.

If the SVM_CLASSIFIER classifier is not used, then this operator returns either 100 (the document matches the criteria) or 0 (the document does not match).

Syntax

```
MATCH_SCORE(label NUMBER)
```

label

Specifies a number to identify the score produced by the query. Use this number to identify the MATCHES clause that returns this score.

Example

To get the matching score, use:

```
select cat_id, match_score(1) from training_result where matches(profile,
text,1)>0;
```

Related Topics

["MATCHES \(page 1-63\)"](#)

1.9 SCORE

Use the SCORE operator in a SELECT statement to return the score values produced by a [CONTAINS \(page 1-29\)](#) query. The SCORE operator can be used in a SELECT, ORDER BY, or GROUP BY clause.

The SCORE operator also supports database links. You can identify a remote table or materialized view by appending @dblink to the end of its name. The dblink must be a complete or partial name for a database link to the database containing the remote table or materialized view. (Querying of remote views is not supported.)

Syntax

```
SCORE(label NUMBER)
```

label

Specifies a number to identify the score produced by the query. Use this number to identify the CONTAINS clause that returns this score.

Example

Single CONTAINS

When the SCORE operator is called (for example, in a SELECT clause), the CONTAINS clause must reference the score label value as in the following example:

```
SELECT SCORE(1), title from newsindex
       WHERE CONTAINS(text, 'oracle', 1) > 0 ORDER BY SCORE(1) DESC;
```

Multiple CONTAINS

Assume that a news database stores and indexes the title and body of news articles separately. The following query returns all the documents that include the words *Oracle* in their title and *java* in their body. The articles are sorted by the scores for the first CONTAINS (*Oracle*) and then by the scores for the second CONTAINS (*java*).

```
SELECT title, body, SCORE(10), SCORE(20)

FROM news
WHERE CONTAINS (news.title, 'Oracle', 10) > 0 OR

CONTAINS (news.body, 'java', 20) > 0
ORDER BY SCORE(10), SCORE(20);
```

Related Topics

["CONTAINS \(page 1-29\)"](#)

[The Oracle Text Scoring Algorithm \(page F-1\)](#)

Oracle Text Indexing Elements

Oracle provides indexing types for storage, filtering, and lexers, and preferences and stoplists that you can use to create an Oracle Text index.

The chapter includes the following topics:

- [Overview](#) (page 2-1)
- [Creating Preferences](#) (page 2-2)
- [Datastore Types](#) (page 2-2)
- [Filter Types](#) (page 2-19)
- [Lexer Types](#) (page 2-32)
- [Wordlist Type](#) (page 2-72)
- [Storage Types](#) (page 2-80)
- [Section Group Types](#) (page 2-86)
- [Classifier Types](#) (page 2-89)
- [Cluster Types](#) (page 2-92)
- [Stoplists](#) (page 2-93)
- [System-Defined Preferences](#) (page 2-95)
- [System Parameters](#) (page 2-98)

2.1 Overview

When you use the [CREATE INDEX](#) (page 1-40) statement to create an index or the [ALTER INDEX](#) (page 1-1) statement to manage an index, you can optionally specify indexing preferences, stoplists, and section groups in the parameter string. Specifying a preference, stoplist, or section group answers one of the following questions about the way Oracle Text indexes text:

Preference Class	Answers the Question
Datastore	How are your documents stored?
Filter	How can the documents be converted to plain text?
Lexer	What language is being indexed?
Wordlist	How should stem and fuzzy queries be expanded?

Preference Class	Answers the Question
Storage	How should the index tables be stored?
Stop List	What words or themes are not to be indexed?
Section Group	Is querying within sections enabled, and how are the document sections defined?

This chapter describes how to set each preference. Enable an option by creating a preference with one of the types described in this chapter.

For example, to specify that your documents are stored in external files, you can create a datastore preference called `mydatastore` using the [FILE_DATASTORE](#) (page 2-9) type. Specify `mydatastore` as the datastore preference in the parameter clause of the `CREATE INDEX` statement.

2.2 Creating Preferences

To create a datastore, lexer, filter, classifier, wordlist, or storage preference, use the `CTX_DDL.CREATE_PREFERENCE` (page 8-31) procedure and specify one of the types described in this chapter. For some types, you can also set attributes with the `CTX_DDL.SET_ATTRIBUTE` (page 8-64) procedure.

An indexing *type* names a class of indexing objects that you can use to create an index *preference*. A type, therefore, is an abstract ID, while a preference is an entity that corresponds to a type. Many system-defined preferences have the same name as types (for example, `BASIC_LEXER`), but exact correspondence is not guaranteed. Be careful in assuming the existence or nature of either indexing types or system preferences.

You specify indexing preferences with the `CREATE INDEX` and `ALTER INDEX` statements. Indexing preferences determine how your index is created. For example, lexer preferences indicate the language of the text to be indexed. You can create and specify your own user-defined preferences, or you can use system-defined preferences.

To create a stoplist, use the `CTX_DDL.CREATE_STOPLIST` (page 8-39) procedure. Add stopwords to a stoplist with `CTX_DDL.ADD_STOPWORD`.

To create section groups, use `CTX_DDL.CREATE_SECTION_GROUP` (page 8-34) and specify a section group type. Add sections to section groups with the `CTX_DDL.ADD_ZONE_SECTION` or `CTX_DDL.ADD_FIELD_SECTION` procedures.

2.3 Datastore Types

Use the datastore types to specify how your text is stored. To create a datastore preference, you must use one of the datastore types described in [Table 2-1](#) (page 2-2).

Table 2-1 Datastore Types

Datastore Type	Use When
DIRECT_DATASTORE (page 2-3)	Data is stored internally in the text column. Each row is indexed as a single document.

Table 2-1 (Cont.) Datastore Types

Datastore Type	Use When
MULTI_COLUMN_DATASTORE (page 2-3)	Data is stored in a text table in more than one column. Columns are concatenated to create a virtual document, one for each row.
DETAIL_DATASTORE (page 2-7)	Data is stored internally in the text column. Document consists of one or more rows stored in a text column in a detail table, with header information stored in a master table.
FILE_DATASTORE (page 2-9)	Data is stored externally in operating system files. File names are stored in the text column, one for each row.
NESTED_DATASTORE (page 2-16)	Data is stored in a nested table.
URL_DATASTORE (page 2-11)	Data is stored externally in files located on an intranet or the Internet. Uniform Resource Locators (URLs) are stored in the text column.
USER_DATASTORE (page 2-14)	Documents are synthesized at index time by a user-defined stored procedure.

2.3.1 DIRECT_DATASTORE

Use the `DIRECT_DATASTORE` type for text stored directly in the text column, one document for each row. The `DIRECT_DATASTORE` type has no attributes.

The following column types are supported: `CHAR`, `VARCHAR`, `VARCHAR2`, `BLOB`, `CLOB`, `BFILE`, `XMLType`, and `URIType`.

Note:

If your column is a `BFILE`, then the index owner must have *read* permission on all directories used by the `BFILES`.

The following example creates a table with a `CLOB` column to store text data. It then populates two rows with text data and indexes the table using the system-defined preference `CTXSYS.DEFAULT_DATASTORE`.

```
create table mytable(id number primary key, docs clob);

insert into mytable values(111555,'this text will be indexed');
insert into mytable values(111556,'this is a direct_datastore example');
commit;

create index myindex on mytable(docs)
  indextype is ctxsys.context
  parameters ('DATASTORE CTXSYS.DEFAULT_DATASTORE');
```

2.3.2 MULTI_COLUMN_DATASTORE

Use the `MULTI_COLUMN_DATASTORE` datastore when your text is stored in more than one column. During indexing, the system concatenates the text columns, tags the

column text, and indexes the text as a single document. The XML-like tagging is optional. You can also set the system to filter and concatenate binary columns.

- [MULTI_COLUMN_DATASTORE Attributes](#) (page 2-4)
- [Indexing and DML](#) (page 2-4)
- [MULTI_COLUMN_DATASTORE Restriction](#) (page 2-5)
- [MULTI_COLUMN_DATASTORE Example](#) (page 2-5)
- [MULTI_COLUMN_DATASTORE Filter Example](#) (page 2-5)
- [Tagging Behavior](#) (page 2-5)
- [Indexing Columns as Sections](#) (page 2-6)

2.3.2.1 MULTI_COLUMN_DATASTORE Attributes

The data store MULTI_COLUMN_DATASTORE has the attributes shown in [Table 2-2](#) (page 2-4).

Table 2-2 MULTI_COLUMN_DATASTORE Attributes

Attribute	Attribute Value
columns	<p>Specify a comma-delimited list of columns to be concatenated during indexing. You can also specify any allowed expression for the SELECT statement column list for the base table. This includes expressions, PL/SQL functions, column aliases, and so on.</p> <p>The NUMBER and DATE column types are supported. They are converted to text before indexing using the default format mask. The TO_CHAR function can be used in the column list for formatting.</p> <p>The RAW and BLOB columns are directly concatenated as binary data.</p> <p>The LONG, LONG RAW, NCHAR, and NCLOB data types, nested table columns, and collections are not supported.</p> <p>The column list is limited to 500 bytes.</p>
filter	<p>Specify a comma-delimited list of Y/N flags. Each flag corresponds to a column in the COLUMNS list and denotes whether to filter the column using the AUTO_FILTER.</p> <p>Specify one of the following allowed values:</p> <p>Y: Column is to be filtered with AUTO_FILTER</p> <p>N or no value: Column is not to be filtered (default)</p>
delimiter	<p>Specify the delimiter that separates column text as follows:</p> <p>COLUMN_NAME_TAG: Column text is set off by XML-like open and close tags (default).</p> <p>NEWLINE: Column text is separated with a newline.</p>

2.3.2.2 Indexing and DML

To index, you must create a dummy column to specify in the CREATE INDEX statement. This column's contents are not made part of the virtual document, unless its name is specified in the columns attribute.

The index is synchronized only when the dummy column is updated. You can create triggers to propagate changes if needed.

2.3.2.3 MULTI_COLUMN_DATASTORE Restriction

You cannot create a multicolumn datastore with XMLType columns.

MULTI_COLUMN_DATA_STORE does not support XMLType. You can create a CONTEXT index with an XMLType column, as described in [Oracle Text SQL Statements and Operators](#) (page 1-1).

2.3.2.4 MULTI_COLUMN_DATASTORE Example

The following example creates a multicolumn datastore preference called `my_multi` with three text columns:

```
begin

ctx_ddl.create_preference('my_multi', 'MULTI_COLUMN_DATASTORE');
ctx_ddl.set_attribute('my_multi', 'columns', 'column1, column2, column3');

end;
```

2.3.2.5 MULTI_COLUMN_DATASTORE Filter Example

The following example creates a multicolumn datastore preference and denotes that the `bar` column is to be filtered with the `AUTO_FILTER`.

```
ctx_ddl.create_preference('MY_MULTI', 'MULTI_COLUMN_DATASTORE');
ctx_ddl.set_attribute('MY_MULTI', 'COLUMNS', 'foo,bar');
ctx_ddl.set_attribute('MY_MULTI', 'FILTER', 'N,Y');
```

The multicolumn datastore fetches the content of the `foo` and `bar` columns, filters `bar`, then composes the compound document as:

```
<FOO>
foo contents
</FOO>
<BAR>
bar filtered contents (probably originally HTML)
</BAR>
```

The `N` flags do not need not be specified, and there does not need to be a flag for every column. Only the `Y` flags must be specified, with commas to denote which column they apply to. For example:

```
ctx_ddl.create_preference('MY_MULTI', 'MULTI_COLUMN_DATASTORE');
ctx_ddl.set_attribute('MY_MULTI', 'COLUMNS', 'foo,bar,zoo,jar');
ctx_ddl.set_attribute('MY_MULTI', 'FILTER', ',,Y');
```

This example filters only the column `zoo`.

2.3.2.6 Tagging Behavior

During indexing, the system creates a virtual document for each row. The virtual document is composed of the contents of the columns concatenated in the listing order with column name tags automatically added.

For example:

```
create table mc(id number primary key, name varchar2(10), address varchar2(80));
insert into mc values(1, 'John Smith', '123 Main Street');
```

```
exec ctx_ddl.create_preference('mymds', 'MULTI_COLUMN_DATASTORE');  
exec ctx_ddl.set_attribute('mymds', 'columns', 'name, address');
```

This produces the following virtual text for indexing:

```
<NAME>  
John Smith  
</NAME>  
<ADDRESS>  
123 Main Street  
</ADDRESS>
```

2.3.2.7 Indexing Columns as Sections

To index the tags as sections, you can optionally create field sections with BASIC_SECTION_GROUP.

Note:

No section group is created when you use the MULTI_COLUMN_DATASTORE. To create sections for these tags, you must create a section group.

When you use expressions or functions, the tag is composed of the first 30 characters of the expression unless a column alias is used.

For example, if your expression is as follows:

```
exec ctx_ddl.set_attribute('mymds', 'columns', '4 + 17');
```

then it produces the following virtual text:

```
<4 + 17>  
21  
</4 + 17>
```

If your expression is as follows:

```
exec ctx_ddl.set_attribute('mymds', 'columns', '4 + 17 coll');
```

then it produces the following virtual text:

```
<coll>  
21  
<coll>
```

The tags are in uppercase unless the column name or column alias is in lowercase and surrounded by double quotation marks. For example:

```
exec ctx_ddl.set_attribute('mymds', 'COLUMNS', 'foo');
```

This produces the following virtual text:

```
<FOO>  
content of foo  
</FOO>
```

For lowercase tags, use the following:

```
exec ctx_ddl.set_attribute('mymds', 'COLUMNS', 'foo "foo"');
```

This expression produces:

```
<foo>
content of foo
</foo>
```

2.3.3 DETAIL_DATASTORE

Use the `DETAIL_DATASTORE` type for text stored directly in the database in detail tables, with the indexed text column located in the master table.

- [DETAIL_DATASTORE Attributes](#) (page 2-7)
- [Synchronizing Master/Detail Indexes](#) (page 2-7)
- [Example Master/Detail Tables](#) (page 2-7)

2.3.3.1 DETAIL_DATASTORE Attributes

The `DETAIL_DATASTORE` type has the attributes described in [Table 2-3](#) (page 2-7).

Table 2-3 *DETAIL_DATASTORE Attributes*

Attribute	Attribute Value
binary	Specify <code>TRUE</code> for Oracle Text to add <i>no</i> newline character after each detail row. Specify <code>FALSE</code> for Oracle Text to add a newline character (<code>\n</code>) after each detail row automatically.
detail_table	Specify the name of the detail table (<code>OWNER . TABLE</code> if necessary).
detail_key	Specify the name of the detail table foreign key column.
detail_lineno	Specify the name of the detail table sequence column.
detail_text	Specify the name of the detail table text column.

2.3.3.2 Synchronizing Master/Detail Indexes

Changes to the detail table do not trigger re-indexing when you synchronize the index. Only changes to the indexed column in the master table triggers a re-index when you synchronize the index.

You can create triggers on the detail table to propagate changes to the indexed column in the master table row.

2.3.3.3 Example Master/Detail Tables

This example illustrates how master and detail tables are related to each other.

- [Master Table Example](#) (page 2-8)
- [Detail Table Example](#) (page 2-8)
- [Detail Table Example Attributes](#) (page 2-8)
- [Master/Detail Index Example](#) (page 2-9)

2.3.3.3.1 Master Table Example

Master tables define the documents in a master/detail relationship. Assign an identifying number to each document. The following table is an example master table, called `my_master`:

Column Name	Column Type	Description
<code>article_id</code>	NUMBER	Document ID, unique for each document (primary key)
<code>author</code>	VARCHAR2(30)	Author of document
<code>title</code>	VARCHAR2(50)	Title of document
<code>body</code>	CHAR(1)	Dummy column to specify in CREATE INDEX

Note:

Your master table must include a primary key column when you use the `DETAIL_DATASTORE` type.

2.3.3.3.2 Detail Table Example

Detail tables contain the text for a document, whose content is usually stored across a number of rows. The following detail table `my_detail` is related to the master table `my_master` with the `article_id` column. This column identifies the master document to which each detail row (sub-document) belongs.

Column Name	Column Type	Description
<code>article_id</code>	NUMBER	Document ID that relates to master table
<code>seq</code>	NUMBER	Sequence of document in the master document defined by <code>article_id</code>
<code>text</code>	VARCHAR2	Document text

2.3.3.3.3 Detail Table Example Attributes

In this example, the `DETAIL_DATASTORE` attributes have the following values:

Attribute	Attribute Value
<code>binary</code>	TRUE
<code>detail_table</code>	<code>my_detail</code>
<code>detail_key</code>	<code>article_id</code>
<code>detail_lineno</code>	<code>seq</code>
<code>detail_text</code>	<code>text</code>

Use CTX_DDL.[CREATE_PREFERENCE](#) (page 8-31) to create a preference with `DETAIL_DATASTORE`. Use CTX_DDL.[SET_ATTRIBUTE](#) (page 8-64) to set the attributes for this preference as described earlier. The following example shows how this is done:

```
begin

ctx_ddl.create_preference('my_detail_pref', 'DETAIL_DATASTORE');
ctx_ddl.set_attribute('my_detail_pref', 'binary', 'true');
ctx_ddl.set_attribute('my_detail_pref', 'detail_table', 'my_detail');
ctx_ddl.set_attribute('my_detail_pref', 'detail_key', 'article_id');
ctx_ddl.set_attribute('my_detail_pref', 'detail_lineno', 'seq');
ctx_ddl.set_attribute('my_detail_pref', 'detail_text', 'text');

end;
```

2.3.3.3.4 Master/Detail Index Example

To index the document defined in this master/detail relationship, specify a column in the master table using the `CREATE INDEX` statement. The column you specify must be one of the allowed types.

This example uses the `body` column, whose function is to enable the creation of the master/detail index and to improve readability of the code. The `my_detail_pref` preference is set to `DETAIL_DATASTORE` with the required attributes:

```
CREATE INDEX myindex on my_master(body) indextype is ctxsys.context
parameters('datastore my_detail_pref');
```

In this example, you can also specify the `title` or `author` column to create the index. However, if you do so, changes to these columns will trigger a re-index operation.

2.3.4 FILE_DATASTORE

The `FILE_DATASTORE` type is used for text stored in files accessed through the local file system.

- [FILE_DATASTORE Attributes](#) (page 2-9)
- [FILE_DATASTORE and Security](#) (page 2-10)
- [FILE_DATASTORE Example](#) (page 2-11)

Note:

- The `FILE_DATASTORE` type may not work with certain types of remote-mounted file systems.
 - The character set of the file datastore is assumed to be the character set of the database.
-

2.3.4.1 FILE_DATASTORE Attributes

The `FILE_DATASTORE` type has the attributes described [Table 2-4](#) (page 2-10).

Table 2-4 FILE_DATASTORE Attributes

Attribute	Attribute Value
<code>path</code>	<i>path1:path2:pathn</i>
<code>filename_charset</code>	<i>name</i>

path

Specifies the full directory path name of the files stored externally in a file system. When you specify the full directory path as such, you need to include only file names in your text column.

You can specify multiple paths for the `path` attribute, with each path separated by a colon (:) on UNIX and semicolon(;) on Windows. File names are stored in the text column in the text table.

If you do not specify a path for external files with this attribute, then Oracle Text requires that the path be included in the file names stored in the text column.

The `PATH` attribute has the following limitations:

- If you specify a `PATH` attribute, then you can only use a simple file name in the indexed column. You cannot combine the `PATH` attribute with a path as part of the file name. If the files exist in multiple folders or directories, you must leave the `PATH` attribute unset, and include the full file name, with `PATH`, in the indexed column.
- On Windows systems, the files must be located on a local drive. They cannot be on a remote drive, whether the remote drive is mapped to a local drive letter.

filename_charset

Specifies a valid Oracle character set name (maximum length 30 characters) to be used by the file datastore for converting file names. In general, the Oracle database can use a different character set than the operating system. This can lead to problems in finding files (which may raise DRG-11513 errors) when the indexed column contains characters that are not convertible to the operating system character set. By default, the file datastore will convert the file name to WE8ISO8859p1 for ASCII platforms or WE8EBCDIC1047 for EBCDIC platforms.

However, this may not be sufficient for applications with multibyte character sets for both the database and the operating system, because neither WE8ISO8859p1 nor WE8EBCDIC1047 supports multibyte characters. The attribute `filename_charset` rectifies this problem. If specified, then the datastore will convert from the database character set to the specified character set rather than to ISO8859 or EBCDIC.

If the `filename_charset` attribute is the same as the database character set, then the file name is used as is. If `filename_charset` is not a valid character set, then the error "DRG-10763: value %s is not a valid character set" is raised.

2.3.4.2 FILE_DATASTORE and Security

File and URL datastores enable access to files on the actual database disk. This may be undesirable when security is an issue since any user can browse the file system that is accessible to the Oracle user. The `FILE_ACCESS_ROLE` system parameter can be used to set the name of a database role that is authorized to create an index using `FILE` or `URL` datastores. If set, any user attempting to create an index using `FILE` or `URL`

datastores must have this role, or the index creation will fail. Only SYS can set FILE_ACCESS_ROLE, and an error will be raised if any other user tries to modify it. If FILE_ACCESS_ROLE is left at the default of NULL, access is disallowed. Thus, by default, users are not able to create indexes that use the file or URL datastores. Users can, if desired, set FILE_ACCESS_ROLE to PUBLIC if they want to preserve the behavior from earlier releases.

For example, the following statement sets the name of the database role:

```
ctx_adm.set_parameter('FILE_ACCESS_ROLE', 'TOPCAT');
```

where TOPCAT is the role that is authorized to create an index on a file or URL datastore. The CREATE INDEX operation will fail when a user that does not have an authorized role tries to create an index on a file or URL datastore. For example:

```
CREATE INDEX myindex ON mydocument(TEXT) INDEXTYPE IS ctxsys.context
PARAMETERS('DATASTORE ctxsys.file_datastore')
```

In this case, if the user does not have the role TOPCAT, then index creation will fail and return an error. For users who have the TOPCAT role, the index creation will proceed normally.

The authorized role name is checked any time the datastore is accessed. This includes index creation, index sync, and calls to document services, such as CTX_DOC.HIGHLIGHT.

2.3.4.3 FILE_DATASTORE Example

This example creates a file datastore preference called COMMON_DIR that has a path of /mydocs:

```
begin
  ctx_ddl.create_preference('COMMON_DIR', 'FILE_DATASTORE');
  ctx_ddl.set_attribute('COMMON_DIR', 'PATH', '/mydocs');
end;
```

When you populate the table mytable, you need only insert file names. The path attribute tells the system where to look during the indexing operation.

```
create table mytable(id number primary key, docs varchar2(2000));
insert into mytable values(111555,'first.txt');
insert into mytable values(111556,'second.txt');
commit;
```

Create the index as follows:

```
create index myindex on mytable(docs)
  indextype is ctxsys.context
  parameters ('datastore COMMON_DIR');
```

2.3.5 URL_DATASTORE

Use the URL_DATASTORE type for text stored:

- In files on the World Wide Web (accessed through HTTP or FTP)
- In files in the local file system (accessed through the file protocol)

Store each URL in a single text field.

- [URL_DATASTORE URL Syntax](#) (page 2-12)

- [URL_DATASTORE Attributes](#) (page 2-12)
- [URL_DATASTORE and Security](#) (page 2-13)
- [URL_DATASTORE Example](#) (page 2-13)

2.3.5.1 URL_DATASTORE URL Syntax

The syntax of a URL you store in a text field is as follows (with brackets indicating optional parameters):

```
[URL:]<access_scheme>://<host_name>[:<port_number>]/[<url_path>]
```

The `access_scheme` string can be either *ftp*, *http*, or *file*. For example:

```
http://mycomputer.us.example.com/home.html
```

Note:

The `login:password@` syntax within the URL is supported only for the *ftp* access scheme.

Because this syntax is partially compliant with the RFC 1738 specification, the following restriction holds for the URL syntax: The URL must contain only printable ASCII characters. Non-printable ASCII characters and multibyte characters must be escaped with the `%xx` notation, where *xx* is the hexadecimal representation of the special character.

2.3.5.2 URL_DATASTORE Attributes

URL_DATASTORE has the following attributes:

Table 2-5 URL_DATASTORE Attributes

Attribute	Attribute Value
<code>timeout</code>	The value of this attribute is ignored. This is provided for backward compatibility.
<code>maxthreads</code>	The value of this attribute is ignored. URL_DATASTORE is single-threaded. This is provided for backward compatibility.
<code>urlsize</code>	The value of this attribute is ignored. This is provided for backward compatibility.
<code>maxurls</code>	The value of this attribute is ignored. This is provided for backward compatibility.
<code>maxdocsize</code>	The value of this attribute is ignored. This is provided for backward compatibility.
<code>http_proxy</code>	Specify the host name of http proxy server. Optionally specify port number with a colon in the form <code>hostname:port</code> .
<code>ftp_proxy</code>	Specify the host name of ftp proxy server. Optionally specify port number with a colon in the form <code>hostname:port</code> .
<code>no_proxy</code>	Specify the domain for no proxy server. Use a comma-delimited string of up to 16 domain names.

timeout

The value of this attribute is ignored. This is provided for backward compatibility.

maxthreads

The value of this attribute is ignored. URL_DATASTORE is single-threaded. This is provided for backward compatibility.

urlsize

The value of this attribute is ignored. This is provided for backward compatibility.

maxdocsize

The value of this attribute is ignored. This is provided for backward compatibility.

maxurls

The value of this attribute is ignored. This is provided for backward compatibility.

http_proxy

Specify the fully qualified name of the host computer that serves as the HTTP proxy (gateway) for the computer on which Oracle Text is installed. You can optionally specify port number with a colon in the form `hostname:port`.

You must set this attribute if the computer is in an intranet that requires authentication through a proxy server to access Web files located outside the firewall.

ftp_proxy

Specify the fully qualified name of the host computer that serves as the FTP proxy (gateway) for the server on which Oracle Text is installed. You can optionally specify a port number with a colon in the form `hostname:port`.

This attribute must be set if the computer is in an intranet that requires authentication through a proxy server to access Web files located outside the firewall.

no_proxy

Specify a string of domains (up to sixteen, separated by commas) that are found in most, if not all, of the computers in your intranet. When one of the domains is encountered in a host name, no request is sent to the server(s) specified for `ftp_proxy` and `http_proxy`. Instead, the request is processed directly by the host computer identified in the URL.

For example, if the string `us.example.com, uk.example.com` is entered for `no_proxy`, any URL requests to computers that contain either of these domains in their host names are not processed by your proxy server(s).

2.3.5.3 URL_DATASTORE and Security

For a discussion of how to control file access security for file and URL datastores, refer to "[FILE_DATASTORE and Security](#) (page 2-10)".

2.3.5.4 URL_DATASTORE Example

This example creates a URL_DATASTORE preference called URL_PREF for which the `http_proxy`, `no_proxy`, and `timeout` attributes are set. The defaults are used for the attributes that are not set.

```
begin
ctx_ddl.create_preference('URL_PREF','URL_DATASTORE');
ctx_ddl.set_attribute('URL_PREF','HTTP_PROXY','www-proxy.us.example.com');
ctx_ddl.set_attribute('URL_PREF','NO_PROXY','us.example.com');
```

```
ctx_ddl.set_attribute('URL_PREF','Timeout','300');
end;
```

Create the table and insert values into it:

```
create table urls(id number primary key, docs varchar2(2000));
insert into urls values(111555,'http://context.us.example.com');
insert into urls values(111556,'http://www.sun.com');
commit;
```

To create the index, specify URL_PREF as the datastore:

```
create index datastores_text on urls ( docs )
  indextype is ctxsys.context
  parameters ( 'Datastore URL_PREF' );
```

2.3.6 USER_DATASTORE

Use the USER_DATASTORE type to define stored procedures that synthesize documents during indexing. For example, a user procedure might synthesize author, date, and text columns into one document to have the author and date information be part of the indexed text.

- [USER_DATASTORE Attributes](#) (page 2-14)
- [USER_DATASTORE Constraints](#) (page 2-15)
- [USER_DATASTORE Editing Procedure after Indexing](#) (page 2-15)
- [USER_DATASTORE with CLOB Example](#) (page 2-15)
- [USER_DATASTORE with BLOB_LOC Example](#) (page 2-16)

2.3.6.1 USER_DATASTORE Attributes

USER_DATASTORE has the following attributes:

Table 2-6 USER_DATASTORE Attributes

Attribute	Attribute Value
procedure	Specify the procedure that synthesizes the document to be indexed. This procedure can be owned by any user and must be executable by the index owner.
output_type	<p>Specify the data type of the second argument to <code>procedure</code>. Valid values are CLOB, BLOB, CLOB_LOC, BLOB_LOC, or VARCHAR2. The default is CLOB.</p> <p>When you specify CLOB_LOC, BLOB_LOC, you indicate that no temporary CLOB or BLOB is needed, because your procedure copies a locator to the IN/OUT second parameter.</p>

procedure

Specify the name of the procedure that synthesizes the document to be indexed. This specification must be in the form PROCEDURENAME or PACKAGENAME . PROCEDURENAME. You can also specify the schema owner name.

The procedure you specify must have two arguments defined as follows:

```
procedure (r IN ROWID, c IN OUT NOCOPY output_type)
```

The first argument `r` must be of type `ROWID`. The second argument `c` must be of type `output_type`. `NOCOPY` is a compiler hint that instructs Oracle Text to pass parameter `c` by reference if possible.

Note:

The procedure name and its arguments can be named anything. The arguments `r` and `c` are used in this example for simplicity.

The stored procedure is called once for each row indexed. Given the rowid of the current row, `procedure` must write the text of the document into its second argument, whose type you specify with `output_type`.

2.3.6.2 USER_DATASTORE Constraints

The following constraints apply to `procedure`:

- It can be owned by any user, but the user must have database permissions to execute `procedure` correctly
- It must be executable by the index owner
- It must not enter DDL or transaction control statements, like `COMMIT`

2.3.6.3 USER_DATASTORE Editing Procedure after Indexing

When you change or edit the stored procedure, indexes based on it will not be notified, so you must manually re-create such indexes. So if the stored procedure makes use of other columns, and those column values change, the row will not be re-indexed. The row is re-indexed only when the indexed column changes.

output_type

Specify the datatype of the second argument to `procedure`. You can use either `CLOB`, `BLOB`, `CLOB_LOC`, `BLOB_LOC`, or `VARCHAR2`.

2.3.6.4 USER_DATASTORE with CLOB Example

Consider a table in which the author, title, and text fields are separate, as in the `articles` table defined as follows:

```
create table articles(
  id      number,
  author  varchar2(80),
  title   varchar2(120),
  text    clob );
```

The author and title fields are to be part of the indexed document text. Assume user `appowner` writes a stored procedure with the user datastore interface that synthesizes a document from the text, author, and title fields:

```
create procedure myproc(rid in rowid, tlob in out clob nocopy) is
begin
  for c1 in (select author, title, text from articles
             where rowid = rid)
  loop
```

```
dbms_lob.writeappend(tlob, length(c1.title), c1.title);
dbms_lob.writeappend(tlob, length(c1.author), c1.author);
dbms_lob.writeappend(tlob, length(c1.text), c1.text);

    end loop;
end;
```

This procedure takes in a rowid and a temporary CLOB locator, and concatenates all the article's columns into the temporary CLOB. The for loop executes only once.

The user appowner creates the preference as follows:

```
begin

ctx_ddl.create_preference('myud', 'user_datastore');
ctx_ddl.set_attribute('myud', 'procedure', 'myproc');
ctx_ddl.set_attribute('myud', 'output_type', 'CLOB');

end;
```

When appowner creates the index on `articles(text)` using this preference, the indexing operation sees author and title in the document text.

2.3.6.5 USER_DATASTORE with BLOB_LOC Example

The following procedure might be used with `OUTPUT_TYPE BLOB_LOC`:

```
procedure myds(rid in rowid, dataout in out nocopy blob)
is
    l_dtype varchar2(10);
    l_pk     number;
begin
    select dtype, pk into l_dtype, l_pk from mytable where rowid = rid;
    if (l_dtype = 'MOVIE') then
        select movie_data into dataout from movietab where fk = l_pk;
    elsif (l_dtype = 'SOUND') then
        select sound_data into dataout from soundtab where fk = l_pk;
    end if;
end;
```

The user appowner creates the preference as follows:

```
begin

ctx_ddl.create_preference('myud', 'user_datastore');
ctx_ddl.set_attribute('myud', 'procedure', 'myproc');
ctx_ddl.set_attribute('myud', 'output_type', 'blob_loc');

end;
```

2.3.7 NESTED_DATASTORE

Use the nested datastore type to index documents stored as rows in a nested table.

- [NESTED_DATASTORE Attributes](#) (page 2-16)
- [NESTED_DATASTORE Example](#) (page 2-17)

2.3.7.1 NESTED_DATASTORE Attributes

NESTED_DATASTORE has the following attributes:

Table 2-7 NESTED_DATASTORE Attributes

Attribute	Attribute Value
nested_column	Specify the name of the nested table column. This attribute is required. Specify only the column name. Do not specify schema owner or containing table name.
nested_type	Specify the type of nested table. This attribute is required. You must provide owner name and type.
nested_lineno	Specify the name of the attribute in the nested table that orders the lines. This is like <code>DETAIL_LINENO</code> in detail datastore. This attribute is required.
nested_text	Specify the name of the column in the nested table type that contains the text of the line. This is like <code>DETAIL_TEXT</code> in detail datastore. This attribute is required. LONG column types are not supported as nested table text columns.
binary	Specify FALSE for Oracle Text to automatically insert a newline character when synthesizing the document text. If you specify TRUE, Oracle Text does not do this. This attribute is not required. The default is FALSE.

When using the nested table datastore, you must index a dummy column, because the extensible indexing framework disallows indexing the nested table column. See ["NESTED_DATASTORE Example \(page 2-17\)"](#).

DML on the nested table is not automatically propagated to the dummy column used for indexing. For DML on the nested table to be propagated to the dummy column, your application code or trigger must explicitly update the dummy column.

Filter defaults for the index are based on the type of the `nested_text` column.

During validation, Oracle Text checks that the type exists and that the attributes you specify for `nested_lineno` and `nested_text` exist in the nested table type. Oracle Text does not check that the named nested table column exists in the indexed table.

2.3.7.2 NESTED_DATASTORE Example

This section shows an example of using the `NESTED_DATASTORE` type to index documents stored as rows in a nested table.

- [Create the Nested Table \(page 2-17\)](#)
- [Insert Values into Nested Table \(page 2-18\)](#)
- [Create Nested Table Preferences \(page 2-18\)](#)
- [Create Index on Nested Table \(page 2-18\)](#)
- [Query Nested Datastore \(page 2-18\)](#)

2.3.7.2.1 Create the Nested Table

The following code creates a nested table and a storage table `mytab` for the nested table:

```
create type nt_rec as object (
  lno number, -- line number
```

```
    ltxt varchar2(80) -- text of line
  );

create type nt_tab as table of nt_rec;
create table mytab (
  id number primary key, -- primary key
  dummy char(1), -- dummy column for indexing
  doc nt_tab -- nested table
)
nested table doc store as myntab;
```

2.3.7.2.2 Insert Values into Nested Table

The following code inserts values into the nested table for the parent row with ID equal to 1.

```
insert into mytab values (1, null, nt_tab());
insert into table(select doc from mytab where id=1) values (1, 'the dog');
insert into table(select doc from mytab where id=1) values (2, 'sat on mat ');
commit;
```

2.3.7.2.3 Create Nested Table Preferences

The following code sets the preferences and attributes for the NESTED_DATASTORE according to the definitions of the nested table type `nt_tab` and the parent table `mytab`:

```
begin
-- create nested datastore pref
ctx_ddl.create_preference('ntds','nested_datastore');

-- nest tab column in main table
ctx_ddl.set_attribute('ntds','nested_column', 'doc');

-- nested table type
ctx_ddl.set_attribute('ntds','nested_type', 'scott.nt_tab');

-- lineno column in nested table
ctx_ddl.set_attribute('ntds','nested_lineno','lno');

--text column in nested table
ctx_ddl.set_attribute('ntds','nested_text', 'ltxt');
end;
```

2.3.7.2.4 Create Index on Nested Table

The following code creates the index using the nested table datastore:

```
create index myidx on mytab(dummy) -- index dummy column, not nest table
indextype is ctxsys.context parameters ('datastore ntds');
```

2.3.7.2.5 Query Nested Datastore

The following select statement queries the index built from a nested table:

```
select * from mytab where contains(dummy, 'dog and mat')>0;
-- returns document 1, because it has dog in line 1 and mat in line 2.
```

2.4 Filter Types

Use the filter types to create preferences that determine how text is filtered for indexing. Filters enable word processor documents, formatted documents, plain text, HTML, and XML documents to be indexed.

For formatted documents, Oracle Text stores documents in their native format and uses filters to build interim plain text or HTML versions of the documents. Oracle Text indexes the words derived from the plain text or HTML version of the formatted document. The TMP_DIR environment variable sets the directory path for storing temporary files created by the filter.

To create a filter preference, you must use one of the filter types shown in [Table 2-8](#) (page 2-19).

Table 2-8 Filter Types

Filter	When Used
AUTO_FILTER (page 2-19)	Auto filter for filtering formatted documents.
NULL_FILTER (page 2-22)	No filtering required. Use for indexing plain text, HTML, or XML documents.
MAIL_FILTER (page 2-22)	Use the MAIL_FILTER to transform RFC-822, RFC-2045 messages in to text that can be indexed.
USER_FILTER (page 2-26)	User-defined external filter to be used for custom filtering.
PROCEDURE_FILTER (page 2-29)	User-defined stored procedure filter to be used for custom filtering.

2.4.1 AUTO_FILTER

The AUTO_FILTER is a universal filter that filters most document formats, including PDF and Microsoft Word documents. Use it for indexing both single-format and mixed-format columns. This filter automatically bypasses plain text, HTML, XHTML, SGML, and XML documents.

- [AUTO_FILTER Attributes](#) (page 2-20)
- [AUTO_FILTER and Indexing Formatted Documents](#) (page 2-20)
- [AUTO_FILTER and Explicitly Bypassing Plain Text or HTML in Mixed Format Columns](#) (page 2-21)
- [AUTO_FILTER and Character Set Conversion With AUTO_FILTER](#) (page 2-22)

See Also:

[Oracle Text Supported Document Formats](#) (page B-1), for a list of the formats supported by AUTO_FILTER, and to learn more about how to set up your environment

Note:

The `AUTO_FILTER` replaces the `INSO_FILTER`, which has been deprecated. While every effort has been made to ensure maximal backward compatibility between the two filters, so that applications using `INSO_FILTER` will continue to work without modification, some differences may arise. Users should therefore use `AUTO_FILTER` in their new programs and, when possible, replace instances of `INSO_FILTER`, and any system preferences or constants that make use of it, in older applications.

2.4.1.1 AUTO_FILTER Attributes

The `AUTO_FILTER` preference has the attributes shown in [Table 2-9](#) (page 2-20).

Table 2-9 AUTO_FILTER Attributes

Attribute	Attribute Value
<code>timeout</code>	<p>Specify the <code>AUTO_FILTER</code> timeout in seconds. Use a number between 0 and 42,949,672. Default is 120. Setting this value to 0 disables the feature.</p> <p>How this wait period is used depends on how you set <code>timeout_type</code>.</p> <p>This feature is disabled for rows for which the corresponding charset and format column cause the <code>AUTO_FILTER</code> to bypass the row, such as when format is marked <code>TEXT</code>.</p> <p>Use this feature to prevent the Oracle Text indexing operation from waiting indefinitely on a hanging filter operation.</p>
<code>timeout_type</code>	<p>Specify either <code>HEURISTIC</code> or <code>FIXED</code>. Default is <code>HEURISTIC</code>.</p> <p>Specify <code>HEURISTIC</code> for Oracle Text to check every <code>TIMEOUT</code> seconds if output from Outside In HTML Export has increased. The operation terminates for the document if output has not increased. An error is recorded in the <code>CTX_USER_INDEX_ERRORS</code> view and Oracle Text moves to the next document row to be indexed.</p> <p>Specify <code>FIXED</code> to terminate the Outside In HTML Export processing after <code>TIMEOUT</code> seconds regardless of whether filtering was progressing normally or just hanging. This value is useful when indexing throughput is more important than taking the time to successfully filter large documents.</p>
<code>output_formatting</code>	<p>Setting this attribute has no effect on filter performance or filter output. It is maintained for backward compatibility.</p>

2.4.1.2 AUTO_FILTER and Indexing Formatted Documents

To index a text column containing formatted documents such as Microsoft Word, use the `AUTO_FILTER`. This filter automatically detects the document format. Use the `CTXSYS.AUTO_FILTER` system-defined preference in the parameter clause as follows:

```
create index hdocsx on hdocs(text) indextype is ctxsys.context
  parameters ('datastore ctxsys.file_datastore
    filter ctxsys.auto_filter');
```

Note:

The CTXSYS.AUTO_FILTER replaces CTXSYS.INSO_FILTER, which has been deprecated. Programs making use of CTXSYS.INSO_FILTER should still work. New programs should use CTXSYS.AUTO_FILTER.

2.4.1.3 AUTO_FILTER and Explicitly Bypassing Plain Text or HTML in Mixed Format Columns

A mixed-format column is a text column containing more than one document format, such as a column that contains Microsoft Word, PDF, plain text, and HTML documents.

The AUTO_FILTER can index mixed-format columns, automatically bypassing plain text, HTML, and XML documents. However, if you prefer not to depend on the built-in bypass mechanism, you can explicitly tag your rows as text and cause the AUTO_FILTER to ignore the row and not process the document in any way.

The format column in the base table enables you to specify the type of document contained in the text column. You can specify the following document types: TEXT, BINARY, and IGNORE. During indexing, the AUTO_FILTER ignores any document typed TEXT, assuming the charset column is not specified. The difference between a document with a TEXT format column type and one with an IGNORE type is that the TEXT document is indexed, but ignored by the filter, while the IGNORE document is not indexed at all. Use IGNORE to overlook documents such as image files, or documents in a language that you do not want to index. IGNORE can be used with any filter type.

To set up the AUTO_FILTER bypass mechanism, you must create a format column in your base table.

For example:

```
create table hdocs (
    id number primary key,
    fmt varchar2(10),
    text varchar2(80)
);
```

Assuming you are indexing mostly Word documents, you specify BINARY in the format column to filter the Word documents. Alternatively, to have the AUTO_FILTER ignore an HTML document, specify TEXT in the format column.

For example, the following statements add two documents to the text table, assigning one format as BINARY and the other TEXT:

```
insert into hdocs values(1, 'binary', '/docs/myword.doc');
insert in hdocs values (2, 'text', '/docs/index.html');
commit;
```

To create the index, use CREATE INDEX and specify the format column name in the parameter string:

```
create index hdocsx on hdocs(text) indextype is ctxsys.context
parameters ('datastore ctxsys.file_datastore
filter ctxsys.auto_filter
format column fmt');
```

If you do not specify TEXT or BINARY for the format column, BINARY is used.

Note:

You need not specify the format column in CREATE INDEX when using the AUTO_FILTER.

2.4.1.4 AUTO_FILTER and Character Set Conversion With AUTO_FILTER

The AUTO_FILTER converts documents to the database character set when the document format column is set to TEXT. In this case, the AUTO_FILTER looks at the charset column to determine the document character set.

If the charset column value is not an Oracle Text character set name, the document is passed through without any character set conversion.

Note:

You need not specify the charset column when using the AUTO_FILTER.

2.4.2 NULL_FILTER

Use the NULL_FILTER type when plain text or HTML is to be indexed and no filtering needs to be performed. NULL_FILTER has no attributes.

NULL_FILTER and Indexing HTML Documents

If your document set is entirely HTML, Oracle recommends that you use the NULL_FILTER in your filter preference.

For example, to index an HTML document set, specify the system-defined preferences for NULL_FILTER and HTML_SECTION_GROUP as follows:

```
create index myindex on docs(htmlfile) indextype is ctxsys.context
  parameters('filter ctxsys.null_filter
    section_group ctxsys.html_section_group');
```

See Also:

For more information on section groups and indexing HTML documents, see "[Section Group Types](#) (page 2-86)".

2.4.3 MAIL_FILTER

Use MAIL_FILTER to transform RFC-822, RFC-2045 messages into indexable text. The following limitations apply to the input:

- Documents must be US-ASCII
- Lines must not be longer than 1024 bytes
- Documents must be syntactically valid with regard to RFC-822.

Behavior for invalid input is not defined. Some deviations may be robustly handled by the filter without error. Others may result in a fetch-time or filter-time error.

- [MAIL_FILTER Attributes](#) (page 2-23)

- [MAIL_FILTER Behavior](#) (page 2-23)
- [About the Mail Filter Configuration File](#) (page 2-24)
- [Mail_Filter Example](#) (page 2-25)

2.4.3.1 MAIL_FILTER Attributes

The MAIL_FILTER has the attributes shown in [Table 2-10](#) (page 2-23).

Table 2-10 MAIL_FILTER Attributes

Attribute	Attribute Value
INDEX_FIELDS	<p>Specify a colon-separated list of fields to preserve in the output. These fields are transformed to tag markup. For example, if INDEX_FIELDS is set to "FROM":</p> <p>From: Scott Tiger</p> <p>becomes:</p> <p><FROM>Scott Tiger</FROM></p> <p>Only top-level fields are transformed in this way.</p>
AUTO_FILTER_TIMEOUT	<p>Specify a timeout value for the AUTO_FILTER filtering invoked by the mail filter. Default is 60. (Replaces the INSO_TIMEOUT attribute and is backward compatible with INSO_TIMEOUT.)</p>
AUTO_FILTER_OUTPUT_FORMATTING	<p>Specify either TRUE or FALSE. Default is TRUE.</p> <p>This attribute replaces the previous INSO_OUTPUT_FORMATTING attribute. However, it has no effect in the current release.</p>
PART_FIELD_STYLE	<p>Specify how fields occurring in lower-level parts and identified by the INDEX_FIELDS attribute should be transformed. The fields of the top-level message part identified by INDEX_FIELDS are always transformed to tag markup (see the previous description of INDEX_FIELDS); PART_FIELD_STYLE controls the transformation of subsequent parts; for example, attached e-mails.</p> <p>Possible values include IGNORE (the default), in which the part fields are not included for indexing; TAG, in which the part field names are transformed to tags, as occurs with top-level part fields; FIELD, in which the part field names are preserved as fields, not as tags; and TEXT, in which the part field names are eliminated and only the field content is preserved for indexing. See "Mail_Filter Example (page 2-25)" for an example of how PART_FIELD_STYLE works.</p>

2.4.3.2 MAIL_FILTER Behavior

This filter behaves in the following way for each document:

- Read and remove header fields
- Decode message body if needed, depending on Content-transfer-encoding field

- Take action depending on the Content-Type field value and the user-specified behavior specified in a mail filter configuration file. (See "[About the Mail Filter Configuration File](#) (page 2-24)".) The possible actions are:
 - produce the body in the output text (INCLUDE). If no character set is encountered in the INCLUDE parts in the Content-Type header field, then Oracle defaults to the value specified in the character set column in the base table. Name your populated character set column in the parameter string of the CREATE INDEX command.
 - AUTO_FILTER the body contents (AUTO_FILTER directive).
 - remove the body contents from the output text (IGNORE)
- If no behavior is specified for the type in the configuration file, then the defaults are as follows:
 - text/*: produce body in the output text
 - application/*: AUTO_FILTER the body contents
 - image/*, audio/*, video/*, model/*: ignore
- Multipart messages are parsed, and the mail filter applied recursively to each part. Each part is appended to the output.
- All text produced will be charset-converted to the database character set, if needed.

2.4.3.3 About the Mail Filter Configuration File

The MAIL_FILTER filter makes use of a mail filter configuration file, which contains directives specifying how a mail document should be filtered. The mail filter configuration file is an editable text file. Here you can override default behavior for each Content-Type. The configuration file also contains IANA-to-Oracle Globalization Support character set name mappings.

The location of the file must be in ORACLE_HOME/ctx/config. The name of the file to use is stored in the new system parameter MAIL_FILTER_CONFIG_FILE. On install, this is set to drmailfl.txt, which has useful default contents.

Oracle recommends that you create your own mail filter configuration files to avoid overwrite by the installation of a new version or patch set. The mail filter configuration file should be in the database character set.

Mail File Configuration File Structure

The file has two sections, BEHAVIOR and CHARSETS. Indicate the start of the behavior section as follows:

```
[behavior]
```

Each line following starts with a mime type, then whitespace, then behavior specification. The MIME type can be a full TYPE/SUBTYPE or just TYPE, which will apply to all subtypes of that type. TYPE/SUBTYPE specification overrides TYPE specification, which overrides default behavior. Behavior can be INCLUDE, AUTO_FILTER, or IGNORE (see "[MAIL_FILTER Behavior](#) (page 2-23)" for definitions). For instance:


```
application/zip      IGNORE
application/msword   AUTO_FILTER
model                IGNORE
```

You cannot specify behavior for "multipart" or "message" types. If you do, such lines are ignored. Duplicate specification for a type replaces earlier specifications.

Comments can be included in the mail configuration file by starting lines with the # symbol.

The charset mapping section begins with

```
[charsets]
```

Lines consist of an IANA name, then whitespace, then an Oracle Globalization Support charset name, like:

```
US-ASCII      US7ASCII
ISO-8859-1    WE8ISO8859P1
```

This file is the only way the mail filter gets the mappings. There are no defaults.

When you change the configuration file, the changes affect only the documents indexed after that point. You must flush the shared pool after changing the file.

2.4.3.4 Mail_Filter Example

Suppose there is an e-mail with the following form, in which other e-mails with different subject lines are attached to this e-mail:

```
To: somebody@someplace
Subject: mainheader
Content-Type: multipart/mixed
. . .
Content-Type: text/plain
X-Ref: some_value
Subject: subheader 1
. . .
Content-Type: text/plain
X-Control: blah blah blah
Subject: subheader 2
. . .
```

Set INDEX_FIELDS to be "Subject" and, initially, PART_FIELD_STYLE to IGNORE.

```
CTX_DDL.CREATE_PREFERENCE('my_mail_filt', 'mail_filter');
CTX_DDL.SET_ATTRIBUTE(my_mail_filt, 'INDEX_FILES', 'subject');
CTX_DDL.SET_ATTRIBUTE ('my_mail_filt', 'PART_FIELD_STYLE', 'ignore');
```

Now when the index is created, the file will be indexed as follows:

```
<SUBJECT>mainheader</SUBJECT>
```

If PART_FIELD_STYLE is instead set to TAG, this becomes:

```
<SUBJECT>mainheader</SUBJECT>
<SUBJECT>subheader1</SUBJECT>
<SUBJECT>subheader2</SUBJECT>
```

If PART_FIELD_STYLE is set to FIELD instead, this is the result:

```
<SUBJECT>mainheader<SUBJECT>
SUBJECT:subheader1
SUBJECT:subheader2
```

Finally, if `PART_FIELD_STYLE` is instead set to `TEXT`, then the result is:

```
<SUBJECT>mainheader</SUBJECT>
subheader1
subheader2
```

2.4.4 USER_FILTER

Use the `USER_FILTER` type to specify an external filter for filtering documents in a column.

This section contains the following topics.

- [USER_FILTER Attributes](#) (page 2-26)
- [Using USER_FILTER with Charset and Format Columns](#) (page 2-27)
- [USER_FILTER and Explicitly Bypassing Plain Text or HTML in Mixed Format Columns](#) (page 2-27)
- [Character Set Conversion with USER_FILTER](#) (page 2-28)
- [User Filter Example](#) (page 2-28)

2.4.4.1 USER_FILTER Attributes

`USER_FILTER` has the following attribute:

Table 2-11 *USER_FILTER Attribute*

Attribute	Attribute Value
command	Specify the name of the filter executable.

WARNING:

The `USER_FILTER` type introduces the potential for security threats. A database user granted the `CTXAPP` role could potentially use `USER_FILTER` to load a malicious application. Therefore, the DBA must safeguard against any combination of input and output file parameters that would enable the named filter executable to compromise system security.

command

Specify the executable for the single external filter that is used to filter all text stored in a column. If more than one document format is stored in the column, then the external filter specified for `command` must recognize and handle all such formats.

The executable that you specify must exist in the `$ORACLE_HOME/ctx/bin` directory on UNIX, and in the `%ORACLE_HOME%/ctx/bin` directory on Windows.

You must create your user-filter command with two parameters:

- The first parameter is the name of the input file to be read.

- The second parameter is the name of the output file to be written to.

If all the document formats are supported by `AUTO_FILTER`, then use `AUTO_FILTER` instead of `USER_FILTER`, unless additional tasks besides filtering are required for the documents.

2.4.4.2 Using `USER_FILTER` with Charset and Format Columns

`USER_FILTER` bypasses documents that do not need to be filtered. Its behavior is sensitive to the values of the format and charset columns. In addition, `USER_FILTER` performs character set conversion according to the charset column values.

2.4.4.3 `USER_FILTER` and Explicitly Bypassing Plain Text or HTML in Mixed Format Columns

A mixed-format column is a text column containing more than one document format, such as a column that contains Microsoft Word, PDF, plain text, and HTML documents.

The `USER_FILTER` executable can index mixed-format columns, automatically bypassing textual documents. However, if you prefer not to depend on the built-in bypass mechanism, you can explicitly tag your rows as text and cause the `USER_FILTER` executable to ignore the row and not process the document in any way.

The format column in the base table enables you to specify the type of document contained in the text column. You can specify the following document types: `TEXT`, `BINARY`, and `IGNORE`. During indexing, the `USER_FILTER` executable ignores any document typed `TEXT`, assuming the charset column is not specified. (The difference between a document with a `TEXT` format column type and one with an `IGNORE` type is that the `TEXT` document is indexed, but ignored by the filter, while the `IGNORE` document is not indexed at all. Use `IGNORE` to overlook documents such as image files, or documents in a language that you do not want to index. `IGNORE` can be used with any filter type.

To set up the `USER_FILTER` bypass mechanism, you must create a format column in your base table. For example:

```
create table hdocs (
  id number primary key,
  fmt varchar2(10),
  text varchar2(80)
);
```

Assuming you are indexing mostly Word documents, you specify `BINARY` in the format column to filter the Word documents. Alternatively, to have the `USER_FILTER` executable ignore an HTML document, specify `TEXT` in the format column.

For example, the following statements add two documents to the text table, assigning one format as `BINARY` and the other `TEXT`:

```
insert into hdocs values(1, 'binary', '/docs/myword.doc');
insert into hdocs values(2, 'text', '/docs/index.html');
commit;
```

Assuming that this file is named `upcase.pl`, create the filter preference as follows:

```
ctx_ddl.create_preference
(
  preference_name => 'USER_FILTER_PREF',
  object_name     => 'USER_FILTER'
);
```

```
ctx_ddl.set_attribute ('USER_FILTER_PREF', 'COMMAND', 'upcase.pl');
```

To create the index, use `CREATE INDEX` and specify the format column name in the parameter string:

```
create index hdocsx on hdocs(text) indextype is ctxsys.context
  parameters ('datastore ctxsys.file_datastore
  filter 'USER_FILTER_PREF'
  format column fmt');
```

If you do not specify `TEXT` or `BINARY` for the format column, `BINARY` is used.

2.4.4.4 Character Set Conversion with `USER_FILTER`

The `USER_FILTER` executable converts documents to the database character set when the document format column is set to `TEXT`. In this case, the `USER_FILTER` executable looks at the `charset` column to determine the document character set.

If the `charset` column value is not an Oracle Text character set name, the document is passed through without any character set conversion.

2.4.4.5 User Filter Example

The following example shows a Perl script to be used as the user filter. This script converts the input text file specified in the first argument to uppercase and writes the output to the location specified in the second argument.

```
#!/usr/local/bin/perl

open(IN, $ARGV[0]);
open(OUT, ">". $ARGV[1]);

while (<IN>)
{
  tr/a-z/A-Z/;
  print OUT;
}

close (IN);
close (OUT);
```

Assuming that this file is named `upcase.pl`, create the filter preference as follows:

```
begin
  ctx_ddl.create_preference
  (
    preference_name => 'USER_FILTER_PREF',
    object_name      => 'USER_FILTER'
  );
  ctx_ddl.set_attribute
  ('USER_FILTER_PREF', 'COMMAND', 'upcase.pl');
end;
```

Create the index in SQL*Plus as follows:

```
create index user_filter_idx on user_filter ( docs )
  indextype is ctxsys.context
  parameters ('FILTER USER_FILTER_PREF');
```

2.4.5 PROCEDURE_FILTER

Use the `PROCEDURE_FILTER` type to filter your documents with a stored procedure. The stored procedure is called each time a document needs to be filtered.

This section contains the following topics.

- [PROCEDURE_FILTER Attributes](#) (page 2-29)
- [PROCEDURE_FILTER Parameter Order](#) (page 2-31)
- [PROCEDURE_FILTER Execute Requirements](#) (page 2-31)
- [PROCEDURE_FILTER Error Handling](#) (page 2-31)
- [PROCEDURE_FILTER Preference Example](#) (page 2-31)

2.4.5.1 PROCEDURE_FILTER Attributes

[Table 2-12](#) (page 2-29) lists the attributes for `PROCEDURE_FILTER`.

Table 2-12 PROCEDURE_FILTER Attributes

Attribute	Purpose	Allowable Values
<code>procedure</code>	Name of the filter stored procedure.	Any procedure. The procedure can be a PL/SQL stored procedure.
<code>input_type</code>	Type of input argument for stored procedure.	<code>VARCHAR2</code> , <code>BLOB</code> , <code>CLOB</code> , <code>FILE</code>
<code>output_type</code>	Type of output argument for stored procedure.	<code>VARCHAR2</code> , <code>CLOB</code> , <code>FILE</code>
<code>rowid_parameter</code>	Include rowid parameter?	<code>TRUE</code> / <code>FALSE</code>
<code>format_parameter</code>	Include format parameter?	<code>TRUE</code> / <code>FALSE</code>
<code>charset_parameter</code>	Include charset parameter?	<code>TRUE</code> / <code>FALSE</code>

procedure

Specify the name of the stored procedure to use for filtering. The procedure can be a PL/SQL stored procedure. The procedure can be a safe callout, or call a safe callout.

With the `rowid_parameter`, `format_parameter`, and `charset_parameter` set to `FALSE`, the procedure can have one of the following signatures:

```
PROCEDURE(IN BLOB, IN OUT NOCOPY CLOB)
PROCEDURE(IN CLOB, IN OUT NOCOPY CLOB)
PROCEDURE(IN VARCHAR, IN OUT NOCOPY CLOB)
PROCEDURE(IN BLOB, IN OUT NOCOPY VARCHAR2)
PROCEDURE(IN CLOB, IN OUT NOCOPY VARCHAR2)
PROCEDURE(IN VARCHAR2, IN OUT NOCOPY VARCHAR2)
```

```
PROCEDURE(IN BLOB, IN VARCHAR2)
PROCEDURE(IN CLOB, IN VARCHAR2)
PROCEDURE(IN VARCHAR2, IN VARCHAR2)
```

The first argument is the content of the unfiltered row, output by the datastore. The second argument is for the procedure to pass back the filtered document text.

The procedure attribute is mandatory and has no default.

input_type

Specify the type of the input argument of the filter procedure. You can specify one of the following types:

Type	Description
procedure	Name of the filter stored procedure.
input_type	Type of input argument for stored procedure.
output_type	Type of output argument for stored procedure.
rowid_parameter	Include rowid parameter?

The `input_type` attribute is not mandatory. If not specified, then `BLOB` is the default.

output_type

Specify the type of output argument of the filter procedure. You can specify one of the following types:

Type	Description
CLOB	The output argument is <code>IN OUT NOCOPY CLOB</code> . Your procedure must write the filtered content to the <code>CLOB</code> passed in.
VARCHAR2	The output argument is <code>IN OUT NOCOPY VARCHAR2</code> . Your procedure must write the filtered content to the <code>VARCHAR2</code> variable passed in.
FILE	The output argument must be <code>IN VARCHAR2</code> . On entering the filter procedure, the output argument is the name of a temporary file. The filter procedure must write the filtered contents to this named file. Using a <code>FILE</code> output type is useful only when the procedure is a safe callout, which can write to the file.

The `output_type` attribute is not mandatory. If not specified, then `CLOB` is the default.

rowid_parameter

When you specify `TRUE`, the rowid of the document to be filtered is passed as the first parameter, before the input and output parameters.

For example, with `INPUT_TYPE BLOB`, `OUTPUT_TYPE CLOB`, and `ROWID_PARAMETER TRUE`, the filter procedure must have the signature as follows:

```
procedure(in rowid, in blob, in out nocopy clob)
```

This attribute is useful for when your procedure requires data from other columns or tables. This attribute is not mandatory. The default is `FALSE`.

format_parameter

When you specify TRUE, the value of the format column of the document being filtered is passed to the filter procedure before input and output parameters, but after the rowid parameter, if enabled.

Specify the name of the format column at index time in the parameters string, using the keyword 'format column <columnname>'. The parameter type must be IN VARCHAR2.

The format column value can be read by means of the rowid parameter, but this attribute enables a single filter to work on multiple table structures, because the format attribute is abstracted and does not require the knowledge of the name of the table or format column.

FORMAT_PARAMETER is not mandatory. The default is FALSE.

charset_parameter

When you specify TRUE, the value of the charset column of the document being filtered is passed to the filter procedure before input and output parameters, but after the rowid and format parameter, if enabled.

Specify the name of the charset column at index time in the parameters string, using the keyword 'charset column <columnname>'. The parameter type must be IN VARCHAR2.

The CHARSET_PARAMETER attribute is not mandatory. The default is FALSE.

2.4.5.2 PROCEDURE_FILTER Parameter Order

ROWID_PARAMETER, FORMAT_PARAMETER, and CHARSET_PARAMETER are all independent. The order is rowid, the format, then charset. However, the filter procedure is passed only the minimum parameters required.

For example, assume that INPUT_TYPE is BLOB and OUTPUT_TYPE is CLOB. If your filter procedure requires all parameters, then the procedure signature must be:

```
(id IN ROWID, format IN VARCHAR2, charset IN VARCHAR2, input IN BLOB, output IN OUT NOCOPY CLOB)
```

If your procedure requires only the ROWID, then the procedure signature must be:

```
(id IN ROWID, input IN BLOB, output IN OUT NOCOPY CLOB)
```

2.4.5.3 PROCEDURE_FILTER Execute Requirements

To create an index using a PROCEDURE_FILTER preference, the index owner must have *execute* permission on the procedure.

2.4.5.4 PROCEDURE_FILTER Error Handling

The filter procedure can raise any errors needed through the normal PL/SQL `raise_application_error` facility. These errors are propagated to the [CTX_USER_INDEX_ERRORS](#) (page G-18) view or reported to the user, depending on how the filter is invoked.

2.4.5.5 PROCEDURE_FILTER Preference Example

Consider a filter procedure CTXSYS.NORMALIZE that you define with the following signature:

```
PROCEDURE NORMALIZE(id IN ROWID, charset IN VARCHAR2, input IN CLOB,
output IN OUT NOCOPY VARCHAR2);
```

To use this procedure as your filter, set up your filter preference as follows:

```
begin
ctx_ddl.create_preference('myfilt', 'procedure_filter');
ctx_ddl.set_attribute('myfilt', 'procedure', 'normalize');
ctx_ddl.set_attribute('myfilt', 'input_type', 'clob');
ctx_ddl.set_attribute('myfilt', 'output_type', 'varchar2');
ctx_ddl.set_attribute('myfilt', 'rowid_parameter', 'TRUE');
ctx_ddl.set_attribute('myfilt', 'charset_parameter', 'TRUE');
end;
```

2.5 Lexer Types

Use the lexer preference to specify the language of the text to be indexed. To create a lexer preference, you must use one of the lexer types described in [Table 2-13](#) (page 2-32).

Table 2-13 *Lexer Types*

Type	Description
AUTO_LEXER (page 2-33)	Lexer for indexing columns that contain documents of different languages.
BASIC_LEXER (page 2-41)	Lexer for extracting tokens from text in languages, such as English and most western European languages that use white space delimited words.
MULTI_LEXER (page 2-49)	Lexer for indexing tables containing documents of different languages such as English, German, and Japanese.
CHINESE_VGRAM_LEXER (page 2-52)	Lexer for extracting tokens from Chinese text.
CHINESE_LEXER (page 2-52)	<p>Lexer for extracting tokens from Chinese text. This lexer offers benefits over the CHINESE_VGRAM lexer:</p> <ul style="list-style-type: none"> • Generates a smaller index • Better query response time • Generates real world tokens resulting in better query precision • Supports stop words
JAPANESE_VGRAM_LEXER (page 2-53)	Lexer for extracting tokens from Japanese text.
JAPANESE_LEXER (page 2-54)	<p>Lexer for extracting tokens from Japanese text. This lexer offers the following advantages over the JAPANESE_VGRAM lexer:</p> <ul style="list-style-type: none"> • Generates smaller index • Better query response time • Generates real world tokens resulting in better precision
KOREAN_MORPH_LEXER (page 2-55)	Lexer for extracting tokens from Korean text.
USER_LEXER (page 2-59)	Lexer you create to index a particular language.
WORLD_LEXER (page 2-71)	Lexer for indexing tables containing documents of different languages; autodetects languages in a document.

2.5.1 AUTO_LEXER

Use the AUTO_LEXER type to index columns that contain documents of different languages. It performs language identification, word segmentation, document analysis, and stemming. The AUTO_LEXER also enables customization of these components. Although parts-of-speech information that is generated by the AUTO_LEXER is not exposed for your use, AUTO_LEXER uses it for context-sensitive or tagged stemming.

This section contains the following topics.

- [AUTO_LEXER Language Support](#) (page 2-33)
- [AUTO_LEXER Attributes Inherited from BASIC_LEXER](#) (page 2-34)
- [AUTO_LEXER Language-Independent Attributes](#) (page 2-34)
- [AUTO_LEXER Language-Dependent Attributes](#) (page 2-37)
- [AUTO_LEXER Dictionary Attribute](#) (page 2-40)

2.5.1.1 AUTO_LEXER Language Support

At index time, AUTO_LEXER automatically detects the language of the document, and tokenizes and stems the document appropriately. To specify an AUTO_LEXER dictionary, use the name of the dictionary you created instead of the filename for the dictionary.

At query time, the language of the query is inherited from the query template. If the query template is not used, or if no language is specified in the query template, then the language of the query is inherited from the session language. [Table 2-14](#) (page 2-33) lists the supported languages.

Note:

Note that dictionary data will not be processed until index/policy creation time or ALTER INDEX time. Errors in dictionary data format will be caught at index/policy creation time or ALTER INDEX time and reported as: DRG-13710: Syntax Error in Dictionary.

Table 2-14 Languages Supported for AUTO_LEXER

Language	Language
ARABIC	NYNORSK
BOKMAL	PERSIAN
CROATIAN	SERBIAN
DANISH	SLOVAK
FINNISH	SLOVENIAN
HEBREW	THAI
CATALAN	KOREAN

Table 2-14 (Cont.) Languages Supported for AUTO_LEXER

Language	Language
CZECH	POLISH
DUTCH	PORTUGUESE
ENGLISH	ROMANIAN
FRENCH	RUSSIAN
GERMAN	SIMPLIFIED CHINESE (See Note)
GREEK	SPANISH
HUNGARIAN	SWEDISH
ITALIAN	TRADITIONAL CHINESE (See Note)
JAPANESE	TURKISH

Note:

Due to the limitation of 30 characters for the string, Traditional Chinese must be specified as `trad_chinese`. Simplified Chinese must be specified as `simp_chinese`.

2.5.1.2 AUTO_LEXER Attributes Inherited from BASIC_LEXER

The following attributes are used in the same way and have the same effect on the AUTO_LEXER as their corresponding attributes in BASIC_LEXER:

- `printjoins`
- `skipjoins`
- `base_letter`
- `base_letter_type`
- `override_base_letter`
- `mixed_case`
- `alternate_spelling`

See Also:

["BASIC_LEXER \(page 2-41\)"](#) and [Table 2-19 \(page 2-41\)](#)

2.5.1.3 AUTO_LEXER Language-Independent Attributes

[Table 2-15 \(page 2-35\)](#) lists the language-independent attributes available in the AUTO_LEXER.

Table 2-15 *AUTO_LEXER Language-Independent Attributes*

Attribute	Attribute Value	Description
language	<characters> (space-delimited string)	<p>Specifies the possible languages of the input documents.</p> <p>If no language is specified, then AUTO_LEXER performs auto detection.</p> <p>If one language is specified, then the language is set manually and AUTO_LEXER does not perform auto detection.</p> <p>If more than one language is specified, then AUTO_LEXER performs auto detection but limits the detected language to be among the language set.</p> <p>Note: The automatic detection of language is statistically based and, thus, inherently imperfect.</p>
deriv_stems	NO (disabled)	<p>Specifies whether the derivational stemming should be used or not. Currently, derivational stemming is only available for English. Hence, the DERIV_STEMS has no effect in other languages.</p> <p>Also, when derivational stemming is performed, tagging and tag stemming is not used. As a result, the tagging and tagged stemming client dictionary has no effect on the stemming result.</p>
deriv_stems	YES (default)	<p>Specifies whether the derivational stemming should be used or not. Currently, derivational stemming is only available for English. Hence, the DERIV_STEMS has no effect in other languages.</p> <p>Also, when derivational stemming is performed, tagging and tag stemming is not used. As a result, the tagging and tagged stemming client dictionary has no effect on the stemming result.</p>
german_decompound	NO (disabled)	<p>Specifies whether German de-compounding should be performed in the stemmer or not.</p>
german_decompound	YES (default, enabled for German only)	<p>Specifies whether German de-compounding should be performed in the stemmer or not.</p>

Table 2-15 (Cont.) AUTO_LEXER Language-Independent Attributes

Attribute	Attribute Value	Description
index_stems	NO (disabled)	<p>Specifies whether an index stemmer should be used.</p> <p>If specified as YES, then the stemmer that corresponds to the document language will be used and the stemmer will always be configured to maximize document recall. Note that this means that the stemmer attribute of BASIC_WORDLIST will be ignored, and the stemmer used by the AUTO_LEXER will be used during query to determine the stem of the given query term.</p> <p>If specified as NO, then queries with stem operators will use the word list stemming to try to stem the tokens. If word list stemming is not available, then the stem operator will be ignored.</p> <p>For documents in Swedish and Dutch, if the index_stems is set to YES, then compound word stemming will automatically be performed, and compounds are always separated into their component stems.</p>
index_stems	YES (default)	<p>Specifies whether an index stemmer should be used.</p> <p>If specified as YES, then the stemmer that corresponds to the document language will be used and the stemmer will always be configured to maximize document recall. Note that this means that the stemmer attribute of BASIC_WORDLIST will be ignored, and the stemmer used by the AUTO_LEXER will be used during query to determine the stem of the given query term.</p> <p>If specified as NO, then queries with stem operators will use the word list stemming to try to stem the tokens. If word list stemming is not available, then the stem operator will be ignored.</p> <p>For documents in Swedish and Dutch, if the index_stems is set to YES, then compound word stemming will automatically be performed, and compounds are always separated into their component stems.</p>
base_letter	NO (disabled)	<p>Specify whether characters that have diacritical marks (umlauts, cedillas, acute accents, and so on) are converted to their base form before being stored in the Text index.</p>
base_letter	YES (enabled)	<p>Specify whether characters that have diacritical marks (umlauts, cedillas, acute accents, and so on) are converted to their base form before being stored in the Text index.</p>
base_letter_type	GENERIC (default)	<p>The GENERIC value is the default and means that base letter transformation uses one transformation table that applies to all languages.</p>

Table 2-15 (Cont.) AUTO_LEXER Language-Independent Attributes

Attribute	Attribute Value	Description
base_letter_type	SPECIFIC	The <code>GENERIC</code> value is the default and means that base letter transformation uses one transformation table that applies to all languages.
override_base_letter	TRUE FALSE (default)	When <code>base_letter</code> is enabled at the same time as <code>alternate_spelling</code> , it is sometimes necessary to override <code>base_letter</code> to prevent unexpected results from serial transformations.
mixed_case	NO (disabled)	Specify whether the lexer leaves the tokens exactly as they appear in the text or converts the tokens to all uppercase. The default is NO (tokens are converted to all uppercase).
mixed_case	YES (enabled)	Specify whether the lexer leaves the tokens exactly as they appear in the text or converts the tokens to all uppercase.
alternate_spelling	GERMAN (German alternate spelling)	Specifies whether German alternate spelling should be used or not.
alternate_spelling	SWEDISH (Swedish alternate spelling)	Specifies whether Swedish alternate spelling should be used or not.
alternate_spelling	NONE (No alternate spelling, default)	The default is NONE. No alternate spelling is specified.
printjoins	<i>characters</i>	Specify the non alphanumeric characters that, when they appear anywhere in a word (beginning, middle, or end), are processed as alphanumeric and included with the token in the Text index. This includes printjoins that occur consecutively. See Basic Lexer " printjoins (page 2-44)".
skipjoins	<i>characters</i>	Specify the non-alphanumeric characters that, when they appear within a word, identify the word as a single token; however, the characters are not stored with the token in the Text index. See Basic Lexer " skipjoins (page 2-45)".

2.5.1.4 AUTO_LEXER Language-Dependent Attributes

AUTO_LEXER provides language-dependent attributes for the languages specified in [Table 2-14](#) (page 2-33).

[Table 2-16](#) (page 2-38) lists the language-dependent attributes available in the AUTO_LEXER. The `<language>` variable in the attribute name refers to any of the supported language names that are listed in [Table 2-14](#) (page 2-33).

Note:

Attribute names must not exceed 30 characters. Therefore, where the `<language>` variable is specified, the language name may need to be abbreviated in certain instances. For example, `traditional_chinese` should be abbreviated to `trad_chinese` and `simplified_chinese` should be abbreviated to `simp_chinese`.

Table 2-16 AUTO_LEXER Language-Dependent Attributes

Attribute	Attribute Value	Description
<code><language>_prefix_morphemes</code>	<i>characters</i> (space-delimited string)	Specifies the list of inflectional prefixes that, when enclosed by parentheses, are kept together with the base word. For example, <i>(re) analyze</i> .
<code><language>_suffix_morphemes</code>	<i>characters</i> (space-delimited string)	Specifies the list of inflectional suffixes that, when enclosed by parentheses are kept together with the base word. For example, <i>file(s)</i> .
<code><language>_punctuations</code>	<i>characters</i> (space-delimited string)	Specifies punctuation that breaks sentences.
<code><language>_non_sent_end_abbr</code>	<i>characters</i> (space-delimited string)	Specifies abbreviations that do not end sentences.

Table 2-17 Default Values for AUTO_LEXER Language-Dependent Attributes

Attribute	Language	Default Value
<code><language>_prefix_morphemes</code>	All languages	None
<code><language>_suffix_morphemes</code>	English	s es er
<code><language>_suffix_morphemes</code>	Spanish	ba n s es
<code><language>_suffix_morphemes</code>	Portuguese	s es
<code><language>_suffix_morphemes</code>	German	in innen
<code><language>_suffix_morphemes</code>	French	ne e
<code><language>_suffix_morphemes</code>	All other languages	None
<code><language>_punctuations</code>	English	. ? !
<code><language>_punctuations</code>	Catalan, Czech, Dutch, Greek, Hungarian, Polish, Romanian, Russian, Turkish	. ? ! - --
<code><language>_punctuations</code>	French, German, Italian, Korean, Portuguese, Spanish, Swedish	, ? !
<code><language>_punctuations</code>	Japanese	. ? ! 。 ? ! :

Table 2-17 (Cont.) Default Values for AUTO_LEXER Language-Dependent Attributes

Attribute	Language	Default Value
<language>_punctuations	Simplified Chinese Abbreviate to: simp_chinese	。 。 ! ? !! ?! !? . ? ! 。
<language>_punctuations	Traditional Chinese Abbreviate to: trad_chinese	。 。 ! ? !! ?! !? . ? ! 。
<language>_non_sent_end_abbr	Polish, Romanian, Russian, Turkish	e.g. i.e. viz. a.k.a.
<language>_non_sent_end_abbr	Catalan	R.D. pp.
<language>_non_sent_end_abbr	Czech, Greek, Hungarian	e.g. i.e. viz. a.k.a.
<language>_non_sent_end_abbr	Dutch	f.eks. f. eks. inkl. sr. skuesp. sekr. prof. mus. lrs. logr. kgl. insp. hr. hrs. gdr. frk. fr. forst. forf. fm. fmd. esq. d.æ d.æ. d.y. dr. dir. dept.chef civiling. bibl. ass. admn. adj. Skt. H.K.H.
<language>_non_sent_end_abbr	English, Japanese, Simplified Chinese (abbreviate to simp_chinese), Traditional Chinese (abbreviate to trad_chinese)	e.g. i.e. viz. a.k.a. Adm. Br. Capt. Cdr. Cmdr. Col. Comdr. Comdt. Dr. Drs. Fr. Gen. Gov. Hon. Ins. Lieut. Lt. Maj. Messrs. Mdm. Mlle. Milles. Mme. Mmes. Mr. Mrs. Ms. Pres. Prof. Profs. Pvt. Rep. Rev. Revd. Secy. Sen. Sgt. Sra. Srta. St. Ste.
<language>_non_sent_end_abbr	French	c.-à-d. cf. e.g. ex. i.e. Pr. Prof. M. Mr. Mrs. Mme Mmes Mlle Milles Mgr. MM. Lieut. Gén. Dr. Col.
<language>_non_sent_end_abbr	German	ca. bzw. e.g. i.e. inkl. Fr. Frl. Mme. Mile. Mag. Stud. Tel. Hr. Hrn. apl.Prof. Prof.
<language>_non_sent_end_abbr	Italian	e.g. i.e. pag. pagg. tel. T.V. N.H. N.D. comm. col. cav. cap. geom. gen. ing. jr. mr. mons. mar. magg. prof. prof.ssa prof.sse proff. pres. perito ind. p. p.i. sr. s.ten. sottoten. sig. serg. sen. segr. sac. ten. uff. vicepres. vesc. S.S. S.E. avv. app. amm. arch. on. dir. dott. dott.ssa dr. rag.
<language>_non_sent_end_abbr	Korean	e.g. i.e. a.k.a. Dr. Mr. Mrs. Ms. Prof.
<language>_non_sent_end_abbr	Portuguese	cf. Cf. e.g. E.g. i.é. I.é. p.ex. P.ex. pág. pag. Pág. Pag. tel. telef. Tel. Telef. sr. srs. sra. mr. eng. dr. dra. Dr. Dra. V.Ex. V.Exa. S. N. S. Mrs. Eng. Ex. Exa.
<language>_non_sent_end_abbr	Spanish	e.g. i.e. ej. p.ej. pág. págs. tel. tfno. Fr. Ldo. Lda. Lic. Pbro. D. Dña. Dr. Dres. Dra. Dras. Dn. Mons. Rvdo. Sto. Sta. Sr. Srs. Srta. Srtas. Sres. Sra. Sras. Excmo. Excma. Ilmo. Ilma. Sto. Sta.
<language>_non_sent_end_abbr	Swedish	inkl. prof. hrr. hr. Hrr. Hr. dr. Dr.

Examples for AUTO_LEXER Language-Dependent Attributes

Example 2-1 *ctx_ddl.create_preference to associate a dictionary with an index*

```
exec CTX_DDL.CREATE_PREFERENCE('A_LEX', 'AUTO_LEXER');
exec CTX_ANL.ADD_DICTIONARY('MY_ENGLISH', 'ENGLISH', lobloc);
select * from CTX_USR_ANL_DICTS;
exec CTX_DDL.SET_ATTRIBUTE('A_LEX', 'english_dictionary', 'MY_ENGLISH'
);
```

Example 2-2 *<language>_prefix_morphemes*

```
ctx_ddl.set_attribute(
    'a_lex', 'english_prefix_morphemes', 're'
);
```

Example 2-3 *<language>_suffix_morphemes*

```
ctx_ddl.set_attribute(
    'a_lex', 'english_suffix_morphemes', 's es'
);
```

Example 2-4 *<language>_punctuations*

```
ctx_ddl.set_attribute(
    'a_lex', 'english_punctuations', '. ? !'
);
```

Example 2-5 *<language>_non_sentence_ending_abbrev*

```
ctx_ddl.set_attribute(
    'a_lex', 'english_non_sentence_ending_abbrev', 'e.g. a.k.a. Dr.'
);
```

2.5.1.5 AUTO_LEXER Dictionary Attribute

The dictionary attribute is language-specific and is used to set the name of the language dictionary. The *<language>_dictionary* attribute specifies one language dictionary for the supported languages as listed in [Table 2-18](#) (page 2-40).

The *<language>_dictionary* attribute has the following behavior:

- The *<language>* value of the attribute specifies only the dictionary name, not the location. For example, *dutch_dictionary* specifies that the Dutch dictionary is to be used.
- The *set_attribute* method does not load the dictionary; it only records the dictionary name. Therefore, the dictionary must be at the specified location when the dictionary is needed. Otherwise, an error will be raised.

Table 2-18 Supported Languages for AUTO_LEXER Dictionary Attribute

Language Attribute	Language Attribute
Catalan	Korean
Czech	Polish
Dutch	Portuguese
English	Romanian

Table 2-18 (Cont.) Supported Languages for AUTO_LEXER Dictionary Attribute

Language Attribute	Language Attribute
French	Russian
German	Simplified Chinese
Greek	Spanish
Hungarian	Swedish
Italian	Traditional Chinese
Japanese	Turkish

2.5.2 BASIC_LEXER

Use the BASIC_LEXER type to identify tokens for creating Text indexes for English and all other supported whitespace-delimited languages.

The BASIC_LEXER also enables base-letter conversion, composite word indexing, case-sensitive indexing and alternate spelling for whitespace-delimited languages that have extended character sets.

In English and French, you can use the BASIC_LEXER to enable theme indexing.

Note:

Any processing that the lexer does to tokens before indexing (for example, removal of characters, and base-letter conversion) are also performed on query terms at query time. This ensures that the query terms match the form of the tokens in the Text index.

BASIC_LEXER supports any database character set.

This section contains the following topics.

- [BASIC_LEXER Attributes](#) (page 2-41)
- [Stemming User-Dictionaries](#) (page 2-47)
- [BASIC_LEXER Example](#) (page 2-49)

2.5.2.1 BASIC_LEXER Attributes

BASIC_LEXER has the attributes shown in [Table 2-19](#) (page 2-41).

Table 2-19 BASIC_LEXER Attributes

Attribute	Attribute Value
continuation	<i>characters</i>
numgroup	<i>characters</i>
numjoin	<i>characters</i>

Table 2-19 (Cont.) BASIC_LEXER Attributes

Attribute	Attribute Value
printjoins	<i>characters</i>
punctuations	<i>characters</i>
skipjoins	<i>characters</i>
startjoins	<i>non alphanumeric characters that occur at the beginning of a token (string)</i>
endjoins	<i>non alphanumeric characters that occur at the end of a token (string)</i>
whitespace	<i>characters (string)</i>
newline	NEWLINE (\n) CARRIAGE_RETURN (\r)
base_letter	NO (disabled)
base_letter	YES (enabled)
base_letter_type	GENERIC (default)
base_letter_type	SPECIFIC
override_base_letter	TRUE FALSE (default)
mixed_case	NO (disabled)
mixed_case	YES (enabled)
composite	DEFAULT (no composite word indexing, default)
composite	GERMAN (German composite word indexing)
composite	DUTCH (Dutch composite word indexing)

Table 2-19 (Cont.) BASIC_LEXER Attributes

Attribute	Attribute Value
index_stems	NONE
Use the numeric value in a string or the string value.	ENGLISH DERIVATIONAL DUTCH FRENCH GERMAN ITALIAN SPANISH CATALAN CZECH GREEK HUNGARIAN POLISH PORTUGUESE ROMANIAN RUSSIAN SWEDISH (see Note) DERIVATIONAL_NEW (see Note) DUTCH_NEW (see Note) ENGLISH_NEW (see Note) FRENCH_NEW (see Note) GERMAN_NEW (see Note) ITALIAN_NEW (see Note) SPANISH_NEW (see Note) TURKISH
	Note: De-compounding word stemming is automatically performed when index_stems is set to SWEDISH, or DUTCH_NEW values.
	Note: Seven of the index_stem attributes that are new for this release have a "_NEW" suffix to enable you to utilize the new stemmer attributes while maintaining backward compatibility with previous releases of Oracle Text.
index_themes	YES (enabled)
index_themes	NO (disabled, default)
index_text	YES (enabled, default)
index_text	NO (disabled)
prove_themes	YES (enabled, default)
prove_themes	NO (disabled)
theme_language	AUTO (default)
theme_language	(any Globalization Support language)

Table 2-19 (Cont.) BASIC_LEXER Attributes

Attribute	Attribute Value
alternate_spelling	GERMAN (German alternate spelling)
alternate_spelling	DANISH (Danish alternate spelling)
alternate_spelling	SWEDISH (Swedish alternate spelling)
alternate_spelling	NONE (No alternate spelling, default)
new_german_spelling	YES
	NO (default)

continuation

Specify the characters that indicate a word continues on the next line and should be indexed as a single token. The most common continuation characters are hyphen '-' and backslash '\'.

numgroup

Specify a single character that, when it appears in a string of digits, indicates that the digits are groupings within a larger single unit.

For example, comma ',' might be defined as a numgroup character because it often indicates a grouping of thousands when it appears in a string of digits.

numjoin

Specify the characters that, when they appear in a string of digits, cause Oracle Text to index the string of digits as a single unit or word.

For example, period '.' can be defined as a numjoin character because it often serves as a decimal point when it appears in a string of digits.

Note:

The default values for numjoin and numgroup are determined by the globalization support initialization parameters that are specified for the database.

In general, a value need not be specified for either numjoin or numgroup when creating a lexer preference for BASIC_LEXER.

printjoins

Specify the non alphanumeric characters that, when they appear anywhere in a word (beginning, middle, or end), are processed as alphanumeric and included with the token in the Text index. This includes printjoins that occur consecutively.

For example, if the hyphen '-' and underscore '_' characters are defined as printjoins, terms such as *pseudo-intellectual* and *_file_* are stored in the Text index as *pseudo-intellectual* and *_file_*.

Note:

If a `printjoins` character is also defined as a `punctuations` character, the character is only processed as an alphanumeric character if the character immediately following it is a standard alphanumeric character or has been defined as a `printjoins` or `skipjoins` character.

punctuations

Specify a list of non-alphanumeric characters that, when they appear at the end of a word, indicate the end of a sentence. The defaults are period '.', question mark '?', and exclamation point '!'.

Characters that are defined as `punctuations` are removed from a token before text indexing. However, if a `punctuations` character is also defined as a `printjoins` character, then the character is removed only when it is the last character in the token.

For example, if the period (.) is defined as both a `printjoins` and a `punctuations` character, then the following transformations take place during indexing and querying as well:

Token	Indexed Token
.doc	.doc
dog.doc	dog.doc
dog..doc	dog..doc
dog.	dog
dog...	dog..

In addition, `BASIC_LEXER` use `punctuations` characters in conjunction with `newline` and `whitespace` characters to determine sentence and paragraph delimiters for sentence/paragraph searching.

skipjoins

Specify the non-alphanumeric characters that, when they appear within a word, identify the word as a single token; however, the characters are not stored with the token in the Text index.

For example, if the hyphen character '-' is defined as a `skipjoins`, then the word *pseudo-intellectual* is stored in the Text index as *pseudointellectual*.

Note:

`Printjoins` and `skipjoins` are mutually exclusive. The same characters cannot be specified for both attributes.

startjoins/endjoins

For `startjoins`, specify the characters that when encountered as the first character in a token explicitly identify the start of the token. The character, as well as any other `startjoins` characters that immediately follow it, is included in the Text index entry for the token. In addition, the first `startjoins` character in a string of `startjoins` characters implicitly ends the previous token.

For `endjoins`, specify the characters that when encountered as the last character in a token explicitly identify the end of the token. The character, as well as any other

`startjoins` characters that immediately follow it, is included in the Text index entry for the token.

The following rules apply to both `startjoins` and `endjoins`:

- The characters specified for `startjoins`/`endjoins` cannot occur in any of the other attributes for `BASIC_LEXER`.
- `startjoins`/`endjoins` characters can occur only at the beginning or end of tokens

`Printjoins` differ from `endjoins` and `startjoins` in that position does not matter. For example, \$35 will be indexed as one token if \$ is a `startjoin` or a `printjoin`, but as two tokens if it is defined as an `endjoin`.

whitespace

Specify the characters that are treated as blank spaces between tokens. `BASIC_LEXER` uses `whitespace` characters in conjunction with punctuations and newline characters to identify character strings that serve as sentence delimiters for sentence and paragraph searching.

The predefined default values for `whitespace` are `space` and `tab`. These values cannot be changed. Specifying characters as `whitespace` characters adds to these defaults.

newline

Specify the characters that indicate the end of a line of text. `BASIC_LEXER` uses `newline` characters in conjunction with punctuations and `whitespace` characters to identify character strings that serve as paragraph delimiters for sentence and paragraph searching.

The only valid values for `newline` are `NEWLINE` and `CARRIAGE_RETURN` (for carriage returns). The default is `NEWLINE`.

base_letter

Specify whether characters that have diacritical marks (umlauts, cedillas, acute accents, and so on) are converted to their base form before being stored in the Text index. The default is `NO` (base-letter conversion disabled). For more information on base-letter conversions and `base_letter_type`, see [Base-Letter Conversion](#) (page 17-2).

base_letter_type

Specify `GENERIC` or `SPECIFIC`.

The `GENERIC` value is the default and means that base letter transformation uses one transformation table that applies to all languages. For more information on base-letter conversions and `base_letter_type`, see ["Base-Letter Conversion"](#) (page 17-2).

override_base_letter

When `base_letter` is enabled at the same time as `alternate_spelling`, it is sometimes necessary to override `base_letter` to prevent unexpected results from serial transformations. See ["Overriding Alternative Spelling Features"](#) (page 17-3). Default is `FALSE`.

mixed_case

Specify whether the lexer leaves the tokens exactly as they appear in the text or converts the tokens to all uppercase. The default is `NO` (tokens are converted to all uppercase).

Note:

Oracle Text ensures that word queries match the case sensitivity of the index being queried. As a result, if you enable case sensitivity for your Text index, queries against the index are always case sensitive.

composite

Specify whether composite word indexing is disabled or enabled for either GERMAN or DUTCH text. The default is DEFAULT (composite word indexing disabled).

Words that are usually one entry in a German dictionary are not split into composite stems, while words that aren't dictionary entries are split into composite stems.

To retrieve the indexed composite stems, you must enter a stem query, such as *\$bahnhof*. The language of the wordlist stemmer must match the language of the composite stems.

2.5.2.2 Stemming User-Dictionaries

You can create a user-dictionary for your own language to customize how words are decomposed. These dictionaries are shown in [Table 2-20](#) (page 2-47).

Table 2-20 Stemming User-Dictionaries

Dictionary	Stemmer
\$ORACLE_HOME/ctx/data/frlx/drfr.dct	French
\$ORACLE_HOME/ctx/data/delx/drde.dct	German
\$ORACLE_HOME/ctx/data/nllx/drnl.dct	Dutch
\$ORACLE_HOME/ctx/data/itlx/drit.dct	Italian
\$ORACLE_HOME/ctx/data/eslx/dres.dct	Spanish
\$ORACLE_HOME/ctx/data/enlx/dren.dct	English and Derivational

Stemming user-dictionaries are not supported for languages other than those listed in [Table 2-20](#) (page 2-47).

The format for the user dictionary is as follows:

```
output term <tab> input term
```

The individual parts of the decomposed word must be separated by the # character. The following example entries are for the German word *Hauptbahnhof*:

```
Hauptbahnhof<tab>Haupt#Bahnhof
Hauptbahnhofes<tab>Haupt#Bahnhof
Hauptbahnhof<tab>Haupt#Bahnhof
Hauptbahnhoefe<tab>Haupt#Bahnhof
```

index_themes

Specify YES to index theme information in English or French. This makes ABOUT queries more precise. The index_themes and index_text attributes cannot both be NO. The default is NO.

You can set this parameter to TRUE for any index type, including CTXCAT. To enter an ABOUT query with CATSEARCH, use the query template with CONTEXT grammar.

prove_themes

Specify YES to prove themes. Theme proving attempts to find related themes in a document. When no related themes are found, parent themes are eliminated from the document.

While theme proving is acceptable for large documents, short text descriptions with a few words rarely prove parent themes, resulting in poor recall performance with ABOUT queries.

Theme proving results in higher precision and less recall (less rows returned) for ABOUT queries. For higher recall in ABOUT queries and possibly less precision, you can disable theme proving. Default is YES.

The prove_themes attribute is supported for CONTEXT and CTXRULE indexes.

theme_language

Specify which knowledge base to use for theme generation when index_themes is set to YES. When index_themes is NO, setting this parameter has no effect on anything.

Specify any globalization support language or AUTO. You must have a knowledge base for the language you specify. This release provides a knowledge base in only English and French. In other languages, you can create your own knowledge base.

See Also:

"[Adding a Language-Specific Knowledge Base](#) (page 16-11)" in [Oracle Text Utilities](#) (page 16-1).

The default is AUTO, which instructs the system to set this parameter according to the language of the environment.

index_stems

Specify the stemmer to use for stem indexing. Choose one of the following stemmers: NONE, ARABIC, CATALAN, CROATIAN, CZECH, DANISH, DERIVATIONAL, DUTCH, ENGLISH, FINNISH, FRENCH, GERMAN, HEBREW, HUNGARIAN, ITALIAN, NORWEGIAN, POLISH, PORTUGUESE, ROMANIAN, SLOVAK, SLOVENIAN, SPANISH, and SWEDISH.

Tokens are stemmed to a single base form at index time in addition to the normal forms. Indexing stems enables better query performance for stem (\$) queries, such as *\$computed*.

Note:

If the index_stems attribute is set to one of the languages with ID 8 to 33, which are listed [Table 2-19](#) (page 2-41), then the stemmer attribute of BASIC_WORDLIST will be ignored and the stemmer used by the BASIC_LEXER will be used during query to determine the stem of the given query term.

index_text

Specify YES to index word information. The `index_themes` and `index_text` attributes cannot both be NO.

The default is YES.

alternate_spelling

Specify either GERMAN, DANISH, or SWEDISH to enable the alternate spelling in one of these languages. Enabling alternate spelling enables you to query a word in any of its alternate forms.

Alternate spelling is off by default; however, in the language-specific scripts that Oracle provides in `admin/defaults` (`drdefd.sql` for German, `drdefdk.sql` for Danish, and `drdefs.sql` for Swedish), alternate spelling is turned on. If your installation uses these scripts, then alternate spelling is on. However, you can specify NONE for no alternate spelling. For more information about the alternate spelling conventions Oracle Text uses, see [Alternate Spelling](#) (page 17-2).

new_german_spelling

Specify whether the queries using the BASIC_LEXER return both traditional and reformed (new) spellings of German words. If `new_german_spelling` is set to YES, then both traditional and new forms of words are indexed. If it is set to NO, then the word will be indexed only as it is provided in the query. The default is NO.

See Also:

["New German Spelling](#) (page 17-3)"

2.5.2.3 BASIC_LEXER Example

The following example sets printjoin characters and disables theme indexing with the BASIC_LEXER:

```
begin
ctx_ddl.create_preference('mylex', 'BASIC_LEXER');
ctx_ddl.set_attribute('mylex', 'printjoins', '_-');
ctx_ddl.set_attribute ('mylex', 'index_themes', 'NO');
ctx_ddl.set_attribute ('mylex', 'index_text', 'YES');
end;
```

To create the index with no theme indexing and with printjoin characters set as described, enter the following statement:

```
create index myindex on mytable ( docs )
  indextype is ctxsys.context
  parameters ( 'LEXER mylex' );
```

2.5.3 MULTI_LEXER

Use MULTI_LEXER to index text columns that contain documents of different languages. For example, use this lexer to index a text column that stores English, German, and Japanese documents.

This lexer has no attributes.

You must have a language column in your base table. To index multi-language tables, specify the language column when you create the index.

Create a multi-lexer preference with `CTX_DDL.CREATE_PREFERENCE`. Add language-specific lexers to the multi-lexer preference with the `CTX_DDL.ADD_SUB_LEXER` procedure.

During indexing, the `MULTI_LEXER` examines each row's language column value and switches in the language-specific lexer to process the document.

The `WORLD_LEXER` lexer also performs multi-language indexing, but without the need for separate language columns (that is, it has automatic language detection). For more on `WORLD_LEXER`, see "[WORLD_LEXER](#) (page 2-71)".

This section contains the following topics.

- [MULTI_LEXER Restriction](#) (page 2-50)
- [MULTI_LEXER Multi-language Stoplists](#) (page 2-50)
- [MULTI_LEXER Example](#) (page 2-50)
- [MULTI_LEXER and Querying Multi-Language Tables](#) (page 2-51)

2.5.3.1 MULTI_LEXER Restriction

`MULTI_LEXER` must have a sublexer specified for different languages. If you already know the language, you can use `BASIC_LEXER` as the sublexer. If the language is not known, then you use `AUTO_LEXER` instead of `MULTI_LEXER`. Hence, using `AUTO_LEXER` as a sublexer of `MULTI_LEXER` is not useful and it is disabled.

Thus, the following statements will not work and throw error DRG-13003.

```
exec ctx_ddl.create_preference ('multilexer', 'MULTI_LEXER');
exec ctx_ddl.create_preference('autolexer', AUTO_LEXER);
exec ctx_ddl.add_sub_lexer('multilexer', 'GERMAN', 'autolexer');
```

2.5.3.2 MULTI_LEXER Multi-language Stoplists

When you use the `MULTI_LEXER`, you can also use a multi-language stoplist for indexing.

See Also:

["Multi-Language Stoplists](#) (page 2-94)".

2.5.3.3 MULTI_LEXER Example

Create the multi-language table with a primary key, a text column, and a language column as follows:

```
create table globaldoc (
    doc_id number primary key,
    lang varchar2(3),
    text clob
);
```

Assume that the table holds mostly English documents, with the occasional German or Japanese document. To handle the three languages, you must create three sub-lexers, one for English, one for German, and one for Japanese:

```
ctx_ddl.create_preference('english_lexer','basic_lexer');
ctx_ddl.set_attribute('english_lexer','index_themes','yes');
```

```
ctx_ddl.set_attribute('english_lexer','theme_language','english');

ctx_ddl.create_preference('german_lexer','basic_lexer');
ctx_ddl.set_attribute('german_lexer','composite','german');
ctx_ddl.set_attribute('german_lexer','mixed_case','yes');
ctx_ddl.set_attribute('german_lexer','alternate_spelling','german');

ctx_ddl.create_preference('japanese_lexer','japanese_vgram_lexer');
```

Create the multi-lexer preference:

```
ctx_ddl.create_preference('global_lexer','multi_lexer');
```

Because the stored documents are mostly English, make the English lexer the default using CTX_DDL.ADD_SUB_LEXER (page 8-24):

```
ctx_ddl.add_sub_lexer('global_lexer','default','english_lexer');
```

Now add the German and Japanese lexers in their respective languages with CTX_DDL.ADD_SUB_LEXER (page 8-24) procedure. Also assume that the language column is expressed in the standard ISO 639-2 language codes, so add those as alternative values.

```
ctx_ddl.add_sub_lexer('global_lexer','german','german_lexer','ger');
ctx_ddl.add_sub_lexer('global_lexer','japanese','japanese_lexer','jpn');
```

Now create the index globalx, specifying the multi-lexer preference and the language column in the parameter clause as follows:

```
create index globalx on globaldoc(text) indextype is ctxsys.context
parameters ('lexer global_lexer language column lang');
```

2.5.3.4 MULTI_LEXER and Querying Multi-Language Tables

At query time, the multi-lexer examines the language setting and uses the sub-lexer preference for that language to parse the query.

If the language is not set, then the default lexer is used. Otherwise, the query is parsed and run as usual. The index contains tokens from multiple languages, so such a query can return documents in several languages. To limit your query to a given language, use a structured clause on the language column.

If the language column is set to AUTO, then the multi-lexer detects the language of the document for the supported languages shown in Table 2-21 (page 2-51).

Table 2-21 Languages Supported for MULTI_LEXER Auto-detection

Language	Language
ARABIC	JAPANESE
CATALAN	KOREAN
TRADITIONAL CHINESE	NORWEGIAN
CROATIAN	POLISH
CZECH	PORTUGUESE
DANISH	ROMANIAN

Table 2-21 (Cont.) Languages Supported for MULTI_LEXER Auto-detection

Language	Language
DUTCH	RUSSIAN
ENGLISH	LATIN SERBIAN
GERMAN	SLOVAK
GREEK	SWEDISH
HEBREW	THAI
HUNGARIAN	TURKISH
ITALIAN	

2.5.4 CHINESE_VGRAM_LEXER

The CHINESE_VGRAM_LEXER type identifies tokens in Chinese text for creating Text indexes.

The CHINESE_VGRAM_LEXER has the following attribute:

Table 2-22 CHINESE_VGRAM_LEXER Attributes

Attribute	Attribute Value
mixed_case_ASCII7	Enable mixed-case (upper- and lower-case) searches of ASCII7 text (for example, <i>cat</i> and <i>Cat</i>). Allowable values are YES and NO (default).

You can use this lexer if your database uses one of the following character sets:

- AL32UTF8
- ZHS16CGB231280
- ZHS16GBK
- ZHS32GB18030
- ZHT32EUC
- ZHT16BIG5
- ZHT32TRIS
- ZHT16HKSCS
- ZHT16MSWIN950
- UTF8

2.5.5 CHINESE_LEXER

The CHINESE_LEXER type identifies tokens in traditional and simplified Chinese text for creating Oracle Text indexes.

This lexer offers the following benefits over the CHINESE_VGRAM_LEXER:

- generates a smaller index
- better query response time
- generates real word tokens resulting in better query precision
- supports stop words

Because the CHINESE_LEXER uses a different algorithm to generate tokens, indexing time is longer than with CHINESE_VGRAM_LEXER.

You can use this lexer if your database character is one of the Chinese or Unicode character sets supported by Oracle.

The CHINESE_LEXER has the following attribute:

Table 2-23 CHINESE_LEXER Attributes

Attribute	Attribute Value
<code>mixed_case_ASCII7</code>	Enable mixed-case (upper- and lower-case) searches of ASCII7 text (for example, <i>cat</i> and <i>Cat</i>). Allowable values are YES and NO (default).

You can modify the existing lexicon (dictionary) used by the Chinese lexer, or create your own Chinese lexicon, with the `ctxlc` command.

See Also:

"[Lexical Compiler \(ctxlc\)](#) (page 16-12)" in [Oracle Text Utilities](#) (page 16-1)

2.5.6 JAPANESE_VGRAM_LEXER

The JAPANESE_VGRAM_LEXER type identifies tokens in Japanese for creating Text indexes. This lexer supports the stem (\$) operator.

This lexer has the following attributes:

Table 2-24 JAPANESE_VGRAM_LEXER Attributes

Attribute	Attribute Value
<code>delimiter</code>	Specify whether to consider certain Japanese blank characters, such as a full-width forward slash or a full-width middle dot. ALL considers these characters, while NONE ignores them. Default is NONE.
<code>mixed_case_ASCII7</code>	Enable mixed-case (upper- and lower-case) searches of ASCII7 text (for example, <i>cat</i> and <i>Cat</i>). Allowable values are YES and NO (default).

Table 2-24 (Cont.) JAPANESE_VGRAM_LEXER Attributes

Attribute	Attribute Value
bigram	Specify TRUE to enable the <i>bigram</i> mode for the Japanese VGRAM lexer. In the <i>bigram</i> mode, the Japanese queries run faster because only 2-gram tokens are generated, thus avoiding the internal wildcard search. But, in the bigram mode, the index size needs to be increased to accommodate the large number of tokens. Enable the <i>bigram</i> mode, if the performance of queries is of higher importance to you than the disk space. Default is FALSE.

You can use this lexer if your database uses one of the following character sets:

- JA16SJIS
- JA16EUC
- UTF8
- AL32UTF8
- JA16EUCTILDE
- JA16EUCYEN
- JA16SJISTILDE
- JA16SJISYEN

2.5.7 JAPANESE_LEXER

The JAPANESE_LEXER type identifies tokens in Japanese for creating Text indexes. This lexer supports the stem (\$) operator.

This lexer offers the following benefits over the JAPANESE_VGRAM_LEXER:

- generates a smaller index
- better query response time
- generates real word tokens resulting in better query precision

Because the JAPANESE_LEXER uses a new algorithm to generate tokens, indexing time is longer than with JAPANESE_VGRAM_LEXER.

You can modify the existing lexicon (dictionary) used by the Japanese lexer, or create your own Japanese lexicon, with the `ctxlc` command.

See Also:

"[Lexical Compiler \(ctxlc\)](#) (page 16-12)" in [Oracle Text Utilities](#) (page 16-1)

This lexer has the following attributes:

Table 2-25 JAPANESE_LEXER Attributes

Attribute	Attribute Value
delimiter	Specify NONE or ALL to ignore certain Japanese blank characters, such as a full-width forward slash or a full-width middle dot. Default is NONE.
mixed_case_ASCII7	Enable mixed-case (upper- and lower-case) searches of ASCII7 text (for example, <i>cat</i> and <i>Cat</i>). Allowable values are YES and NO (default).

The JAPANESE_LEXER supports the following character sets:

- JA16SJIS
- JA16EUC
- UTF8
- AL32UTF8
- JA16EUCTILDE
- JA16EUCYEN
- JA16SJISTILDE
- JA16SJISYEN

When you specify JAPANESE_LEXER for creating text index, the JAPANESE_LEXER resolves a sentence into words.

For example, the following compound word (*natural language institute*)

’ 自然言語処理 ’

is indexed as three tokens:

’ 自然 ’, ’ 言語 ’, ’ 処理 ’

To resolve a sentence into words, the internal dictionary is referenced. When a word cannot be found in the internal dictionary, Oracle Text uses the JAPANESE_VGRAM_LEXER to resolve it.

2.5.8 KOREAN_MORPH_LEXER

The KOREAN_MORPH_LEXER type identifies tokens in Korean text for creating Oracle Text indexes.

This section contains the following topics.

- [KOREAN_MORPH_LEXER Dictionaries](#) (page 2-56)

- [KOREAN_MORPH_LEXER Unicode Support](#) (page 2-56)
- [KOREAN_MORPH_LEXER Attributes](#) (page 2-57)
- [KOREAN_MORPH_LEXER Limitations](#) (page 2-58)
- [KOREAN_MORPH_LEXER Example: Setting Composite Attribute](#) (page 2-58)

2.5.8.1 KOREAN_MORPH_LEXER Dictionaries

The KOREAN_MORPH_LEXER uses four dictionaries:

Table 2-26 KOREAN_MORPH_LEXER Dictionaries

Dictionary	File
System	\$ORACLE_HOME/ctx/data/kolx/drk2sdic.dat
Grammar	\$ORACLE_HOME/ctx/data/kolx/drk2gram.dat
Stopword	\$ORACLE_HOME/ctx/data/kolx/drk2xdic.dat
User-defined	\$ORACLE_HOME/ctx/data/kolx/drk2udic.dat

The grammar, user-defined, and stopword dictionaries should be written using the KSC 5601 or MSWIN949 character sets. You can modify these dictionaries using the defined rules. The system dictionary must not be modified.

You can add unregistered words to the user-defined dictionary file. The rules for specifying new words are in the file.

You can use KOREAN_MORPH_LEXER if your database uses one of the following character sets:

- KO16KSC5601
- KO16MSWIN949
- UTF8
- AL32UTF8

The KOREAN_MORPH_LEXER enables mixed-case searches.

2.5.8.2 KOREAN_MORPH_LEXER Unicode Support

The KOREAN_MORPH_LEXER has the following Unicode support:

- Words in non-KSC5601 Korean characters defined in Unicode
- Supplementary characters

See Also:

For information on supplementary characters, see the *Oracle Database Globalization Support Guide*

Some Korean documents may have non-KSC5601 characters in them. As the KOREAN_MORPH_LEXER can recognize all possible 11,172 Korean (Hangul) characters,

such documents can also be interpreted by using the UTF8 or AL32UTF8 character sets.

Use the AL32UTF8 character set for your database to extract surrogate characters. By default, the KOREAN_MORPH_LEXER extracts all series of surrogate characters in a document as one token for each series.

Limitations on Korean Unicode Support

For conversion from Hanja to Hangul (Korean), the KOREAN_MORPH_LEXER supports only the 4,888 Hanja characters defined in KSC5601.

2.5.8.3 KOREAN_MORPH_LEXER Attributes

When you use the KOREAN_MORPH_LEXER, you can specify the following attributes:

Table 2-27 KOREAN_MORPH_LEXER Attributes

Attribute	Attribute Value
verb_adjective	Specify TRUE or FALSE to index verbs, adjectives, and adverbs. Default is FALSE.
one_char_word	Specify TRUE or FALSE to index one syllable. Default is FALSE.
number	Specify TRUE or FALSE to index number. Default is FALSE.
user_dic	Specify TRUE or FALSE to index user dictionary. Default is TRUE.
stop_dic	Specify TRUE or FALSE to use stop-word dictionary. Default is TRUE. The stop-word dictionary belongs to KOREAN_MORPH_LEXER.
composite	Specify indexing style of composite noun. Specify COMPOSITE_ONLY to index only composite nouns. Specify NGRAM to index all noun components of a composite noun. Specify COMPONENT_WORD to index single noun components of composite nouns as well as the composite noun itself. Default is COMPONENT_WORD. "KOREAN_MORPH_LEXER Example: Setting Composite Attribute (page 2-58)" describes the difference between NGRAM and COMPONENT_WORD.
morpheme	Specify TRUE or FALSE for morphological analysis. If set to FALSE, tokens are created from the words that are divided by delimiters such as white space in the document. Default is TRUE.
to_upper	Specify TRUE or FALSE to convert English to uppercase. Default is TRUE.
hanja	Specify TRUE to index hanja characters. If set to FALSE, hanja characters are converted to hangul characters. Default is FALSE.
long_word	Specify TRUE to index long words that have more than 16 syllables in Korean. Default is FALSE.
japanese	Specify TRUE to index Japanese characters in Unicode (only in the 2-byte area). Default is FALSE.
english	Specify TRUE to index alphanumeric strings. Default is TRUE.

2.5.8.4 KOREAN_MORPH_LEXER Limitations

Sentence and paragraph sections are not supported with the KOREAN_MORPH_LEXER.

2.5.8.5 KOREAN_MORPH_LEXER Example: Setting Composite Attribute

Use the composite attribute to control how composite nouns are indexed.

NGRAM Example

When you specify NGRAM for the composite attribute, composite nouns are indexed with all possible component tokens. For example, the following composite noun (*information processing institute*)

‘정보처리학회’;

is indexed as six tokens:

‘정보’, ‘처리’, ‘학회’, ‘정보처리’,
‘처리학회’, ‘정보처리학회’

Specify NGRAM indexing as follows:

```
begin
ctx_ddl.create_preference('my_lexer','KOREAN_MORPH_LEXER');
ctx_ddl.set_attribute('my_lexer','COMPOSITE','NGRAM');
end
```

To create the index:

```
create index koreanx on korean(text) indextype is ctxsys.context
parameters ('lexer my_lexer');
```

COMPONENT_WORD Example

When you specify COMPONENT_WORD for the composite attribute, composite nouns and their components are indexed. For example, the following composite noun (*information processing institute*)

‘정보처리학회’;

is indexed as four tokens:

‘정보’, ‘처리’, ‘학회’

Specify COMPONENT_WORD indexing as follows:

```
begin
ctx_ddl.create_preference('my_lexer','KOREAN_MORPH_LEXER');
ctx_ddl.set_attribute('my_lexer','COMPOSITE','COMPONENT_WORD');
end
```

To create the index:

```
create index koreanx on korean(text) indextype is ctxsys.context
parameters ('lexer my_lexer');
```

2.5.9 USER_LEXER

Use `USER_LEXER` to plug in your own language-specific lexing solution. This enables you to define lexers for languages that are not supported by Oracle Text. It also enables you to define a new lexer for a language that is supported but whose lexer is inappropriate for your application.

This section contains the following topics.

- [USER_LEXER Routines](#) (page 2-59)
- [USER_LEXER Limitations](#) (page 2-59)
- [USER_LEXER Attributes](#) (page 2-60)
- [INDEX_PROCEDURE](#) (page 2-60)
- [INPUT_TYPE](#) (page 2-60)
- [QUERY_PROCEDURE](#) (page 2-62)
- [Encoding Tokens as XML](#) (page 2-64)
- [XML Schema for No-Location_ User-defined Indexing Procedure](#) (page 2-64)
- [XML Schema for User-defined Indexing Procedure with Location](#) (page 2-67)
- [XML Schema for User-defined Lexer Query Procedure](#) (page 2-69)

2.5.9.1 USER_LEXER Routines

The user-defined lexer you register with Oracle Text is composed of two routines that you must supply:

Table 2-28 User-Defined Routines for USER_LEXER

User-Defined Routine	Description
Indexing Procedure	Stored procedure (PL/SQL) which implements the tokenization of documents and stop words. Output must be an XML document as specified in this section.
Query Procedure	Stored procedure (PL/SQL) which implements the tokenization of query words. Output must be an XML document as specified in this section.

2.5.9.2 USER_LEXER Limitations

The following features are not supported with the `USER_LEXER`:

- `CTX_DOC.GIST` and `CTX_DOC.THEMES`
- `CTX_QUERY.HFEEDBACK`
- `ABOUT` query operator
- `CTXRULE` index type
- `VGRAM` indexing algorithm

2.5.9.3 USER_LEXER Attributes

USER_LEXER has the following attributes:

Table 2-29 USER_LEXER Attributes

Attribute	Attribute Value
INDEX_PROCEDURE	Name of a stored procedure. No default provided.
INPUT_TYPE	VARCHAR2, CLOB. Default is CLOB.
QUERY_PROCEDURE	Name of a stored procedure. No default provided.

2.5.9.4 INDEX_PROCEDURE

This callback stored procedure is called by Oracle Text as needed to tokenize a document or a stop word found in the stoplist object.

Requirements

This procedure can be a PL/SQL stored procedure.

The index owner must have EXECUTE privilege on this stored procedure.

This stored procedure must not be replaced or dropped after the index is created. You can replace or drop this stored procedure after the index is dropped.

Parameters

Two different interfaces are supported for the user-defined lexer indexing procedure:

- [VARCHAR2 Interface](#) (page 2-61)
- [CLOB Interface](#) (page 2-61)

Restrictions

This procedure must not perform any of the following operations:

- Rollback
- Explicitly or implicitly commit the current transaction
- Enter any other transaction control statement
- Alter the session language or territory

The child elements of the root element tokens of the XML document returned must be in the same order as the tokens occur in the document or stop word being tokenized.

The behavior of this stored procedure must be deterministic with respect to all parameters.

2.5.9.5 INPUT_TYPE

Two different interfaces are supported for the User-defined lexer indexing procedure. One interface enables the document or stop word and the corresponding tokens encoded as XML to be passed as VARCHAR2 datatype whereas the other interface uses the CLOB datatype. This attribute indicates the interface implemented by the stored procedure specified by the INDEX_PROCEDURE attribute.

- [VARCHAR2 Interface](#) (page 2-61)
- [CLOB Interface](#) (page 2-61)

2.5.9.5.1 VARCHAR2 Interface

[Table 2-30](#) (page 2-61) describes the interface that enables the document or stop word from stoplist object to be tokenized to be passed as VARCHAR2 from Oracle Text to the stored procedure and for the tokens to be passed as VARCHAR2 as well from the stored procedure back to Oracle Text.

Your user-defined lexer indexing procedure should use this interface when all documents in the column to be indexed are smaller than or equal to 32512 bytes and the tokens can be represented by less than or equal to 32512 bytes. In this case the CLOB interface given in [Table 2-31](#) (page 2-62) can also be used, although the VARCHAR2 interface will generally perform faster than the CLOB interface.

This procedure must be defined with the following parameters:

Table 2-30 VARCHAR2 Interface for INDEX PROCEDURES

Parameter Position	Parameter Mode	Parameter Datatype	Description
1	IN	VARCHAR2	Document or stop <i>word</i> from stoplist object to be tokenized. If the document is larger than 32512 bytes then Oracle Text will report a document level indexing error.
2	IN OUT	VARCHAR2	Tokens encoded as XML. If the document contains no tokens, then either NULL must be returned or the tokens element in the XML document returned must contain no child elements. Byte length of the data must be less than or equal to 32512. To improve performance, use the NOCOPY hint when declaring this parameter. This passes the data by reference, rather than passing data by value. The XML document returned by this procedure should not include unnecessary whitespace characters (typically used to improve readability). This reduces the size of the XML document which in turn minimizes the transfer time. To improve performance, index_procedure should not validate the XML document with the corresponding XML schema at run-time. Note that this parameter is IN OUT for performance purposes. The stored procedure has no need to use the IN value.
3	IN	BOOLEAN	Oracle Text sets this parameter to TRUE when Oracle Text needs the character offset and character length of the tokens as found in the document being tokenized. Oracle Text sets this parameter to FALSE when Text is not interested in the character offset and character length of the tokens as found in the document being tokenized. This implies that the XML attributes off and len must not be used.

2.5.9.5.2 CLOB Interface

[Table 2-31](#) (page 2-62) describes the CLOB interface that enables the document or stop word from stoplist object to be tokenized to be passed as CLOB from Oracle Text to the

stored procedure and for the tokens to be passed as CLOB as well from the stored procedure back to Oracle Text.

The user-defined lexer indexing procedure should use this interface when at least one of the documents in the column to be indexed is larger than 32512 bytes or the corresponding tokens are represented by more than 32512 bytes.

Table 2-31 CLOB Interface for INDEX_PROCEDURE

Parameter Position	Parameter Mode	Parameter Datatype	Description
1	IN	CLOB	Document or stop <i>word</i> from stoplist object to be tokenized.
2	IN OUT	CLOB	<p>Tokens encoded as XML.</p> <p>If the document contains no tokens, then either NULL must be returned or the tokens element in the XML document returned must contain no child elements.</p> <p>To improve performance, use the NOCOPY hint when declaring this parameter. This passes the data by reference, rather than passing data by value.</p> <p>The XML document returned by this procedure should not include unnecessary whitespace characters (typically used to improve readability). This reduces the size of the XML document which in turn minimizes the transfer time.</p> <p>To improve performance, index_procedure should not validate the XML document with the corresponding XML schema at run-time.</p> <p>Note that this parameter is IN OUT for performance purposes. The stored procedure has no need to use the IN value. The IN value will always be a truncated CLOB.</p>
3	IN	BOOLEAN	<p>Oracle Text sets this parameter to TRUE when Oracle Text needs the character offset and character length of the tokens as found in the document being tokenized.</p> <p>Oracle Text sets this parameter to FALSE when Text is not interested in the character offset and character length of the tokens as found in the document being tokenized. This implies that the XML attributes off and len must not be used.</p>

The first and second parameters are temporary CLOBs. Avoid assigning these CLOB locators to other locator variables. Assigning the formal parameter CLOB locator to another locator variable causes a new copy of the temporary CLOB to be created resulting in a performance hit.

2.5.9.6 QUERY_PROCEDURE

This callback stored procedure is called by Oracle Text as needed to tokenize *words* in the query. A space-delimited group of characters (excluding the query operators) in the query will be identified by Oracle Text as a *word*.

Requirements

This procedure can be a PL/SQL stored procedure.

The index owner must have EXECUTE privilege on this stored procedure.

This stored procedure must not be replaced or be dropped after the index is created. You can replace or drop this stored procedure after the index is dropped.

Restrictions

This procedure must not perform any of the following operations:

- Rollback
- Explicitly or implicitly commit the current transaction
- Enter any other transaction control statement
- Alter the session language or territory

The child elements of the root element tokens of the XML document returned must be in the same order as the tokens occur in the query *word* being tokenized.

The behavior of this stored procedure must be deterministic with respect to all parameters.

Parameters

[Table 2-32](#) (page 2-63) describes the interface for the user-defined lexer query procedure:

Table 2-32 User-defined Lexer Query Procedure XML Schema Attributes

Parameter Position	Parameter Mode	Parameter Datatype	Description
1	IN	VARCHAR2	Query <i>word</i> to be tokenized.
2	IN	CTX_ULEXER.WILDCARD_TAB	<p>Character offsets of wildcard characters (%) and _ in the query <i>word</i>. If the query <i>word</i> passed in by Oracle Text does not contain any wildcard characters then this index-by table will be empty.</p> <p>The wildcard characters in the query <i>word</i> must be preserved in the tokens returned in order for the wildcard query feature to work properly.</p> <p>The character offset is 0 (zero) based. Offset information follows USC-2 codepoint semantics.</p>
3	IN OUT	VARCHAR2	<p>Tokens encoded as XML.</p> <p>If the query <i>word</i> contains no tokens then either NULL must be returned or the tokens element in the XML document returned must contain no child elements.</p> <p>The length of the data must be less-than or equal to 32512 bytes.</p>

2.5.9.7 Encoding Tokens as XML

The sequence of tokens returned by your stored procedure must be represented as an XML 1.0 document. The XML document must be valid with respect to the XML Schemas given in the following sections.

- [XML Schema for No-Location_ User-defined Indexing Procedure](#) (page 2-64)
- [XML Schema for User-defined Indexing Procedure with Location](#) (page 2-67)
- [XML Schema for User-defined Lexer Query Procedure](#) (page 2-69)

Limitations

To boost performance of this feature, the XML parser in Oracle Text will not perform validation and will not be a full-featured XML compliant parser. This implies that only minimal XML features will be supported. The following XML features are not supported:

- Document Type Declaration (for example, `<!DOCTYPE [. . .]>`) and therefore entity declarations. Only the following built-in entities can be referenced: lt, gt, amp, quot, and apos.
- CDATA sections.
- Comments.
- Processing Instructions.
- XML declaration (for example, `<?xml version="1.0" . . . ?>`).
- Namespaces.
- Use of elements and attributes other than those defined by the corresponding XML Schema.
- Character references (for example `ট`).
- `xml:space` attribute.
- `xml:lang` attribute

2.5.9.8 XML Schema for No-Location, User-defined Indexing Procedure

This section describes additional constraints imposed on the XML document returned by the user-defined lexer indexing procedure when the third parameter is `FALSE`. The XML document returned must be valid with respect to the following XML Schema:

```
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema">
```

```
  <xsd:element name="tokens">
    <xsd:complexType>
      <xsd:sequence>
        <xsd:choice minOccurs="0" maxOccurs="unbounded">
          <xsd:element name="eos" type="EmptyTokenType"/>
          <xsd:element name="eop" type="EmptyTokenType"/>
          <xsd:element name="num" type="xsd:token"/>
          <xsd:group ref="IndexCompositeGroup"/>
        </xsd:choice>
      </xsd:sequence>
    </xsd:complexType>
```



```

</xsd:element>

<!--
Enforce constraint that compMem element must be preceeded by word element
or compMem element for indexing
-->
<xsd:group name="IndexCompositeGroup">
  <xsd:sequence>
    <xsd:element name="word" type="xsd:token"/>
    <xsd:element name="compMem" type="xsd:token" minOccurs="0"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:group>

<!-- EmptyTokenType defines an empty element without attributes -->
<xsd:complexType name="EmptyTokenType"/>

</xsd:schema>

```

Here are some of the constraints imposed by this XML Schema:

- The root element is tokens. This is mandatory. It has no attributes.
- The root element can have zero or more child elements. The child elements can be one of the following elements: eos, eop, num, word, and compMem. Each of these represent a specific type of token.
- The compMem element must be preceded by a word element or a compMem element.
- The eos and eop elements have no attributes and must be empty elements.
- The num, word, and compMem elements have no attributes. Oracle Text will normalize the content of these elements as follows: convert whitespace characters to space characters, collapse adjacent space characters to a single space character, remove leading and trailing spaces, perform entity reference replacement, and truncate to 64 bytes.

[Table 2-33](#) (page 2-65) describes the element names defined in the preceding XML Schema.

Table 2-33 User-defined Lexer Indexing Procedure XML Schema Element Names

Element	Description
word	This element represents a simple word token. The content of the element is the word itself. Oracle Text does the work of identifying this token as being a stop word or non-stop word and processing it appropriately.
num	This element represents an arithmetic number token. The content of the element is the arithmetic number itself. Oracle Text treats this token as a stop word if the stoplist preference has NUMBERS added as the stopclass. Otherwise this token is treated the same way as the word token. Supporting this token type is optional. Without support for this token type, adding the NUMERBS stopclass will have no effect.
eos	This element represents end-of-sentence token. Oracle Text uses this information so that it can support WITHIN SENTENCE queries. Supporting this token type is optional. Without support for this token type, queries against the SENTENCE section will not work as expected.

Table 2-33 (Cont.) User-defined Lexer Indexing Procedure XML Schema Element Names

Element	Description
eop	This element represents end-of-paragraph token. Oracle Text uses this information so that it can support WITHIN PARAGRAPH queries. Supporting this token type is optional. Without support for this token type, queries against the PARAGRAPH section will not work as expected.
compMem	Same as the word element, except that the implicit word offset is the same as the previous word token. Support for this token type is optional.

Examples

Document: Vom Nordhauptbahnhof und aus der Innenstadt zum Messegelände.

Tokens:

```
<tokens>
  <word> VOM </word>
  <word> NORDHAUPTBAHNHOF </word>
  <compMem>NORD</compMem>
  <compMem>HAUPT </compMem>
  <compMem>BAHNHOF </compMem>
  <compMem>HAUPTBAHNHOF </compMem>
  <word> UND </word>
  <word> AUS </word>
  <word> DER </word>
  <word> INNENSTADT </word>
  <word> ZUM </word>
  <word> MESSEGELENDE </word>
  <eos/>
</tokens>
```

Document: Oracle Database 11g Release 1

Tokens:

```
<tokens>
  <word> ORACLE11G</word>
  <word> RELEASE </word>
  <num> 1 </num>
</tokens>
```

Document: WHERE salary<25000.00 AND job = 'F&B Manager'

Tokens:

```
<tokens>
  <word> WHERE </word>
  <word> salary<25000.00 </word>
  <word> AND </word>
  <word> job </word>
  <word> F&B </word>
  <word> Manager </word>
</tokens>
```

2.5.9.9 XML Schema for User-defined Indexing Procedure with Location

This section describes additional constraints imposed on the XML document returned by the user-defined lexer indexing procedure when the third parameter is TRUE. The XML document returned must be valid according to the following XML schema:

```
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema">

  <xsd:element name="tokens">
    <xsd:complexType>
      <xsd:sequence>
        <xsd:choice minOccurs="0" maxOccurs="unbounded">
          <xsd:element name="eos" type="EmptyTokenType"/>
          <xsd:element name="eop" type="EmptyTokenType"/>
          <xsd:element name="num" type="DocServiceTokenType"/>
          <xsd:group ref="DocServiceCompositeGroup"/>
        </xsd:choice>
      </xsd:sequence>
    </xsd:complexType>
  </xsd:element>

  <!--
  Enforce constraint that compMem element must be preceeded by word element
  or compMem element for document service
  -->
  <xsd:group name="DocServiceCompositeGroup">
    <xsd:sequence>
      <xsd:element name="word" type="DocServiceTokenType"/>
      <xsd:element name="compMem" type="DocServiceTokenType" minOccurs="0"
        maxOccurs="unbounded"/>
    </xsd:sequence>
  </xsd:group>

  <!-- EmptyTokenType defines an empty element without attributes -->
  <xsd:complexType name="EmptyTokenType"/>

  <!--
  DocServiceTokenType defines an element with content and mandatory attributes
  -->
  <xsd:complexType name="DocServiceTokenType">
    <xsd:simpleContent>
      <xsd:extension base="xsd:token">
        <xsd:attribute name="off" type="OffsetType" use="required"/>
        <xsd:attribute name="len" type="xsd:unsignedShort" use="required"/>
      </xsd:extension>
    </xsd:simpleContent>
  </xsd:complexType>

  <xsd:simpleType name="OffsetType">
    <xsd:restriction base="xsd:unsignedInt">
      <xsd:maxInclusive value="2147483647"/>
    </xsd:restriction>
  </xsd:simpleType>

</xsd:schema>
```

Some of the constraints imposed by this XML Schema are as follows:

- The root element is tokens. This is mandatory. It has no attributes.

- The root element can have zero or more child elements. The child elements can be one of the following elements: `eos`, `eop`, `num`, `word`, and `compMem`. Each of these represent a specific type of token.
- The `compMem` element must be preceded by a `word` element or a `compMem` element.
- The `eos` and `eop` elements have no attributes and must be empty elements.
- The `num`, `word`, and `compMem` elements have two mandatory attributes: `off` and `len`. Oracle Text will normalize the content of these elements as follows: convert whitespace characters to space characters, collapse adjacent space characters to a single space character, remove leading and trailing spaces, perform entity reference replacement, and truncate to 64 bytes.
- The `off` attribute value must be an integer between 0 and 2147483647 inclusive.
- The `len` attribute value must be an integer between 0 and 65535 inclusive.

[Table 2-33](#) (page 2-65) describes the element types defined in the preceding XML Schema.

[Table 2-34](#) (page 2-68) describes the attributes defined in the preceding XML Schema.

Table 2-34 User-defined Lexer Indexing Procedure XML Schema Attributes

Attribute	Description
<code>off</code>	<p>This attribute represents the character offset of the token as it appears in the document being tokenized.</p> <p>The offset is with respect to the character document passed to the user-defined lexer indexing procedure, not the document fetched by the datastore. The document fetched by the datastore may be pre-processed by the filter object or the section group object, or both, before being passed to the user-defined lexer indexing procedure.</p> <p>The offset of the first character in the document being tokenized is 0 (zero). Offset information follows USC-2 codepoint semantics.</p>
<code>len</code>	<p>This attribute represents the character length (same semantics as SQL function <code>LENGTH</code>) of the token as it appears in the document being tokenized.</p> <p>The length is with respect to the character document passed to the user-defined lexer indexing procedure, not the document fetched by the datastore. The document fetched by the datastore may be pre-processed by the filter object or the section group object before being passed to the user-defined lexer indexing procedure.</p> <p>Length information follows USC-2 codepoint semantics.</p>

Sum of `off` attribute value and `len` attribute value must be less than or equal to the total number of characters in the document being tokenized. This is to ensure that the document offset and characters being referenced are within the document boundary.

Example

Document: User-defined Lexer.

Tokens:

```
<tokens>
  <word off="0" len="4"> USE </word>
```

```

<word off="5" len="7"> DEF </word>
<word off="13" len="5"> LEX </word>
<eos/>
</tokens>

```

2.5.9.10 XML Schema for User-defined Lexer Query Procedure

This section describes additional constraints imposed on the XML document returned by the user-defined lexer query procedure. The XML document returned must be valid with respect to the following XML Schema:

```

<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema">

  <xsd:element name="tokens">
    <xsd:complexType>
      <xsd:sequence>
        <xsd:choice minOccurs="0" maxOccurs="unbounded">
          <xsd:element name="num" type="QueryTokenType"/>
          <xsd:group ref="QueryCompositeGroup"/>
        </xsd:choice>
      </xsd:sequence>
    </xsd:complexType>
  </xsd:element>

  <!--
  Enforce constraint that compMem element must be preceeded by word element
  or compMem element for query
  -->
  <xsd:group name="QueryCompositeGroup">
    <xsd:sequence>
      <xsd:element name="word" type="QueryTokenType"/>
      <xsd:element name="compMem" type="QueryTokenType" minOccurs="0"
        maxOccurs="unbounded"/>
    </xsd:sequence>
  </xsd:group>

  <!--
  QueryTokenType defines an element with content and with an optional attribute
  -->
  <xsd:complexType name="QueryTokenType">
    <xsd:simpleContent>
      <xsd:extension base="xsd:token">
        <xsd:attribute name="wildcard" type="WildcardType" use="optional"/>
      </xsd:extension>
    </xsd:simpleContent>
  </xsd:complexType>

  <xsd:simpleType name="WildcardType">
    <xsd:restriction base="WildcardBaseType">
      <xsd:minLength value="1"/>
      <xsd:maxLength value="64"/>
    </xsd:restriction>
  </xsd:simpleType>

  <xsd:simpleType name="WildcardBaseType">
    <xsd:list>
      <xsd:simpleType>
        <xsd:restriction base="xsd:unsignedShort">
          <xsd:maxInclusive value="378"/>
        </xsd:restriction>
      </xsd:simpleType>
    </xsd:list>
  </xsd:simpleType>

```

```

    </xsd:list>
  </xsd:simpleType>

</xsd:schema>

```

Here are some of the constraints imposed by this XML Schema:

- The `root` element is `tokens`. This is mandatory. It has no attributes.
- The `root` element can have zero or more child elements. The child elements can be one of the following elements: `num` and `word`. Each of these represent a specific type of token.
- The `compMem` element must be preceded by a `word` element or a `compMem` element.

The purpose of `compMem` is to enable `USER_LEXER` queries to return multiple forms for a single query. For example, if a user-defined lexer indexes the word `bank` as `BANK (FINANCIAL)` and `BANK (RIVER)`, the query procedure can return the first term as a `word` and the second as a `compMem` element:

```

<tokens>
  <word>BANK ( RIVER ) </word>
  <compMem>BANK ( FINANCIAL ) </compMem>
</tokens>

```

See [Table 2-35](#) (page 2-70), "[Table 2-35](#) (page 2-70)" for more on the `compMem` element.

- The `num` and `word` elements have a single optional attribute: `wildcard`. Oracle Text will normalize the content of these elements as follows: convert whitespace characters to space characters, collapse adjacent space characters to a single space character, remove leading and trailing spaces, perform entity reference replacement, and truncate to 64 bytes.
- The `wildcard` attribute value is a white-space separated list of integers. The minimum number of integers is 1 and the maximum number of integers is 64. The value of the integers must be between 0 and 378 inclusive. The integers in the list can be in any order.

[Table 2-33](#) (page 2-65) describes the element types defined in the preceding XML Schema.

[Table 2-35](#) (page 2-70) describes the attribute defined in the preceding XML Schema.

Table 2-35 User-defined Lexer Query Procedure XML Schema Attributes

Attribute	Description
<code>compMem</code>	Same as the <code>word</code> element, but its implicit word offset is the same as the previous <code>word</code> token. Oracle Text will equate this token with the previous <code>word</code> token and with subsequent <code>compMem</code> tokens using the query <code>EQUIV</code> operator.

Table 2-35 (Cont.) User-defined Lexer Query Procedure XML Schema Attributes

Attribute	Description
wildcard	<p>Any % or _ characters in the query which are not escaped by the user are considered wildcard characters because they are replaced by other characters. These wildcard characters in the query must be preserved during tokenization in order for the wildcard query feature to work properly. This attribute represents the character offsets (same semantics as SQL function LENGTH) of wildcard characters in the content of the element. Oracle Text will adjust these offsets for any normalization performed on the content of the element. The characters pointed to by the offsets must either be % or _ characters.</p> <p>The offset of the first character in the content of the element is 0. Offset information follows USC-2 codepoint semantics.</p> <p>If the token does not contain any wildcard characters then this attribute must not be specified.</p>

Examples

Query *word*: pseudo-%morph%

Tokens:

```
<tokens>
  <word> PSEUDO </word>
  <word wildcard="1 7"> %MORPH% </word>
</tokens>
```

Query *word*: <%>

Tokens:

```
<tokens>
  <word wildcard="5"> &lt;%&gt; </word>
</tokens>
```

2.5.10 WORLD_LEXER

Use the WORLD_LEXER to index text columns that contain documents of different languages. For example, use this lexer to index a text column that stores English, Japanese, and German documents.

WORLD_LEXER differs from MULTI_LEXER in that WORLD_LEXER automatically detects the language(s) of a document. Unlike MULTI_LEXER, WORLD_LEXER does not require you to have a language column in your base table nor to specify the language column when you create the index. Moreover, it is not necessary to use sub-lexers, as with MULTI_LEXER. (See "[MULTI_LEXER](#) (page 2-49)".)

WORLD_LEXER supports all database character sets, and for languages whose character sets are Unicode-based, it supports the Unicode 5.0 standard. For a list of languages that WORLD_LEXER can work with, see "[World Lexer Features](#) (page D-5)".

The WORLD_VGRAM_LEXER has the following attribute:

Table 2-36 *WORLD_LEXER Attribute*

Attribute	Attribute Value
<code>mixed_case</code>	Enable mixed-case (upper- and lower-case) searches of text (for example, <i>cat</i> and <i>Cat</i>). Allowable values are YES and NO (default).

The following is an example of creating an index using `WORLD_LEXER`.

```
exec ctx_ddl.create_preference('MYLEXER', 'world_lexer');
create index doc_idx on doc(data)
  indextype is CONTEXT
  parameters ('lexer MYLEXER
              stoplist CTXSYS.EMPTY_STOPLIST');
```

2.6 Wordlist Type

Use the wordlist preference to enable the query options such as stemming, fuzzy matching for your language. You can also use the wordlist preference to enable substring and prefix indexing, which improves performance for wildcard queries with `CONTAINS` and `CATSEARCH`.

To create a wordlist preference, you must use `BASIC_WORDLIST`, which is the only type available.

- [BASIC_WORDLIST](#) (page 2-72)
- [BASIC_WORDLIST Example](#) (page 2-79)

2.6.1 BASIC_WORDLIST

Use `BASIC_WORDLIST` type to enable stemming and fuzzy matching or to create prefix indexes with Text indexes.

See Also:

[Oracle Text CONTAINS Query Operators](#) (page 3-1)

[Table 2-37](#) (page 2-73) lists the attributes for `BASIC_WORDLIST`.

Table 2-37 BASIC_WORDLIST Attributes

Attribute	Attribute Values
<code>stemmer</code>	<p>Specify which language stemmer to use. You can specify one of the following stemmers:</p> <p>NULL (no stemming)</p> <p>ENGLISH (English inflectional)</p> <p>DERIVATIONAL (English derivational)</p> <p>DUTCH</p> <p>FRENCH</p> <p>GERMAN</p> <p>ITALIAN</p> <p>SPANISH</p> <p>AUTO (Automatic language-detection for stemming, derived from the database session language. If the database session language is AMERICAN or ENGLISH, then the ENGLISH stemmer is used. Does not auto-detect JAPANESE.)</p> <p>JAPANESE</p>
<code>fuzzy_match</code>	<p>Specify which fuzzy matching cluster to use. You can specify one of the following types:</p> <p>AUTO (Automatic language detection for stemming.)</p> <p>CHINESE_VGRAM</p> <p>DUTCH</p> <p>ENGLISH</p> <p>FRENCH</p> <p>GENERIC</p> <p>GERMAN</p> <p>ITALIAN</p> <p>JAPANESE_VGRAM</p> <p>KOREAN</p> <p>OCR</p> <p>SPANISH</p>
<code>fuzzy_score</code>	<p>Specify a default lower limit of fuzzy score. Specify a number between 1 and 80. Text with scores below this number is not returned. Default is 60.</p>
<code>fuzzy_numresults</code>	<p>Specify the maximum number of fuzzy expansions. Use a number between 0 and 5,000. Default is 100.</p>
<code>substring_index</code>	<p>Specify TRUE for Oracle Text to create a substring index. A substring index improves left-truncated and double-truncated wildcard queries such as <code>%ing</code> or <code>%benz%</code>. Default is FALSE.</p>
<code>prefix_index</code>	<p>Specify TRUE to enable prefix indexing. Prefix indexing improves performance for right truncated wildcard searches such as <code>TO%</code>. Default is FALSE.</p>
<code>prefix_min_length</code>	<p>Specify the minimum length of indexed prefixes. Default is 1. Length information must follow USC-2 codepoint semantics.</p>

Table 2-37 (Cont.) BASIC_WORDLIST Attributes

Attribute	Attribute Values
prefix_max_length	Specify the maximum length of indexed prefixes. Default is 64. Length information must follow USC-2 codepoint semantics.
wildcard_maxterms	Specify the maximum number of terms in a wildcard expansion. The maximum value is 50000 and the default value is 20000. If you specify a value of 0, then the number of wildcard expansions will be unbounded. Note that when set to 0, the system may run out of memory due to the high number of wildcard expansions.
ndata_base_letter	Specify whether characters that have diacritical marks are converted to their base form before being stored in the Text index or queried by the NDATA operator. FALSE (default) or TRUE When set to FALSE, no base lettering is used.
ndata_altername_spelling	Specify whether to enable alternate spelling for German, Danish, and Swedish. Enabling alternate spelling allows you to index NDATA section data and query using the NDATA operator in alternate form. FALSE (default) or TRUE When set to FALSE, no alternate spelling is used.
ndata_thesaurus	Name of the thesaurus used for alternate name expansion.
ndata_join_particles	A list of colon-separated name particles that can be joined with a name that follows them.

stemmer

Specify the stemmer used for word stemming in Text queries. When you do not specify a value for STEMMER, the default is ENGLISH.

Specify AUTO for the system to automatically set the stemming language according to the language setting of the database session. If the database language is AMERICAN or ENGLISH, then the ENGLISH stemmer is automatically used. Otherwise, the stemmer that maps to the database session language is used.

When there is no stemmer for a language, the default is NULL. With the NULL stemmer, the stem operator is ignored in queries.

You can create your own stemming user-dictionary. See "[Stemming User-Dictionaries](#) (page 2-47)" for more information.

Note:

The STEMMER attribute of BASIC_WORDLIST preference will be ignored if:

1. INDEX_STEMS attribute of BASIC_LEXER preference is set to BOKMAL, CATALAN, CROATIAN, CZECH, DANISH, FINNISH, GREEK, HEBREW, HUNGARIAN, NYNORSK, POLISH, PORTUGUESE, ROMANIAN, RUSSIAN, SERBIAN, SLOVAK, SLOVENIAN, SWEDISH, ENGLISH_NEW, DERIVATIONAL_NEW, DUTCH_NEW, FRENCH_NEW, GERMAN_NEW, ITALIAN_NEW, or SPANISH_NEW.

Or

2. INDEX_STEMS attribute of AUTO_LEXER preference is set to YES.

Or

3. The database session language causes MULTI_LEXER to choose a SUB_LEXER with the same setting as 1 or 2 above.

In these cases, the same stemmer that is used by the BASIC_LEXER or AUTO_LEXER during indexing will be used to determine the stem of the query term during query.

fuzzy_match

Specify which fuzzy matching routines are used for the column. Fuzzy matching is currently supported for English, Japanese, and, to a lesser extent, the Western European languages.

Note:

The fuzzy_match attributes value for Chinese and Korean are dummy attribute values that prevent the English and Japanese fuzzy matching routines from being used on Chinese and Korean text.

The default for fuzzy_match is GENERIC.

Specify AUTO for the system to automatically set the fuzzy matching language according to language setting of the session.

fuzzy_score

Specify a default lower limit of fuzzy score. Specify a number between 0 and 80. Text with scores below this number are not returned. The default is 60.

Fuzzy score is a measure of how close the expanded word is to the query word. The higher the score the better the match. Use this parameter to limit fuzzy expansions to the best matches.

fuzzy_numresults

Specify the maximum number of fuzzy expansions. Use a number between 0 and 5000. The default is 100.

Setting a fuzzy expansion limits the expansion to a specified number of the best matching words.

substring_index

Specify `TRUE` for Oracle Text to create a substring index. A substring index improves performance for left-truncated or double-truncated wildcard queries such as `%ing` or `%benz%`. The default is `false`.

Substring indexing has the following impact on indexing and disk resources:

- Index creation and DML processing is up to 4 times slower
- Index creation with `substring_index` enabled requires more rollback segments during index flushes than with substring index off. Oracle recommends that you do either of the following when creating a substring index:
 - Make available double the usual rollback or
 - Decrease the index memory to reduce the size of the index flushes to disk

prefix_index

Specify `yes` to enable prefix indexing. Prefix indexing improves performance for right truncated wildcard searches such as `TO%`. Default is `NO`.

Note:

Enabling prefix indexing increases index size.

Prefix indexing chops up tokens into multiple prefixes to store in the \$I table. For example, words `TOKEN` and `TOY` are normally indexed as follows in the \$I table:

Token	Type	Information
TOKEN	0	DOCID 1 POS 1
TOY	0	DOCID 1 POS 3

With prefix indexing, Oracle Text indexes the prefix substrings of these tokens as follows with a new token type of 6:

Token	Type	Information
TOKEN	0	DOCID 1 POS 1
TOY	0	DOCID 1 POS 3
T	6	DOCID 1 POS 1 POS 3
TO	6	DOCID 1 POS 1 POS 3
TOK	6	DOCID 1 POS 1
TOKE	6	DOCID 1 POS 1
TOKEN	6	DOCID 1 POS 1
TOY	6	DOCID 1 POS 3

Wildcard searches such as `TO%` are now faster because Oracle Text does no expansion of terms and merging of result sets. To obtain the result, Oracle Text need only examine the (TO,6) row.

prefix_min_length

Specify the minimum length of indexed prefixes. Default is 1.

For example, setting `prefix_min_length` to 3 and `prefix_max_length` to 5 indexes all prefixes between 3 and 5 characters long.

Note:

A wildcard search whose pattern is below the minimum length or above the maximum length is searched using the slower method of equivalence expansion and merging.

prefix_max_length

Specify the maximum length of indexed prefixes. Default is 64.

For example, setting `prefix_min_length` to 3 and `prefix_max_length` to 5 indexes all prefixes between 3 and 5 characters long.

Note:

A wildcard search whose pattern is below the minimum length or above the maximum length is searched using the slower method of equivalence expansion and merging.

wildcard_maxterms

Specify the maximum number of terms in a wildcard (%) expansion. Use this parameter to keep wildcard query performance within an acceptable limit. When the wildcard query expansion exceeds this number, Oracle Text returns the following error:

```
ORA-29902: error in executing ODCIIndexStart() routine
ORA-20000: Oracle Text error:
DRG-51030: wildcard query expansion resulted in too many terms
```

In such cases, use a more restrictive query so that it results in fewer matches or increase the value of `wildcard_maxterms`. You can also set `wildcard_maxterms` to 0 to ignore the limit.

Note:

If the value of `wildcard_maxterms` is set as 0, the query might fail and returns the above error again if too many terms are matched by the wildcard search term.

You can also capture the above error and display your own less terse message.

Note:

Search terms with wildcard queries having only the wildcard character, for example: `%`, `%_%`, and `%_`, are threaded as stopwords.

ndata_base_letter

Specify whether characters that have diacritical marks (umlauts, cedillas, acute accents, and so on) are converted to their base form before being stored in the Text index or queried by the NDATA operator. The default is FALSE (base-letter conversion disabled). For more information on base-letter conversions, see "[Base-Letter Conversion](#) (page 17-2)".

ndata_alternate_spelling

Specify whether to enable alternate spelling for German, Danish, and Swedish. Enabling alternate spelling allows you to index NDATA section data and query using the NDATA operator in alternate form.

When `ndata_base_letter` is enabled at the same time as `ndata_alternate_spelling`, NDATA section data is serially transformed first by alternate spelling and then by base lettering. For more information about the alternate spelling conventions Oracle Text uses, see "[Alternate Spelling](#) (page 17-2)".

ndata_thesaurus

Specify a name of the thesaurus used for alternate name expansion. The indexing engine expands names in documents using synonym rings in the thesaurus. A user should make use of homographic disambiguating feature of the thesaurus to distinguish common nicknames.

An example is:

```
Albert
  SYN Al
  SYN Bert
Alfred
  SYN Al
  SYN Fred
```

A simple definition such as the above will put Albert, Alfred, Al, Bert, and Fred into the same synonym ring. This will cause an unexpected expansion such that the expansion of Bert includes Fred. To prevent this, you can use homographic disambiguation as in:

```
Albert
  SYN Al (Albert)
  SYN Bert (Albert)
Alfred
  SYN Al (Alfred)
  SYN Fred (Alfred)
```

This forms two synonym rings, Albert-Al-Bert and Alfred-Al-Fred. Thus, the expansion of Bert no longer includes Fred. A more detailed example is:

```
begin
  ctx_ddl.create_preference('NDAT_PREF', 'BASIC_WORDLIST');
  ctx_ddl.set_attribute('NDATA_PREF', 'NDATA_ALTERNATE_SPELLING', 'FALSE');
  ctx_ddl.set_attribute('NDATA_PREF', 'NDATA_BASE_LETTER', 'TRUE');
  ctx_ddl.set_attribute('NDATA_PREF', 'NDATA_THESAURUS', 'NICKNAMES');
end;
```

Note:

A sample thesaurus for names can be found in the \$ORACLE_HOME/ctx/sample/thes directory. This file is dr0thsnames.txt.

ndata_join_particles

Specify a list of colon-separated name particles that can be joined with a name that follows them. A name particle, such as da, is written separately from or joined with its following name like da Vinci or daVinci. The indexing engine generates index data for both separated and join versions of a name when it finds a name particle specified in this preference. The same happens in the query processing for better recall.

2.6.2 BASIC_WORDLIST Example

The following example shows the use of the BASIC_WORDLIST type.

- [Enabling Fuzzy Matching and Stemming](#) (page 2-79)
- [Enabling Sub-string and Prefix Indexing](#) (page 2-79)
- [Setting Wildcard Expansion Limit](#) (page 2-80)

2.6.2.1 Enabling Fuzzy Matching and Stemming

The following example enables stemming and fuzzy matching for English. The preference STEM_FUZZY_PREF sets the number of expansions to the maximum allowed. This preference also instructs the system to create a substring index to improve the performance of double-truncated searches.

```
begin
  ctx_ddl.create_preference('STEM_FUZZY_PREF', 'BASIC_WORDLIST');
  ctx_ddl.set_attribute('STEM_FUZZY_PREF', 'FUZZY_MATCH', 'ENGLISH');
  ctx_ddl.set_attribute('STEM_FUZZY_PREF', 'FUZZY_SCORE', '0');
  ctx_ddl.set_attribute('STEM_FUZZY_PREF', 'FUZZY_NUMRESULTS', '5000');
  ctx_ddl.set_attribute('STEM_FUZZY_PREF', 'SUBSTRING_INDEX', 'TRUE');
  ctx_ddl.set_attribute('STEM_FUZZY_PREF', 'STEMMER', 'ENGLISH');
end;
```

To create the index in SQL, enter the following statement:

```
create index fuzzy_stem_subst_idx on mytable ( docs )
  indextype is ctxsys.context parameters ('Wordlist STEM_FUZZY_PREF');
```

2.6.2.2 Enabling Sub-string and Prefix Indexing

The following example sets the wordlist preference for prefix and sub-string indexing. For prefix indexing, it specifies that Oracle Text create token prefixes between 3 and 4 characters long:

```
begin

  ctx_ddl.create_preference('mywordlist', 'BASIC_WORDLIST');
  ctx_ddl.set_attribute('mywordlist', 'PREFIX_INDEX', 'TRUE');
  ctx_ddl.set_attribute('mywordlist', 'PREFIX_MIN_LENGTH', 3);
  ctx_ddl.set_attribute('mywordlist', 'PREFIX_MAX_LENGTH', 4);
  ctx_ddl.set_attribute('mywordlist', 'SUBSTRING_INDEX', 'YES');

end;
```

2.6.2.3 Setting Wildcard Expansion Limit

Use the `wildcard_maxterms` attribute to set the maximum allowed terms in a wildcard expansion.

```
--- create a sample table
drop table quick ;
create table quick
(
    quick_id number primary key,
    text      varchar(80)
);

--- insert a row with 10 expansions for 'tire%'
insert into quick ( quick_id, text )
values ( 1, 'tire tirea tireb tirec tired tiree tiref tireg tireh tirei tirej');
commit;

--- create an index using wildcard_maxterms=100
begin
    Ctx_Ddl.Create_Preference('wildcard_pref', 'BASIC_WORDLIST');
    ctx_ddl.set_attribute('wildcard_pref', 'wildcard_maxterms', 100) ;
end;
/
create index wildcard_idx on quick(text)
    indextype is ctxsys.context
    parameters ('Wordlist wildcard_pref') ;

--- query on 'tire%' - should work fine
select quick_id from quick
    where contains ( text, 'tire%' ) > 0;

--- now re-create the index with wildcard_maxterms=5

drop index wildcard_idx ;

begin
    Ctx_Ddl.Drop_Preference('wildcard_pref');
    Ctx_Ddl.Create_Preference('wildcard_pref', 'BASIC_WORDLIST');
    ctx_ddl.set_attribute('wildcard_pref', 'wildcard_maxterms', 5) ;
end;
/

create index wildcard_idx on quick(text)
    indextype is ctxsys.context
    parameters ('Wordlist wildcard_pref') ;

--- query on 'tire%' gives "wildcard query expansion resulted in too many terms"
select quick_id from quick
    where contains ( text, 'tire%' ) > 0;
```

2.7 Storage Types

Use the storage preference to specify tablespace and creation parameters for tables associated with a Text index. The system provides a single storage type called `BASIC_STORAGE`:

Table 2-38 Storage Types

Type	Description
BASIC_STORAGE (page 2-81)	Indexing type used to specify the tablespace and creation parameters for the database tables and indexes that constitute a Text index.

2.7.1 BASIC_STORAGE

The BASIC_STORAGE indexing type specifies the tablespace and creation parameters for the database tables and indexes that constitute a Text index.

The clause you specify is added to the internal CREATE TABLE (CREATE INDEX for the i_index_clause) statement at index creation. You can specify most allowable clauses, such as storage, LOB storage, or partitioning. However, you cannot specify an index organized table clause.

This section contains the following topics.

- [BASIC_STORAGE Attributes](#) (page 2-81)
- [BASIC_STORAGE Default Behavior](#) (page 2-85)
- [BASIC_STORAGE Examples](#) (page 2-85)

See Also:

For more information about how to specify CREATE TABLE and CREATE INDEX statements, see *Oracle Database SQL Language Reference*.

2.7.1.1 BASIC_STORAGE Attributes

BASIC_STORAGE has the attributes specified in [Table 2-39](#) (page 2-81).

Table 2-39 BASIC_STORAGE Attributes

Attribute	Attribute Value
big_io	<p>Parameter clause to improve the query performance for the CONTEXT index that is extensively used for IO operations. It uses SECUREFILES, and hence the tablespace must use automatic segment space management (ASSM). This clause mainly improves the query performance for rotational disks, where seeks are expensive compared to serial reads. Creating an index with the BIG_IO index option requires the CREATE TRIGGER privilege, as a temporary trigger is created during the indexing process. There is not much of a query performance improvement when the data storage is on solid state disks.</p> <p>Set it to YES to enable the BIG_IO index option for the CONTEXT index. The default is NO.</p>

Table 2-39 (Cont.) BASIC_STORAGE Attributes

Attribute	Attribute Value
d_table_clause	<p>Parameter clause to specify the storage clause for the \$D table.</p> <p>This clause may be specified if the forward index feature is being used. The forward index feature is used to increase the query performance while calculating snippets.</p> <p>If the d_table_clause is manually set, then it is recommended that you choose SecureFiles with high compression for the document blob column doc of the \$D table. If the d_table_clause is not set, then the document blob uses SecureFiles by default, if the index owner's default tablespace is ASSM and the database compatible parameter is 11.0 or higher.</p> <p>The \$D table is created to save a copy of a document into the index by either specifying a save_copy column or by specifying the save_copy storage attribute.</p>
e_table_clause	<p>Parameter clause for dr\$indexname\$E table creation. Used to specify the storage and tablespace clauses to add to the end of the internal CREATE TABLE statement.</p>
forward_index	<p>Parameter clause to improve the performance of the following CTX_DOC package procedures:</p> <ul style="list-style-type: none"> ctx_doc.snippet ctx_doc.highlight ctx_doc.markup <p>Set it to TRUE to enable the forward index feature. This creates the \$O table. The \$O table stores the mapping information from the token offsets in the \$I table to character offsets in the indexed documents.</p> <p>The default is FALSE.</p>
g_index_clause	<p>Parameter clause for the \$H btree index on the \$G table.</p> <p>Specify the storage and tablespace clauses to add to the end of the internal CREATE INDEX statement.</p> <p>When a CONTEXT index is created with the STAGE_ITAB index option, an empty \$G table is created with the \$H btree index on it. Use the g_index_clause clause in conjunction with the STAGE_ITAB index option for improving the query performance for the CONTEXT index that is extensively used for DML operations.</p>
g_table_clause	<p>Parameter clause for the \$G table.</p> <p>Specify the storage and tablespace clauses to add to the end of the internal CREATE TABLE statement.</p> <p>When a CONTEXT index is created with the STAGE_ITAB index option, an empty \$G table is created with the \$H btree index on it. Use the g_table_clause clause in conjunction with the STAGE_ITAB index option for improving the query performance for the CONTEXT index that is extensively used for DML operations.</p>
i_index_clause	<p>Parameter clause for dr\$indexname\$X index creation. Specify storage and tablespace clauses to add to the end of the internal CREATE INDEX statement. The default clause is: 'COMPRESS 2', which instructs Oracle Text to compress this index table.</p> <p>If you choose to override the default, Oracle recommends including COMPRESS 2 in your parameter clause to compress this table, because such compression saves disk space and helps query performance.</p>

Table 2-39 (Cont.) BASIC_STORAGE Attributes

Attribute	Attribute Value
<code>i_rowid_index_clause</code>	<p>Parameter clause to specify the storage clause for the \$R index on <code>dr\$rowid</code> column of the \$I table. Specify storage and tablespace clauses to add to the end of the internal <code>CREATE INDEX</code> statement.</p> <p>This clause is only used by the CTXCAT index type.</p>
<code>i_table_clause</code>	<p>Parameter clause for <code>dr\$indexname\$I</code> table creation. Specify storage and tablespace clauses to add to the end of the internal <code>CREATE TABLE</code> statement.</p> <p>The I table is the index data table.</p> <p>Note: Oracle strongly recommends that you do not specify "disable storage in row" for \$I LOBs, as this will greatly degrade the query performance.</p>
<code>k_table_clause</code>	<p>Parameter clause for <code>dr\$indexname\$K</code> table creation. Specify storage and tablespace clauses to add to the end of the internal <code>CREATE TABLE</code> statement.</p> <p>The K table is the keymap table.</p>
<code>n_table_clause</code>	<p>Parameter clause for <code>dr\$indexname\$N</code> table creation. Specify storage and tablespace clauses to add to the end of the internal <code>CREATE TABLE</code> statement.</p> <p>The N table is the negative list table.</p>
<code>o_table_clause</code>	<p>Parameter clause to specify the storage clause for the \$O table.</p> <p>This clause may be specified if the forward index feature is being used. The forward index feature is used to increase the query performance while calculating snippets.</p> <p>If the <code>o_table_clause</code> is manually set, then it is recommended that you choose SecureFiles with high compression for the document blob column mapping of the \$O table. If the <code>o_table_clause</code> is not set, then the document blob uses SecureFiles by default, if the index owner's default tablespace is ASSM and the database compatible parameter is 11.0 or higher.</p> <p>The \$O table is created when the forward index feature is enabled by specifying the <code>forward_index</code> storage attribute. The \$O table stores the mapping information from the token offsets in the \$I table to character offsets in the indexed documents.</p>
<code>p_table_clause</code>	<p>Parameter clause for the substring index if you have enabled <code>SUBSTRING_INDEX</code> in the <code>BASIC_WORDLIST</code>.</p> <p>Specify storage and tablespace clauses to add to the end of the internal <code>CREATE INDEX</code> statement. The P table is an index-organized table so the storage clause you specify must be appropriate to this type of table.</p>
<code>query_filter_cache_size</code>	<p>Parameter clause to specify the maximum size of the query filter cache in bytes. The query filter cache is allocated out of the shared pool, so its maximum size must be smaller than the shared pool size. When this storage preference is set at the partition level, it is implicitly set at the index level.</p> <p>The default is 0.</p>

Table 2-39 (Cont.) BASIC_STORAGE Attributes

Attribute	Attribute Value
<code>r_table_clause</code>	<p>Parameter clause for <code>dr\$indexname\$R</code> table creation. Specify storage and tablespace clauses to add to the end of the internal <code>CREATE TABLE</code> statement.</p> <p>The R table is the rowid table.</p> <p>The default clause is: <code>'LOB(DATA) STORE AS (CACHE)'</code>.</p> <p>If you modify this attribute, always include this clause for good performance.</p>
<code>s_table_clause</code>	<p>Parameter clause for <code>dr\$indexname\$S</code> table creation*. Specify storage and tablespace clauses to add to the end of the internal <code>CREATE TABLE</code> statement. The default clause is <code>nocompress</code>.</p> <p>* For performance reasons, <code>\$S</code> table must be created on a tablespace with db block size <code>>= 4K</code> without overflow segment and without a <code>PCTTHRESHOLD</code> clause. If <code>\$S</code> is created on a tablespace with db block size <code>< 4K</code>, or is created with an overflow segment or with <code>PCTTHRESHOLD</code> clause, then appropriate errors will be raised during <code>CREATE INDEX</code>.</p> <p>The S table is the table that stores <code>SDATA</code> section values.</p> <p>If this clause is specified for a storage preference in an index without <code>SDATA</code>, then it will have no effect on the index, and index creation will still succeed.</p>
<code>save_copy</code>	<p>Parameter clause to specify saving the document to the <code>\$D</code> index table.</p> <p>Specify this clause to use the forward index feature for increasing the query performance while calculating snippets.</p> <p>Set it to <code>PLAINTEXT</code> to save the copy of a document in the <code>\$D</code> table in the plaintext format. This improves the performance of snippet generation, since it does not invoke the datastore or filter to fetch the text. This also improves the performance of highlight.</p> <p>Set it to <code>FILTERED</code> to save the copy of a document in the <code>\$D</code> table in the filtered (HTML) format. This improves the performance of highlight and markup, but requires more disk space than plaintext format. It is less efficient for snippets generation, since the HTML markup must be removed during the creation of snippets.</p> <p>The default is <code>NONE</code>, and the copy of a document is not saved in the <code>\$D</code> table.</p>
<code>save_copy_max_size</code>	<p>Parameter clause to specify the maximum size of a document to save in the <code>\$D</code> table using a basic_storage attribute.</p> <p>If the document size is greater than the size specified in this attribute, the truncated version of the document having the size specified in this attribute is saved in the <code>\$D</code> table.</p> <p>If the <code>\$D</code> table is using SecureFiles with compression for the document blob, then the <code>save_copy_max_size</code> restriction is applied on the document size before compression.</p> <p>The default is 0, and the whole document is saved in the <code>\$D</code> table irrespective of its size.</p> <p>Note: The <code>save_copy_max_size</code> parameter clause is effective only when the <code>save_copy</code> parameter clause is specified.</p>

Table 2-39 (Cont.) BASIC_STORAGE Attributes

Attribute	Attribute Value
<code>separate_offsets</code>	<p>Parameter clause to improve the query performance for the CONTEXT index that is extensively used for IO operations, and whose queries are mainly single-word or boolean queries.</p> <p>Set it to T to enable the SEPARATE_OFFSETS index option for the CONTEXT index. The default is F.</p>
<code>stage_itab</code>	<p>Switch to improve the query performance for the CONTEXT index that is extensively used for DML operations.</p> <p>When the STAGE_ITAB index option is disabled, then when a new document is added to the index, SYNC_INDEX is called to make the documents searchable. This creates new rows in the \$I table, thus increasing the fragmentation in the \$I table. This leads to the deterioration of the query performance.</p> <p>When the STAGE_ITAB index option is enabled, the information about the new documents is stored in the \$G staging table, and not in the \$I table. This ensures that the \$I table does not get fragmented, and thus does not deteriorate the query performance.</p> <p>When the STAGE_ITAB index option is enabled, the \$H btree index is also created on the \$G table. The \$G table and \$H btree index are equivalent to the \$I table and \$X btree index.</p> <p>Set <code>stage_itab</code> to YES to enable the STAGE_ITAB index option for the CONTEXT index. The default is NO.</p>

2.7.1.2 BASIC_STORAGE Default Behavior

By default, BASIC_STORAGE attributes are not set. In such cases, the Text index tables are created in the index owner's default tablespace. Consider the following statement, entered by user IUSER, with no BASIC_STORAGE attributes set:

```
create index IOWNER.idx on TOWNER.tab(b) indextype is ctxsys.context;
```

In this example, the text index is created in IOWNER's default tablespace.

2.7.1.3 BASIC_STORAGE Examples

The following examples specify that the index tables are to be created in the foo tablespace with an initial extent of 1K:

```
begin
ctx_ddl.create_preference('mystore', 'BASIC_STORAGE');
ctx_ddl.set_attribute('mystore', 'I_TABLE_CLAUSE',
                     'tablespace foo storage (initial 1K)');
ctx_ddl.set_attribute('mystore', 'K_TABLE_CLAUSE',
                     'tablespace foo storage (initial 1K)');
ctx_ddl.set_attribute('mystore', 'R_TABLE_CLAUSE',
                     'tablespace users storage (initial 1K) lob
                     (data) store as (disable storage in row cache)');
ctx_ddl.set_attribute('mystore', 'N_TABLE_CLAUSE',
                     'tablespace foo storage (initial 1K)');
ctx_ddl.set_attribute('mystore', 'I_INDEX_CLAUSE',
                     'tablespace foo storage (initial 1K) compress 2');
ctx_ddl.set_attribute('mystore', 'P_TABLE_CLAUSE',
                     'tablespace foo storage (initial 1K)');
ctx_ddl.set_attribute('mystore', 'S_TABLE_CLAUSE',
```

```
        'tablespace foo storage (initial 1K)');  
end;
```

The following example adds to the end of the internal table that is created.

```
exec ctx_ddl.create_preference('sto', 'basic_storage');  
exec ctx_ddl.set_attribute('sto', 'e_table_clause', 'tablespace foo');
```

The following example uses `query_filter_cache_size` storage parameter for a partitioned index:

```
exec ctx_ddl.create_preference('fcs', 'basic_storage');  
exec ctx_ddl.set_attribute('fcs', 'query_filter_cache_size', '100000000');  
  
create table fc(id number primary key, txt varchar2(64))  
partition by range (id)  
(  
    partition p1 values less than (25),  
    partition p2 values less than (50),  
    partition p3 values less than (75)  
);  
  
create index fci on fc(txt) indextype is ctxsys.context  
local (  
    partition p1,  
    partition p2,  
    partition p3) parameters('storage fcs memory 49M sync (on commit)');
```

The query filter cache is an index level storage preference. The storage preference for the query filter cache can be set at partition level only if this is also set at the index level.

```
select count(*) from fc partition (p1) where  
contains(txt, 'ctxfiltercache(hello)') > 0;
```

2.8 Section Group Types

To enter `WITHIN` queries on document sections, you must create a section group before you define your sections. Specify your section group in the parameter clause of [CREATE INDEX](#) (page 1-40).

This section contains the following topics.

- [Section Group Types for Creating a Section Group](#) (page 2-86)
- [Section Group Examples for HTML, XML, and JSON Enabled Documents](#) (page 2-88)

2.8.1 Section Group Types for Creating a Section Group

To create a section group, you can specify one of the following group types with the `CTX_DDL.CREATE_SECTION_GROUP` (page 8-34) procedure.

Table 2-40 Section Group Types

Type	Description
<code>NULL_SECTION_GROUP</code>	Use this group type when you define no sections or when you define <i>only</i> <code>SENTENCE</code> or <code>PARAGRAPH</code> sections. This is the default.

Table 2-40 (Cont.) Section Group Types

Type	Description
BASIC_SECTION_GROUP	<p>Use this group type for defining sections where the start and end tags are of the form <A> and .</p> <p>Note: This group type does not support input such as unbalanced parentheses, comments tags, and attributes. Use HTML_SECTION_GROUP for this type of input.</p>
HTML_SECTION_GROUP	Use this group type for indexing HTML documents and for defining sections in HTML documents.
JSON_SECTION_GROUP	<p>Use this group to create a JSON enabled context index. The JSON_ENABLE attribute cannot be used with XML_ENABLE. A section group can only be marked as JSON_ENABLE. If it is already marked with XML_ENABLE, then the path section group cannot be used for JSON_ENABLE and vice versa.</p>
XML_SECTION_GROUP	Use this group type for indexing XML documents and for defining sections in XML documents. All sections to be indexed must be manually defined for this group.
AUTO_SECTION_GROUP	<p>Use this group type to automatically create a zone section for each start-tag/end-tag pair in an XML document. The section names derived from XML tags are case sensitive as in XML.</p> <p>Attribute sections are created automatically for XML tags that have attributes. Attribute sections are named in the form tag@attribute.</p> <p>Special sections can be added to AUTO_SECTION_GROUP for WITHIN SENTENCE and WITHIN PARAGRAPH searches. Once a sentence or paragraph section is added to the AUTO_SECTION_GROUP, sections with corresponding tag names 'sentence' or 'paragraph' (case insensitive) are treated as stop sections.</p> <p>Stop sections, empty tags, processing instructions, and comments are not indexed.</p> <p>The following limitations apply to automatic section groups:</p> <ul style="list-style-type: none"> • You cannot add zone, field, sdata, or special sections to an automatic section group. • You can define a stop section that applies only to one particular type; that is, if you have two different XML DTDs, both of which use a tag called FOO, you can define (TYPE1) FOO to be stopped, but (TYPE2) FOO to not be stopped. • The length of the indexed tags, including prefix and namespace, cannot exceed 64 bytes. Tags longer than this are not indexed.
PATH_SECTION_GROUP	<p>Use this group type to index XML documents. Behaves like the AUTO_SECTION_GROUP.</p> <p>The difference is that with this section group you can do path searching with the INPATH and HASPATH operators. Queries are also case-sensitive for tag and attribute names. Stop sections are not allowed.</p>
NEWS_SECTION_GROUP	Use this group for defining sections in newsgroup formatted documents according to RFC 1036.

2.8.2 Section Group Examples for HTML, XML, and JSON Enabled Documents

The examples show the use of section groups in HTML and XML documents, and in JSON enabled documents. See [Table 2-40](#) (page 2-86) for a summary.

This section contains the following examples:

- [Creating Section Groups in HTML Documents](#) (page 2-88)
- [Creating Sections Groups in XML Documents](#) (page 2-88)
- [Automatic Sectioning in XML Documents](#) (page 2-89)
- [Creating JSON Section Groups for JSON Search Index](#) (page 2-89)
- [Using JSON Search Index with JSON_TEXTCONTAINS](#) (page 2-89)
- [Using JSON Search Index with JSON_EXISTS](#) (page 2-89)

2.8.2.1 Creating Section Groups in HTML Documents

The following statement creates a section group called `htmgroup` with the HTML group type.

```
begin
ctx_ddl.create_section_group('htmgroup', 'HTML_SECTION_GROUP');
end;
```

You can optionally add sections to this group using the procedures in the `CTX_DDL` package, such as `CTX_DDL.ADD_SPECIAL_SECTION` or `CTX_DDL.ADD_ZONE_SECTION`. To index your documents, enter a statement such as:

```
create index myindex on docs(htmlfile) indextype is ctxsys.context
parameters('filter ctxsys.null_filter section group htmgroup');
```

See Also:

For more information on section groups, see [CTX_DDL Package](#) (page 8-1)

2.8.2.2 Creating Sections Groups in XML Documents

The following statement creates a section group called `xmlgroup` with the `XML_SECTION_GROUP` group type.

```
begin
ctx_ddl.create_section_group('xmlgroup', 'XML_SECTION_GROUP');
end;
```

You can optionally add sections to this group using the procedures in the `CTX_DDL` package, such as `CTX_DDL.ADD_ATTR_SECTION` or `CTX_DDL.ADD_STOP_SECTION`. To index your documents, enter a statement such as:

```
create index myindex on docs(htmlfile) indextype is ctxsys.context
parameters('filter ctxsys.null_filter section group xmlgroup');
```

See Also:

For more information on section groups, see [CTX_DDL Package](#) (page 8-1)

2.8.2.3 Automatic Sectioning in XML Documents

The following statement creates a section group called `auto` with the `AUTO_SECTION_GROUP` group type. This section group automatically creates sections from tags in XML documents.

```
begin

ctx_ddl.create_section_group('auto', 'AUTO_SECTION_GROUP');

end;

CREATE INDEX myindex on docs(htmlfile) INDEXTYPE IS ctxsys.context
PARAMETERS('filter ctxsys.null_filter section group auto');
```

2.8.2.4 Creating JSON Section Groups for JSON Search Index

The following example creates a JSON enabled text index.

```
create index json_ctx_idx on customers (customer
_info)
indextype is ctxsys.context
parameters ('section group CTXSYS.JSON_SECTION_GROUP');
```

2.8.2.5 Using JSON Search Index with JSON_TEXTCONTAINS

The following example searches for customers having keyword "gold" in the description.

```
select customer_info
from customers
where JSON_TEXTCONTAINS(customer_info, '$.description', 'gold');
```

2.8.2.6 Using JSON Search Index with JSON_EXISTS

Find JSON enabled data.

```
select customer_info from customers
where JSON_EXISTS(customer_info, '$.dataplan');
```

2.9 Classifier Types

This section describes the classifier types used to create a preference for `CTX_CLS.TRAIN` and `CTXRULE` index creation. The following two classifier types are supported:

- [RULE_CLASSIFIER](#) (page 2-90)
- [SVM_CLASSIFIER](#) (page 2-91)

Note:

In Oracle Database Express Edition (Oracle Database XE), `RULE_CLASSIFIER` and `SVM_CLASSIFIER` are not supported because the Data Mining option is not available. This is also true for `KMEAN_CLUSTERING`.

2.9.1 RULE_CLASSIFIER

Use the `RULE_CLASSIFIER` type for creating preferences for the query rule generating procedure, `CTX_CLS . TRAIN` and for `CTXRULE` creation. The rules generated with this type are essentially query strings and can be easily examined. The queries generated by this classifier can use the `AND`, `NOT`, or `ABOUT` operators. The `WITHIN` operator is supported for queries on field sections only.

[Table 2-41](#) (page 2-90) lists the attributes for the `RULE_CLASSIFIER` type.

Table 2-41 *RULE_CLASSIFIER Attributes*

Attribute	Data Type	Default	Min Value	Max Value	Description
THRESHOLD	I	50	1	99	Specify threshold (in percentage) for rule generation. One rule is output only when its confidence level is larger than threshold.
MAX_TERMS	I	100	20	2000	For each class, a list of relevant terms is selected to form rules. Specify the maximum number of terms that can be selected for each class.
MEMORY_SIZE	I	500	10	4000	Specify memory usage for training in MB. Larger values improve performance.
NT_THRESHOLD	F	0.001	0	0.90	Specify a threshold for term selection. There are two thresholds guiding two steps in selecting relevant terms. This threshold controls the behavior of the first step. At this step, terms are selected as candidate terms for the further consideration in the second step. The term is chosen when the ratio of the occurrence frequency over the number of documents in the training set is larger than this threshold.
TERM_THRESHOLD	I	10	0	100	Specify a threshold as a percentage for term selection. This threshold controls the second step term selection. Each candidate term has a numerical quantity calculated to imply its correlation with a given class. The candidate term will be selected for this class only when the ratio of its quantity value over the maximum value for all candidate terms in the class is larger than this threshold.

Table 2-41 (Cont.) RULE_CLASSIFIER Attributes

Attribute	Data Type	Default	Min Value	Max Value	Description
PRUNE_LEVEL	I	75	0	100	Specify how much to prune a built decision tree for better coverage. Higher values mean more aggressive pruning and the generated rules will have larger coverage but less accuracy.

2.9.2 SVM_CLASSIFIER

Use the SVM_CLASSIFIER type for creating preferences for the rule generating procedure, CTX_CLS.TRAIN, and for CTXRULE creation. This classifier type represents the Support Vector Machine method of classification and generates rules in binary format. Use this classifier type when you need high classification accuracy.

This type has the following attributes:

Table 2-42 SVM_CLASSIFIER Attributes

Attribute Name	Data Type	Default	Min Value	Max Value	Description
MAX_DOCTERMS	I	50	10	8192	Specify the maximum number of terms representing one document.
MAX_FEATURES	I	3,000	1	100,000	Specify the maximum number of distinct features.
THEME_ON	B	FALSE	NULL	NULL	Specify TRUE to use themes as features.
TOKEN_ON	B	TRUE	NULL	NULL	Specify TRUE to use regular tokens as features.
STEM_ON	B	FALSE	NULL	NULL	Specify TRUE to use stemmed tokens as features. This only works when turning INDEX_STEM on for the lexer.
MEMORY_SIZE	I	500	10	4000	Specify approximate memory size in MB.

Table 2-42 (Cont.) SVM_CLASSIFIER Attributes

Attribute Name	Data Type	Default	Min Value	Max Value	Description
SECTION_WEIGHT	1	2	0	100	Specify the occurrence multiplier for adding a term in a field section as a normal term. For example, by default, the term <i>cat</i> in "<A>cat" is a field section term and is treated as a normal term with occurrence equal to 2, but you can specify that it be treated as a normal term with a weight up to 100. SECTION_WEIGHT is only meaningful when the index policy specifies a field section.

2.10 Cluster Types

This section describes the cluster types used for creating preferences for the CTX_CLS.CLUSTERING procedure.

- [KMEAN_CLUSTERING](#) (page 2-92)

Note:

In Oracle Database Express Edition (Oracle Database XE), KMEAN_CLUSTERING is not supported because the Data Mining option is not available. This is also true for RULE_CLASSIFIER and SVM_CLASSIFIER.

See Also:

For more information about clustering, see "[CLUSTERING](#) (page 7-4)" in [CTX_CLS Package](#) (page 7-1) as well as the *Oracle Text Application Developer's Guide*

2.10.1 KMEAN_CLUSTERING

The KMEAN_CLUSTERING clustering type has the attributes listed in [Table 2-43](#) (page 2-92).

Table 2-43 KMEAN_CLUSTERING Attributes

Attribute Name	Data Type	Default	Min Value	Max Value	Description
MAX_DOCTERMS	I	50	10	8192	Specify the maximum number of distinct terms representing one document.

Table 2-43 (Cont.) KMEAN_CLUSTERING Attributes

Attribute Name	Data Type	Default	Min Value	Max Value	Description
MAX_FEATURES	I	3,000	1	500,000	Specify the maximum number of distinct features.
THEME_ON	B	FALSE	NULL	NULL	Specify TRUE to use themes as features.
TOKEN_ON	B	TRUE	NULL	NULL	Specify TRUE to use regular tokens as features.
STEM_ON	B	FALSE	NULL	NULL	Specify TRUE to use stemmed tokens as features. This only works when turning INDEX_STEM on for the lexer.
MEMORY_SIZE	I	500	10	4000	Specify approximate memory size in MB.
SECTION_WEIGHT	1	2	0	100	Specify the occurrence multiplier for adding a term in a field section as a normal term. For example, by default, the term <i>cat</i> in "<A>cat" is a field section term and is treated as a normal term with occurrence equal to 2, but you can specify that it be treated as a normal term with a weight up to 100. SECTION_WEIGHT is only meaningful when the index policy specifies a field section.
CLUSTER_NUM	I	200	2	20000	Specify the total number of leaf clusters to be generated.

2.11 Stoplists

Stoplists identify the words in your language that are not to be indexed. In English, you can also identify stopthemes that are not to be indexed. By default, the system indexes text using the system-supplied stoplist that corresponds to your database language.

Oracle Text provides default stoplists for most common languages including English, French, German, Spanish, Chinese, Dutch, and Danish. These default stoplists contain only stopwords.

- [Multi-Language Stoplists](#) (page 2-94)
- [Creating Stoplists](#) (page 2-94)
- [Modifying the Default Stoplist](#) (page 2-94)

See Also:

For more information about the supplied default stoplists, see [Oracle Text Supplied Stoplists](#) (page E-1)

2.11.1 Multi-Language Stoplists

You can create multi-language stoplists to hold language-specific stopwords. A multi-language stoplist is useful when you use the `MULTI_LEXER` to index a table that contains documents in different languages, such as English, German.

To create a multi-language stoplist, use the `CTX_DLL.CREATE_STOPLIST` (page 8-39) procedure and specify a stoplist type of `MULTI_STOPLIST`. Add language specific stopwords with `CTX_DDL.ADD_STOPWORD` (page 8-23).

At indexing time, the language column of each document is examined, and only the stopwords for that language are eliminated. At query time, the session language setting determines the active stopwords, like it determines the active lexer when using the multi-lexer.

2.11.2 Creating Stoplists

Create your own stoplists using the `CTX_DLL.CREATE_STOPLIST` (page 8-39) procedure. With this procedure you can create a `BASIC_STOPLIST` for single language stoplist, or you can create a `MULTI_STOPLIST` for a multi-language stoplist.

When you create your own stoplist, you must specify it in the parameter clause of `CREATE INDEX`.

To create stoplists for Chinese or Japanese languages, use the `CHINESE_LEXER` or `JAPANESE_LEXER` respectively, and update the appropriate lexicon to be *@contained_such_stopwords*.

2.11.3 Modifying the Default Stoplist

The default stoplist is always named `.CTXSYS.DEFAULT_STOPLIST`. Use the following procedures to modify this stoplist:

- `CTX_DDL.ADD_STOPWORD` (page 8-23)
- `CTX_DDL.REMOVE_STOPWORD` (page 8-62)
- `CTX_DDL.ADD_STOPTHEME` (page 8-22)
- `CTX_DDL.ADD_STOPCLASS` (page 8-19)

When you modify `CTXSYS.DEFAULT_STOPLIST` with the `CTX_DDL` package, you must re-create your index for the changes to take effect.

Dynamic Addition of Stopwords

You can *add* stopwords dynamically to a default or custom stoplist with [ALTER INDEX](#) (page 1-1). When you add a stopword dynamically, you need not re-index, because the word immediately becomes a stopword and is removed from the index.

Note:

Even though you can dynamically add stopwords to an index, you cannot dynamically remove stopwords. To remove a stopword, you must use CTX_DDL.[REMOVE_STOPWORD](#) (page 8-62), drop your index and re-create it.

See Also:

"[ALTER INDEX](#) (page 1-1)" in [Oracle Text SQL Statements and Operators](#) (page 1-1)

2.12 System-Defined Preferences

When you install Oracle Text, some indexing preferences are created. You can use these preferences in the parameter clause of [CREATE INDEX](#) (page 1-40) or define your own.

The default index parameters are mapped to some of the system-defined preferences described in this section.

See Also:

For more information about default index parameters, see "[Default Index Parameters](#) (page 2-99)"

System-defined preferences are divided into the following categories:

- [Data Storage Preferences](#) (page 2-95)
- [Filter Preferences](#) (page 2-96)
- [Lexer Preferences](#) (page 2-96)
- [Section Group Preferences](#) (page 2-97)
- [Stoplist Preferences](#) (page 2-98)
- [Storage Preferences](#) (page 2-98)
- [Wordlist Preferences](#) (page 2-98)

2.12.1 Data Storage Preferences

This section discusses the types associated with data storage preferences.

- The CTXSYS.DEFAULT_DATASTORE preference uses the [DIRECT_DATASTORE](#) (page 2-3) type. Use this preference to create indexes for text columns in which the text is stored directly in the column.
- The CTXSYS.FILE_DATASTORE preference uses the [FILE_DATASTORE](#) (page 2-9) type.

- The `CTXSYS.URL_DATASTORE` preference uses the [URL_DATASTORE](#) (page 2-11) type.

2.12.2 Filter Preferences

This section discusses the types associated with filtering preferences.

- The `CTXSYS.NULL_FILTER` preference uses the [NULL_FILTER](#) (page 2-22) type.
- The `CTXSYS.AUTO_FILTER` preference uses the [AUTO_FILTER](#) (page 2-19) type.

2.12.3 Lexer Preferences

This section discusses the types associated with *lexer* preferences.

- [CTXSYS.DEFAULT_LEXER](#) (page 2-96)
- [CTXSYS.DEFAULT_EXTRACT_LEXER](#) (page 2-97)
- [CTXSYS.BASIC_LEXER](#) (page 2-97)

2.12.3.1 CTXSYS.DEFAULT_LEXER

The `CTXSYS.DEFAULT_LEXER` default lexer depends on the language used at install time. The following sections describe the default settings for `CTXSYS.DEFAULT_LEXER` for each language.

- American and English Language Settings
If your language is English, this preference uses the [BASIC_LEXER](#) (page 2-41) with the `index_themes` attribute disabled.
- Danish Language Settings
If your language is Danish, this preference uses the [BASIC_LEXER](#) (page 2-41) with the following option enabled:
 - Alternate spelling (`alternate_spelling` attribute set to `DANISH`)
- Dutch Language Settings
If your language is Dutch, this preference uses the [BASIC_LEXER](#) (page 2-41) with the following options enabled:
 - composite indexing (`composite` attribute set to `DUTCH`)
- German and German DIN Language Settings
If your language is German, then this preference uses the [BASIC_LEXER](#) (page 2-41) with the following options enabled:
 - Case-sensitive indexing (`mixed_case` attribute enabled)
 - Composite indexing (`composite` attribute set to `GERMAN`)
 - Alternate spelling (`alternate_spelling` attribute set to `GERMAN`)
- Finnish, Norwegian, and Swedish Language Settings
If your language is Finnish, Norwegian, or Swedish, this preference uses the [BASIC_LEXER](#) (page 2-41) with the following option enabled:

- Alternate spelling (alternate_spelling attribute set to SWEDISH)
- Japanese Language Settings
If your language is Japanese, this preference uses the [JAPANESE_VGRAM_LEXER](#) (page 2-53).
- Korean Language Settings
If your language is Korean, this preference uses the [KOREAN_MORPH_LEXER](#) (page 2-55). All attributes for the KOREAN_MORPH_LEXER are enabled.
- Chinese Language Settings
If your language is Simplified or Traditional Chinese, this preference uses the [CHINESE_VGRAM_LEXER](#) (page 2-52).
- Other Languages
For all other languages not listed in this section, this preference uses the [BASIC_LEXER](#) (page 2-41) with no attributes set.

See Also:

To learn more about these options, see "[BASIC_LEXER](#) (page 2-41)"

2.12.3.2 CTXSYS.DEFAULT_EXTRACT_LEXER

The CTXSYS.DEFAULT_EXTRACT_LEXER preference uses [AUTO_LEXER](#) (page 2-33) and includes all Oracle-supplied features (rules, dictionary, etc.).

CTXSYS.DEFAULT_EXTRACT_LEXER uses AUTO_LEXER with the following options:

- alternate_spelling is NONE
- base_letter is NO
- mixed_case is YES
- <> printjoin is '-*' <>

2.12.3.3 CTXSYS.BASIC_LEXER

The CTXSYS.BASIC_LEXER preference uses the [BASIC_LEXER](#) (page 2-41).

2.12.4 Section Group Preferences

This section discusses the types associated with section group preferences.

- The CTXSYS.NULL_SECTION_GROUP preference uses the NULL_SECTION_GROUP type.
- The CTXSYS.HTML_SECTION_GROUP preference uses the HTML_SECTION_GROUP type.
- The CTXSYS.JSON_SECTION_GROUP preference uses the JSON_SECTION_GROUP type.
- The CTXSYS.AUTO_SECTION_GROUP preference uses the AUTO_SECTION_GROUP type.

- The `CTXSYS.PATH_SECTION_GROUP` preference uses the `PATH_SECTION_GROUP` type.

2.12.5 Stoplist Preferences

This section discusses the types associated with stoplist preferences.

- The `CTXSYS.DEFAULT_STOPLIST` stoplist preference defaults to the stoplist of your database language.
- The `CTXSYS.EMPTY_STOPLIST` stoplist has no words.

See Also:

For a complete list of the stop words in the supplied stoplists, see [Oracle Text Supplied Stoplists](#) (page E-1)

2.12.6 Storage Preferences

This section discusses the types associated with storage preferences.

The `CTXSYS.DEFAULT_STORAGE` storage preference uses the [BASIC_STORAGE](#) (page 2-81) type.

2.12.7 Wordlist Preferences

This section discusses the types associated with wordlist preferences.

The `CTXSYS.DEFAULT_WORDLIST` preference uses the language stemmer for your database language. If your language is not listed in [Table 2-37](#) (page 2-73), then this preference defaults to the `NULL` stemmer and the `GENERIC` fuzzy matching attribute.

2.13 System Parameters

This section describes the Oracle Text system parameters, which are divided into the following categories:

- [General System Parameters](#) (page 2-98)
- [Default Index Parameters](#) (page 2-99)
- [Default Policy Parameters](#) (page 2-102)

See Also:

["System-Defined Preferences](#) (page 2-95)"

2.13.1 General System Parameters

When you install Oracle Text, in addition to the system-defined preferences, the following system parameters are set:

Table 2-44 General System Parameters

System Parameter	Description
MAX_INDEX_MEMORY	This is the maximum indexing memory that can be specified in the parameter clause of <code>CREATE INDEX</code> and <code>ALTER INDEX</code> . The maximum value for this parameter is 2 GB -1.
DEFAULT_INDEX_MEMORY	This is the default indexing memory used with <code>CREATE INDEX</code> and <code>ALTER INDEX</code> .
LOG_DIRECTORY	This is the directory for CTX_OUTPUT log files.
CTX_DOC_KEY_TYPE	This is the default input key type, either ROWID or PRIMARY_KEY, for the CTX_DOC procedures. Set to ROWID at install time. See Also: CTX_DOC. SET_KEY_TYPE (page 9-40).

View system defaults by querying the [CTX_PARAMETERS](#) (page G-10) view. Change defaults using the CTX_ADM.[SET_PARAMETER](#) (page 5-3) procedure.

2.13.2 Default Index Parameters

This section describes the index parameters that you can use when you create CONTEXT and CTXCAT indexes.

This section contains the following topics:

- [CONTEXT Index Parameters](#) (page 2-99)
- [CTXCAT Index Parameters](#) (page 2-101)
- [CTXRULE Index Parameters](#) (page 2-101)

Viewing Default Values

View system defaults by querying the [CTX_PARAMETERS](#) (page G-10) view. For example, to see all parameters and values, enter the following statement:

```
SQL> SELECT par_name, par_value from ctx_parameters;
```

Changing Default Values

Change a default value using the CTX_ADM.[SET_PARAMETER](#) (page 5-3) procedure to name another custom or system-defined preference to use as default.

2.13.2.1 CONTEXT Index Parameters

The following default parameters are used when you create a CONTEXT index and do not specify preferences in the parameter clause of [CREATE INDEX](#) (page 1-40). Each default parameter names a system-defined preference to use for data storage, filtering, lexing, and so on.

Table 2-45 Default CONTEXT Index Parameters

Parameter	Used When	Default Value
DEFAULT_DATASTORE	No datastore preference specified in parameter clause of <code>CREATE INDEX</code> .	CTXSYS.DEFAULT_DATASTORE

Table 2-45 (Cont.) Default CONTEXT Index Parameters

Parameter	Used When	Default Value
DEFAULT_FILTER_FILE	No filter preference specified in parameter clause of CREATE INDEX, and either of the following conditions is true: <ul style="list-style-type: none"> Your files are stored in external files (BFILES) or Specify a datastore preference that uses FILE_DATASTORE 	CTXSYS.AUTO_FILTER
DEFAULT_FILTER_BINARY	No filter preference specified in parameter clause of CREATE INDEX, and Oracle Text detects that the text column datatype is RAW, LONG RAW, or BLOB.	CTXSYS.AUTO_FILTER
DEFAULT_FILTER_TEXT	No filter preference specified in parameter clause of CREATE INDEX, and Oracle Text detects that the text column datatype is either LONG, VARCHAR2, VARCHAR, CHAR, or CLOB.	CTXSYS.NULL_FILTER
DEFAULT_SECTION_HTML	No section group specified in parameter clause of CREATE INDEX, and when either of the following conditions is true: <ul style="list-style-type: none"> Your datastore preference uses URL_DATASTORE or Your filter preference uses AUTO_FILTER. 	CTXSYS.HTML_SECTION_GROUP
DEFAULT_SECTION_TEXT	No section group specified in parameter clause of CREATE INDEX, and when you do <i>not</i> use either URL_DATASTORE or AUTO_FILTER.	CTXSYS.NULL_SECTION_GROUP
DEFAULT_STORAGE	No storage preference specified in parameter clause of CREATE INDEX.	CTXSYS.DEFAULT_STORAGE
DEFAULT_LEXER	No lexer preference specified in parameter clause of CREATE INDEX.	CTXSYS.DERFAULT_LEXER
DEFAULT_STOPLIST	No stoplist specified in parameter clause of CREATE INDEX.	CTXSYS.DEFAULT_STOPLIST
DEFAULT_WORDLIST	No wordlist preference specified in parameter clause of CREATE INDEX.	CTXSYS.DEFAULT_WORDLIST

See Also:

["System-Defined Preferences \(page 2-95\)"](#)

2.13.2.2 CTXCAT Index Parameters

The following default parameters are used when you create a CTXCAT index with `CREATE INDEX` and do not specify any parameters in the parameter string. The CTXCAT index supports only the index set, lexer, storage, stoplist, and wordlist parameters. Each default parameter names a system-defined preference.

Table 2-46 Default CTXCAT Index Parameters

Parameter	Used When	Default Value
DEFAULT_CTXCAT_INDEX_SET	No index set specified in parameter clause of <code>CREATE INDEX</code> .	n/a
DEFAULT_CTXCAT_STORAGE	No storage preference specified in parameter clause of <code>CREATE INDEX</code> .	CTXSYS.DEFAULT_STORAGE
DEFAULT_CTXCAT_LEXER	No lexer preference specified in parameter clause of <code>CREATE INDEX</code> .	CTXSYS.DERFAULT_LEXER
DEFAULT_CTXCAT_STOPLIST	No stoplist specified in parameter clause of <code>CREATE INDEX</code> .	CTXSYS.DEFAULT_STOPLIST
DEFAULT_CTXCAT_WORDLIST	No wordlist preference specified in parameter clause of <code>CREATE INDEX</code> . Note that while you can specify a wordlist preference for CTXCAT indexes, most of the attributes do not apply, because the catsearch query language does not support wildcarding, fuzzy, and stemming. The only attribute that is useful is <code>PREFIX_INDEX</code> for Japanese data.	CTXSYS.DEFAULT_WORDLIST

See Also:

["System-Defined Preferences \(page 2-95\)"](#)

2.13.2.3 CTXRULE Index Parameters

[Table 2-47](#) (page 2-101) lists the default parameters that are used when you create a CTXRULE index with `CREATE INDEX` and do not specify any parameters in the parameter string. The CTXRULE index supports only the lexer, storage, stoplist, and wordlist parameters. Each default parameter names a system-defined preference.

Table 2-47 Default CTXRULE Index Parameters

Parameter	Used When	Default Value
DEFAULT_CTRRULE_LEXER	No lexer preference specified in parameter clause of <code>CREATE INDEX</code> .	CTXSYS.DERFAULT_LEXER
DEFAULT_CTRRULE_STORAGE	No storage preference specified in parameter clause of <code>CREATE INDEX</code> .	CTXSYS.DEFAULT_STORAGE
DEFAULT_CTRRULE_STOPLIST	No stoplist specified in parameter clause of <code>CREATE INDEX</code> .	CTXSYS.DEFAULT_STOPLIST

Table 2-47 (Cont.) Default CTXRULE Index Parameters

Parameter	Used When	Default Value
DEFAULT_CTXRULE_WORDLIST	No wordlist preference specified in parameter clause of CREATE INDEX.	CTXSYS.DEFAULT_WORDLIST
DEFAULT_CLASSIFIER	No classifier preference is specified in parameter clause.	RULE_CLASSIFIER

See Also:

["System-Defined Preferences \(page 2-95\)"](#)

CTXRULE Index Limitations

The CTXRULE index does not support the following query operators:

- Fuzzy
- Soundex

It also does not support the following BASIC_WORDLIST attributes:

- SUBSTRING_INDEX
- PREFIX_INDEX

2.13.3 Default Policy Parameters

Policies in Oracle Text enable you to use document services without creating an index. For example, the document services might be filtering to generate a plain text or HTML version of a document, generating theme summaries or lists of themes, and highlighting.

[Table 2-48](#) (page 2-102) lists the default parameters when you create a policy and do not specify preferences when using CTX_DDL.CREATE_POLICY (page 8-30). Each default parameter names a system-defined preference to use for filtering, lexing, and so on.

Table 2-48 Default Policy Parameters for CTX_DDL.CREATE_POLICY

Parameter	Used When	Default Value
DEFAULT_FILTER_BINARY	No filter preference specified for CREATE_POLICY, and the document parameter of the document service is VARCHAR2 or CLOB datatype; BLOB or BFILE datatype.	CTXSYS.AUTO_FILTER
DEFAULT_FILTER_TEXT	No filter preference specified for CREATE_POLICY, and the document parameter of the document service is VARCHAR2 or CLOB datatype; BLOB or BFILE datatype.	CTXSYS.NULL_FILTER

Table 2-48 (Cont.) Default Policy Parameters for CTX_DDL.CREATE_POLICY

Parameter	Used When	Default Value
DEFAULT_SECTION_HTML	No section group specified for CREATE_POLICY, and when your filter preference uses AUTO_FILTER.	CTXSYS.HTML_SECTION_GROUP
DEFAULT_SECTION_TEXT	No section_group specified for CREATE_POLICY, and when you do <i>not</i> use AUTO_FILTER.	CTXSYS.NULL_SECTION_GROUP
DEFAULT_LEXER	No lexer preference specified for CREATE_POLICY.	CTXSYS.DEFAULT_LEXER
DEFAULT_STOPLIST	No stoplist specified for CREATE_POLICY.	CTXSYS.DEFAULT_STOPLIST
DEFAULT_WORDLIST	No wordlist preference specified for CREATE_POLICY.	CTXSYS.DEFAULT_WORDLIST

See Also:

- ["System-Defined Preferences \(page 2-95\)"](#)
- ["CREATE_POLICY \(page 8-30\)"](#) for complete information

Oracle Text CONTAINS Query Operators

This chapter describes operator precedence and provides descriptions, syntax, and examples for every [CONTAINS](#) (page 1-29) operator.

This chapter contains the following topics:

- [Operator Precedence](#) (page 3-2)
- [ABOUT](#) (page 3-4)
- [ACCUMulate \(_ \)](#) (page 3-7)
- [AND \(&\)](#) (page 3-8)
- [Broader Term \(BT_ BTG_ BTP_ BTI\)](#) (page 3-9)
- [CTXFILTERCACHE](#) (page 3-11)
- [DEFINEMERGE](#) (page 3-14)
- [DEFINESCORE](#) (page 3-15)
- [EQUIValence \(=\)](#) (page 3-19)
- [Fuzzy](#) (page 3-20)
- [HASPATH](#) (page 3-21)
- [INPATH](#) (page 3-23)
- [MDATA](#) (page 3-29)
- [MINUS \(-\)](#) (page 3-31)
- [MNOT](#) (page 3-31)
- [Narrower Term \(NT_ NTG_ NTP_ NTI\)](#) (page 3-32)
- [NDATA](#) (page 3-34)
- [NEAR \(;\)](#) (page 3-36)
- [NOT \(~\)](#) (page 3-39)
- [OR \(|\)](#) (page 3-40)
- [Preferred Term \(PT\)](#) (page 3-41)
- [Related Term \(RT\)](#) (page 3-41)
- [SDATA](#) (page 3-42)

- [soundex \(!\)](#) (page 3-45)
- [stem \(\\$\)](#) (page 3-45)
- [Stored Query Expression \(SQE\)](#) (page 3-46)
- [SYNonym \(SYN\)](#) (page 3-47)
- [threshold \(>\)](#) (page 3-48)
- [Translation Term \(TR\)](#) (page 3-48)
- [Translation Term Synonym \(TRSYN\)](#) (page 3-49)
- [Top Term \(TT\)](#) (page 3-50)
- [weight \(*\)](#) (page 3-51)
- [wildcards \(% _\)](#) (page 3-52)
- [WITHIN](#) (page 3-54)

3.1 Operator Precedence

Operator precedence determines the order in which the components of a query expression are evaluated. Text query operators can be divided into two sets of operators that have their own order of evaluation. These two groups are described later as Group 1 and Group 2.

In all cases, query expressions are evaluated in order from left to right according to the precedence of their operators. Operators with higher precedence are applied first. Operators of equal precedence are applied in order of their appearance in the expression from left to right.

- [Group 1 Operators](#) (page 3-2)
- [Group 2 Operators and Characters](#) (page 3-3)
- [Procedural Operators](#) (page 3-3)
- [Precedence Examples](#) (page 3-3)
- [Altering Precedence](#) (page 3-4)

3.1.1 Group 1 Operators

Within query expressions, the Group 1 operators have the following order of evaluation from highest precedence to lowest:

1. [EQUIValence \(=\)](#) (page 3-19)
2. [NEAR \(;\)](#) (page 3-36)
3. [weight \(*\)](#) (page 3-51), [threshold \(>\)](#) (page 3-48)
4. [MINUS \(-\)](#) (page 3-31)
5. [NOT \(~\)](#) (page 3-39)
6. [MNOT](#) (page 3-31)

7. [WITHIN](#) (page 3-54)
8. [AND \(&\)](#) (page 3-8)
9. [OR \(|\)](#) (page 3-40)
10. [ACCUMulate \(_ \)](#) (page 3-7)

3.1.2 Group 2 Operators and Characters

Within query expressions, the Group 2 operators have the following order of evaluation from highest to lowest:

1. Wildcard Characters
2. [stem \(\\$\)](#) (page 3-45)
3. [Fuzzy](#) (page 3-20)
4. [soundex \(!\)](#) (page 3-45)

3.1.3 Procedural Operators

Other operators not listed under Group 1 or Group 2 are procedural. These operators have no sense of precedence attached to them. They include the SQE and thesaurus operators.

3.1.4 Precedence Examples

Table 3-1 Query Expression Precedence Examples

Query Expression	Order of Evaluation
<code>w1 w2 & w3</code>	<code>(w1) (w2 & w3)</code>
<code>w1 & w2 w3</code>	<code>(w1 & w2) w3</code>
<code>?w1, w2 w3 & w4</code>	<code>(?w1), (w2 (w3 & w4))</code>
<code>abc = def ghi & jkl = mno</code>	<code>((abc = def) ghi) & (jkl=mno)</code>
<code>dog and cat WITHIN body</code>	<code>dog and (cat WITHIN body)</code>

In the first example, because AND has a higher precedence than OR, the query returns all documents that contain *w1* and all documents that contain both *w2* and *w3*.

In the second example, the query returns all documents that contain both *w1* and *w2* and all documents that contain *w3*.

In the third example, the fuzzy operator is first applied to *w1*, then the AND operator is applied to arguments *w3* and *w4*, then the OR operator is applied to term *w2* and the results of the AND operation, and finally, the score from the fuzzy operation on *w1* is added to the score from the OR operation.

The fourth example shows that the equivalence operator has higher precedence than the AND operator.

The fifth example shows that the AND operator has lower precedence than the WITHIN operator.

3.1.5 Altering Precedence

Precedence is altered by grouping characters as follows:

- Within parentheses, expansion or execution of operations is resolved before other expansions regardless of operator precedence.
- Within parentheses, precedence of operators is maintained during evaluation of expressions.
- Within parentheses, expansion operators are not applied to expressions unless the operators are also within the parentheses.

See Also:

"[Grouping Characters](#) (page 4-1)" in [Special Characters in Oracle Text Queries](#) (page 4-1)

3.2 ABOUT

General Behavior

Use the ABOUT operator to return documents that are related to a query term or phrase. In English and French, ABOUT enables you to query on concepts, even if a concept is not actually part of a query. For example, an ABOUT query on *heat* might return documents related to temperature, even though the term *temperature* is not part of the query.

In other languages, using ABOUT will often increase the number of returned documents and may improve the sorting order of results. For all languages, Oracle Text scores results for an ABOUT query with the most relevant document receiving the highest score.

English and French Behavior

In English and French, use the ABOUT operator to query on concepts. The system looks up concept information in the theme component of the index. Create a theme component to your index by setting the INDEX_THEMES [BASIC_LEXER](#) (page 2-41) attribute to YES.

Note:

You need not have a theme component in the index to enter ABOUT queries in English and French. However, having a theme component in the index yields the best results for ABOUT queries.

Oracle Text retrieves documents that contain concepts that are related to your query word or phrase. For example, if you enter an ABOUT query on *California*, the system might return documents that contain the terms *Los Angeles* and *San Francisco*, which are cities in California. The document need not contain the term *California* to be returned in this ABOUT query.

The word or phrase specified in your ABOUT query need not exactly match the themes stored in the index. Oracle Text normalizes the word or phrase before performing lookup in the index.

You can use the ABOUT operator with the CONTAINS and CATSEARCH SQL operators. In the case of CATSEARCH, you must use query templating with the CONTEXT grammar to query on the indexed themes. See [ABOUT Query with CATSEARCH](#) (page 3-6) in the Examples section.

Syntax

Syntax	Description
<code>about(<i>phrase</i>)</code>	<p>In all languages, increases the number of relevant documents returned for the same query without the ABOUT operator. The <i>phrase</i> parameter can be a single word or a phrase, or a string of words in free text format.</p> <p>In English and French, returns documents that contain concepts related to <i>phrase</i>, provided the BASIC_LEXER INDEX_THEMES attribute is set to YES at index time.</p> <p>The score returned is a relevance score.</p> <p>Oracle Text ignores any query operators that are included in <i>phrase</i>.</p> <p>If your index contains only theme information, an ABOUT operator and operand must be included in your query on the text column or else Oracle Text returns an error.</p> <p>The <i>phrase</i> you specify cannot be more than 4000 characters.</p>

Case-Sensitivity

ABOUT queries give the best results when your query is formulated with proper case. This is because the normalization of your query is based on the knowledge catalog which is case-sensitive.

However, you need not type your query in exact case to obtain results from an ABOUT query. The system does its best to interpret your query. For example, if you enter a query of CISCO and the system does not find this in the knowledge catalog, the system might use *Cisco* as a related concept for look-up.

Improving ABOUT Results

The ABOUT operator uses the supplied knowledge base in English and French to interpret the phrase you enter. Your ABOUT query therefore is limited to knowing and interpreting the concepts in the knowledge base.

Improve the results of your ABOUT queries by adding your application-specific terminology to the knowledge base.

See Also:

"[Extending the Knowledge Base](#) (page 16-10)" in [Oracle Text Utilities](#) (page 16-1)

Limitations

The phrase you specify in an ABOUT query cannot be more than 4000 characters.

Examples for ABOUT Operator

Single Words

To search for documents that are about soccer, use the following syntax:

```
'about(soccer)'
```

Phrases

Further refine the query to include documents about soccer rules in international competition by entering the phrase as the query term:

```
'about(soccer rules in international competition)'
```

In this English example, Oracle Text returns all documents that have themes of *soccer*, *rules*, or *international competition*.

In terms of scoring, documents which have all three themes will generally score higher than documents that have only one or two of the themes.

Unstructured Phrases

You can also query on unstructured phrases, such as the following:

```
'about(japanese banking investments in indonesia)'
```

Combined Queries

Use other operators, such as AND or NOT, to combine ABOUT queries with word queries. For example, enter the following combined ABOUT and word query:

```
'about(dogs) and cat'
```

Combine an ABOUT query with another ABOUT query as follows:

```
'about(dogs) not about(labradors)'
```

Note:

You cannot combine ABOUT with the WITHIN operator, as for example *'ABOUT (xyz) WITHIN abc'*.

ABOUT Query with CATSEARCH

Enter ABOUT queries with CATSEARCH using the query template method with grammar set to CONTEXT as follows:

```
select pk||' ==> '||text from test
where catsearch(text,
'<query>
  <textquery grammar="context">
    about(California)
  </textquery>
  <score datatype="integer"/>
</query>', '')>0
order by pk;
```

3.3 ACCUMulate (,)

Use the ACCUM operator to search for documents that contain at least one occurrence of any query terms, with the returned documents ranked by a cumulative score based on how many query terms are found (and how frequently).

Syntax

Syntax	Description
<i>term1,term2</i>	Returns documents that contain <i>term1</i> or <i>term2</i> . Ranks documents according to document term weight, with the highest scores assigned to documents that have the highest total term weight.
<i>term1</i> ACCUM <i>term2</i>	

ACCUMulate Scoring

ACCUMulate first scores documents on how many query terms a document matches. A document that matches more terms will always score higher than a document that matches fewer terms, even if the terms appear more frequently in the latter. In other words, if you search for *dog ACCUM cat*, you'll find that

the dog played with the cat

scores higher than

the big dog played with the little dog while a third dog ate the dog food

Scores are divided into ranges. In a two-term ACCUM, hits that match both terms will always score between 51 and 100, whereas hits matching only one of the terms will score between 1 and 50. Likewise, for a three-term ACCUM, a hit matching one term will score between 1 and 33; a hit matching two terms will score between 34 and 66, and a hit matching all three terms will score between 67 and 100. *Within these ranges*, normal scoring algorithms apply.

See Also:

[The Oracle Text Scoring Algorithm](#) (page F-1) for more information on how scores are calculated

You can assign different weights to different terms. For example, in a query of the form

soccer, Brazil*3

the term *Brazil* is weighted three times as heavily as *soccer*. Therefore, the document people play soccer because soccer is challenging and fun

will score lower than

Brazil is the largest nation in South America

but both documents will rank below

soccer is the national sport of Brazil

Note that a query of *soccer ACCUM Brazil*3* is equivalent to *soccer ACCUM Brazil ACCUM Brazil ACCUM Brazil*. Because each query term *Brazil* is considered independent, the entire query is scored as though it has four terms, not two, and thus has four scoring ranges. The first *Brazil*-and-*soccer* example document shown above scores in the first range (1-25), the second scores in the third range (51-75), and the third scores in the fourth range (76-100). (No document scores in the second range, because any document with *Brazil* in it will be considered to match at least three query terms.)

Example for ACCUM Operator

```
set serveroutput on;
DROP TABLE accumtbl;
CREATE TABLE accumtbl (id NUMBER, text VARCHAR2(4000) );

INSERT INTO accumtbl VALUES ( 1, 'the little dog played with the big dog
    while the other dog ate the dog food');
INSERT INTO accumtbl values (2, 'the cat played with the dog');

CREATE INDEX accumtbl_idx ON accumtbl (text) indextype is ctxsys.context;

PROMPT dog ACCUM cat
SELECT SCORE(10) FROM accumtbl WHERE CONTAINS (text, 'dog ACCUM cat', 10)
    > 0;

PROMPT dog*3 ACCUM cat
SELECT SCORE(10) FROM accumtbl WHERE CONTAINS (text, 'dog*3 ACCUM cat', 10)
    > 0;
```

This produces the following output. Note that the document with both *dog* and *cat* scores highest.

```
dog ACCUM cat
  ID  SCORE(10)
-----
   1         6
   2        52

dog*3 ACCUM cat
  ID  SCORE(10)
-----
   1        53
   2        76
```

Related Topics

[weight \(*\)](#) (page 3-51)

3.4 AND (&)

Use the AND operator to search for documents that contain at least one occurrence of each of the query terms. The AND operator returns documents that contain *all* of the query terms, while OR operator returns documents that contain *any* of the query terms.

Syntax

Syntax	Description
<i>term1</i> & <i>term2</i> <i>term1</i> and <i>term2</i>	Returns documents that contain <i>term1</i> and <i>term2</i> . Returns the minimum score of its operands. All query terms must occur; lower score taken.

Example for AND Operator

To obtain all the documents that contain the terms *blue* and *black* and *red*, enter the following query:

```
'blue & black & red'
```

In an AND query, the score returned is the score of the lowest query term. In this example, if the three individual scores for the terms *blue*, *black*, and *red* is 10, 20 and 30 within a document, the document scores 10.

Related Topics

["OR \(|\)"](#) (page 3-40)"

3.5 Broader Term (BT, BTG, BTP, BTI)

Use the broader term operators (BT, BTG, BTP, BTI) to expand a query to include the term that has been defined in a thesaurus as the broader or higher level term for a specified term. They can also expand the query to include the broader term for the broader term and the broader term for that broader term, and so on up through the thesaurus hierarchy.

Syntax

Syntax	Description
BT(<i>term</i> [(<i>qualifier</i>)][, <i>level</i>][, <i>thes</i>])	Expands a query to include the term defined in the thesaurus as a broader term for <i>term</i> .
BTG(<i>term</i> [(<i>qualifier</i>)][, <i>level</i>][, <i>thes</i>])	Expands a query to include all terms defined in the thesaurus as broader generic terms for <i>term</i> .
BTP(<i>term</i> [(<i>qualifier</i>)][, <i>level</i>][, <i>thes</i>])	Expands a query to include all the terms defined in the thesaurus as broader partitive terms for <i>term</i> .
BTI(<i>term</i> [(<i>qualifier</i>)][, <i>level</i>][, <i>thes</i>])	Expands a query to include all the terms defined in the thesaurus as broader instance terms for <i>term</i> .

term

Specify the operand for the broader term operator. Oracle Text expands *term* to include the broader term entries defined for the term in the thesaurus specified by *thes*. For example, if you specify *BTG(dog)*, the expansion includes only those terms that are defined as broader term generic for *dog*. You cannot specify expansion operators in the *term* argument.

The number of broader terms included in the expansion is determined by the value for `level`.

qualifier

Specify a qualifier for `term`, if `term` is a homograph (word or phrase with multiple meanings, but the same spelling) that appears in two or more nodes in the same hierarchy branch of `thes`.

If a qualifier is not specified for a homograph in a broader term query, the query expands to include the broader terms of all the homographic terms.

level

Specify the number of levels traversed in the thesaurus hierarchy to return the broader terms for the specified term. For example, a level of 1 in a BT query returns the broader term entry, if one exists, for the specified term. A level of 2 returns the broader term entry for the specified term, as well as the broader term entry, if one exists, for the broader term.

The level argument is optional and has a default value of one (1). Zero or negative values for the level argument return only the original query term.

thes

Specify the name of the thesaurus used to return the expansions for the specified term. The `thes` argument is optional and has a default value of `DEFAULT`. A thesaurus named `DEFAULT` *must* exist in the thesaurus tables if you use this default value.

Note:

If you specify `thes`, then you must also specify `level`.

Examples for Broader Term Operators

The following query returns all documents that contain the term *tutorial* or the BT term defined for *tutorial* in the `DEFAULT` thesaurus:

```
'BT(tutorial)'
```

When you specify a thesaurus name, you must also specify `level` as in:

```
'BT(tutorial, 2, mythes)'
```

Broader Term Operator on Homographs

If *machine* is a broader term for *crane* (*building equipment*) and *bird* is a broader term for *crane* (*waterfowl*) and no qualifier is specified for a broader term query, the query

```
BT(crane)
```

expands to:

```
'{crane} or {machine} or {bird}'
```

If *waterfowl* is specified as a qualifier for *crane* in a broader term query, the query

```
BT(crane{waterfowl})
```

expands to the query:

```
'{crane} or {bird}'
```

Note:

When specifying a qualifier in a broader or narrower term query, the qualifier and its notation (parentheses) must be escaped, as is shown in this example.

Related Topics

[CTX_THES.BT](#) (page 14-4) in [CTX_THES Package](#) (page 14-1) for more information on browsing the broader terms in your thesaurus

3.6 CTXFILTERCACHE

Oracle Text provides a cache layer called query filter cache that can be used to cache the query results. Query filter cache is sharable across queries. Thus, the cached query results can be reused by multiple queries, improving the query response time. The CTXFILTERCACHE operator is used to specify which query results or part of query results to cache in the query filter cache.

CTXFILTERCACHE only supports CONTEXT grammar queries. CONTAINER queries like template queries are not supported. If you execute it with a template query, then errors are raised.

Caution:

Before using CTXFILTERCACHE, you must run `PURGE recyclebin` as follows:

```
SQL> PURGE recyclebin;
```

See *Oracle Database Administrator's Guide* for complete information about purging objects in the recycle bin.

Syntax

```
ctxfiltercache((query_text) [, save_score] [, topN])
```

query_text

Specify the query whose results need to be stored in the cache.

save_score

Specify `TRUE` if you want to cache all the query results along with their scores in the cache.

The default is `FALSE`. In this case, a score of 100 is returned for each query result, and these scores are not stored in the cache. Only the query results are stored in the cache.

Specify `FALSE` when you want to reuse the query results and not their scores in other queries. This is particularly useful when you use the query text as a filter, such as a security filter, where the relevance of the cached part of the query does not affect the relevance of the query as a whole. Thus, when used with the `AND` operator (which returns a lower score of its operands), a score of 100 does not affect the score of a query as a whole.

topN

Specify TRUE if you want only the highest scoring query results to be stored in the cache. Oracle Text internally determines how many highest scoring query results to store in the cache. This helps in reducing the memory consumption of the cache.

Note:

If you specify TRUE for topN, then save_score should also be TRUE.

Examples for CTXFILTERCACHE**Stored Query Results and TopN Examples**

The following example stores the query results of the common_predicate query in the cache:

```
select * from docs where contains(txt, 'ctxfiltercache((common_predicate),
FALSE)')>0;
```

Here, save_score is FALSE, and hence the score of 100 is returned for each query result, and the scores are not stored in the cache.

In the following example, the cached results of the common_predicate query are reused by the new_query query.

```
select * from docs where contains(txt, 'new_query &
ctxfiltercache((common_predicate), FALSE)')>0;
```

Set save_score to TRUE as shown in the following example to store all the query results of the common_predicate query, along with the actual scores, in the cache.

```
select * from docs where contains(txt, 'ctxfiltercache((common_predicate), TRUE)')>0;
```

Set topN to TRUE if you want to store only the highest scoring query results of the common_predicate query in the cache as described in the following example.

```
select id, score(1) from docs where contains(txt,
'ctxfiltercache((common_predicate), TRUE, TRUE)', 1)>0 order by score(1) desc;
```

Set topN to TRUE for the main part of the query and FALSE for the filter part, when the score is relevant only for the main part of the query. The following example shows a query with two ctxfiltercache clauses. It performs a free-text search for "cat AND dog" and then applies a security filter to the search operation. Results of both the parts of this query are separately cached so that they can be reused, but the score is relevant only for the first part of the query.

```
select id, score(1) from docs where contains(txt, 'ctxfiltercache((cat AND dog),
TRUE, TRUE) AND ctxfiltercache((john WITHIN allowedUsers), FALSE, FALSE)', 1) > 0;
```

Cached Score Example

CTXFILTERCACHE stores one query result for score at a time in the cache. Hence, two similar queries executed serially are considered the same query, and there is only one such query stored in the cache.

The following examples, query A and query B, show two similar queries. The hit score for A is 100, and the hit score for B is 5. Assume the cache is empty and you execute query A first. The computed score 100 is stored in the cache for this query. When you execute query B subsequently now, the cache contains the stored score of 100, and

therefore, query *B* returns the cached score of 100. Conversely, if you execute query *B* before query *A*, then the cached computed score that gets returned is 5.

Query A:

```
select /*+ DOMAIN_INDEX_SORT */ id, score(1) as ORADD from mydocs where contains
(txt , 'ctxfiltercache((DEFINEMERGE
      (      ((definescore(Oracle,relevance)),(definescore(Java,discrete)))
      ,OR,ADD
      )),T,T)',1)>0 order by score(1) desc;
```

Query B:

```
select /*+ DOMAIN_INDEX_SORT */ id, score(1) as ORAVG from docs where contains
(txt , 'ctxfiltercache((DEFINEMERGE
      (      ((definescore(Oracle,relevance)),(definescore(Java,discrete)))
      ,OR,AVG
      )),T,T)',1)>0 order by score(1) desc;
```

Notes

The query filter cache is an index level storage preference.

The storage preference for the query filter cache can be set at *partition* level only if this is also set at *index* level. If a filter cache preference is set at partition level without any filter cache preference being set at index level, then an error is thrown as follows: "Illegal syntax for index, preference, source or section name."

Note that CTXFILTERCACHE is not utilized with:

- INPATH/HASPATH queries
- First query after syncindex for NDATA and SDATA

When topN is FALSE, the CTXFILTERCACHE operator can be either a top-level operator or a child of the following operators:

- AND
- ACCUM
- NOT
- OR
- THRESHOLD (left side operand only)
- WEIGHT (left side operand only)

When topN is TRUE:

- The ctxfiltercache operator can be either a top-level operator or a child of the following operators:
 - AND
 - THRESHOLD (left side operand only)
 - WEIGHT (left side operand only)
- TopN is enabled only when the ctxfiltercache operator is used with the order key ORDER BY SCORE(n) DESC and Oracle hint DOMAIN_INDEX_SORT for global index. Additionally, for a partitioned index, be sure to have partition

pruning in your query. Otherwise, although topN is set to TRUE, normal mode will be used instead of topN mode.

Note:

The `ctxfiltercache` operator only supports a CONTEXT grammar query. This means that container queries like template queries are not supported.

If `ctxfiltercache` is used with a query template, then the following type of error will occur:

```
ERROR at line 1:
ORA-29902: error in executing ODCIIndexStart() routine
ORA-20000: Oracle Text error:
DRG-50900: text query parser error on line 1, column 8
DRG-50905: invalid score threshold <textquery
```

An example of a query that results in this error is as follows:

```
select score(1), id, txt from tdrbqfc45 where contains(txt,
'ctxfiltercache((<query><textquery>near2((a,b,c,d))
</textquery><score datatype="FLOAT"/>
</query>),true)', 1)>0 order by id;
```

To use `ctxfiltercache` you must specify a size for the query filter cache using the basic storage attribute `query_filter_cache_size`. The default size is 0, which means that `ctxfiltercache` is disabled by default.

The view `ctx_filter_cache_statistics` provides various statistics about the query filter cache.

The query filter cache does not differentiate queries that only vary in how the score is computed. Score is never computed on the fly within the query filter cache. See ["Cached Score Example" \(page 3-12\)](#) for an illustration of how this works.

Related Topics

["CTX_FILTER_CACHE_STATISTICS" \(page G-4\)](#) for more information about the `ctx_filter_cache_statistics` view

["BASIC_STORAGE" \(page 2-81\)](#) for more information about the `query_filter_cache_size` basic storage attribute

3.7 DEFINEMERGE

Use the `DEFINEMERGE` operator to define how the score of child nodes of the AND and OR should be merged. The `DEFINEMERGE` operator can be used as operand(s) of any operators that allow AND or OR as operands. The score can be merged in three ways: picking the minimum value, picking the maximum value, or calculating the average score of all child nodes.

Use [DEFINESCORE](#) (page 3-15) before using `DEFINEMERGE`.

Syntax

```
DEFINEMERGE ( ( (text_query1), (text_query2), ... ) , operator, merge_method )
```

Syntax	Description
<i>text_query1,2 ...</i>	Defines the search criteria. These parameters can have any value that is valid for the AND/OR operator.
<i>operator</i>	Defines the relationship between the two <i>text_query</i> parameters.
<i>merge_method</i>	Defines how the score of the <i>text_query</i> should be merged. Possible values: MIN, MAX, AVG, ADD

Example for DEFINEMERGE Operator

```
'DEFINEMERGE (((dog , cat) , (blue or black)), AND, MIN )'
```

Queries for the expression "dog ACCUM cat" and "blue OR black," using the default scoring schemes and then using the minimum score of the two as the merged-score.

```
'DEFINEMERGE( ((DEFINESCORE(dog, DISCRETE)) , (cat)), AND, MAX)'
```

Queries for the term "dog" using the DISCRETE scoring, and for the term "cat" using the default relevant scoring, and then using the maximum score of the two as the merged-score.

Example 3-1 DEFINEMERGE and text_query

The following examples show only the *text_query* part of a CONTAINS query:

```
'DEFINEMERGE ( ((dog), (cat)), OR, AVG)'
```

Queries for the term "dog" or "cat," using the average relevance score of both terms as the merged score.

Related Topic

[DEFINESCORE](#) (page 3-15).

3.8 DEFINESCORE

Use the DEFINESCORE operator to define how a term or phrase, or a set of term equivalences will be scored. The definition of a scoring expression can consist of an arithmetic expression of predefined scoring components and numeric literals.

[DEFINEMERGE](#) (page 3-14) can be used after DEFINESCORE.

Syntax

```
DEFINESCORE (query_term, scoring_expression)
```

query_term

The query term or phrase. Expressions containing the following operators are also allowed:

Operators	Operators
-	-
ABOUT	EQUIV(=)

Operators	Operators
Fuzzy	Soundex (!)
Stem (\$)	Wildcards (% _)
SDATA	MDATA

scoring_expression

An arithmetic expression that describes how the `query_term` should be scored. This operand is a string that contains the following components:

- Arithmetic operators: + - * /. The precedence is multiplication and division (*, /) first before addition and subtraction (+, -).
- Grouping operators: (). Parentheses can be used to alter the precedence of the arithmetic operators.
- Absolute function: ABS (n) returns the absolute value of n; where n is any expression that returns a number.
- Logarithmic function: LOG (n) returns the base-10 logarithmic value of n ; where n is any expression that returns a number.
- Predefined scoring components: Each of the following scoring components returns a value of 0 - 100, depending on different criteria:

Name	Description
DISCRETE	If the term exists in the document, score = 100. Otherwise, score = 0.
OCCURRENCE	Score based on the number of occurrences.
RELEVANCE	Score based on the document's relevance.
COMPLETION	Score based on coverage. Documents will score higher if the ratio between the number of the matching terms and the number of all terms in the section (counting stop words) is higher. The COMPLETION scoring is only applicable when used with the WITHIN operator to search in zone sections.
IGNORE	Ignore the scoring of this term. This component should be used alone. Otherwise, the query will return a syntax error. If the scoring of the only term in the query is set to IGNORE, then all the matching documents should be returned with the same score of 100.

Note:

For numeric literals, any number literal can be used that conforms to the SQL pattern of number literal, and is within the range of the double precision floating point (-3.4×10^{38} to 3.4×10^{38}).

scoring_expression Syntax

```

<Exp>    :=          <Exp> + <Term> | <Exp> - <Term> | <Term>

<Term>   :=          <Term> * <Factor> | <Term> / <Factor> | <Factor>

<Factor> :=          <<NumericLiterals >>| DISCRETE | OCCURRENCE | RELEVANCE |
                     COMPLETION | IGNORE | ( <Exp> ) | -<Factor> | Abs(<Exp>) | Log(<Exp>)

```

Examples for DEFINESCORE Operator

```
'DEFINESCORE (dog, OCCURRENCE)'
```

Queries for the word *dog*, and scores each document using the occurrence score. Returns the score as integer.

```
'DEFINESCORE (Labradors are big dog, RELEVANCE)'
```

Queries for the phrase *Labradors are big dogs*, and scores each document using the relevance score.

```
'cat and DEFINESCORE (dog, IGNORE)'
```

Queries for the words *dog* and *cat*, using only the default relevance score of *cat* as the overall score of the document. Returns the score as integer.

```
'DEFINESCORE (dog, IGNORE)'
```

Queries for the word *dog*, and returns all documents with the word *dog*. The result is the same as if all documents get a score of 100. Returns the score as integer.

```
'DEFINESCORE (dog, ABS (100-RELEVANCE))'
```

Queries for the word *dog*, and scores each document using the absolute value of 100 minus the relevance score. Returns the score as integer.

```
'cat and DEFINESCORE (dog, RELEVANCE*5 - OCCURRENCE)'
```

Returns a syntax error: Two predefined components are used.

When DEFINESCORE is used with query templates, the `scoring_expression` overrides the values specified by the template. The following example queries for "dog" and "cat," scores "cat" using OCCURRENCE (COUNT) and scores "dog" based on RELEVANCE.

```

<query>
  <textquery grammar="CONTEXT" lang="english">
    DEFINESCORE(dog, RELEVANCE) and cat
  </textquery>
  <score datatype="INTEGER" algorithm="COUNT"/>
</query>

```

Limitations

- If the ABOUT operator is used in `query_term`, the OCCURRENCE and COMPLETION scoring will not be applicable. If used, the query will return a syntax error.
- The IGNORE score cannot be used as right hand of the minus operator. If used, then a syntax error will occur.
- The COMPLETION score is only applicable if the DEFINESCORE is used with a WITHIN operator to search in zone sections, for example:

```
'DEFINESCORE (dog, COMPLETION) within zonesection'
```

otherwise, the query will return a syntax error.

- For the left hand operand of WITHIN:
 - All nodes must use the same predefined-scoring component. (If not specified, then the predefined scoring is RELEVANCE.)
 - If the nodes use DISCRETE or COMPLETION, then only the AND and OR operator is allowed as the left hand children of WITHIN.
 - If the nodes use DISCRETE or COMPLETION, then WITHIN will use the max score of all section instances as the score.
 - If the nodes use RELEVANCE or OCCURRENCE, then WITHIN will use the summation of the score of all section instances as the score.
- Only one predefined scoring component can be used in the `scoring_expression` at one time. If more than one predefined scoring component is used, then a syntax error will occur.

See Also:

Oracle Database SQL Language Reference

Notes

- The DEFINESCORE operator, the absolute function, the logarithmic function, and the predefined scoring components are case-insensitive.
- The `query_term` and the `scoring_expression` parameters are mandatory.
- The final score of the DEFINESCORE operator will be truncated to be in the 0 – 100 range. If the data type is INTEGER, then the score is rounded up.
- The intermediate data type of the scoring value is a double precision float. As a result, the value is limited to be in the -3.4×10^{38} to 3.4×10^{38} range. If the intermediate scoring of any document exceeds the value, then the score will be truncated. If an integer scoring is required, then the score will always be rounded up after the score is calculated.
- The DEFINESCORE operator can be used as an operand of the following operators:
 - AND

- NOT
- INPATH
- THRESHOLD
- WITHIN
- SQE
- OR
- DEFINEMERGE
- MINUS
- WEIGHT
- ACCUM

For example, the following statement is valid:

```
DEFINESCORE('dog', OCCURRENCE) AND DEFINESCORE('cat', RELEVANCE)
```

Queries for the term "dog" using occurrence scoring, and the term "cat" using relevance scoring.

- If DEFINESCORE is used as a parameter of other operators, then an error will be returned. For example, the following example returns an error:

```
SYN(DEFINESCORE('cat', OCCURRENCE))
```

- When used with query templates, the `scoring_expression` overrides the values specified by the template. For example,

```
<query>
  <textquery grammar="CONTEXT" lang="english">
    DEFINESCORE(dog, RELEVANCE) and cat
  </textquery>
  <score datatype="INTEGER" algorithm="COUNT"/>
</query>
```

Queries for "dog" and "cat", scores "cat" using `OCCURRENCE (COUNT)`, and scores "dog" based on `RELEVANCE`.

Related Topic

[DEFINEMERGE](#) (page 3-14).

3.9 EQUIValence (=)

Use the EQUIV operator to specify an acceptable substitution for a word in a query.

Syntax

Syntax	Description
<i>term1=term2</i>	Specifies that <code>term2</code> is an acceptable substitution for <code>term1</code> . Score calculated as the sum of all occurrences of both terms.
<i>term1 equiv term2</i>	

Example for EQUIV Operator

The following example returns all documents that contain either the phrase *alsatians are big dogs* or *labradors are big dogs*:

```
'labradors=alsatians are big dogs'
```

Operator Precedence

The `EQUIV` operator has higher precedence than all other operators except the expansion operators (fuzzy, soundex, stem).

3.10 Fuzzy

Use the `fuzzy` operator to expand queries to include words that are spelled similarly to the specified term. This type of expansion is helpful for finding more accurate results when there are frequent misspellings in your document set.

The `fuzzy` syntax enables you to rank the result set so that documents that contain words with high similarity to the query word are scored higher than documents with lower similarity. You can also limit the number of expanded terms.

Unlike stem expansion, the number of words generated by a `fuzzy` expansion depends on what is in the index. Results can vary significantly according to the contents of the index.

Supported Languages

Oracle Text supports `fuzzy` definitions for English, French, German, Italian, Dutch, Spanish, Portuguese, Japanese, OCR, and auto-language detection.

Stopwords

If the `fuzzy` expansion returns a stopword, the stopword is not included in the query or highlighted by `CTX_DOC.HIGHLIGHT` or `CTX_DOC.MARKUP`.

Base-Letter Conversion

If base-letter conversion is enabled for a text column and the query expression contains a `fuzzy` operator, Oracle Text operates on the base-letter form of the query.

Syntax

```
fuzzy(term, score, numresults, weight)
```

Parameter	Description
term	Specify the word on which to perform the <code>fuzzy</code> expansion. Oracle Text expands <code>term</code> to include words only in the index. The word needs to be at least 3 characters for the <code>fuzzy</code> operator to process it.
score	Specify a similarity score. Terms in the expansion that score below this number are discarded. Use a number between 1 and 80. The default is 60.
numresults	Specify the maximum number of terms to use in the expansion of <code>term</code> . Use a number between 1 and 5000. The default is 100.

Parameter	Description
weight	Specify WEIGHT or W for the results to be weighted according to their similarity scores. Specify NOWEIGHT or N for no weighting of results.

Examples for Fuzzy Operator

Consider the CONTAINS query:

```
...CONTAINS(TEXT, 'fuzzy(government, 70, 6, weight)', 1) > 0;
```

This query expands to the first six fuzzy variations of *government* in the index that have a similarity score over 70.

In addition, documents in the result set are weighted according to their similarity to *government*. Documents containing words most similar to government receive the highest score.

Skip unnecessary parameters using the appropriate number of commas. For example:

```
'fuzzy(government,,,weight)'
```

Backward Compatibility Syntax

The old fuzzy syntax from previous releases is still supported. This syntax is as follows:

Parameter	Description
?term	Expands term to include all terms with similar spellings as the specified term. Term needs to be at least 3 characters for the fuzzy operator to process it.

3.11 HASPATH

Use the HASPATH operator to find all XML documents that contain a specified section path. You can also use this operator to do section equality testing.

Your index must be created with the PATH_SECTION_GROUP for this operator to work.

Syntax

Syntax	Description
HASPATH(path)	Searches an XML document set and returns a score of 100 for all documents where <i>path</i> exists. Separate parent and child paths with the / character. For example, you can specify A/B/C. See example.

Syntax	Description
HASPATH(A="value")	Searches an XML document set and returns a score of 100 for all documents that have the element A with content <i>value</i> and only <i>value</i> . See example.

Using Special Characters with HASPATH and INPATH

The following rules govern the use of special characters with regard to both the HASPATH and INPATH operators:

- Left-brace ({) and right-brace (}) characters are not allowed inside HASPATH or INPATH expressions unless they are inside the equality operand enclosed by double quotes. So both 'HASPATH ({ /A/B })' and 'HASPATH (/A/ { B })' will return errors. However, 'HASPATH (/A[B= " { author } "])' will be parsed correctly.
- With exception of the backslash (\), special characters, such as dollar sign (\$), percent sign (%), underscore (_), left brace ({), and right brace (}), when inside the equality operand enclosed by double or single quotes, have no special meaning. (That is, no stemming, wildcard expansion, or similar processing will be performed on them.) However, they are still subject to regular text lexing and will be translated to whitespace, with the exception of characters declared as printjoins. A backslash will still escape any character that immediately follows it.

For example, if the hyphen (-) and the double quote character (") are defined as printjoins in a lexer preference, then:

- The string *B_TEXT* inside HASPATH (/A[B= " B_TEXT ") will be lexed as the phrase *B TEXT*.
- The string *B-TEXT* inside HASPATH (/A[B= " B-TEXT ") will be lexed as the word *B-TEXT*.
- The string *B'TEXT* inside HASPATH (/A[B= " B'TEXT ") will be lexed as the word *B'TEXT*. You must use a backslash to escape the double quote between *B* and *TEXT*, or you will get a parsing error.
- The string *{B_TEXT}* inside HASPATH (/A[B= " { B_TEXT } ") will be lexed as a phrase *B TEXT*.

Examples for HASPATH Operator

Path Testing

The query

```
HASPATH(A/B/C)
```

finds and returns a score of 100 for the document

```
<A><B><C>dog</C></B></A>
```

without the query having to reference *dog* at all.

Section Equality Testing

The query

```
dog INPATH A
```

finds

```
<A>dog</A>
```

but it also finds

```
<A>dog park</A>
```

To limit the query to the term *dog* and nothing else, you can use a section equality test with the HASPATH operator. For example,

```
HASPATH(A="dog")
```

finds and returns a score of 100 only for the first document, and not the second.

Limitations

Because of how XML section data is recorded, false matches might occur with XML sections that are completely empty as follows:

```
<A><B><C></C></B><D><E></E></D></A>
```

A query of HASPATH(A/B/E) or HASPATH(A/D/C) falsely matches this document. This type of false matching can be avoided by inserting text between empty tags.

False matches might also occur when the document has empty elements but has values in attributes, as in the following example document:

```
<Test>
<Client id="1">
  <Info infoid="1"/>
</Client>
<Client id="2">
  <Info infoid="2"/>
</Client>
</Test>
```

When searching with the following query, the query returns the document shown in the example, which is a false match.

The following query was used to return the example document, which is a false match:

```
SELECT main_detail_logging_id, t.xml_data.getstringval() xml_data FROM
TEST_XMLTYPE t
WHERE CONTAINS(t.xml_data,
'HASPATH(/Test/Client[@id="1"]/Info[@infoid="2"])' ) > 0;
```

3.12 INPATH

Use the INPATH operator to do path searching in XML documents. This operator is like the WITHIN operator except that the right-hand side is a parentheses enclosed path, rather than a single section name.

Your index must be created with the PATH_SECTION_GROUP for the INPATH operator to work.

Syntax

The INPATH operator has the following syntax:

Top-Level Tag Searching

Syntax	Description
term INPATH (/A)	Returns documents that have <i>term</i> within the <A> and tags.
term INPATH (A)	

Any-Level Tag Searching

Syntax	Description
term INPATH (//A)	Returns documents that have <i>term</i> in the <A> tag at any level. This query is the same as ' <i>term WITHIN A</i> '

Direct Parentage Path Searching

Syntax	Description
term INPATH (A/B)	Returns documents where <i>term</i> appears in a B element which is a direct child of a top-level A element. For example, a document containing <A>term is returned.

Single-Level Wildcard Searching

Syntax	Description
term INPATH (A/*/B)	Returns documents where <i>term</i> appears in a B element which is a grandchild (two levels down) of a top-level A element. For example a document containing <A><D>term</D> is returned.

Multi-level Wildcard Searching

Syntax	Description
term INPATH (A/*/B/**/C)	Returns documents where <i>term</i> appears in a C element which is 3 levels down from a B element which is two levels down (grandchild) of a top-level A element.

Any-Level Descendant Searching

Syntax	Description
term INPATH(A / B)	Returns documents where term appears in a B element which is some descendant (any level) of a top-level A element.

Attribute Searching

Syntax	Description
term INPATH (/ A / @B)	Returns documents where <i>term</i> appears in the B attribute of an A element at any level. Attributes must be bound to a direct parent.

Descendant / Attribute Existence Testing

Syntax	Description
term INPATH (A[B])	Returns documents where term appears in a top-level A element which has a B element as a direct child.
term INPATH (A[. / B])	Returns documents where term appears in a top-level A element which has a B element as a descendant at any level.
term INPATH (/ A[@B])	Finds documents where term appears in an A element at any level which has a B attribute. Attributes must be tied to a direct parent.

Attribute Value Testing

Syntax	Description
term INPATH (A[@B = "value"])	Finds all documents where <i>term</i> appears in a top-level A element which has a B attribute whose value is <i>value</i> .
term INPATH (A[@B != "value"])	Finds all documents where <i>term</i> appears in a top-level A element which has a B attribute whose value is not <i>value</i> .

Tag Value Testing

Syntax	Description
term INPATH (A[B = "value"])	Returns documents where <i>term</i> appears in an A tag which has a B tag whose value is <i>value</i> .

Not

Syntax	Description
term INPATH (A[NOT(B)])	Finds documents where <i>term</i> appears in a top-level A element which does not have a B element as an immediate child.

AND and OR Testing

Syntax	Description
term INPATH (A[B and C])	Finds documents where <i>term</i> appears in a top-level A element which has a B and a C element as an immediate child.
term INPATH (A[B and @C="value"])	Finds documents where <i>term</i> appears in a top-level A element which has a B element and a C attribute whose value is <i>value</i> .
term INPATH (A [B OR C])	Finds documents where <i>term</i> appears in a top-level A element which has a B element or a C element.

Combining Path and Node Tests

Syntax	Description
term INPATH (A[@B = "value"]/C/D)	Returns documents where <i>term</i> appears in a D element which is the child of a C element, which is the child of a top-level A element with a B attribute whose value is <i>value</i> .

Nested INPATH

Nest the entire INPATH expression in another INPATH expression as follows:

```
(dog INPATH (//A/B/C)) INPATH (D)
```

When you do so, the two INPATH paths are completely independent. The outer INPATH path does not change the context node of the inner INPATH path. For example:

```
(dog INPATH (A)) INPATH (D)
```

never finds any documents, because the inner INPATH is looking for *dog* within the top-level tag A, and the outer INPATH constrains that to document with top-level tag D. A document can have only one top-level tag, so this expression never finds any documents.

Case-Sensitivity

Tags and attribute names in path searching are case-sensitive. That is,

```
dog INPATH (A)
```

finds <A>dog but does not find <a>dog. Instead use

`dog INPATH (a)`

Using Special Characters with INPATH

See "[Using Special Characters with HASPATH and INPATH](#) (page 3-22)" for information on using special characters, such as the percent sign (%) or the backslash (\), with INPATH.

Examples for INPATH Operator

Top-Level Tag Searching

To find all documents that contain the term *dog* in the top-level tag <A>:

`dog INPATH (/A)`

or

`dog INPATH(A)`

Any-Level Tag Searching

To find all documents that contain the term *dog* in the <A> tag at any level:

`dog INPATH(//A)`

This query finds the following documents:

`<A>dog`

and

`<C><A>dog</C>`

Direct Parentage Searching

To find all documents that contain the term *dog* in a B element that is a direct child of a top-level A element:

`dog INPATH(A/B)`

This query finds the following XML document:

`<A>My dog is friendly.`

but does not find:

`<C>My dog is friendly.</C>`

Tag Value Testing

You can test the value of tags. For example, the query:

`dog INPATH(A[B="dog"])`

Finds the following document:

`<A>dog`

But does not find:

`<A>My dog is friendly.`

Attribute Searching

You can search the content of attributes. For example, the query:

```
dog INPATH (//A/@B)
```

Finds the document

```
<C><A B="snoop dog"> </A> </C>
```

Attribute Value Testing

You can test the value of attributes. For example, the query

```
California INPATH (//A[@B = "home address"])
```

Finds the document:

```
<A B="home address">San Francisco, California, USA</A>
```

But does not find:

```
<A B="work address">San Francisco, California, USA</A>
```

Path Testing

You can test if a path exists with the HASPATH operator. For example, the query:

```
HASPATH(A/B/C)
```

finds and returns a score of 100 for the document

```
<A><B><C>dog</C></B></A>
```

without the query having to reference *dog* at all.

Limitations

Testing for Equality

The following is an example of an INPATH equality test.

```
dog INPATH (A[@B = "foo"])
```

The following limitations apply for these expressions:

- Only equality and inequality are supported. Range operators and functions are not supported.
- The left hand side of the equality must be an attribute. Tags and literals here are not enabled.
- The right hand side of the equality must be a literal. Tags and attributes here are not allowed.
- The test for equality depends on your lexer settings. With the default settings, the query

```
dog INPATH (A[@B= "pot of gold"])
```

matches the following sections:

```
<A B="POT OF GOLD">dog</A>
```

and

```
<A B="pot of gold">dog</A>
```

because lexer is case-insensitive by default.

```
<A B="POT IS GOLD">dog</A>
```

because *of* and *is* are default stopwords in English, and a stopword matches any stopword word.

```
<A B="POT_OF_GOLD">dog</A>
```

because the underscore character is not a join character by default.

3.13 MDATA

Use the MDATA operator to query documents that contain MDATA sections. MDATA sections are metadata that have been added to documents to speed up mixed querying.

MDATA queries are treated exactly as literals. For example, with the query:

```
MDATA(price, $1.24)
```

the \$ is not interpreted as a stem operator, nor is the . (period) transformed into whitespace. A right (close) parenthesis terminates the MDATA operator, so that MDATA values that have close parentheses cannot be searched.

Syntax

```
MDATA(sectionname, value)
```

sectionname

The name of the MDATA section(s) to search. MDATA will also search DATE or numerical equality if the sectionname parameter is mapped to a FILTER BY column of DATE or some numerical type.

value

The value of the MDATA section. For example, if an MDATA section called Booktype has been created, it might have a value of *paperback*.

For MDATA operator on MDATA sections that are mapped to a DATE FILTER BY column, the MDATA value must follow the Date format: YYYY-MM-DD HH24:MI:SS. Otherwise, the expected rows will not be returned. If the time component is omitted, it will default to 00:00:00, according to SQL semantics.

Example for MDATA Operator

Suppose you want to query for books written by the writer *Nigella Lawson* that contain the word *summer*. Assuming that an MDATA section called AUTHOR has been declared, you can query as follows:

```
SELECT id FROM idx_docs
WHERE CONTAINS(text, 'summer AND MDATA(author, Nigella Lawson)')>0
```

This query will only be successful if an AUTHOR tag has the exact value *Nigella Lawson* (after simplified tokenization). *Nigella* or *Ms. Nigella Lawson* will not work.

Notes

MDATA query values ignore stopwords.

The MDATA operator returns an unlimited number of results or 0, depending on whether the document is a match. You can set the maximum.

The MDATA operator is not supported for CTXCAT and CTXRULE indexes.

Table 3-2 (page 3-30) shows how MDATA interacts with some other query operators:

Table 3-2 MDATA and Other Query Operators

Operator	Example	Allowed?
AND	dog & MDATA(a, b)	yes
OR	dog MDATA(a, b)	yes
NOT	dog ~ MDATA(a, b)	yes
MINUS	dog - MDATA(a, b)	yes
ACCUM	dog , MDATA(a, b)	yes
PHRASE	MDATA(a, b) dog	no
NEAR	MDATA(a, b) ; dog	no
WITHIN, HASPATH, INPATH	MDATA(a, b) WITHIN c	no
Thesaurus	MDATA(a, SYN(b))	no
expansion	MDATA(a, \$b) MDATA(a, b%) MDATA(a, !b) MDATA(a, ?b)	no (syntactically allowed, but the inner operator is treated as literal text)
ABOUT	ABOUT(MDATA(a,b)) MDATA(ABOUT(a))	no (syntactically allowed, but the inner operator is treated as literal text)

When MDATA sections repeat, each instance is a separate and independent value. For instance, the document

```
<AUTHOR>Terry Pratchett</AUTHOR><AUTHOR>Douglas Adams</AUTHOR>
```

can be found with any of the following queries:

```
MDATA(author, Terry Pratchett)
MDATA(author, Douglas Adams)
MDATA(author, Terry Pratchett) and MDATA(author, Douglas Adams)
```

but not any of the following:

```
MDATA(author, Terry Pratchett Douglas Adams)
MDATA(author, Terry Pratchett & Douglas Adams)
MDATA(author, Pratchett Douglas)
```

Related Topics

["ADD_MDATA" \(page 8-9\)](#)

["ADD_MDATA_SECTION" \(page 8-12\)](#)

See Also:

Oracle Text Application Developer's Guide for information about section searching

3.14 MINUS (-)

Use the MINUS operator to lower the score of documents that contain unwanted noise terms. MINUS is useful when you want to search for documents that contain one query term but want the presence of a second term to cause a document to be ranked lower.

Syntax

Syntax	Description
<i>term1-term2</i>	Returns documents that contain <i>term1</i> . Calculates score by subtracting the score of <i>term2</i> from the score of <i>term1</i> . Only documents with positive score are returned.
<i>term1</i> minus <i>term2</i>	

Example for MINUS Operator

Suppose a query on the term *cars* always returned high scoring documents about *Ford cars*. You can lower the scoring of the Ford documents by using the expression:

```
'cars - Ford'
```

In essence, this expression returns documents that contain the term *cars* and possibly *Ford*. However, the score for a returned document is the score of *cars* minus the score of *Ford*.

Related Topics

["NOT \(~\)" \(page 3-39\)](#)

3.15 MNOT

The Mild Not (MNOT) operator is similar to the NOT and MINUS operators. The Mild Not operator returns hits where the left child is not contained by the right child. Both children can only be TERM or PHRASE nodes.

The semantics can be illustrated with a query of "term1 mnot term1 term2", where the hits for "term1 term2" will be filtered out. For example:

- A document with only *term1* will be returned, with score unchanged.
- A document with only *term1 term2* will not be returned.
- A document with *term1 term1 term2* will be returned, but the score will be calculated using just the first *term1* hit.

The behavior described in the third bullet is different from the behavior of NOT, which does not return this type of document.

The MNOT operator is more specific than the MINUS operator, in that the left child must be contained by the right child. If it is not, the Mild Not operator ignores the right child. Also, for Mild Not, the right child is a true filter, that is, it does not simply subtract the scores of left child and right child.

The MNOT operator has precedence lower than NOT and higher than WITHIN.

Syntax

Syntax	Description
<i>term1</i> mnot <i>term1 term2</i>	Returns docs that contain <i>term1</i> unless it is part of the phrase <i>term1 term2</i> .
<i>term1</i> mnot <i>term2</i>	Returns all documents that contain <i>term1</i> . It will be the same query as just <i>term1</i> .

Example for MNOT Operator

The children of the MNOT operator must be a TERM or PHRASE.

```
SELECT * FROM docs
WHERE CONTAINS(txt, 'term1 mnot term1 term2') >0
```

Related Topic

["NOT \(~\) \(page 3-39\)"](#)

3.16 Narrower Term (NT, NTG, NTP, NTI)

Use the narrower term operators (NT, NTG, NTP, NTI) to expand a query to include all the terms that have been defined in a thesaurus as the narrower or lower level terms for a specified term. They can also expand the query to include all of the narrower terms for each narrower term, and so on down through the thesaurus hierarchy.

Syntax

Syntax	Description
NT(<i>term</i> [(<i>qualifier</i>)][, <i>level</i>][, <i>thes</i>])	Expands a query to include all the lower level terms defined in the thesaurus as narrower terms for <i>term</i> .
NTG(<i>term</i> [(<i>qualifier</i>)][, <i>level</i>][, <i>thes</i>])	Expands a query to include all the lower level terms defined in the thesaurus as narrower generic terms for <i>term</i> .
NTP(<i>term</i> [(<i>qualifier</i>)][, <i>level</i>][, <i>thes</i>])	Expands a query to include all the lower level terms defined in the thesaurus as narrower partitive terms for <i>term</i> .

Syntax	Description
<code>NTI(term[(qualifier)][,level][,thes])</code>	Expands a query to include all the lower level terms defined in the thesaurus as narrower instance terms for <code>term</code> .

term

Specify the operand for the narrower term operator. `term` is expanded to include the narrower term entries defined for the term in the thesaurus specified by `thes`. The number of narrower terms included in the expansion is determined by the value for `level`. You cannot specify expansion operators in the `term` argument.

qualifier

Specify a qualifier for `term`, if `term` is a homograph (word or phrase with multiple meanings, but the same spelling) that appears in two or more nodes in the same hierarchy branch of `thes`.

If a qualifier is not specified for a homograph in a narrower term query, the query expands to include all of the narrower terms of all homographic terms.

level

Specify the number of levels traversed in the thesaurus hierarchy to return the narrower terms for the specified term. For example, a level of 1 in an NT query returns all the narrower term entries, if any exist, for the specified term. A level of 2 returns all the narrower term entries for the specified term, as well as all the narrower term entries, if any exist, for each narrower term.

The level argument is optional and has a default value of one (1). Zero or negative values for the level argument return only the original query term.

thes

Specify the name of the thesaurus used to return the expansions for the specified term. The `thes` argument is optional and has a default value of `DEFAULT`. A thesaurus named `DEFAULT` *must* exist in the thesaurus tables if you use this default value.

Note:

If you specify `thes`, then you must also specify `level`.

Examples for Narrower Term Operators

The following query returns all documents that contain either the term *cat* or any of the NT terms defined for *cat* in the `DEFAULT` thesaurus:

```
'NT(cat)'
```

If you specify a thesaurus name, then you must also specify `level` as in:

```
'NT(cat, 2, mythes)'
```

The following query returns all documents that contain either *fairy tale* or any of the narrower instance terms for *fairy tale* as defined in the `DEFAULT` thesaurus:

```
'NTI(fairy tale)'
```

That is, if the terms *cinderella* and *snow white* are defined as narrower term instances for *fairy tale*, Oracle Text returns documents that contain *fairy tale*, *cinderella*, or *snow white*.

Notes

Each hierarchy in a thesaurus represents a distinct, separate branch, corresponding to the four narrower term operators. In a narrower term query, Oracle Text only expands the query using the branch corresponding to the specified narrower term operator.

Related Topic

CTX_THES.NT (page 14-19) in [CTX_THES Package](#) (page 14-1) for more information on browsing the narrower terms in your thesaurus

3.17 NDATA

Use the NDATA operator to find matches that are spelled in a similar way or where rearranging the terms of the specified phrase is useful. It is helpful for finding more accurate results when there are frequent misspellings (or inaccurate orderings) of name data in the document set. This operator can be used only on defined NDATA sections. The NDATA syntax enables you to rank the result set so that documents that contain words with high orthographic similarity are scored higher than documents with lower similarity.

Normalization

A lexer does not process NDATA query phrases. Users can, however, set base letter and alternate spelling attributes for a particular section group containing NDATA sections. Query case is normalized and non-character data (except for white space) is removed (for example, numerical or punctuation).

Syntax

```
ndata(sectionname, phrase [,order][,proximity])
```

Parameter Name	Default Value	Parameter Description
sectionname		Specify the name of a defined NDATA sections to query (that is, <code>section_name</code>)
phrase		<p>Specify the phrase for the name data query.</p> <p>The phrase parameter can be a single word or a phrase, or a string of words in free text format.</p> <p>The score returned is a relevant score.</p> <p>Oracle Text ignores any query operators that are included in phrase.</p> <p>The phrase should be a minimum of two characters in length and should not exceed 4000 characters in length.</p>

Parameter Name	Default Value	Parameter Description
order	NOORDER	Specify whether individual tokens (terms) in a query should be matched in-order or in any order. The order parameter provides a primary filter for matching candidate documents. ORDER or O - The query terms are matched in-order. NOORDER or N [DEFAULT] - The query terms are matched in any order.
proximity	NOPROXIMITY	Specify whether the proximity of terms should influence the similarity score of candidate matches. That is, if the proximity parameter is enabled, non-matching additional terms between matching terms will reduce the similarity score of candidate matches. PROXIMITY or P - The similarity score influenced by the proximity of query terms in candidate matches. NOPROXIMITY or N [DEFAULT] - The similarity score is not influenced by the proximity of query terms in candidate matches.

Examples for NDATA Operator

An NDATA query on an indexed surname section name that matches terms in the query phrase in any order without influencing the similarity score by the proximity of the black and smith terms has the form:

```
SELECT entryid, SCORE(1) FROM people WHERE
CONTAINS(idx_column, 'NDATA(surname, black smith)',1)>0;
```

An NDATA query on an indexed surname section name that matches terms in the query phrase in any order and in which similarity scores are influenced by the proximity of the black and smith terms has the form:

```
SELECT entryid, SCORE(1) FROM people WHERE
CONTAINS(idx_column, 'NDATA(surname, black smith,,proximity)',1)>0;
```

An NDATA query on an indexed surname section name that matches terms in the query phrase in-order without influencing the similarity score by the proximity of the black and smith terms has the form:

```
SELECT entryid, SCORE(1) FROM people WHERE
CONTAINS(idx_column, 'NDATA(surname, black smith, order)',1)>0;
```

An NDATA query on an indexed surname section name that matches terms in the query phrase in-order and in which similarity scores are influenced by the proximity of the black and smith terms has the form:

```
SELECT entryid, SCORE(1) FROM people WHERE
CONTAINS(idx_column, 'NDATA(surname, black smith, order, proximity)',1)>0;
```

Notes

The NDATA query operator does not provide offset information. As such, it cannot be used as a child of WITHIN, NEAR(;), or EQUIV(=), and NDATA sections will be

ignored by CTX_DOC.HIGHLIGHT, CTX_DOC.SNIPPET, and CTX_DOC.MARKUP. The NDATA operator also is not supported in the CTXCAT grammar. It can be used with other operators, including OR and query templates.

A use case of the NDATA operator may involve finding a particular entry based on an approximate spelling of a person's full-name and an estimated date-of-birth. Supposing the entries' date-of-births are stored as an SDATA section, user-defined scoring's alternate scoring template can be used to combine the scores of the full-name's NDATA section data and the date-of-birth's SDATA section data.

The name *john smith* is queried for the section specified by the fullname section_name. Altering the NDATA operator's score based on the closeness of the SDATA section's date-of-birth to the date 08-NOV-2012 modifies the ranking of matching documents as follows:

```
<query>
  <textquery grammar="CONTEXT" lang="english">
    NDATA(fullname, john smith)
  </textquery>
  <score algorithm="COUNT" normalization_expr =
    "doc_score-(DATE(8-NOV-2012)-sdata:dob)" />
</query>
```

Restrictions

The NDATA query operator does not work with [CTX_DOC Package](#) (page 9-1) procedures. Attempting to use NDATA with CTX_DOC procedures will return an error stating that this is not supported.

3.18 NEAR (;

Use the NEAR operator to return a score based on the proximity of two or more query terms. Oracle Text returns higher scores for terms closer together and lower scores for terms farther apart in a document. If a word or term appears more than once in a NEAR query, then the word must appear more than once in the document in order to match.

Note:

The NEAR operator works with only word queries. You cannot use NEAR in ABOUT queries.

Syntax

```
NEAR((word1,word2,...,wordn) [, max_span [, order [, maxreqd]]])
```

Backward compatibility syntax:

```
word1;word2
```

word1-n

Specify the terms in the query separated by commas. The query terms can be single words or phrases and may make use of other query operators (see "[NEAR with Other Operators](#) (page 3-37)").

max_span

Optionally specify the size of the biggest clump. The default is 100. Oracle Text returns an error if you specify a number greater than 100.

A clump is the smallest group of words in which all query terms occur. All clumps begin and end with a query term.

For near queries with two terms, `max_span` is the maximum distance allowed between the two terms. For example, to query on *dog* and *cat* where *dog* is within 6 words of *cat*, enter the following query:

```
'near((dog, cat), 6)'
```

order

Specify TRUE for Oracle Text to search for terms in the order you specify. The default is FALSE.

For example, to search for the words *monday*, *tuesday*, and *wednesday* in that order with a maximum clump size of 20, enter the following query:

```
'near((monday, tuesday, wednesday), 20, TRUE)'
```

Note:

To specify `order`, then you must always specify a number for `max_span`.

Oracle Text might return different scores for the same document when you use identical query expressions that have the `order` flag set differently. For example, Oracle Text might return different scores for the same document when you enter the following queries:

```
'near((dog, cat), 50, FALSE)'
'near((dog, cat), 50, TRUE)'
```

NEAR Scoring

The scoring for the NEAR operator combines frequency of the terms with proximity of terms. For each document that satisfies the query, Oracle Text returns a score between 1 and 100 that is proportional to the number of clumps in the document and inversely proportional to the average size of the clumps. This means many small clumps in a document result in higher scores, because small clumps imply closeness of terms.

The number of terms in a query also affects score. Queries with many terms, such as seven, generally need fewer clumps in a document to score 100 than do queries with few terms, such as two.

A *clump* is the smallest group of words in which all query terms occur. All clumps begin and end with a query term. Define clump size with the `max_span` parameter, as described in this section.

The size of a clump does not include the query terms themselves. So for the query `NEAR((DOG, CAT) , 1)`, *dog cat* will be a match, and *dog ate cat* will be a match, but *dog sat on cat* will *not* be a match.

NEAR with Other Operators

You can use the NEAR operator with other operators such as AND and OR. Scores are calculated in the regular way.

For example, to find all documents that contain the terms *tiger*, *lion*, and *cheetah* where the terms *lion* and *tiger* are within 10 words of each other, enter the following query:

```
'near((lion, tiger), 10) AND cheetah'
```

The score returned for each document is the lower score of the near operator and the term *cheetah*.

You can also use the equivalence operator to substitute a single term in a near query:

```
'near((stock crash, Japan=Korea), 20)'
```

This query asks for all documents that contain the phrase *stock crash* within twenty words of *Japan* or *Korea*.

The following NEAR syntax is now valid:

```
SELECT * FROM docs WHERE CONTAINS(txt, 'near((aterm1 aterm2 ... atermI
OR bterm1 bterm2 ... btermJ
OR cterm1 cterm2 ... ctermK, dterm)))' >0
```

There can be any number of ORs in a given NEAR child, and the OR can appear in any of the NEAR children.

The NEAR within NEAR feature allows users to use nested proximity queries. Users can execute queries such as the following:

```
SELECT * FROM docs
WHERE CONTAINS(txt, 'near((near((term1, term2),5), term3), 100)')>0
```

This will return documents where *term1*, *term2*, and *term3* are near within a 100 token window and, additionally, the tokens *term1* and *term2* are near within a 5 token window.

Mixing the semicolon and NEAR syntax is not supported and will throw an error. That is, the queries "near((a;b,c),3)" or "near((a,b);c)" will be disallowed.

The following operators also work with NEAR and ; :

- EQUIV
- All expansion operators that produce words, phrases, or EQUIV. These include:
 - soundex
 - fuzzy
 - wildcards
 - stem

Backward Compatibility NEAR Syntax

You can write near queries using the syntax of previous Oracle Text releases. However, in a nested NEAR query, the semicolon operator cannot be used as the inner NEAR. That is, the query 'near((a;d),f),3)' produces a syntax error. The semicolon operator can be used as the outermost NEAR in a nested NEAR query.

For example, to find all documents where *lion* occurs near *tiger*, write:

```
'lion near tiger'
```

or with the semi-colon as follows:

```
'lion;tiger'
```

This query is equivalent to the following query:

```
'near((lion, tiger), 100, FALSE)'
```

Note:

Only the syntax of the NEAR operator is backward compatible. In the example, the score returned is calculated using the clump method as described in this section.

Highlighting with the NEAR Operator

When you use highlighting and your query contains the near operator, all occurrences of all terms in the query that satisfy the proximity requirements are highlighted. Highlighted terms can be single words or phrases.

For example, assume a document contains the following text:

```
Chocolate and vanilla are my favorite ice cream flavors. I like chocolate served
in a waffle cone, and vanilla served in a cup with carmel syrup.
```

If the query is *near((chocolate, vanilla), 100, FALSE)*, the following is highlighted:

```
<<Chocolate>> and <<vanilla>> are my favorite ice cream flavors. I like
<<chocolate>> served in a waffle cone, and <<vanilla>> served in a cup with
caramel syrup.
```

However, if the query is *near((chocolate, vanilla), 4, FALSE)*, only the following is highlighted:

```
<<Chocolate>> and <<vanilla>> are my favorite ice cream flavors. I like
chocolate served in a waffle cone, and vanilla served in a cup with carmel syrup.
```

See Also:

[CTX_DOC Package](#) (page 9-1) for more information about the procedures for highlighting

Section Searching and NEAR

Use the NEAR operator with the WITHIN operator for section searching as follows:

```
'near((dog, cat), 10) WITHIN Headings'
```

When evaluating expressions such as these, Oracle Text looks for clumps that lie entirely within the given section.

In this example, only those clumps that contain *dog* and *cat* that lie entirely within the section *Headings* are counted. That is, if the term *dog* lies within *Headings* and the term *cat* lies five words from *dog*, but outside of *Headings*, this pair of words does not satisfy the expression and is not counted.

3.19 NOT (~)

Use the NOT operator to search for documents that contain one query term and not another.

Syntax

Syntax	Description
<i>term1</i> ~ <i>term2</i>	Returns documents that contain <i>term1</i> and not <i>term2</i> .
<i>term1</i> not <i>term2</i>	

Examples for NOT Operator

To obtain the documents that contain the term *animals* but not *dogs*, use the following expression:

```
'animals ~ dogs'
```

Similarly, to obtain the documents that contain the term *transportation* but not *automobiles* or *trains*, use the following expression:

```
'transportation not (automobiles or trains)'
```

Note:

The NOT operator does not affect the scoring produced by the other logical operators.

Related Topics

["MINUS \(-\) \(page 3-31\)"](#)

3.20 OR (|)

Use the OR operator to search for documents that contain at least one occurrence of *any* of the query terms. The OR operator returns documents that contain *any* of the query terms, while the AND operator returns documents that contain *all* query terms.

Syntax

Syntax	Description
<i>term1</i> <i>term2</i>	Returns documents that contain <i>term1</i> or <i>term2</i> . Returns the maximum score of its operands. At least one term must exist; higher score taken.
<i>term1</i> or <i>term2</i>	

Examples for OR Operator

To obtain the documents that contain the term *cats* or the term *dogs*, use either of the following expressions:

```
'cats | dogs'
'cats OR dogs'
```


Scoring

In an OR query, the score returned is the score for the highest query term. In the example, if the scores for *cats* and *dogs* is 30 and 40 within a document, the document scores 40.

Related Topics

["AND \(&\)"](#) (page 3-8)"

3.21 Preferred Term (PT)

Use the preferred term operator (PT) to replace a term in a query with the preferred term that has been defined in a thesaurus for the term.

Syntax

Syntax	Description
PT(<i>term</i> [, <i>thes</i>])	Replaces the specified word in a query with the preferred term for <i>term</i> .

term

Specify the operand for the preferred term operator. *term* is replaced by the preferred term defined for the term in the specified thesaurus. However, if no PT entries are defined for the term, *term* is not replaced in the query expression and *term* is the result of the expansion.

You cannot specify expansion operators in the *term* argument.

thes

Specify the name of the thesaurus used to return the expansions for the specified term. The *thes* argument is optional and has a default value of DEFAULT. As a result, a thesaurus named DEFAULT *must* exist in the thesaurus tables before using any of the thesaurus operators.

Example for PT Operator

The term *automobile* has a preferred term of *car* in a thesaurus. A PT query for *automobile* returns all documents that contain the word *car*. Documents that contain the word *automobile* are not returned.

Related Topics

CTX_THES.PT (page 14-25) in [CTX_THES Package](#) (page 14-1) form more information on browsing the preferred terms in your thesaurus

3.22 Related Term (RT)

Use the related term operator (RT) to expand a query to include all related terms that have been defined in a thesaurus for the term.

Syntax

Syntax	Description
<code>RT(<i>term</i>[,<i>thes</i>])</code>	Expands a query to include all the terms defined in the thesaurus as a related term for <i>term</i> .

term

Specify the operand for the related term operator. *term* is expanded to include *term* and all the related entries defined for *term* in *thes*.

You cannot specify expansion operators in the *term* argument.

thes

Specify the name of the thesaurus used to return the expansions for the specified *term*. The *thes* argument is optional and has a default value of `DEFAULT`. As a result, a thesaurus named `DEFAULT` *must* exist in the thesaurus tables before using any of the thesaurus operators.

Example for RT Operator

The term *dog* has a related term of *wolf*. An RT query for *dog* returns all documents that contain the word *dog* and *wolf*.

Related Topics

CTX_THES.[RT](#) (page 14-27) in [CTX_THES Package](#) (page 14-1) for more information on browsing the related terms in your thesaurus

3.23 SDATA

Use the SDATA operator to perform tests on SDATA sections and columns, which contain structured data values. SDATA sections speed up mixed querying and ordering. This operator provides structured predicate support for `CONTAINS`, which extends non-SQL interfaces such as `count_hits` or the result set interface.

SDATA operators should only be used as descendants of `AND` operators that also have non-SDATA children.

SDATA queries perform on string or numeric literals, and on date strings. The string literal and date string are enclosed within single or double quote characters. The numeric value is not enclosed in quote characters, and must conform to the SQL format of `NUMBER`. For example:

```
CONTAINS(text, "dog and SDATA(category = 'news')")>0 ...
```

```
SDATA(rating between 1.2 and 3.4) ...
```

```
SDATA(author LIKE 'FFORDE%') ...
```

```
SDATA(date >='2005-09-18') ...
```

Closed parentheses are permitted, as long as they are enclosed in single or double quotes.

The SDATA operator can be used in query templates.

Syntax

Syntax	Operators
SData	<code>:= "SDATA" "(" SDataPredicate ")"</code>
SDataPredicate	<code>:= section_name SDataTest</code>
SDataTest	<code>:= <SDataSingleOp SDataLiteral> SDataBetweenOp <"is" ("not")? "null"></code>
SDataSingleOp	<code>:= ("<" "<=" "=" ">=" ">" "!=" "<>" "like") SDataLiteral</code>
SDataBetweenOp	<code>:= "between" SDataLiteral "and" SDataLiteral</code>
SDataLiteral	<code>:= numeric_literal "" string_literal "" "" date_string ""</code>

section_name

The name of the SDATA section(s) on which to search and perform the test, or check.

SDataLiteral

The value of the SDATA section. This must be either a string literal, numeric literal, or a date string.

The SDATA operator returns a score of 100 if the enclosed predicate returns TRUE, and returns 0 otherwise. In the case of a NULL value, the SDATA operator returns a score of 0 (since in SQL it would not return TRUE).

Multi-valued semantics are not defined, as multi-valued SDATA sections are not supported.

Comparison of strings is case sensitive. The BINARY collation is always used.

Note:

For the SDATA operator on SDATA sections that are mapped to a DATE FILTER BY column, the SDATA value must follow the Date format: YYYY-MM-DD or YYYY-MM-DD HH24:MI:SS. Otherwise, the expected rows will not be returned. If the time component is omitted, it will default to 00:00:00, according to SQL semantics. This Date format is always used, regardless of the setting of the NLS_DATE_FORMAT environment variable.

Example for SDATA Operator

Suppose that you want to query for books in the fiction category that contain the word *summer*. Assuming that an SDATA section called CATEGORY has been declared, you can query as follows:

```
SELECT id FROM idx_docs
WHERE CONTAINS(text, 'summer AND SDATA(category = "fiction")')>0
```

Restrictions

- The sum of the numbers for INDEXED_COLUMN, FILTER BY columns, and ORDER BY columns cannot be greater than 99.

- An error is raised if the section name is not a defined `SDATA` section. The source of the section (for example, tag versus column) is not important.
- The syntax precludes `RHS SDATA` and expressions.
- `SDATA` operators cannot be children of `WITHIN`, `INPATH`, `HASPATH`, or `NEAR`.
- The datatype of the named `SDATA` section must be compatible with the literal provided (and the operator, for example, `LIKE`) or an error is raised.
- `SDATA` operators are not supported in `CTXRULE` query documents.
- `SDATA` operators have no effect on highlighting.

Notes

Oracle recommends using `SDATA` operators only as descendants of `AND` operators that also have non-`SDATA` children. Essentially, use `SDATA` operators as secondary (that is, checking or non-driving) criteria. For instance, "find documents with `DOG` that also have `price > 5`", rather than "find documents with `rating > 4`". Other usage may operate properly, but may not have optimal performance.

The following examples are consistent with recommended use:

```
dog & SDATA(foo = 5)
```

The `SDATA` is a child of an `AND` operator that also has non-`SDATA` children.

```
dog & (SDATA(foo = 5) | SDATA(x = 1))
```

Although the `SDATA` operators here are children of `OR`, they are still descendants of an `AND` operator with non-`SDATA` children.

The following examples show use that is not recommended:

```
SDATA(foo = 5)
```

Here, `SDATA` is the only criteria and, therefore, the driving criteria.

```
dog | SDATA(bar = 9)
```

The `SDATA` in this example is a child of an `OR` operator rather than an `AND`.

```
SDATA(foo = 5) & SDATA(bar = 7)
```

While both `SDATA` operators in this example are descendants of `AND`, this `AND` operator does not have non-`SDATA` children.

Related Topics

["ADD_SDATA_COLUMN \(page 8-14\)"](#)

["ADD_SDATA_SECTION \(page 8-16\)"](#)

["UPDATE_SDATA \(page 8-73\)"](#)

["CTX_SECTIONS \(page G-12\)"](#) in [Oracle Text Views \(page G-1\)](#)

See Also:

- *Oracle Database SQL Language Reference*
- Chapter 8, "Searching Document Sections in Oracle Text" in *Oracle Text Application Developer's Guide*

3.24 soundex (!)

Use the soundex (!) operator to expand queries to include words that have similar sounds; that is, words that sound like other words. This function enables comparison of words that are spelled differently, but sound alike in English.

Syntax

Syntax	Description
<i>!term</i>	Expands a query to include all terms that sound the same as the specified term (English-language text only).

Example for Soundex (!) Operator

```
SELECT ID, COMMENT FROM EMP_RESUME
WHERE CONTAINS (COMMENT, '!SMYTHE') > 0 ;

ID COMMENT
--
23 Smith is a hard worker who..
```

Language

Soundex works best for languages that use a 7-bit character set, such as English. It can be used, with lesser effectiveness, for languages that use an 8-bit character set, such as many Western European languages.

If you have base-letter conversion specified for a text column and the query expression contains a soundex operator, then Oracle Text operates on the base-letter form of the query.

3.25 stem (\$)

Use the stem (\$) operator to search for terms that have the same linguistic root as the query term.

If you use the `BASIC_LEXER` to index your language, stemming performance can be improved by using the `index_stems` attribute.

The Oracle Text stemmer, licensed from XSoft Division of Xerox Corporation, supports the following languages with the [BASIC_LEXER](#) (page 2-41): English, French, Spanish, Italian, German, and Dutch.

Japanese stemming is supported with the [JAPANESE_LEXER](#) (page 2-54).

Specify your stemming language with the [BASIC_WORDLIST](#) (page 2-72) wordlist preference.

Syntax

Syntax	Description
<i>\$term</i>	Expands a query to include all terms having the same stem or root word as the specified term.

Examples for Stem (\$) Operator

Input	Expands To
\$scream	scream screaming screamed
\$distinguish	distinguish distinguished distinguishes
\$guitars	guitars guitar
\$commit	commit committed
\$cat	cat cats
\$sing	sang sung sing

Behavior with Stopwords

If stem returns a word designated as a stopwords, the stopwords is not included in the query or highlighted by `CTX_QUERY.HIGHLIGHT` or `CTX_QUERY.MARKUP`.

Related Topics

For more information about enabling the stem operator with `BASIC_LEXER`, see "[BASIC_LEXER](#) (page 2-41)" in [Oracle Text Indexing Elements](#) (page 2-1)

3.26 Stored Query Expression (SQE)

Use the SQE operator to call a stored query expression created with the `CTX_QUERY.STORE_SQE` (page 12-18) procedure.

Stored query expressions can be used for creating predefined bins for organizing and categorizing documents or to perform iterative queries, in which an initial query is refined using one or more additional queries.

Syntax

Syntax	Description
<code>SQE(SQE_name)</code>	Returns the results for the stored query expression <i>SQE_name</i> .

Examples for SQE Operator

To create an SQE named *disasters*, use `CTX_QUERY.STORE_SQE` (page 12-18) as follows:

```
begin
ctx_query.store_sqe('disasters', 'hurricane or earthquake or blizzard');
end;
```

This stored query expression returns all documents that contain either *hurricane*, *earthquake* or *blizzard*.

This SQE can then be called within a query expression as follows:

```
SELECT SCORE(1), docid FROM news
WHERE CONTAINS(resume, 'sqe(disasters)', 1)> 0
ORDER BY SCORE(1);
```

Limitations

Up to 100 stored query expressions (SQEs) can be stored in a single Text query. If a Text query has more than 100 SQEs, including nested SQEs, then the query fails and error DRG-50949 is raised.

Related Topic

["STORE_SQE \(page 12-18\)"](#)

3.27 SYNonym (SYN)

Use the synonym operator (SYN) to expand a query to include all the terms that have been defined in a thesaurus as synonyms for the specified term.

Syntax

Syntax	Description
<code>SYN(<i>term</i>[,<i>thes</i>])</code>	Expands a query to include all the terms defined in the thesaurus as synonyms for <i>term</i> .

term

Specify the operand for the synonym operator. *term* is expanded to include *term* and all the synonyms defined for *term* in *thes*.

You cannot specify expansion operators in the *term* argument.

thes

Specify the name of the thesaurus used to return the expansions for the specified term. The *thes* argument is optional and has a default value of `DEFAULT`. A thesaurus named `DEFAULT` must exist in the thesaurus tables if you use this default value.

Examples for SYN Operator

The following query expression returns all documents that contain the term *dog* or any of the synonyms defined for *dog* in the `DEFAULT` thesaurus:

```
'SYN(dog) '
```

Compound Phrases in Synonym Operator

Expansion of compound phrases for a term in a synonym query are returned as AND conjunctives.

For example, the compound phrase *temperature + measurement + instruments* is defined in a thesaurus as a synonym for the term *thermometer*. In a synonym query for *thermometer*, the query is expanded to:

```
{thermometer} OR ({temperature}&{measurement}&{instruments})
```

Related Topics

CTX_THES.SYN (page 14-28) in [CTX_THES Package](#) (page 14-1) for more information on browsing the synonym terms in your thesaurus

3.28 threshold (>)

Use the threshold operator (>) in two ways:

- at the expression level
- at the query term level

The threshold operator at the expression level eliminates documents in the result set that score below a threshold number.

The threshold operator at the query term level selects a document based on how a term scores in the document.

Syntax

Syntax	Description
<i>expression</i> > <i>n</i>	Returns only those documents in the result set that score above the threshold <i>n</i> .
<i>term</i> > <i>n</i>	Within an expression, returns documents that contain the query term with score of at least <i>n</i> .

Examples for Threshold (>) Operator

At the expression level, to search for documents that contain *relational databases* and to return only documents that score greater than 75, use the following expression:

```
'relational databases > 75'
```

At the query term level, to select documents that have at least a score of 30 for *lion* and contain *tiger*, use the following expression:

```
'(lion > 30) and tiger'
```

3.29 Translation Term (TR)

Use the translation term operator (TR) to expand a query to include all defined foreign language equivalent terms.

Syntax

Syntax	Description
<code>TR(<i>term</i> [, <i>lang</i>, [<i>thes</i>]])</code>	Expands <i>term</i> to include all the foreign equivalents that are defined for <i>term</i> .

term

Specify the operand for the translation term operator. *term* is expanded to include all the foreign language entries defined for *term* in *thes*. You cannot specify expansion operators in the *term* argument.

lang

Optionally, specify which foreign language equivalents to return in the expansion. The language you specify must match the language as defined in *thes*. (You may specify only one language at a time.) If you omit this parameter or specify it as `ALL`, the system expands to use all defined foreign language terms.

thes

Optionally, specify the name of the thesaurus used to return the expansions for the specified term. The *thes* argument has a default value of `DEFAULT`. As a result, a thesaurus named `DEFAULT` *must* exist in the thesaurus tables before you can use any of the thesaurus operators.

Note:

If you specify *thes*, then you must also specify *lang*.

Examples for TR Operator

Consider a thesaurus `MY_THES` with the following entries for *cat*:

```
cat
  SPANISH: gato
  FRENCH:  chat
```

To search for all documents that contain *cat* and the spanish translation of *cat*, enter the following query:

```
'tr(cat, spanish, my_thes)'
```

This query expands to:

```
'{cat}||{gato}'
```

Related Topics

`CTX_THES.TR` (page 14-31) in [CTX_THES Package](#) (page 14-1) for more information on browsing the related terms in your thesaurus

3.30 Translation Term Synonym (TRSYN)

Use the translation term synonym operator (`TRSYN`) to expand a query to include all the defined foreign equivalents of the query term, the synonyms of query term, and the foreign equivalents of the synonyms.

Syntax

Syntax	Description
TRSYN(<i>term</i> [, <i>lang</i> , [<i>thes</i>]])	Expands <i>term</i> to include foreign equivalents of <i>term</i> , the synonyms of <i>term</i> , and the foreign equivalents of the synonyms.

term

Specify the operand for this operator. *term* is expanded to include all the foreign language entries and synonyms defined for *term* in *thes*. You cannot specify expansion operators in the *term* argument.

lang

Optionally, specify which foreign language equivalents to return in the expansion. The language you specify must match the language as defined in *thes*. If you omit this parameter, the system expands to use all defined foreign language terms.

thes

Optionally, specify the name of the thesaurus used to return the expansions for the specified term. The *thes* argument has a default value of `DEFAULT`. As a result, a thesaurus named `DEFAULT` *must* exist in the thesaurus tables before you can use any of the thesaurus operators.

Note:

If you specify *thes*, then you must also specify *lang*.

Examples for TRSYN Operator

Consider a thesaurus `MY_THES` with the following entries for *cat*:

```
cat
  SPANISH: gato
  FRENCH:  chat
  SYN lion
  SPANISH: leon
```

To search for all documents that contain *cat*, the spanish equivalent of *cat*, the synonym of *cat*, and the spanish equivalent of *lion*, enter the following query:

```
'trsyn(cat, spanish, my_thes)'
```

This query expands to:

```
'{cat}|{gato}|{lion}|{leon}'
```

Related Topics

CTX_THES.[TRSYN](#) (page 14-32) in [CTX_THES Package](#) (page 14-1) for more information on browsing the translation and synonym terms in your thesaurus

3.31 Top Term (TT)

Use the top term operator (TT) to replace a term in a query with the *top term* that has been defined for the term in the standard hierarchy (Broader Term [BT], Narrower

Term [NT]) in a thesaurus. A top term is the broadest conceptual term related to a given query term. For example, a thesaurus might define the following hierarchy:

```
DOG
  BT1 CANINE
    BT2 MAMMAL
      BT3 VERTEBRATE
        BT4 ANIMAL
```

The top term for *dog* in this thesaurus is *animal*.

Top terms in the generic (BTG, NTG), partitive (BTP, NTP), and instance (BTI, NTI) hierarchies are not returned.

Syntax

Syntax	Description
TT(<i>term</i> [, <i>thes</i>])	Replaces the specified word in a query with the top term in the standard hierarchy (BT, NT) for <i>term</i> .

term

Specify the operand for the top term operator. *term* is replaced by the top term defined for the term in the specified thesaurus. However, if no TT entries are defined for *term*, *term* is not replaced in the query expression and *term* is the result of the expansion.

You cannot specify expansion operators in the *term* argument.

thes

Specify the name of the thesaurus used to return the expansions for the specified term. The *thes* argument is optional and has a default value of `DEFAULT`. A thesaurus named `DEFAULT` must exist in the thesaurus tables if you use this default value.

Example for TT Operator

The term *dog* has a top term of *animal* in the standard hierarchy of a thesaurus. A TT query for *dog* returns all documents that contain the phrase *animal*. Documents that contain the word *dog* are not returned.

Related Topics

CTX_THES.[TT](#) (page 14-34) for more information on browsing the top terms in your thesaurus

3.32 weight (*)

The weight operator multiplies the score by the given factor, topping out at 100 when the score exceeds 100. For example, the query *cat, dog*2* sums the score of *cat* with twice the score of *dog*, topping out at 100 when the score is greater than 100.

In expressions that contain more than one query term, use the weight operator to adjust the relative scoring of the query terms. Reduce the score of a query term by using the weight operator with a number less than 1; increase the score of a query term by using the weight operator with a number greater than 1 and less than 10.

The weight operator is useful in [ACCUMulate \(_ \)](#) (page 3-7), [AND \(&\)](#) (page 3-8), or [OR \(|\)](#) (page 3-40) queries when the expression has more than one query term. With no weighting on individual terms, the score cannot tell which of the query terms occurs the most. With term weighting, you can alter the scores of individual terms and hence make the overall document ranking reflect the terms you are interested in.

Syntax

Syntax	Description
<i>term*n</i>	Returns documents that contain <i>term</i> . Calculates score by multiplying the raw score of <i>term</i> by <i>n</i> , where <i>n</i> is a number from 0.1 to 10.

Examples for Weight (*) Operator

Suppose you have a collection of sports articles. You are interested in the articles about Brazilian soccer. It turns out that a regular query on *soccer or Brazil* returns many high ranking articles on US soccer. To raise the ranking of the articles on Brazilian soccer, enter the following query:

```
'soccer or Brazil*3'
```

[Table 3-3](#) (page 3-52) illustrates how the weight operator can change the ranking of three hypothetical documents A, B, and C, which all contain information about soccer. The columns in the table show the total score of four different query expressions on the three documents.

Table 3-3 Score Samples

Document	soccer	Brazil	soccer or Brazil	soccer or Brazil*3
A	20	10	20	30
B	10	30	30	90
C	50	20	50	60

The score in the third column containing the query *soccer or Brazil* is the score of the highest scoring term. The score in the fourth column containing the query *soccer or Brazil*3* is the larger of the score of the first column *soccer* and of the score *Brazil* multiplied by three, *Brazil*3*.

With the initial query of *soccer or Brazil*, the documents are ranked in the order C B A. With the query of *soccer or Brazil*3*, the documents are ranked B C A, which is the preferred ranking.

Weights can be added to multiple terms. The query *Brazil OR (soccer AND Brazil)*3* will increase the relative scores for documents that contain both *soccer* and *Brazil*.

3.33 wildcards (% _)

Wildcard characters can be used in query expressions to expand word searches into pattern searches. When a wildcard is used on its own, for example, "DOG %" or "%.%" or "%" by itself, it is treated as a stopword.

The wildcard characters are as follows:

Wildcard Character	Description
%	The percent wildcard can appear any number of times at any part of the search term. The search term will be expanded into an equivalence list of terms. The list consists of all terms in the index that match the wildcarded term, with zero or more characters in place of the percent character.
_	The underscore wildcard specifies a single position in which any character can occur.

The total number of wildcard expansions from all words in a query containing unescaped wildcard characters cannot exceed the maximum number of expansions specified by the BASIC_WORDLIST attribute WILDCARD_MAXTERMS. For more information, see "[BASIC_WORDLIST](#) (page 2-72)".

Note:

- When a wildcard is used on its own, it is treated as a stopword.
 - When a wildcard expression translates to a stopword, the stopword is not included in the query and not highlighted by CTX_DOC.HIGHLIGHT (page 9-9) or CTX_DOC.MARKUP (page 9-13).
-
-

Right-Truncated Queries

Right truncation involves placing the wildcard on the right-hand-side of the search string.

For example, the following query expression finds all terms beginning with the pattern *scal*:

```
'scal%'
```

Left- and Double-Truncated Queries

Left truncation involves placing the wildcard on the left-hand-side of the search string.

To find words such as *king*, *wing* or *sing*, write the query as follows:

```
'_ing'
```

For all words that end with *ing*, enter:

```
'%ing'
```

Combine left-truncated and right-truncated searches to create double-truncated searches. The following query finds all documents that contain words that contain the substring *%benz%*

```
'%benz%'
```

Improving Wildcard Query Performance

Improve wildcard query performance by adding a substring or prefix index.

When your wildcard queries are left- and double-truncated, you can improve query performance by creating a substring index. Substring indexes improve query performance for all types of left-truncated wildcard searches such as *%ed*, *_ing*, or *%benz%*.

When your wildcard queries are right-truncated, you can improve performance by creating a prefix index. A prefix index improves query performance for wildcard searches such as *to%*.

See Also:

"[BASIC_WORDLIST](#) (page 2-72)" in [Oracle Text Indexing Elements](#) (page 2-1) for more information about creating substring and prefix indexes

3.34 WITHIN

Use the **WITHIN** operator to narrow a query down into document sections. Document sections can be one of the following:

- Zone sections
- Field sections
- Attribute sections
- Special sections (sentence or paragraph)

Syntax

Syntax	Description
<i>expression</i> WITHIN <i>section</i>	Searches for <i>expression</i> within the predefined zone, field, or attribute section. If <i>section</i> is a zone, <i>expression</i> can contain one or more WITHIN operators (nested WITHIN) whose section is a zone or special section. If <i>section</i> is a field or attribute section, <i>expression</i> cannot contain another WITHIN operator.
<i>expression</i> WITHIN SENTENCE	Searches for documents that contain <i>expression</i> within a sentence. Specify an AND or NOT query for <i>expression</i> . The <i>expression</i> can contain one or more WITHIN operators (nested WITHIN) whose section is a zone or special section.
<i>expression</i> WITHIN PARAGRAPH	Searches for documents that contain <i>expression</i> within a paragraph. Specify an AND or NOT query for <i>expression</i> . The <i>expression</i> can contain one or more WITHIN operators (nested WITHIN) whose section is a zone or special section.

WITHIN Limitations

The WITHIN operator has the following limitations:

- You cannot embed the WITHIN clause in a phrase. For example, you cannot write:
term1 WITHIN section term2
- Because WITHIN is a reserved word, you must escape the word with braces to search on it.

WITHIN Operator Examples

Querying Within Zone Sections

To find all the documents that contain the term *San Francisco* within the section *Headings*, write the query as follows:

```
'San Francisco WITHIN Headings'
```

To find all the documents that contain the term *sailing* and contain the term *San Francisco* within the section *Headings*, write the query in one of two ways:

```
'(San Francisco WITHIN Headings) and sailing'
```

```
'sailing and San Francisco WITHIN Headings'
```

Compound Expressions with WITHIN

To find all documents that contain the terms *dog* and *cat* within the same section *Headings*, write the query as follows:

```
'(dog and cat) WITHIN Headings'
```

This query is logically different from:

```
'dog WITHIN Headings and cat WITHIN Headings'
```

This query finds all documents that contain *dog* and *cat* where the terms *dog* and *cat* are in *Headings* sections, regardless of whether they occur in the same *Headings* section or different sections.

Near with WITHIN

To find all documents in which *dog* is near *cat* within the section *Headings*, write the query as follows:

```
'dog near cat WITHIN Headings'
```

Note:

The near operator has higher precedence than the WITHIN operator so braces are not necessary in this example. This query is equivalent to *(dog near cat) WITHIN Headings*.

Nested WITHIN Queries

You can nest the within operator to search zone sections within zone sections.

For example, assume that a document set had the zone section `AUTHOR` nested within the zone `BOOK` section. Write a nested `WITHIN` query to find all occurrences of *scott* within the `AUTHOR` section of the `BOOK` section as follows:

```
'(scott WITHIN AUTHOR) WITHIN BOOK'
```

Querying Within Field Sections

The syntax for querying within a field section is the same as querying within a zone section. The syntax for most of the examples given in the previous section, "[Querying Within Zone Sections](#) (page 3-55)", apply to field sections.

However, field sections behave differently from zone sections in terms of

- **Visibility:** Make text within a field section invisible.
- **Repeatability:** `WITHIN` queries cannot distinguish repeated field sections.
- **Nestability:** You cannot enter a nested `WITHIN` query with a field section.

The following sections describe these differences.

Visible Flag in Field Sections

When a field section is created with the visible flag set to `FALSE` in `CTX_DDL.ADD_FIELD_SECTION`, the text within a field section can only be queried using the `WITHIN` operator.

For example, assume that `TITLE` is a field section defined with visible flag set to `FALSE`. Then the query *dog* without the `WITHIN` operator will *not* find a document containing:

```
<TITLE>The dog</TITLE> I like my pet.
```

To find such a document, use the `WITHIN` operator as follows:

```
'dog WITHIN TITLE'
```

Alternatively, set the visible flag to `TRUE` when you define `TITLE` as a field section with `CTX_DDL.ADD_FIELD_SECTION`.

See Also:

"[ADD_FIELD_SECTION](#) (page 8-5)" in [CTX_DDL Package](#) (page 8-1) for more information about creating field sections

Repeated Field Sections

`WITHIN` queries *cannot* distinguish repeated field sections in a document. For example, consider the document with the repeated section `<author>`:

```
<author> Charles Dickens </author>
<author> Martin Luther King </author>
```

Assuming that `<author>` is defined as a field section, a query such as (*charles and martin*) *within author* returns the document, even though these words occur in separate tags.

To have `WITHIN` queries distinguish repeated sections, define the sections as zone sections.

Nested Field Sections

You cannot enter a nested `WITHIN` query with field sections. Doing so raises an error.

Querying Within Sentence or Paragraphs

Querying within sentence or paragraph boundaries is useful to find combinations of words that occur in the same sentence or paragraph. To query sentence or paragraphs, you must first add the special section to your section group before you index. Do so with `CTX_DDL.ADD_SPECIAL_SECTION`.

To find documents that contain *dog* and *cat* within the same sentence:

```
'(dog and cat) WITHIN SENTENCE'
```

To find documents that contain *dog* and *cat* within the same paragraph:

```
'(dog and cat) WITHIN PARAGRAPH'
```

To find documents that contain sentences with the word *dog* but not *cat*:

```
'(dog not cat) WITHIN SENTENCE'
```

Querying Within Attribute Sections

Query within attribute sections when you index with either `XML_SECTION_GROUP` or `AUTO_SECTION_GROUP` as your section group type.

Assume you have an XML document as follows:

```
<book title="Tale of Two Cities">It was the best of times.</book>
```

Define the section `title@book` to be the attribute section `title`. Do so with the `CTX_DDL.ADD_ATTR_SECTION` procedure or dynamically after indexing with `ALTER INDEX`.

Note:

When you use the `AUTO_SECTION_GROUP` to index XML documents, the system automatically creates attribute sections and names them in the form `attribute@tag`.

If you use the `XML_SECTION_GROUP`, you can name attribute sections anything with `CTX_DDL.ADD_ATTR_SECTION`.

To search on *Tale* within the attribute section `title`, enter the following query:

```
'Tale WITHIN title'
```

Constraints for Querying Attribute Sections

The following constraints apply to querying within attribute sections:

- Regular queries on attribute text do not hit the document unless qualified in a within clause. Assume you have an XML document as follows:

```
<book title="Tale of Two Cities">It was the best of times.</book>
```

A query on *Tale* by itself does not produce a hit on the document unless qualified with `WITHIN title@book`. (This behavior is like field sections when you set the visible flag set to false.)

- You cannot use attribute sections in a nested `WITHIN` query.
- Phrases ignore attribute text. For example, if the original document looked like:

Now is the time for all good <word type="noun"> men </word> to come to the aid.

Then this document would hit on the regular query *good men*, ignoring the intervening attribute text.

- `WITHIN` queries can distinguish repeated attribute sections. This behavior is like zone sections but unlike field sections. For example, you have a document as follows:

```
<book title="Tale of Two Cities">It was the best of times.</book>
<book title="Of Human Bondage">The sky broke dull and gray.</book>
```

Assume that `book` is a zone section and `book@author` is an attribute section. Consider the query:

```
'(Tale and Bondage) WITHIN book@author'
```

This query does *not* hit the document, because *tale* and *bondage* are in different occurrences of the attribute section `book@author`.

Notes

Section Names

The `WITHIN` operator requires you to know the name of the section you search. A list of defined sections can be obtained using the [CTX_SECTIONS](#) (page G-12) or [CTX_USER_SECTIONS](#) (page G-23) views.

Section Boundaries

For special and zone sections, the terms of the query must be fully enclosed in a particular occurrence of the section for the document to satisfy the query. This is not a requirement for field sections.

For example, consider the query where *bold* is a zone section:

```
'(dog and cat) WITHIN bold'
```

This query finds:

```
<B>dog cat</B>
```

but it does not find:

```
<B>dog</B><B>cat</B>
```

This is because *dog* and *cat* must be in the same *bold* section.

This behavior is especially useful for special sections, where

```
'(dog and cat) WITHIN sentence'
```

means find *dog* and *cat* within the same sentence.

Field sections on the other hand are meant for non-repeating, embedded metadata such as a title section. Queries within field sections cannot distinguish between occurrences. All occurrences of a field section are considered to be parts of a single section. For example, the query:

```
(dog and cat) WITHIN title
```

can find a document like this:

```
<TITLE>dog</TITLE><TITLE>cat</TITLE>
```

In return for this field section limitation and for the overlap and nesting limitations, field section queries are generally faster than zone section queries, especially if the section occurs in every document, or if the search term is common.

Special Characters in Oracle Text Queries

This chapter describes the special characters that can be used in Text queries. In addition, it provides a list of the words and characters that Oracle Text treats as reserved words and characters.

The following topics are covered in this chapter:

- [Grouping Characters](#) (page 4-1)
- [Escape Characters](#) (page 4-1)
- [Reserved Words and Characters](#) (page 4-2)

4.1 Grouping Characters

The grouping characters control operator precedence by grouping query terms and operators in a query expression. The grouping characters are described in [Table 4-1](#) (page 4-1).

Table 4-1 Characters for Grouping Query Terms

Grouping Character	Description
()	The parentheses characters serve to group terms and operators found between the characters
[]	The bracket characters serve to group terms and operators found between the characters; however, they prevent penetrations for the expansion operators (fuzzy, soundex, stem).

The beginning of a group of terms and operators is indicated by an open character from one of the sets of grouping characters. The ending of a group is indicated by the occurrence of the appropriate close character for the open character that started the group. Between the two characters, other groups may occur.

For example, the open parenthesis indicates the beginning of a group. The first close parenthesis encountered is the end of the group. Any open parentheses encountered before the close parenthesis indicate nested groups.

4.2 Escape Characters

To query on words or symbols that have special meaning in query expressions such as *and* & *or* | *accum*, you must escape them. There are two ways to escape characters in a query expression, as described in [Table 4-2](#) (page 4-2).

Table 4-2 Characters for Escaping Query Terms

Escape Character	Description
{ }	Use braces to escape a string of characters or symbols. Everything within a set of braces is considered part of the escape sequence. When you use braces to escape a single character, the escaped character becomes a separate token in the query.
\	Use the backslash character to escape a single character or symbol. Only the character immediately following the backslash is escaped. For example, a query of <i>blue\ -green</i> matches <i>blue-green</i> and <i>blue green</i> .

In the following examples, an escape sequence is necessary because each expression contains a Text operator or reserved symbol:

```
'high\ -voltage'
'{high-voltage}'
```

```
'XY\&Z'
'{XY&Z}'
```

In the first example, the query matches *high-voltage* or *high voltage*.

Note that in the second example, a query on *XY&Z* will return 'XY Z', 'XY-Z', 'XY*Z', and so forth, as well as 'XY&Z'. This is because non-alphabetic characters are treated as whitespace (so *XY&Z* is treated as 'XY Z'). To match only *XY&Z*, you must declare & as a printjoin. (If you do, however, *XY&Z* will not match 'XY & Z'.) For more on printjoins, see [BASIC_LEXER](#) (page 2-41).

Note:

If you use braces to escape an individual character within a word, the character is escaped, but the word is broken into three tokens. For example, a query written as *high{-voltage* searches for *high - voltage*, with the space on either side of the hyphen.

Querying Escape Characters

The open brace { signals the beginning of the escape sequence, and the closed brace } indicates the end of the sequence. Everything between the opening brace and the closing brace is part of the escaped query expression (including any open brace characters). To include the close brace character in an escaped query expression, use } }. To escape the backslash escape character, use \ \.

4.3 Reserved Words and Characters

[Table 4-3](#) (page 4-3) lists the Oracle Text reserved words and characters that must be escaped when you want to search them in CONTAINS queries. Refer to [Table 4-2](#) (page 4-2) for the rule for when to use braces {} or the backslash \ for the escape sequence.

Table 4-3 *Reserved Words and Characters*

Reserved Words	Reserved Characters	Operator
ABOUT	(none)	ABOUT
ACCUM	,	Accumulate
AND	&	And
BT	(none)	Broader Term
BTG	(none)	Broader Term Generic
BTI	(none)	Broader Term Instance
BTP	(none)	Broader Term Partitive
EQUIV	=	Equivalence
FUZZY	?	fuzzy
(none)	{ }	escape characters (multiple)
(none)	\	escape character (single)
(none)	()	grouping characters
(none)	[]	grouping characters
HASPATH	(none)	HASPATH
INPATH	(none)	INPATH
MDATA	(none)	MDATA
MINUS	-	MINUS
NEAR	;	NEAR
NOT	~	NOT
NT	(none)	Narrower Term
NTG	(none)	Narrower Term Generic
NTI	(none)	Narrower Term Instance
NTP	(none)	Narrower Term Partitive
OR		OR
PT	(none)	Preferred Term
RT	(none)	Related Term
(none)	\$	stem
(none)	!	soundex
SQE	(none)	Stored Query Expression

Table 4-3 (Cont.) Reserved Words and Characters

Reserved Words	Reserved Characters	Operator
SYN	(none)	Synonym
(none)	>	threshold
TR	(none)	Translation Term
TRSYN	(none)	Translation Term Synonym
TT	(none)	Top Term
(none)	*	weight
(none)	%	wildcard character (multiple)
(none)	–	wildcard character (single)
WITHIN	(none)	WITHIN

CTX_ADM Package

This chapter contains the following topics.

- [About CTX_ADM Package Procedures](#) (page 5-1)
- [MARK_FAILED](#) (page 5-1)
- [RECOVER](#) (page 5-2)
- [RESET_AUTO_OPTIMIZE_STATUS](#) (page 5-2)
- [SET_PARAMETER](#) (page 5-3)

5.1 About CTX_ADM Package Procedures

The CTX_ADM PL/SQL package provides administrative procedures for managing index preferences.

The CTX_ADM package contains the following stored procedures.

Name	Description
MARK_FAILED (page 5-1)	Changes an index's status from <code>LOADING</code> to <code>FAILED</code> .
RECOVER (page 5-2)	Cleans up database objects for deleted Text tables.
RESET_AUTO_OPTIMIZE_STATUS (page 5-2)	Resets the CTX_AUTO_OPTIMIZE_STATUS (page G-3) view.
SET_PARAMETER (page 5-3)	Sets system-level defaults for index creation.

Note:

Only the CTXSYS user can use the procedures in the CTX_ADM package.

5.2 MARK_FAILED

Use the `MARK_FAILED` procedure to change the status of an index from `LOADING` to `FAILED`.

Under rare circumstances, if `CREATE INDEX` or `ALTER INDEX` fails, an index may be left with the status `LOADING`. When an index is in `LOADING` status, any attempt to recover using `RESUME INDEX` is blocked. For this situation, use `CTX_ADM.MARK_FAILED` to forcibly change the status from `LOADING` to `FAILED` so that you can recover the index with `RESUME INDEX`.

You must log on as CTXSYS to run `CTX_ADM.MARK_FAILED`.

WARNING:

Use `CTX_ADM.MARK_FAILED` with caution. It should only be used as a last resort and only when no other session is touching the index. Normally, `CTX_ADM.MARK_FAILED` does not succeed if another session is actively building the index with `CREATE` or `ALTER INDEX`. However, index creation or alteration may include windows of time during which `CTX_ADM.MARK_FAILED` can succeed, marking the index as failed even as it is being built by another session.

`CTX_ADM.MARK_FAILED` works with local partitioned indexes. However, it changes the status of all partitions to `FAILED`. Therefore, you should rebuild all index partitions with `ALTER INDEX REBUILD PARTITION PARAMETERS ('RESUME')` after using `CTX_ADM.MARK_FAILED`. If you run `ALTER INDEX PARAMETER ('RESUME')` after this operation, then Oracle resets the index partition status to valid. Oracle does not rebuild the index partitions that were successfully built before the `MARK_FAILED` operation.

Syntax

```
CTX_ADM.MARK_FAILED(  
    owner_name      in   VARCHAR2,  
    index_name      in   VARCHAR2);
```

owner_name

The name of the owner of the index whose status is to be changed.

index_name

The name of the index whose status is to be changed.

Example

```
begin  
    CTX_ADM.MARK_FAILED('owner_1', 'index_1');  
end;
```

5.3 RECOVER

The `RECOVER` procedure cleans up the Text data dictionary, deleting objects such as leftover preferences.

Syntax

```
CTX_ADM.RECOVER;
```

Example

```
begin  
    ctx_adm.recover;  
end;
```

5.4 RESET_AUTO_OPTIMIZE_STATUS

Use the `RESET_AUTO_OPTIMIZE_STATUS` procedure to reset (or delete the contents of) the [CTX_AUTO_OPTIMIZE_STATUS](#) (page G-3) view.

You must log on as CTXSYS to run CTX_ADM.RESET_AUTO_OPTIMIZE_STATUS.

Syntax

```
CTX_ADM.RESET_AUTO_OPTIMIZE_STATUS;
```

Example

```
begin
    ctx_adm.reset_auto_optimize_status;
end;
```

5.5 SET_PARAMETER

The SET_PARAMETER procedure sets system-level parameters for index creation and for near real-time indexes.

Syntax

```
CTX_ADM.SET_PARAMETER(param_name IN VARCHAR2,
                      param_value IN VARCHAR2);
```

param_name

Specify the name of the parameter to set, which can be one of the following parameters:

- max_index_memory (maximum memory allowed for indexing)
- default_index_memory (default memory allocated for indexing)
- log_directory (directory for CTX_OUPUT files)
- ctx_doc_key_type (default input key type for CTX_DOC procedures)
- file_access_role (default database role name for index creation when using FILE or URL datastores)
- auto_optimize (ENABLE or DISABLE for auto optimization)
- auto_optimize_logfile (the base file name for the auto optimization log file)

Note:

The auto optimization log file is created in the log directory and the timestamp of the auto optimization job start time is appended to the base file name. The new log file name will take effect when the next auto optimization job is run.

- default_datastore (default datastore preference)
- default_filter_file (default filter preference for data stored in files)
- default_filter_text (default text filter preference)
- default_filter_binary (default binary filter preference)
- default_section_html (default html section group preference)

- `default_section_xml` (default xml section group preference)
- `default_section_text` (default text section group preference)
- `default_lexer` (default lexer preference)
- `default_wordlist` (default wordlist preference)
- `default_stoplist` (default stoplist preference)
- `default_storage` (default storage preference)
- `default_ctxcat_lexer` (default lexer preference for CTXCAT index)
- `default_ctxcat_stoplist` (default stoplist preference for CTXCAT index)
- `default_ctxcat_storage` (default CTXCAT index storage)
- `default_ctxcat_wordlist` (default wordlist preference for CTXCAT index)
- `default_ctxrule_lexer` (default lexer for CTXRULE index)
- `default_ctxrule_stoplist` (default stoplist for CTXRULE index)
- `default_ctxrule_storage` (default storage for CTXRULE index)
- `default_ctxrule_wordlist` (default wordlist for CTXRULE index)

See Also:

To learn more about the default values for these parameters, see "[System Parameters](#) (page 2-98)" in [Oracle Text Indexing Elements](#) (page 2-1)

param_value

Specify the value to assign to the parameter. For `max_index_memory` and `default_index_memory`, the value you specify must have the following syntax:

`number[K|M|G]`

where K stands for kilobytes, M stands for megabytes, and G stands for gigabytes.

For each of the other parameters, specify the *name* of a preference to use as the default for indexing.

For `auto_optimize`, the value you specify must be either `ENABLE` or `DISABLE`.

When you set this parameter to `ENABLE`, auto optimization jobs can be started. When you set this parameter to `DISABLE`, no auto optimization jobs can be started and all the currently-running optimization jobs are terminated.

Example

```
begin
  ctx_adm.set_parameter('default_lexer', 'my_lexer');
end;
```

CTX_ANL Package

This chapter contains the following topics.

- [About CTX_ANL Package Procedures](#) (page 6-1)
- [ADD_DICTIONARY](#) (page 6-1)
- [DROP_DICTIONARY](#) (page 6-4)

6.1 About CTX_ANL Package Procedures

The CTX_ANL PL/SQL package is used with [AUTO_LEXER](#) (page 2-33) and provides procedures for adding and dropping a custom dictionary from the lexer. A custom dictionary might be one that you develop for a special field of study or for your industry. In most cases, the dictionaries supplied with Oracle Text are more than sufficient to handle your requirements.

See Also:

"[AUTO_LEXER](#) (page 2-33)" for a discussion of AUTO_LEXER and supported languages

The CTX_ANL package contains the following stored procedures.

Name	Description
ADD_DICTIONARY (page 6-1)	Adds a custom dictionary to the lexer.
DROP_DICTIONARY (page 6-4)	Drops a custom dictionary from the lexer.

Note:

Only the CTXSYS user can use the procedures in CTX_ANL.

6.2 ADD_DICTIONARY

Use the CTX_ANL.ADD_DICTIONARY procedure to add a custom dictionary to be used by "[AUTO_LEXER](#) (page 2-33)".

Note:

The dictionary data is not processed until index/policy creation time or ALTER INDEX time. Errors in dictionary data format are detected at index/policy creation time or ALTER INDEX time and result in error: DRG-13710: Syntax Error in Dictionary.

Syntax

```
CTX_ANL.ADD_DICTIONARY(  
    name          in VARCHAR2,  
    language      in VARCHAR2,  
    dictionary    in CLOB  
);
```

name

The unique name for the user-created custom dictionary.

language

The language used by the custom dictionary.

dictionary

The CLOB containing the custom dictionary. The custom dictionary comprises a list of definitions, which are declared separated by a tab or one per line as described in "[Custom Dictionary Format and Syntax](#) (page 6-2)".

Custom Dictionary Format and Syntax

The custom dictionary enables you to define a new stem or redefine an existing stem to add words to [AUTO_LEXER](#) (page 2-33) for your language.

Define a new stem or redefine an existing one using the following syntax:

```
COMPOUND<tab>word|word<tab>STEM<tab>word<tab>parts-of-speech<tab>features
```

COMPOUND

Use COMPOUND to create a compound word by joining two whole words with a pipe (|). The *word* is a simple text string that you want to join to another word to create one compound word to add to the language you specify in [AUTO_LEXER](#) (page 2-33).

Note that COMPOUND supports a maximum of 8 component words for a compound word.

STEM

Use STEM to add the root for a new word.

word

For COMPOUND and STEM, the *word* value is a simple text string representing a word that you want to join with another word to create a new word; or a word root or stem that you want to add to the language dictionary in [AUTO_LEXER](#).

parts-of-speech

The *parts-of-speech* value is a list of valid parts of speech, separated by a comma. [Table 6-1](#) (page 6-3) lists the names for *parts-of-speech* value. At least one *parts-of-speech* value is required.

features

The *features* represent a list of valid linguistic features, as shown in [Table 6-2](#) (page 6-3). Multiple features are separated by a comma. Features are optional. If the word is already defined in the supplied language dictionary, then this definition overrides it. It is an error to have an invalid value for *parts-of-speech* or *features*.

Table 6-1 Custom Dictionary Valid Parts-of-Speech (case sensitive)

Part-of-Speech	Description
noun	A simple noun, like table, book, or procedure.
nounProper	A proper name, for person, place, etc., typically capitalized, like Zachary, Supidito, Susquehanna
adjective	Modifiers of nouns, which typically can be compared (green, greener, greenest), like fast, trenchant, pendulous.
adverb	Any general modifier of a sentence that may modify an adjective or verb or may stand alone, like slowly, yet, perhaps.
preposition	A word that forms a prepositional phrase with a noun, like off, beside, from. Used for postpositions too, in languages that have postpositions of similar function.

[Table 6-2](#) (page 6-3) lists the features and their usage. The specified language determines whether these are relevant and necessary. Note that *declension* refers to the inflection some languages use to determine number (singular or plural), case, and gender. The features are relevant depending on the language for the custom dictionary.

Table 6-2 Custom Dictionary Valid Features

Feature (case sensitive)	Description
genderMasculine	masculine
genderFeminine	feminine
genderNeuter	neuter
declensionHard	hard declension
declensionSoft	soft declension

Examples

```
exec CTX_DDL.CREATE_PREFERENCE('A_LEX', 'AUTO_LEXER');
exec CTX_ANL.ADD_DICTIONARY('my_dict1', 'ENGLISH', lobloc);
select * from CTX_USR_ANL_DICTS;
exec CTX_DDL.SET_ATTRIBUTE('A_LEX', 'english_dictionary', 'MY_ENGLISH');
```

The following example creates a custom dictionary named `d1` to be added to `AUTO_LEXER` for the English language.

```
declare
  dict clob;
begin
  dict := '# compounds
COMPOUND      help|desk
COMPOUND      help|desks
COMPOUND      book|shelf
COMPOUND      book|shelves
COMPOUND      back|woods|man
' ||
  '# define company abbreviations
STEM  comp.  noun
STEM  ltd.   noun
STEM  co.    noun
STEM  oracle nounProper
STEM  make   verb
STEM  unkwor noun
STEM  unkwor verb
';
  ctx_anl.add_dictionary('d1','ENGLISH',dict);
end;
/
```

Related Topics

["AUTO_LEXER \(page 2-33\)"](#)

["CREATE_PREFERENCE \(page 8-31\)"](#)

["SET_ATTRIBUTE \(page 8-64\)"](#)

["DROP_DICTIONARY \(page 6-4\)"](#)

6.3 DROP_DICTIONARY

Use this procedure to drop a custom dictionary from [AUTO_LEXER \(page 2-33\)](#).

Syntax

```
CTX_ANL.DROP_DICTIONARY(
  name          in VARCHAR2,
  language      in VARCHAR2,
  dictionary     in CLOB
);
```

name

The unique name for the user-created custom dictionary.

language

The language for the custom dictionary.

dictionary

The CLOB representing the custom dictionary.

Example

```
begin
  CTX_ANL.DROP_DICTIONARY('dict1', 'english', 'dictionary');
end;
```

Related Topic

["AUTO_LEXER \(page 2-33\)"](#)

["ADD_DICTIONARY \(page 6-1\)"](#)

CTX_CLS Package

This chapter contains the following topics.

- [About CTX_CLS Package Procedures](#) (page 7-1)
- [TRAIN](#) (page 7-1)
- [CLUSTERING](#) (page 7-4)

7.1 About CTX_CLS Package Procedures

The CTX_CLS PL/SQL package provides procedures for generating rules that define document categories, and enables you to perform document classification.

The following procedures are in the CTX_CLS PL/SQL package.

Name	Description
TRAIN (page 7-1)	Generates rules that define document categories. Output based on input training document set.
CLUSTERING (page 7-4)	Generates clusters for a document collection.

See Also:

Oracle Text Application Developer's Guide for more information on document classification

7.2 TRAIN

Use this procedure to generate query rules that select document categories. You must supply a training set consisting of categorized documents. Documents can be in any format supported by Oracle Text and must belong to one or more categories. This procedure generates the queries that define the categories and then writes the results to a table.

You must also have a document table and a category table. The category table must contain at least two categories.

For example, your document and category tables can be defined as:

```
create table trainingdoc(  
  
docid number primary key,  
text varchar2(4000));
```

```
create table category (

docid trainingdoc(docid),
categoryid number);
```

You can use one of two syntaxes depending on the classification algorithm you need. The query compatible syntax uses the `RULE_CLASSIFIER` preference and generates rules as query strings. The *Support Vector Machine syntax* uses the `SVM_CLASSIFIER` preference and generates rules in binary format. The `SVM_CLASSIFIER` is good for high classification accuracy, but because its rules are generated in binary format, they cannot be examined like the query strings generated with the `RULE_CLASSIFIER`. Note that only those document ids that appear in both the document table and the category table will impact `RULE_CLASSIFIER` and `SVM_CLASSIFIER` learning.

The `CTX_CLS . TRAIN` procedure requires that your document table have an associated context index. For best results, the index should be synchronized before running this procedure. `SVM_CLASSIFIER` syntax enables the use of an unpopulated context index, while query-compatible syntax requires that the context index be populated.

See Also:

Oracle Text Application Developer's Guide for more on document classification

Query Compatible Syntax

The following syntax generates query-compatible rules and is used with the [RULE_CLASSIFIER](#) (page 2-90) preference. Use this syntax and preference when different categories are separated from others by several key words. An advantage of generating your rules as query strings is that you can easily examine the generated rules. This is different from generating SVM rules, which are in binary format.

```
CTX_CLS.TRAIN(

index_name    in varchar2,
docid         in varchar2,
cattab        in varchar2,
catdocid      in varchar2,
catid         in varchar2,
restab        in varchar2,
rescatid      in varchar2,
resquery      in varchar2,
resconfid     in varchar2,
preference    in varchar2 DEFAULT NULL

);
```

index_name

Specify the name of the context index associated with your document training set.

docid

Specify the name of the document ID column in the document table. The document IDs in this column must be unique, and this column must be of datatype `NUMBER`. The values for this column must be stored in an unsigned 32-bit integer and must be in the range 0-4294967295.

cattab

Specify the name of the category table. You must have the `READ` or `SELECT` privilege on this table. (See *Oracle Database Security Guide* for information about the `READ` privilege.)

catdocid

Specify the name of the document ID column in the category table. The document IDs in this table must also exist in the document table. This column must be a `NUMBER`. The values for this column must be stored in an unsigned 32-bit integer and must be in the range 0-4294967295.

catid

Specify the name of the category ID column in the category table. This column must be a `NUMBER`. The values for this column must be stored in an unsigned 32-bit integer and must be in the range 0-4294967295.

restab

Specify the name of the result table. You must have `INSERT` privilege on this table.

rescatid

Specify the name of the category ID column in the result table. This column must be a `NUMBER`. The values for this column must be stored in an unsigned 32-bit integer and must be in the range 0-4294967295.

resquery

Specify the name of the query column in the result table. This column must be `VARACHAR2`, `CHAR`, `CLOB`, `NVARCHAR2`, or `NCHAR`.

The queries generated in this column connects terms with `AND` or `NOT` operators, such as:

```
'T1 & T2 ~ T3'
```

Terms can also be theme tokens and be connected with the `ABOUT` operator, such as:

```
'about(T1) & about(T2) ~ about(T3)'
```

Generated rules also support `WITHIN` queries on field sections.

resconfid

Specify the name of the confidence column in result table. This column contains the estimated probability from training data that a document is relevant if that document satisfies the query.

preference

Specify the name of the preference. For classifier types and attributes, see "[Classifier Types](#) (page 2-89)" in [Oracle Text Indexing Elements](#) (page 2-1).

Syntax for Support Vector Machine (SVM) Rules

The Support Vector Machine, or SVM, rules preference generates rules in binary format. Use this syntax when your application requires high classification accuracy.

The following syntax generates Support Vector Machine (SVM) rules with the [SVM_CLASSIFIER](#) (page 2-91) preference.

```
CTX_CLS.TRAIN(
    index_name in varchar2,
```

```
docid      in varchar2,  
cattab     in varchar2,  
catdocid   in varchar2,  
catid      in varchar2,  
restab     in varchar2,  
preference in varchar2 );
```

index_name

Specify the name of the text index.

docid

Specify the name of docid column in document table.

cattab

Specify the name of category table.

catdocid

Specify the name of docid column in category table.

catid

Specify the name of category ID column in category table.

restab

Specify the name of result table.

The result table has the following format:

Column Name	Datatype	Description
CAT_ID	NUMBER	The ID of the category.
TYPE	NUMBER (3) NOT NULL	0 for the actual rule or catid; 1 for other.
RULE	BLOB	The returned rule.

preference

Specify the name of user preference. For classifier types and attributes, see "[Classifier Types](#) (page 2-89)" in [Oracle Text Indexing Elements](#) (page 2-1).

Example

The CTX_CLS . TRAIN procedure is used in supervised classification. For an extended example, see *Oracle Text Application Developer's Guide*.

7.3 CLUSTERING

Use this procedure to cluster a collection of documents. A *cluster* is a group of documents similar to each other in content.

A clustering result set is composed of *document assignments* and *cluster descriptions*:

- A document assignment result set shows how relevant each document is to all generated leaf clusters.
- A cluster description result set contains information about what topic a cluster is about. This result set identifies the cluster and contains cluster description text, a suggested cluster label, and a quality score for the cluster.

Cluster output is hierarchical. Only leaf clusters are scored for relevance to documents. Producing more clusters requires more computing time. Indicate the upper limit for generated clusters with the `CLUSTER_NUM` attribute of the `KMEAN_CLUSTERING` cluster type (see "[Cluster Types](#) (page 2-92)" in this chapter).

There are two versions of this procedure: one with a table result set, and one with an in-memory result set.

Clustering is also known as *unsupervised classification*.

See Also:

For more information about clustering and relevant preferences, see [Cluster Types](#) (page 2-92) in [Oracle Text Indexing Elements](#) (page 2-1), as well as the *Oracle Text Application Developer's Guide*

Syntax: Table Result Set

```
ctx_cls.clustering (
  index_name  IN VARCHAR2,
  docid       IN VARCHAR2,
  doctab_name IN VARCHAR2,
  clstab_name IN VARCHAR2,
  pref_name   IN VARCHAR2 DEFAULT NULL
);
```

index_name

Specify the name of the context index on collection table.

docid

Specify the name of document ID column of the collection table.

doctab_name

Specify the name of document assignment table. This procedure creates the table with the following structure:

```
doc_assign(
  docid number,
  clusterid number,
  score number
);
```

Column	Description
DOCID	Document ID to identify document.
CLUSTERID	ID of a leaf cluster associated with this document. If CLUSTERID is -1, then the cluster contains "miscellaneous" documents; for example, documents that cannot be assigned to any other cluster category.
SCORE	The associated score between the document and the cluster.

If you require more columns, then create the table before you call this procedure.

clstab_name

Specify the name of the cluster description table. This procedure creates the table with the following structure:

```
cluster_desc(
  clusterid NUMBER,
  descript VARCHAR2(4000),
  label VARCHAR2(200),
  size NUMBER,
  quality_score NUMBER,
  parent NUMBER
);
```

Column	Description
CLUSTERID	Cluster ID to identify cluster. If CLUSTERID is -1, then the cluster contains "miscellaneous" documents; for example, documents that cannot be assigned to any other cluster category.
DESCRIPT	String to describe the cluster.
LABEL	A suggested label for the cluster.
SIZE	This parameter currently has no value.
QUALITY_SCORE	The quality score of the cluster. A higher number indicates greater coherence.
PARENT	The parent cluster ID. Zero means no parent cluster.

If you require more columns, then create the table before you call this procedure.

pref_name

Specify the name of the preference.

Syntax: In-Memory Result Set

Put the result set into in-memory structures for better performance. Two in-memory tables are defined in CTX_CLS package for document assignment and cluster description respectively.

```
CTX_CLS.CLUSTERING(
  index_name    IN VARCHAR2,
  docid         IN VARCHAR2,
  dids          IN DOCID_TAB,
  doctab_name   IN OUT NOCOPY DOC_TAB,
  clstab_name   IN OUT NOCOPY CLUSTER_TAB,
  pref_name     IN VARCHAR2 DEFAULT NULL
);
```

index_name

Specify the name of context index on the collection table.

docid

Specify the document ID column of the collection table.

dids

Specify the name of the in-memory docid_tab.


```
TYPE docid_tab IS TABLE OF number INDEX BY BINARY_INTEGER;
```

doctab_name

Specify name of the document assignment in-memory table. This table is defined as follows:

```
TYPE doc_rec IS RECORD (
    docid NUMBER,
    clusterid NUMBER,
    score NUMBER
)
TYPE doc_tab IS TABLE OF doc_rec INDEX BY BINARY_INTEGER;
```

Column	Description
DOCID	Document ID to identify document.
CLUSTERID	ID of a leaf cluster associated with this document. If CLUSTERID is -1, then the cluster contains "miscellaneous" documents; for example, documents that cannot be assigned to any other cluster category.
SCORE	The associated score between the document and the cluster.

cls_tab

Specify the name of cluster description in-memory table.

```
TYPE cluster_rec IS RECORD(
    clusterid NUMBER,
    descript VARCHAR2(4000),
    label VARCHAR2(200),
    size NUMBER,
    quality_score NUMBER,
    parent NUMBER
);
TYPE cluster_tab IS TABLE OF cluster_rec INDEX BY BINARY_INTEGER;
```

Column	Description
CLUSTERID	Cluster ID to identify cluster. If CLUSTERID is -1, then the cluster contains "miscellaneous" documents; for example, documents that cannot be assigned to any other cluster category.
DESCRIPT	String to describe the cluster.
LABEL	A suggested label for the cluster.
SIZE	This parameter currently has no value.
QUALITY_SCORE	The quality score of the cluster. A higher number indicates greater coherence.
PARENT	The parent cluster ID. Zero means no parent cluster.

pref_name

Specify the name of the preference. For cluster types and attributes, see [Cluster Types](#) (page 2-92) in [Oracle Text Indexing Elements](#) (page 2-1).

Example

See Also:

The *Oracle Text Application Developer's Guide* for an example of using clustering

CTX_DDL Package

The CTX_DDL PL/SQL package provides procedures to create and manage the preferences, section groups, and stoplists required for Text indexes.

CTX_DDL contains the following stored procedures and functions:

Name	Description
ADD_ATTR_SECTION (page 8-3)	Adds an attribute section to an XML section group.
ADD_AUTO_OPTIMIZE (page 8-4)	Adds an index or partition to the list of indexes subject to auto optimization.
ADD_FIELD_SECTION (page 8-5)	Creates a field section and assigns it to the specified section group.
ADD_INDEX (page 8-8)	Adds an index to a catalog index preference.
ADD_MDATA (page 8-9)	Changes the MDATA value of a document.
ADD_MDATA_COLUMN (page 8-11)	Maps a <code>FILTER BY</code> column to the specified MDATA section.
ADD_MDATA_SECTION (page 8-12)	Adds an MDATA metadata section to a document.
ADD_NDATA_SECTION (page 8-13)	Adds an NDATA section to a document.
ADD_SDATA_COLUMN (page 8-14)	Maps a <code>FILTER BY</code> column to the specified SDATA section.
ADD_SDATA_SECTION (page 8-16)	Adds an SDATA structured data section to a document.
ADD_SEC_GRP_ATTR_VAL (page 8-17)	Adds a section group attribute value to the list of values of an already existing section group attribute.
ADD_SPECIAL_SECTION (page 8-18)	Adds a special section to a section group.
ADD_STOPCLASS (page 8-19)	Adds a stopclass to a stoplist.
ADD_STOP_SECTION (page 8-21)	Adds a stop section to an automatic section group.
ADD_STOPTHEME (page 8-22)	Adds a stoptheme to a stoplist.
ADD_STOPWORD (page 8-23)	Adds a stopword to a stoplist.
ADD_SUB_LEXER (page 8-24)	Adds a sub-lexer to a multi-lexer preference.
ADD_ZONE_SECTION (page 8-26)	Creates a zone section and adds it to the specified section group.
COPY_POLICY (page 8-29)	Creates a copy of a policy.

Name	Description
CREATE_INDEX_SET (page 8-29)	Creates an index set for CTXCAT index types.
CREATE_POLICY (page 8-30)	Creates a policy to use with <code>ORA:CONTAINS()</code> .
CREATE_PREFERENCE (page 8-31)	Creates a preference in the Text data dictionary.
CREATE_SECTION_GROUP (page 8-34)	Creates a section group in the Text data dictionary.
CREATE_SHADOW_INDEX (page 8-37)	Creates a policy for the passed-in index. For nonpartitioned index, also creates an index table.
CREATE_STOPLIST (page 8-39)	Creates a stoplist.
DROP_INDEX_SET (page 8-40)	Drops an index set.
DROP_POLICY (page 8-40)	Drops a policy.
DROP_PREFERENCE (page 8-41)	Deletes a preference from the Text data dictionary.
DROP_SECTION_GROUP (page 8-41)	Deletes a section group from the Text data dictionary.
DROP_SHADOW_INDEX (page 8-42)	Drops a shadow index.
DROP_STOPLIST (page 8-42)	Drops a stoplist.
EXCHANGE_SHADOW_INDEX (page 8-43)	Swaps the shadow index metadata and data.
OPTIMIZE_INDEX (page 8-44)	Optimizes the index.
POPULATE_PENDING (page 8-50)	Populates the pending queue with every rowid in the base table or table partition.
PREFERENCE_IMPLICIT_COMMIT (page 8-50)	Specifies whether procedures related to CTX_DDL preferences issue an implicit commit.
RECREATE_INDEX_ONLINE (page 8-51)	Recreates the passed-in index.
REM_SEC_GRP_ATTR_VAL (page 8-58)	Removes a specific section group attribute value from the list of values of an existing section group attribute.
REMOVE_AUTO_OPTIMIZE (page 8-58)	Removes an index or partition from the list of indexes subject to auto optimization
REMOVE_INDEX (page 8-59)	Removes an index from a CTXCAT index preference.
REMOVE_MDATA (page 8-59)	Removes MDATA values from a document.
REMOVE_SECTION (page 8-60)	Deletes a section from a section group.
REMOVE_STOPCLASS (page 8-61)	Deletes a stopclass from a stoplist.
REMOVE_STOPTHEME (page 8-61)	Deletes a stoptheme from a stoplist.
REMOVE_STOPWORD (page 8-62)	Deletes a stopword from a stoplist.
REMOVE_SUB_LEXER (page 8-63)	Deletes a sub-lexer from a multi-lexer preference.
REPLACE_INDEX_METADATA (page 8-63)	Replaces metadata for local domain indexes.

Name	Description
SET_ATTRIBUTE (page 8-64)	Sets a preference attribute.
SET_SEC_GRP_ATTR (page 8-65)	Adds a section group-specific attribute to a section group identified by name.
SET_SECTION_ATTRIBUTE (page 8-66)	Sets a section attribute.
SYNC_INDEX (page 8-68)	Synchronizes the index.
UNSET_ATTRIBUTE (page 8-70)	Removes a set attribute from a preference.
UPDATE_SUB_LEXER (page 8-71)	Updates a sub-lexer.
UNSET_SEC_GRP_ATTR (page 8-71)	Removes a section group specific attribute.
UPDATE_POLICY (page 8-72)	Updates a policy.
UPDATE_SDATA (page 8-73)	Updates an SDATA section.

8.1 ADD_ATTR_SECTION

Adds an attribute section to an XML section group. This procedure is useful for defining attributes in XML documents as sections. This enables you to search XML attribute text with the `WITHIN` operator.

Note:

When you use `AUTO_SECTION_GROUP`, attribute sections are created automatically. Attribute sections created automatically are named in the form `tag@attribute`.

Syntax

```
CTX_DDL.ADD_ATTR_SECTION(
  group_name      IN   VARCHAR2,
  section_name    IN   VARCHAR2,
  tag             IN   VARCHAR2);
```

group_name

Specify the name of the XML section group. You can add attribute sections only to XML section groups.

section_name

Specify the name of the attribute section. This is the name used for `WITHIN` queries on the attribute text.

The section name you specify cannot contain the colon (:), comma (,), or dot (.) characters. The section name must also be unique within `group_name`. Section names are case-insensitive.

Attribute section names can be no more than 64 bytes long.

tag

Specify the name of the attribute in tag@attr form. This parameter is case-sensitive.

Examples

Consider an XML file that defines the BOOK tag with a TITLE attribute as follows:

```
<BOOK TITLE="Tale of Two Cities">
  It was the best of times.
</BOOK>
```

To define the title attribute as an attribute section, create an XML_SECTION_GROUP and define the attribute section as follows:

```
begin
ctx_ddl.create_section_group('myxmlgroup', 'XML_SECTION_GROUP');
ctx_ddl.add_attr_section('myxmlgroup', 'booktitle', 'BOOK@TITLE');
end;
```

When you define the TITLE attribute section as such and index the document set, you can query the XML attribute text as follows:

```
'Cities within booktitle'
```

Related Topic

["PREFERENCE_IMPLICIT_COMMIT \(page 8-50\)"](#)

8.2 ADD_AUTO_OPTIMIZE

Adds an index or partition to the list of indexes subject to auto optimization. For partitioned indexes, the name of the partition must be specified, or else an error occurs. For global indexes, STAGE_ITAB must be enabled, or else an error occurs.

The AUTO_OPTIMIZE feature improves the manageability of indexes that use the STAGE_ITAB feature. The STAGE_ITAB feature introduces a staging \$G table to collect postings from newly synced documents.

The AUTO_OPTIMIZE feature has the following goals:

- Enables you to register indexes and partitions to a background AUTO_OPTIMIZE process.
- Automatically moves rows from the \$G table to \$I at appropriate times.
- Movement of rows from \$G to \$I is done in a way to maximize query performance.

This procedure starts the background process if it has not already been started. The progress of the auto optimization is tracked by CTX logging.

The changes made by this procedure take effect immediately.

Note:

The init.ora parameter JOB_QUEUE_PROCESSES must be set to one or higher. See *Oracle Database Reference* for more information about JOB_QUEUE_PROCESSES.

Syntax

```
CTX_DDL.ADD_AUTO_OPTIMIZE(  
  
    idx_name      IN VARCHAR2,  
    part_name     IN VARCHAR2 default NULL,  
    optlevel      IN VARCHAR2 default CTX_DDL.OPTLEVEL_MERGE  
);
```

idx_name

Specify the name of the index to add.

part_name

Specify the name of the partition to add.

optlevel

Specifies the `optlevel` of the `CTX_DDL.OPTIMIZE_INDEX` (page 8-44) procedure. The only valid value for this parameter is `merge`.

Notes

The recommended sequence of steps for using auto optimization is:

1. Create the required indexes.
2. Add these indexes to the auto optimization list by using the `CTX_DDL.ADD_AUTO_OPTIMIZE` procedure.

The synchronize index operation automatically begins executing an auto optimization job (unless it is already running). This job continues until it runs out of work. Future synchronize index operations will automatically start executing the auto optimization job, if it is not already running.

Related Topics

["REMOVE_AUTO_OPTIMIZE](#) (page 8-58)"

Oracle Text Application Developer's Guide for information about using `STAGE_ITAB` with `CONTEXT` indexes

8.3 ADD_FIELD_SECTION

Creates a field section and adds the section to an existing section group. This enables field section searching with the [WITHIN](#) (page 3-54) operator. You can add an unlimited number of field sections.

Field sections are delimited by start and end tags. By default, the text within field sections are indexed as a sub-document separate from the rest of the document.

Unlike zone sections, field sections cannot nest or overlap. As such, field sections are best suited for non-repeating, non-overlapping sections such as `TITLE` and `AUTHOR` markup in e-mail- or news-type documents.

Because of how field sections are indexed, [WITHIN](#) (page 3-54) queries on field sections are usually faster than `WITHIN` queries on zone sections.

Syntax

```
CTX_DDL.ADD_FIELD_SECTION(  
    group_name      IN      VARCHAR2,  
    section_name    IN      VARCHAR2,  
    tag              IN      VARCHAR2,  
    visible          IN      BOOLEAN default FALSE  
);
```

group_name

Specify the name of the section group to which `section_name` is added. You can add an unlimited number of field sections to a single section group. Within the same group, section zone names and section field names cannot be the same.

section_name

Specify the name of the section to add to the `group_name`. Use this name to identify the section in queries. Avoid using names that contain non-alphanumeric characters such as `_`, because these characters must be escaped in queries. Section names are case-insensitive.

Within the same group, zone section names and field section names cannot be the same. The terms *Paragraph* and *Sentence* are reserved for special sections.

Section names need not be unique across tags. You can assign the same section name to more than one tag, which makes details transparent to searches.

tag

Specify the tag that marks the start of a section. For example, if the tag is `<H1>`, then specify `H1`. The start tag you specify must be unique within a section group.

If `group_name` is an `HTML_SECTION_GROUP`, then you can create field sections for the `META` tag's `NAME/CONTENT` attribute pairs. To do so, specify `tag` as `meta@namevalue` where `namevalue` is the value of the `NAME` attribute whose `CONTENT` attribute is to be indexed as a section. Refer to the example "[Creating Sections for <META> Tags](#) (page 8-7)".

Oracle Text knows what the end tags look like from the `group_type` parameter you specify when you create the section group.

visible

Specify `TRUE` to make the text visible within the rest of the document.

By default the `visible` flag is `FALSE`. This means that Oracle Text indexes the text within field sections as a sub-document separate from the rest of the document. However, you can set the `visible` flag to `TRUE` if you want text within the field section to be indexed as part of the enclosing document.

Examples

Visible and Invisible Field Sections

The following example defines a section group `basicgroup` of the `BASIC_SECTION_GROUP` type. (See "[Section Group Types](#) (page 2-86)" for information about the `BASIC_SECTION_GROUP` type.) The example then creates a field section in `basicgroup` called `Author` for the `<A>` tag.

The example also sets the `visible` flag to `FALSE`:

```
begin
```



```
ctx_ddl.create_section_group('basicgroup', 'BASIC_SECTION_GROUP');
ctx_ddl.add_field_section('basicgroup', 'Author', 'A', FALSE);

end;
```

Because the Author field section is not visible, to find text within the Author section, you must use the [WITHIN](#) (page 3-54) operator as follows:

```
'(Martin Luther King) WITHIN Author'
```

A query of *Martin Luther King* without the WITHIN operator does not return instances of this term in field sections. To query text within field sections without specifying WITHIN, you must set the visible flag to TRUE when you create the section as follows:

```
begin
ctx_ddl.add_field_section('basicgroup', 'Author', 'A', TRUE);
end;
```

Creating Sections for <META> Tags

When you use the HTML_SECTION_GROUP, you can create sections for META tags.

Consider an HTML document that has a META tag as follows:

```
<META NAME="author" CONTENT="ken">
```

To create a field section that indexes the CONTENT attribute for the <META NAME="author"> tag:

```
begin
ctx_ddl.create_section_group('myhtmlgroup', 'HTML_SECTION_GROUP');
ctx_ddl.add_field_section('myhtmlgroup', 'author', 'META@AUTHOR');
end
```

After indexing with section group mygroup, query the document as follows:

```
'ken WITHIN author'
```

Limitations

Nested Sections

Field sections cannot be nested. For example, if you define a field section to start with <TITLE> and define another field section to start with <FOO>, the two sections *cannot* be nested as follows:

```
<TITLE> dog <FOO> cat </FOO> </TITLE>
```

To work with nested section define them as zone sections.

Repeated Sections

Repeated field sections are allowed, but WITHIN queries treat them as a single section. The following is an example of repeated field section in a document:

```
<TITLE> cat </TITLE>
<TITLE> dog </TITLE>
```

The query (*dog and cat*) *within title* returns the document, even though these words occur in different sections.

To have WITHIN queries distinguish repeated sections, define them as zone sections.

Related Topics

["WITHIN \(page 3-54\)"](#)

["Section Group Types \(page 2-86\)"](#)

["CREATE_SECTION_GROUP \(page 8-34\)"](#)

["ADD_ZONE_SECTION \(page 8-26\)"](#)

["ADD_SPECIAL_SECTION \(page 8-18\)"](#)

["REMOVE_SECTION \(page 8-60\)"](#)

["DROP_SECTION_GROUP \(page 8-41\)"](#)

8.4 ADD_INDEX

Use this procedure to add a subindex to a catalog index preference. Create this preference by naming one or more columns in the base table.

Because you create subindexes to improve the response time of structured queries, the column you add should be used in the `structured_query` clause of the `CATSEARCH` operator at query time.

Syntax

```
CTX_DDL.ADD_INDEX(  
    set_name          IN VARCHAR2,  
    column_list       IN VARCHAR2,  
    storage_clause    IN VARCHAR2  
);
```

set_name

Specify the name of the index set.

column_list

Specify a comma-delimited list of columns to index. At index time, any column listed here cannot have a NULL value in any row in the base table. If any row is NULL during indexing, then an error is raised.

Always ensure that your columns have non-NULL values before and after indexing.

storage_clause

Specify a storage clause.

Example

Consider a table called `AUCTION` with the following schema:

```
create table auction(  
  
    item_id number,  
    title varchar2(100),  
    category_id number,  
    price number,  
    bid_close date);
```

Assume that queries on the table involve a mandatory text query clause and optional structured conditions on `category_id`. Results must be sorted based on `bid_close`.

You can create a catalog index to support the different types of structured queries a user might enter.

To create the indexes, first create the index set preference then add the required indexes to it:

```
begin
  ctx_ddl.create_index_set('auction_iset');
  ctx_ddl.add_index('auction_iset','bid_close');
  ctx_ddl.add_index('auction_iset','category_id, bid_close');
end;
```

Create the combined catalog index with CREATE INDEX as follows:

```
create index auction_titlex on AUCTION(title) indextype is CTXCAT parameters
('index set auction_iset');
```

Querying

To query the title column for the word *pokemon*, enter regular and mixed queries as follows:

```
select * from AUCTION where CATSEARCH(title, 'pokemon',NULL)> 0;
select * from AUCTION where CATSEARCH(title, 'pokemon', 'category_id=99 order by
bid_close desc')> 0;
```

Notes

VARCHAR2 columns in the column list of a CTXCAT index of an index set cannot exceed 30 bytes.

Related Topic

["REMOVE_INDEX \(page 8-59\)"](#)

8.5 ADD_MDATA

Use this procedure to change the metadata of a document that has been specified as an MDATA section. After this call, MDATA queries involving the named MDATA value will find documents with the given MDATA value.

There are two versions of CTX_DDL.ADD_MDATA: one for adding a single metadata value to a single rowid, and one for handling multiple values, multiple rowids, or both.

CTX_DDL.ADD_MDATA is transactional; it takes effect immediately in the calling session, can be seen only in the calling session, can be reversed with a ROLLBACK command, and must be committed to take permanent effect.

Use CTX_DDL.REMOVE_MDATA (page 8-59) to remove metadata values from already-indexed documents. Only the owner of the index is allowed to call ADD_MDATA and REMOVE_MDATA.

Syntax

This is the syntax for adding a single value to a single rowid:

```
CTX_DDL.ADD_MDATA(
  idx_name          IN VARCHAR2,
  section_name      IN VARCHAR2,
  mdata_value       IN VARCHAR2,
  mdata_rowid       IN VARCHAR2,
```

```
    [part_name]          IN VARCHAR2]
);
```

idx_name

Name of the text index that contains the named *rowid*.

section_name

Name of the MDATA section.

mdata_value

The metadata value to add to the document.

mdata_rowid

The rowid to which to add the metadata value.

[part_name]

Name of the index partition, if any. Must be provided for local partitioned indexes and must be NULL for global, nonpartitioned indexes.

This is the syntax for handling multiple values, multiple rowids, or both. This version is more efficient for large numbers of new values or rowids.

```
CTX_DDL.ADD_MDATA(
    idx_name          IN VARCHAR2,
    section_name      IN VARCHAR2,
    mdata_values      SYS.ODCIVARCHAR2LIST,
    mdata_rowids      SYS.ODCIRIDLIST,
    [part_name]       IN VARCHAR2]
);
```

idx_name

Name of the text index that contains the named *rowids*.

section_name

Name of the MDATA section.

mdata_values

List of metadata values. If a metadata value contains a comma, the comma must be escaped with a backslash.

mdata_rowids

The rowids to which to add the metadata values.

[part_name]

Name of the index partition, if any. Must be provided for local partitioned indexes and must be NULL for global, nonpartitioned indexes.

Example

This example updates a single value:

```
select rowid from mytab where contains(text, 'MDATA(sec, value')>0;
No rows returned
exec ctx_ddl.add_mdata('my_index', 'sec', 'value', 'ABC');
select rowid from mytab where contains(text, 'MDATA(sec, value')>0;
ROWID
```

```
-----
ABC
```

This example updates multiple values:

```
begin
ctx_ddl.add_mdata('my_index', 'sec',
  sys.odcivarchar2list('value1','value2','value3'),
  sys.odciridlist('ABC','DEF'));
end;
```

This is equivalent to:

```
begin
ctx_ddl.add_mdata('my_index', 'sec', 'value1', 'ABC');
ctx_ddl.add_mdata('my_index', 'sec', 'value1', 'DEF');
ctx_ddl.add_mdata('my_index', 'sec', 'value2', 'ABC');
ctx_ddl.add_mdata('my_index', 'sec', 'value2', 'DEF');
ctx_ddl.add_mdata('my_index', 'sec', 'value3', 'ABC');
ctx_ddl.add_mdata('my_index', 'sec', 'value3', 'DEF');
end;
```

Notes

If a rowid is not yet indexed, CTX_DDL.ADD_MDATA completes without error, but an error is logged in CTX_USER_INDEX_ERRORS.

These updates are updates directly on the index itself, not on the actual contents stored in the base table. Therefore, they will not survive when the Text index is rebuilt.

Related Topics

["ADD_MDATA_SECTION \(page 8-12\)"](#)

["REMOVE_MDATA \(page 8-59\)"](#)

["MDATA \(page 3-29\)"](#)

See Also:

Chapter 8, "Searching Document Sections in Oracle Text" in *Oracle Text Application Developer's Guide*

8.6 ADD_MDATA_COLUMN

Use this procedure to map the FILTER BY column named in *column_name* to the MDATA section named in *section_name*.

Syntax

The syntax is as follows:

```
CTX_DDL.ADD_MDATA_COLUMN(
  group_name          IN VARCHAR2,
  section_name        IN VARCHAR2,
  column_name         IN VARCHAR2,
);
```

group_name

Name of the group that contains the section.

section_name

Name of the MDATA section.

column_name

Name of the `FILTER BY` column to add to the MDATA section.

Restrictions

MDATA sections that are created with `CTX_DDL.ADD_MDATA_COLUMN` cannot have their values changed using `CTX_DDL.ADD_MDATA` or `CTX_DDL.REMOVE_MDATA`. Doing so will result in errors being returned. The section values must be updated using SQL.

Notes

- The stored datatype for MDATA sections is `text`. Therefore, the value of the `FILTER BY` column is converted to `text` during indexing. For non-text datatypes, the `FILTER BY` columns are normalized to an internal format during indexing. If the section is queried with an MDATA operator, then the MDATA query string will also be normalized to the internal format before processing.
- When a `FILTER BY` column is mapped as MDATA, the cost-based optimizer in Oracle Text tries to avoid using the Oracle Text composite domain index to process range predicate(s) on that `FILTER BY` column. This is because range predicates on MDATA `FILTER BY` columns are processed less efficiently than if they were declared as `SDATA`. For this reason, you should not add a `FILTER BY` column as MDATA if you plan to do range searches on the column.

Related Topics

["MDATA \(page 3-29\)"](#)

["ADD_MDATA_SECTION \(page 8-12\)"](#)

["REMOVE_MDATA \(page 8-59\)"](#)

["ADD_SDATA_COLUMN \(page 8-14\)"](#)

See Also:

Chapter 8, "Searching Document Sections in Oracle Text" in *Oracle Text Application Developer's Guide*

8.7 ADD_MDATA_SECTION

Use this procedure to add an MDATA section, with an accompanying value, to an existing section group. MDATA sections cannot be added to Null Section groups, Path Section groups, or Auto Section groups.

Section values undergo a simplified normalization:

- Leading and trailing whitespace on the value is removed.
- The value is truncated to 64 bytes.

- The value is indexed as a single value; if the value consists of multiple words, it is not broken up.
- Case is preserved. If the document is dynamically generated, then implement case-insensitivity by uppercasing MDATA values and making sure to search only in uppercase.

Use CTX_DDL.[REMOVE_SECTION](#) (page 8-60) to remove sections.

Syntax

```
CTX_DDL.ADD_MDATA_SECTION(  
    group_name    IN VARCHAR2,  
    section_name  IN VARCHAR2,  
    tag           IN VARCHAR2,  
);
```

group_name

Name of the section group that will contain the MDATA section.

section_name

Name of the MDATA section.

tag

The value of the MDATA section. For example, if the section is <AUTHOR>, the value could be *Cynthia Kadohata* (author of the novel *The Floating World*). More than one *tag* can be assigned to a given MDATA section.

Example

This example creates an MDATA section called auth.

```
ctx_ddl.create_section_group('htmgroup', 'HTML_SECTION_GROUP');  
ctx_ddl.add_mdata_section('htmgroup', 'auth', 'author');
```

Related Topics

["ADD_MDATA](#) (page 8-9)"

["REMOVE_MDATA](#) (page 8-59)"

["MDATA](#) (page 3-29)"

["CREATE_SECTION_GROUP](#) (page 8-34)"

See Also:

Chapter 8, "Searching Document Sections in Oracle Text" in *Oracle Text Application Developer's Guide*

8.8 ADD_NDATA_SECTION

Use this procedure to find matches that are spelled in a similar way. The value of an NDATA section is extracted from the document text like other sections, but is indexed as name data. NDATA sections are stored in the CTX_USER_SECTIONS view.

Syntax

```
CTX_DDL.ADD_NDATA_SECTION(  
    group_name    IN VARCHAR2,  
    section_name  IN VARCHAR2,  
    tag           IN VARCHAR2  
);
```

group_name

Name of the group that contains the section.

section_name

Name of the NDATA section.

tag

Name of the tag that marks the start of a section. For example, if the tag is <H1>, specify H1. The start tag you specify must be unique within a section group.

Notes

NDATA sections support both single and multi-byte data, however, there are character- and term-based limitations. NDATA section data that is indexed is constrained as follows:

- number of characters in a single, white space delimited term
511
- number of white space delimited terms
255
- total number of characters, including white spaces
511

NDATA section data that exceeds these constraints are truncated.

Example

The following example defines a section group namegroup of the BASIC_SECTION_GROUP type. It then creates an NDATA section in namegroup called firstname.

```
begin  
    ctx_ddl.create_section_group('namegroup', 'BASIC_SECTION_GROUP');  
    ctx_ddl.add_ndata_section('namegroup', 'firstname', 'fname1');  
end;
```

8.9 ADD_SDATA_COLUMN

Use this procedure to map the FILTER BY or ORDER BY column named in *column_name* to the SDATA section named in *section_name*. By default, all FILTER BY columns are mapped as SDATA.

Syntax

The syntax is as follows:


```

CTX_DDL.ADD_SDATA_COLUMN(
    group_name      IN VARCHAR2,
    section_name    IN VARCHAR2,
    column_name     IN VARCHAR2,
);

```

group_name

Name of the group that contains the section.

section_name

Name of the SDATA section.

column_name

Name of the FILTER BY column to add to the SDATA section.

Notes

- Mapping FILTER BY columns to sections is optional. If no section mapping exists for a FILTER BY column, then it is mapped to an SDATA section, and the section name will be the name of the FILTER BY column.
- If a section group is not specified during CREATE INDEX of a composite domain index, then system default section group settings will be used, and a SDATA section will be created for each of the FILTER BY and ORDER BY columns.

Note:

Because section name does not allow certain special characters and is case insensitive, if the column name is case sensitive or contains special characters, then an error will be raised. To work around this problem, you need to map the column to an MDATA or SDATA section before creating the index. Refer to [CTX_DDL.ADD_MDATA_COLUMN](#) (page 8-11) or [CTX_DDL.ADD_SDATA_COLUMN](#) (page 8-14) in this chapter.

- An error will be raised if a column mapped to MDATA also appears in the ORDER BY column clause.
- Column section names are unique to their section group. That is, you cannot have an MDATA column section named FOO if you already have an MDATA column section named FOO. Furthermore, you cannot have a field section named FOO if you already have an SDATA column section named FOO. This is true whether it is implicitly created (by CREATE INDEX for FILTER BY or ORDER BY clauses) or explicitly created (by CTX_DDL.ADD_SDATA_COLUMN).
- One section name can only be mapped to one FILTER BY column, and vice versa. For example, mapping a section to more than one column or mapping a column to more than one section is not allowed.
- Column sections can be added to any type of section group, including the NULL section group.
- 99 is the maximum number for SDATA sections and columns.

Related Topics

["SDATA \(page 3-42\)"](#)

["ADD_SDATA_SECTION \(page 8-16\)"](#)

["UPDATE_SDATA \(page 8-73\)"](#)

See Also:

Chapter 8, "Searching Document Sections in Oracle Text" in *Oracle Text Application Developer's Guide*

8.10 ADD_SDATA_SECTION

This procedure adds an SDATA section to a section group. By default, all FILTER BY columns are mapped as SDATA.

Syntax

The syntax is as follows:

```
CTX_DDL.ADD_SDATA_SECTION(  
    group_name      IN VARCHAR2,  
    section_name    IN VARCHAR2,  
    tag             IN VARCHAR2,  
    datatype        IN VARCHAR2 default NULL,  
);
```

group_name

Name of the group that contains the section.

section_name

Name of the SDATA section.

tag

Name of the tag to add to the SDATA section.

datatype

Specifies the stored format for the data, as well as the semantics of comparison in later use in SDATA operators. The default is VARCHAR2, but if specified must be one of the following values:

- VARCHAR2
- CHAR
- RAW
- NUMBER
- DATE

The VARCHAR2 datatype stores up to 249 bytes of character data in the database character set. Values larger than this result in a per-document indexing error. Note that leading and trailing whitespace are always trimmed from SDATA section values when extracted by the sectioner. This is different than SDATA columns. Column

values are never trimmed. No lexing is performed on the value from either kind of SDATA.

The CHAR datatype stores up to 249 bytes of character data in the database character set. Values larger than this result in a per-document indexing error. Note that leading and trailing whitespace are always trimmed from SDATA section values when extracted by the sectioner. This is different than SDATA columns. Column values are never trimmed. No lexing is performed on the value from either kind of SDATA. To be consistent with SQL, the comparisons of CHAR datatype SDATA values are blank-padded comparisons.

RAW datatype stores up to 249 bytes of binary data. Values larger than this result in a per-document indexing error. The value is converted from hexadecimal string representation. That is, to store a value of 65, the document should look like <TAG>40</TAG>, and not <TAG>65</TAG> or <TAG>A</TAG>.

The DATE datatype values must conform to the following format: YYYY-MM-DD or YYYY-MM-DD HH24:MI:SS. That is, to store a DATE value of "Nov. 24, 2006 10:32pm 36sec", the document should look like <TAG>2006-11-24 22:32:36</TAG>.

Limitations

- The maximum number of SDATA sections that can be created for an index is 99. That is, the sum total of SDATA sections for an index, created implicitly with FILTER BY and ORDER BY and explicitly with the CTX_DDL.ADD_SDATA_SECTION() API is 99.
- SDATA are single-occurrence only. If multiple instances of an SDATA tag are encountered in a single document, then later instances supersede the value set by earlier instances. This means that the last occurrence of an SDATA tag takes effect.
- If no SDATA tag occurs in a given document, then this is treated as an SDATA value of NULL.
- Empty SDATA tags are treated as NULL values.
- SDATA sections cannot be nested. Sections that are nested inside are ignored.
- 99 is the maximum number for SDATA sections and columns.

Related Topics

["SDATA \(page 3-42\)"](#)

["ADD_SDATA_COLUMN \(page 8-14\)"](#)

["UPDATE_SDATA \(page 8-73\)"](#)

See Also:

Chapter 8, "Searching Document Sections in Oracle Text" in *Oracle Text Application Developer's Guide*

8.11 ADD_SEC_GRP_ATTR_VAL

Adds a section group attribute value to the list of values of an already existing section group attribute.

Syntax

```
CTX_DDL.ADD_SEC_GRP_ATTR_VAL(  
    group_name      IN VARCHAR2,  
    attribute_name  IN VARCHAR2,  
    attribute_value IN VARCHAR2  
);
```

group_name
Specify the section group name.

attribute_name
Specify the name of the section group attribute.

attribute_value
Specify the section group attribute value.

8.12 ADD_SPECIAL_SECTION

Adds a special section, either SENTENCE or PARAGRAPH, to a section group. This enables searching within sentences or paragraphs in documents with the [WITHIN](#) (page 3-54) operator.

A special section in a document is a section which is not explicitly tagged like zone and field sections. The start and end of special sections are detected when the index is created. Oracle Text supports two such sections: *paragraph* and *sentence*.

The sentence and paragraph boundaries are determined by the lexer. For example, the lexer recognizes sentence and paragraph section boundaries as follows:

Table 8-1 Paragraph and Sentence Section Boundaries

Special Section	Boundary
SENTENCE	WORD/PUNCT/WHITESPACE
SENTENCE	WORD/PUNCT/NEWLINE
PARAGRAPH	WORD/PUNCT/NEWLINE/WHITESPACE (indented paragraph)
PARAGRAPH	WORD/PUNCT/NEWLINE/NEWLINE (block paragraph)

The punctuation, whitespace, and newline characters are determined by your lexer settings and can be changed.

If the lexer cannot recognize the boundaries, no sentence or paragraph sections are indexed.

Syntax

```
CTX_DDL.ADD_SPECIAL_SECTION(  
    group_name      IN VARCHAR2,  
    section_name    IN VARCHAR2  
);
```

group_name
Specify the name of the section group.

section_name

Specify SENTENCE or PARAGRAPH.

Example

The following example enables searching within sentences within HTML documents:

```
begin
ctx_ddl.create_section_group('htmgroup', 'HTML_SECTION_GROUP');
ctx_ddl.add_special_section('htmgroup', 'SENTENCE');
end;
```

Add zone sections to the group to enable zone searching in addition to sentence searching. The following example adds the zone section *Headline* to the section group *htmgroup*:

```
begin
ctx_ddl.create_section_group('htmgroup', 'HTML_SECTION_GROUP');
ctx_ddl.add_special_section('htmgroup', 'SENTENCE');
ctx_ddl.add_zone_section('htmgroup', 'Headline', 'H1');
end;
```

If you are only interested in sentence or paragraph searching within documents and not interested in defining zone or field sections, then use the `NULL_SECTION_GROUP` as follows:

```
begin
ctx_ddl.create_section_group('nullgroup', 'NULL_SECTION_GROUP');
ctx_ddl.add_special_section('nullgroup', 'SENTENCE');
end;
```

Related Topics

["WITHIN \(page 3-54\)"](#)

["Section Group Types \(page 2-86\)"](#)

["CREATE_SECTION_GROUP \(page 8-34\)"](#)

["ADD_ZONE_SECTION \(page 8-26\)"](#)

["ADD_FIELD_SECTION \(page 8-5\)"](#)

["REMOVE_SECTION \(page 8-60\)"](#)

["DROP_SECTION_GROUP \(page 8-41\)"](#)

8.13 ADD_STOPCLASS

Adds a stopclass to a stoplist. A stopclass is a class of tokens that is not to be indexed. A stoplist cannot have more than 250 stopclasses with stoppatterns. This does not include the `NUMBERS` stopclass. When indexing with Stop Patterns, the recommended memory setting is at least 500 MB to 1 GB to optimize the performance of indexing.

Syntax

```
CTX_DDL.ADD_STOPCLASS(
  stoplist_name      IN   VARCHAR2,
  stopclass          IN   VARCHAR2,
  stoppattern        IN   VARCHAR2 default NULL
);
```

stoplist_name

Specify the name of the stoplist.

stopclass

Specify the stopclass to be added to `stoplist_name`. It can be either the `NUMBERS` stopclass or else it is considered as the pattern stopclass.

`NUMBERS` includes tokens that follow the number pattern: `digits`, `numgroup`, and `numjoin` only. Therefore, `123ABC` is not a number, nor is `A123`. These are labeled as `MIXED`. `$123` is not a number (this token is not common in a text index because non-alphanumerics become whitespace by default). In the United States, `123.45` is a number, but `123.456.789` is not; in Europe, where `numgroup` may be `'.'`, the reverse is true.

If `NUMBERS` is not specified for the `stopclass` parameter, then it is treated as a pattern stopclass, and you can provide any name to the `stopclass` parameter. If you specify `stopclass` as a pattern class, then you need to specify the pattern in the `stoppattern` parameter. The pattern includes any string pattern that may contain numbers and dates as well.

The maximum number of stopwords, stopthemes, and stopclasses you can add to a stoplist is 4095.

stoppattern

Specify the stop pattern to add to the stoplist. If the stopclass is specified as a pattern class, then the stop pattern must be specified. You can use the Oracle Regular Expression to specify the stop pattern.

Call the `ADD_STOPCLASS` procedure multiple times to add multiple stop patterns to a stoplist. You must specify different stopclass names for adding multiple stop patterns to a stoplist.

A stop pattern is not case-sensitive by default, but acts as case-sensitive when the `MIXED_CASE` lexer preference is enabled. The stop pattern can have the maximum length of 512 characters. When indexing with Stop Patterns, the recommended memory setting is at least 500 MB to 1 GB to optimize the performance of indexing.

See Also:

Oracle Database Development Guide for more information about the syntax of the Oracle Regular Expression.

Example

The following example adds a stopclass of `NUMBERS` to the stoplist `mystoplist`:

```
begin
ctx_ddl.add_stopclass('mystoplist', 'NUMBERS');
end;
```

The following example adds the pattern stopclass of `SSN` to the stoplist `mystoplist`:

```
begin
ctx_ddl.add_stopclass('mystoplist', 'SSN', '\d{3}-\d{2}-\d{4}');
end;
```

In this example, the stopclass `SSN` matches all the tokens of the form `<3 digit number>-<2 digit number>-<4 digit number>`, example, `234-11-8902`.

Related Topics

["CREATE_STOPLIST \(page 8-39\)"](#)

["REMOVE_STOPCLASS \(page 8-61\)"](#)

["DROP_STOPLIST \(page 8-42\)"](#)

8.14 ADD_STOP_SECTION

Adds a stop section to an automatic section group. Adding a stop section causes the automatic section indexing operation to ignore the specified section in XML documents.

Note:

Adding a stop section causes no section information to be created in the index. However, the text within a stop section is always searchable.

Adding a stop section is useful when your documents contain many low information tags. Adding stop sections also improves indexing performance with the automatic section group.

The number of stop sections you can add is unlimited.

Stop sections do not have section names and hence are not recorded in the section views.

Syntax

```
CTX_DDL.ADD_STOP_SECTION(
    section_group IN VARCHAR2,
    tag           IN VARCHAR2
);
```

section_group

Specify the name of the automatic section group. If you do not specify an automatic section group, then this procedure returns an error.

tag

Specify the tag to ignore during indexing. This parameter is case-sensitive. Defining a stop tag as such also stops the tag's attribute sections, if any.

Qualify the tag with document type in the form (doctype)tag. For example, if you wanted to make the <fluff> tag a stop section only within the mydoc document type, specify (mydoc)fluff for tag.

Example**Defining Stop Sections**

The following example adds a stop section identified by the tag <fluff> to the automatic section group myauto:

```
begin
ctx_ddl.add_stop_section('myauto', 'fluff');
end;
```

This example also stops any attribute sections contained within <fluff>. For example, if a document contained:

```
<fluff type="computer">
```

Then the preceding example also stops the attribute section `fluff@type`.

Doctype Sensitive Stop Sections

The following example creates a stop section for the tag <fluff> only in documents that have a root element of mydoc:

```
begin
ctx_ddl.add_stop_section('myauto', '(mydoc)fluff');
end;
```

Related Topics

["ALTER INDEX \(page 1-1\)"](#)

["CREATE_SECTION_GROUP \(page 8-34\)"](#)

8.15 ADD_STOPTHEME

Adds a single stoptheme to a stoplist. A stoptheme is a theme that is not to be indexed.

In English, query on indexed themes using the [ABOUT \(page 3-4\)](#) operator.

Syntax

```
CTX_DDL.ADD_STOPTHEME(
  stoplist_name      IN   VARCHAR2,
  stoptheme          IN   VARCHAR2
);
```

stoplist_name

Specify the name of the stoplist.

stoptheme

Specify the stoptheme to be added to `stoplist_name`. The system normalizes the stoptheme you enter using the knowledge base. If the normalized theme is more than one theme, then the system does not process your stoptheme. For this reason, Oracle recommends that you submit single stopthemes.

The maximum number of stopwords, stopthemes, and stopclasses you can add to a stoplist is 4095.

Example

The following example adds the stoptheme banking to the stoplist mystop:

```
begin
ctx_ddl.add_stoptheme('mystop', 'banking');
end;
```

Related Topics

["CREATE_STOPLIST \(page 8-39\)"](#)

["REMOVE_STOPTHEME \(page 8-61\)"](#)

["DROP_STOPLIST \(page 8-42\)"](#)

["ABOUT \(page 3-4\)"](#)

8.16 ADD_STOPWORD

Use this procedure to add a single stopword to a stoplist.

To create a list of stopwords, you must call this procedure once for each word.

Syntax

```
CTX_DDL.ADD_STOPWORD(

    stoplist_name      IN VARCHAR2,
    stopword           IN VARCHAR2,
    language           IN VARCHAR2 default NULL,
    language_dependent IN BOOLEAN default TRUE

);
```

stoplist_name

Specify the name of the stoplist.

stopword

Specify the stopword to be added.

Language-specific stopwords must be unique across the other stopwords specific to the language. For example, it is valid to have a German *die* and an English *die* in the same stoplist.

The maximum number of stopwords, stopthemes, and stopclasses you can add to a stoplist is 4095.

language

Specify the language of `stopword` when the stoplist you specify with `stoplist_name` is of type `MULTI_STOPLIST`. You must specify the globalization support name or abbreviation of an Oracle Text-supported language.

To make a stopword active in multiple languages, specify `ALL` for this parameter. For example, defining `ALL` stopwords is useful when you have international documents that contain English fragments that need to be stopped in any language.

An `ALL` stopword is active in all languages. If you use the multi-lexer, the language-specific lexing of the stopword occurs, just as if it had been added multiple times in multiple specific languages.

Otherwise, specify `NULL`.

language_dependent

Set this parameter to `FALSE` to indicate that any user-defined string can be specified for the `language` parameter.

Example

Single Language Stoplist

The following example adds the stopwords *because*, *notwithstanding*, *nonetheless*, and *therefore* to the stoplist `mystop`:

```
begin

ctx_ddl.add_stopword('mystop', 'because');
ctx_ddl.add_stopword('mystop', 'notwithstanding');
ctx_ddl.add_stopword('mystop', 'nonetheless');
ctx_ddl.add_stopword('mystop', 'therefore');

end;
```

Multi-Language Stoplist

The following example adds the German word *die* to a multi-language stoplist:

```
begin

ctx_ddl.add_stopword('mystop', 'Die','german');

end;
```

Note:

Add stopwords after you create the index with ALTER INDEX.

Adding An ALL Stopword

The following adds the word *the* as an ALL stopword to the multi-language stoplist *globallist*:

```
begin

ctx_ddl.add_stopword('globallist','the','ALL');

end;
```

Related Topics

["CREATE_STOPLIST \(page 8-39\)"](#)

["REMOVE_STOPWORD \(page 8-62\)"](#)

["DROP_STOPLIST \(page 8-42\)"](#)

["ALTER INDEX \(page 1-1\)"](#)

[Oracle Text Supplied Stoplists \(page E-1\)](#)

8.17 ADD_SUB_LEXER

Adds a sub-lexer to a multi-lexer preference. A sub-lexer identifies a language in a multi-lexer (multi-language) preference. Use a multi-lexer preference when you want to index more than one language.

Syntax

```
CTX_DDL.ADD_SUB_LEXER(
    lexer_name          IN VARCHAR2,
    language            IN VARCHAR2,
    sub_lexer           IN VARCHAR2,
    alt_value           IN VARCHAR2 default NULL,
```

```
language_dependent IN BOOLEAN default TRUE
);
```

lexer_name

Specify the name of the multi-lexer preference.

language

Specify the globalization support language name or abbreviation of the sub-lexer. For example, specify JAPANESE or JA for Japanese.

The sub-lexer you specify with `sub_lexer` is used when the language column has a value case-insensitive equal to the globalization support name or abbreviation of language.

Specify `DEFAULT` to assign a default sub-lexer to use when the value of the language column in the base table is null, invalid, or unmapped to a sub-lexer. The `DEFAULT` lexer is also used to parse stopwords.

If a sub-lexer definition for language already exists, then it is replaced by this call.

sub_lexer

Specify the name of the sub-lexer to use for this language.

alt_value

Optionally specify an alternate value for language.

If you specify `DEFAULT` for language, then you cannot specify an `alt_value`.

The `alt_value` is limited to 30 bytes and cannot be a globalization support language name, abbreviation, or `DEFAULT`.

language_dependent

Set this parameter to `FALSE` to indicate that any user-defined string can be specified for the language parameter. If set to `FALSE`, then the lexing applied to the search expression will not be dependent on the query language. The `FALSE` option can only be used when a `BASIC_SECTION_GROUP` is in use for the index.

Example

This example shows how to create a multi-language text table and how to set up the multi-lexer to index the table.

Create the multi-language table with a primary key, a text column, and a language column as follows:

```
create table globaldoc (
  doc_id number primary key,
  lang varchar2(3),
  text clob
);
```

Assume that the table holds mostly English documents, with an occasional German or Japanese document. To handle the three languages, you must create three sub-lexers: one for English, one for German, and one for Japanese as follows:

```
ctx_ddl.create_preference('english_lexer','basic_lexer');
ctx_ddl.set_attribute('english_lexer','index_themes','yes');
ctx_ddl.set_attribute('english_lexer','theme_language','english');

ctx_ddl.create_preference('german_lexer','basic_lexer');
```

```
ctx_ddl.set_attribute('german_lexer','composite','german');
ctx_ddl.set_attribute('german_lexer','mixed_case','yes');
ctx_ddl.set_attribute('german_lexer','alternate_spelling','german');

ctx_ddl.create_preference('japanese_lexer','japanese_vgram_lexer');
```

Create the multi-lexer preference:

```
ctx_ddl.create_preference('global_lexer','multi_lexer');
```

Because the stored documents are mostly English, make the English lexer the default:

```
ctx_ddl.add_sub_lexer('global_lexer','default','english_lexer');
```

Add the German and Japanese lexers in their respective languages. Also assume that the language column is expressed in ISO 639-2, so add those as alternative values.

```
ctx_ddl.add_sub_lexer('global_lexer','german','german_lexer','ger');
ctx_ddl.add_sub_lexer('global_lexer','japanese','japanese_lexer','jpn');
```

Create the index `globalx`, specifying the multi-lexer preference and the language column in the parameters string as follows:

```
create index globalx on globaldoc(text) indextype is ctxsys.context
parameters ('lexer global_lexer language column lang');
```

You can specify a user-defined string for the language parameter as follows:

```
ctx_ddl.add_sub_lexer('global_lexer','mysymbol','german_lexer','my_alt_symbol',
language_dependent => FALSE);
```

Restrictions

The following restrictions apply to using `CTX_DDL.ADD_SUB_LEXER`:

- The invoking user must be the owner of the multi-lexer or `CTXSYS`.
- The `lexer_name` parameter must name a preference which is a multi-lexer lexer.
- A lexer for default must be defined before the multi-lexer can be used in an index.
- The sub-lexer preference owner must be the same as multi-lexer preference owner.
- The sub-lexer preference must not be a multi-lexer lexer.
- A sub-lexer preference cannot be dropped while it is being used in a multi-lexer preference.
- `CTX_DDL.ADD_SUB_LEXER` records only a reference. The sub-lexer values are copied at create index time to index value storage.

8.18 ADD_ZONE_SECTION

Creates a zone section and adds the section to an existing section group. This enables zone section searching with the [WITHIN](#) (page 3-54) operator.

Zone sections are sections delimited by start and end tags. The `` and `` tags in HTML, for instance, marks a range of words which are to be rendered in boldface.

Zone sections can be nested within one another, can overlap, and can occur more than once in a document.

Syntax

```
CTX_DDL.ADD_ZONE_SECTION(
  group_name      IN   VARCHAR2,
  section_name    IN   VARCHAR2,
  tag             IN   VARCHAR2
);
```

group_name

Specify the name of the section group to which `section_name` is added.

section_name

Specify the name of the section to add to the `group_name`. Use this name to identify the section in `WITHIN` queries. Avoid using names that contain non-alphanumeric characters such as `_`, because most of these characters are special must be escaped in queries. Section names are case-insensitive.

Within the same group, zone section names and field section names cannot be the same. The terms *Paragraph* and *Sentence* are reserved for special sections.

Section names need not be unique across tags. You can assign the same section name to more than one tag, making details transparent to searches.

tag

Specify the pattern which marks the start of a section. For example, if `<H1>` is the HTML tag, specify `H1` for `tag`. The start tag you specify must be unique within a section group.

Oracle Text knows what the end tags look like from the `group_type` parameter you specify when you create the section group.

If `group_name` is an `HTML_SECTION_GROUP`, you can create zone sections for the `META` tag's `NAME/CONTENT` attribute pairs. To do so, specify `tag` as `meta@namevalue` where `namevalue` is the value of the `NAME` attribute whose `CONTENT` attributes are to be indexed as a section. Refer to the example.

If `group_name` is an `XML_SECTION_GROUP`, you can optionally qualify `tag` with a document type (root element) in the form `(doctype)tag`. Doing so makes `section_name` sensitive to the XML document type declaration. Refer to the example.

Examples

Creating HTML Sections

The following example defines a section group called `htmgroup` of type `HTML_SECTION_GROUP`. It then creates a zone section in `htmgroup` called `headline` identified by the `<H1>` tag:

```
begin
  ctx_ddl.create_section_group('htmgroup', 'HTML_SECTION_GROUP');
  ctx_ddl.add_zone_section('htmgroup', 'heading', 'H1');
end;
```

After indexing with section group `htmgroup`, query within the heading section by issuing a query as follows:

```
'Oracle WITHIN heading'
```

Creating Sections for <META NAME> Tags

You can create zone sections for HTML META tags when you use the `HTML_SECTION_GROUP`.

Consider an HTML document that has a META tag as follows:

```
<META NAME="author" CONTENT="ken">
```

To create a zone section that indexes all `CONTENT` attributes for the META tag whose `NAME` value is `author`:

```
begin
ctx_ddl.create_section_group('htmgroup', 'HTML_SECTION_GROUP');
ctx_ddl.add_zone_section('htmgroup', 'author', 'meta@author');
end
```

After indexing with section group `htmgroup`, query the document as follows:

```
'ken WITHIN author'
```

Creating Document Type Sensitive Sections (XML Documents Only)

You have an XML document set that contains the `<book>` tag declared for different document types (DTDs). You want to create a distinct book section for each document type.

Assume that `myDTDname` is declared as an XML document type as follows:

```
<!DOCTYPE myDTDname>
<myDTDname>
...

```

(Note: the `DOCTYPE` must match the top-level tag.)

Within `myDTDname`, the element `<book>` is declared. For this tag, create a section named `mybooksec` that is sensitive to the tag's document type as follows:

```
begin
ctx_ddl.create_section_group('myxmlgroup', 'XML_SECTION_GROUP');
ctx_ddl.add_zone_section('myxmlgroup', 'mybooksec', '(myDTDname)book');
end;
```

Notes

Repeated Sections

Zone sections can repeat. Each occurrence is treated as a separate section. For example, if `<H1>` denotes a heading section, they can repeat in the same documents as follows:

```
<H1> The Brown Fox </H1>
```

```
<H1> The Gray Wolf </H1>
```

Assuming that these zone sections are named `Heading`, the query *Brown WITHIN Heading* returns this document. However, a query of *(Brown and Gray) WITHIN Heading* does not.

Overlapping Sections

Zone sections can overlap each other. For example, if `` and `<I>` denote two different zone sections, they can overlap in document as follows:

```
plain <B> bold <I> bold and italic </B> only italic </I> plain
```

Nested Sections

Zone sections can nest, including themselves as follows:

```
<TD> <TABLE><TD>nested cell</TD></TABLE></TD>
```

Using the WITHIN operator, you can write queries to search for text in sections within sections. For example, assume the BOOK1, BOOK2, and AUTHOR zone sections occur as follows in documents doc1 and doc2:

doc1:

```
<book1> <author>Scott Tiger</author> This is a cool book to read.</book1>
```

doc2:

```
<book2> <author>Scott Tiger</author> This is a great book to read.</book2>
```

Consider the nested query:

```
'(Scott within author) within book1'
```

This query returns only doc1.

Related Topics

["WITHIN \(page 3-54\)"](#)

["Section Group Types \(page 2-86\)"](#)

["CREATE_SECTION_GROUP \(page 8-34\)"](#)

["ADD_FIELD_SECTION \(page 8-5\)"](#)

["ADD_SPECIAL_SECTION \(page 8-18\)"](#)

["REMOVE_SECTION \(page 8-60\)"](#)

["DROP_SECTION_GROUP \(page 8-41\)"](#)

8.19 COPY_POLICY

Creates a new policy from an existing policy or index.

Syntax

```
ctx_ddl.copy_policy(
    source_policy    VARCHAR2,
    policy_name      VARCHAR2    );
```

source_policy

The name of the policy or index being copied.

policy_name

The name of the new policy copy.

The preference values are copied from the `source_policy`. Both the source policy or index and the new policy must be owned by the same database user.

8.20 CREATE_INDEX_SET

Creates an index set for CTXCAT index types. Name this index set in the parameter clause of CREATE INDEX when you create a CTXCAT index.

Syntax

```
CTX_DDL.CREATE_INDEX_SET(set_name in varchar2);
```

set_name

Specify the name of the index set. Name this index set in the parameter clause of `CREATE INDEX` when you create a CTXCAT index.

8.21 CREATE_POLICY

Creates a policy to use with the `CTX_DOC.POLICY_*` procedures and the `ORA:CONTAINS` function. `ORA:CONTAINS` is a function you use within an XPATH query expression with `existsNode()`.

See Also:

Oracle XML DB Developer's Guide

Syntax

```
CTX_DDL.CREATE_POLICY(  
    policy_name      IN VARCHAR2,  
    filter           IN VARCHAR2 DEFAULT NULL,  
    section_group    IN VARCHAR2 DEFAULT NULL,  
    lexer            IN VARCHAR2 DEFAULT NULL,  
    stoplist         IN VARCHAR2 DEFAULT NULL,  
    wordlist         IN VARCHAR2 DEFAULT NULL);
```

policy_name

Specify the name for the new policy. Policy names and Text indexes share the same namespace.

filter

Specify the filter preference to use.

section_group

Specify the section group to use. You can specify any section group that is supported by `CONTEXT` index.

lexer

Specify the lexer preference to use. Your `INDEX_THEMES` attribute must be disabled.

stoplist

Specify the stoplist to use.

wordlist

Specify the wordlist to use.

Example

Create mylex lexer preference named mylex.

```
begin  
    ctx_ddl.create_preference('mylex', 'BASIC_LEXER');  
    ctx_ddl.set_attribute('mylex', 'printjoins', '_-');
```



```

    ctx_ddl.set_attribute ( 'mylex', 'index_themes', 'NO');
    ctx_ddl.set_attribute ( 'mylex', 'index_text', 'YES');
end;

```

Create a stoplist preference named mystop.

```

begin
    ctx_ddl.create_stoplist('mystop', 'BASIC_STOPLIST');
    ctx_ddl.add_stopword('mystop', 'because');
    ctx_ddl.add_stopword('mystop', 'nonetheless');
    ctx_ddl.add_stopword('mystop', 'therefore');
end;

```

Create a wordlist preference named 'mywordlist'.

```

begin
    ctx_ddl.create_preference('mywordlist', 'BASIC_WORDLIST');
    ctx_ddl.set_attribute('mywordlist', 'FUZZY_MATCH', 'ENGLISH');
    ctx_ddl.set_attribute('mywordlist', 'FUZZY_SCORE', '0');
    ctx_ddl.set_attribute('mywordlist', 'FUZZY_NUMRESULTS', '5000');
    ctx_ddl.set_attribute('mywordlist', 'SUBSTRING_INDEX', 'TRUE');
    ctx_ddl.set_attribute('mywordlist', 'STEMMER', 'ENGLISH');
end;

```

```

exec ctx_ddl.create_policy('my_policy', NULL, NULL, 'mylex', 'mystop',
'mywordlist');

```

or

```

exec ctx_ddl.create_policy(policy_name => 'my_policy',
                           lexer => 'mylex',
                           stoplist => 'mystop',
                           wordlist => 'mywordlist');

```

Then enter the following existsNode() query with your own defined policy:

```

select id from xmltab
  where existsNode(doc, '/book/chapter[ ora:contains(summary,"dog or cat",
"my_policy") >0 ]', 'xmlns:ora="http://xmlns.example.com/xdb" ')=1;

```

Update the policy with the following:

```

exec ctx_ddl.update_policy(policy_name => 'my_policy', lexer => 'my_new_lex');

```

Drop the policy with the following:

```

exec ctx_ddl.drop_policy(policy_name => 'my_policy');

```

8.22 CREATE_PREFERENCE

Creates a preference in the Text data dictionary. Specify preferences in the parameter string of [CREATE INDEX](#) (page 1-40) or [ALTER INDEX](#) (page 1-1).

Caution:

CTX_DDL.CREATE_PREFERENCE does not respect the current schema as set by ALTER SESSION SET current_schema. Therefore, if you need to create or delete a preference owned by another user, then you must explicitly state this, and you must have the CREATE ANY TABLE system privilege.

See note 249991.1 titled "Oracle Text Overview of New Features in Release 10g" on My Oracle Support at <https://support.oracle.com>. This note provides a technical overview that is relevant to Oracle Database release 10g and later releases.

Syntax

```
CTX_DDL.CREATE_PREFERENCE(preference_name in varchar2,  
                           object_name     in varchar2);
```

preference_name

Specify the name of the preference to be created.

object_name

Specify the name of the preference type.

See Also:

For a complete list of preference types and their associated attributes, see [Oracle Text Indexing Elements](#) (page 2-1)

Examples**Creating Text-only Index**

The following example creates a lexer preference that specifies a text-only index. It does so by creating a BASIC_LEXER preference called my_lexer with CTX_DDL.CREATE_PREFERENCE. It then calls CTX_DDL.SET_ATTRIBUTE (page 8-64) twice, first specifying YES for the INDEX_TEXT attribute, then specifying NO for the INDEX_THEMES attribute.

```
begin  
ctx_ddl.create_preference('my_lexer', 'BASIC_LEXER');  
ctx_ddl.set_attribute('my_lexer', 'INDEX_TEXT', 'YES');  
ctx_ddl.set_attribute('my_lexer', 'INDEX_THEMES', 'NO');  
end;
```

Specifying File Data Storage

The following example creates a data storage preference called mypref that tells the system that the files to be indexed are stored in the operating system. The example then uses CTX_DDL.SET_ATTRIBUTE (page 8-64) to set the PATH attribute of to the directory /docs.

```
begin  
ctx_ddl.create_preference('mypref', 'FILE_DATASTORE');  
ctx_ddl.set_attribute('mypref', 'PATH', '/docs');  
end;
```

See Also:

For more information about data storage, see "[Datastore Types](#) (page 2-2)"

Creating Master/Detail Relationship

Use CTX_DDL.[CREATE_PREFERENCE](#) (page 8-31) to create a preference with `DETAIL_DATASTORE`. Use CTX_DDL.[SET_ATTRIBUTE](#) (page 8-64) to set the attributes for this preference. The following example shows how this is done:

```
begin
ctx_ddl.create_preference('my_detail_pref', 'DETAIL_DATASTORE');
ctx_ddl.set_attribute('my_detail_pref', 'binary', 'true');
ctx_ddl.set_attribute('my_detail_pref', 'detail_table', 'my_detail');
ctx_ddl.set_attribute('my_detail_pref', 'detail_key', 'article_id');
ctx_ddl.set_attribute('my_detail_pref', 'detail_lineno', 'seq');
ctx_ddl.set_attribute('my_detail_pref', 'detail_text', 'text');
end;
```

See Also:

For more information about master/detail, see "[DETAIL_DATASTORE](#) (page 2-7)"

Specifying Storage Attributes

The following examples specify that the index tables are to be created in the `foo` tablespace with an initial extent of 1K:

```
begin
ctx_ddl.create_preference('mystore', 'BASIC_STORAGE');
ctx_ddl.set_attribute('mystore', 'I_TABLE_CLAUSE',
                    'tablespace foo storage (initial 1K)');
ctx_ddl.set_attribute('mystore', 'K_TABLE_CLAUSE',
                    'tablespace foo storage (initial 1K)');
ctx_ddl.set_attribute('mystore', 'R_TABLE_CLAUSE',
                    'tablespace foo storage (initial 1K)');
ctx_ddl.set_attribute('mystore', 'S_TABLE_CLAUSE',
                    'tablespace foo storage (initial 1K)');
ctx_ddl.set_attribute('mystore', 'N_TABLE_CLAUSE',
                    'tablespace foo storage (initial 1K)');
ctx_ddl.set_attribute('mystore', 'I_INDEX_CLAUSE',
                    'tablespace foo storage (initial 1K)');
end;
```

Note:

If `S_TABLE_CLAUSE` is specified for a storage preference in an index without `SDATA`, then it has no effect on the index, and the index creation will still succeed.

See Also:

[Storage Types](#) (page 2-80)

Creating Preferences with No Attributes

When you create preferences with types that have no attributes, you need only create the preference, as in the following example which sets the filter to the `NULL_FILTER`:

```
begin
ctx_ddl.create_preference('my_null_filter', 'NULL_FILTER');
end;
```

Specifying BIGRAM Mode for Japanese VGRAM Lexer

The following example creates a Japanese VGRAM lexer preference that specifies the BIGRAM mode of operation for the Japanese queries:

```
begin
ctx_ddl.create_preference('jp_lexer', 'JAPANESE_VGRAM_LEXER');
ctx_ddl.set_attribute('jp_lexer', 'BIGRAM', 'TRUE');
end;

/* create the index */
create index jp_idx on jp_doc(text) indextype is ctxsys.context
  parameters('lexer jp_lexer');
```

Related Topics

["SET_ATTRIBUTE \(page 8-64\)"](#)

["DROP_PREFERENCE \(page 8-41\)"](#)

["CREATE INDEX \(page 1-40\)"](#)

["ALTER INDEX \(page 1-1\)"](#)

[Oracle Text Indexing Elements \(page 2-1\)](#)

8.23 CREATE_SECTION_GROUP

Creates a section group for defining sections in a text column.

When you create a section group, you can add to it zone, field, or special sections with [ADD_ZONE_SECTION \(page 8-26\)](#), [ADD_FIELD_SECTION \(page 8-5\)](#), [ADD_MDATA_SECTION \(page 8-12\)](#), or [ADD_SPECIAL_SECTION \(page 8-18\)](#).

You also use `CREATE_SECTION_GROUP` with `CTX_DDL.SET_SEC_GRP_ATTR` (page 8-65) to set `xml_enable` to create an Oracle XML Search Index.

When you index, name the section group in the parameter string of [CREATE INDEX \(page 1-40\)](#) or [ALTER INDEX \(page 1-1\)](#).

After indexing, query within your defined sections with the [WITHIN \(page 3-54\)](#) operator.

Syntax

```
CTX_DDL.CREATE_SECTION_GROUP(
  group_name      in   varchar2,
  group_type      in   varchar2
);
```

group_name

Specify the section group name to create as `[user.]section_group_name`. This parameter must be unique within an owner.

group_type

Specify section group type. The `group_type` parameter can be one of the following:

Section Group Preference	Description
<code>NULL_SECTION_GROUP</code>	Use this group type when you define no sections or when you define <i>only</i> SENTENCE or PARAGRAPH sections. This is the default.
<code>BASIC_SECTION_GROUP</code>	Use this group type for defining sections where the start and end tags are of the form <code><A></code> and <code></code> . Note: This group type does not support input such as unbalanced parentheses, comments tags, and attributes. Use <code>HTML_SECTION_GROUP</code> for this type of input.
<code>HTML_SECTION_GROUP</code>	Use this group type for indexing HTML documents and for defining sections in HTML documents.
<code>JSON_SECTION_GROUP</code>	Use this group to create a JSON enabled context index. The <code>JSON_ENABLE</code> attribute cannot be used with <code>XML_ENABLE</code> . A section group can only be marked as <code>JSON_ENABLE</code> . If it is already marked with <code>XML_ENABLE</code> , then the path section group cannot be used for <code>JSON_ENABLE</code> and vice versa.
<code>XML_SECTION_GROUP</code>	Use this group type for indexing XML documents and for defining sections in XML documents.
<code>AUTO_SECTION_GROUP</code>	Use this group type to automatically create a zone section for each start-tag/end-tag pair in an XML document. The section names derived from XML tags are case sensitive as in XML. Attribute sections are created automatically for XML tags that have attributes. Attribute sections are named in the form <code>attribute@tag</code> . Stop sections, empty tags, processing instructions, and comments are not indexed. The following limitations apply to automatic section groups: <ul style="list-style-type: none"> You cannot add zone, field, or special sections to an automatic section group. Automatic sectioning does not index XML document types (root elements.) However, you can define stop sections with document type. The length of the indexed tags, including prefix and namespace, cannot exceed 64 bytes. Tags longer than this are not indexed.

Section Group Preference	Description
PATH_SECTION_GROUP	Use this group type to index XML documents. Behaves like the AUTO_SECTION_GROUP. The difference is that with this section group you can do path searching with the INPATH and HASPATH operators. Queries are also case-sensitive for tag and attribute names.
NEWS_SECTION_GROUP	Use this group for defining sections in newsgroup formatted documents according to RFC 1036.

Examples

The following command creates a section group called `htmgroup` with the HTML group type.

```
begin

ctx_ddl.create_section_group('htmgroup', 'HTML_SECTION_GROUP');

end;
```

The following command creates a section group called `auto` with the `AUTO_SECTION_GROUP` group type to be used to automatically index tags in XML documents.

```
begin

ctx_ddl.create_section_group('auto', 'AUTO_SECTION_GROUP');

end;
```

The following example creates an Oracle XML Search index:

```
exec CTX_DDL.CREATE_SECTION_GROUP('secgroup', 'PATH_SECTION_GROUP');
exec CTX_DDL.SET_SEC_GRP_ATTR('secgroup', 'xml_enable', 't');
CREATE INDEX po_ctx_idx on T(X) indextype is ctxsys.context
parameters ('section group SECGRP');
```

Related Topics

["WITHIN \(page 3-54\)"](#)

["Section Group Types \(page 2-86\)"](#)

["ADD_ZONE_SECTION \(page 8-26\)"](#)

["ADD_FIELD_SECTION \(page 8-5\)"](#)

["ADD_MDATA_SECTION \(page 8-12\)"](#)

["ADD_SPECIAL_SECTION \(page 8-18\)"](#)

["REMOVE_SECTION \(page 8-60\)"](#)

["DROP_SECTION_GROUP \(page 8-41\)"](#)

8.24 CREATE_SHADOW_INDEX

Creates index metadata (or policy) for the specified index. If the index is not partitioned, then it also creates the index tables. This procedure is only supported in Enterprise Edition of Oracle Database.

The following changes are not supported:

- Transition from non-composite domain index to composite, or changing the composite domain index columns.
- Rebuild indexes that have partitioned index tables, for example, \$I, \$P, \$K.

Note:

For a partitioned index, you must first call this procedure to create the shadow index metadata. This procedure will not create index tables. It has no effect on query, DML, sync, or optimize operations.

Syntax

```
CTX_DDL.CREATE_SHADOW_INDEX(
    idx_name          IN VARCHAR2,
    parameter_string  IN VARCHAR2 DEFAULT NULL,
    parallel_degree    IN NUMBER DEFAULT 1
);
```

idx_name

The name of a valid CONTEXT indextype.

parameter_string

For nonpartitioned index, the same string as in ALTER INDEX. For partitioned index, the same string as in ALTER INDEX PARAMETER.

parallel_degree

Reserved for future use. Specify the degree of parallelism. Parallel operation is not currently supported.

Example

Example 8-1 Scheduled Global Index RECREATE (Incremental Rebuild)

In this example, you have the finest control over each stage of [RECREATE_INDEX_ONLINE](#) (page 8-51). Since SYNC_INDEX can take a time limit, you can limit SYNC_INDEX during non-business hours and incrementally recreate the index.

```
/* create lexer and original index */
exec ctx_ddl.create_preference('us_lexer','basic_lexer');
create index idx on tbl(text) indextype is ctxsys.context
    parameters('lexer us_lexer');

/* create a new lexer */
begin
    ctx_ddl.create_preference('e_lexer','basic_lexer');
    ctx_ddl.set_attribute('e_lexer','base_letter','yes');
```

```
ctx_ddl.create_preference('m_lexer','multi_lexer');
ctx_ddl.add_sub_lexer('m_lexer','default','us_lexer');
ctx_ddl.add_sub_lexer('m_lexer','e','e_lexer');
end;
/

/* add new language column to the table for multi-lexer */
alter table tbl add(lang varchar2(10) default 'us');

/* create shadow index */
exec ctx_ddl.create_shadow_index('idx',
    'replace lexer m_lexer language column lang NOPOPULATE');

declare
    idxid integer;
begin
    /* figure out shadow index name */
    select idx_id into idxid from ctx_user_indexes
        where idx_name = 'IDX';
    /* populate pending */
    ctx_ddl.populate_pending('RIO$'||idxid);
    /* time limited sync */
    ctx_ddl.sync_index(idx_name => 'RIO$'||idxid,
        maxtime => 480);
    /* more sync until no pending rows for the shadow index */
end;
/* swap in the shadow index */
exec ctx_ddl.exchange_shadow_index('idx');
```

Notes

The index name for the shadow index is `RIO$index_id`. By default it will also populate index tables for nonpartitioned indexes, unless `NOPOPULATE` is specified in `CREATE INDEX` or in `ALTER INDEX`. For a local partitioned index, it will only create index metadata without creating the index tables for each partition. Each index can have only one shadow index.

When building a nonpartitioned index online, you can first call this procedure to create index metadata and index tables. If you specify `POPULATE`, then this procedure will populate the index, but will not do swapping. You can schedule the swapping at a later, preferred time.

If you specify `NOPOPULATE`, it will only create metadata for the index tables, but will not populate them. You must perform `POPULATE_PENDING` (`CTX_DDL.POPULATE_PENDING` (page 8-50)) to populate the pending queues after running this procedure, and then sync the indexes. This is referred to as *incremental re-create*.

Queries are all processed normally when this procedure is running.

If `POPULATE` is specified, then DML is blocked for a very short time at the beginning of populate, after which all further DML is logged into an online pending queue and processed later.

Sync with `CTX_DDL.SYNC_INDEX` (page 8-68) runs normally on the index. `OPTIMIZE_INDEX` (page 8-44) runs without doing anything, but does not return an error.

Related Topics

`POPULATE` | `NOPOPULATE` in `ALTER INDEX` (page 1-1)

[CREATE INDEX](#) (page 1-40) in [Oracle Text SQL Statements and Operators](#) (page 1-1)

CTX_DDL.[DROP_SHADOW_INDEX](#) (page 8-42)

CTX_DDL.[EXCHANGE_SHADOW_INDEX](#) (page 8-43)

CTX_DDL.[SYNC_INDEX](#) (page 8-68)

CTX_DDL.[POPULATE_PENDING](#) (page 8-50)

8.25 CREATE_STOPLIST

Use this procedure to create a new, empty stoplist. Stoplists can contain words or themes that are not to be indexed.

You can also create multi-language stoplists to hold language-specific stopwords. A multi-language stoplist is useful when you index a table that contains documents in different languages, such as English, German, and Japanese. When you do so, the text table must contain a language column.

Add either stopwords, stopclasses, or stopthemes to a stoplist using [ADD_STOPWORD](#) (page 8-23), [ADD_STOPCLASS](#) (page 8-19), or [ADD_STOPTHEME](#) (page 8-22). Specify a stoplist in the parameter string of [CREATE INDEX](#) (page 1-40) or [ALTER INDEX](#) (page 1-1) to override the default stoplist CTXSYS.DEFAULT_STOPLIST.

Syntax

```
CTX_DDL.CREATE_STOPLIST(  
  
  stoplist_name IN VARCHAR2,  
  stoplist_type IN VARCHAR2 DEFAULT 'BASIC_STOPLIST');
```

stoplist_name

Specify the name of the stoplist to be created.

stoplist_type

Specify BASIC_STOPLIST to create a stoplist for a single language. This is the default.

Specify MULTI_STOPLIST to create a stoplist with language-specific stopwords.

At indexing time, the language column of each document is examined, and only the stopwords for that language are eliminated. At query time, the session language setting determines the active stopwords, like it determines the active lexer when using the multi-lexer.

Note:

When indexing a multi-language table with a multi-language stoplist, the table must have a language column.

Examples

Example 8-2 Single Language Stoplist

The following example creates a stoplist called mystop:

```
begin
ctx_ddl.create_stoplist('mystop', 'BASIC_STOPLIST');
end;
```

Example 8-3 Multi-Language Stoplist

The following example creates a multi-language stoplist called `multistop` and then adds two language-specific stopwords:

```
begin
ctx_ddl.create_stoplist('multistop', 'MULTI_STOPLIST');
ctx_ddl.add_stopword('mystop', 'Die', 'german');
ctx_ddl.add_stopword('mystop', 'Or', 'english');
end;
```

Related Topics

["ADD_STOPWORD \(page 8-23\)"](#)

["ADD_STOPCLASS \(page 8-19\)"](#)

["ADD_STOPTHEME \(page 8-22\)"](#)

["DROP_STOPLIST \(page 8-42\)"](#)

["CREATE INDEX \(page 1-40\)"](#)

["ALTER INDEX \(page 1-1\)"](#)

[Oracle Text Supplied Stoplists \(page E-1\)](#)

8.26 DROP_INDEX_SET

Drops a CTXCAT index set created with CTX_DDL.[CREATE_INDEX_SET](#) (page 8-29).

Syntax

```
CTX_DDL.DROP_INDEX_SET(
    set_name    IN VARCHAR2
);
```

set_name

Specify the name of the index set to drop.

Dropping an index set drops all of the sub-indexes it contains.

8.27 DROP_POLICY

Drops a policy created with CTX_DDL.[CREATE_POLICY](#) (page 8-30).

Syntax

```
CTX_DDL.DROP_POLICY(
    policy_name  IN VARCHAR2
);
```

policy_name

Specify the name of the policy to drop.

8.28 DROP_PREFERENCE

The `DROP_PREFERENCE` procedure deletes the specified preference from the Text data dictionary. Dropping a preference does not affect indexes that have already been created using that preference.

Syntax

```
CTX_DDL.DROP_PREFERENCE(  
    preference_name    IN VARCHAR2  
);
```

preference_name

Specify the name of the preference to be dropped.

Example

The following example drops the preference `my_lexer`.

```
begin  
ctx_ddl.drop_preference('my_lexer');  
end;
```

Related Topics

CTX_DDL.[CREATE_PREFERENCE](#) (page 8-31)

8.29 DROP_SECTION_GROUP

The `DROP_SECTION_GROUP` procedure deletes the specified section group, as well as all the sections in the group, from the Text data dictionary.

Syntax

```
CTX_DDL.DROP_SECTION_GROUP(  
    group_name        IN VARCHAR2  
);
```

group_name

Specify the name of the section group to delete.

Example

The following example drops the section group `htmgroup` and all its sections:

```
begin  
ctx_ddl.drop_section_group('htmgroup');  
end;
```

Related Topics

["CREATE_SECTION_GROUP](#) (page 8-34)"

["PREFERENCE_IMPLICIT_COMMIT](#) (page 8-50)"

8.30 DROP_SHADOW_INDEX

Drops a shadow index for the specified index. When you drop a shadow index, if it is partitioned, then its metadata and the metadata of all this shadow index's partitions are dropped. This procedure also drops all the shadow index tables and cleans up any online pending queue.

Syntax

```
CTX_DDL.DROP_SHADOW_INDEX(  
    idx_name          in VARCHAR2  
);
```

idx_name

The name of a valid CONTEXT indextype.

Example

The following example drops the shadow index myshadowidx:

```
begin  
ctx_ddl.drop_shadow_index('myshadowidx');  
end;
```

Related Topics

CTX_DDL.[CREATE_SHADOW_INDEX](#) (page 8-37)

8.31 DROP_STOPLIST

Drops a stoplist from the Text data dictionary. When you drop a stoplist, you must re-create or rebuild the index for the change to take effect.

Syntax

```
CTX_DDL.DROP_STOPLIST(stoplist_name in varchar2);
```

stoplist_name

Specify the name of the stoplist.

Example

The following example drops the stoplist mystop:

```
begin  
ctx_ddl.drop_stoplist('mystop');  
end;
```

Related Topics

CTX_DDL.[CREATE_STOPLIST](#) (page 8-39)

8.32 EXCHANGE_SHADOW_INDEX

This procedure swaps the index (or index partition) metadata and index (or index partition) data.

For nonpartitioned indexes, this procedure swaps both the metadata and the index data, and processes the online pending queue.

Syntax

```
CTX_DDL.EXCHANGE_SHADOW_INDEX(
    idx_name          IN VARCHAR2
    partition_name    IN VARCHAR2 default NULL
);
```

idx_name

Specify the name of the CONTEXT indextype.

partition_name

Specify the name of the shadow index partition. May also be NULL.

Example

Example 8-4 Global Index RECREATE with Scheduled Swap

This example demonstrates running CTX_DDL.EXCHANGE_SHADOW_INDEX during non-business hours when query failures and DML blocking can be tolerated.

```
/* create lexer and original index */
exec ctx_ddl.create_preference('us_lexer','basic_lexer');
create index idx on tbl(text) indextype is ctxsys.context
    parameters('lexer us_lexer');

/* create a new lexer */
begin
    ctx_ddl.create_preference('e_lexer','basic_lexer');
    ctx_ddl.set_attribute('e_lexer','base_letter','yes');
    ctx_ddl.create_preference('m_lexer','multi_lexer');
    ctx_ddl.add_sub_lexer('m_lexer','default','us_lexer');
    ctx_ddl.add_sub_lexer('m_lexer','e','e_lexer');
end;
/

/* add new language column to the table for multi-lexer */
alter table tbl add(lang varchar2(10) default 'us');

/* recreate index online with the new multip-lexer */
exec ctx_ddl.create_shadow_index('idx',
    'replace lexer m_lexer language column lang');
exec ctx_ddl.exchange_shadow_index('idx');
```

Notes

Using EXCHANGE_SHADOW_INDEX with Nonpartitioned Indexes

For nonpartitioned indexes, this procedure will swap both metadata and index data, and will process the online pending queue.

Queries will return *column not indexed* errors when swapping metadata and index data, but queries are processed normally when processing online pending queue. The period of errors being raised should be short.

If you specify `POPULATE` when you create the shadow index, and if many DML operations have been issued since the creation of the shadow index, then there could be a large pending queue. However, if you use *incremental recreate*, that is, specify `NOPOPULATE` when you create the shadow index, and you then populate the pending queue and sync, then the online pending queue is always empty no matter how many DML operations have occurred since `CREATE_SHADOW_INDEX` was issued.

When this procedure is running, DML will first fail with an error about index being in in-progress status. After that DML could be blocked (hang) if there are rows in online pending queue that need to be reapplied.

Note:

When this procedure is running, DML statements will fail with an error that the index is in "in-progress status." If, when this error occurs, there are rows in the online pending queue that need to be reapplied, then the DML could be blocked and hang.

Using `EXCHANGE_SHADOW_INDEX` with Partitioned Indexes

For partitions that are recreated with `NOSWAP`: when the index is partitioned, and if *partition_name* is a valid index partition, then this procedure will swap the index partition data and the index partition metadata, and will process the online pending queue for this partition.

This procedure swaps only one partition at a time. When you run this procedure on partitions that are recreated with `NOSWAP`:

- Queries that span multiple partitions will not return consistent results across all partitions.
- Queries on the partition that is being swapped will return errors.
- Queries on partitions that are already swapped will be based on the new index.
- Queries on the partitions that haven't been swapped will be based on the old index.

If the *partition_name* is `NULL`, then this procedure will swap the index metadata. Run this procedure as the last step when recreating a local partitioned index online.

Related Topics

CTX_DDL."[RECREATE_INDEX_ONLINE](#) (page 8-51)"

CTX_DDL."[CREATE_SHADOW_INDEX](#) (page 8-37)"

CTX_DDL."[DROP_SHADOW_INDEX](#) (page 8-42)"

8.33 OPTIMIZE_INDEX

Use this procedure to optimize the index. Optimize your index after you synchronize it. Optimizing an index removes old data and minimizes index fragmentation, which

can improve query response time. Querying and DML may proceed while optimization takes place.

You can optimize in fast, full, rebuild, token, token-type, or merge mode.

- Fast mode compacts data but does not remove rows.
- Full mode compacts data and removes rows.
- Optimize in rebuild mode rebuilds the \$I table (the inverted list table) in its entirety. Rebuilding an index is often significantly faster than performing a full optimization, and is more likely to result in smaller indexes, especially if the index is heavily fragmented.

Rebuild optimization creates a more compact copy of the \$I table, and then switches the original \$I table and the copy. The rebuild operation will therefore require enough space to store the copy as well as the original. (If redo logging is enabled, then additional space is required in the redo log as well.) At the end of the rebuild operation, the original \$I table is dropped, and the space can be reused. A temporary "change capture trigger" is used to ensure that updates to the \$I table during the optimization are not lost. For this reason, the user calling OPTIMIZE_INDEX in REBUILD mode must have the CREATE TRIGGER privilege.

Optimize in rebuild mode supports partitioning on the \$I table via the `i_table_clause` attribute of the `basic_storage` preference with the following limitations:

- The `i_index_clause` must specify using a local btree index if the \$I table is partitioned.
- Partitioning schemes on the `token_first`, `token_last`, or `token_count` columns are not allowed.
- In token mode, specify a specific token to be optimized (for example, all rows with documents containing the word *elections*). Use this mode to optimize index tokens that are frequently searched, without spending time on optimizing tokens that are rarely referenced. An optimized token can improve query response time (but only for queries on that token).
- Token-type optimization is similar to token mode, except that the optimization is performed on field, MDATA, or SDATA sections (for example, sections with an <A> tag). This is useful in keeping critical field or MDATA sections optimal.
- Use the merge mode to optimize the \$I table for the CONTEXT indexes that are frequently used for DML operations. The merge operation removes the old data (deleted rows) from the \$G table, compacts the existing data in the \$G table, and then copies that data to the \$I table. Using merge optimization for a particular token copies only that token from the \$G table to the \$I table.

A common strategy for optimizing indexes is to perform regular token optimizations on frequently referenced terms, and to perform rebuild optimizations less frequently. (Use CTX_REPORT.QUERY_LOG_SUMMARY (page 13-10) to find out which queries are made most frequently.) You can perform full, fast, or token-type optimizations instead of token optimizations.

Some users choose to perform frequent time-limited full optimizations along with occasional rebuild optimizations.

Note:

Optimizing an index can result in better response time only if you insert, delete, or update documents in the base table after your initial indexing operation.

Using this procedure to optimize the index is recommended over using the ALTER INDEX statement.

Optimization of a large index may take a long time. To monitor the progress of a lengthy optimization, log the optimization with CTX_OUTPUT.START_LOG (page 11-9) and check the resultant logfile from time to time.

Note that, unlike serial optimize full, CTX_DDL.OPTIMIZE_INDEX() run with optlevel of FULL and parallel_degree > 1 is not resumable. That is, it will not resume from where it left after a time-out or failure.

Note:

There is a very small window of time when a query might fail in CTX_DDL.OPTIMIZE_INDEX REBUILD mode when the \$I table is being swapped with the optimized shadow \$I table.

Syntax

```
CTX_DDL.OPTIMIZE_INDEX(  
  
  idx_name          IN  VARCHAR2,  
  optlevel          IN  VARCHAR2,  
  maxtime           IN  NUMBER DEFAULT NULL,  
  token             IN  VARCHAR2 DEFAULT NULL,  
  part_name         IN  VARCHAR2 DEFAULT NULL,  
  token_type        IN  NUMBER DEFAULT NULL,  
  parallel_degree   IN  NUMBER DEFAULT 1  
  
);
```

idx_name

Specify the name of the index. If you do not specify an index name, then Oracle Text chooses a single index to optimize.

optlevel

Specify optimization level as a string. You can specify one of the following methods for optimization:

optlevel value	Description
FAST or CTX_DDL.OPTLEVEL_FAST	This method compacts fragmented rows. However, old data is not removed. FAST optimization is not supported for CTXCAT indexes. FAST optimization will not optimize \$\$ index table.

optlevel value	Description
FULL or CTX_DDL.OPTLEVEL_FULL	<p>In this mode you can optimize the entire index or a portion of the index. This method compacts rows and removes old data (deleted rows). Optimizing in full mode runs even when there are no deleted rows.</p> <p>Full optimization is not supported for CTXCAT indexes.</p>
REBUILD or CTX_DDL.OPTLEVEL_REBUILD	<p>This <code>optlevel</code> rebuilds the \$I table (the inverted list table) to produce more compact token info rows. Like FULL optimize, this mode also deletes information pertaining to deleted rows of the base table.</p> <p>REBUILD is not supported for CTCAT and CTXRULE indexes.</p> <p>REBUILD is not supported when the \$I table is partitioned.</p>
TOKEN or CTX_DDL.OPTLEVEL_TOKEN	<p>This method lets you specify a specific token to be optimized. Oracle Text does a full optimization on the token you specify with <code>token</code>. If no token type is provided, 0 (zero) will be used as the default.</p> <p>Use this method to optimize those tokens that are searched frequently.</p> <p>Token optimization is not supported for CTCAT and CTXRULE indexes.</p>
TOKEN_TYPE or CTX_DDL.OPTLEVEL_TOKEN_TYPE	<p>This <code>optlevel</code> optimizes on demand all tokens in the index matching the input token type.</p> <p>When <code>optlevel</code> is <code>TOKEN_TYPE</code>, <code>token_type</code> must be provided. <code>TOKEN_TYPE</code> performs FULL optimize on any token of the input <code>token_type</code>. Like a TOKEN optimize, <code>TOKEN_TYPE</code> optimize does not change the FULL optimize state, and runs to completion on each invocation.</p> <p>Token_type optimization is not supported for CTCAT and CTXRULE indexes.</p>
MERGE or CTX_DDL.OPTLEVEL_MERGE	<p>This <code>optlevel</code> optimizes the \$I table. It removes the old data (deletes rows) from the \$G table, compacts the existing data in the \$G table, and then copies that optimized data to the \$I table.</p> <p>When this option is used for a particular token, only that token gets copied from the \$G table to the \$I table.</p> <p>Merge optimization should be used for CONTEXT indexes with the <code>STAGE_ITAB</code> index option enabled.</p>

The behavior of CTX_DDL.OPTIMIZE_INDEX with respect to the \$\$ index table is as follows:

optlevel value	Will Optimize \$\$ Index Table Yes/No	Notes
FAST or CTX_DDL.OPTLEVEL_FAST	No	

optlevel value	Will Optimize \$\$ Index Table Yes/No	Notes
FULL or CTX_DDL.OPTLEVEL_FULL	Yes	<ul style="list-style-type: none"> The optimize process will optimize \$I table first. Once \$I table optimize is finished, CTX_DDL.OPTIMIZE_INDEX will continue on to optimize \$\$ index table. MAXTIME will also be honored. Once CTX_DDL.OPTIMIZE_INDEX completes optimizing \$\$ rows for a given SDATA_ID, it will check MAXTIME and exit if total elapsed time (including time taken to optimize \$I) exceeds specified MAXTIME. The next CTX_DDL.OPTIMIZE_INDEX with optlevel=>'FULL' will pick up where it left off. \$\$ table optimize will be done in serial.
REBUILD or CTX_DDL.OPTLEVEL_REBUILD	Yes	<ul style="list-style-type: none"> \$\$ optimize will start after \$I rebuild finishes. \$\$ optimize in this case will be processed the same way as \$\$ optimize in FULL mode. \$\$ table is optimized in place, not rebuilt. Note: If for some reason \$\$ optimize exits abnormally, then it is recommended that you use optlevel=>TOKEN_TYPE to optimize \$\$ to avoid rebuilding the \$I table again. \$\$ table optimize will be done in serial.
TOKEN or CTX_DDL.OPTLEVEL_TOKEN	No	
TOKEN_TYPE or CTX_DDL.OPTLEVEL_TOKEN_TYPE	Yes	You can optimize \$\$ rows for a given SDATA_ID by setting optlevel => TOKEN_TYPE and the TOKEN_TYPE parameter to the target SDATA_ID.

maxtime

Specify maximum optimization time, in minutes, for FULL optimize.

When you specify the symbol CTX_DDL.MAXTIME_UNLIMITED (or pass in NULL), the entire index is optimized. This is the default.

token

Specify the token to be optimized.

part_name

If your index is a local index, then you must specify the name of the index partition to synchronize otherwise an error is returned.

If your index is a global, nonpartitioned index, then specify NULL, which is the default.

token_type

Specify the token_type to be optimized.

parallel_degree

Specify the parallel degree as a number for parallel optimization. The actual parallel degree depends on your resources.

Because the `optlevel` values are executed serially, this setting is ignored these values:

- `TOKEN` or `CTX_DDL.OPTLEVEL_TOKEN`
- `FAST` or `CTX_DDL.OPTLEVEL_FAST`

Examples

The following two examples are equivalent ways of optimizing an index using fast optimization:

```
begin
  ctx_ddl.optimize_index('myidx','FAST');
end;

begin
  ctx_ddl.optimize_index('myidx',CTX_DDL.OPTLEVEL_FAST);
end;
```

The following example optimizes the index token *Oracle*:

```
begin
  ctx_ddl.optimize_index('myidx','token', TOKEN=>'Oracle');
end;
```

To optimize all tokens of field section MYSEC in index MYINDEX:

```
begin
  ctx_ddl.optimize_index('myindex', ctx_ddl.optlevel_token_type,
    token_type=> ctx_report.token_type('myindex','field mysec text'));end;
```

The following two examples are equivalent ways of optimizing an index using merge optimization:

```
begin
  ctx_ddl.optimize_index('idx','MERGE');
end;

begin
  ctx_ddl.optimize_index('idx',CTX_DDL.OPTLEVEL_MERGE);
end;
```

Notes

You can run `CTX_DDL.SYNC_INDEX` and `CTX_DDL.OPTIMIZE_INDEX` at the same time. You can also run `CTX_DDL.SYNC_INDEX` and `CTX_DDL.OPTIMIZE_INDEX` with parallelism at the same time. However, you should not:

- Run `CTX_DDL.SYNC_INDEX` with parallelism at the same time as `CTX_DDL.OPTIMIZE_INDEX`
- Run `CTX_DDL.SYNC_INDEX` with parallelism at the same time as `CTX_DDL.OPTIMIZE_INDEX` with parallelism.

If you should run one of these combinations, no error is generated; however, one operation will wait until the other is done.

Related Topics

CTX_DDL.["SYNC_INDEX"](#) (page 8-68)"

["ALTER INDEX"](#) (page 1-1)"

8.34 POPULATE_PENDING

This procedure populates the pending queue with every rowid in the base table or table partition. This procedure is only supported for CONTEXT indexes.

This procedure is valuable for large installations that cannot afford to have the indexing process run continuously, and, therefore, need finer control over creating text indexes. The preferred method is to create an empty index, place all the rowids into the pending queue, and build the index through CTX_DDL.[SYNC_INDEX](#) (page 8-68).

Syntax

```
ctx_ddl.populate_pending(  
    idx_name  IN VARCHAR2,  
    part_name IN VARCHAR2 DEFAULT NULL  
);
```

idx_name

Name of the CONTEXT indextype.

part_name

Name of the index partition, if any. Must be provided for local partitioned indexes and must be NULL for global, nonpartitioned indexes.

Notes

The SYNC_INDEX is blocked for the duration of the processing. The index unit must be totally empty (idx_docid_count = 0, idx_nextid = 1). The rowids of rows waiting to be indexed are inserted into table ctxsys.dr\$pending. You should ensure that there is sufficient space in this table to hold the rowids of the base table.

Related Topics

["SYNC_INDEX"](#) (page 8-68)"

["CREATE_SHADOW_INDEX"](#) (page 8-37)"

["DROP_SHADOW_INDEX"](#) (page 8-42)"

["EXCHANGE_SHADOW_INDEX"](#) (page 8-43)"

["RECREATE_INDEX_ONLINE"](#) (page 8-51)"

8.35 PREFERENCE_IMPLICIT_COMMIT

This variable, set at the package level for CTX_DDL, determines whether procedures related to CTX_DDL preferences issue an implicit commit and is session duration.

You can set the PREFERENCE_IMPLICIT_COMMIT variable for the procedures listed in the following table.

Procedure Name	Procedure Name
ADD_ATTR_SECTION (page 8-3)	CREATE_INDEX_SET (page 8-29)
ADD_FIELD_SECTION (page 8-5)	CREATE_PREFERENCE (page 8-31)
ADD_INDEX (page 8-8)	CREATE_SECTION_GROUP (page 8-34)
ADD_MDATA_COLUMN (page 8-11)	CREATE_STOPLIST (page 8-39)
ADD_MDATA_SECTION (page 8-12)	DROP_PREFERENCE (page 8-41)
ADD_SDATA_COLUMN (page 8-14)	DROP_SECTION_GROUP (page 8-41)
ADD_SDATA_SECTION (page 8-16)	DROP_STOPLIST (page 8-42)
ADD_SPECIAL_SECTION (page 8-18)	REMOVE_INDEX (page 8-59)
ADD_STOPCLASS (page 8-19)	REMOVE_SECTION (page 8-60)
ADD_STOP_SECTION (page 8-21)	REMOVE_SUB_LEXER (page 8-63)
ADD_STOPTHEME (page 8-22)	SET_ATTRIBUTE (page 8-64)
ADD_STOPWORD (page 8-23)	UNSET_ATTRIBUTE (page 8-70)
ADD_SUB_LEXER (page 8-24)	UPDATE_SUB_LEXER (page 8-71)
ADD_ZONE_SECTION (page 8-26)	

Note:

The REMOVE_STOPCLASS, REMOVE_STOPTHEME, and REMOVE_STOPWORD procedures do not issue an implicit commit, and, therefore, do not use the PREFERENCE_IMPLICIT_COMMIT flag.

Syntax

```
exec CTX_DDL.PREFERENCE_IMPLICIT_COMMIT := TRUE|FALSE ;
```

The default value of the PREFERENCE_IMPLICIT_COMMIT variable is TRUE. When this variable is set to FALSE, procedures related to CTX_DDL preferences will not issue an implicit commit. This enables you to easily rollback multiple preference changes. This variable is session duration.

Example

The following example turns off implicit commit.

```
exec CTX_DDL.PREFERENCE_IMPLICIT_COMMIT : update_sub_lexer = FALSE;
```

8.36 RECREATE_INDEX_ONLINE

Recreates the specified index, or recreates the passed-in index partition if the index is local partitioned. For global nonpartitioned indexes, this is a one-step procedure. For local partitioned indexes, this procedure must be run separately on every partition

after first using [CREATE_SHADOW_INDEX](#) (page 8-37) to create a shadow policy (or metadata). This procedure is only supported in Enterprise Edition of Oracle Database.

The following changes are not supported:

- Transitioning from non-composite domain index to composite, or changing the composite domain index columns.
- Rebuilding indexes that have partitioned index tables, for example, \$I, \$P, \$K.

Syntax

```
CTX_DDL.RECREATE_INDEX_ONLINE(  
    idx_name          IN VARCHAR2,  
    parameter_string  IN VARCHAR2 default NULL,  
    parallel_degree   IN NUMBER default 1,  
    partition_name    IN VARCHAR2 default NULL  
);
```

idx_name

The name of a valid CONTEXT indextype.

parameter_string

If the index is a global nonpartitioned index, specify the same index-level parameter string as in ALTER INDEX. Must start with REPLACE, if it is not NULL. Optionally specify SWAP or NOSWAP. The default is SWAP.

parallel_degree

Reserved for future use. Specify the degree of parallelism. Parallel operation is not supported in the current release.

partition_name

Specify the name of a valid index partition for a local partitioned index. Otherwise, the default is NULL. If the index is partitioned, then first pass a partition name, and then specify the partition-level parameter string for ALTER INDEX REBUILD PARTITION.

Examples

Example 8-5 Recreate Simple Global Index

The following example creates an index `idx` with a BASIC_LEXER-based preference `us_lexer`. It then recreates the index with a new MULTI_LEXER based preference `m_lexer` in one step. You can use this one step approach when you do not mind that a query might fail for a small window of time at the end of the operation, and DML might get blocked at the beginning for a short time and again at the end.

```
/* create lexer and original index */  
exec ctx_ddl.create_preference('us_lexer','basic_lexer');  
create index idx on tbl(text) indextype is ctxsys.context  
    parameters('lexer us_lexer');  
  
/* create a new lexer */  
begin  
    ctx_ddl.create_preference('e_lexer','basic_lexer');  
    ctx_ddl.set_attribute('e_lexer','base_letter','yes');  
    ctx_ddl.create_preference('m_lexer','multi_lexer');  
    ctx_ddl.add_sub_lexer('m_lexer','default','us_lexer');  
    ctx_ddl.add_sub_lexer('m_lexer','e','e_lexer');
```

```

end;
/

/* add new language column to the table for multi-lexer */
alter table tbl add(lang varchar2(10) default 'us');

/* recreate index online with the new multip-lexer */
exec ctx_ddl.recreate_index_online('idx',
    'replace lexer m_lexer language column lang');

```

Example 8-6 Local Index Recreate with All-At-Once Swap

The following example creates a local partitioned index `idxp` with a basic lexer `us_lexer`. It has two index partitions `idx_p1` and `idx_p2`. It then recreates a local partitioned index `idxp` online with partition `idx_p1`, which will have a new storage preference `new_store`. The swapping of the partition metadata and index partition data occur at the end. In this example, queries spanning multiple partitions return consistent results across partitions when recreate is in process, except at the end when [EXCHANGE_SHADOW_INDEX](#) (page 8-43) is running. The extra space required is the combined index size of partition `idx_p1` and `idx_p2`.

```

/* create a basic lexer and a local partition index with the lexer*/
exec ctx_ddl.create_preference('us_lexer','basic_lexer');
create index idxp on tblp(text) indextype is ctxsys.context local
    (partition idx_p1,
     partition idx_p2)
parameters('lexer us_lexer');

/* create new preferences */
begin
    ctx_ddl.create_preference('my_store','basic_storage');
    ctx_ddl.set_attribute('my_store','i_table_clause','tablespace tbs');
end;
/
begin
    ctx_ddl.create_preference('e_lexer','basic_lexer');
    ctx_ddl.set_attribute('e_lexer','base_letter','yes');
    ctx_ddl.create_preference('m_lexer','multi_lexer');
    ctx_ddl.add_sub_lexer('m_lexer','default','us_lexer');
    ctx_ddl.add_sub_lexer('m_lexer','e','e_lexer');
end;
/

/* add new language column */
alter table tblp add column (lang varchar2(10) default 'us');

/* create a shadow policy with a new lexer */
exec ctx_ddl.create_shadow_index('idxp', null,
    'replace lexer m_lexer language column lang');

/* recreate every index partition online without swapping */
exec ctx_ddl.recreate_index_online('idxp',
    'replace storage my_store NOSWAP', 1, 'idx_p1');
exec ctx_ddl.recreate_index_online('idxp','replace NOSWAP',1,'idx_p2');

/* exchange in shadow index partition all at once */
exec ctx_ddl.exchange_shadow_index('idxp',
    'idx_p1') /* exchange index partition data*/
exec ctx_ddl.exchange_shadow_index('idxp',
    'idx_p2') /* exchange index partition data*/

```

```
/* exchange in shadow index metadata */
exec ctx_ddl.exchange_shadow_index('idxp')
```

Example 8-7 Local Index Recreate with Per-Partition Swap

This example performs the same tasks as [Example 8-6](#) (page 8-53), except that each index partition is swapped in as it is completed. Queries across all partitions may return inconsistent results in this example.

```
/* create a basic lexer and a local partition index with the lexer*/
exec ctx_ddl.create_preference('us_lexer','basic_lexer');
create index idxp on tblp(text) indextype is ctxsys.context local
  (partition idx_p1,
   partition idx_p2)
parameters('lexer us_lexer');

/* create new preferences */
begin
  ctx_ddl.create_preference('my_store','basic_storage');
  ctx_ddl.set_attribute('my_store','i_table_clause','tablespace tbs');
end;
/
begin
  ctx_ddl.create_preference('e_lexer','basic_lexer');
  ctx_ddl.set_attribute('e_lexer','base_letter','yes');
  ctx_ddl.create_preference('m_lexer','multi_lexer');
  ctx_ddl.add_sub_lexer('m_lexer','default','us_lexer');
  ctx_ddl.add_sub_lexer('m_lexer','e','e_lexer');
end;
/

/* add new language column */
alter table tblp add column (lang varchar2(10) default 'us');

/* create a shadow policy with a new lexer */
exec ctx_ddl.create_shadow_index('idxp',
  'replace lexer m_lexer language column lang');

/* recreate every index partition online and swap (default) */
exec ctx_ddl.recreate_index_online('idxp',
  'replace storage my_store', 1, 'idx_p1');
exec ctx_ddl.recreate_index_online('idxp', 'replace SWAP', 1, 'idx_p2',

  /* exchange in shadow index metadata */
  exec ctx_ddl.exchange_shadow_index('idxp')
```

Example 8-8 Scheduled Local Index Recreate with All-At-Once Swap

This example shows the incremental recreation of a local partitioned index, where partitions are all swapped at the end.

```
/* create a basic lexer and a local partition index with the lexer*/
exec ctx_ddl.create_preference('us_lexer','basic_lexer');
create index idxp on tblp(text) indextype is ctxsys.context local
  (partition idx_p1,
   partition idx_p2)
parameters('lexer us_lexer');

/* create new preferences */
begin
  ctx_ddl.create_preference('my_store','basic_storage');
  ctx_ddl.set_attribute('my_store','i_table_clause','tablespace tbs');
```



```

end;
/
begin
    ctx_ddl.create_preference('e_lexer','basic_lexer');
    ctx_ddl.set_attribute('e_lexer','base_letter','yes');
    ctx_ddl.create_preference('m_lexer','multi_lexer');
    ctx_ddl.add_sub_lexer('m_lexer','default','us_lexer');
    ctx_ddl.add_sub_lexer('m_lexer','e','e_lexer');
end;
/

/* add new language column */
alter table tblpl add column (lang varchar2(10) default 'us');

/* create a shadow policy with a new lexer */
exec ctx_ddl.create_shadow_index('idxp',
    'replace lexer m_lexer language column lang');
/* create shadow partition with new storage preference */
exec ctx_ddl.recreate_index_online('idxp', 'replace storage ctxsys.default_storage nopopulate',
1,'idx_p1');
exec ctx_ddl.recreate_index_online('idxp', 'replace storage ctxsys.default_storage nopopulate',
1,'idx_p2');

declare
    idxid integer;
    ixpid integer;
begin
    select idx_id into idxid from ctx_user_indexes
        where idx_name = 'IDXP';
    select ixp_id into ixpid from ctx_user_index_partitions
        where ixp_index_name = 'IDXP'
            and ixp_index_partition_name = 'IDX_P1';
    /* populate pending */
    ctx_ddl.populate_pending('RIO$'||idxid, 'RIO$'||idxid||'#'||ixpid);
    /* incremental sync
    ctx_ddl.sync_index('RIO$'||idxid, null, 'RIO$'||idxid||'#'||ixpid,
        maxtime=>400);
    /* more incremental sync until no more pending rows */

    select ixp_id into ixpid from ctx_user_index_partitions
        where ixp_index_name = 'IDXP'
            and ixp_index_partition_name = 'IDX_P2';
    /* populate pending */
    ctx_ddl.populate_pending('RIO$'||idxid, 'RIO$'||idxid||'#'||ixpid);
    /* incremental sync
    ctx_ddl.sync_index('RIO$'||idxid, null, 'RIO$'||idxid||'#'||ixpid,
        maxtime=>400);
    /* more incremental sync until no more pending rows */
end;
/

exec ctx_ddl.exchange_shadow_index('idxp','idx_p1');
exec ctx_ddl.exchange_shadow_index('idxp','idx_p2');
exec ctx_ddl.exchange_shadow_index('idxp');

```

Example 8-9 Schedule Local Index Recreate with Per-Partition Swap

For incremental recreate where partitions are swapped as they becomes available, follow the steps in example [Example 8-8](#) (page 8-54), except instead of waiting until all syncs are finished before starting exchange shadow index,

[EXCHANGE_SHADOW_INDEX](#) (page 8-43) is done for each partition right after sync is finished.

Notes

Using RECREATE_INDEX_ONLINE with Global Nonpartitioned Indexes

For global indexes, this procedure provides a one-step process to recreate an index online. It recreates an index, with new preference values, while preserving base table DML and query capability during the recreate process.

Note:

Because the new index is created alongside the existing index, this operation requires additional storage roughly equal to the size of the existing index.

DML Behavior

Because this procedure is performed online, DML on the base table are permitted during this operation, and are processed as normal. All DML statements that occur during RECREATE_INDEX_ONLINE are logged into an online pending queue.

Towards the end of the recreate operation, there will be a short duration when DML will fail with an error being raised stating that the index is in an in-progress status. DML may hang again during the process, and the duration will depend on how many DML are logged in the online pending queue since the start of the recreate process.

Note that after the recreate index operation is complete, new information, from all the DML that becomes pending since RECREATE_INDEX_ONLINE started, may not be immediately reflected. As with creating an index with INDEXTYPE IS `ctxsys.context ONLINE`, the index should be synchronized after the recreate index operation is complete, to bring it fully up-to-date.

See Also:

- [CTX_DDL.CREATE_SHADOW_INDEX](#) (page 8-37) and [CTX_DDL.EXCHANGE_SHADOW_INDEX](#) (page 8-43) for information about how to manually go through each stage of recreation, and to schedule each step to run at a preferred time
 - The `ONLINE` parameter under "[Syntax for CONTEXT Index Type](#) (page 1-41)"
-
-

Sync and Optimize Behavior

Syncs issued against the index during the recreate operation are processed against the old, existing data. Syncs are also blocked during the same window when queries return errors. Optimize commands issued against the index during the recreate operation return immediately without error and without processing.

Query Behavior

During the recreate operation, the index can be queried normally most of the time. Queries return results based on the existing index and policy (or metadata) until after the final swap.

There is a short interval towards the end of `RECREATE_INDEX_ONLINE` when queries will return an error indicating that the column is not indexed. This duration should be short for regular queries. It is mainly the time taken for swapping data segments of the shadow index tables and the index tables, plus the time to delete all the rows in the pending queue. This is the same window of time when DML will fail.

During `RECREATE_INDEX_ONLINE`, if you issue DML statements and synchronize them, then you will be able to see the new rows when you query on the existing index. However, after `RECREATE_INDEX_ONLINE` finishes (swapping completes and query is on the new index) and before sync is performed, it is possible that you will not be able to query on the new rows, which once could be queried on the old index.

Note:

Transactional queries are not supported.

Using `RECREATE_INDEX_ONLINE` with Local Partitioned Indexes

If the index is local partitioned, you cannot recreate index in one step. You must first create a shadow policy, and then run this procedure for every partition. You can specify `SWAP` or `NOSWAP` to indicate whether `RECREATE_INDEX_ONLINE` partition will swap the index partition data and index partition metadata or not. If the partition was built with `NOSWAP`, then another call to `EXCHANGE_SHADOW_INDEX` must be invoked later against this partition.

This procedure can also be used to update the metadata (for example, storage preference) of each partition when you specify `NOPOPULATE` in the parameter string. This is useful for incremental building of a shadow index through time-limited sync.

If `NOPOPULATE` is specified, then `NOSWAP` is silently enforced.

NOSWAP Behavior

During the recreate of the index partition, since no swapping is performed, queries on the partition are processed regularly. Until the swapping stage is reached, queries spanning multiple partitions return consistent results across partitions.

DML and sync are processed normally. Running optimize on partitions that are being recreated, or that have been built (but not swapped), simply returns without doing anything. Running optimize on a partition that has not been rebuilt processes normally.

As with a global index, when all of the partitions use `NOSWAP`, the additional storage requirement is roughly equal to the size of the existing index.

SWAP Behavior

Because index partition data and metadata are swapped after index recreate, queries that span multiple partitions will not return consistent results from partition to partition, but will always be correct with respect to each index partition. There is also a short interval towards the end of partition recreate, when the index partition is swapped, during which a query will return a "column not indexed" error.

When partitions are recreated with `SWAP`, the additional storage requirement for the operation is equal to the size of the existing index partition.

DML on the partition is blocked. Sync is also blocked during swapping.

Related Topics[CREATE_SHADOW_INDEX](#) (page 8-37)[DROP_SHADOW_INDEX](#) (page 8-42)[EXCHANGE_SHADOW_INDEX](#) (page 8-43)*Oracle Text Application Developer's Guide*

8.37 REM_SEC_GRP_ATTR_VAL

Removes a specific section group attribute value from the list of values of an existing section group attribute.

Syntax

```
CTX_DDL.REM_SEC_GRP_ATTR_VAL(group_name IN VARCHAR2,  
                             attribute_name IN VARCHAR2,  
                             attribute_value IN VARCHAR2);
```

group_name

Specify the section group name.

attribute_name

Specify the name of the section group attribute.

attribute_value

Specify the section group attribute value.

8.38 REMOVE_AUTO_OPTIMIZE

Removes an index or partition from the list of indexes subject to auto optimization. No new auto optimization calls are made to this index. The removal takes effect immediately.

If the specified index is not in the existing list of indexes, then an error occurs. For partitioned indexes, an error occurs when the partition name is not specified.

Syntax

```
CTX_DDL.REMOVE_AUTO_OPTIMIZE(  
  
    idx_name      IN VARCHAR2,  
    part_name     IN VARCHAR2 default NULL  
);
```

idx_name

Specify the name of the index to remove.

part_name

Specify the name of the partition to remove.

Related Topic

["ADD_AUTO_OPTIMIZE](#) (page 8-4)"

8.39 REMOVE_INDEX

Removes the index with the specified column list from a CTXCAT index set preference.

Note:

This procedure does not remove a CTXCAT sub-index from the existing index. To do so, you must drop your index and re-index with the modified index set preference.

Syntax

```
CTX_DDL.REMOVE_INDEX(

    set_name          IN VARCHAR2,
    column_list       IN VARCHAR2
    language          IN VARCHAR2 default NULL
);
```

set_name

Specify the name of the index set.

column_list

Specify the name of the column list to remove.

8.40 REMOVE_MDATA

Use this procedure to remove metadata values, which are associated with an MDATA section, from a document. Only the owner of the index is allowed to call [ADD_MDATA](#) (page 8-9) and REMOVE_MDATA.

CTX_DDL.REMOVE_MDATA is transactional and takes effect immediately in the calling session. This procedure can be seen only in the calling session and must be committed to take permanent effect. You can reverse this procedure with a ROLLBACK command.

Syntax

```
CTX_DDL.REMOVE_MDATA(

    idx_name          IN VARCHAR2,
    section_name      IN VARCHAR2,
    values            SYS.ODCIVARCHAR2LIST,
    rowids            SYS.ODCIRIDLIST,
    [part_name]       IN VARCHAR2
);
```

idx_name

Name of the text index that contains the named *rowids*.

section_name

Name of the MDATA section.

values

List of metadata values. If a metadata value contains a comma, the comma must be escaped with a backslash.

rowids

Rowids from which to remove the metadata values.

[part_name]

Name of the index partition, if any. Must be provided for local partitioned indexes and must be NULL for global, nonpartitioned indexes.

Example

This example removes the MDATA value *blue* from the MDATA section BGCOLOR.

```
ctx_ddl.remove_mdata('idx_docs', 'bgcolor', 'blue', 'rows');
```

Notes

These updates are updates directly on the index itself, not on the actual contents stored in the base table. Therefore, they will not survive when the Text index is rebuilt.

Related Topics

["ADD_MDATA \(page 8-9\)"](#)

["ADD_MDATA_SECTION \(page 8-12\)"](#)

["MDATA \(page 3-29\)"](#)

The Section Searching chapter of *Oracle Text Application Developer's Guide*

8.41 REMOVE_SECTION

The REMOVE_SECTION procedure removes the specified section from the specified section group. You can specify the section by name or ID. View section ID with the CTX_USER_SECTIONS view.

Syntax 1

Use the following syntax to remove a section by section name:

```
CTX_DDL.REMOVE_SECTION(  
    group_name      IN    VARCHAR2,  
    section_name    IN    VARCHAR2  
);
```

group_name

Specify the name of the section group from which to delete section_name.

section_name

Specify the name of the section to delete from group_name.

Syntax 2

Use the following syntax to remove a section by section ID:

```
CTX_DDL.REMOVE_SECTION(  
    group_name      IN    VARCHAR2,
```

```
    section_id    IN    NUMBER
);
```

group_name

Specify the name of the section group from which to delete `section_id`.

section_id

Specify the section ID of the section to delete from `group_name`.

Example

The following example drops a section called `Title` from the `htmgroup`:

```
begin
ctx_ddl.remove_section('htmgroup', 'Title');
end;
```

Related Topics

["ADD_FIELD_SECTION \(page 8-5\)"](#)

["ADD_SPECIAL_SECTION \(page 8-18\)"](#)

["ADD_ZONE_SECTION \(page 8-26\)"](#)

8.42 REMOVE_STOPCLASS

Removes a stopclass from a stoplist.

Syntax

```
CTX_DDL.REMOVE_STOPCLASS(
    stoplist_name IN    VARCHAR2,
    stopclass     IN    VARCHAR2
);
```

stoplist_name

Specify the name of the stoplist.

stopclass

Specify the name of the stopclass to be removed.

Example

The following example removes the stopclass `NUMBERS` from the stoplist `mystop`.

```
begin
ctx_ddl.remove_stopclass('mystop', 'NUMBERS');
end;
```

Related Topic

["ADD_STOPCLASS \(page 8-19\)"](#)

8.43 REMOVE_STOPTHEME

Removes a stoptheme from a stoplist.

Syntax

```
CTX_DDL.REMOVE_STOPTHEME(  
    stoplist_name IN VARCHAR2,  
    stoptheme     IN VARCHAR2  
);
```

stoplist_name

Specify the name of the stoplist.

stoptheme

Specify the stoptheme to be removed from stoplist_name.

Example

The following example removes the stoptheme *banking* from the stoplist *mystop*:

```
begin  
ctx_ddl.remove_stoptheme('mystop', 'banking');  
end;
```

Related Topic

["ADD_STOPTHEME \(page 8-22\)"](#)

8.44 REMOVE_STOPWORD

Removes a stopword from a stoplist. To have the removal of a stopword be reflected in the index, you must rebuild your index. You can also remove a language-independent stopword.

Syntax

```
CTX_DDL.REMOVE_STOPWORD(  
  
stoplist_name IN VARCHAR2,  
stopword      IN VARCHAR2,  
language      IN VARCHAR2 default NULL  
  
);
```

stoplist_name

Specify the name of the stoplist.

stopword

Specify the stopword to be removed from stoplist_name.

language

Specify the language of stopword to remove when the stoplist you specify with stoplist_name is of type MULTI_STOPLIST. You must specify the globalization support name or abbreviation of an Oracle Text-supported language. You can also remove ALL stopwords.

Example

The following example removes a stopword *because* from the stoplist *mystop*:


```
begin

ctx_ddl.remove_stopword('mystop', 'because');

end;
```

Related Topic

["ADD_STOPWORD \(page 8-23\)"](#)

8.45 REMOVE_SUB_LEXER

Removes a sub-lexer from a multi-lexer preference. You cannot remove the lexer for DEFAULT. You can also remove a language-independent sub-lexer.

Syntax

```
CTX_DDL.REMOVE_SUB_LEXER(

lexer_name  IN    VARCHAR2,
language    IN    VARCHAR2 default NULL

);
```

lexer_name

Specify the name of the multi-lexer preference or language-independent sub-lexer.

language

Specify the language of the sub-lexer to remove. You must specify the globalization support name or abbreviation of an Oracle Text-supported language.

Example

The following example removes a sub-lexer *german_lexer* of language *german*:

```
begin

ctx_ddl.remove_sub_lexer('german_lexer', 'german');

end;
```

Related Topic

["ADD_SUB_LEXER \(page 8-24\)"](#)

8.46 REPLACE_INDEX_METADATA

Use this procedure to replace metadata in local domain indexes at the global (index) level.

Note:

The `ALTER INDEX PARAMETERS` command performs the same function as this procedure and can replace more than just metadata. For that reason, using `ALTER INDEX PARAMETERS` is the preferred method of replacing metadata at the global (index) level and should be used in place of this procedure when possible. For more information, see "[ALTER INDEX PARAMETERS Syntax](#) (page 1-3)".

`CTX_REPLACE_INDEX_METADATA` may be deprecated in a future release of Oracle Text.

Syntax

```
CTX_DDL.REPLACE_INDEX_METADATA(  
                                idx_name          IN VARCHAR2,  
                                parameter_string IN VARCHAR2  
);
```

idx_name

Specify the name of the index whose metadata you want to replace.

parameter_string

Specify the parameter string to be passed to `ALTER INDEX`. This must begin with `'REPLACE METADATA'`.

Notes

`ALTER INDEX REBUILD PARAMETERS ('REPLACE METADATA')` does not work for a local partitioned index at the index (global) level. You cannot, for example, use that `ALTER INDEX` syntax to change a global preference, such as filter or lexer type, without rebuilding the index. Therefore, `CTX_DDL.REPLACE_INDEX_METADATA` is provided as a method of overcoming this limitation of `ALTER INDEX`. Also, `ALTER INDEX REBUILD PARAMETERS ('REPLACE METADATA')` does not work with `forward_index`; instead use `'REPLACE STORAGE'`.

Though it is meant as a way to replace metadata for a local partitioned index, `CTX_DDL.REPLACE_INDEX_METADATA` can be used on a global, nonpartitioned index, as well.

`REPLACE_INDEX_METADATA` cannot be used to change the sync type at the partition level; that is, *parameter_string* cannot be `'REPLACE METADATA SYNC'`. For that purpose, use `ALTER INDEX REBUILD PARTITION` to change the sync type at the partition level.

Related Topics

"[ALTER INDEX PARAMETERS Syntax](#) (page 1-3)"

"[ALTER INDEX REBUILD Syntax](#) (page 1-4)"

8.47 SET_ATTRIBUTE

Sets a preference attribute. Use this procedure after you have created a preference with `CTX_DDL.CREATE_PREFERENCE` (page 8-31).

Syntax

```
CTX_DDL.SET_ATTRIBUTE(  
    preference_name IN VARCHAR2,  
    attribute_name  IN VARCHAR2,  
    attribute_value IN VARCHAR2  
);
```

preference_name

Specify the name of the preference.

attribute_name

Specify the name of the attribute.

attribute_value

Specify the attribute value. Specify boolean values as TRUE or FALSE, T or F, YES or NO, Y or N, ON or OFF, or 1 or 0.

Example**Specifying File Data Storage**

The following example creates a data storage preference called `filepref` that tells the system that the files to be indexed are stored in the operating system. The example then uses `CTX_DDL.SET_ATTRIBUTE` (page 8-64) to set the `PATH` attribute to the directory `/docs`.

```
begin  
ctx_ddl.create_preference('filepref', 'FILE_DATASTORE');  
ctx_ddl.set_attribute('filepref', 'PATH', '/docs');  
end;
```

See Also:

For more information about data storage, see "[Datastore Types](#) (page 2-2)"

For more examples of using `SET_ATTRIBUTE`, see "[CREATE_PREFERENCE](#) (page 8-31)"

8.48 SET_SEC_GRP_ATTR

Adds a section group-specific attribute to a section group identified by name.

Also used to set `xml_enable` to support XML awareness.

Syntax

```
CTX_DDL.SET_SEC_GRP_ATTR(  
    group_name      IN VARCHAR2,  
    attribute_name  IN VARCHAR2,  
    attribute_value IN VARCHAR2  
);
```

group_name

Specify the section group name.

attribute_name

Specify the name of the section group attribute.

attribute_value

Specify the section group attribute value. Specify boolean values as TRUE or FALSE, T or F, YES or NO, Y or N, ON or OFF, or 1 or 0.

Examples

```
exec ctx_ddl.create_section_group('secgroup', 'PATH_SECTION_GROUP');
exec ctx_ddl.set_sec_grp_attr('secgroup', 'xml_enable', 'TRUE');
exec ctx_ddl.set_sec_grp_attr('json_group', 'json_enable', 'TRUE');
```

Example 8-10 JSON enabled example

```
exec ctx_ddl.create_section_group('json_group', 'PATH_SECTION_GROUP');
/*A new 'json_enable' section attribute will be available in 12.1.0.2 to enable json mode of context index*/
exec ctx_ddl.set_sec_grp_attr('json_group', 'json_enable', 't');
create table jtab2(j varchar2(4000) check (j is json));
insert into jtab2 values(
 '{"person" : {"id" : ''124'', "name" : ''John Smith''}}');
insert into jtab2 values(
 '{"person" : {"id" : ''125'', "name" : ''JennifierHwang'',
 "college_majors" : [ ''cs'', ''literature'', ''english '' ]}}');
insert into jtab2 values(
 '{"person" : {"id" : ''126'', "name" : ''Mark Dwight'',
 "likeFootBall" : ''Y''}}');
insert into jtab2 values(
 '{"person" : {"id" : ''127'', "name" : ''Zhen Hua Liu'',
 "MachineLearning" : ''Y''}}');
insert into jtab2 values(
 '{"person" : {"id" : ''128'', "name" : ''Jeffery Tang'',
 "address" : {"city" : ''San Francisco''}}});
insert into jtab2 values(
 '{"person" : {"id" : ''129'', "name" : ''Cecilia Sutton'',
 "address" : {"city" : ''San Mateo''}}});

commit;

drop index jsn_ctx_idx ;
/* create json enabled text index */
create index jsn2_ctx_idx on jtab2 (j) indextype is
ctxsys.context_parameters
(' section group json_group');
```

Related Topics

["CREATE_SECTION_GROUP \(page 8-34\)"](#)

8.49 SET_SECTION_ATTRIBUTE

Use SET_SECTION_ATTRIBUTE to specify attributes or properties for a given section.

The **attribute** names listed under "[Syntax \(page 8-67\)](#)" are supported. Note that some attributes only apply to sections that are tokenized. The following section types are tokenized:

- Field sections

- Zone sections
- SDATA sections

Syntax

```
CTX_DDL.SET_SECTION_ATTRIBUTE(
    group_name  IN VARCHAR2,
    section_name IN VARCHAR2,
    attribute    IN VARCHAR2,
    value        IN VARCHAR2
);
```

group_name

Specify the name of the section group.

section_name

Specify the name of the section.

attribute

Specify this attribute for SDATA sections:

- `visible` section attribute

This attribute works with FIELD sections only. For FIELD sections:

Specify TRUE to make the text visible within the rest of the document. By default the visible flag is FALSE. This means that Oracle Text indexes the text within field sections as a sub-document separate from the rest of the document. However, you can set the visible flag to TRUE if you want text within the field section to be indexed as part of the enclosing document.

For field sections, *attribute* will override the value specified in [CTX_DDL.ADD_FIELD_SECTION](#) (page 8-5).

An error is thrown if you try to set the `visible` attribute for a zone section.

An error is thrown if the `visible` attribute is set on a non-tokenized section.

- `save_copy`. Set to True or False. The `save_copy` option is valid for all types of sections, but only SDATA attributes are fetched from \$D table. The rest of the sections are stored for display purposes only (depending on value of `save_copy`). SDATA sections are never stored for display purposes, but are stored independently (in a separate column of \$D table) for efficient fetching (depending on value of `save_copy`). For all sections (except for SDATA sections): A section is either displayed or discarded during document service procedures (snippet, markup, highlight) depending on the value of `save_copy`.

value

Specify the attribute value. Specify boolean values as TRUE or FALSE, T or F, YES or NO, Y or N, ON or OFF, or 1 or 0.

Example

The following example enables the `visible` attribute of a Field section:

```
begin
    ctx_ddl.create_section_group('fieldgroup', 'BASIC_SECTION_GROUP');
    ctx_ddl.add_field_section('fieldgroup', 'author', 'AUTHOR');
```

```

    ctx_ddl.set_section_attribute('fieldgroup', 'author', 'visible', 'true');
end;
```

Notes

Like CTX_DDL.[SET_ATTRIBUTE](#) (page 8-64), this procedure issues a commit.

Related Topic

See also the "Searching Document Sections in Oracle Text" chapter of *Oracle Text Application Developer's Guide*.

8.50 SYNC_INDEX

Synchronizes the index to process inserts, updates, and deletes to the base table.

Note:

Because CTX_DDL.SYNC_INDEX issues implicit commits, calling CTX_DDL.SYNC_INDEX in a trigger is strongly discouraged. Doing so can result in errors being raised, as both SYNC_INDEX and post-commit \$R LOB maintenance try to update the same \$R LOB.

Syntax

```

CTX_DDL.SYNC_INDEX(

    idx_name          IN  VARCHAR2 DEFAULT NULL
    memory            IN  VARCHAR2 DEFAULT NULL,
    part_name         IN  VARCHAR2 DEFAULT NULL,
    parallel_degree   IN  NUMBER  DEFAULT 1
    maxtime           IN  NUMBER  DEFAULT NULL,
    locking           IN  NUMBER  DEFAULT LOCK_WAIT
);
```

idx_name

Specify the name of the index to synchronize.

Note:

When idx_name is null, all CONTEXT and CTXRULE indexes that have pending changes are synchronized. You must be connected as ctxsys to perform this operation. Each index or index partition is synchronized in sequence, one after the other. Because of this, the individual syncs are performed with locking set to NOWAIT and maxtime set to 0. Any values that you specify for locking or maxtime on the SYNC_INDEX call are ignored. However, the memory and parallel_degree parameters are passed on to the individual synchronizations.

memory

Specify the runtime memory to use for synchronization. This value overrides the DEFAULT_INDEX_MEMORY system parameter.

The memory parameter specifies the amount of memory Oracle Text uses for the synchronization operation before flushing the index to disk. Specifying a large amount of memory:

- Improves indexing performance because there is less I/O
- Improves query performance and maintenance because there is less fragmentation
- The indexing memory size specified in the second argument applies to each parallel slave. For example, if the `memory` argument is set to 500M and `parallel_degree` is set to 2, then ensure that there is at least 1GB of memory available on the system used for the parallel SYNC_INDEX.

Specifying smaller amounts of memory increases disk I/O and index fragmentation, but might be useful when runtime memory is scarce.

part_name

If your index is a local index, then you must specify the name of the index partition to synchronize otherwise an error is returned.

If your index is a global, nonpartitioned index, then specify NULL, which is the default.

parallel_degree

Specify the degree to run parallel synchronize. A number greater than 1 turns on parallel synchronize. The actual degree of parallelism might be smaller depending on your resources.

maxtime

Indicate a suggested time limit on the operation, in minutes. SYNC_INDEX will process as many documents in the queue as possible within the time limit. The maxtime value of NULL is equivalent to CTX_DDL.MAXTIME_UNLIMITED. This parameter is ignored when SYNC_INDEX is invoked without an index name, in which case maxtime value of 0 is used instead. The locking parameter is ignored for automatic syncs (that is, SYNC ON COMMIT or SYNC EVERY).

The time limit specified is treated as approximate. The actual time taken may be somewhat less than or greater than what you specify. The "time clock" for maxtime does not start until the SYNC lock is acquired.

locking

Configure how SYNC_INDEX deals with the situation where another sync is already running on the same index or index partition. When locking is ignored because SYNC_INDEX is invoked without an index name, then locking value of LOCK_NOWAIT is used instead. The locking parameter is ignored for automatic syncs (that is, SYNC ON COMMIT or SYNC EVERY).

The options for locking are:

Locking Parameter	Description
CTX_DDL.LOCK_WAIT	If another sync is running, wait until the running sync is complete, then begin sync. (In the event of not being able to get a lock, it will wait forever and ignore the maxtime setting.)

Locking Parameter	Description
CTX_DDL.LOCK_NOWAIT	If another sync is running, immediately returns without error.
CTX_DDL.LOCK_NOWAIT_ERROR	If another sync is running, error "DRG-51313: timeout while waiting for DML or optimize lock" is raised.

Example

The following example synchronizes the index `myindex` with 2 megabytes of memory:

```
begin
  ctx_ddl.sync_index('myindex', '2M');
end;
```

The following example synchronizes the `part1` index partition with 2 megabytes of memory:

```
begin
  ctx_ddl.sync_index('myindex', '2M', 'part1');
end;
```

Notes

You can run `CTX_DDL.SYNC_INDEX` and `CTX_DDL.OPTIMIZE_INDEX` at the same time. You can also run `CTX_DDL.SYNC_INDEX` and `CTX_DDL.OPTIMIZE_INDEX` with parallelism at the same time. However, you should not run `CTX_DDL.SYNC_INDEX` with parallelism at the same time as `CTX_DDL.OPTIMIZE_INDEX`, nor `CTX_DDL.SYNC_INDEX` with parallelism at the same time as `CTX_DDL.OPTIMIZE_INDEX` with parallelism. If you should run one of these combinations, no error is generated; however, one operation will wait until the other is done.

Related Topics

["ALTER INDEX \(page 1-1\)"](#)

8.51 UNSET_ATTRIBUTE

Removes a set attribute from a preference.

Syntax

```
CTX_DDL.UNSET_ATTRIBUTE(preference_name varchar2,
                        attribute_name  varchar2);
```

preference_name

Specify the name of the preference.

attribute_name

Specify the name of the attribute.

Example**Enabling/Disabling Alternate Spelling**

The following example shows how you can enable alternate spelling for German and disable alternate spelling with `CTX_DDL.UNSET_ATTRIBUTE`:

```
begin
ctx_ddl.create_preference('GERMAN_LEX', 'BASIC_LEXER');
ctx_ddl.set_attribute('GERMAN_LEX', 'ALTERNATE_SPELLING', 'GERMAN');
end;
```

To disable alternate spelling, use the `CTX_DDL.UNSET_ATTRIBUTE` procedure as follows:

```
begin
ctx_ddl.unset_attribute('GERMAN_LEX', 'ALTERNATE_SPELLING');
end;
```

Related Topics

["SET_ATTRIBUTE \(page 8-64\)"](#)

8.52 UNSET_SEC_GRP_ATTR

Removes a section group-specific attribute.

Syntax

```
CTX_DDL.UNSET_SEC_GRP_ATTR(group_name varchar2,
                           attribute_name varchar2);
```

group_name

Specify the name of the section group.

attribute_name

Specify the name of the attribute.

Related Topics

["UNSET_ATTRIBUTE \(page 8-70\)"](#)

8.53 UPDATE_SUB_LEXER

Updates a sub-lexer and modifies its multi-lexer preference, language, or sub-lexer. You can also update default sub-lexers using this procedure. This procedure can be used in conjunction with the `CTX_DDL.PREFERENCE_IMPLICIT_COMMIT` (page 8-50) variable.

See Also:

["PREFERENCE_IMPLICIT_COMMIT \(page 8-50\)"](#) for information about setting this variable

Syntax

```
UPDATE_SUB_LEXER (  
    lexer_name      IN   VARCHAR2,  
    language        IN   VARCHAR2,  
    sub_lexer       IN   VARCHAR2  
);
```

lexer_name

Specify the name of the multi-lexer preference that needs to be updated.

language

Specify the language name of the sub-lexer. Use `DEFAULT` for the default sub-lexers.

See "[language](#) (page 8-25)" for information on how to specify the globalization support language name or abbreviation of the sub-lexer.

sub_lexer

Specify the name of the sub-lexer to use for this language.

Related Topics

"[ADD_SUB_LEXER](#) (page 8-24)"

"[REMOVE_SUB_LEXER](#) (page 8-63)"

8.54 UPDATE_POLICY

Updates a policy created with `CREATE_POLICY`. Replaces the preferences of the policy. Null arguments are not replaced.

Syntax

```
CTX_DDL.UPDATE_POLICY(  
    policy_name      IN VARCHAR2,  
    filter           IN VARCHAR2 DEFAULT NULL,  
    section_group    IN VARCHAR2 DEFAULT NULL,  
    lexer            IN VARCHAR2 DEFAULT NULL,  
    stoplist         IN VARCHAR2 DEFAULT NULL,  
    wordlist         IN VARCHAR2 DEFAULT NULL);
```

policy_name

Specify the name of the policy to update.

filter

Specify the filter preference to use.

section_group

Specify the section group to use.

lexer

Specify the lexer preference to use.

stoplist

Specify the stoplist to use.

wordlist

Specify the wordlist to use.

8.55 UPDATE_SDATA

UPDATE_SDATA is an index API that modifies the specified SDATA values in the index. It does not store or modify column values in a base table, where the base table column may have been used as an SDATA section.

Export/import operations rebuild the index from the base table using the specified preferences. Since modifications made using the UPDATE_SDATA API are not present in the base table, the export/import operation does not preserve these changes.

UPDATE_SDATA modifies temporary metadata it adds in the index table, not the base table. It cannot be used to directly add metadata. For export/import of metadata that is persistent, create a base table column that contains the metadata values. You can then update the metadata through the column in the base table.

Syntax

```
CTX_DDL.UPDATE_SDATA(  
    idx_name      IN VARCHAR2 DEFAULT NULL,  
    section_name  IN VARCHAR2 DEFAULT NULL,  
    sdata_value   IN sys.anydata,  
    sdata_rowid   IN rowid,  
    part_name     IN VARCHAR2 DEFAULT NULL);
```

idx_name

Specify the name of the index.

section_name

Specify the name of the SDATA section.

sdata_value

Specify the new SDATA value.

sdata_rowid

Specify the rowid for which the SDATA value needs to be updated.

part_name

Specify the name of the locally partitioned index, if applicable. Specify NULL for the global index.

Related Topics

["SDATA" \(page 3-42\)](#)

["ADD_SDATA_COLUMN" \(page 8-14\)](#)

["ADD_SDATA_SECTION" \(page 8-16\)](#)

See Also:

Chapter 8, "Searching Document Sections in Oracle Text" in *Oracle Text Application Developer's Guide*

CTX_DOC Package

The CTX_DOC PL/SQL package provides procedures and functions for requesting document services, such as highlighting extracted text or generating a list of themes for a document.

- [About CTX_DOC Package Procedures](#) (page 9-2)

The CTX_DOC package includes the following procedures and functions:

Name	Description
FILTER (page 9-2)	Generates a plain text or HTML version of a document.
GIST (page 9-5)	Generates a Gist or theme summaries for a document.
HIGHLIGHT (page 9-9)	Generates plain text or HTML highlighting offset information for a document.
IFILTER (page 9-12)	Generates a plain text version of binary data. Can be called from a USER_DATASTORE procedure.
MARKUP (page 9-13)	Generates a plain text or HTML version of a document with query terms highlighted.
PKENCODE (page 9-19)	Encodes a composite textkey string (value) for use in other CTX_DOC procedures.
POLICY_FILTER (page 9-20)	Generates a plain text or HTML version of a document, without requiring an index.
POLICY_GIST (page 9-21)	Generates a Gist or theme summaries for a document, without requiring an index.
POLICY_HIGHLIGHT (page 9-23)	Generates plain text or HTML highlighting offset information for a document, without requiring an index.
POLICY_LANGUAGES (page 9-24)	Provides the ability to fetch the language for a section of text.
POLICY_MARKUP (page 9-26)	Generates a plain text or HTML version of a document with query terms highlighted, without requiring an index.
POLICY_NOUN_PHRASES (page 9-29)	Extracts noun phrases for a document.
POLICY_PART_OF_SPEECH (page 9-32)	Extracts the part of speech for each word in a document.

Name	Description
POLICY_SNIPPET (page 9-34)	Generates a concordance for a document, based on query terms, without requiring an index.
POLICY_STEMS (page 9-36)	Extracts stems for each word in a body of text.
POLICY_THEMES (page 9-37)	Generates a list of themes for a document, without requiring an index.
POLICY_TOKENS (page 9-39)	Generates all index tokens for a document, without requiring an index.
SET_KEY_TYPE (page 9-40)	Sets CTX_DOC procedures to accept rowid or primary key document identifiers.
SNIPPET (page 9-40)	Generates a concordance for a document, based on query terms.
THEMES (page 9-44)	Generates a list of themes for a document.
TOKENS (page 9-47)	Generates all index tokens for a document.

The performance of the procedures [SNIPPET](#) (page 9-40), [HIGHLIGHT](#) (page 9-9), and [MARKUP](#) (page 9-13) can be improved by using the forward index feature, and the performance of the procedures [FILTER](#) (page 9-2), [GIST](#) (page 9-5), [THEMES](#) (page 9-44), [TOKENS](#) (page 9-47) can be improved by using the save copy feature of Oracle Text.

See Also:

Oracle Text Application Developer's Guide for more information about forward index and save copy features

9.1 About CTX_DOC Package Procedures

Many of the CTX_DOC PL/SQL package procedures exist in two versions: those that make use of indexes, and those that do not. Those that do not make use of indexes are called "policy-based" procedures. They are offered because there are times when you may want to use document services on a single document without creating a CONTEXT index in advance. Policy-based procedures enable you to do this.

The policy_* procedures mirror the conventional in-memory document services and are used with policy_name replacing index_name, and document of type VARCHAR2, CLOB, BLOB, or BFILE replacing textkey. Thus, you need not create an index to obtain document services output with these procedures.

For the procedures that generate character offsets and lengths, such as HIGHLIGHT and TOKENS, Oracle Text follows USC-2 codepoint semantics.

9.2 FILTER

Use the CTX_DOC.FILTER procedure to generate either a plain text or HTML version of a document. You can store the rendered document in either a result table or in

memory. This procedure is generally called after a query, from which you identify the document to be filtered.

Note:

The resultant HTML document does not include graphics.

Syntax 1: In-memory Result Storage

```
exec CTX_DOC.FILTER(
    index_name  IN VARCHAR2,
    textkey     IN VARCHAR2,
    restab      IN OUT NOCOPY CLOB,
    plaintext   IN BOOLEAN DEFAULT FALSE,
    use_saved_copy IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);

exec CTX_DOC.HIGHLIGHT_CLOB_QUERY(
    index_name IN VARCHAR2,
    textkey IN VARCHAR2,
    text_query IN CLOB,
    restab IN OUT NOCOPY HIGHLIGHT_TAB,
    plaintext IN BOOLEAN DEFAULT FALSE,
    use_saved_copy IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);
```

Syntax 2: Result Table Storage

```
exec CTX_DOC.FILTER(
    index_name  IN VARCHAR2,
    textkey     IN VARCHAR2,
    restab      IN VARCHAR2,
    query_id    IN NUMBER DEFAULT 0,
    plaintext   IN BOOLEAN DEFAULT FALSE,
    use_saved_copy IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);

exec CTX_DOC.HIGHLIGHT_CLOB_QUERY(
    index_name IN VARCHAR2,
    textkey IN VARCHAR2,
    text_query IN CLOB,
    restab IN VARCHAR2,
    query_id IN NUMBER DEFAULT 0,
    plaintext IN BOOLEAN DEFAULT FALSE,
    use_saved_copy IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);
```

index_name

Specify the name of the index associated with the text column containing the document identified by `textkey`.

textkey

Specify the unique identifier (usually the primary key) for the document.

The `textkey` parameter can be as follows:

- a single column primary key value
- encoded specification for a composite (multiple column) primary key. Use `CTX_DOC.PKENCODER` (page 9-19)
- the rowid of the row containing the document

Toggle between primary key and rowid identification using `CTX_DOC.SET_KEY_TYPE` (page 9-40).

restab

You can specify that this procedure store the marked-up text to either a table or to an in-memory CLOB.

To store results to a table, specify the name of the table. The table to which you want to store results must exist before you make this call.

See Also:

"[Filter Table](#) (page A-7)" in [Oracle Text Result Tables](#) (page A-1) for more information about the structure of the filter result table

To store results in memory, specify the name of the CLOB locator. If `restab` is `NULL`, then a temporary CLOB is allocated and returned. You must de-allocate the locator after using it with `DBMS_LOB.FREETEMPORARY()`.

If `restab` is not `NULL`, then the CLOB is truncated before the operation.

query_id

Specify an identifier to use to identify the row inserted into `restab`.

When `query_id` is not specified or set to `NULL`, it defaults to 0. You must manually truncate the table specified in `restab`.

plaintext

Specify `TRUE` to generate a plaintext version of the document. Specify `FALSE` to generate an HTML version of the document if you are using the `AUTO_FILTER` filter or indexing HTML documents.

use_saved_copy

Specify whether to refer to the \$D table to fetch the copy of the document, and what action to take when the copy of the document is not available in the \$D table.

You can specify one of the following values for the `use_saved_copy` parameter:

- `CTX_DOC.SAVE_COPY_FALLBACK`: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then fetch the document from the data store.
- `CTX_DOC.SAVE_COPY_ERROR`: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then show an error message. Specify this value when you want to implement a specific fallback logic when the copy of the document is not available in the \$D table.
- `CTX_DOC.SAVE_COPY_IGNORE`: Always fetch the document from the data store.

The default value is `CTX_DOC.SAVE_COPY_FALLBACK`.

Example**In-Memory Filter**

The following code shows how to filter a document to HTML in memory.


```

declare
mklob clob;
amt number := 40;
line varchar2(80);

begin
  ctx_doc.filter('myindex','1', mklob, FALSE);
  -- mklob is NULL when passed-in, so ctx-doc.filter will allocate a temporary
  -- CLOB for us and place the results there.
  dbms_lob.read(mklob, amt, 1, line);
  dbms_output.put_line('FIRST 40 CHARS ARE:'||line);
  -- have to de-allocate the temp lob
  dbms_lob.freetemporary(mklob);
end;

```

Create the filter result table to store the filtered document as follows:

```

create table filtertab (query_id number,
                       document clob);

```

To obtain a plaintext version of document with textkey 20, enter the following statement:

```

begin
  ctx_doc.filter('newsindex', '20', 'filtertab', '0', TRUE);
end;

```

9.3 GIST

Use the `CTX_DOC.GIST` procedure to generate gist and theme summaries for a document. You can generate paragraph-level or sentence-level gists or theme summaries.

Syntax 1: In-Memory Storage

```

CTX_DOC.GIST(

index_name      IN VARCHAR2,
textkey         IN VARCHAR2,
restab          IN OUT CLOB,
glevel          IN VARCHAR2 DEFAULT 'P',
pov             IN VARCHAR2 DEFAULT 'GENERIC',
numParagraphs  IN NUMBER DEFAULT 16,
maxPercent      IN NUMBER DEFAULT 10,
num_themes      IN NUMBER DEFAULT 50,
use_saved_copy  IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);

```

Syntax 2: Result Table Storage

```

CTX_DOC.GIST(

index_name      IN VARCHAR2,
textkey         IN VARCHAR2,
restab          IN VARCHAR2,
query_id        IN NUMBER DEFAULT 0,
glevel          IN VARCHAR2 DEFAULT 'P',
pov             IN VARCHAR2 DEFAULT NULL,
numParagraphs  IN NUMBER DEFAULT 16,
maxPercent      IN NUMBER DEFAULT 10,

```

```
num_themes      IN NUMBER DEFAULT 50,  
use_saved_copy  IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);
```

index_name

Specify the name of the index associated with the text column containing the document identified by `textkey`.

textkey

Specify the unique identifier (usually the primary key) for the document.

The `textkey` parameter can be as follows:

- a single column primary key value
- an encoded specification for a composite (multiple column) primary key. To encode a composite `textkey`, use the `CTX_DOC.PK_ENCODE` procedure
- the `rowid` of the row containing the document

Toggle between primary key and `rowid` identification using `CTX_DOC.SET_KEY_TYPE`.

restab

Specify that this procedure store the gist and theme summaries to either a table or to an in-memory CLOB.

To store results to a table specify the name of an existing table.

See Also:

["Gist Table" \(page A-7\)](#) in [Oracle Text Result Tables](#) (page A-1)

To store results in memory, specify the name of the CLOB locator. If `restab` is `NULL`, then a temporary CLOB is allocated and returned. You must de-allocate the locator after using it.

If `restab` is not `NULL`, then the CLOB is truncated before the operation.

query_id

Specify an identifier to use to identify the row(s) inserted into `restab`.

glevel

Specify the type of gist or theme summary to produce. The possible values are:

- *P* for paragraph
- *S* for sentence

The default is *P*.

pov

Specify whether a gist or a single theme summary is generated. The type of gist or theme summary generated (sentence-level or paragraph-level) depends on the value specified for `glevel`.

To generate a gist for the entire document, specify a value of 'GENERIC' for `pov`. To generate a theme summary for a single theme in a document, specify the theme as the value for `pov`.

When using result table storage, if you do not specify a value for `pov`, then this procedure returns the generic gist plus up to 50 theme summaries for the document.

When using in-memory result storage to a CLOB, you must specify a `pov`. However, if you do not specify a `pov`, then this procedure generates only a generic gist for the document.

Note:

The `pov` parameter is case sensitive. To return a gist for a document, specify 'GENERIC' in all uppercase. To return a theme summary, specify the theme exactly as it is generated for the document.

Only the themes generated by [THEMES](#) (page 9-44) for a document can be used as input for `pov`.

numParagraphs

Specify the maximum number of document paragraphs (or sentences) selected for the document gist or theme summaries. The default is 16.

Note:

The `numParagraphs` parameter is used only when this parameter yields a smaller gist or theme summary size than the gist or theme summary size yielded by the `maxPercent` parameter.

This means that the system always returns the smallest size gist or theme summary.

maxPercent

Specify the maximum number of document paragraphs (or sentences) selected for the document gist or theme summaries as a percentage of the total paragraphs (or sentences) in the document. The default is 10.

Note:

The `maxPercent` parameter is used only when this parameter yields a smaller gist or theme summary size than the gist or theme summary size yielded by the `numParagraphs` parameter.

This means that the system always returns the smallest size gist or theme summary.

num_themes

Specify the number of theme summaries to produce when you do not specify a value for `pov`. For example, if you specify 10, this procedure returns the top 10 theme summaries. The default is 50.

If you specify 0 or NULL, then this procedure returns all themes in a document. If the document contains more than 50 themes, only the top 50 themes show conceptual hierarchy.

use_saved_copy

Specify whether to refer to the \$D table to fetch the copy of the document, and what action to take when the copy of the document is not available in the \$D table.

You can specify one of the following values for the use_saved_copy parameter:

- `CTX_DOC.SAVE_COPY_FALLBACK`: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then fetch the document from the data store.
- `CTX_DOC.SAVE_COPY_ERROR`: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then show an error message. Specify this value when you want to implement a specific fallback logic when the copy of the document is not available in the \$D table.
- `CTX_DOC.SAVE_COPY_IGNORE`: Always fetch the document from the data store.

The default value is `CTX_DOC.SAVE_COPY_FALLBACK`.

Examples**In-Memory Gist**

The following example generates a non-default size generic gist of at most 10 paragraphs. The result is stored in memory in a CLOB locator. The code then de-allocates the returned CLOB locator after using it.

```
set serveroutput on;
declare
  gklob clob;
  amt number := 40;
  line varchar2(80);

begin
  ctx_doc.gist('newsindex','34',gklob, pov => 'GENERIC',numParagraphs => 10);
  -- gklob is NULL when passed-in, so ctx-doc.gist will allocate a temporary
  -- CLOB for us and place the results there.

  dbms_lob.read(gklob, amt, 1, line);
  dbms_output.put_line('FIRST 40 CHARS ARE:'||line);
  -- have to de-allocate the temp lob
  dbms_lob.freetemporary(gklob);
end;
```

Result Table Gists

The following example creates a gist table called `CTX_GIST`:

```
create table CTX_GIST (query_id number,
                      pov      varchar2(80),
                      gist      CLOB);
```

Gists and Theme Summaries

The following example returns a default sized paragraph-level gist for document 34 as well as the top 10 theme summaries in the document:

```
begin
  ctx_doc.gist('newsindex','34','CTX_GIST', 1, num_themes=>10);
end;
```

The following example generates a non-default size gist of at most 10 paragraphs:

```
begin
  ctx_doc.gist('newsindex','34','CTX_GIST',1,pov =>'GENERIC',numParagraphs=>10);
end;
```

The following example generates a gist whose number of paragraphs is at most 10 percent of the total paragraphs in document:

```
begin
  ctx_doc.gist('newsindex','34','CTX_GIST',1,pov => 'GENERIC', maxPercent => 10);
end;
```

Theme Summary

The following example returns a paragraph-level theme summary for *insects* for document 34. The default theme summary size is returned.

```
begin
  ctx_doc.gist('newsindex','34','CTX_GIST',1, pov => 'insects');
end;
```

9.4 HIGHLIGHT

Use the `CTX_DOC.HIGHLIGHT` procedure to generate highlight offsets for a document. The offset information is generated for the terms in the document that satisfy the query you specify. These highlighted terms are either the words that satisfy a word query or the themes that satisfy an ABOUT query.

You can generate highlight offsets for either plaintext or HTML versions of the document. The table returned by `CTX_DOC.HIGHLIGHT` does not include any graphics found in the original document. Apply the offset information to the same documents filtered with `CTX_DOC.FILTER` (page 9-2).

You usually call this procedure after a query, from which you identify the document to be processed. You can store the highlight offsets to either an in-memory PL/SQL table or a result table.

Note that for queries that have predicates used mainly for filtering documents at query time, the predicates are ignored during highlighting. This applies to `SNIPPET`, `MARKUP` and `HIGHLIGHT` procedures. The following predicates are treated as filter predicates for this purpose: `SDATA`, `HASPATH`, and `WITHIN/INPATH` searching inside XML attributes.

See `CTX_DOC.POLICY_HIGHLIGHT` (page 9-23) for a version of this procedure that does not require an index.

The performance of the procedures `SNIPPET` (page 9-40), `HIGHLIGHT`, and `MARKUP` (page 9-13) can be improved by using the forward index feature of Oracle Text.

See Also:

Oracle Text Application Developer's Guide for more information about forward index

Syntax 1: In-Memory Result Storage

```
exec CTX_DOC.HIGHLIGHT(
  index_name IN VARCHAR2,
  textkey    IN VARCHAR2,
```

```
text_query  IN VARCHAR2,
restab      IN OUT NOCOPY HIGHLIGHT_TAB,
plaintext   IN BOOLEAN  DEFAULT FALSE,
use_saved_copy IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);

exec CTX_DOC.HIGHLIGHT_CLOB_QUERY(
    index_name IN VARCHAR2,
    textkey    IN VARCHAR2,
    text_query IN CLOB,
    restab     IN OUT NOCOPY HIGHLIGHT_TAB,
    plaintext   IN BOOLEAN DEFAULT FALSE,
    use_saved_copy IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);
```

Syntax 2: Result Table Storage

```
exec CTX_DOC.HIGHLIGHT(
    index_name IN VARCHAR2,
    textkey    IN VARCHAR2,
    text_query IN VARCHAR2,
    restab     IN VARCHAR2,
    query_id   IN NUMBER  DEFAULT 0,
    plaintext   IN BOOLEAN DEFAULT FALSE,
    use_saved_copy IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);

exec CTX_DOC.HIGHLIGHT_CLOB_QUERY(
    index_name IN VARCHAR2,
    textkey    IN VARCHAR2,
    text_query IN CLOB,
    restab     IN VARCHAR2,
    query_id   IN NUMBER DEFAULT 0,
    plaintext   IN BOOLEAN DEFAULT FALSE,
    use_saved_copy IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);
```

index_name

Specify the name of the index associated with the text column containing the document identified by `textkey`.

textkey

Specify the unique identifier (usually the primary key) for the document.

The `textkey` parameter can be as follows:

- a single column primary key value
- encoded specification for a composite (multiple column) primary key. Use the `CTX_DOC.PKENCODER` (page 9-19) procedure.
- the rowid of the row containing the document

Toggle between primary key and rowid identification using `CTX_DOC.SET_KEY_TYPE` (page 9-40).

text_query

Specify the original query expression used to retrieve the document. If NULL, no highlights are generated.

If `text_query` includes wildcards, stemming, fuzzy matching which result in stopwords being returned, `HIGHLIGHT` does not highlight the stopwords.

If `text_query` contains the threshold operator, the operator is ignored. The `HIGHLIGHT` procedure always returns highlight information for the entire result set.

restab

You can specify that this procedure store highlight offsets to either a table or to an in-memory PL/SQL table.

To store results to a table specify the name of the table. The table must exist before you call this procedure.

See Also:

"[Highlight Table](#) (page A-7)" in [Oracle Text Result Tables](#) (page A-1) for more information about the structure of the highlight result table.

To store results to an in-memory table, specify the name of the in-memory table of type `CTX_DOC.HIGHLIGHT_TAB`. The `HIGHLIGHT_TAB` datatype is defined as follows:

```
type highlight_rec is record (
    offset number,
    length number
);
type highlight_tab is table of highlight_rec index by binary_integer;
```

`CTX_DOC.HIGHLIGHT` clears `HIGHLIGHT_TAB` before the operation.

query_id

Specify the identifier used to identify the row inserted into `restab`. When `query_id` is not specified or set to `NULL`, it defaults to 0. You must manually truncate the table specified in `restab`.

plaintext

Specify `TRUE` to generate a plaintext offsets of the document. Specify `FALSE` to generate HTML offsets of the document if you are using the `AUTO_FILTER` filter or indexing HTML documents.

use_saved_copy

Specify whether to refer to the `$D` table to fetch the copy of the document, and what action to take when the copy of the document is not available in the `$D` table. The default value is `CTX_DOC.SAVE_COPY_FALLBACK`.

You can specify one of the following values for the `use_saved_copy` parameter:

- `CTX_DOC.SAVE_COPY_FALLBACK`: Fetch the copy of the document from the `$D` table. If the copy of the document is not present in the `$D` table, then fetch the document from the data store.
- `CTX_DOC.SAVE_COPY_ERROR`: Fetch the copy of the document from the `$D` table. If the copy of the document is not present in the `$D` table, then show an error message. Specify this value when you want to implement a specific fallback logic when the copy of the document is not available in the `$D` table.
- `CTX_DOC.SAVE_COPY_IGNORE`: Always fetch the document from the data store.

Examples

Create Highlight Table

Create the highlight table to store the highlight offset information:

```
create table hightab(query_id number,
                    offset number,
                    length number);
```

Word Highlighting in the Presence of Filters

When performing highlight on queries such as the following, only the keyword ("dog" in these examples) will be highlighted. The filtering predicates after the AND operator will be ignored.

```
begin
ctx_doc.highlight('newsindex', '20', 'dog AND cat WITHIN titlesection@name',
'hightab', 0, FALSE);
end;
begin
ctx_doc.highlight('newsindex', '20', 'dog AND SDATA(price > 100)', 'hightab', 0,
FALSE);
end;
```

Word Highlight Offsets

To obtain HTML highlight offset information for document 20 for the word *dog*:

```
begin
ctx_doc.highlight('newsindex', '20', 'dog', 'hightab', 0, FALSE);
end;

begin
ctx_doc.highlight('newsindex', '20', 'dog AND cat WITHIN titlesection', 'hightab',
0, FALSE);
end;
```

Theme Highlight Offsets

Assuming the index *newsindex* has a theme component, obtain HTML highlight offset information for the theme query of *politics* by issuing the following query:

```
begin
ctx_doc.highlight('newsindex', '20', 'about(politics)', 'hightab', 0, FALSE);
end;
```

The output for this statement are the offsets to highlighted words and phrases that represent the theme of *politics* in the document.

Restrictions

CTX_DOC.HIGHLIGHT does not support the use of query templates or highlighting XML attribute values.

Related Topics

["POLICY_HIGHLIGHT \(page 9-23\)"](#)

["MARKUP \(page 9-13\)"](#)

["SNIPPET \(page 9-40\)"](#)

9.5 IFILTER

Use this procedure to filter binary data to text.

This procedure takes binary data (BLOB IN), filters the data with the AUTO_FILTER filter, and writes the text version to a CLOB. (Any graphics in the original document are ignored.) CTX_DOC.IFILTER employs the safe callout, and it does not require an index, as CTX_DOC.FILTER does.

Note:

This procedure will not be supported in future releases. Applications should use CTX_DOC.POLICY_FILTER (page 9-20) instead.

Requirements

Because CTX_DOC.IFILTER employs the safe callout mechanism, the SQL*Net listener must be running and configured for extproc agent startup.

Syntax

```
CTX_DOC.IFILTER(data IN BLOB, text IN OUT NOCOPY CLOB);
```

data

Specify the binary data to be filtered.

text

Specify the destination CLOB. The filtered data is placed in here. This parameter must be a valid CLOB locator that is writable. Passing NULL or a non-writable CLOB will result in an error. Filtered text will be appended to the end of existing content, if any.

Example

The document text used in a MATCHES query can be VARCHAR2 or CLOB. It does not accept BLOB input, so you cannot match filtered documents directly. Instead, you must filter the binary content to CLOB using the AUTO_FILTER filter. Assuming the document data is in bind variable :doc_blob:

```
declare
  doc_text clob;
begin
  -- create a temporary CLOB to hold the document text
  dbms_lob.createtemporary(doc_text, TRUE, DBMS_LOB.SESSION);

  -- call ctx_doc.ifilter to filter the BLOB to CLOB data
  ctx_doc.ifilter(:doc_blob, doc_text);

  -- now do the matches query using the CLOB version
  for c1 in (select * from queries where matches(query_string, doc_text)>0)
  loop
    -- do what you need to do here
  end loop;

  dbms_lob.freetemporary(doc_text);
end;
```

9.6 MARKUP

The CTX_DOC.MARKUP procedure takes a query specification and a document textkey and returns a version of the document in which the query terms are marked up. These

marked-up terms are either the words that satisfy a word query or the themes that satisfy an ABOUT query.

You can set the marked-up output to be either plaintext or HTML. The marked-up document returned by `CTX_DOC.MARKUP` does not include any graphics found in the original document.

You can use one of the predefined tag sets for marking highlighted terms, including a tag sequence that enables HTML navigation.

You usually call `CTX_DOC.MARKUP` after a query, from which you identify the document to be processed.

You can store the marked-up document either in memory or in a result table.

Note that for queries that have predicates used mainly for filtering documents at query time, the predicates are ignored during MARKUP. The following predicates are treated as filter predicates for this purpose: `SDATA`, `HASPATH`, and `WITHIN/INPATH` searching inside XML attributes.

See `CTX_DOC.POLICY_MARKUP` (page 9-26) for a version of this procedure that does not require an index.

The performance of the procedures [SNIPPET](#) (page 9-40), [HIGHLIGHT](#) (page 9-9), and `MARKUP` can be improved by using the forward index feature of Oracle Text.

See Also:

Oracle Text Application Developer's Guide for more information about forward index

Note:

Oracle Text does not guarantee well-formed output from `CTX_DOC.MARKUP`, especially for terms that are already marked up with HTML or XML. In particular, unexpected nesting of markup tags may occasionally result.

Syntax 1: In-Memory Result Storage

```
exec CTX_DOC.MARKUP(  
  
  index_name      IN VARCHAR2,  
  textkey         IN VARCHAR2,  
  text_query      IN VARCHAR2,  
  restab          IN OUT NOCOPY CLOB,  
  plaintext       IN BOOLEAN   DEFAULT FALSE,  
  tagset          IN VARCHAR2  DEFAULT 'TEXT_DEFAULT',  
  starttag        IN VARCHAR2  DEFAULT NULL,  
  endtag          IN VARCHAR2  DEFAULT NULL,  
  prevtag         IN VARCHAR2  DEFAULT NULL,  
  nexttag         IN VARCHAR2  DEFAULT NULL,  
  use_saved_copy  IN NUMBER    DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);  
  
exec CTX_DOC.MARKUP_CLOB_QUERY(  
  index_name      IN VARCHAR2,  
  textkey         IN VARCHAR2,  
  text_query      IN CLOB,
```

```

restab          IN OUT NOCOPY CLOB,
plaintext       IN BOOLEAN DEFAULT FALSE,
tagset          IN VARCHAR2 DEFAULT 'TEXT_DEFAULT',
starttag        IN VARCHAR2 DEFAULT NULL,
endtag          IN VARCHAR2 DEFAULT NULL,
prevtag         IN VARCHAR2 DEFAULT NULL,
nexttag         IN VARCHAR2 DEFAULT NULL,
use_saved_copy  IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);

```

Syntax 2: Result Table Storage

```

exec CTX_DOC.MARKUP(

index_name      IN VARCHAR2,
textkey         IN VARCHAR2,
text_query      IN VARCHAR2,
restab          IN VARCHAR2,
query_id        IN NUMBER   DEFAULT 0,
plaintext       IN BOOLEAN   DEFAULT FALSE,
tagset          IN VARCHAR2   DEFAULT 'TEXT_DEFAULT',
starttag        IN VARCHAR2   DEFAULT NULL,
endtag          IN VARCHAR2   DEFAULT NULL,
prevtag         IN VARCHAR2   DEFAULT NULL,
nexttag         IN VARCHAR2   DEFAULT NULL,
use_saved_copy  IN NUMBER     DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);

exec CTX_DOC.MARKUP_CLOB_QUERY(
index_name      IN VARCHAR2,
textkey         IN CLOB,
text_query      IN VARCHAR2,
restab          IN VARCHAR2,
query_id        IN NUMBER     DEFAULT 0,
plaintext       IN BOOLEAN     DEFAULT FALSE,
tagset          IN VARCHAR2     DEFAULT 'TEXT_DEFAULT',
starttag        IN VARCHAR2     DEFAULT NULL,
endtag          IN VARCHAR2     DEFAULT NULL,
prevtag         IN VARCHAR2     DEFAULT NULL,
nexttag         IN VARCHAR2     DEFAULT NULL,
use_saved_copy  IN NUMBER     DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);

```

index_name

Specify the name of the index associated with the text column containing the document identified by `textkey`.

textkey

Specify the unique identifier (usually the primary key) for the document.

The `textkey` parameter can be as follows:

- A single column primary key value
- Encoded specification for a composite (multiple column) primary key. Use the [CTX_DOC.PKENCODE](#) (page 9-19) procedure.
- The rowid of the row containing the document

Toggle between primary key and rowid identification using [CTX_DOC.SET_KEY_TYPE](#) (page 9-40).

text_query

Specify the original query expression used to retrieve the document.

If `text_query` includes wildcards, stemming, fuzzy matching which result in stopwords being returned, MARKUP does not highlight the stopwords.

If `text_query` contains the threshold operator, the operator is ignored. The MARKUP procedure always returns highlight information for the entire result set.

restab

You can specify that this procedure store the marked-up text to either a table or to an in-memory CLOB.

To store results to a table specify the name of the table. The result table must exist before you call this procedure.

See Also:

For more information about the structure of the markup result table, see "[Markup Table](#) (page A-8)" in [Oracle Text Result Tables](#) (page A-1).

To store results in memory, specify the name of the CLOB locator. If `restab` is NULL, a temporary CLOB is allocated and returned. You must de-allocate the locator after using it.

If `restab` is not NULL, the CLOB is truncated before the operation.

query_id

Specify the identifier used to identify the row inserted into `restab`.

When `query_id` is not specified or set to NULL, it defaults to 0. You must manually truncate the table specified in `restab`.

plaintext

Specify TRUE to generate plaintext marked-up document. Specify FALSE to generate a marked-up HTML version of document if you are using the `AUTO_FILTER` filter or indexing HTML documents.

tagset

Specify one of the following predefined tag sets. The second and third columns show how the four different tags are defined for each `tagset`:

Tagset	Tag	Tag Value
TEXT_DEFAULT	starttag	<<<
TEXT_DEFAULT	endtag	>>>
HTML_DEFAULT	starttag	
HTML_DEFAULT	endtag	
HTML_NAVIGATE	starttag	
HTML_NAVIGATE	endtag	
HTML_NAVIGATE	prevtag	< /A>

Tagset	Tag	Tag Value
HTML_NAVIGATE	nexttag	> ;

starttag

Specify the character(s) inserted by MARKUP to indicate the start of a highlighted term.

The sequence of `starttag`, `endtag`, `prevtag` and `nexttag` with respect to the highlighted word is as follows:

```
... prevtag starttag word endtag nexttag...
```

endtag

Specify the character(s) inserted by MARKUP to indicate the end of a highlighted term.

prevtag

Specify the markup sequence that defines the tag that navigates the user to the previous highlight.

In the markup sequences `prevtag` and `nexttag`, you can specify the following offset variables which are set dynamically:

Offset Variable	Value
%CURNUM	the current offset number
%PREVNUM	the previous offset number
%NEXTNUM	the next offset number

See the description of the HTML_NAVIGATE "[tagset](#) (page 9-16)" for an example.

nexttag

Specify the markup sequence that defines the tag that navigates the user to the next highlight tag.

Within the markup sequence, you can use the same offset variables you use for `prevtag`. See the explanation for "[prevtag](#) (page 9-17)" and the HTML_NAVIGATE "[tagset](#) (page 9-16)" for an example.

use_saved_copy

Specify whether to refer to the \$D table to fetch the copy of the document, and what action to take when the copy of the document is not available in the \$D table.

You can specify one of the following values for the `use_saved_copy` parameter:

- `CTX_DOC.SAVE_COPY_FALLBACK`: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then fetch the document from the data store.
- `CTX_DOC.SAVE_COPY_ERROR`: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then show an error message. Specify this value when you want to implement a specific fallback logic when the copy of the document is not available in the \$D table.
- `CTX_DOC.SAVE_COPY_IGNORE`: Always fetch the document from the data store.

The default value is `CTX_DOC.SAVE_COPY_FALLBACK`.

Examples

In-Memory Markup

The following code takes document (*the dog chases the cat*), performs the assigned markup on it, and stores the result in memory.

```
set serveroutput on

drop table mark_tab;
create table mark_tab (id number primary key, text varchar2(80) );
insert into mark_tab values ('1', 'The dog chases the cat.');
```

```
create index mark_tab_idx on mark_tab(text)
      indextype is ctxsys.context parameters
      ('filter ctxsys.null_filter');
```

```
declare
mklob clob;
amt number := 40;
line varchar2(80);

begin
  ctx_doc.markup('mark_tab_idx','1','dog AND cat', mklob);
  -- mklob is NULL when passed-in, so ctx_doc.markup will
  -- allocate a temporary CLOB for us and place the results there.
  dbms_lob.read(mklob, amt, 1, line);
  dbms_output.put_line('FIRST 40 CHARS ARE:'||line);
  -- have to de-allocate the temp lob
  dbms_lob.freetemporary(mklob);
end;
/
```

The output from this example shows what the marked-up document looks like:

```
FIRST 40 CHARS ARE:  The <<<dog>>> chases the <<<cat>>>.
```

Markup Table

Create the highlight markup table to store the marked-up document as follows:

```
create table markuptab (query_id number,
                        document clob);
```

Word Highlighting in HTML

You can also store your MARKUP results in a table. To create HTML highlight markup for the words *dog* or *cat* for document 23, enter the following examples:

```
begin
  ctx_doc.markup(index_name => 'my_index',
                  textkey => '23',
                  text_query => 'dog|cat',
                  restab => 'markuptab',
                  query_id => '1',
                  tagset => 'HTML_DEFAULT');
```

```
end;
```

```
begin
  ctx_doc.markup(index_name => 'my_index',
                  textkey => '23',
                  text_query => 'dog AND cat WITHIN titlesection@name',
                  restab => 'markuptab',
```

```

        query_id => '1',
        tagset => 'HTML_DEFAULT');
end;

```

Word Highlighting in the Presence of Filters

When performing markup on queries such as the following, only the keyword ("dog" in these examples) will be marked up. The filtering predicates after the AND operator will be ignored.

```

begin
  ctx_doc.markup(index_name => 'my_index',
                 textkey => '23',
                 text_query => 'dog AND cat WITHIN titlesection@name',
                 restab => 'markuptab',
                 query_id => '1',
                 tagset => 'HTML_DEFAULT');
end;

begin
  ctx_doc.markup(index_name => 'my_index',
                 textkey => '23',
                 text_query => 'dog AND SDATA(price > 100)',
                 restab => 'markuptab',
                 query_id => '1',
                 tagset => 'HTML_DEFAULT');
end;

```

Theme Highlighting in HTML

To create HTML highlight markup for the theme of *politics* for document 23, enter the following statement:

```

begin
  ctx_doc.markup(index_name => 'my_index',
                 textkey => '23',
                 text_query => 'about(politics)',
                 restab => 'markuptab',
                 query_id => '1',
                 tagset => 'HTML_DEFAULT');
end;

```

Restrictions

CTX_DOC.MARKUP does not support the use of query templates.

Related Topics

["POLICY_MARKUP \(page 9-26\)"](#)

["SNIPPET \(page 9-40\)"](#)

9.7 PKENCODE

The CTX_DOC.PKENCODE function converts a composite textkey list into a single string and returns the string.

The string created by PKENCODE can be used as the primary key parameter textkey in other CTX_DOC procedures, such as CTX_DOC.THEMES (page 9-44) and CTX_DOC.GIST (page 9-5).

Syntax

```
CTX_DOC.PKENCOD(  
    pk1    IN VARCHAR2,  
    pk2    IN VARCHAR2 DEFAULT NULL,  
    pk4    IN VARCHAR2 DEFAULT NULL,  
    pk5    IN VARCHAR2 DEFAULT NULL,  
    pk6    IN VARCHAR2 DEFAULT NULL,  
    pk7    IN VARCHAR2 DEFAULT NULL,  
    pk8    IN VARCHAR2 DEFAULT NULL,  
    pk9    IN VARCHAR2 DEFAULT NULL,  
    pk10   IN VARCHAR2 DEFAULT NULL,  
    pk11   IN VARCHAR2 DEFAULT NULL,  
    pk12   IN VARCHAR2 DEFAULT NULL,  
    pk13   IN VARCHAR2 DEFAULT NULL,  
    pk14   IN VARCHAR2 DEFAULT NULL,  
    pk15   IN VARCHAR2 DEFAULT NULL,  
    pk16   IN VARCHAR2 DEFAULT NULL)  
RETURN VARCHAR2;
```

pk1-pk16

Each PK argument specifies a column element in the composite textkey list. You can encode at most 16 column elements.

Returns

String that represents the encoded value of the composite textkey.

Example

```
begin  
ctx_doc.gist('newsindex',CTX_DOC.PKENCOD('smith', 14), 'CTX_GIST');  
end;
```

In this example, *smith* and *14* constitute the composite textkey value for the document.

9.8 POLICY_FILTER

Generates a plain text or an HTML version of a document. With this procedure, no CONTEXT index is required.

This procedure uses a trusted callout.

Syntax

```
ctx_doc.policy_filter(policy_name    in  VARCHAR2,  
                      document      in  [VARCHAR2|CLOB|BLOB|BFILE],  
                      restab        in  out nocopy CLOB,  
                      plaintext      in  BOOLEAN default FALSE,  
                      language       in  VARCHAR2 default NULL,  
                      format         in  VARCHAR2 default NULL,  
                      charset        in  VARCHAR2 default NULL);
```

policy_name

Specify the policy name created with CTX_DDL.[CREATE_POLICY](#) (page 8-30).

document

Specify the document to filter.

restab

Specify the name of the CLOB locator.

plaintext

Specify TRUE to generate a plaintext version of the document. Specify FALSE to generate an HTML version of the document if you are using the AUTO_FILTER filter or indexing HTML documents.

language

Specify the language of the document. Use an Oracle Text supported language value as you would in the language column of the base table. See [BASIC_LEXER](#) (page 2-41) in [Oracle Text Indexing Elements](#) (page 2-1).

format

Specify the format of the document. Use an Oracle Text supported format value, either TEXT, BINARY or IGNORE as you would specify in the format column of the base table. For more information, see the format column description in [CREATE INDEX](#) (page 1-40) in [Oracle Text SQL Statements and Operators](#) (page 1-1).

charset

Specify the character set of the document. Use an Oracle Text supported value as you would specify in the charset column of the base table. See [Filter Types](#) (page 2-19)".

9.9 POLICY_GIST

Generates a gist or theme summary for document. You can generate paragraph-level or sentence-level gists or theme summaries. With this procedure, no CONTEXT index is required.

Syntax

```
ctx_doc.policy_gist(policy_name      in VARCHAR2,
                    document         in [VARCHAR2|CLOB|BLOB|BFILE],
                    restab           in out nocopy CLOB,
                    glevel           in VARCHAR2 default 'P',
                    pov              in VARCHAR2 default 'GENERIC',
                    numParagraphs    in VARCHAR2 default NULL,
                    maxPercent       in NUMBER default NULL,
                    num_themes       in NUMBER default 50
                    language         in VARCHAR2 default NULL,
                    format           in VARCHAR2 default NULL,
                    charset          in VARCHAR2 default NULL
                    );
```

policy_name

Specify the policy name created with CTX_DDL.[CREATE_POLICY](#) (page 8-30).

document

Specify the document for which to generate the Gist or theme summary.

restab

Specify the name of the CLOB locator.

glevel

Specify the type of gist or theme summary to produce. The possible values are:

- *P* for paragraph
- *S* for sentence

The default is *P*.

pov

Specify whether a gist or a single theme summary is generated. The type of gist or theme summary generated (sentence-level or paragraph-level) depends on the value specified for `glevel`.

To generate a gist for the entire document, specify a value of 'GENERIC' for `pov`. To generate a theme summary for a single theme in a document, specify the theme as the value for `pov`.

When using result table storage and you do not specify a value for `pov`, this procedure returns the generic gist plus up to 50 theme summaries for the document.

Note:

The `pov` parameter is case sensitive. To return a gist for a document, specify 'GENERIC' in all uppercase. To return a theme summary, specify the theme *exactly* as it is generated for the document.

Only the themes generated by [THEMES](#) (page 9-44) for a document can be used as input for `pov`.

numParagraphs

Specify the maximum number of document paragraphs (or sentences) selected for the document gist or theme summaries. The default is 16.

Note:

The `numParagraphs` parameter is used only when this parameter yields a smaller gist or theme summary size than the gist or theme summary size yielded by the `maxPercent` parameter.

This means that the system always returns the smallest size gist or theme summary.

maxPercent

Specify the maximum number of document paragraphs (or sentences) selected for the document gist or theme summaries as a percentage of the total paragraphs (or sentences) in the document. The default is 10.

Note:

The `maxPercent` parameter is used only when this parameter yields a smaller gist or theme summary size than the gist or theme summary size yielded by the `numParagraphs` parameter.

This means that the system always returns the smallest size gist or theme summary.

num_themes

Specify the number of theme summaries to produce when you do not specify a value for `pov`. For example, if you specify 10, this procedure returns the top 10 theme summaries. The default is 50.

If you specify 0 or NULL, this procedure returns all themes in a document. If the document contains more than 50 themes, only the top 50 themes show conceptual hierarchy.

language

Specify the language of the document. Use an Oracle Text supported language value as you would in the language column of the base table. See "[MULTI_LEXER](#) (page 2-49)".

format

Specify the format of the document. Use an Oracle Text supported format value, either TEXT, BINARY or IGNORE as you would specify in the format column of the base table. For more information, see the format column description in "[CREATE INDEX](#) (page 1-40)".

charset

Specify the character set of the document. Use an Oracle Text supported value as you would specify in the charset column of the base table.

9.10 POLICY_HIGHLIGHT

Generates plain text or HTML highlighting offset information for a document. With this procedure, no CONTEXT index is required.

The offset information is generated for the terms in the document that satisfy the query you specify. These highlighted terms are either the words that satisfy a word query or the themes that satisfy an ABOUT query.

You can generate highlight offsets for either plaintext or HTML versions of the document. You can apply the offset information to the same documents filtered with CTX_DOC.[FILTER](#) (page 9-2).

Syntax

```
exec ctx_doc.policy_highlight(
    policy_name in VARCHAR2,
    document    in [VARCHAR2|CLOB|BLOB|BFILE],
    text_query  in VARCHAR2,
    restab      in out nocopy highlight_tab,
    plaintext   in boolean FALSE
    language    in VARCHAR2 default NULL,
    format      in VARCHAR2 default NULL,
    charset     in VARCHAR2 default NULL
);

exec ctx_doc.policy_highlight_clob_query(
    policy_name in VARCHAR2,
    document    in [VARCHAR2|CLOB|BLOB|BFILE],
    text_query  in CLOB,
    restab      in out nocopy highlight_tab,
    plaintext   in boolean FALSE
    language    in VARCHAR2 default NULL,
    format      in VARCHAR2 default NULL,
```

```
                                charset          in VARCHAR2 default NULL  
);
```

policy_name

Specify the policy name created with CTX_DDL.[CREATE_POLICY](#) (page 8-30).

document

Specify the document to generate highlighting offset information.

text_query

Specify the original query expression used to retrieve the document. If NULL, no highlights are generated.

If `text_query` includes wildcards, stemming, or fuzzy matching which result in stopwords being returned, this procedure does not highlight the stopwords.

If `text_query` contains the threshold operator, the operator is ignored. This procedure always returns highlight information for the entire result set.

restab

Specify the name of the `highlight_tab` PL/SQL index-by-table type.

See Also:

["HIGHLIGHT](#) (page 9-9)" for more information about the structure of the `highlight_tab` table type

plaintext

Specify `TRUE` to generate a plaintext offsets of the document.

Specify `FALSE` to generate HTML offsets of the document if you are using the `AUTO_FILTER` filter or indexing HTML documents.

language

Specify the language of the document. Use an Oracle Text supported language value as you would in the language column of the base table. See ["MULTI_LEXER](#) (page 2-49)" in [Oracle Text Indexing Elements](#) (page 2-1).

format

Specify the format of the document. Use an Oracle Text supported format value, either `TEXT`, `BINARY` or `IGNORE` as you would specify in the format column of the base table. For more information, see the format column description under ["CREATE INDEX](#) (page 1-40)".

charset

Specify the character set of the document. Use an Oracle Text supported value as you would specify in the charset column of the base table.

Restrictions

`CTX_DOC.POLICY_HIGHLIGHT` does not support the use of query templates.

9.11 POLICY_LANGUAGES

Provides the ability to fetch the language for a section of text.

Returns a table of language descriptors and scores, where the score is the confidence level with which the system can assert that the supplied text is in the specific language.

Syntax

```
CTX_DOC.POLICY_LANGUAGES (  
    policy_name    IN VARCHAR2 | CLOB,  
    document       IN VARCHAR2,  
    restab         IN OUT NOCOPY CTX_DOC.LANGUAGE_TAB  
);
```

policy_name

A policy that was previously created using the CTX_DDL.[CREATE_POLICY](#) (page 8-30) method. If the specified policy includes a sectioning preference, the API will honor the sectioning preference. For instance, if HTML sectioning is specified, then HTML tags will be removed before processing the input document.

document

A body of text for which the languages are to be extracted. The text is assumed to be plain text with UTF-8 character encoding.

restab

The result of the language extraction process. The result is a table of records. Each record has two attributes: the language string, and the score for each language string. The score can range from 0 to 100 and represents the confidence with which the system can assert that the supplied text is in the specified language. The resulting languages are returned in sorted order with the language with the most confidence appearing first.

The table layout for `restab` is similar to that for `HIGHLIGHT`.

See Also:

"[HIGHLIGHT](#) (page 9-9)" for information on `restab` layout

Supported Languages for CTX_DOC.POLICY_LANGUAGES and POLICY_STEMS

Language extraction is supported for text in the languages supported by [AUTO_LEXER](#) (page 2-33). The supported languages for CTX_DOC.POLICY_LANGUAGES and CTX_DOC.[POLICY_STEMS](#) (page 9-36) for this release are:

Arabic
Bokmal
Catalan
Croatian
Czech
Danish
Dutch
English
Finnish

French
German
Greek
Hebrew
Hungarian
Italian
Japanese
Korean
Polish
Nynorsk
Persian
Portuguese
Romanian
Russian
Serbian
Slovak
Slovenian
Simplified Chinese
Spanish
Swedish
Thai
Traditional Chinese
Turkish

Related Topics

["POLICY_STEMS \(page 9-36\)"](#)

["AUTO_LEXER \(page 2-33\)"](#)

9.12 POLICY_MARKUP

Generates plain text or HTML version of a document with query terms highlighted. With this procedure, no CONTEXT index is required.

The CTX_DOC.POLICY_MARKUP procedure takes a query specification and a document and returns a version of the document in which the query terms are marked up. These marked-up terms are either the words that satisfy a word query or the themes that satisfy an ABOUT query.

You can set the marked-up output to be either plaintext or HTML.

You can use one of the predefined tag sets for marking highlighted terms, including a tag sequence that enables HTML navigation.

Syntax

```
ctx_doc.policy_markup(policy_name      in VARCHAR2,
                      document         in [VARCHAR2|CLOB|BLOB|BFILE],
                      text_query       in VARCHAR2,
                      restab           in out nocopy CLOB,
                      plaintext         in BOOLEAN default FALSE,
                      tagset           in VARCHAR2 default 'TEXT_DEFAULT',
                      starttag         in VARCHAR2 default NULL,
                      endtag           in VARCHAR2 default NULL,
                      prevtag          in VARCHAR2 default NULL,
                      nexttag          in VARCHAR2 default NULL,
                      language         in VARCHAR2 default NULL,
                      format           in VARCHAR2 default NULL,
                      charset           in VARCHAR2 default NULL
);

ctx_doc.policy_markup_clob_query(
    policy_name      in VARCHAR2,
    document         in [VARCHAR2|CLOB|BLOB|BFILE],
    text_query       in CLOB,
    restab           in out nocopy CLOB,
    plaintext         in BOOLEAN default FALSE,
    tagset           in VARCHAR2 default 'TEXT_DEFAULT',
    starttag         in VARCHAR2 default NULL,
    endtag           in VARCHAR2 default NULL,
    prevtag          in VARCHAR2 default NULL,
    nexttag          in VARCHAR2 default NULL,
    language         in VARCHAR2 default NULL,
    format           in VARCHAR2 default NULL,
    charset           in VARCHAR2 default NULL
);
```

policy_name

Specify the policy name created with CTX_DDL.[CREATE_POLICY](#) (page 8-30).

document

Specify the document to generate highlighting offset information.

text_query

Specify the original query expression used to retrieve the document.

If `text_query` includes a NULL, then this procedure will fail and generate errors.

If `text_query` includes wildcards, stemming, or fuzzy matching which result in stopwords being returned, then this procedure does not highlight the stopwords.

If `text_query` contains the threshold operator, the operator is ignored. This procedure always returns highlight information for the entire result set.

restab

Specify the name of the CLOB locator.

plaintext

Specify TRUE to generate a plaintext marked-up document. Specify FALSE to generate a marked-up HTML version of the document if you are using the `AUTO_FILTER` filter or indexing HTML documents.

tagset

Specify one of the following predefined tag sets. The second and third columns show how the four different tags are defined for each tagset:

Tagset	Tag	Tag Value
TEXT_DEFAULT	starttag	<<<
TEXT_DEFAULT	endtag	>>>
HTML_DEFAULT	starttag	
HTML_DEFAULT	endtag	
HTML_NAVIGATE	starttag	
HTML_NAVIGATE	endtag	
HTML_NAVIGATE	prevtag	< ;
HTML_NAVIGATE	nexttag	> ;

starttag

Specify the character(s) inserted by MARKUP to indicate the start of a highlighted term.

The sequence of `starttag`, `endtag`, `prevtag` and `nexttag` with regard to the highlighted word is as follows:

```
... prevtag starttag word endtag nexttag...
```

endtag

Specify the character(s) inserted by MARKUP to indicate the end of a highlighted term.

prevtag

Specify the markup sequence that defines the tag that navigates the user to the previous highlight.

In the markup sequences `prevtag` and `nexttag`, you can specify the following offset variables which are set dynamically:

Offset Variable	Value
%CURNUM	the current offset number
%PREVNUM	the previous offset number
%NEXTNUM	the next offset number

See the description of the `HTML_NAVIGATE` tagset for an example "[tagset](#) (page 9-16)".

nexttag

Specify the markup sequence that defines the tag that navigates the user to the next highlight tag.

Within the markup sequence, you can use the same offset variables you use for `prevtag`. See the explanation for `prevtag` and the `HTML_NAVIGATE` "[tagset](#) (page 9-16)" for an example.

language

Specify the language of the document. Use an Oracle Text supported language value as you would in the language column of the base table. See "[MULTI_LEXER](#) (page 2-49)" in [Oracle Text Indexing Elements](#) (page 2-1).

format

Specify the format of the document. Use an Oracle Text supported format value, either TEXT, BINARY or IGNORE as you would specify in the format column of the base table. For more information, see the format column description in "[CREATE INDEX](#) (page 1-40)".

charset

Specify the character set of the document. Use an Oracle Text supported value as you would specify in the charset column of the base table. See "[Filter Types](#) (page 2-19)".

Restrictions

CTX_DOC.POLICY_MARKUP does not support the use of query templates.

9.13 POLICY_NOUN_PHRASES

Provides the ability to extract the noun phrases along with part-of-speech information for each word in each noun phrase from a given document.

For example, consider the following sentence:

"The mayor of Chicago is giving a brief press conference."

The noun phrases for this input are "mayor of Chicago" and "brief press conference." The subgroups in the input text are not returned. For instance, in the above example, subgroups such as "mayor,Chicago, brief press, press conference, press, conference" are not returned.

POLICY_NOUN_PHRASES (and [POLICY_PART_OF_SPEECH](#) (page 9-32)) supports the following languages:

- Dutch
- English
- German
- French
- Italian
- Japanese
- Korean
- Simplified Chinese
- Spanish
- Traditional Chinese

Syntax

```
ctx_doc.policy_noun_phrases (  
    policy_name    in varchar2,
```

```
document      in varchar2 | CLOB,  
restab        in out nocopy noun_phrase_tab,  
language      in varchar2 default NULL,  
format        in varchar2 default NULL,  
charset       in varchar2 default NULL  
);
```

policy_name

Specify the policy name created with CTX_DDL.[CREATE_POLICY](#) (page 8-30).

document

A body of text for which the languages are to be extracted. The text is assumed to be plain text with UTF-8 character encoding.

restab

Specify the name of the CLOB locator.

language

Specify the language. See the list of supported languages in this section. If this parameter is null, the language will be automatically detected. There is a cost associated with language detection.

format

The format of the input text.

charset

The character set of the input text.

Abbreviations for Use with POLICY_NOUN_PHRASES and POLICY_PART_OF_SPEECH

[Table 9-1](#) (page 9-30) provides a list of abbreviations to use in queries for POLICY_NOUN_PHRASES and POLICY_PART_OF_SPEECH. The examples use these abbreviations.

Table 9-1 *Part of Speech Abbreviations*

Abbreviation	Part of Speech
N	noun
propN	nounProper
V	verb
Adj	adjective
Adv	adverb
Prep	preposition
Part	particle
Punct	punct
Pro	pronoun

Table 9-1 (Cont.) Part of Speech Abbreviations

Abbreviation	Part of Speech
Wh	interrog
Det	determiner
Conj	conjunction
Card	numCardinal
Ord	numOrdinal
Suf	suffix
Pre	prefix
Acr	nounAcronym
Poss	poss
Unk	unknown

Example for POLICY__NOUN_PHRASES

The example in this section uses the abbreviations shown in [Table 9-1](#) (page 9-30).

```

set serverout on
create or replace function toString(b boolean) return varchar2 is
begin
    if (b) then
        return 'TRUE';
    end if;
    return 'FALSE';
end;
/

declare
    the_nps ctx_doc.noun_phrase_tab;
begin
    ctx_ddl.create_preference('rvlex', 'AUTO_LEXER');
    ctx_ddl.set_attribute('rvlex','mixed_case','YES');
    ctx_ddl.set_attribute('rvlex','timeout',0);

    ctx_ddl.create_policy(policy_name => 'rv_policy_21',lexer => 'rvlex');

    ctx_doc.policy_noun_phrases('rv_policy_21','The mayor of Chicago is giving a
    brief press conference',the_nps);
    dbms_output.put_line(the_nps.count);

    for i in 1..the_nps.count loop
        if (the_nps(i).is_phrase_start) then
            if (i>1) then
                dbms_output.put(' ');
                dbms_output.new_line;
            end if;
            dbms_output.put('Phrase{term,POS,is_in_lex,offset,len,is_phrase_
            start}:['');

```

```
        else
            dbms_output.put(',');
        end if;
        dbms_output.put('{ ' || the_nps(i).term || ', ' || the_nps(i).pos_tag || ', '
            || toString(the_nps(i).is_in_lexicon) || ', ' || the_nps(i).offset
            || ', ' || the_nps(i).length || ', ' || toString(the_nps(i).is_phrase_start)
            || ' }');
        end loop;
        dbms_output.put(']');
        dbms_output.new_line;
    end;
/
```

Output for this example:

```
Phrase{term,POS,is_in_lex,offset,len,is_phrase_start}:
[{The,Det,TRUE,1,3,TRUE},{mayor,N,TRUE,5,5,FALSE},
{of,Prep,TRUE,11,2,FALSE},{Chicago,propN,TRUE,14,7,FALSE}]
```

```
Phrase{term,POS,is_in_lex,offset,len,is_phrase_start}:
[{a,Det,TRUE,32,1,TRUE},{brief,N,TRUE,34,5,FALSE},
{press,N,TRUE,40,5,FALSE},{conference,N,TRUE,46,10,FALSE}]
```

Related Topics

["POLICY_PART_OF_SPEECH \(page 9-32\)"](#)

9.14 POLICY_PART_OF_SPEECH

Extracts part of speech information for each word in a body of text.

[POLICY_NOUN_PHRASES \(page 9-29\)](#) has the list of supported languages.

Syntax

```
ctx_doc.policy_part_of_speech (
    policy_name      in varchar2,
    document         in varchar2 | CLOB,
    restab           in out nocopy noun_phrase_tab,
    language         in varchar2 default NULL,
    format           in varchar2 default NULL,
    charset          in varchar2 default NULL,
    disambiguate_tags in boolean default TRUE
);
```

policy_name

Specify the policy name created with CTX_DDL.[CREATE_POLICY \(page 8-30\)](#). If the specified policy includes a sectioning preference, the API will honor the sectioning preference. For instance, if HTML sectioning is specified, HTML tags will be removed before processing the input document.

document

A body of text for which the languages are to be extracted. The text is assumed to be plain text with UTF-8 character encoding.

restab

Specify the name of the CLOB locator. The query returns a table with the result of the noun phrase extraction. For each word, the following attributes are also returned:

- **pos_tags**: the part of speech tags for this word. There can be multiple part of speech tags with the most likely tag listed first.
- **offset**: offset of the word in the input string
- **length**: length of the word in the input string.
- **is_in_lexicon**: Indicates whether the word is in the lexicon.

language

Specify the language. See the list of supported languages in this section. If this parameter is null, the language will be automatically detected. There is a cost associated with language detection.

format

The format of the input text.

charset

The character set of the input text.

Example for POLICY_PART_OF_SPEECH

The example in this section uses the abbreviations shown in [Table 9-1](#) (page 9-30).

```
set serveroutput on;
declare
    the_nps ctx_doc.part_of_speech_tab;
begin
    ctx_doc.policy_part_of_speech(policy_name => 'rv_policy_21',
                                document => 'The mayor of Chicago is giving
                                              a brief press conference',
                                restab => the_nps,
                                disambiguate_tags => false,
                                language => 'english');

    for i in 1..the_nps.count loop
        dbms_output.put('word:' || the_nps(i).word || ',pos:');
        for j in 1..the_nps(i).pos_tags.count loop
            dbms_output.put(the_nps(i).pos_tags(j) || ',');
        end loop;
        dbms_output.put_line('');
    end loop;
end;
/
```

Output for this example:

```
word:The,pos:[Det,]
word:mayor,pos:[N,]
word:of,pos:[Prep,]
word:Chicago,pos:[propN,]
word:is,pos:[V,]
word:giving,pos:[N,V,Adj,]
word:a,pos:[Det,]
word:brief,pos:[N,V,Adj,]
word:press,pos:[N,V,]
word:conference,pos:[N,V,]
```

Related Topics

["POLICY_NOUN_PHRASES](#) (page 9-29)"

["Custom Dictionary Valid Parts-of-Speech \(case sensitive\) \(page 6-3\)"](#)

9.15 POLICY_SNIPPET

Displays marked-up keywords in context. The returned text contains either the words that satisfy a word query or the themes that satisfy an ABOUT query. This version of the CTX_DOC.[SNIPPET](#) (page 9-40) procedure does not require an index.

Syntax

Syntax 1

```
exec CTX_DOC.POLICY_SNIPPET(  
  
  policy_name          IN VARCHAR2,  
  document             IN [VARCHAR2|CLOB|BLOB|BFILE],  
  text_query          IN VARCHAR2,  
  language             IN VARCHAR2 default NULL,  
  format              IN VARCHAR2 default NULL,  
  charset              IN VARCHAR2 default NULL,  
  starttag            IN VARCHAR2 DEFAULT '<b>',  
  endtag              IN VARCHAR2 DEFAULT '</b>',  
  entity_translation   IN BOOLEAN  DEFAULT TRUE,  
  separator           IN VARCHAR2 DEFAULT '<b>...</b>',  
  radius              IN INTEGER  DEFAULT 25,  
  max_length          IN INTEGER  DEFAULT 250  
)  
return varchar2;
```

Syntax 2

```
exec CTX_DOC.POLICY_SNIPPET_CLOB_QUERY(  
  policy_name          IN VARCHAR2,  
  document             IN [VARCHAR2|CLOB|BLOB|BFILE],  
  text_query          IN CLOB,  
  language             IN VARCHAR2 default NULL,  
  format              IN VARCHAR2 default NULL,  
  charset              IN VARCHAR2 default NULL,  
  starttag            IN VARCHAR2 DEFAULT '<b>',  
  endtag              IN VARCHAR2 DEFAULT '</b>',  
  entity_translation   IN BOOLEAN  DEFAULT TRUE,  
  separator           IN VARCHAR2 DEFAULT '<b>...</b>',  
  radius              IN INTEGER  DEFAULT 25,  
  max_length          IN INTEGER  DEFAULT 250  
)  
return varchar2;
```

policy_name

Specify the name of a policy created with CTX_DDL.[CREATE_POLICY](#) (page 8-30).

document

Specify the document in which to search for keywords.

text_query

Specify the original query expression used to retrieve the document. If NULL, no highlights are generated.

If `text_query` includes wildcards, stemming, fuzzy matching which result in stopwords being returned, `POLICY_SNIPPET` does not highlight the stopwords.

If `text_query` contains the threshold operator, the operator is ignored.

language

Specify the language of the document. Use an Oracle Text supported language value as you would in the language column of the base table. See [MULTI_LEXER](#) (page 2-49) in [Oracle Text Indexing Elements](#) (page 2-1).

format

Specify the format of the document. Use an Oracle Text supported format value, either TEXT, BINARY or IGNORE as you would specify in the format column of the base table. For more information, see the format column description in "[CREATE INDEX](#) (page 1-40)".

charset

Specify the character set of the document. Use an Oracle Text supported value as you would specify in the charset column of the base table. See "[Filter Types](#) (page 2-19)".

starttag

Specify the start tag for marking up the query keywords. Default is '``'.

endtag

Specify the end tag for marking up the query keywords. Default is '``'.

entity_translation

Specify if you want HTML entities to be translated. The default is TRUE, which means the special entities (<, >, and &) are translated into their alternate forms ('<', '>', and '&') when output by the procedure. However, special characters in the markup tags generated by `CTX_DOC.POLICY_SNIPPET` will not be translated.

separator

Specify the string separating different returned fragments. Default is '`...`'.

radius

Specify the number of characters to be shown on either side of the hit query in a segment. The character count before the hit query begins on the first character of the first hit query displayed in a segment. Accordingly, the character count after the hit query begins on the last character of the last hit query displayed on a specific segment. Two segments are merged into one if their radii overlap. The displayed number of characters on each side may be modified by +/-10 chars to best match the beginning or ending of a sentence or word.

Special attention is required for the value 0. When specified, the radius is set to automatic and varies between sentences. A best guess of the results is displayed, which attempts to match a full sentence. Note that the length of the radius on each side of the hit query will most likely significantly differ.

The default value is 25.

max_length

Specify the maximum length of the snippet output in characters. This value is currently upper-bounded by the current return type of `CTX_DOC.SNIPPET` (page 9-40) and `CTX_DOC.POLICY_SNIPPET` (VARCHAR2). Should the output be longer than the return type VARCHAR2, the result will be truncated.

The default value for `max_length` is 250.

Note:

If you set `max_length` value to a very low value, no snippet may be generated. For example, if `max_length` is set to 0 or if `max_length` is lower than the length of query tokens themselves, no snippet may be generated at all.

Limitations

`CTX_DOC.POLICY_SNIPPET` does not support the use of query templates.

`CTX_DOC.POLICY_SNIPPET` displays marked-up keywords in context when used with `NULL_SECTION_GROUP`. However, there are limitations when using this procedure with XML documents. When used with `XML_SECTION_GROUP` or `AUTO_SECTION_GROUP`, the XML structure is ignored and user-specified tags are stripped out, which results in parts of surrounding text to be included in the returned snippet.

Related Topics

["SNIPPET \(page 9-40\)"](#)

["MARKUP \(page 9-13\)"](#)

9.16 POLICY_STEMS

Extracts stems for each word in a body of text. This procedure is for use with [AUTO_LEXER](#) (page 2-33). This procedure can only use the languages supported by `AUTO_LEXER`, which are listed under ["POLICY_LANGUAGES \(page 9-24\)"](#).

Syntax

```
exec CTX_DOC.POLICY_STEMS (  
  policy_name  in varchar2,  
  document     in varchar2 | CLOB,  
  restab       in out nocopy ctx_doc.stem_group_tab,  
  language     in varchar2 default NULL,  
  format       in varchar2 default NULL,  
  charset      in varchar2 default NULL  
);
```

policy_name

A policy that was previously created using the `CTX_DDL.CREATE_POLICY` (page 8-30) method. If the specified policy includes a `HTML_SECTION_GROUP` sectioning preference, the API will honor the sectioning preference. For instance, if HTML sectioning is specified, HTML tags will be removed before processing the input document.

Note that the policy must use `AUTO_LEXER` only.

document

A body of text for which the languages are to be extracted. The text is assumed to be plain text with UTF-8 character encoding.

restab

The result of the stem extraction process. The returned values in the PL/SQL table will have one cell for each word in the input string document. Each word can be a multi-word as determined by the lexer. For each word, all the stems (including all alternate stems) are returned. For each stem, the offset and the length (in the input string) of the word for which this is a stem is returned. Additionally, for each stem, a Boolean value is returned that indicates if the stem was found in the lexicon.

stem_group_tab is a table of stem_group_records.

language

The language of the input text. The language string can be one of the values specified in the previous section on language extraction. If this parameter is null, the language will be automatically detected. There is a cost associated with language detection. So, if the language is known, it is best to supply the language value. See ["POLICY_LANGUAGES \(page 9-24\)"](#) for the list of languages.

format

The format of the input text.

charset

The character set of the input text.

Restrictions and Notes

The stem extraction process supports certain nonstandard word forms—e.g. capitalization errors—as well as standard forms, and thus can be used to process informal or imperfect text (such as email, online documents, or queries). It also handles some variations in the text including case variation, hyphenation and unaccented characters among others.

The stem extraction process does not break compound words, but instead separates compound words with a # character. Such compound words are common in German. For instance, the German compound word *Bildungsroman* (from Bildung "education" and Roman "novel") yields a single stem Bildungs#roman instead of two stems *Bildungs* and *roman*.

Related Topics

["POLICY_LANGUAGES \(page 9-24\)"](#)

["AUTO_LEXER \(page 2-33\)"](#)

["CREATE_POLICY \(page 8-30\)"](#)

9.17 POLICY_THEMES

Generates a list of themes for a document. With this procedure, no CONTEXT index is required.

Syntax

```
ctx_doc.policy_themes(policy_name    in VARCHAR2,
                      document       in [VARCHAR2|CLOB|BLOB|BFILE],
                      restab         in out nocopy theme_tab,
                      full_themes    in BOOLEAN default FALSE,
                      num_themes     in number   default 50,
                      language       in VARCHAR2 default NULL,
```

```
format          in VARCHAR2 default NULL,  
charset         in VARCHAR2 default NULL  
);
```

policy_name

Specify the policy you create with CTX_DDL.[CREATE_POLICY](#) (page 8-30).

document

Specify the document for which to generate a list of themes.

restab

Specify the name of the theme_tab PL/SQL index-by-table type.

See Also:

["THEMES](#) (page 9-44)" for more information about the structure of the theme_tab type.

full_themes

Specify whether this procedure generates a single theme or a hierarchical list of parent themes (full themes) for each document theme.

Specify TRUE for this procedure to write full themes to the THEME column of the result table.

Specify FALSE for this procedure to write single theme information to the THEME column of the result table. This is the default.

num_themes

Specify the maximum number of themes to retrieve. For example, if you specify 10, up to first 10 themes are returned for the document. The default is 50.

If you specify 0 or NULL, this procedure returns all themes in a document. If the document contains more than 50 themes, only the first 50 themes show conceptual hierarchy.

language

Specify the language of the document. Use an Oracle Text supported language value as you would in the language column of the base table. See ["MULTI_LEXER](#) (page 2-49)" in [Oracle Text Indexing Elements](#) (page 2-1).

format

Specify the format of the document. Use an Oracle Text supported format value, either TEXT, BINARY or IGNORE as you would specify in the format column of the base table. For more information, see the format column description in ["CREATE INDEX](#) (page 1-40)" in [Oracle Text SQL Statements and Operators](#) (page 1-1).

charset

Specify the character set of the document. Use an Oracle Text supported value as you would specify in the charset column of the base table. See ["Filter Types](#) (page 2-19)".

Example

Create a policy:

```
exec ctx_ddl.create_policy('mypolicy');
```

Run themes:

```
declare
  la      varchar2(200);
  rtab    ctx_doc.theme_tab;
begin
  ctx_doc.policy_themes('mypolicy',
    'To define true madness, What is''t but to be nothing but mad?', rtab);
  for i in 1..rtab.count loop
    dbms_output.put_line(rtab(i).theme||':'||rtab(i).weight);
  end loop;
end;
```

9.18 POLICY_TOKENS

Generate all index tokens for document. With this procedure, no CONTEXT index is required.

Syntax

```
ctx_doc.policy_tokens(policy_name  in  VARCHAR2,
                        document    in  [VARCHAR2|CLOB|BLOB|BFILE],
                        restab      in  out nocopy token_tab,
                        language    in  VARCHAR2 default NULL,
                        format      in  VARCHAR2 default NULL,
                        charset     in  VARCHAR2 default NULL);
```

policy_name

Specify the policy name created with CTX_DDL.[CREATE_POLICY](#) (page 8-30).

document

Specify the document for which to generate tokens.

restab

Specify the name of the token_tab PL/SQL index-by-table type.

The tokens returned are those tokens which are inserted into the index for the document. Stop words are not returned. Section tags are not returned because they are not text tokens.

See Also:

["TOKENS](#) (page 9-47)" of this chapter for more information about the structure of the token_tab type

language

Specify the language of the document. Use an Oracle Text supported language value as you would in the language column of the base table. See ["MULTI_LEXER](#) (page 2-49)" in [Oracle Text Indexing Elements](#) (page 2-1).

format

Specify the format of the document. Use an Oracle Text supported format value, either TEXT, BINARY or IGNORE as you would specify in the format column of the base table. For more information, see the format column description in ["CREATE INDEX](#) (page 1-40)".

charset

Specify the character set of the document. Use an Oracle Text supported value as you would specify in the charset column of the base table. See "[Filter Types](#) (page 2-19)".

Example

Get tokens:

```
declare
  la      varchar2(200);
  rtab    ctx_doc.token_tab;
begin
  ctx_doc.policy_tokens('mypolicy',
    'To define true madness, What is''t but to be nothing but mad?',rtab);
  for i in 1..rtab.count loop
    dbms_output.put_line(rtab(i).offset||':'||rtab(i).token);
  end loop;
end;
```

9.19 SET_KEY_TYPE

Use this procedure to set the CTX_DOC procedures to accept either the ROWID or the PRIMARY_KEY document identifiers. This setting affects the invoking session only.

Syntax

```
ctx_doc.set_key_type(key_type in varchar2);
```

key_type

Specify either ROWID or PRIMARY_KEY as the input key type (document identifier) for CTX_DOC procedures.

This parameter defaults to the value of the CTX_DOC_KEY_TYPE system parameter.

Note:

When your base table has no primary key, setting key_type to PRIMARY_KEY is ignored. The textkey parameter that you specify for any CTX_DOC procedure is interpreted as a ROWID.

Example

The following example sets CTX_DOC procedures to accept primary key document identifiers.

```
begin
  ctx_doc.set_key_type('PRIMARY_KEY');
end
```

9.20 SNIPPET

Use the CTX_DOC.SNIPPET procedure to produce a concordance for a document. The output of a snippet is a collection of segments. A concordance is a text fragment that contains a query term with some of its surrounding text. This is also sometimes known as Key Word in Context or KWIC, because it returns query keywords marked up in their surrounding text, which enables the user to evaluate them in context. The returned text can also contain themes that satisfy an ABOUT query.

For example, a search on *brillig* and *slithey* might return one relevant fragment of a document as follows:

```
'Twas <b>brillig</b>, and the <b>slithey</b> toves did gyre and
```

CTX_DOC.SNIPPET returns one or more most relevant fragments for a document that contains the query term. Because CTX_DOC.SNIPPET returns surrounding text, you can immediately evaluate how useful the returned term is. CTX_DOC.SNIPPET returns the entire document if no words in the returned text are marked up.

Note that for queries that have predicates used mainly for filtering documents at query time, the predicates are ignored during SNIPPET generation. The following predicates are treated as filter predicates for this purpose: SDATA, HASPATH, and WITHIN/INPATH searching inside xml attributes.

See Also:

CTX_DOC.POLICY_SNIPPET (page 9-34) for a policy-based version of this procedure

Syntax

Syntax 1

```
exec CTX_DOC.SNIPPET(

index_name           IN VARCHAR2,
textkey              IN VARCHAR2,
text_query           IN VARCHAR2,
starttag             IN VARCHAR2 DEFAULT '<b>',
endtag               IN VARCHAR2 DEFAULT '</b>',
entity_translation   IN BOOLEAN  DEFAULT TRUE,
separator            IN VARCHAR2 DEFAULT '<b>...</b>',
radius               IN INTEGER  DEFAULT 25,
max_length           IN INTEGER  DEFAULT 250
use_saved_copy       IN NUMBER   DEFAULT CTX_DOC.SAVE_COPY_FALLBACK
return varchar2
);
```

Syntax 2

```
exec CTX_DOC.SNIPPET_CLOB_QUERY(
index_name           IN VARCHAR2,
textkey              IN VARCHAR2,
text_query           IN CLOB,
starttag             IN VARCHAR2 DEFAULT '<b>',
endtag               IN VARCHAR2 DEFAULT '</b>',
entity_translation   IN BOOLEAN  DEFAULT TRUE,
separator            IN VARCHAR2 DEFAULT '<b>...</b>',
radius               IN INTEGER  DEFAULT 25,
max_length           IN INTEGER  DEFAULT 250
use_saved_copy       IN NUMBER   DEFAULT CTX_DOC.SAVE_COPY_FALLBACK
return varchar2
);
```

index_name

Specify the name of the index for the text column.

textkey

Specify the unique identifier (usually the primary key) for the document.

The `textkey` parameter can be as follows:

- A single column primary key value
- An encoded specification for a composite (multiple column) primary key. When `textkey` is a composite key, you must encode the composite `textkey` string using the `CTX_DOC.PK_ENCODE` procedure.
- The `rowid` of the row containing the document

Use `CTX_DOC.SET_KEY_TYPE` to toggle between primary key and `rowid` identification.

text_query

Specify the original query expression used to retrieve the document. If `NULL`, no highlights are generated.

If `text_query` includes wildcards, stemming, fuzzy matching which result in stopwords being returned, `SNIPPET` does not highlight the stopwords.

If `text_query` contains the threshold operator, the operator is ignored.

starttag

Specify the start tag for marking up the query keywords. Default is '``'.

endtag

Specify the end tag for marking up the query keywords. Default is '``'.

entity_translation

Specify if you want HTML entities to be translated. The default is `TRUE`, which means that the special entities (`<`, `>`, and `&`) are translated into their alternative forms ('`<`', '`>`', and '`&`') when output by the procedure. However, special characters in the markup tags that are generated by `CTX_DOC.SNIPPET` will not be translated.

separator

Specify the string separating different returned fragments. Default is '`...`'.

radius

Specify the number of characters to be shown on either side of the hit query in a segment. The character count before the hit query begins on the first character of the first hit query displayed in a segment. Accordingly, the character count after the hit query begins on the last character of the last hit query displayed on a specific segment. Two segments are merged into one if their radii overlap. The displayed number of characters on each side may be modified by ± 10 chars to best match the beginning or ending of a sentence or word.

Special attention is required for the value 0. When specified, the radius is set to automatic and varies between sentences. A best guess of the results is displayed, which attempts to match a full sentence. Note that the length of the radius on each side of the hit query will most likely significantly differ.

The default value is 25.

max_length

Specify the maximum length of the snippet output in characters. This value is currently upper-bounded by the current return type of CTX_DOC.[SNIPPET](#) (page 9-40) and CTX_DOC.[POLICY_SNIPPET](#) (page 9-34) (VARCHAR2). Should the output be longer than the return type VARCHAR2, the result will be truncated. The default value for max_length is 250.

If you set max_length value to a very low value, no snippet may be generated. For example, if max_length is set to 0 or if max_length is lower than the length of query tokens themselves, no snippet may be generated at all.

use_saved_copy

Specify whether to refer to the \$D table to fetch the copy of the document, and what action to take when the copy of the document is not available in the \$D table. The default value is CTX_DOC.SAVE_COPY_FALLBACK.

You can specify one of the following values for the use_saved_copy parameter:

- CTX_DOC.SAVE_COPY_FALLBACK: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then fetch the document from the data store.
- CTX_DOC.SAVE_COPY_ERROR: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then show an error message. Specify this value when you want to implement a specific fallback logic when the copy of the document is not available in the \$D table.
- CTX_DOC.SAVE_COPY_IGNORE: Always fetch the document from the data store.

Example

```
create table tdrbhk01 (id number primary key, text varchar2(4000));

insert into tdrbhk01 values (1, 'Oracle Text adds powerful search
and intelligent text management to the Oracle
database. Complete. You can search and manage documents, web pages,
catalog entries in more than 150 formats in any language. Provides a
complete text query language and complete character support. Simple. You
can index and search text using SQL. Oracle Text Management can be done
using Oracle Enterprise Manager - a GUI tool. Fast. You can search
millions of documents, document,web pages, catalog entries using the
power and scalability of the database. Intelligent. Oracle Text's
unique knowledge-base enables you to search, classify, manage
documents, clusters and summarize text based on its meaning as well as
its content. ');

create index tdrbhk01x on tdrbhk01(text) indextype is ctxsys.context;

create or replace function my_snippet_wrapper(
  key in varchar2,
  query in varchar2,
  radius in number,
  max_length in number) return varchar2 is
  buff varchar2(4000);
begin
  buff := ctx_doc.snippet('tdrbhk01x', key, query, '<b>', '<b>', true, '<b>..<b>',
radius, max_length);
  return buff;
end;
/
```

```
show errors;
```

```
select my_snippet_wrapper('1','Oracle', 10, 100) from dual;
```

The result looks something like this:

```
CTX_DOC.SNIPPET('TDRBHK01X','1','SEARCH|CLASSIFY')
```

Text's unique knowledge-base enables you to search,
classify, manage documents, clusters and summarize

Limitations

CTX_DOC.SNIPPET does not support the use of query templates.

CTX_DOC.SNIPPET displays marked-up keywords in context when used with NULL_SECTION_GROUP. However, there are limitations when using this procedure with XML documents. When used with XML_SECTION_GROUP or AUTO_SECTION_GROUP, the XML structure is ignored and user-specified tags are stripped out, which results in parts of surrounding text to be included in the returned snippet.

Related Topics

["POLICY_SNIPPET \(page 9-34\)"](#)

["HIGHLIGHT \(page 9-9\)"](#)

["MARKUP \(page 9-13\)"](#)

9.21 THEMES

Use the CTX_DOC.THEMES procedure to generate a list of themes for a document. You can store each theme as a row in either a result table or an in-memory PL/SQL table that you specify.

Syntax 1: In-Memory Table Storage

```
CTX_DOC.THEMES(  
  
    index_name      IN VARCHAR2,  
    textkey         IN VARCHAR2,  
    restab          IN OUT NOCOPY THEME_TAB,  
    full_themes     IN BOOLEAN DEFAULT FALSE,  
    num_themes      IN NUMBER DEFAULT 50,  
    use_saved_copy  IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);
```

Syntax 2: Result Table Storage

```
CTX_DOC.THEMES(  
  
    index_name      IN VARCHAR2,  
    textkey         IN VARCHAR2,  
    restab          IN VARCHAR2,  
    query_id        IN NUMBER DEFAULT 0,  
    full_themes     IN BOOLEAN DEFAULT FALSE,  
    num_themes      IN NUMBER DEFAULT 50,  
    use_saved_copy  IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);
```


index_name

Specify the name of the index for the text column.

textkey

Specify the unique identifier (usually the primary key) for the document.

The `textkey` parameter can be as follows:

- A single column primary key value
- An encoded specification for a composite (multiple column) primary key. When `textkey` is a composite key, you must encode the composite `textkey` string using the `CTX_DOC.PK_ENCODE` procedure.
- The `rowid` of the row containing the document

Toggle between primary key and `rowid` identification using `CTX_DOC.SET_KEY_TYPE`.

restab

You can specify this procedure to store results to either a table or to an in-memory PL/SQL table.

To store results in a table, specify the name of the table.

See Also:

["Theme Table" \(page A-8\)](#) in [Oracle Text Result Tables](#) (page A-1)

To store results in an in-memory table, specify the name of the in-memory table of type `THEME_TAB`. The `THEME_TAB` datatype is defined as follows:

```
type theme_rec is record (
    theme varchar2(2000),
    weight number
);
```

```
type theme_tab is table of theme_rec index by binary_integer;
```

`CTX_DOC.THEMES` clears the `THEME_TAB` you specify before the operation.

query_id

Specify the identifier used to identify the row(s) inserted into `restab`.

full_themes

Specify whether this procedure generates a single theme or a hierarchical list of parent themes (full themes) for each document theme.

Specify `TRUE` for this procedure to write full themes to the `THEME` column of the result table.

Specify `FALSE` for this procedure to write single theme information to the `THEME` column of the result table. This is the default.

num_themes

Specify the maximum number of themes to retrieve. For example, if you specify 10, then up to the first 10 themes are returned for the document. The default is 50.

If you specify 0 or NULL, then this procedure returns all themes in a document. If the document contains more than 50 themes, then only the first 50 themes show conceptual hierarchy.

use_saved_copy

Specify whether to refer to the \$D table to fetch the copy of the document, and what action to take when the copy of the document is not available in the \$D table.

You can specify one of the following values for the use_saved_copy parameter:

- `CTX_DOC.SAVE_COPY_FALLBACK`: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then fetch the document from the data store.
- `CTX_DOC.SAVE_COPY_ERROR`: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then show an error message. Specify this value when you want to implement a specific fallback logic when the copy of the document is not available in the \$D table.
- `CTX_DOC.SAVE_COPY_IGNORE`: Always fetch the document from the data store.

The default value is `CTX_DOC.SAVE_COPY_FALLBACK`.

Examples

In-Memory Themes

The following example generates the first 10 themes for document 1 and stores them in an in-memory table called `the_themes`. The example then loops through the table to display the document themes.

```
declare
  the_themes ctx_doc.theme_tab;

begin
  ctx_doc.themes('myindex','1',the_themes, num_themes=>10);
  for i in 1..the_themes.count loop
    dbms_output.put_line(the_themes(i).theme||':'||the_themes(i).weight);
  end loop;
end;
```

Theme Table

The following example creates a theme table called `CTX_THEMES`:

```
create table CTX_THEMES (query_id number,
                        theme varchar2(2000),
                        weight number);
```

Single Themes

To obtain a list of up to the first 20 themes, where each element in the list is a single theme, enter a statement like the following example:

```
begin

  ctx_doc.themes('newsindex','34','CTX_THEMES',1,full_themes => FALSE,
    num_themes=> 20);

end;
```

Full Themes

To obtain a list of the top 20 themes, where each element in the list is a hierarchical list of parent themes, enter a statement like the following example:

```
begin

ctx_doc.themes('newsindex','34','CTX_THEMES',1,full_themes => TRUE, num_
themes=>20);

end;
```

9.22 TOKENS

Use this procedure to identify all text tokens in a document. The tokens returned are those tokens that are inserted into the index. This feature is useful for implementing document classification, routing, or clustering.

Stopwords are not returned. Section tags are not returned because they are not text tokens.

Syntax 1: In-Memory Table Storage

```
CTX_DOC.TOKENS(index_name      IN VARCHAR2,
               textkey         IN VARCHAR2,
               restab          IN OUT NOCOPY TOKEN_TAB,
               use_saved_copy  IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);
```

Syntax 2: Result Table Storage

```
CTX_DOC.TOKENS(index_name      IN VARCHAR2,
               textkey         IN VARCHAR2,
               restab          IN VARCHAR2,
               query_id        IN NUMBER DEFAULT 0,
               use_saved_copy  IN NUMBER DEFAULT CTX_DOC.SAVE_COPY_FALLBACK);
```

index_name

Specify the name of the index for the text column.

textkey

Specify the unique identifier (usually the primary key) for the document.

The `textkey` parameter can be as follows:

- A single column primary key value
- Encoded specification for a composite (multiple column) primary key. To encode a composite `textkey`, use the `CTX_DOC.PKENCOD` (page 9-19) procedure.
- The `rowid` of the row containing the document

Toggle between primary key and `rowid` identification using

`CTX_DOC.SET_KEY_TYPE` (page 9-40).

restab

You can specify that this procedure store results to either a table or to an in-memory PL/SQL table.

The tokens returned are those tokens that are inserted into the index for the document (or row) named with `textkey`. Stop words are not returned. Section tags are not returned because they are not text tokens.

Specifying a Token Table

To store results to a table, specify the name of the table. Token tables can be named anything, but must include the columns shown in the following table, with names and datatypes as specified.

Table 9-2 Required Columns for Token Tables

Column Name	Type	Description
QUERY_ID	NUMBER	The identifier for the results generated by a particular call to CTX_DOC.TOKENS (only populated when table is used to store results from multiple TOKEN calls)
TOKEN	VARCHAR2 (64)	The token string in the text.
OFFSET	NUMBER	The position of the token in the document, relative to the start of document which has a position of 1.
LENGTH	NUMBER	The character length of the token.

Specifying an In-Memory Table

To store results to an in-memory table, specify the name of the in-memory table of type TOKEN_TAB. The TOKEN_TAB datatype is defined as follows:

```
type token_rec is record (
    token varchar2(64),
    offset number,
    length number
);

type token_tab is table of token_rec index by binary_integer;
```

CTX_DOC.TOKENS clears the TOKEN_TAB you specify before the operation.

query_id

Specify the identifier used to identify the row(s) inserted into restab.

use_saved_copy

Specify whether to refer to the \$D table to fetch the copy of the document, and what action to take when the copy of the document is not available in the \$D table.

You can specify one of the following values for the use_saved_copy parameter:

- CTX_DOC.SAVE_COPY_FALLBACK: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then fetch the document from the data store.
- CTX_DOC.SAVE_COPY_ERROR: Fetch the copy of the document from the \$D table. If the copy of the document is not present in the \$D table, then show an error message. Specify this value when you want to implement a specific fallback logic when the copy of the document is not available in the \$D table.
- CTX_DOC.SAVE_COPY_IGNORE: Always fetch the document from the data store.

The default value is CTX_DOC.SAVE_COPY_FALLBACK.

Example

In-Memory Tokens

The following example generates the tokens for document 1 and stores them in an in-memory table, declared as `the_tokens`. The example then loops through the table to display the document tokens.

```
declare
  the_tokens ctx_doc.token_tab;

begin
  ctx_doc.tokens('myindex','1',the_tokens);
  for i in 1..the_tokens.count loop
    dbms_output.put_line(the_tokens(i).token);
  end loop;
end;
```


CTX_ENTITY Package

The CTX_ENTITY PL/SQL package is used to locate and classify words and phrases into categories, such as persons or companies.

CTX_ENTITY contains the following stored procedures and functions.

Name	Description
ADD_EXTRACT_RULE (page 10-1)	Adds a single extraction rule to an extraction policy.
ADD_STOP_ENTITY (page 10-4)	Marks certain entity mentions or entity types as not to be extracted.
COMPILE (page 10-6)	Compiles added extraction rules into an extraction policy.
CREATE_EXTRACT_POLICY (page 10-7)	Creates an extraction policy to use.
DROP_EXTRACT_POLICY (page 10-8)	Drops an extraction policy.
EXTRACT (page 10-8)	Generates an XML document describing the entities found in an input document.
REMOVE_EXTRACT_RULE (page 10-10)	Removes a single extraction rule from an extraction policy.
REMOVE_STOP_ENTITY (page 10-10)	Removes a stop entity from an extraction policy.

10.1 ADD_EXTRACT_RULE

The ADD_EXTRACT_RULE procedure adds a single extraction rule to extract policy. Invokers add rules into their own extraction policy. Extraction rules have sentence-wide scopes. Extraction rules have to be case-sensitive except for entity types and rule operators in the rule expression. Order of rule addition is not important. Addition of a rule will not be effective until CTX_ENTITY.COMPILE (page 10-6) is executed. This procedure issues a commit.

Syntax

```
CTX_ENTITY.ADD_EXTRACT_RULE(
    policy_name          IN VARCHAR2,
    rule_id              IN INTEGER,
    extraction_rule      IN VARCHAR2);
```

policy_name

Specify the policy name.

rule_id

Specify a unique rule ID within an extraction policy. The rule ID must be greater than 0.

extraction_rule

The rule text in XML format specifies the language, expression, and entities to be extracted. The rule text follows the XML schema as follows:

```
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema">
<xsd:element name="rule">
  <xsd:sequence>
    <xsd:element name="expression" type="xsd:string"/>
    <xsd:complexType>
      <xsd:attribute name="refid" type="xsd:positiveInteger"/>
    </xsd:complexType>
    <xsd:element name="comments" type="xsd:string" default="\0"/>
  </xsd:sequence>
  </xsd:attribute name="language" type="xsd:string" default="ALL"/>
</xsd:element>
</xsd:schema>
```

Where:

- The language attribute of the rule tag specifies the applied language for the rule. The rule will only be applied to documents that are of the specified languages. The language attribute can be left out, or set to "ALL" if the rule is to match on all documents.
- The expression tag contains the posix regular expression that will be used in the matching.
- The comments tag allows users to associate any comments with this user rule.
- The type tag assigns the extracted entity text to a given entity type. The refid attribute of the type tag specifies which backreference in the regular expression corresponds to the actual entity. The entity type can be one of the Oracle supplied types, listed in [Table 10-1](#) (page 10-2), or it can be a user-defined type, which must be prefixed with the letter "x".

Supplied Entity Type	Explanation	Examples
building	A particular building	White House
city		New York
company		Oracle Corporation
country		United States
currency		Dollar
date		July 4
day		Monday, Tuesday
email_address		person@example.com
geo_political	A political or strategic organization	United Nations

Supplied Entity Type	Explanation	Examples
holiday	Name of a country holiday	Labor Day
location_other	Other types of locations	Atlantic Ocean
month		June, July
non_profit	Non-profit organization	Red Cross
organization_other	Other types of organizations	Supreme Court
percent	Expressed as number and %	10%
person_jobtitle	Person referred to by title	President, Professor
person_name	Person referred to by name	John Doe
person_other	Other types of persons	Other types of persons (for example, criminal)
phone_number		(123)-456-7890
postal_address		Redwood Shores, CA
product		Oracle Text
region		North America
ssn	Social Security Number	123-45-6789
state	A state or province	California
time_duration	A length of time	10 seconds
tod	Time of day	8:00 AM
url	Web address	www.example.com
zip_code	Zip Code	CA 94065

Example 1

The following example shows how to define an extraction rule and associate it with an entity extraction policy. The following rule defines a simple extraction rule for finding email addresses in documents.

```
begin
  ctx_entity.add_extract_rule('poll', 1,
    '<rule>
      <expression>email is (\w+@\w+\. \w+)</expression>
      <type refid = "1">email_address</type>
    </rule>');
end;
/
```

Where:

- Given the sentence: "My email address is jdoe@company.com", this extraction rule will extract "jdoe@company.com" as an entity of type `email_address`.
- The rule is added to the extraction policy called `poll`.
- The rule is added with rule ID of 1.
- This XML description of the rule is as follows:
 - The language attribute of the rule tag is left empty, so the rule will apply to all languages.
 - The expression tag contains the regular expression to use in the extraction.
 - The value of the type element and the `refid` attribute of the type tag specify that the first backreference corresponds to the text of the entity.

Example 2

The following rule defines a simple extraction rule for finding phone numbers in documents:

```
begin
  ctx_entity.add_extract_rule('poll', 2,
    '<rule language="english">
      <expression>(\d{3}\) \d{3}-\d{3}-\d{4})</expression>
      <comments>Rule for phone numbers</comments>
      <type refid="1">email_address</type>
    </rule>';
end;
/
```

Where:

- Given the sentence: "I can be contacted at (123) 456-7890", this extraction rule will extract "(123) 456-7890" as an entity of type `phone_number`.
- The rule is added to the extraction policy called `poll`.
- The rule is added with rule ID of 2.
- The XML description of the rule is as follows:
 - The language attribute of the rule tag is set to `english`, so the rule will only apply to English documents.
 - The expression tag contains the regular expression to use in the extraction.
 - The value of the type element and the `refid` attribute of the type tag specify that the first backreference corresponds to the text of the entity.
 - Explanatory comments are associated with this rule.

10.2 ADD_STOP_ENTITY

This procedure is used to mark certain entity mentions or entity types as not to be extracted. Invokers add stop entities to their own extraction policy. It does not take effect until after `CTX_ENTITY.COMPILE` (page 10-6) is run. Either

`entity_name` or `entity_type` can be NULL, but not both. If one stop entity is a subset of another, it will be marked as a subset after `CTX_ENTITY.COMPILE`, and not used in extraction. This procedure issues a commit.

Syntax

```
CTX_ENTITY.ADD_STOP_ENTITY(
    policy_name          IN VARCHAR2,
    entity_name          IN INTEGER,
    entity_type          IN VARCHAR2 DEFAULT NULL,
    comments             IN VARCHAR2 DEFAULT NULL);
```

policy_name

Specify the policy name of the stop entity that is to be added.

entity_name

Specify the entity name to be listed as a stop entity. If `entity_type` is NULL, all mentions with this `entity_name` will be listed as stop entities. It is case-sensitive.

entity_type

If `entity_name` is NULL, this will specify an entire entity type to be listed as stop entity. If `entity_name` is not NULL, this will specify only the mention `<entity_type, entity_name>` as a stop entity. It is case-insensitive. The maximum byte length is 4000 bytes.

comments

The maximum byte length is 4000 bytes.

Example

The following example adds a stop entity corresponding to all persons. After compilation, extraction will not report any mentions of entity type `person`.

```
exec ctx_entity.add_stop_entity('poll', NULL, 'person');
```

The following example adds a stop entity corresponding to `<'person', 'john doe'>`. After compilation, extraction will not report any mentions of the pair `<'person', 'john doe'>`. This stop entity is actually a subset of the first stop entity added. It will be marked subset in the [CTX_USER_EXTRACT_STOP_ENTITIES](#) (page G-17) view, and will not be used in extraction.

```
exec ctx_entity.add_stop_entity('poll', 'john doe', 'person');
```

The following example adds a stop entity corresponding to all mentions of `ford`. After compilation, extraction will not report any mentions of the entity `ford`, irrespective of the entity type of the mention. For example, if a rule matches `ford` to a person, the extraction will not report this match. If a rule matches `ford` to a company, the extraction will again not report this match.

```
exec ctx_entity.add_stop_entity('poll', 'ford', NULL);
```

Related Topics

["COMPILE](#) (page 10-6)"

["CTX_USER_EXTRACT_STOP_ENTITIES](#) (page G-17)"

10.3 COMPILE

This procedure compiles added extraction rules into an extraction policy. It can also be used to compile added stop entities into an extraction policy. Users have to invoke this procedure if they have added any rules or stop entities to their policy.

Invokers compile rules and stop entities into their own extraction policy. Users can choose to compile added rules, added stop entities, or both.

After compilation, the [CTX_USER_EXTRACT_RULES](#) (page G-16) and [CTX_USER_EXTRACT_STOP_ENTITIES](#) (page G-17) views will show which rules and stop entities are being used in the entity extraction.

Syntax

```
CTX_ENTITY.COMPILE(  
    policy_name           IN VARCHAR2,  
    compile_choice        IN NUMBER DEFAULT COMPILE_ALL,  
    locking               IN NUMBER DEFAULT LOCK_NOWAIT_ERROR);
```

policy_name

Specify the policy name that is to be compiled.

compile_choice

Specify the entity name to be listed as a stop entity. If `entity_type` is NULL, all mentions with this `entity_name` will be listed as stop entities. It is case-sensitive.

The options are `COMPILE_ALL`, `COMPILE_RULES`, and `COMPILE_STOP_ENTITIES`. `COMPILE_ALL` compiles both rules and stop entities. `COMPILE_RULES` compiles only rules. `COMPILE_STOP_ENTITIES` compiles only stop entities.

locking

The maximum byte length is 4000 bytes. Configure how `COMPILE` deals with the situation where another `COMPILE` is already running on the same policy.

The options for locking are:

- `CTX_ENTITY.LOCK_WAIT`
If another compile is running, wait until the running compile is complete, then begin compile. (In the event of not being able to get a lock, it will wait forever and ignore the maxtime setting.).
- `CTX_ENTITY.LOCK_NOWAIT`
If another compile is running, immediately returns without error.
- `CTX_ENTITY.LOCK_NOWAIT_ERROR`
If another sync is running, error "DRG-51313: timeout while waiting for DML or optimize lock" is raised.

Example

The following example compiles the policy using the default setting:

```
exec ctx_entity.compile('poll');
```

The following example compiles only the stop entities for the policy:

```
exec ctx_entity.compile('poll', CTX_ENTITY.COMPILE_STOP_ENTITIES);
```

The following example compiles both rules and stop entities. If a lock exists, the function returns immediately, but does not raise an error.

```
exec ctx_entity.compile('poll', CTX_ENTITY.COMPILE_ALL,
                             CTX_ENTITY.LOCK_NOWAIT);
```

Related Topics

["CTX_USER_EXTRACT_RULES \(page G-16\)"](#)

["CTX_USER_EXTRACT_STOP_ENTITIES \(page G-17\)"](#)

10.4 CREATE_EXTRACT_POLICY

The CREATE_EXTRACT_POLICY procedure creates an extraction policy to use. This policy can only be used by the policy owner.

Syntax

```
CTX_ENTITY.CREATE_EXTRACT_POLICY(
  policy_name          IN VARCHAR2,
  lexer                IN VARCHAR2 DEFAULT NULL,
  include_supplied_rules IN BOOLEAN DEFAULT TRUE,
  include_supplied_dictionary IN BOOLEAN DEFAULT TRUE
);
```

policy_name

Specify the name of the new extraction policy.

lexer

Specify the name of the lexer preference. Only [AUTO_LEXER \(page 2-33\)](#) is supported. If not specified, [CTXSYS.DEFAULT_EXTRACT_LEXER \(page 2-97\)](#) will be used. The attributes `index_stems` and `deriv_stems` are not allowed.

include_supplied_rules

Specify whether Oracle-supplied rules are included in entity extraction. If false, automatic acronym resolution will be turned off. The default is true.

include_supplied_dictionary

Specify whether the Oracle-supplied dictionary is included in entity extraction. The default is true.

Examples

The following example creates an extraction policy using the default settings. By default, the Oracle-supplied features, such as rules and dictionary, are enabled.

```
exec CTX_ENTITY.CREATE_EXTRACT_POLICY('poll');
```

The following example creates an extraction policy that explicitly specifies certain parameters. It specifies the lexer to be used as `mylex`, which must be an [AUTO_LEXER \(page 2-33\)](#) preference. It also includes the Oracle-supplied rules, but disables the Oracle-supplied dictionary.

```
exec CTX_ENTITY.CREATE_EXTRACT_POLICY('pol2', 'mylex', TRUE, FALSE);
```

Related Topics

["AUTO_LEXER \(page 2-33\)"](#)

["CTXSYS.DEFAULT_EXTRACT_LEXER \(page 2-97\)"](#)

10.5 DROP_EXTRACT_POLICY

The `DROP_EXTRACT_POLICY` procedure drops an extraction policy. These policies can only be dropped by the policy owner. This procedure issues a commit.

Syntax

```
CTX_ENTITY.DROP_EXTRACT_POLICY(  
    policy_name          IN VARCHAR2  
);
```

policy_name

Specify the name of the extraction policy to be dropped.

Example

The following example drops the extraction policy `pol2`:

```
exec ctx_entity.drop_extract_policy('pol2');
```

10.6 EXTRACT

The `EXTRACT` procedure runs entity extraction on a given document and generates an XML document describing the entities found in the document. The XML document will give the entity text, type, and location of the entity in the document. The extraction will use the settings (rules, stop entities, and dictionary) defined in the given extraction policy.

Entity type names in the result will be uppercased. Invokers can run extraction using their own extraction policy.

Before execution, you have to issue `CTX_ENTITY.COMPILE` ([page 10-6](#)).

Syntax

```
CTX_ENTITY.EXTRACT(  
    policy_name          IN VARCHAR2,  
    document             IN CLOB,  
    language            IN VARCHAR2,  
    result              IN OUT NOCOPY CLOB,  
    entity_type_list     IN CLOB DEFAULT NULL  
);
```

policy_name

Run extraction using the given policy.

document

The input document to run extraction on.

If `entity_type` is `NULL`, all mentions with this `entity_name` will be listed as stop entities. It is case-sensitive.

language

Only English is supported.

result

A CLOB containing the XML description of the entities extracted from the document.

If `entity_type` is `NULL`, all mentions with this `entity_name` will be listed as stop entities. It is case-sensitive.

entity_type_list

Specify that extraction will only consider a subset of entity types. The `entity_type_list` is a comma-delimited list. If the `entity_type_list` is not specified, the entity extraction will consider all entity types.

Example

The following example shows the results of entity extraction on an example document. Suppose that we have created an extraction policy called `pol1`, and we are given the input document:

```
Sam A. Schwartz retired as executive vice president of Hupplewhite INC. in New York.
```

We then call the `ctx_entity.extract` procedure to generate an XML document containing the entities in this document. We insert the results CLOB into a table called `entities` for future viewing.

```
declare
  myresults clob;
begin
  select txt into mydoc from docs where id=1;
  ctx_entity.extract('p1', mydoc, null, myresults);
  insert into entities values(1, myresults);
  commit;
end;
/
```

Then we can examine the extracted entities from the `entities` table. Note that each entity is tagged with its location in the input document, as well as the source used to classify the entity.

```
<entities>
<entity id="0" offset="75" length="8" source="SuppliedDictionary">
<text>New York</text>
<type>city</type>
</entity>
<entity id="1" offset="55" length="16" source="SuppliedRule">
<text>Hupplewhite Inc.</text>
<type>company</type>
</entity>
<entity id="2" offset="27" length="24" source="SuppliedDictionary">
<text>Sam A. Schwartz</text>
<type>person_name</type>
</entity>
<entity id="4" offset="75" length="8" source="SuppliedDictionary">
<text>New York</text>
<type>state</type>
</entity>
</entities>
```

10.7 REMOVE_EXTRACT_RULE

The `REMOVE_EXTRACT_RULE` procedure removes an extraction rule from the specified policy given a `rule_id`. Only the owner of the specified policy can remove an extraction rule from the policy. Removal of the extraction rule will be in effect after running `CTX_ENTITY.COMPILE` (page 10-6).

Syntax

```
CTX_ENTITY.REMOVE_EXTRACT_RULE(  
    policy_name          IN VARCHAR2,  
    rule_id              IN INTEGER  
);
```

policy_name

Remove the extraction rule from the specified policy.

rule_id

Specify the rule ID of the extraction rule to be removed.

Example

The following example removes the extraction rule with ID 1 from the policy `poll1`:

```
exec ctx_entity.remove_extract_rule('poll1', 1);
```

10.8 REMOVE_STOP_ENTITY

The `REMOVE_STOP_ENTITY` procedure removes a stop entity from an extraction policy. Only the owner of the specified policy can remove a stop entity from the policy. Removal of the stop entity will be in effect after running `CTX_ENTITY.COMPILE` (page 10-6). Either the `entity_name` or `entity_type` can be null, but not both.

Syntax

```
CTX_ENTITY.REMOVE_STOP_ENTITY(  
    policy_name          IN VARCHAR2,  
    entity_name          IN INTEGER DEFAULT NULL,  
    entity_type          IN VARCHAR2 DEFAULT NULL  
);
```

policy_name

Remove the `stop_entity` from the specified policy.

entity_name

Specify the name to be removed from the stop entity list. The `stop_entity` must have already been added to the `stop_entity` list using `CTX_ENTITY.ADD_STOP_ENTITY` (page 10-4).

entity_type

Specify the type of entity to be removed from the stop entity list. The `stop_entity` must have already been added to the stop entity list using `CTX_ENTITY.ADD_STOP_ENTITY` (page 10-4).

Example

```
exec ctx_entity.remove_stop_entity('poll', NULL, 'person_name');
```

The example statement removes the stop entity corresponding to all mentions of the entity_type person_name from the policy poll. After execution, this stop entity will be marked as "to be deleted" in the [CTX_USER_EXTRACT_STOP_ENTITIES](#) (page G-17) view. The removal of the stop entity will take effect once the user runs CTX_ENTITY.[COMPILE](#) (page 10-6).

Related Topics

["COMPILE \(page 10-6\)"](#)

["ADD_STOP_ENTITY \(page 10-4\)"](#)

["CTX_USER_EXTRACT_STOP_ENTITIES \(page G-17\)"](#)

CTX_OUTPUT Package

This chapter provides reference information for using the CTX_OUTPUT PL/SQL package.

CTX_OUTPUT contains the following stored procedures:

Name	Description
ADD_EVENT (page 11-1)	Adds an event to the index log.
ADD_TRACE (page 11-2)	Enables tracing.
DISABLE_QUERY_STATS (page 11-4)	Turns off the gathering of query stats for the index.
ENABLE_QUERY_STATS (page 11-4)	Enables gathering of query stats for the index.
END_LOG (page 11-5)	Halts logging of index and document services requests.
END_QUERY_LOG (page 11-5)	Stops logging queries into a logfile.
GET_TRACE_VALUE (page 11-6)	Returns the value of a trace.
LOG_TRACES (page 11-6)	Prints traces to logfile.
LOGFILENAME (page 11-7)	Returns the name of the current log file.
REMOVE_EVENT (page 11-7)	Removes an event from the index log.
REMOVE_TRACE (page 11-8)	Disables tracing.
RESET_TRACE (page 11-8)	Clears a trace.
START_LOG (page 11-9)	Starts logging index and document service requests.
START_QUERY_LOG (page 11-9)	Creates a log file of queries.

11.1 ADD_EVENT

Use this procedure to add an event to the index log for more detailed log output or to enable error tracing for Oracle Text errors.

Syntax

```
CTX_OUTPUT.ADD_EVENT(event in NUMBER, errnum in NUMBER := null);
```

event

Specify the type of index event to log. You can add the following events:

- `CTX_OUTPUT.EVENT_INDEX_PRINT_ROWID`, which logs the rowid of each row as it is indexed. This is useful for debugging a failed index operation.
- `CTX_OUTPUT.EVENT_OPT_PRINT_TOKEN`, which prints each token as it is being optimized.
- `CTX_OUTPUT.EVENT_INDEX_PRINT_TOKEN`, which prints the each token as it is being indexed.
- `CTX_OUTPUT.EVENT_DRG_DUMP_ERRORSTACK`, which prints the stack trace for the specified DRG error in the log. An error will be raised if `errnum` is not specified.

errnum

Specify the DRG error number for a `CTX_OUTPUT.EVENT_DRG_DUMP_ERRORSTACK` event.

Example

```
begin
CTX_OUTPUT.ADD_EVENT(CTX_OUTPUT.EVENT_INDEX_PRINT_ROWID);
end;
```

Related Topics

["REMOVE_EVENT \(page 11-7\)"](#)

11.2 ADD_TRACE

Use this procedure to enable a trace. If the trace has not been enabled, this call adds the trace to the list of active traces and resets its value to 0. If the trace has already been enabled, an error is raised.

Syntax

```
CTX_OUTPUT.ADD_TRACE(trace_id BINARY_INTEGER);
```

trace_id

Specify the ID of the trace to enable. See [Table 11-1](#) (page 11-3) for possible trace values.

Notes

[Table 11-1](#) (page 11-3) shows the available traces:

Table 11-1 Available Traces

Symbol	ID	Metric
TRACE_IDX_USER_DATASTORE	1	Time spent executing user datastore
TRACE_IDX_AUTO_FILTER	2	Time spent invoking the AUTO_FILTER filter. (Replaces the deprecated TRACE_IDX_INSO_FILTER trace)
TRACE_QRY_XX_TIME	3	Time spent executing the \$X cursor
TRACE_QRY_XF_TIME	4	Time spent fetching from \$X
TRACE_QRY_X_ROWS	5	Total number of rows whose token metadata was fetched from \$X
TRACE_QRY_IF_TIME	6	Time spent fetching the LOB locator from \$I
TRACE_QRY_IR_TIME	7	Time spent reading \$I LOB information
TRACE_QRY_I_ROWS	8	Number of rows whose \$I token_info was actually read
TRACE_QRY_I_SIZE	9	Number of bytes read from \$I LOBs
TRACE_QRY_R_TIME	10	Time spent fetching and reading \$R information
TRACE_QRY_CON_TIME	11	Time spent in CONTAINS processing (drexrcontains/drexrstart/drexrfetch)
TRACE_QRY_S_TIME	15	Time spent fetching and reading \$\$ information
TRACE_QRY_O_TIME	19	Time spent reading \$O information
TRACE_QRY_D_TIME	23	Time spent reading \$D information
TRACE_QRY_SNIPPET_TIME	25	Time spent extracting a snippet from a document
TRACE_HIL_DOCSERV_TIME	26	Time spent by document service procedures (snippet, highlight, and markup)

Tracing is independent of logging. Logging does not have to be on to start tracing, and vice-versa.

Traces are associated with a session—they can measure operations that take place within a single session, and conversely, cannot make measurements across sessions.

During parallel sync or optimize, the trace profile will be copied to the slave sessions if and only if tracing is currently enabled. Each slave will accumulate its own traces and implicitly write all trace values to the slave logfile before termination.

Related Topics

["REMOVE_TRACE \(page 11-8\)"](#)

["GET_TRACE_VALUE \(page 11-6\)"](#)

["LOG_TRACES \(page 11-6\)"](#)

["RESET_TRACE \(page 11-8\)"](#)

Oracle Text Application Developer's Guide

11.3 DISABLE_QUERY_STATS

Disables gathering of query stats for the index.

Syntax

```
ctx_output.disable_query_stats(  
  index_name IN VARCHAR2  
);
```

index_name

The name of the index on which query stats collection is to be disabled.

Example

Turn off gathering of query stats for the index myindex.

```
CTX_OUTPUT.DISABLE_QUERY_STATS(myindex);
```

Notes

Once the query stats is disabled for an index, gathering and storing query-related metadata is stopped for that index. All the entries corresponding to that index are cleared from the dictionary tables. An error is returned if you call this procedure on an index where query stats is not enabled.

Related Topics

CTX_OUTPUT.["ENABLE_QUERY_STATS \(page 11-4\)"](#)

CTX_REPORT.["INDEX_STATS \(page 13-6\)"](#)

11.4 ENABLE_QUERY_STATS

Enables gathering of query stats for the index. To have query-related metadata stored for the index, use this procedure to enable collection of statistics on that index. You can only access the gathered metadata when `ctx_output.enable_query_stats` is turned on for the index.

Note:

Accessing the query stats metadata only works when `ctx_output.enable_query_stats` is turned on for the index. Please see CTX_REPORT.["INDEX_STATS \(page 13-6\)"](#) for the list of gathered query stats metadata.

Syntax

```
ctx_output.enable_query_stats(  
  index_name IN VARCHAR2  
);
```

index_name

The name of the index on which query stats collection is to be enabled.

Example

Turn on gathering of query stats for the index `myindex`.

```
CTX_OUTPUT.ENABLE_QUERY_STATS(myindex);
```

Notes

The information that shows whether query stats is enabled on an index is available in the views: `CTX_INDEXES` and `CTX_USER_INDEXES` under the column `idx_query_stats_enabled`, which is in both of these views. If `query_stats` is enabled for an index, then the column displays YES; if not, then the column displays NO.

The data corresponding to the query statistics will be stored in persistent dictionary tables. Once `statistics` has been enabled for a particular index, query statistics will be collected for that index from all sessions.

If you call this procedure for an index where query stats is already enabled, then an error is thrown.

Statistics collection has a minimal effect on query performance.

Related Topics

CTX_OUTPUT."[DISABLE_QUERY_STATS](#) (page 11-4)"

CTX_REPORT."[INDEX_STATS](#) (page 13-6)".

11.5 END_LOG

This procedure halts logging index and document service requests.

Syntax

```
ctx_output.end_log;
```

Example

```
begin
  CTX_OUTPUT.END_LOG;
end;
```

11.6 END_QUERY_LOG

Use this procedure to stop logging queries into a logfile created with CTX_OUTPUT.[START_QUERY_LOG](#) (page 11-9).

Syntax

```
ctx_output.end_query_log;
```

Example

```
begin
```

```
CTX_OUTPUT.START_QUERY_LOG('mylog1');  
    < get queries >  
CTX_OUTPUT.END_QUERY_LOG;  
  
end;
```

11.7 GET_TRACE_VALUE

Use this procedure to programmatically retrieve the current value of a trace.

Syntax

```
CTX_OUTPUT.GET_TRACE_VALUE(trace_id BINARY_INTEGER);
```

trace_id

Specify the trace ID whose value you want. See [Table 11-1](#) (page 11-3) for possible values.

Example

This sets the value of the variable *value*:

```
value := ctx_output.get_trace_value(trace_id);
```

Notes

You can also retrieve trace values through SQL:

```
select * from ctx_trace_values;
```

See "[CTX_TRACE_VALUES](#) (page G-15)" for the entries in the CTX_TRACE_VALUES view.

If the trace has not been enabled, an error is raised.

Traces are not reset to 0 by this call.

Traces are associated with a session—they can measure operations that take place within a single session, and conversely, cannot make measurements across sessions.

Related Topics

["REMOVE_TRACE](#) (page 11-8)"

["ADD_TRACE](#) (page 11-2)"

["LOG_TRACES](#) (page 11-6)"

["RESET_TRACE](#) (page 11-8)"

Oracle Text Application Developer's Guide

11.8 LOG_TRACES

Use this procedure to print all active traces to the logfile.

Syntax

```
CTX_OUTPUT.LOG_TRACES;
```


Notes

If logging has not been started, an error is raised.

Traces are not reset to 0 by this call.

This procedure looks for the logfile in the directory specified by the LOG_DIRECTORY system parameter, which is \$ORACLE_HOME/ctx/log on UNIX. You can query the CTX_PARAMETERS view to find the current setting.

Related Topics

["REMOVE_TRACE \(page 11-8\)"](#)

["GET_TRACE_VALUE \(page 11-6\)"](#)

["ADD_TRACE \(page 11-2\)"](#)

["RESET_TRACE \(page 11-8\)"](#)

Oracle Text Application Developer's Guide

11.9 LOGFILENAME

Returns the filename for the current log. This procedure looks for the logfile in the directory specified by the LOG_DIRECTORY system parameter, which is \$ORACLE_HOME/ctx/log on UNIX. You can query the CTX_PARAMETERS view to find the current setting.

Syntax

```
CTX_OUTPUT.LOGFILENAME RETURN VARCHAR2;
```

Returns

Log file name.

Example

```
declare
  logname varchar2(100);
begin
  logname := CTX_OUTPUT.LOGFILENAME;
  dbms_output.put_line('The current log file is: '||logname);
end;
```

11.10 REMOVE_EVENT

Use this procedure to remove an event from the index log.

Syntax

```
CTX_OUTPUT.REMOVE_EVENT(event in NUMBER);
```

event

Specify the type of index event to remove from the log. You can remove the following events:

- `CTX_OUTPUT.EVENT_INDEX_PRINT_ROWID`, which logs the rowid of each row after it is indexed. This is useful for debugging a failed index operation.
- `CTX_OUTPUT.EVENT_OPT_PRINT_TOKEN`, which prints each token as it is being optimized.
- `CTX_OUTPUT.EVENT_INDEX_PRINT_TOKEN`, which prints the each token as it is being indexed.

Example

```
begin

CTX_OUTPUT.REMOVE_EVENT(CTX_OUTPUT.EVENT_INDEX_PRINT_ROWID);

end;
```

Related Topics

["ADD_EVENT \(page 11-1\)"](#)

11.11 REMOVE_TRACE

Use this procedure to disable a trace.

Syntax

```
CTX_OUTPUT.REMOVE_TRACE(trace_id BINARY_INTEGER);
```

trace_id

Specify the ID of the trace to disable. See [Table 11-1 \(page 11-3\)](#) for possible values.

Notes

If the trace has not been enabled, an error is raised.

Related Topics

["GET_TRACE_VALUE \(page 11-6\)"](#)

["ADD_TRACE \(page 11-2\)"](#)

["LOG_TRACES \(page 11-6\)"](#)

["RESET_TRACE \(page 11-8\)"](#)

Oracle Text Application Developer's Guide

11.12 RESET_TRACE

Use this procedure to clear a trace (that is, reset it to 0).

Syntax

```
CTX_OUTPUT.RESET_TRACE(trace_id BINARY_INTEGER);
```

trace_id

Specify the ID of the trace to reset. See [Table 11-1](#) (page 11-3) for possible values.

Notes

If the trace has not been enabled, an error is raised.

Related Topics

["REMOVE_TRACE](#) (page 11-8)"

["GET_TRACE_VALUE](#) (page 11-6)"

["ADD_TRACE](#) (page 11-2)"

["LOG_TRACES](#) (page 11-6)"

Oracle Text Application Developer's Guide

11.13 START_LOG

Begin logging index and document service requests.

Syntax

```
CTX_OUTPUT.START_LOG(logfile in varchar2, overwrite in default true);
```

logfile

Specify the name of the log file. The log is stored in the directory specified by the system parameter LOG_DIRECTORY.

overwrite

Specify whether you want to overwrite or append to the original query log file specified by *logfile*, if it already exists. The default is to overwrite the original query log file.

Example

```
begin
  CTX_OUTPUT.START_LOG('mylog1');
end;
```

Notes

Logging is independent of tracing. Logging does not have to be on to start tracing, and vice-versa.

Logging is associated with a session—it can log operations that take place within a single session, and, conversely, cannot make measurements across sessions.

Filenames used in CTX_OUTPUT.START_LOG are restricted to the following characters: alphanumeric, minus, period, space, hash, underscore, single and double quotes. Any other character in the filename will raise an error.

11.14 START_QUERY_LOG

Begin logging query requests into a query log file.

Use `CTX_OUTPUT.END_QUERY_LOG` to stop logging queries. Use `CTX_REPORT.QUERY_LOG_SUMMARY` to obtain reports on logged queries, such as which queries returned successfully the most times.

The query log includes the query string, the index name, and the timestamp of the query, as well as whether or not the query successfully returned a hit. A successful query for the phrase *Blues Guitarists* made at 6:46 (local time) on November 11th, 2003, would be entered into the query log in this form:

```
<QuerySet><TimeStamp>18:46:51 02/04/03</TimeStamp><IndexName>
IDX_SEARCH_TABLE</IndexName><Query>Blues
Guitarists</Query><ReturnHit>Yes</ReturnHit></QuerySet>
```

Syntax

```
CTX_OUTPUT.START_QUERY_LOG(logfile in varchar2, overwrite in default true);
```

logfile

Specify the name of the query log file. The query log is stored in the directory specified by the system parameter `LOG_DIRECTORY`.

overwrite

Specify whether you want to overwrite or append to the original query log file specified by *logfile*, if it already exists. The default is to overwrite the original query log file.

Example

```
begin

CTX_OUTPUT.START_QUERY_LOG('mylog1');
    < get queries >
CTX_OUTPUT.END_QUERY_LOG;

end;
```

Notes

Filenames used in `CTX_OUTPUT.START_QUERY_LOG` are restricted to the following characters: alphanumeric, minus, period, space, hash, underscore, single and double quotes. Any other character in the filename will raise an error.

Logging is associated with a session—it can log operations that take place within a single session, and, conversely, cannot make measurements across sessions.

CTX_QUERY Package

This chapter describes the CTX_QUERY PL/SQL package you can use for generating query feedback, counting hits, and creating stored query expressions.

The CTX_QUERY package includes the following procedures and functions:

Name	Description
BROWSE_WORDS (page 12-1)	Returns the words around a seed word in the index.
COUNT_HITS (page 12-4)	Returns the number hits to a query.
EXPLAIN (page 12-4)	Generates query expression parse and expansion information.
HFEEDBACK (page 12-7)	Generates hierarchical query feedback information (broader term, narrower term, and related term).
REMOVE_SQE (page 12-10)	Removes a specified stored query expression from the SQL tables.
RESULT_SET (page 12-11)	Executes a query and generates a result set.
RESULT_SET_DOCUMENT (page 12-17)	Holds the result set document after the CONTAINS query cursor is explicitly closed and if the query template has the <ctx_result_set_descriptor> element.
STORE_SQE (page 12-18)	Executes a query and stores the results in stored query expression tables.

Note:

You can use this package only when your index type is CONTEXT. This package does not support the CTXCAT index type.

12.1 BROWSE_WORDS

This procedure enables you to browse words in an Oracle Text index. Specify a seed word and BROWSE_WORDS returns the words around it in the index, and an approximate count of the number of documents that contain each word.

This feature is useful for refining queries. You can identify the following words:

- Unselective words (words that have low document count)
- Misspelled words in the document set

Syntax 1: To Store Results in Table

```
ctx_query.browse_words(  
  
  index_name IN   VARCHAR2,  
  seed       IN   VARCHAR2,  
  restab     IN   VARCHAR2,  
  browse_id  IN   NUMBER   DEFAULT 0,  
  numwords   IN   NUMBER   DEFAULT 10,  
  direction  IN   VARCHAR2 DEFAULT BROWSE_AROUND,  
  part_name  IN   VARCHAR2 DEFAULT NULL  
  
);
```

Syntax 2: To Store Results in Memory

```
ctx_query.browse_words(  
  
  index_name IN      VARCHAR2,  
  seed       IN      VARCHAR2,  
  resarr     IN OUT  BROWSE_TAB,  
  numwords   IN      NUMBER   DEFAULT 10,  
  direction  IN      VARCHAR2 DEFAULT BROWSE_AROUND,  
  part_name  IN      VARCHAR2 DEFAULT NULL  
  
);
```

index

Specify the name of the index. You can specify `schema.name`. Must be a local index.

seed

Specify the seed word. This word is lexed before browse expansion. The word need not exist in the token table. `seed` must be a single word. Using multiple words as the seed will result in an error.

restab

Specify the name of the result table. You can enter `restab` as `schema.name`. The table must exist before you call this procedure, and you must have `INSERT` permissions on the table. This table must have the following schema.

Column	Datatype
<code>browse_id</code>	<code>number</code>
<code>word</code>	<code>varchar2(64)</code>
<code>doc_count</code>	<code>number</code>

Existing rows in `restab` are not deleted before `BROWSE_WORDS` is called.

resarr

Specify the name of the result array. `resarr` is of type `ctx_query.browse_tab`.

```
type browse_rec is record (  
  word varchar2(64),  
  doc_count number  
);  
type browse_tab is table of browse_rec index by binary_integer;
```

browse_id

Specify a numeric identifier between 0 and 2^{32} . The rows produced for this browse have a value of in the `browse_id` column in `restab`. When you do not specify `browse_id`, the default is 0.

numwords

Specify the number of words returned.

direction

Specify the direction for the browse. You can specify one of:

value	behavior
BEFORE	Browse seed word and words alphabetically before the seed.
AROUND	Browse seed word and words alphabetically before and after the seed.
AFTER	Browse seed word and words alphabetically after the seed.

Symbols `CTX_QUERY.BROWSE_BEFORE`, `CTX_QUERY.BROWSE_AROUND`, and `CTX_QUERY.BROWSE_AFTER` are defined for these literal values as well.

part_name

Specify the name of the index partition to browse.

Example**Browsing Words with Result Table**

```
begin
ctx_query.browse_words('myindex','dog','myres',numwords=>5,direction=>'AROUND');
end;
```

```
select word, doc_count from myres order by word;
```

WORD	DOC_COUNT
CZAR	15
DARLING	5
DOC	73
DUNK	100
EAR	3

Browsing Words with Result Array

```
set serveroutput on;
declare
    resarr ctx_query.browse_tab;
begin
ctx_query.browse_words('myindex','dog',resarr,5,CTX_QUERY.BROWSE_AROUND);
for i in 1..resarr.count loop
    dbms_output.put_line(resarr(i).word || ':' || resarr(i).doc_count);
end loop;
end;
```

12.2 COUNT_HITS

Returns the number of hits for the specified query. You can call `COUNT_HITS` in exact or estimate mode. Exact mode returns the exact number of hits for the query. Estimate mode returns an upper-bound estimate but runs faster than exact mode.

Syntax

Syntax 1

```
exec CTX_QUERY.COUNT_HITS(  
    index_name  IN VARCHAR2,  
    text_query  IN VARCHAR2,  
    exact       IN BOOLEAN DEFAULT TRUE,  
    part_name   IN VARCHAR2 DEFAULT NULL  
) RETURN NUMBER;
```

Syntax 2

```
exec CTX_QUERY.COUNT_HITS_CLOB_QUERY(  
    index_name  IN VARCHAR2,  
    text_query  IN CLOB,  
    exact       IN BOOLEAN DEFAULT TRUE,  
    part_name   IN VARCHAR2 DEFAULT NULL  
) RETURN NUMBER;
```

index_name

Specify the index name.

text_query

Specify the query.

exact

Specify `TRUE` for an exact count. Specify `FALSE` for an upper-bound estimate.

Specifying `FALSE` returns a less accurate number but runs faster. Specifying `FALSE` might return a number which is too high if rows have been updated or deleted since the last `FULL` index optimize. Optimizing in full mode removes these false hits, and then `EXACT` set to `FALSE` will return the same number as `EXACT` set to `TRUE`.

part_name

Specify the name of the index partition to query.

Notes

If the query contains structured criteria, then you should use `SELECT COUNT(*)`.

If the index was created with the `TRANSACTIONAL` parameter, then `COUNT_HITS` will include pending rowids as well as those that have been synchronized.

12.3 EXPLAIN

Use `CTX_QUERY.EXPLAIN` to generate explain plan information for a query expression. The `EXPLAIN` plan provides a graphical representation of the parse tree for a Text query expression. This information is stored in a result table.

This procedure does *not* execute the query. Instead, this procedure can tell you how a query is expanded and parsed before you enter the query. This is especially useful for stem, wildcard, thesaurus, fuzzy, soundex, or about queries. Parse trees also show the following information:

- Order of execution (precedence of operators)
- ABOUT query normalization
- Query expression optimization
- Stop-word transformations
- Breakdown of composite-word tokens

Knowing how Oracle Text evaluates a query is useful for refining and debugging queries. You can also design your application so that it uses the explain plan information to help users write better queries.

Syntax

Syntax 1

```
exec CTX_QUERY.EXPLAIN(

    index_name      IN VARCHAR2,
    text_query      IN VARCHAR2,
    explain_table   IN VARCHAR2,
    sharelevel      IN NUMBER DEFAULT 0,
    explain_id      IN VARCHAR2 DEFAULT NULL,
    part_name       IN VARCHAR2 DEFAULT NULL

);
```

Syntax 2

```
exec CTX_QUERY.EXPLAIN_CLOB_QUERY(

    index_name      IN VARCHAR2,
    text_query      IN CLOB,
    explain_table   IN VARCHAR2,
    sharelevel      IN NUMBER DEFAULT 0,
    explain_id      IN VARCHAR2 DEFAULT NULL,
    part_name       IN VARCHAR2 DEFAULT NULL

);
```

index_name

Specify the name of the index to be queried.

text_query

Specify the query expression to be used as criteria for selecting rows.

When you include a wildcard, fuzzy, or soundex operator in `text_query`, this procedure looks at the index tables to determine the expansion.

Wildcard, fuzzy (?), and soundex (!) expression feedback does not account for lazy deletes as in regular queries.

explain_table

Specify the name of the table used to store representation of the parse tree for *text_query*. You must have at least INSERT and DELETE privileges on the table used to store the results from EXPLAIN.

See Also:

"EXPLAIN Table (page A-1)" in [Oracle Text Result Tables](#) (page A-1) for more information about the structure of the explain table.

sharelevel

Specify whether `explain_table` is shared by multiple EXPLAIN calls. Specify 0 for exclusive use and 1 for shared use. Default is 0 (single-use).

When you specify 0, the system automatically truncates the result table before the next call to EXPLAIN.

When you specify 1 for shared use, this procedure does not truncate the result table. Only results with the same `explain_id` are updated. When no results with the same `explain_id` exist, new results are added to the EXPLAIN table.

explain_id

Specify a name that identifies the explain results returned by an EXPLAIN procedure when more than one EXPLAIN call uses the same shared EXPLAIN table. Default is NULL.

part_name

Specify the name of the index partition to query.

Example**Creating the Explain Table**

To create an explain table called `test_explain` for example, use the following SQL statement:

```
create table test_explain(
    explain_id varchar2(30),
    id number,
    parent_id number,
    operation varchar2(30),
    options varchar2(30),
    object_name varchar2(64),
    position number,
    cardinality number);
```

Running CTX_QUERY.EXPLAIN

To obtain the expansion of a query expression such as *comp% OR ?smith*, use `CTX_QUERY.EXPLAIN` as follows:

```
ctx_query.explain(
    index_name => 'newindex',
    text_query => 'comp% OR ?smith',
    explain_table => 'test_explain',
    sharelevel => 0,
    explain_id => 'Test');
```

Retrieving Data from Explain Table

To read the explain table, you can select the columns as follows:

```
select explain_id, id, parent_id, operation, options, object_name, position
from test_explain order by id;
```

The output is ordered by ID to simulate a hierarchical query:

EXPLAIN_ID	ID	PARENT_ID	OPERATION	OPTIONS	OBJECT_NAME	POSITION
Test	1	0	OR	NULL	NULL	1
Test	2	1	EQUIVALENCE	NULL	COMP%	1
Test	3	2	WORD	NULL	COMPTROLLER	1
Test	4	2	WORD	NULL	COMPUTER	2
Test	5	1	EQUIVALENCE	(?)	SMITH	2
Test	6	5	WORD	NULL	SMITH	1
Test	7	5	WORD	NULL	SMYTHE	2

Restrictions

CTX_QUERY.EXPLAIN does not support the use of query templates.

You cannot use CTX_QUERY.EXPLAIN with remote queries.

Related Topics

[Oracle Text CONTAINS Query Operators](#) (page 3-1)

[Stopword Transformations in Oracle Text](#) (page H-1)

12.4 HFEEDBACK

In English or French, this procedure generates hierarchical query feedback information (broader term, narrower term, and related term) for the specified query.

Broader term, narrower term, and related term information is obtained from the knowledge base. However, only knowledge base terms that are also in the index are returned as query feedback information. This increases the chances that terms returned from HFEEDBACK produce hits over the currently indexed document set.

Hierarchical query feedback information is useful for suggesting other query terms to the user.

Syntax

Syntax 1

```
exec CTX_QUERY.HFEEDBACK(
    index_name      IN VARCHAR2,
    text_query      IN VARCHAR2,
    feedback_table  IN VARCHAR2,
    sharelevel      IN NUMBER DEFAULT 0,
    feedback_id     IN VARCHAR2 DEFAULT NULL,
    part_name       IN VARCHAR2 DEFAULT NULL
);
```

Syntax 2

```
exec CTX_QUERY.HFEEDBACK_CLOB_QUERY(
    index_name      IN VARCHAR2,
    text_query      IN CLOB,
    feedback_table  IN VARCHAR2,
    sharelevel      IN NUMBER DEFAULT 0,
```

```
        feedback_id    IN VARCHAR2 DEFAULT NULL,  
        part_name      IN VARCHAR2 DEFAULT NULL  
    );
```

index_name

Specify the name of the index for the text column to be queried.

text_query

Specify the query expression to be used as criteria for selecting rows.

feedback_table

Specify the name of the table used to store the feedback terms.

See Also:

["HFEEDBACK Table \(page A-3\)" in Oracle Text Result Tables](#)
(page A-1) for more information about the structure of the explain table.

sharelevel

Specify whether `feedback_table` is shared by multiple `HFEEDBACK` calls. Specify 0 for exclusive use and 1 for shared use. Default is 0 (single-use).

When you specify 0, the system automatically truncates the feedback table before the next call to `HFEEDBACK`.

When you specify 1 for shared use, this procedure does not truncate the feedback table. Only results with the same `feedback_id` are updated. When no results with the same `feedback_id` exist, new results are added to the feedback table.

feedback_id

Specify a value that identifies the feedback results returned by a call to `HFEEDBACK` when more than one `HFEEDBACK` call uses the same shared feedback table. Default is `NULL`.

part_name

Specify the name of the index partition to query.

Example

Create `HFEEDBACK` Result Table

Create a result table to use with `CTX_QUERY.HFEEDBACK` as follows:

```
CREATE TABLE restab (  
    feedback_id VARCHAR2(30),  
    id          NUMBER,  
    parent_id   NUMBER,  
    operation   VARCHAR2(30),  
    options     VARCHAR2(30),  
    object_name VARCHAR2(80),  
    position    NUMBER,  
    bt_feedback ctxsys.ctx_feedback_type,  
    rt_feedback ctxsys.ctx_feedback_type,  
    nt_feedback ctxsys.ctx_feedback_type,  
    NESTED TABLE bt_feedback STORE AS res_bt,  
    NESTED TABLE rt_feedback STORE AS res_rt,  
    NESTED TABLE nt_feedback STORE AS res_nt
```

;

[CTX_FEEDBACK_TYPE](#) (page A-5) is a system-defined type in the CTXSYS schema.

See Also:

"[HFEEDBACK Table](#) (page A-3)" in [Oracle Text Result Tables](#) (page A-1) for more information about the structure of the HFEEDBACK table.

Call CTX_QUERY.HFEEDBACK

The following code calls the HFEEDBACK procedure with the query *computer industry*.

```
BEGIN
ctx_query.hfeedback (index_name      => 'my_index',
                    text_query       => 'computer industry',
                    feedback_table    => 'restab',
                    sharelevel        => 0,
                    feedback_id      => 'query10'
                    );
END;
```

Select From the Result Table

The following code extracts the feedback data from the result table. It extracts broader term, narrower term, and related term feedback separately from the nested tables.

```
DECLARE
  i NUMBER;
BEGIN
  FOR frec IN (
    SELECT object_name, bt_feedback, rt_feedback, nt_feedback
    FROM restab
    WHERE feedback_id = 'query10' AND object_name IS NOT NULL
  ) LOOP

    dbms_output.put_line('Broader term feedback for ' || frec.object_name ||
    ':');
    i := frec.bt_feedback.FIRST;
    WHILE i IS NOT NULL LOOP
      dbms_output.put_line(frec.bt_feedback(i).text);
      i := frec.bt_feedback.NEXT(i);
    END LOOP;

    dbms_output.put_line('Related term feedback for ' || frec.object_name ||
    ':');
    i := frec.rt_feedback.FIRST;
    WHILE i IS NOT NULL LOOP
      dbms_output.put_line(frec.rt_feedback(i).text);
      i := frec.rt_feedback.NEXT(i);
    END LOOP;

    dbms_output.put_line('Narrower term feedback for ' || frec.object_name ||
    ':');
    i := frec.nt_feedback.FIRST;
    WHILE i IS NOT NULL LOOP
      dbms_output.put_line(frec.nt_feedback(i).text);
      i := frec.nt_feedback.NEXT(i);
    END LOOP;
  END LOOP;
```

```
END LOOP;  
  
END LOOP;  
END;
```

Sample Output

The following output is for the preceding example, which queries on *computer industry*:

```
Broader term feedback for computer industry:  
hard sciences  
Related term feedback for computer industry:  
computer networking  
electronics  
knowledge  
library science  
mathematics  
optical technology  
robotics  
satellite technology  
semiconductors and superconductors  
symbolic logic  
telecommunications industry  
Narrower term feedback for computer industry:  
ABEND - abnormal end of task  
AT&T Starlans  
ATI Technologies, Incorporated  
ActivCard  
Actrade International Ltd.  
Alta Technology  
Amiga Format  
Amiga Library Services  
Amiga Shopper  
Amstrat Action  
Apple Computer, Incorporated  
..
```

Note:

The HFEEDBACK information you obtain depends on the contents of your index and knowledge base and as such might differ from the sample shown.

Restrictions

CTX_QUERY.HFEEDBACK does not support the use of query templates.

12.5 REMOVE_SQE

The CTX_QUERY.REMOVE_SQE procedure removes the specified stored query expression.

CTX_QUERY.REMOVE_SQE can be used to remove both session-duration and persistent SQEs. See "[STORE_SQE](#) (page 12-18)".

Since the query_name namespace is shared between the persistent and session-duration SQEs, it is unnecessary to specify the duration of the SQE to be removed.

Syntax

```
CTX_QUERY.REMOVE_SQE(  
    query_name IN VARCHAR2  
);
```

query_name

Specify the name of the stored or session-duration query expression to be removed.

Example

```
begin  
    ctx_query.remove_sqe('dis1');  
    ctx_query.remove_sqe('dis2');  
end;  
/
```

12.6 RESULT_SET

This procedure executes an XML query and generates a result set in XML. The Result Set Interface can return data views that are difficult to express in SQL.

See Also:

Oracle Text Application Developer's Guide for details on how to use the Result Set Interface

Syntax

```
CTX_QUERY.RESULT_SET (  
    index_name          IN VARCHAR2,  
    query               IN VARCHAR2,  
    result_set_descriptor IN CLOB,  
    result_set          IN OUT NOCOPY CLOB,  
    part_name           IN VARCHAR2 DEFAULT NULL  
);
```

index_name

Specify the index against which to execute the query.

query

Specify the query string.

result_set_descriptor

Specify the result set descriptor in XML. It describes what the result set should contain. See "[The Input Result Set Descriptor](#) (page 12-12)" for more details.

result_set

Specify the output result set. If this variable is NULL on input, a session-duration temporary lob will be allocated and returned to the user. The user is responsible for deallocating this temporary lob. See "[The Output Result Set XML](#) (page 12-14)" for more details.

part_name

Specify the index partition name. If the index is global, `part_name` must be `NULL`. If the index is partitioned and `part_name` is not `NULL`, then the query will only be evaluated for the given partition. If the index is partitioned and `part_name` is `NULL`, then the query will be evaluated for all partitions.

The Input Result Set Descriptor

The result set descriptor is an XML message which describes what to calculate for the result set. The elements present in the result set descriptor and the order in which they occur serve as a simple template, specifying what to include in the output result set. That is, there should be the list of hit rowids, then a count, then a token count, and so on. The attributes of the elements specify the parameters and options to the specific operations, such as number of hits in the list of rowids, estimate versus exact count, and so on.

The result set descriptor itself is XML conforming to the following DTD:

```
<!ELEMENT ctx_result_set_descriptor (hitlist?, group*, count?)>
<!ELEMENT hitlist (rowid?, score?, sdata*)>
<!ELEMENT group(count?)>
<!ELEMENT count EMPTY>
<!ELEMENT rowid EMPTY>
<!ELEMENT score EMPTY>
<!ELEMENT sdata EMPTY>
<!--ATTLIST group sdata CDATA #REQUIRED-->
<!--ATTLIST hitlist start_num_hit integer #REQUIRED-->
<!--ATTLIST hitlist end_num_hit integer #REQUIRED-->
<!--ATTLIST hitlist order PCDATA #IMPLIED-->
<!--ATTLIST count exact (TRUE|FALSE) "FALSE"-->
<!--ATTLIST sdata name CDATA #REQUIRED-->
```

The following is a description of the possible XML elements for the result set descriptor:

- `ctx_result_set_descriptor`

This is the root element for the result set descriptor. The parent element is none, as are the available attributes.

The possible child elements are:

- Zero or more `hitlist` elements.
- Zero or more `group` elements.
- At most one `count` element.

- `group`

The `group` element causes the generated result set to include a group breakdown. In other words, a breakdown of the results by `SDATA` section values. The parent element is `ctx_result_set_descriptor`, and the available attributes are:

- `sdata`
Specifies the name of the `SDATA` section to use for grouping. It is required.

Possible child elements of `group` are:

- At most one `count` element.

- `hitlist`

The `hitlist` element controls inclusion of a list of hit documents. The parent element is `ctx_result_set_descriptor`, and the available attributes are:

The possible child elements of order are:

- `start_hit_num`

This specifies the starting document hit to be included in the generated result set. This can be set to any positive integer less than or equal to 16000. For example, if `start_hit_num` is 21, then the result set will include document hits starting from the 21st document hit. This element is required.

- `end_hit_num`

This specifies the last document hit to be included in the generated result set. This can be set to any positive integer less than or equal to 16000. For example, if `end_hit_num` is 40, then the result set will include document hits up to the 40th document hit. This element is required.

The possible child elements for `hitlist` are:

- At most one `rowid` element.
- At most one `score` element.
- At most one `sdata` element.
- At most one `snippet` element.
- `order`

This is an optional attribute that specifies the order for the documents in the generated result set. The value is a list similar to a SQL `ORDER BY` statement, except that, instead of column names, they can either be `SCORE` or `SDATA` section names. In the following example, `MYDATE` and `MYPRICE` are the `SDATA` section names:

```
(order = "SCORE DESC, MYDATE, MYPRICE DESC")
```

- At most one `rowid` element.
- At most one `score` element.
- At most one `sdata` element.

- `count`

This element causes the generated result set to include a count of the number of hit documents. The parent elements are:

- `ctx_result_set_descriptor`
- `group`

The available attributes for `count` are:

- `exact`

This is to estimate mode. Set to `true` or `false`. It is required, and the default is `false`.

The possible child elements for `count` are none.

- `rowid`

This child element causes the generated result set to include `rowid` information for each hit. The parent element is `hitlist`. There are no attributes and no possible child elements.
- `score`

This child element causes the generated result set to include `score` information for each hit.

 - The parent element is `hitlist`.
 - There are no available attributes, and no possible child elements.
- `sdata`

This child element causes the generated result set to include `sdata` values for each hit.

 - The parent element is `hitlist`.
 - The available attribute is `name`. This specifies the name of the `sdata` section. It is required.
 - There are no child elements.

The Output Result Set XML

The output result set XML is XML conforming to the following DTD:

```
<!ELEMENT ctx_result_set (hitlist?, groups*, count?)>
<!ELEMENT hitlist (hit*)>
<!ELEMENT hit(rowid?, score?, sdata*)>
<!ELEMENT groups (group*)>
<!ELEMENT group (count?)>
<!ELEMENT count CDATA>
<!ELEMENT rowid CDATA>
<!ELEMENT score CDATA>
<!ELEMENT sdata CDATA>
<!ATTLIST groups sdata CDATA #REQUIRED>
<!ATTLIST group value CDATA #REQUIRED>
<!ATTLIST sdata name CDATA #REQUIRED>
```

The following is a description of the list of possible XML elements for the output result set:

- `ctx_result_set`

This is the root element for the generated result set. There are no attributes. The parent is none. The possible child elements are:

 - At most one `hitlist` element.
 - Zero or more `groups` elements.
- `groups`

This delimits the start of a group breakdown section. The parent element is `ctx_result_set`. The available attributes are:

 - `sdata`

This is the name of the `sdata` section used for grouping.

The possible child elements are:

- Zero or more `group` elements.

- `group`

This delimits the start of a `GROUP BY` value. The parent element is the `groups` element. The available attributes are:

- `value`

This is the value of the `sdata` section.

The possible child elements are at most one `count` element.

- `hitlist`

This delimits the start of `hitlist` information. The parent element is `ctx_result_set`, while the children are zero or more `hit` elements. There are no attributes.

- `hit`

This delimits the start of the information for a particular document within a `hitlist`. The parent element is `hitlist`, and there are no available attributes. The possible child elements are:

- Zero or one `rowid` elements.
- Zero or one `score` element.
- Zero or one `sdata` element.
- Zero or one `snippet` element.

- `rowid`

This is the `rowid` of the document, so the content is the `rowid` of the document. The parent element is the `hit` element. There are no child elements, and no available attributes.

- `score`

This is the score of the document. The parent element is the `hit` element. The content is the numeric score. There are no available attributes, and no possible child elements.

- `sdata`

This is the `SDATA` value or values for the document. The parent element is the `hit` element, and the available attribute is `name`, which is the name of the `sdata` section. There are no possible child elements available. The content is the `SDATA` section value, which, for `DATE` values, is in the format "YYYY-MM-DD HH24:MI:SS", depending upon the actual values being stored.

- `count`

This is the document hit count. The parent element is the `ctx_result_set` element or the `group` element. It contains the numeric hit count, and has no attributes, and no possible child elements.

Example

This call to `CTX_QUERY.RESULT_SET` with the specified XML `result_set_descriptor` will generate the following information in the form of XML:

- top 20 hits displaying, score, rowid, author `SDATA` section value, and pubDate `SDATA` section value, order by pubDate `SDATA` section value `DESC` and score `DESC`
- total doc hit count for the text query
- counts group by pubDate `SDATA` section values
- counts group by author `SDATA` section values

```
declare
  rs clob;
begin
  dbms_lob.createtemporary(rs, true, dbms_lob.session);
  ctx_query.result_set('docidx', 'oracle', '
<ctx_result_set_descriptor>
  <count/>
  <hitlist start_hit_num="1" end_hit_num="5" order="pubDate desc, score desc">
    <score/>
    <rowid/>
    <sdata name="author"/>
    <sdata name="pubDate"/>
  </hitlist>
  <group sdata="pubDate">
    <count/>
  </group>
  <group sdata="author">
    <count/>
  </group>
</ctx_result_set_descriptor>
', rs);
  dbms_lob.freetemporary(rs);
exception
  when others then
    dbms_lob.freetemporary(rs);
    raise;
end;
/
```

The XML output store in the result set output clob will resemble the following:

```
<ctx_result_set>
  <hitlist>
    <hit>
      <score>3</score><rowid>AAAPoEAABAAAMWsAAC</rowid>
      <sdata name="AUTHOR">John</sdata>
      <sdata name="PUBDATE">2001-01-03 00:00:00</sdata>
    </hit>
    <hit>
      <score>3</score><rowid>AAAPoEAABAAAMWsAAG</rowid>
      <sdata name="AUTHOR">John</sdata>
      <sdata name="PUBDATE">2001-01-03 00:00:00</sdata>
    </hit>
    <hit>
      <score>3</score><rowid>AAAPoEAABAAAMWsAAK</rowid>
      <sdata name="AUTHOR">John</sdata>
      <sdata name="PUBDATE">2001-01-03 00:00:00</sdata>
```

```

</hit>
<hit>
  <score>3</score><rowid>AAPoEAABAAAMWsAAO</rowid>
  <sdata name="AUTHOR">John</sdata>
  <sdata name="PUBDATE">2001-01-03 00:00:00</sdata>
</hit>
<hit>
  <score>3</score><rowid>AAPoEAABAAAMWsAAS</rowid>
  <sdata name="AUTHOR">John</sdata>
  <sdata name="PUBDATE">2001-01-03 00:00:00</sdata>
</hit>
</hitlist>

<count>100</count>

<groups sdata="PUBDATE">
  <group value="2001-01-01 00:00:00"><count>25</count></group>
  <group value="2001-01-02 00:00:00"><count>50</count></group>
  <group value="2001-01-03 00:00:00"><count>25</count></group>
</groups>

<groups sdata="AUTHOR">
  <group value="John"><count>50</count></group>
  <group value="Mike"><count>25</count></group>
  <group value="Steve"><count>25</count></group>
</groups>

</ctx_result_set>

```

Limitations and Restrictions

The following limitations and restrictions apply for RESULT_SET.

- The Result Set Interface (RSI) is not supported with Virtual Private Database. (VPD is supported with the regular CONTAINS query, but not with RSI.)
- In order to execute the function, you must be able to query the base table.
- If a VPD policy is active on the base table, the documents portion of the result set will not show any documents to which you are not entitled.
- When a VPD policy is being used, aggregate measures such as count may not be accurate.

Related Topics

Oracle Text Application Developer's Guide for information on the XML Result Set Interface

12.7 RESULT_SET_DOCUMENT

RESULT_SET_DOCUMENT holds the result set document after the CONTAINS query cursor is explicitly closed and if the query template has the <ctx_result_set_descriptor> element.

Syntax

```

CTX_QUERY.RESULT_SET_DOCUMENT(
  index_name          IN VARCHAR2,
  query               IN VARCHAR2,

```

```
result_set_descriptor IN CLOB,  
result_set            IN OUT NOCOPY CLOB,  
part_name             IN VARCHAR2 DEFAULT NULL  
);
```

index_name

Specify the index against which to execute the query.

query

Specify the query string.

result_set_descriptor

Specify the result set descriptor in XML. It describes what the result set should contain. See "[The Input Result Set Descriptor](#) (page 12-12)" for more details.

result_set

Specify the output result set. If this variable is NULL on input, a session-duration temporary lob will be allocated and returned to the user. The user is responsible for deallocating this temporary lob. See "[The Output Result Set XML](#) (page 12-14)" for more details.

part_name

Specify the index partition name. If the index is global, `part_name` must be NULL. If the index is partitioned and `part_name` is not NULL, then the query will only be evaluated for the given partition. If the index is partitioned and `part_name` is NULL, then the query will be evaluated for all partitions.

12.8 STORE_SQE

This procedure creates either a stored or session-duration query expression (SQE). Only the query definition is stored.

SQEs are used to store the definition of a query without storing any results. Referencing the query with the `CONTAINS` SQL operator references the definition of the query. In this way, SQEs make it easy for defining long or frequently used query expressions. Creating a session-duration SQE is useful for when you do not want the maintenance overhead of deleting unused or no longer needed SQEs.

Supported Operators

Stored query expressions support all of the `CONTAINS` query operators. Stored query expressions also support all of the special characters and other components that can be used in a query expression, including other stored query expressions.

Privileges

Users are permitted to create and remove stored query expressions owned by them. Users are permitted to use stored query expressions owned by anyone. The `CTXSYS` user can create or remove stored query expressions for any user.

Syntax**Syntax 1**

```
CTX_QUERY.STORE_SQE(  
    query_name      IN VARCHAR2,  
    text_query      IN VARCHAR2
```

```

        duration          IN NUMBER default CTX_QUERY.DURATION_SESSION
    );

```

Syntax 2

```

CTX_QUERY.STORE_SQE_CLOB_SYNTAX(
    query_name          IN VARCHAR2,
    text_query          IN CLOB
    duration            IN NUMBER default CTX_QUERY.DURATION_SESSION
);

```

query_name

Specify the name of the stored query expression to be created.

text_query

Specify the query expression to be associated with `query_name`.

duration

The possible values are `DURATION_SESSION` and `DURATION_PERSISTENT`.

- When `duration` is set to `DURATION_SESSION`, the stored query expression is stored in a PL/SQL package variable and is available for the session.
- When `duration` is set to `DURATION_PERSISTENT`, the stored query expression is stored in a database table, and can be referenced by other database sessions.
- The `query_name` namespace is shared between the persistent and session-duration SQEs. If you try to add a persistent or session-duration SQE with a name that is already used by another persistent or session-duration SQE, then an error will be raised.

duration_persistent

When there is a CLOB query, specify that the duration is stored in a database table. This SQE must be deleted when it is no longer needed.

- The `query_name` namespace is shared between the persistent and session-duration SQEs. If you try to add a persistent or session-duration SQE with a name that is already used by another persistent or session-duration SQE, then an error will be raised.

Example

```

begin
    ctx_query.store_sqe('dis1', 'flood', CTX_QUERY.DURATION_SESSION);
    ctx_query.store_sqe('dis2', 'tornado', CTX_QUERY.DURATION_PERSISTENT);
    ctx_query.store_sqe('dis3', 'fire')
end;
/

```

CTX_REPORT Package

This chapter describes how to use the CTX_REPORT package to create reports on indexing and querying. These reports can help you troubleshoot problems or fine-tune your applications.

This chapter contains the following topics:

- [Description of Procedures in CTX_REPORT](#) (page 13-1)
- [Using the Function Versions](#) (page 13-2)
- [DESCRIBE_INDEX](#) (page 13-2)
- [DESCRIBE_POLICY](#) (page 13-3)
- [CREATE_INDEX_SCRIPT](#) (page 13-4)
- [CREATE_POLICY_SCRIPT](#) (page 13-5)
- [INDEX_SIZE](#) (page 13-5)
- [INDEX_STATS](#) (page 13-6)
- [QUERY_LOG_SUMMARY](#) (page 13-10)
- [TOKEN_INFO](#) (page 13-14)
- [TOKEN_TYPE](#) (page 13-15)
- [VALIDATE_INDEX](#) (page 13-17)

See Also:

Oracle Text Application Developer's Guide for an overview of the CTX_REPORT package and how you can use the various procedures described in this chapter

13.1 Description of Procedures in CTX_REPORT

The CTX_REPORT package contains the following procedures:

Name	Description
DESCRIBE_INDEX (page 13-2)	Creates a report describing the index.

Name	Description
DESCRIBE_POLICY (page 13-3)	Creates a report describing a policy.
CREATE_INDEX_SCRIPT (page 13-4)	Creates a SQL*Plus script to duplicate the named index.
CREATE_POLICY_SCRIPT (page 13-5)	Creates a SQL*Plus script to duplicate the named policy.
INDEX_SIZE (page 13-5)	Creates a report to show the internal objects of an index, their tablespaces and used sizes.
INDEX_STATS (page 13-6)	Creates a report to show the various statistics of an index.
QUERY_LOG_SUMMARY (page 13-10)	Creates a report showing query statistics
TOKEN_INFO (page 13-14)	Creates a report showing the information for a token, decoded.
TOKEN_TYPE (page 13-15)	Translates a name and returns a numeric token type.
VALIDATE_INDEX (page 13-17)	Checks for index corruption and reports on problems found. Mainly used with Oracle Support.

13.2 Using the Function Versions

Some of the procedures in the CTX_REPORT package have function versions. You can call these functions as follows:

```
select ctx_report.describe_index('MYINDEX') from dual;
```

In SQL*Plus, to generate an output file to send to support, you can do:

```
set long 64000
set pages 0
set heading off
set feedback off
spool outputfile
select ctx_report.describe_index('MYINDEX') from dual;
spool off
```

13.3 DESCRIBE_INDEX

Creates a report describing the index. This includes the settings of the index metadata, the indexing objects used, the settings of the attributes of the objects, and index partition descriptions, if any.

You can call this operation as a procedure with an IN OUT CLOB parameter or as a function that returns the report as a CLOB.

Syntax

```
procedure CTX_REPORT.DESCRIBE_INDEX(
  index_name      IN VARCHAR2,
  report          IN OUT NOCOPY CLOB,
  report_format   IN VARCHAR2 DEFAULT FMT_TEXT
```

```
);  
  
function CTX_REPORT.DESCRIBE_INDEX(  
    index_name      IN VARCHAR2,  
    report_format   IN VARCHAR2 DEFAULT FMT_TEXT  
) return CLOB;
```

index_name

Specify the name of the index to describe.

report

Specify the CLOB locator to which to write the report.

If `report` is NULL, a session-duration temporary CLOB will be created and returned. It is the caller's responsibility to free this temporary CLOB as needed.

The `report` CLOB will be truncated before report is generated, so any existing contents will be overwritten by this call.

report_format

Specify whether the report should be generated as 'TEXT' or as 'XML'. TEXT is the default. You can also specify the values `CTX_REPORT.FMT_TEXT` or `CTX_REPORT.FMT_XML`.

Notes

`CTX_REPORT.DESCRIBE_INDEX` outputs `FILTER BY` and `ORDER BY` column information if the index is created with `FILTER BY` and/or `ORDER BY` clauses.

Related Topics

["CREATE INDEX \(page 1-40\)"](#)

["ADD_SDATA_COLUMN \(page 8-14\)"](#)

13.4 DESCRIBE_POLICY

Creates a report describing the policy. This includes the settings of the policy metadata, the indexing objects used, and the settings of the attributes of the objects.

You can call this operation as a procedure with an IN OUT CLOB parameter or as a function that returns the report as a CLOB.

Syntax

```
procedure CTX_REPORT.DESCRIBE_POLICY(  
    policy_name      IN VARCHAR2,  
    report           IN OUT NOCOPY CLOB,  
    report_format    IN VARCHAR2 DEFAULT FMT_TEXT  
)  
;  
  
function CTX_REPORT.DESCRIBE_POLICY(  
    policy_name      IN VARCHAR2,  
    report_format    IN VARCHAR2 DEFAULT FMT_TEXT  
) return CLOB;
```

report

Specify the CLOB locator to which to write the report.

If `report` is `NULL`, a session-duration temporary `CLOB` will be created and returned. It is the caller's responsibility to free this temporary `CLOB` as needed.

The `report` `CLOB` will be truncated before `report` is generated, so any existing contents will be overwritten by this call.

report_format

Specify whether the report should be generated as 'TEXT' or as 'XML'. TEXT is the default. You can also specify the values `CTX_REPORT.FMT_TEXT` or `CTX_REPORT.FMT_XML`.

policy_name

Specify the name of the policy to describe.

13.5 CREATE_INDEX_SCRIPT

Creates a SQL*Plus script which will create a text index that duplicates the named text index.

The created script will include creation of preferences identical to those used in the named text index. However, the names of the preferences will be different.

You can call this operation as a procedure with an `IN OUT CLOB` parameter or as a function that returns the report as a `CLOB`.

Syntax

```
procedure CTX_REPORT.CREATE_INDEX_SCRIPT(  
    index_name      in varchar2,  
    report          in out nocopy clob,  
    prefname_prefix in varchar2 default null  
);
```

```
function CTX_REPORT.CREATE_INDEX_SCRIPT(  
    index_name      in varchar2,  
    prefname_prefix in varchar2 default null  
) return clob;
```

index_name

Specify the name of the index.

report

Specify the `CLOB` locator to which to write the script.

If `report` is `NULL`, a session-duration temporary `CLOB` will be created and returned. It is the caller's responsibility to free this temporary `CLOB` as needed.

The `report` `CLOB` will be truncated before `report` is generated, so any existing contents will be overwritten by this call.

prefname_prefix

Specify optional prefix to use for preference names.

If `prefname_prefix` is omitted or `NULL`, index name will be used. The `prefname_prefix` follows index length restrictions.

Notes

CTX_REPORT.CREATE_INDEX_SCRIPT will also generate necessary FILTER BY and ORDER BY clauses for CREATE INDEX statements.

Related Topics

["CREATE INDEX \(page 1-40\)"](#)

13.6 CREATE_POLICY_SCRIPT

Creates a SQL*Plus script which will create a text policy that duplicates the named text policy.

The created script will include creation of preferences identical to those used in the named text policy.

You can call this operation as a procedure with an IN OUT CLOB parameter or as a function that returns the report as a CLOB.

Syntax

```
procedure CTX_REPORT.CREATE_POLICY_SCRIPT(
  policy_name      in varchar2,
  report           in out nocopy clob,
  prefname_prefix  in varchar2 default null
);
```

```
function CTX_REPORT.CREATE_POLICY_SCRIPT(
  policy_name      in varchar2,
  prefname_prefix  in varchar2 default null
) return clob;
```

policy_name

Specify the name of the policy.

report

Specify the locator to which to write the script.

If report is NULL, a session-duration temporary CLOB will be created and returned. It is the caller's responsibility to free this temporary CLOB as needed.

The report CLOB will be truncated before report is generated, so any existing contents will be overwritten by this call.

prefname_prefix

Specify the optional prefix to use for preference names. If prefname_prefix is omitted or NULL, policy name will be used. prefname_prefix follows policy length restrictions.

13.7 INDEX_SIZE

Creates a report showing the internal objects of the text index or text index partition, and their tablespaces, allocated, and used sizes.

You can call this operation as a procedure with an IN OUT CLOB parameter, or as a function that returns the report as a CLOB.

Syntax

```
procedure CTX_REPORT.INDEX_SIZE(  
    index_name      IN VARCHAR2,  
    report          IN OUT NOCOPY CLOB,  
    part_name       IN VARCHAR2 DEFAULT NULL,  
    report_format    IN VARCHAR2 DEFAULT FMT_TEXT  
);  
  
function CTX_REPORT.INDEX_SIZE(  
    index_name      IN VARCHAR2,  
    part_name       IN VARCHAR2 DEFAULT NULL,  
    report_format    IN VARCHAR2 DEFAULT FMT_TEXT  
) return clob;
```

index_name

Specify the name of the index to describe.

report

Specify the CLOB locator to which to write the report.

If `report` is NULL, a session-duration temporary CLOB will be created and returned. It is the caller's responsibility to free this temporary CLOB as needed.

The `report` CLOB will be truncated before report is generated, so any existing contents will be overwritten by this call

part_name

Specify the name of the index partition (optional). If `part_name` is NULL, and the index is a local partitioned text index, then all objects of all partitions will be displayed. If `part_name` is provided, then only the objects of a particular partition will be displayed.

report_format

Specify whether the report should be generated as 'TEXT' or as 'XML'. TEXT is the default. You can also specify the values `CTX_REPORT.FMT_TEXT` or `CTX_REPORT.FMT_XML`.

Notes

`CTX_REPORT.INDEX_SIZE` will also output information on `dr$indexname$S` table.

Related Topics

["CREATE INDEX \(page 1-40\)"](#)

[Table 2-39 \(page 2-81\)](#)

13.8 INDEX_STATS

Creates a report showing various calculated statistics about the text index.

This procedure fully scans the text index tables, so it may take a long time to run for large indexes.

Syntax

```
procedure ctx_report.index_stats(  
    index_name      IN VARCHAR2,
```

```

report      IN OUT NOCOPY CLOB,
part_name   IN VARCHAR2 DEFAULT NULL,
frag_stats  IN BOOLEAN DEFAULT TRUE,
list_size   IN NUMBER DEFAULT 100,
report_format IN VARCHAR2 DEFAULT FMT_TEXT,
stat_type   IN VARCHAR2 DEFAULT NULL
);

```

index_name

Specify the name of the index to describe. This must be a CONTEXT index.

report

Specify the CLOB locator to which to write the report. If report is NULL, a session-duration temporary CLOB will be created and returned. It is the caller's responsibility to free this temporary CLOB as needed.

The report CLOB will be truncated before report is generated, so any existing contents will be overwritten by this call.

part_name

Specify the name of the index partition. If the index is a local partitioned index, then part_name must be provided. INDEX_STATS will calculate the statistics for that index partition.

frag_stats

Specify TRUE to calculate fragmentation statistics. If frag_stats is FALSE, the report will not show any statistics relating to size of index data. However, the operation should take less time and resources to calculate the token statistics.

list_size

Specify the number of elements in each compiled list. list_size has a maximum value of 1000.

report_format

Specify whether the report should be generated as 'TEXT' or as 'XML'. TEXT is the default. You can also specify the values CTX_REPORT.FMT_TEXT or CTX_REPORT.FMT_XML.

stat_type

Specify the estimated statistics to output. If this parameter is set, then frag_stats is ignored. The possible values are:

Statistics Type	Description
EST_FRAG_STATS	Get the estimated fragmentation stats for the index. When this type is given list_size is ignored.
EST_FREQUENT_TOKENS	Get the estimated frequently queried tokens for the index. You can give a value of up to 100 for list_size.
EST_TOKENS_TO_OPTIMIZE	Show best tokens to optimize, based on frequency of querying and fragmentation. You can give a value of up to 100 for list_size.

Statistics Type	Description
EST_SLOWEST_QUERIES	Show slowest running queries for the index. You can give a value of up to 100 for list_size.

Note:

The estimated statistics for `stat_type` is only available if `query_stats` is enabled. See [CTX_OUTPUT.ENABLE_QUERY_STATS](#) (page 11-4) and [CTX_OUTPUT.DISABLE_QUERY_STATS](#) (page 11-4).

Example

```
create table output (result CLOB);

declare
  x clob := null;
begin
  ctx_report.index_stats('tdrbprx21',x);
  insert into output values (x);
  commit;
  dbms_lob.freetemporary(x);
end;
/

set long 32000
set head off
set pagesize 10000
select * from output;
```

The following sample output is for INDEX_STATS on a context index. This report has been truncated for clarity. It shows some of the token statistics and all of the fragmentation statistics.

The fragmentation statistics are at the end of the report. It tells you optimal row fragmentation, an estimated amount of garbage data in the index, and a list of the most fragmented tokens. Running `CTX_DDL.OPTIMIZE_INDEX` cleans up the index.

```
=====
STATISTICS FOR "DR_TEST"."TDRBPRX21"
=====

indexed documents:                    53
allocated docids:                     68
$I rows:                             16,259

-----
TOKEN STATISTICS
-----

unique tokens:                        13,445
average $I rows for each token:       1.21
tokens with most $I rows:
  telecommunications industry (THEME) 6
  science and technology (THEME)      6
  EMAIL (FIELD SECTION "SOURCE")      6
  DEC (FIELD SECTION "TIMESTAMP")     6
```

electronic mail (THEME)	6
computer networking (THEME)	6
communications (THEME)	6
95 (FIELD SECTION "TIMESTAMP")	6
15 (FIELD SECTION "TIMESTAMP")	6
HEADLINE (ZONE SECTION)	6
average size for each token:	8
tokens with largest size:	
T (NORMAL)	405
SAID (NORMAL)	313
HEADLINE (ZONE SECTION)	272
NEW (NORMAL)	267
I (NORMAL)	230
MILLION (PREFIX)	222
D (NORMAL)	219
MILLION (NORMAL)	215
U (NORMAL)	192
DEC (FIELD SECTION "TIMESTAMP")	186
average frequency for each token:	2.00
most frequent tokens:	
HEADLINE (ZONE SECTION)	68
DEC (FIELD SECTION "TIMESTAMP")	62
95 (FIELD SECTION "TIMESTAMP")	62
15 (FIELD SECTION "TIMESTAMP")	62
T (NORMAL)	61
D (NORMAL)	59
881115 (THEME)	58
881115 (NORMAL)	58
I (NORMAL)	55
geography (THEME)	52
token statistics by type:	
token type:	NORMAL
unique tokens:	6,344
total rows:	7,631
average rows:	1.20
total size:	67,445 (65.86 KB)
average size:	11
average frequency:	2.33
most frequent tokens:	
T	61
D	59
881115	58
I	55
SAID	45
C	43
NEW	36
MILLION	32
FIRST	28
COMPANY	27
token type:	THEME
unique tokens:	4,563
total rows:	5,523
average rows:	1.21
total size:	21,930 (21.42 KB)
average size:	5
average frequency:	2.40
most frequent tokens:	

881115	58
political geography	52
geography	52
United States	51
business and economics	50
abstract ideas and concepts	48
North America	48
science and technology	46
NKS	34
nulls	34

The fragmentation portion of this report is as follows:

FRAGMENTATION STATISTICS	
total size of \$I data:	
	116,772 (114.04 KB)
\$I rows:	
	16,259
estimated \$I rows if optimal:	
	13,445
estimated row fragmentation:	
	17 %
garbage docids:	
	15
estimated garbage size:	
	21,379 (20.88 KB)
most fragmented tokens:	
telecommunications industry (THEME)	83 %
science and technology (THEME)	83 %
EMAIL (FIELD SECTION "SOURCE")	83 %
DEC (FIELD SECTION "TIMESTAMP")	83 %
electronic mail (THEME)	83 %
computer networking (THEME)	83 %
communications (THEME)	83 %
95 (FIELD SECTION "TIMESTAMP")	83 %
HEADLINE (ZONE SECTION)	83 %
15 (FIELD SECTION "TIMESTAMP")	83 %

Notes

These metadata are available only when QUERY_STATS is turned on for the index: estimated fragmentation stats, estimated frequently queried tokens, estimated most fragmented frequently queried token, and estimated slowest running queries for the specified index.

CTX_REPORT.INDEX_STATS will also output information on dr\$indexname\$S table, which is the section data, or SDATA, table.

Related Topics

CTX_OUTPUT.ENABLE_QUERY_STATS (page 11-4)

CTX_OUTPUT.DISABLE_QUERY_STATS (page 11-4)

CREATE INDEX (page 1-40)

Table 2-39 (page 2-81)

13.9 QUERY_LOG_SUMMARY

Obtain a report of logged queries.

QUERY_LOG_SUMMARY enables you to analyze queries you have logged. For example, suppose you have an application that searches a database of large animals, and your analysis of queries against it shows that users are continually searching for the word *mouse*; this analysis might induce you to rewrite your application so that a search for *mouse* redirects the user to a database for small animals instead of simply returning an unsuccessful search.

With query analysis, you can find out the following:

- Which queries were made
- Which queries were successful
- Which queries were unsuccessful
- How many times each query was made

You can combine these factors in various ways, such as determining the 50 most frequent unsuccessful queries made by your application.

Query logging is begun with CTX_OUTPUT . START_QUERY_LOG and terminated with CTX_OUTPUT . END_QUERY_LOG.

Note:

You must connect as CTXSYS to use CTX_REPORT . QUERY_LOG_SUMMARY.

See Also:

"[START_QUERY_LOG](#) (page 11-9)" and "[END_QUERY_LOG](#) (page 11-5)"

Syntax

```
procedure CTX_REPORT.QUERY_LOG_SUMMARY(
    logfile          IN VARCHAR2,
    indexname        IN VARCHAR2 DEFAULT NULL,
    result_table      IN OUT NOCOPY QUERY_TABLE,
    row_num           IN NUMBER,
    most_freq         IN BOOLEAN DEFAULT TRUE,
    has_hit           IN BOOLEAN DEFAULT TRUE
);
```

logfile

Specify the name of the logfile that contains the queries.

indexname

Specify the name of the context index for which you want the summary report. If you specify NULL, the procedure provides a summary report for all context indexes.

result_table

Specify the name of the in-memory table of type TABLE OF RECORD where the results of the QUERY_LOG_SUMMARY are to go. The default is the location specified by the system parameter LOG_DIRECTORY.

row_num

The number of rows of results from QUERY_LOG_SUMMARY to be reported into the table named by *restab*. For example, if this is number is 10, *most_freq* is TRUE, and *has_hit* is TRUE, then the procedure returns the 10 most frequent queries that were successful (that is, returned hits).

most_freq

Specify whether QUERY_LOG_SUMMARY should return the most frequent or least frequent queries. The default is most frequent queries. If *most_freq* is set to FALSE, the procedure returns the least successful queries.

has_hit

Specify whether QUERY_LOG_SUMMARY should return queries that are successful (that is, that generate hits) or unsuccessful queries. The default is to count successful queries; set *has_hit* to FALSE to return unsuccessful queries.

Example

The following example shows how a query log can be used.

First connect as CTXSYS. Then create and populate two tables, and then create an index for each:

```
create table qlogtab1 (tk number primary key, text varchar2(2000));
insert into qlogtab1 values(1, 'The Roman name for France was Gaul.');
```

```
insert into qlogtab1 values(2, 'The Tour de France is held each summer.');
```

```
insert into qlogtab1 values(3, 'Jacques Anatole Thibault took the pen name Anatole France.');
```

```
create index idx_qlog1 on qlogtab1(text) indextype is ctxsys.context;
```

```
create table qlogtab2 (tk number primary key, text varchar2(2000));
insert into qlogtab2 values(1, 'The Great Wall of China is about 2400 kilometers long');
```

```
insert into qlogtab2 values(2, 'Soccer dates back at least to 217 C.E.');
```

```
insert into qlogtab2 values(3, 'The Corn Palace is a tourist attraction in South Dakota.');
```

```
create index idx_qlog2 on qlogtab2(text) indextype is ctxsys.context;
```

Turn on query logging, creating a log called query_log:

```
exec ctx_output.start_query_log('query.log');
```

Now make some queries (some of which will be unsuccessful):

```
select text from qlogtab1 where contains(text, 'France',1)>0;
```

```
select text from qlogtab1 where contains(text, 'cheese',1)>0;
```

```
select text from qlogtab1 where contains(text, 'Text Wizard',1)>0;
```

```
select text from qlogtab2 where contains(text, 'Corn Palace',1)>0;
```

```
select text from qlogtab2 where contains(text, 'China',1)>0;
```

```
select text from qlogtab1 where contains(text, 'Text Wizards',1)>0;
```

```
select text from qlogtab2 where contains(text, 'South Dakota',1)>0;
```

```
select text from qlogtab1 where contains(text, 'Text Wizard',1)>0;
```

```
select text from qlogtab2 where contains(text, 'China',1)>0;
```

```
select text from qlogtab1 where contains(text, 'Text Wizard',1)>0;
```

```
select text from qlogtab2 where contains(text, 'company',1)>0;
```

```
select text from qlogtab1 where contains(text, 'Text Wizard',1)>0;
```

```
select text from qlogtab1 where contains(text, 'France',1)>0;
```

```
select text from qlogtab1 where contains(text, 'database',1)>0;
```

```
select text from qlogtab2 where contains(text, 'high-tech',1)>0;
```

```
select text from qlogtab1 where contains(text, 'database',1)>0;
```

```
select text from qlogtab1 where contains(text, 'France',1)>0;
```

```
select text from qlogtab1 where contains(text, 'Japan',1)>0;
```

```
select text from qlogtab1 where contains(text, 'Egypt',1)>0;
select text from qlogtab1 where contains(text, 'Argentina',1)>0;
select text from qlogtab1 where contains(text, 'Argentina',1)>0;
select text from qlogtab1 where contains(text, 'Argentina',1)>0;
select text from qlogtab1 where contains(text, 'Japan',1)>0;
select text from qlogtab1 where contains(text, 'Egypt',1)>0;
select text from qlogtab1 where contains(text, 'Air Shuttle',1)>0;
select text from qlogtab1 where contains(text, 'Argentina',1)>0;
```

With the querying over, turn query logging off:

```
exec ctx_output.end_query_log;
```

Use QUERY_LOG_SUMMARY to get query reports. In the first instance, you ask to see the three most frequent queries that return successfully. First declare the results table (the_queries).

```
set serveroutput on;
declare
    the_queries ctx_report.query_table;
begin
    ctx_report.query_log_summary('query.log', null, the_queries,
                                row_num=>3, most_freq=>TRUE, has_hit=>TRUE);
    dbms_output.put_line('The 3 most frequent queries returning hits');
    dbms_output.put_line('number of times  query string');
    for i in 1..the_queries.count loop
        dbms_output.put_line(the_queries(i).times||'                ||the_queries(i).query);
    end loop;
end;
/
```

This returns the following:

```
TThe 3 most frequent queries returning hits
number of times  query string
3                France
2                China
1                Corn Palace
```

Next, look for the three most frequent queries on idx_qlog1 that were successful.

```
declare
    the_queries ctx_report.query_table;
begin
    ctx_report.query_log_summary('query.log', 'idx_qlog1', the_queries,
                                row_num=>3, most_freq=>TRUE, has_hit=>TRUE);
    dbms_output.put_line('The 3 most frequent queries returning hits for index idx_qlog1');
    dbms_output.put_line('number of times  query string');
    for i in 1..the_queries.count loop
        dbms_output.put_line(the_queries(i).times||'                ||the_queries(i).query);
    end loop;
end;
/
```

Because only the queries for *France* were successful, ctx_report.query_log_summary returns the following:

```
The 3 most frequent queries returning hits for index idx_qlog1
number of times  query string
3                France
```

Lastly, ask to see the three least frequent queries that returned no hits (that is, queries that were unsuccessful and called infrequently). In this case, you are interested in queries on both context indexes, so you set the indexname parameter to NULL.

```
declare
  the_queries ctx_report.query_table;
begin
  ctx_report.query_log_summary('query.log', null, the_queries, row_num=>3,
    most_freq=>FALSE, has_hit=>FALSE);
  dbms_output.put_line('The 3 least frequent queries returning no hit');
  dbms_output.put_line('number of times  query string');
  for i in 1..the_queries.count loop
    dbms_output.put_line(the_queries(i).times||'          '||the_queries(i).query);
  end loop;
end;
/
```

This returns the following results:

```
The 3 least frequent queries returning no hit
number of times  query string
1                high-tech
1                company
1                cheese
```

Argentina and *Japan* do not make this list, because they are queried more than once, while *Corn Palace* does not make this list because it is successfully queried.

13.10 TOKEN_INFO

Creates a report showing the information for a token, decoded. This procedure will fully scan the info for a token, so it may take a long time to run for really large tokens.

You can call this operation as a procedure with an IN OUT CLOB parameter or as a function that returns the report as a CLOB.

Syntax

```
procedure CTX_REPORT.TOKEN_INFO(
  index_name      IN VARCHAR2,
  report          IN OUT NOCOPY CLOB,
  token           IN VARCHAR2,
  token_type      IN NUMBER,
  part_name       IN VARCHAR2 DEFAULT NULL,
  raw_info        IN BOOLEAN  DEFAULT FALSE,
  decoded_info    IN BOOLEAN  DEFAULT TRUE,
  report_format   IN VARCHAR2 DEFAULT FMT_TEXT
);

function CTX_REPORT.TOKEN_INFO(
  index_name      IN VARCHAR2,
  token           IN VARCHAR2,
  token_type      IN NUMBER,
  part_name       IN VARCHAR2 DEFAULT NULL,
  raw_info        IN VARCHAR2 DEFAULT 'N',
  decoded_info    IN VARCHAR2 DEFAULT 'Y',
  report_format   IN VARCHAR2 DEFAULT FMT_TEXT
) return clob;
```

index_name

Specify the name of the index.

report

Specify the CLOB locator to which to write the report.

If report is NULL, a session-duration temporary CLOB will be created and returned. It is the caller's responsibility to free this temporary CLOB as needed.

The report CLOB will be truncated before report is generated, so any existing contents will be overwritten by this call token may be case-sensitive, depending on the passed-in token type.

token

Specify the token text.

token_type

Specify the token type. You can use a number returned by the [TOKEN_TYPE](#) (page 13-15) function. THEME, ZONE, ATTR, PATH, and PATH ATTR tokens are case-sensitive.

Everything else gets passed through the lexer, so if the index's lexer is case-sensitive, the token input is case-sensitive.

part_name

Specify the name of the index partition.

If the index is a local partitioned index, then part_name must be provided.

TOKEN_INFO will apply to just that index partition.

raw_info

Specify TRUE to include a hex dump of the index data. If raw_info is TRUE, the report will include a hex dump of the raw data in the token_info column.

decoded_info

Specify decode and include docid and offset data. If decoded_info is FALSE, CTX_REPORT will not attempt to decode the token information. This is useful when you just want a dump of data.

report_format

Specify whether the report should be generated as 'TEXT' or as 'XML'. TEXT is the default. You can also specify the values CTX_REPORT.FMT_TEXT or CTX_REPORT.FMT_XML.

13.11 TOKEN_TYPE

This is a helper function which translates an English name into a numeric token type. This is suitable for use with token_info, or any other CTX API which takes in a token_type.

```
function token_type(
    index_name in varchar2,
    type_name  in varchar2
) return number;

TOKEN_TYPE_TEXT      constant number := 0;
TOKEN_TYPE_THEME     constant number := 1;
TOKEN_TYPE_ZONE_SEC  constant number := 2;
TOKEN_TYPE_ORIG      constant number := 3;
```

```
TOKEN_TYPE_ATTR_TEXT constant number := 4;
TOKEN_TYPE_ATTR_SEC  constant number := 5;
TOKEN_TYPE_PREFIX    constant number := 6;
TOKEN_TYPE_PATH_SEC   constant number := 7;
TOKEN_TYPE_PATH_ATTR  constant number := 8;
TOKEN_TYPE_STEM       constant number := 9;
```

index_name

Specify the name of the index.

type_name

Specify an English name for token_type. The following strings are legal input. All input is case-insensitive.

Input	Meaning	Type Returned
TEXT	Normal text token.	0
THEME	Theme token.	1
ZONE SEC	Zone token.	2
ORIGINAL	Original form token	3
ATTR TEXT	Text that occurs in attribute.	4
ATTR SEC	Attribute section.	5
PREFIX	Prefix token.	6
PATH SEC	Path section.	7
PATH ATTR	Path attribute section.	8
STEM	Stem form token.	9
FIELD <name> TEXT	Text token in field section <name>	16-79
FIELD <name> PREFIX	Prefix token in field section <name>	616-916
FIELD <name> STEM	Stem token in field section <name>	916-979
NDATA <name>	NDATA-type token	200-299
TOKEN_TYPE_ATTR_TXT_ PREFIX	Attribute text prefix.	604
TOKEN_TYPE_ATTR_TXT_ STEM	Attribute text stem.	904

For FIELD types, the index metadata needs to be read, so if you are going to be calling this a lot for such things, you might want to consider caching the values in local variables rather than calling token_type over and over again.

The constant types (0 - 9) also have constants in this package defined.

Notes

To get token types for MDATA tokens, do not use `CTX_REPORT.TOKEN_TYPE`; use the [MDATA](#) (page 3-29) operator instead. (See "[MDATA](#) (page 3-29)".) The syntax to use is 'MDATA *secname*'.

Example

```
typenum := ctx_report.token_type('myindex', 'field author text');
```

13.12 VALIDATE_INDEX

Provides diagnostics if index corruption is believed to have occurred.

`CTX_REPORT.VALIDATE_INDEX` checks an index (or a partition for a locally partitioned index) and reports whether or not any corruption has been detected.

`VALIDATE_INDEX` only checks \$I rows that have `token_type` 0 and does not check other rows that contain information about sections, such as the NDATA section.

This procedure is primarily intended as a diagnostic tool to be used under the direction of Oracle Support.

CTX_THES Package

This chapter provides reference information for using the CTX_THES package to manage and browse thesauri. These thesaurus functions are based on the ISO-2788 and ANSI Z39.19 standards except where noted.

Knowing how information is stored in your thesaurus helps in writing queries with thesaurus operators. You can also use a thesaurus to extend the knowledge base, which is used for ABOUT queries in English and French and for generating document themes.

CTX_THES contains the following stored procedures and functions:

Name	Description
ALTER_PHRASE (page 14-2)	Alters thesaurus phrase.
ALTER_THESAURUS (page 14-4)	Renames or truncates a thesaurus.
BT (page 14-4)	Returns all broader terms of a phrase.
BTG (page 14-6)	Returns all broader terms generic of a phrase.
BTI (page 14-7)	Returns all broader terms instance of a phrase.
BTP (page 14-9)	Returns all broader terms partitive of a phrase.
CREATE_PHRASE (page 14-10)	Adds a phrase to the specified thesaurus.
CREATE_RELATION (page 14-11)	Creates a relation between two phrases.
CREATE_THESAURUS (page 14-12)	Creates the specified thesaurus.
CREATE_TRANSLATION (page 14-13)	Creates a new translation for a phrase.
DROP_PHRASE (page 14-13)	Removes a phrase from thesaurus.
DROP_RELATION (page 14-14)	Removes a relation between two phrases.
DROP_THESAURUS (page 14-16)	Drops the specified thesaurus from the thesaurus tables.
DROP_TRANSLATION (page 14-16)	Drops a translation for a phrase.

Name	Description
EXPORT_THESAURUS (page 14-17)	Exports a thesaurus from the thesaurus tables.
HAS_RELATION (page 14-18)	Tests for the existence of a thesaurus relation.
IMPORT_THESAURUS (page 14-18)	Imports a thesaurus into the thesaurus tables.
NT (page 14-19)	Returns all narrower terms of a phrase.
NTG (page 14-21)	Returns all narrower terms generic of a phrase.
NTI (page 14-22)	Returns all narrower terms instance of a phrase.
NTP (page 14-24)	Returns all narrower terms partitive of a phrase.
OUTPUT_STYLE (page 14-25)	Sets the output style for the expansion functions.
PT (page 14-25)	Returns the preferred term of a phrase.
RT (page 14-27)	Returns the related terms of a phrase
SN (page 14-28)	Returns scope note for phrase.
SYN (page 14-28)	Returns the synonym terms of a phrase
THES_TT (page 14-30)	Returns all top terms for phrase.
TR (page 14-31)	Returns the foreign equivalent of a phrase.
TRSYN (page 14-32)	Returns the foreign equivalent of a phrase, synonyms of the phrase, and foreign equivalent of the synonyms.
TT (page 14-34)	Returns the top term of a phrase.
UPDATE_TRANSLATION (page 14-35)	Updates an existing translation.

See Also:

[Oracle Text CONTAINS Query Operators](#) (page 3-1) for more information about the thesaurus operators.

14.1 ALTER_PHRASE

Alters an existing phrase in the thesaurus. Only CTXSYS or thesaurus owner can alter a phrase.

Syntax

```
CTX_THES.ALTER_PHRASE(tname      in varchar2,  
                      phrase      in varchar2,  
                      op          in varchar2,  
                      operand     in varchar2 default null);
```

tname

Specify the thesaurus name.

phrase

Specify a phrase to alter.

op (alter operation)

Specify the alter operation as a string or symbol. You can specify one of the following operations with the op and operand pair:

op (or alter operation)	meaning	operand
RENAME or CTX_THES.OP_RENAME	Rename phrase. If the new phrase already exists in the thesaurus, this procedure raises an exception.	Specify a new phrase. You can include qualifiers to change, add, or remove qualifiers from phrases.
PT or CTX_THES.OP_PT	Make phrase the preferred term. Existing preferred terms in the synonym ring becomes non-preferred synonym.	(none)
SN or CTX_THES.OP_SN	Change the scope note on the phrase.	Specify a new scope note.

operand

Specify an argument to the alter operation. See table for "[op \(alter operation\)](#)" (page 14-3).

Examples

Correct misspelled word in thesaurus:

```
ctx_thes.alter_phrase('thes1', 'tee', 'rename', 'tea');
```

Remove qualifier from mercury (metal):

```
ctx_thes.alter_phrase('thes1', 'mercury (metal)', 'rename', 'mercury');
```

Add qualifier to mercury:

```
ctx_thes.alter_phrase('thes1', 'mercury', 'rename', 'mercury (planet)');
```

Make Kowalski the preferred term in its synonym ring:

```
ctx_thes.alter_phrase('thes1', 'Kowalski', 'pt');
```

Change scope note for view cameras:

```
ctx_thes.alter_phrase('thes1', 'view cameras', 'sn', 'Cameras with lens focusing');
```

14.2 ALTER_THESAURUS

Use this procedure to rename or truncate an existing thesaurus. Only the thesaurus owner or CTXSYS can invoke this function on a given thesaurus.

Syntax

```
CTX_THES.ALTER_THESAURUS(tname      in   varchar2,  
                          op         in   varchar2,  
                          operand    in   varchar2 default null);
```

tname

Specify the thesaurus name.

op

Specify the alter operation as a string or symbol. You can specify one of two operations:

op	Meaning	operand
RENAME or CTX_THES.OP_RENAME	Rename thesaurus. Returns an error if the new name already exists.	Specify a new thesaurus name.
TRUNCATE or CTX_THES.OP_TRUNCATE	Truncate thesaurus.	None.

operand

Specify the argument to the alter operation. See table for op.

Examples

Rename thesaurus THES1 to MEDICAL:

```
ctx_thes.alter_thesaurus('thes1', 'rename', 'medical');
```

or

```
ctx_thes.alter_thesaurus('thes1', ctx_thes.op_rename, 'medical');
```

You can use symbols for any op argument, but all further examples will use strings.

Remove all phrases and relations from thesaurus THES1:

```
ctx_thes.alter_thesaurus('thes1', 'truncate');
```

14.3 BT

This function returns all broader terms of a phrase as recorded in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.BT(restab IN OUT NOCOPY EXP_TAB,  
            phrase IN VARCHAR2,
```

```

        lvl    IN NUMBER DEFAULT 1,
        tname  IN VARCHAR2 DEFAULT 'DEFAULT';

```

Syntax 2: String Result

```

CTX_THES.BT(phrase IN VARCHAR2,
            lvl    IN NUMBER DEFAULT 1,
            tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN VARCHAR2;

```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```

type exp_rec is record (
    xrel varchar2(12),
    xlevel number,
    xphrase varchar2(256)
);
type exp_tab is table of exp_rec index by binary_integer;

```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB

phrase

Specify a phrase to lookup in thesaurus.

lvl

Specify how many levels of broader terms to return. For example 2 means get the broader terms of the broader terms of the phrase.

tname

Specify a thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns a string of broader terms in the form:

```
{bt1}|{bt2}|{bt3} ...
```

Example

String Result

Consider a thesaurus named MY_THES that has an entry for *cat* as follows:

```

cat
  BT1 feline
    BT2 mammal
      BT3 vertebrate
        BT4 animal

```

To look up the broader terms for *cat* up to two levels, enter the following statements:

```

set serveroutput on

declare

```

```
terms varchar2(2000);
begin
  terms := ctx_thes.bt('CAT', 2, 'MY_THES');
  dbms_output.put_line('The broader expansion for CAT is: ' || terms);
end;
```

This code produces the following output:

The broader expansion for CAT is: {cat}||{feline}||{mammal}

Table Result

The following example performs a broader term lookup for *white wolf* using the table result:

```
set serveroutput on

declare
  xtab ctx_thes.exp_tab;
begin
  ctx_thes.bt(xtab, 'white wolf', 2, 'my_thesaurus');
  for i in 1..xtab.count loop
    dbms_output.put_line(xtab(i).rel || ' ' || xtab(i).phrase);
  end loop;
end;
```

This code produces the following output:

```
PHRASE WHITE WOLF
BT WOLF
BT CANINE
BT ANIMAL
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["Broader Term \(BT_ BTG_ BTP_ BTI\) \(page 3-9\)"](#)

14.4 BTG

This function returns all broader terms generic of a phrase as recorded in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.BTG(restab IN OUT NOCOPY EXP_TAB,
             phrase IN VARCHAR2,
             lvl    IN NUMBER DEFAULT 1,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT');
```

Syntax 2: String Result

```
CTX_THES.BTG(phrase IN VARCHAR2,
             lvl    IN NUMBER DEFAULT 1,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN VARCHAR2;
```


restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (
    xrel varchar2(12),
    xlevel number,
    xphrase varchar2(256)
);
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

lvl

Specify how many levels of broader terms to return. For example 2 means get the broader terms of the broader terms of the phrase.

tname

Specify thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns a string of broader terms generic in the form:

```
{bt1}||{bt2}||{bt3} ...
```

Example

To look up the broader terms generic for *cat* up to two levels, enter the following statements:

```
set serveroutput on
declare
    terms varchar2(2000);
begin
    terms := ctx_thes.btg('CAT', 2, 'MY_THES');
    dbms_output.put_line('the broader expansion for CAT is: '||terms);
end;
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["Broader Term \(BT_ BTG_ BTP_ BTI\) \(page 3-9\)"](#)

14.5 BTI

This function returns all broader terms instance of a phrase as recorded in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.BTI(restab IN OUT NOCOPY EXP_TAB,
             phrase IN VARCHAR2,
             lvl    IN NUMBER DEFAULT 1,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT');
```

Syntax 2: String Result

```
CTX_THES.BTI(phrase IN VARCHAR2,
             lvl    IN NUMBER DEFAULT 1,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN VARCHAR2;
```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (
    xrel varchar2(12),
    xlevel number,
    xphrase varchar2(256)
);
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

lvl

Specify how many levels of broader terms to return. For example 2 means get the broader terms of the broader terms of the phrase.

tname

Specify a thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns a string of broader terms instance in the form:

```
{bt1}||{bt2}||{bt3} ...
```

Example

To look up the broader terms instance for *cat* up to two levels, enter the following statements:

```
set serveroutput on
declare
    terms varchar2(2000);
begin
    terms := ctx_thes.bti('CAT', 2, 'MY_THES');
    dbms_output.put_line('the broader expansion for CAT is: '||terms);
end;
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["Broader Term \(BT_ BTG_ BTP_ BTI\) \(page 3-9\)"](#)

14.6 BTP

This function returns all broader terms partitive of a phrase as recorded in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.BTP(restab IN OUT NOCOPY EXP_TAB,
             phrase IN VARCHAR2,
             lvl    IN NUMBER DEFAULT 1,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT');
```

Syntax 2: String Result

```
CTX_THES.BTP(phrase IN VARCHAR2,
             lvl    IN NUMBER DEFAULT 1,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN VARCHAR2;
```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (
    xrel varchar2(12),
    xlevel number,
    xphrase varchar2(256)
);
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

lvl

Specify how many levels of broader terms to return. For example 2 means get the broader terms of the broader terms of the phrase.

tname

Specify a thesaurus name. If not specified, the system default thesaurus is used.

Returns

This function returns a string of broader terms in the form:

```
{bt1}|{bt2}|{bt3} ...
```

Example

To look up the two broader terms partitive for *cat*, enter the following statements:

```
declare
    terms varchar2(2000);
begin
    terms := ctx_thes.btp('CAT', 2, 'MY_THES');
    dbms_output.put_line('the broader expansion for CAT is: ' || terms);
end;
```

Related Topics

["OUTPUT_STYLE" \(page 14-25\)](#)

["Broader Term \(BT_ BTG_ BTP_ BTI\)" \(page 3-9\)](#)

14.7 CREATE_PHRASE

The CREATE_PHRASE procedure adds a new phrase to the specified thesaurus.

Note:

Even though you can create thesaurus relations with this procedure, Oracle recommends that you use CTX_THES.CREATE_RELATION rather than CTX_THES.CREATE_PHRASE to create relations in a thesaurus.

Syntax

```
CTX_THES.CREATE_PHRASE(tname    IN VARCHAR2,
                       phrase    IN VARCHAR2,
                       rel       IN VARCHAR2 DEFAULT NULL,
                       relname   IN VARCHAR2 DEFAULT NULL);
```

tname

Specify the name of the thesaurus in which the new phrase is added or the existing phrase is located.

phrase

Specify the phrase to be added to a thesaurus or the phrase for which a new relationship is created.

rel

Specify the new relationship between *phrase* and *relname*. This parameter is supported only for backward compatibility. Use CTX_THES.[CREATE_RELATION](#) (page 14-11) to create new relations in a thesaurus.

relname

Specify the existing phrase that is related to *phrase*. This parameter is supported only for backward compatibility. Use CTX_THES.[CREATE_RELATION](#) (page 14-11) to create new relations in a thesaurus.

Returns

The ID for the entry.

Example

In this example, two new phrases (*os* and *operating system*) are created in a thesaurus named `tech_thes`.

```
begin
  ctx_thes.create_phrase('tech_thes','os');
  ctx_thes.create_phrase('tech_thes','operating system');
end;
```

14.8 CREATE_RELATION

Creates a relation between two phrases in the thesaurus. The synonym ring is limited in length to about 4000 synonyms, depending on word length.

Note:

Oracle recommends that you use `CTX_THES.CREATE_RELATION` rather than `CTX_THES.CREATE_PHRASE` to create relations in a thesaurus.

Only thesaurus owner and CTXSYS can invoke this procedure on a given thesaurus.

Syntax

```
CTX_THES.CREATE_RELATION(tname      in   varchar2,
                        phrase      in   varchar2,
                        rel         in   varchar2,
                        relphrase   in   varchar2);
```

tname

Specify the thesaurus name

phrase

Specify the phrase to alter or create. If `phrase` is a disambiguated homograph, you must specify the qualifier. If `phrase` does not exist in the thesaurus, it is created.

rel

Specify the relation to create. The relation is from `phrase` to `relphrase`. You can specify one of the following relations:

relation	meaning	relphrase
BT*/NT*	Add hierarchical relation.	Specify the related phrase. The relationship is interpreted from <code>phrase</code> to <code>relphrase</code> .
RT	Add associative relation.	Specify the phrase to associate.
SYN	Add phrase to a synonym ring.	Specify an existing phrase in the synonym ring.
Specify language	Add translation for a phrase.	Specify a new translation phrase.

relphrase

Specify the related phrase. If relphrase does not exist in tname, relphrase is created. See table for rel.

Notes

The relation you specify for rel is interpreted as from phrase to relphrase. For example, consider dog with broader term animal:

```
dog
  BT animal
```

To add this relation, specify the arguments as follows:

```
begin
CTX_THES.CREATE_RELATION('thes','dog','BT','animal');
end;
```

Note:

The order in which you specify arguments for CTX_THES.CREATE_RELATION is different from the order you specify them with CTX_THES.CREATE_PHRASE.

Examples

Create relation VEHICLE NT CAR:

```
ctx_thes.create_relation('thes1','vehicle','NT','car');
```

Create Japanese translation for *you*:

```
ctx_thes.create_relation('thes1','you','JAPANESE:', 'kimi');
```

14.9 CREATE_THESAURUS

The CREATE_THESAURUS procedure creates an empty thesaurus with the specified name in the thesaurus tables.

Syntax

```
CTX_THES.CREATE_THESAURUS(name          IN VARCHAR2,
                           casesens      IN BOOLEAN DEFAULT FALSE);
```

name

Specify the name of the thesaurus to be created. The name of the thesaurus must be unique. If a thesaurus with the specified name already exists, CREATE_THESAURUS returns an error and does not create the thesaurus.

casesens

Specify whether the thesaurus to be created is case-sensitive. If casesens is *true*, Oracle Text retains the cases of all terms entered in the specified thesaurus. As a result, queries that use the thesaurus are case-sensitive.

Example

```
begin
  ctx_thes.create_thesaurus('tech_thes', FALSE);
end;
```

14.10 CREATE_TRANSLATION

Use this procedure to create a new translation for a phrase in a specified language.

Syntax

```
CTX_THES.CREATE_TRANSLATION(tname      in   varchar2,
                             phrase     in   varchar2,
                             language   in   varchar2,
                             translation in   varchar2);
```

tname

Specify the name of the thesaurus, using no more than 30 characters.

phrase

Specify the phrase in the thesaurus to which to add a translation. Phrase must already exist in the thesaurus, or an error is raised.

language

Specify the language of the translation, using no more than 10 characters.

translation

Specify the translated term, using no more than 256 characters.

If a translation for this phrase already exists, this new translation is added without removing that original translation, so long as that original translation is not the same. Adding the same translation twice results in an error.

Example

The following code adds the Spanish translation for *dog* to *my_thes*:

```
begin
  ctx_thes.create_translation('my_thes', 'dog', 'SPANISH', 'PERRO');
end;
```

14.11 DROP_PHRASE

Removes a phrase from the thesaurus. Only thesaurus owner and CTXSYS can invoke this procedure on a given thesaurus.

Syntax

```
CTX_THES.DROP_PHRASE(tname      in varchar2,
                     phrase     in varchar2);
```

tname

Specify thesaurus name.

phrase

Specify a phrase to drop. If the phrase is a disambiguated homograph, then you must include the qualifier. If the phrase does not exist in `tname`, then this procedure raises an exception.

BT* / NT* relations are patched around the dropped phrase. For example, if A has a BT B, and B has BT C, after B is dropped, A has BT C.

When a word has multiple broader terms, then a relationship is established for each narrower term to each broader term.

Note that BT, BTG, BTP, and BTI are separate hierarchies, so if A has BTG B, and B has BTI C, when B is dropped, there is no relation implicitly created between A and C.

RT relations are not patched. For example, if A has RT B, and B has RT C, then if B is dropped, there is no associative relation created between A and C.

Example

Assume you have the following relations defined in *mythes*:

```
wolf
  BT canine
canine
  BT animal
```

You drop phrase *canine*:

```
begin
ctx_thes.drop_phrase('mythes', 'canine');
end;
```

The resulting thesaurus is patched and looks like:

```
wolf
  BT animal
```

14.12 DROP_RELATION

Removes a relation between two phrases from the thesaurus.

Note:

CTX_THES.DROP_RELATION removes only the relation between two phrases. Phrases are never removed by this call.

Only thesaurus owner and CTXSYS can invoke this procedure on a given thesaurus.

Syntax

```
CTX_THES.DROP_RELATION(tname      in   varchar2,
                        phrase      in   varchar2,
                        rel         in   varchar2,
                        relphrase   in   varchar2 default null);
```

tname

Specify the thesaurus name.

phrase

Specify the filing phrase.

rel

Specify the relation to drop. The relation is from phrase to relphrase. You can specify one of the following relations:

relation	meaning	relphrase
BT*/NT*	Remove hierarchical relation.	Optional specify relphrase. If not provided, all relations of that type for the phrase are removed.
RT	Remove associative relation.	Optionally specify relphrase. If not provided, all RT relations for the phrase are removed.
SYN	Remove phrase from its synonym ring.	(none)
PT	Remove preferred term designation from the phrase. The phrase remains in the synonym ring.	(none)
language	Remove a translation from a phrase.	Optionally specify relphrase. You can specify relphrase when there are multiple translations for a phrase for the language, and you want to remove just one translation. If relphrase is NULL, all translations for the phrase for the language are removed.

relphrase

Specify the related phrase.

Notes

The relation you specify for rel is interpreted as from phrase to relphrase. For example, consider dog with broader term animal:

```
dog
  BT animal
```

To remove this relation, specify the arguments as follows:

```
begin
CTX_THES.DROP_RELATION('thes','dog','BT','animal');
end;
```

You can also remove this relation using NT as follows:

```
begin
CTX_THES.DROP_RELATION('thes','animal','NT','dog');
end;
```

Example

Remove relation VEHICLE NT CAR:

```
ctx_thes.drop_relation('thes1', 'vehicle', 'NT', 'car');
```

Remove all narrower term relations for vehicle:

```
ctx_thes.drop_relation('thes1', 'vehicle', 'NT');
```

Remove Japanese translations for *me*:

```
ctx_thes.drop_relation('thes1', 'me', 'JAPANESE:');
```

Remove a specific Japanese translation for *me*:

```
ctx_thes.drop_relation('thes1', 'me', 'JAPANESE:', 'boku')
```

14.13 DROP_THESAURUS

The DROP_THESAURUS procedure deletes the specified thesaurus and all of its entries from the thesaurus tables.

Syntax

```
CTX_THES.DROP_THESAURUS(name IN VARCHAR2);
```

name

Specify the name of the thesaurus to be dropped.

Example

```
begin
ctx_thes.drop_thesaurus('tech_thes');
end;
```

14.14 DROP_TRANSLATION

Use this procedure to remove one or more translations for a phrase.

Syntax

```
CTX_THES.DROP_TRANSLATION (tname      in   varchar2,
                           phrase     in   varchar2,
                           language   in   varchar2 default null,
                           translation in   varchar2 default null);
```

tname

Specify the name of the thesaurus, using no more than 30 characters.

phrase

Specify the phrase in the thesaurus to which to remove a translation. The phrase must already exist in the thesaurus or an error is raised.

language

Optionally, specify the language of the translation, using no more than 10 characters. If not specified, the translation must also not be specified and all translations in all

languages for the phrase are removed. An error is raised if the phrase has no translations.

translation

Optionally, specify the translated term to remove, using no more than 256 characters. If no such translation exists, an error is raised.

Example

The following code removes the Spanish translation for *dog*:

```
begin
  ctx_thes.drop_translation('my_thes', 'dog', 'SPANISH', 'PERRO');
end;
```

To remove all translations for dog in all languages:

```
begin
  ctx_thes.drop_translation('my_thes', 'dog');
end;
```

14.15 EXPORT_THESAURUS

Use this procedure to export a thesaurus as a clob from the Oracle Text thesaurus tables. The format of the exported thesaurus is same as that of the format of the thesaurus file that is used by the `ctxload` utility to import thesaurus into the Oracle Text thesaurus tables.

See Also:

["Thesaurus Loader \(ctxload\)" \(page 16-1\)](#) in [Oracle Text Utilities](#) (page 16-1) for more information about the `ctxload` utility.

Only the owner of the thesaurus, or the `sys` user, or the `ctxsys` user can export a thesaurus from the Oracle Text thesaurus tables using `export_thesaurus`.

You should call `ctx_output.start_log` before calling `export_thesaurus` to log the operations done by `export_thesaurus`.

Syntax

```
CTX_THES.EXPORT_THESAURUS(name in varchar2,
                           thesdump in out nocopy CLOB);
```

name

Specify the name of the thesaurus in the Oracle Text thesaurus tables that you want to export. If the specified thesaurus does not exist in the Oracle Text thesaurus tables, then this procedure raises an exception.

thesdump

Specify the name of the clob where you want to store the thesaurus that is exported from the Oracle Text thesaurus tables.

Example

The following example copies the thesaurus named `mythesaurus` from the Oracle Text thesaurus tables into the clob `mythesdump`:

```
declare
  mythesdump clob;
begin
  ctx_thes.export_thesaurus('mythesaurus', mythesdump);
end;
```

14.16 HAS_RELATION

`HAS_RELATION` tests that a thesaurus relation exists without actually performing the expansion. The function returns `TRUE` if the phrase has any of the relations in the specified list.

Syntax

```
CTX_THES.HAS_RELATION(phrase in varchar2,
                      rel in varchar2,
                      tname in varchar2 default 'DEFAULT')
returns boolean;
```

phrase

Specify the phrase.

rel

Specify a single thesaural relation or a comma-delimited list of relations, except `PT`. Specify `'ANY'` for any relation.

tname

Specify the thesaurus name.

Example

The following example returns `TRUE` if the phrase `cat` in the `DEFAULT` thesaurus has any broader terms or broader generic terms:

```
set serveroutput on
result boolean;

begin
  result := ctx_thes.has_relation('cat','BT,BTG');
  if (result) then dbms_output.put_line('TRUE');
  else dbms_output.put_line('FALSE');
  end if;
end;
```

14.17 IMPORT_THESAURUS

Use this procedure to import a thesaurus into the Oracle Text thesaurus tables. You should call `ctx_output.start_log` before calling `import_thesaurus` to log the operations done by `import_thesaurus`.

Syntax

```
CTX_THES.IMPORT_THESAURUS(name in varchar2,
                           content in CLOB,
                           thescase in varchar2 default 'N');
```

name

Specify the name of the thesaurus to be created. If the name of the thesaurus specified in the name parameter already exists in the Oracle Text thesaurus tables, then this procedure raises an exception.

content

Specify the thesaurus content to be imported in the Oracle Text thesaurus tables. The format of the thesaurus to be imported should be the same as used by the `ctxload` utility. If the format of the thesaurus to be imported is not correct, then this procedure raises an exception.

See Also:

["Thesaurus Loader \(ctxload\)"](#) (page 16-1) in [Oracle Text Utilities](#) (page 16-1) for more information about the `ctxload` utility.

thescase

Specify 'Y' to create a case-sensitive thesaurus and 'N' to create a case-insensitive thesaurus. The default is 'N'.

Example

The following example creates a case-sensitive thesaurus named `mythesaurus` and imports the thesaurus content present in `myclob` into the Oracle Text thesaurus tables:

```
declare
  myclob clob;
begin
  myclob := to_clob('peking SYN beijing BT capital country NT beijing tokyo');
  ctx_thes.import_thesaurus('mythesaurus', myclob, 'Y');
end;
```

14.18 NT

This function returns all narrower terms of a phrase as recorded in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.NT(restab IN OUT NOCOPY EXP_TAB,
             phrase IN VARCHAR2,
             lvl    IN NUMBER DEFAULT 1,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT');
```

Syntax 2: String Result

```
CTX_THES.NT(phrase IN VARCHAR2,
            lvl    IN NUMBER DEFAULT 1,
            tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN VARCHAR2;
```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (  
    xrel varchar2(12),  
    xlevel number,  
    xphrase varchar2(256)  
);  
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables](#) (page A-1) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

lvl

Specify how many levels of narrower terms to return. For example 2 means get the narrower terms of the narrower terms of the phrase.

tname

Specify thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns a string of narrower terms in the form:

```
{nt1}||{nt2}||{nt3} ...
```

Example**String Result**

Consider a thesaurus named MY_THES that has an entry for *cat* as follows:

```
cat  
  NT domestic cat  
  NT wild cat  
  BT mammal  
mammal  
  BT animal  
domestic cat  
  NT Persian cat  
  NT Siamese cat
```

To look up the narrower terms for *cat* down to two levels, enter the following statements:

```
declare  
    terms varchar2(2000);  
begin  
    terms := ctx_thes.nt('CAT', 2, 'MY_THES');  
    dbms_output.put_line('the narrower expansion for CAT is: '||terms);  
end;
```

This code produces the following output:

the narrower expansion for CAT is: {cat}||{domestic cat}||{Persian cat}||{Siamese cat}||{wild cat}

Table Result

The following code does an narrower term lookup for *canine* using the table result:

```
declare
  xtab ctx_thes.exp_tab;
begin
  ctx_thes.nt(xtab, 'canine', 2, 'my_thesaurus');
  for i in 1..xtab.count loop
    dbms_output.put_line(lpad(' ', 2*xtab(i).xlevel) ||
      xtab(i).xrel || ' ' || xtab(i).xphrase);
  end loop;
end;
```

This code produces the following output:

```
PHRASE CANINE
NT WOLF (Canis lupus)
  NT WHITE WOLF
  NT GREY WOLF
NT DOG (Canis familiaris)
  NT PIT BULL
  NT DASCHUND
  NT CHIHUAHUA
NT HYENA (Canis mesomelas)
NT COYOTE (Canis latrans)
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["Narrower Term \(NT_ NTG_ NTP_ NTI\) \(page 3-32\)"](#)

14.19 NTG

This function returns all narrower terms generic of a phrase as recorded in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.NTG(restab IN OUT NOCOPY EXP_TAB,
             phrase IN VARCHAR2,
             lvl    IN NUMBER DEFAULT 1,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT');
```

Syntax 2: String Result

```
CTX_THES.NTG(phrase IN VARCHAR2,
             lvl    IN NUMBER DEFAULT 1,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN VARCHAR2;
```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (  
    xrel varchar2(12),  
    xlevel number,  
    xphrase varchar2(256)  
);  
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

lvl

Specify how many levels of narrower terms to return. For example 2 means get the narrower terms of the narrower terms of the phrase.

tname

Specify the thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns a string of narrower terms generic in the form:

```
{nt1}||{nt2}||{nt3} ...
```

Example

To look up the narrower terms generic for *cat* down to two levels, enter the following statements:

```
declare  
    terms varchar2(2000);  
begin  
    terms := ctx_thes.ntg('CAT', 2, 'MY_THES');  
    dbms_output.put_line('the narrower expansion for CAT is: '||terms);  
end;
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["Narrower Term \(NT_ NTG_ NTP_ NTI\) \(page 3-32\)"](#)

14.20 NTI

This function returns all narrower terms instance of a phrase as recorded in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.NTI(restab IN OUT NOCOPY EXP_TAB,  
    phrase IN VARCHAR2,  
    lvl    IN NUMBER DEFAULT 1,  
    tname  IN VARCHAR2 DEFAULT 'DEFAULT');
```


Syntax 2: String Result

```
CTX_THES.NTI(phrase IN VARCHAR2,
             lvl    IN NUMBER DEFAULT 1,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN VARCHAR2;
```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (
    xrel varchar2(12),
    xlevel number,
    xphrase varchar2(256)
);
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

lvl

Specify how many levels of narrower terms to return. For example 2 means get the narrower terms of the narrower terms of the phrase.

tname

Specify the thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns a string of narrower terms instance in the form:

```
{nt1}|{nt2}|{nt3} ...
```

Example

To look up the narrower terms instance for *cat* down to two levels, enter the following statements:

```
declare
    terms varchar2(2000);
begin
    terms := ctx_thes.nti('CAT', 2, 'MY_THES');
    dbms_output.put_line('the narrower expansion for CAT is: '||terms);
end;
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["Narrower Term \(NT_ NTG_ NTP_ NTI\) \(page 3-32\)"](#)

14.21 NTP

This function returns all narrower terms partitive of a phrase as recorded in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.NTP(restab IN OUT NOCOPY EXP_TAB,  
             phrase IN VARCHAR2,  
             lvl    IN NUMBER DEFAULT 1,  
             tname  IN VARCHAR2 DEFAULT 'DEFAULT');
```

Syntax 2: String Result

```
CTX_THES.NTP(phrase IN VARCHAR2,  
            lvl    IN NUMBER DEFAULT 1,  
            tname  IN VARCHAR2 DEFAULT 'DEFAULT')  
RETURN VARCHAR2;
```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (  
    xrel varchar2(12),  
    xlevel number,  
    xphrase varchar2(256)  
);  
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

lvl

Specify how many levels of narrower terms to return. For example 2 means get the narrower terms of the narrower terms of the phrase.

tname

Specify the thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns a string of narrower terms partitive in the form:

```
{nt1}|{nt2}|{nt3} ...
```

Example

To look up the narrower terms partitive for *cat* down to two levels, enter the following statements:

```

declare
    terms varchar2(2000);
begin
    terms := ctx_thes.ntp('CAT', 2, 'MY_THES');
    dbms_output.put_line('the narrower expansion for CAT is: '||terms);
end;
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["Narrower Term \(NT_ NTG_ NTP_ NTI\) \(page 3-32\)"](#)

14.22 OUTPUT_STYLE

Sets the output style for the return string of the CTX_THES expansion functions. This procedure has no effect on the table results to the CTX_THES expansion functions.

Syntax

```

CTX_THES.OUTPUT_STYLE (
    showlevel      IN BOOLEAN DEFAULT FALSE,
    showqualify    IN BOOLEAN DEFAULT FALSE,
    showpt         IN BOOLEAN DEFAULT FALSE,
    showid         IN BOOLEAN DEFAULT FALSE
);
```

showlevel

Specify TRUE to show level in BT/NT expansions.

showqualify

Specify TRUE to show phrase qualifiers.

showpt

Specify TRUE to show preferred terms with an asterisk *.

showid

Specify TRUE to show phrase ids.

Notes

The general syntax of the return string for CTX_THES expansion functions is:

```
{pt indicator:phrase (qualifier):level:phraseid}
```

Preferred term indicator is an asterisk then a colon at the start of the phrase. The qualifier is in parentheses after a space at the end of the phrase. Level is a number.

The following is an example return string for turkey the bird:

```
*:TURKEY (BIRD):1:1234
```

14.23 PT

This function returns the preferred term of a phrase as recorded in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.PT(restab IN OUT NOCOPY EXP_TAB,  
            phrase IN VARCHAR2,  
            tname  IN VARCHAR2 DEFAULT 'DEFAULT')  
RETURN varchar2;
```

Syntax 2: String Result

```
CTX_THES.PT(phrase IN VARCHAR2,  
            tname  IN VARCHAR2 DEFAULT 'DEFAULT')  
RETURN varchar2;
```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (  
    xrel varchar2(12),  
    xlevel number,  
    xphrase varchar2(256)  
);  
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

tname

Specify thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns the preferred term as a string in the form:

{pt}

Example

Consider a thesaurus MY_THES with the following preferred term definition for automobile:

```
AUTOMOBILE  
  PT CAR
```

To look up the preferred term for *automobile*, execute the following code:

```
declare  
    terms varchar2(2000);  
begin  
    terms := ctx_thes.pt('AUTOMOBILE', 'MY_THES');  
    dbms_output.put_line('The preferred term for automobile is: ' || terms);  
end;
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["Preferred Term \(PT\) \(page 3-41\)"](#)

14.24 RT

This function returns the related terms of a term in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.RT(restab IN OUT NOCOPY EXP_TAB,
            phrase IN VARCHAR2,
            tname  IN VARCHAR2 DEFAULT 'DEFAULT');
```

Syntax 2: String Result

```
CTX_THES.RT(phrase IN VARCHAR2,
            tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN varchar2;
```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (
    xrel varchar2(12),
    xlevel number,
    xphrase varchar2(256)
);
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)"](#) in [Oracle Text Result Tables](#) (page A-1) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

tname

Specify the thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns a string of related terms in the form:

```
{rt1}|{rt2}|{rt3}| ...
```

Example

Consider a thesaurus MY_THES with the following related term definition for dog:

```
DOG
  RT WOLF
  RT HYENA
```

To look up the related terms for *dog*, execute the following code:

```
declare
  terms varchar2(2000);
begin
  terms := ctx_thes.rtf('DOG','MY_THES');
  dbms_output.put_line('The related terms for dog are: '||terms);
end;
```

This code produces the following output:

The related terms for dog are: {dog}||{wolf}||{hyena}

Related Topics

["OUTPUT_STYLE" \(page 14-25\)](#)

["Related Term \(RT\)" \(page 3-41\)](#)

14.25 SN

This function returns the scope note of the given phrase.

Syntax

```
CTX_THES.SN(phrase IN VARCHAR2,
            tname IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN VARCHAR2;
```

phrase

Specify a phrase to lookup in thesaurus.

tname

Specify the thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns the scope note as a string.

Example

```
declare
  note varchar2(80);
begin
  note := ctx_thes.sn('camera','mythes');
  dbms_output.put_line('CAMERA');
  dbms_output.put_line(' SN ' || note);
end;
```

sample output:

```
CAMERA
SN Optical cameras
```

14.26 SYN

This function returns all synonyms of a phrase as recorded in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.SYN(restab IN OUT NOCOPY EXP_TAB,
             phrase IN VARCHAR2,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT');
```

Syntax 2: String Result

```
CTX_THES.SYN(phrase IN VARCHAR2,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN VARCHAR2;
```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (
    xrel varchar2(12),
    xlevel number,
    xphrase varchar2(256)
);
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

tname

Specify the thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns a string of the form:

```
{syn1}||{syn2}||{syn3} ...
```

Example**String Result**

Consider a thesaurus named ANIMALS that has an entry for *cat* as follows:

```
CAT
  SYN KITTY
  SYN FELINE
```

To look-up the synonym for *cat* and obtain the result as a string, enter the following statements:

```
declare
    synonyms varchar2(2000);
begin
    synonyms := ctx_thes.syn('CAT', 'ANIMALS');
```

```
dbms_output.put_line('the synonym expansion for CAT is: '||synonyms);
end;
```

This code produces the following output:

```
the synonym expansion for CAT is: {CAT}||{KITTY}||{FELINE}
```

Table Result

The following code looks up the synonyms for *canine* and obtains the results in a table. The contents of the table are printed to the standard output.

```
declare
  xtab ctx_thes.exp_tab;
begin
  ctx_thes.syn(xtab, 'canine', 'my_thesaurus');
  for i in 1..xtab.count loop
    dbms_output.put_line(lpad(' ', 2*xtab(i).xlevel) ||
      xtab(i).xrel || ' ' || xtab(i).xphrase);
  end loop;
end;
```

This code produces the following output:

```
PHRASE CANINE
  PT DOG
SYN PUPPY
SYN MUTT
SYN MONGREL
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["SYNonym \(SYN\) \(page 3-47\)"](#)

14.27 THES_TT

This procedure finds and returns all top terms of a thesaurus. A top term is defined as any term which has a narrower term but has no broader terms.

This procedure differs from TT in that TT takes in a phrase and finds the top term for that phrase, but THES_TT searches the whole thesaurus and finds all top terms.

Large Thesauri

Because this procedure searches the whole thesaurus, it can take some time on large thesauri. Oracle recommends that you not call this often for such thesauri. Instead, your application should call this once, store the results in a separate table, and use those stored results.

Syntax

```
CTX_THES.THES_TT(restab IN OUT NOCOPY EXP_TAB,
                 tname IN VARCHAR2 DEFAULT 'DEFAULT');
```

restab

Specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:


```

type exp_rec is record (
    xrel varchar2(12),
    xlevel number,
    xphrase varchar2(256)
);
type exp_tab is table of exp_rec index by binary_integer;

```

See Also:

"[CTX_THES Result Tables and Data Types](#) (page A-9)" in [Oracle Text Result Tables](#) (page A-1) for more information about EXP_TAB.

tname

Specify the thesaurus name. If not specified, system default thesaurus is used.

Returns

This procedure returns all top terms and stores them in `restab`.

14.28 TR

For a given mono-lingual thesaurus, this function returns the foreign language equivalent of a phrase as recorded in the thesaurus.

Note:

Foreign language translation is not part of the ISO-2788 or ANSI Z39.19 thesaural standards. The behavior of TR is specific to Oracle Text.

Syntax 1: Table Result

```

CTX_THES.TR(restab IN OUT NOCOPY EXP_TAB,
    phrase IN VARCHAR2,
    lang   IN VARCHAR2 DEFAULT NULL,
    tname  IN VARCHAR2 DEFAULT 'DEFAULT')

```

Syntax 2: String Result

```

CTX_THES.TR(phrase IN VARCHAR2,
    lang   IN VARCHAR2 DEFAULT NULL,
    tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN VARCHAR2;

```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```

type exp_rec is record (
    xrel varchar2(12),
    xlevel number,
    xphrase varchar2(256)
);
type exp_tab is table of exp_rec index by binary_integer;

```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

lang

Specify the foreign language. Specify 'ALL' for all translations of phrase.

tname

Specify the thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns a string of foreign terms in the form:

```
{ft1}||{ft2}||{ft3} ...
```

Example

Consider a thesaurus MY_THES with the following entries for *cat*:

```
cat
  SPANISH: gato
  FRENCH:  chat
  SYN lion
  SPANISH: leon
```

To look up the translation for *cat*, enter the following statements:

```
declare
  trans      varchar2(2000);
  span_trans varchar2(2000);
begin
  trans := ctx_thes.tr('CAT','ALL','MY_THES');
  span_trans := ctx_thes.tr('CAT','SPANISH','MY_THES')
  dbms_output.put_line('the translations for CAT are: '||trans);
  dbms_output.put_line('the Spanish translations for CAT are: '||span_trans);
end;
```

This codes produces the following output:

```
the translations for CAT are: {CAT}||{CHAT}||{GATO}
the Spanish translations for CAT are: {CAT}||{GATO}
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["Translation Term \(TR\) \(page 3-48\)"](#)

14.29 TRSYN

For a given mono-lingual thesaurus, this function returns the foreign equivalent of a phrase, synonyms of the phrase, and foreign equivalent of the synonyms as recorded in the specified thesaurus.

Note:

Foreign language translation is not part of the ISO-2788 or ANSI Z39.19 thesaural standards. The behavior of TRSYN is specific to Oracle Text.

Syntax 1: Table Result

```
CTX_THES.TRSYN(restab IN OUT NOCOPY EXP_TAB,
               phrase IN VARCHAR2,
               lang   IN VARCHAR2 DEFAULT NULL,
               tname  IN VARCHAR2 DEFAULT 'DEFAULT');
```

Syntax 2: String Result

```
CTX_THES.TRSYN(phrase IN VARCHAR2,
               lang   IN VARCHAR2 DEFAULT NULL,
               tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN VARCHAR2;
```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (
    xrel varchar2(12),
    xlevel number,
    xphrase varchar2(256)
);
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

lang

Specify the foreign language. Specify 'ALL' for all translations of *phrase*.

tname

Specify the thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns a string of foreign terms in the form:

```
{ft1}|{ft2}|{ft3} ...
```

Example

Consider a thesaurus MY_THES with the following entries for *cat*:

```
cat
  SPANISH: gato
```

```
FRENCH: chat
SYN lion
SPANISH: leon
```

To look up the translation and synonyms for *cat*, enter the following statements:

```
declare
  synonyms  varchar2(2000);
  span_syn  varchar2(2000);
begin
  synonyms := ctx_thes.trsyn('CAT','ALL','MY_THES');
  span_syn := ctx_thes.trsyn('CAT','SPANISH','MY_THES');
  dbms_output.put_line('all synonyms for CAT are: '||synonyms);
  dbms_output.put_line('the Spanish synonyms for CAT are: '||span_syn);
end;
```

This codes produces the following output:

```
all synonyms for CAT are: {CAT}||{CHAT}||{GATO}||{LION}||{LEON}
the Spanish synonyms for CAT are: {CAT}||{GATO}||{LION}||{LEON}
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["Translation Term Synonym \(TRSYN\) \(page 3-49\)"](#)

14.30 TT

This function returns the top term of a phrase as recorded in the specified thesaurus.

Syntax 1: Table Result

```
CTX_THES.TT(restab IN OUT NOCOPY EXP_TAB,
             phrase IN VARCHAR2,
             tname  IN VARCHAR2 DEFAULT 'DEFAULT');
```

Syntax 2: String Result

```
CTX_THES.TT(phrase IN VARCHAR2,
            tname  IN VARCHAR2 DEFAULT 'DEFAULT')
RETURN varchar2;
```

restab

Optionally, specify the name of the expansion table to store the results. This table must be of type EXP_TAB which the system defines as follows:

```
type exp_rec is record (
  xrel varchar2(12),
  xlevel number,
  xphrase varchar2(256)
);
type exp_tab is table of exp_rec index by binary_integer;
```

See Also:

["CTX_THES Result Tables and Data Types \(page A-9\)" in Oracle Text Result Tables \(page A-1\)](#) for more information about EXP_TAB.

phrase

Specify a phrase to lookup in thesaurus.

tname

Specify the thesaurus name. If not specified, system default thesaurus is used.

Returns

This function returns the top term string in the form:

```
{tt}
```

Example

Consider a thesaurus MY_THES with the following broader term entries for *dog*:

```
DOG
  BT1 CANINE
    BT2 MAMMAL
      BT3 VERTEBRATE
        BT4 ANIMAL
```

To look up the top term for *DOG*, execute the following code:

```
declare
  terms varchar2(2000);
begin
  terms := ctx_thes.tt('DOG','MY_THES');
  dbms_output.put_line('The top term for DOG is: '||terms);
end;
```

This code produces the following output:

```
The top term for dog is: {ANIMAL}
```

Related Topics

["OUTPUT_STYLE \(page 14-25\)"](#)

["Top Term \(TT\) \(page 3-50\)"](#)

14.31 UPDATE_TRANSLATION

Use this procedure to update an existing translation.

Syntax

```
CTX_THES.UPDATE_TRANSLATION(tname      in      varchar2,
                             phrase     in      varchar2,
                             language   in      varchar2,
                             translation in      varchar2,
                             new_translation in varchar2);
```

tname

Specify the name of the thesaurus, using no more than 30 characters.

phrase

Specify the phrase in the thesaurus to which to update a translation. The phrase must already exist in the thesaurus or an error is raised.

language

Specify the language of the translation, using no more than 10 characters.

translation

Specify the translated term to update. If no such translation exists, an error is raised.

You can specify `NULL` if there is only one translation for the *phrase*. An error is raised if there is more than one translation for the term in the specified language.

new_translation

Optionally, specify the new form of the translated term.

Example

The following code updates the Spanish translation for *dog*:

```
begin
  ctx_thes.update_translation('my_thes', 'dog', 'SPANISH:', 'PERRO', 'CAN');
end;
```

CTX_ULEXER Package

This chapter provides reference information on how to use the CTX_ULEXER PL/SQL package with the user-defined lexer.

CTX_ULEXER declares the following type:

Name	Description
WILDCARD_TAB (page 15-1)	Index-by table type that you use to specify the offset of characters to be treated as wildcard characters by the user-defined lexer query procedure.

15.1 WILDCARD_TAB

```
TYPE WILDCARD_TAB IS TABLE OF NUMBER INDEX BY BINARY_INTEGER;
```

Use this index-by table type to specify the offset of those characters in the query word to be treated as wildcard characters by the user-defined lexer query procedure.

Character offset information follows USC-2 codepoint semantics.

Oracle Text Utilities

Oracle Text provides utilities for managing and operating on Text indexes. For example, you can load a specific thesaurus into the index, and you can create your own knowledge base to be associated with the index, among other things. This chapter discusses the utilities shipped with Oracle Text.

The following topics are included:

- [Thesaurus Loader \(ctxload\)](#) (page 16-1)
- [Entity Extraction User Dictionary Loader \(ctxload\)](#) (page 16-3)
- [Knowledge Base Extension Compiler \(ctxkbtcl\)](#) (page 16-6)
- [Lexical Compiler \(ctxlcl\)](#) (page 16-12)

16.1 Thesaurus Loader (ctxload)

Use `ctxload` to import a thesaurus file into the Oracle Text thesaurus tables.

An import file is an ASCII flat file that contains entries for synonyms, broader terms, narrower terms, or related terms, which can be used to expand queries.

This section contains the following topics.

- [ctxload Text Loading](#) (page 16-1)
- [ctxload Syntax](#) (page 16-2)
- [ctxload Examples](#) (page 16-3)

See Also:

For examples of import files for thesaurus importing, see "[Structure of ctxload Thesaurus Import File](#) (page C-3)" in [Text Loading Examples for Oracle Text](#) (page C-1)

16.1.1 ctxload Text Loading

The `ctxload` program no longer supports the loading of text columns. To load files to a text column in batch mode, Oracle recommends that you use `SQL*Loader`.

See Also:

"[SQL*Loader Example](#) (page C-1)" in [Text Loading Examples for Oracle Text](#) (page C-1)

16.1.2 ctxload Syntax

```
ctxload -user username[/password][@sqlnet_address]
        -name object_name
        -file file_name

        [-thes]
        [-thescase y|n]
        [-thesdump]
        [-log file_name]
        [-trace]
        [-drop]
```

ctxload Mandatory Arguments

-user

Specify the user name and password of the user running ctxload.

The user name and password can be followed immediately by *@sqlnet_address* to permit logging on to remote databases. The value for *sqlnet_address* is a database connect string. If the *TWO_TASK* environment variable is set to a remote database, then you do not need to specify a value for *sqlnet_address* to connect to the database.

-name object_name

When you use ctxload to import a thesaurus, use *object_name* to specify the name of the thesaurus to be imported.

Use *object_name* to identify the thesaurus in queries that use thesaurus operators.

Note:

Thesaurus name must be unique. If the name specified for the thesaurus is identical to an existing thesaurus, then ctxload returns an error and does not overwrite the existing thesaurus.

-file file_name

When ctxload is used to import a thesaurus, use *file_name* to specify the name of the import file that contains the thesaurus entries.

When ctxload is used to export a thesaurus, use *file_name* to specify the name of the export file created by ctxload.

Note:

If the name specified for the thesaurus dump file is identical to an existing file, then ctxload overwrites the existing file.

ctxload Optional Arguments

-thes

Import a thesaurus. Specify the source file with the *-file* argument. Specify the name of the thesaurus to be imported with *-name*.

-thescase y | n

Specify *y* to create a case-sensitive thesaurus with the name specified by `-name` and populate the thesaurus with entries from the thesaurus import file specified by `-file`. If `-thescase` is *y* (the thesaurus is case-sensitive), `ctxload` enters the terms in the thesaurus exactly as they appear in the import file.

The default for `-thescase` is *n* (case-insensitive thesaurus).

Note:

`-thescase` is valid for use only with the `-thes` argument.

-thesdump

Export a thesaurus. Specify the name of the thesaurus to be exported with the `-name` argument. Specify the destination file with the `-file` argument.

-log

Specify the name of the log file to which `ctxload` writes any national-language supported (Globalization Support) messages generated during processing. If you do not specify a log file name, the messages appear on the standard output.

-trace

Enables SQL statement tracing using `ALTER SESSION SET SQL_TRACE TRUE`. This command captures all processed SQL statements in a trace file, which can be used for debugging. The location of the trace file is operating-system dependent and can be modified using the `DIAGNOSTIC_DEST` initialization parameter.

See Also:

For more information about SQL trace and the `DIAGNOSTIC_DEST` initialization parameter, see *Oracle Database Administrator's Guide*

16.1.3 ctxload Examples

This section provides examples for some of the operations that `ctxload` can perform.

See Also:

For more document loading examples, see [Text Loading Examples for Oracle Text](#) (page C-1)

The following example imports a thesaurus named `tech_doc` from an import file named `tech_thesaurus.txt`:

```
ctxload -user jsmith/password -thes -name tech_doc -file tech_thesaurus.txt
```

The following example exports the contents of a thesaurus named `tech_doc` into a file named `tech_thesaurus.out`:

```
ctxload -user jsmith/password -thesdump -name tech_doc -file tech_thesaurus.out
```

16.2 Entity Extraction User Dictionary Loader (ctxload)

Use `ctxload` to import an entity extraction user dictionary into Oracle Text tables.

An import file is an XML flat file containing entries for entities, with their associated types and alternate forms.

This section contains the following topics.

- [ctxload Syntax](#) (page 16-4)
- [Considerations When Creating a User Dictionary](#) (page 16-4)
- [XML Schema](#) (page 16-5)
- [ctxload Example](#) (page 16-6)

16.2.1 ctxload Syntax

```
ctxload -user username[/password][@sqlnet_address]
        -extract
        -name entity extraction policy name
        -file user-dictionary file name
        [-drop] to drop a user-dictionary from a policy
```

ctxload Mandatory Arguments

-user

Specify the user name and password of the user running ctxload.

The user name and password can be followed immediately by *@sqlnet_address* to permit logging on to remote databases. The value for *sqlnet_address* is a database connect string. If the *TWO_TASK* environment variable is set to a remote database, then you do not need to specify a value for *sqlnet_address* to connect to the database.

-name entity extraction policy name

When you use ctxload to import an entity extraction dictionary, use *object_name* to specify the entity extraction policy to associate the dictionary with. An entity extraction policy can have only one user dictionary.

-file user-dictionary file name

Use file to specify the name of the XML file containing the user dictionary.

-drop

Drop the user dictionary currently associated with an entity extraction policy.

16.2.2 Considerations When Creating a User Dictionary

The following are some considerations for when creating a user dictionary:

- Entity mentions are case-sensitive. They cannot contain any null characters.
- Entity type names are case-insensitive. They cannot contain any null or comma characters.
- Customers will be able to assign two or more entity types to a single entity mention. For example, the entity "Washington" could be assigned the type "CITY" and also the type "STATE".
- The content of a user's dictionary is invisible to other users.
- The maximum byte length of an entity mention is 512 bytes by the server-side database character set.

- The maximum byte length of an entity type name is 30 bytes by the server-side database character set.
- User-defined entity type names must start with the letter "x".

16.2.3 XML Schema

The entity extraction dictionary follows this XML schema:

```
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema">

  <xsd:element name="dictionary">
    <xsd:complexType>
      <xsd:sequence>
        <xsd:element name="entities" type="entityType" maxOccurs="unbounded"/>
      </xsd:sequence>
    </xsd:complexType>
  </xsd:element>

  <xsd:complexType name="entityType">
    <xsd:sequence>
      <xsd:element name="entity" type="entType" maxOccurs="unbounded"/>
    </xsd:sequence>
    </xsd:attribute name="language" type="xsd:string"/>
  </xsd:complexType>

  <xsd:complexType name="entType">
    <xsd:sequence>
      <xsd:element name="value" type="xsd:string"/>
      <xsd:element name="type" type="xsd:string" minOccurs="1" maxOccurs="unbounded"/>
      <xsd:element name="alternate" type="xsd:string" minOccurs="0"
maxOccurs="unbounded"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:schema>
```

The following tables illustrate some aspects of the XML schema for the entity extraction dictionary.

Element Name	Description
dictionary	Collection of entities
entities	Collection of entities per language
entity	Each entity
value	Entity mention
type	Entity type
alternate	Alternate form of entity

Attribute Name	Element Name	Description
language	Entities	Language name of each entity in entities

16.2.4 ctxload Example

The following is an example of an entity extraction user dictionary file that can be loaded using `ctxload`:

```
<?xml version="1.0" encoding="utf-8"?>
<dictionary>
  <entities>
    <entity>
      <value>New York</value>
      <type>city</type>
    </entity>
  </entities>
  <entities language="german">
    <entity>
      <value>Deutschland</value>
      <type>country</type>
    </entity>
  </entities>
  <entities language="english">
    <entity>
      <value>Astra</value>
      <type>person</type>
      <type>organization</type>
    </entity>
    <entity>
      <value>George W. Bush</value>
      <type>person</type>
      <alternate>G. W. Bush</alternate>
      <alternate>G. Bush</alternate>
    </entity>
  </entities>
</dictionary>
```

16.3 Knowledge Base Extension Compiler (ctxkbtc)

The knowledge base is the information source that Oracle Text uses to perform theme analysis, such as theme indexing, processing ABOUT queries, and to document theme extraction with the CTX_DOC package. A knowledge base is supplied for English and French and is installed by default.

With the `ctxkbtc` compiler, you can:

- Extend your knowledge base by compiling one or more thesauri with the Oracle Text knowledge base. The extended information can be application-specific terms and relationships. During theme analysis, the extended portion of the knowledge base overrides any terms and relationships in the knowledge base where there is overlap.
- Create a new user-defined knowledge base by compiling one or more thesauri. In languages other than English and French, this feature can be used to create a language-specific knowledge base.

Note:

Only CTXSYS can extend the knowledge base.

This section contains the following topics.

- [Knowledge Base Character Set](#) (page 16-7)
- [ctxkbtc Syntax](#) (page 16-7)
- [ctxkbtc Usage Notes](#) (page 16-8)
- [ctxkbtc Limitations](#) (page 16-8)
- [ctxkbtc Constraints on Thesaurus Terms](#) (page 16-9)
- [ctxkbtc Constraints on Thesaurus Relations](#) (page 16-9)
- [Extending the Knowledge Base](#) (page 16-10)
[Example for Extending the Knowledge Base](#) (page 16-10)
- [Adding a Language-Specific Knowledge Base](#) (page 16-11)
[Limitations for Adding a Knowledge Base](#) (page 16-11)
- [Order of Precedence for Multiple Thesauri](#) (page 16-11)
- [Size Limits for Extended Knowledge Base](#) (page 16-12)

See Also:

For more information about the ABOUT operator, see [ABOUT](#) (page 3-4) operator in [Oracle Text CONTAINS Query Operators](#) (page 3-1)

For more information about document services, see [CTX_DOC Package](#) (page 9-1)

16.3.1 Knowledge Base Character Set

Knowledge bases can be in any single-byte character set. Supplied knowledge bases are in WE8ISO8859P1. You can store an extended knowledge base in another character set such as US7ASCII.

16.3.2 ctxkbtc Syntax

```
ctxkbtc -user uname/passwd
```

```
[-name thesname1 [thesname2 ... thesname16]]  
[-revert]  
[-stoplist stoplistname]  
[-verbose]  
[-log filename]
```

-user

Specify the user name and password for the administrator creating an extended knowledge base. This user must have write permission to the ORACLE_HOME directory.

-name *thesname1 [thesname2 ... thesname16]*

Specify the names of the thesauri (up to 16) to be compiled with the knowledge base to create the extended knowledge base. The thesauri you specify must already be loaded with `ctxload` with the `"-thescase Y"` option.

-revert

Reverts the extended knowledge base to the default knowledge base provided by Oracle Text.

-stoplist *stoplistname*

Specify the name of the stoplist. Stopwords in the stoplist are added to the knowledge base as useless words that are prevented from becoming themes or contributing to themes. Add stopthemes after running this command using `CTX_DLL.ADD_STOPTHEME`.

-verbose

Displays all warnings and messages, including non-Globalization Support messages, to the standard output.

-log

Specify the log file for storing all messages. When you specify a log file, no messages are reported to standard out.

16.3.3 ctxkbtc Usage Notes

- Before running `ctxkbtc`, you must set the `NLS_LANG` environment variable to match the database character set.
- The user issuing `ctxkbtc` must have write permission to the `ORACLE_HOME`, because the program writes files to this directory.
- Before being compiled, each thesaurus must be loaded into Oracle Text case sensitive with the `"-thescase Y"` option in `ctxload`.
- Running `ctxkbtc` twice removes the previous extension.

16.3.4 ctxkbtc Limitations

The `ctxkbtc` program has the following limitations:

- When upgrading or downgrading your database to a different release, for theme indexing and related features to work correctly, Oracle recommends that you recompile your extended knowledge base in the new environment.
- Before extending the knowledge base, you must terminate all server processes that have invoked any knowledge base-related Text functions during their lifetime.
- There can be only one user extension for each language for each installation. Because a user extension affects all users at the installation, only the `CTXSYS` user can extend the knowledge base.
- In an Oracle RAC environment, the `ORACLE_HOME` can either be shared between multiple nodes, or each node can have its own `ORACLE_HOME`. The following requirements apply:

- Before using any knowledge base-dependent functionality in any of the Oracle RAC nodes, `ctxkbtc` must be run in every `ORACLE_HOME` in the Oracle RAC environment.
- When using `ctxkbtc`, the exact same input thesaurus content must be used in every `ORACLE_HOME` in the Oracle RAC environment.

16.3.5 ctxkbtc Constraints on Thesaurus Terms

Terms are case sensitive. If a thesaurus has a term in uppercase, for example, the same term present in lowercase form in a document will not be recognized.

The maximum length of a term is 80 characters.

Disambiguated homographs are not supported.

16.3.6 ctxkbtc Constraints on Thesaurus Relations

The following constraints apply to thesaurus relations:

- BTG and BTP are the same as BT. NTG and NTP are the same as NT.
- Only preferred terms can have a BT, NTs or RTs.
- If a term has no USE relation, it will be treated as its own preferred term.
- If a set of terms are related by SYN relations, only one of them may be a preferred term.
- An existing category cannot be made a top term.
- There can be no cycles in BT and NT relations.
- A term can have at most one preferred term and at most one BT. A term may have any number of NTs.
- An RT of a term cannot be an ancestor or descendent of the term. A preferred term may have any number of RTs up to a maximum of 32.
- The maximum height of a tree is 16 including the top term level.
- When multiple thesauri are being compiled, a top term in one thesaurus should not have a broader term in another thesaurus.

Note:

The thesaurus compiler tolerates some violations of the preceding rules. For example, if a term has multiple BTs, then the compiler ignores all but the last one it encounters.

Similarly, BTs between existing knowledge base categories result only in a warning message.

Oracle recommends that you do not set up extended storage bases with violations. Using extended storage bases containing violations can produce undesired results.

16.3.7 Extending the Knowledge Base

Extend the supplied knowledge base by compiling one or more thesauri with the Oracle Text knowledge base. The extended information can be application-specific terms and relationships. During theme analysis, the extended portion of the knowledge base overrides any terms and relationships in the knowledge base where there is overlap.

When extending the knowledge base, Oracle recommends that new terms be linked to one of the categories in the knowledge base for best results in theme proving when appropriate.

If new terms are kept completely disjoint from existing categories, fewer themes from new terms will be proven. The result of this is poorer precision and recall with ABOUT queries as well poor quality of gists and theme highlighting.

Link new terms to existing terms by making an existing term the broader term for the new terms.

16.3.8 Example for Extending the Knowledge Base

You purchase a medical thesaurus `medthes` containing a hierarchy of medical terms. The four top terms in the thesaurus are the following:

- Anesthesia and Analgesia
- Anti-Allergic and Respiratory System Agents
- Anti-Inflammatory Agents, Antirheumatic Agents, and Inflammation Mediators
- Antineoplastic and Immunosuppressive Agents

To link these terms to the existing knowledge base, add the following entries to the medical thesaurus to map the new terms to the existing *health and medicine* branch:

```
health and medicine
NT Anesthesia and Analgesia
NT Anti-Allergic and Respiratory System Agents
NT Anti-Inflammatory Agents, Antirheumatic Agents, and Inflammation Mediators
NT Antineoplastic and Immunosuppressive Agents
```

Set your globalization support language environment variable to match the database character set. For example, if your database character set is `WE8ISO8859P1` and you are using American English, set your `NLS_LANG` as follows:

```
setenv NLS_LANG AMERICAN_AMERICA.WE8ISO8859P1
```

Assuming the medical thesaurus is in a file called `medthes`, load the thesaurus as `medthes` with `ctxload` as follows:

```
ctxload -thes -thescase y -name medthes -file medthes -user ctxsys/ctxsys
```

To link the loaded thesaurus `medthes` to the knowledge base, use `ctxkbtc` as follows:

```
ctxkbtc -user ctxsys/ctxsys -name medthes
```

16.3.9 Adding a Language-Specific Knowledge Base

Extend theme functionality to languages other than English or French by loading your own knowledge base for any single-byte whitespace delimited language, including Spanish.

Theme functionality includes theme indexing, ABOUT queries, theme highlighting, and the generation of themes, gists, and theme summaries with the CTX_DOC PL/SQL package.

Extend theme functionality by adding a user-defined knowledge base. For example, you can create a Spanish knowledge base from a Spanish thesaurus.

To load your language-specific knowledge base, follow these steps:

1. Load your custom thesaurus using `ctxload`.
2. Set `NLS_LANG` so that the language portion is the target language. The charset portion must be a single-byte character set.
3. Compile the loaded thesaurus using `ctxkbtcc`:

```
ctxkbtcc -user ctxsys/ctxsys -name my_lang_thes
```

This command compiles your language-specific knowledge base from the loaded thesaurus. To use this knowledge base for theme analysis during indexing and ABOUT queries, specify the `NLS_LANG` language as the `THEME_LANGUAGE` attribute value for the `BASIC_LEXER` preference.

16.3.10 Limitations for Adding a Knowledge Base

The following limitations hold for adding knowledge bases:

- Oracle Text supplies knowledge bases in English and French only. You must provide your own thesaurus for any other language.
- You can only add knowledge bases for languages with single-byte character sets. You cannot create a knowledge base for languages which can be expressed only in multibyte character sets. If the database is a multibyte universal character set, such as UTF-8, the `NLS_LANG` parameter must still be set to a compatible single-byte character set when compiling the thesaurus.
- Adding a knowledge base works best for whitespace delimited languages.
- You can have at most one knowledge base for each globalization support language.
- Obtaining hierarchical query feedback information such as broader terms, narrower terms and related terms does not work in languages other than English and French. In other languages, the knowledge bases are derived entirely from your thesauri. In such cases, Oracle recommends that you obtain hierarchical information directly from your thesauri.

16.3.11 Order of Precedence for Multiple Thesauri

When multiple thesauri are to be compiled, precedence is determined by the order in which thesauri are listed in the arguments to the compiler, assumed to be *most*

preferred first. A user-defined thesaurus always has precedence over the built-in knowledge base.

16.3.12 Size Limits for Extended Knowledge Base

The following table lists the size limits associated with creating and compiling an extended knowledge base.

Table 16-1 Size Limit for the Extended Knowledge Base

Description of Parameter	Limit
Number of RTs (from + to) for each term	32
Number of terms for each single hierarchy (for example, all narrower terms for a given top term)	64000
Number of new terms in an extended knowledge base	1 million
Number of separate thesauri that can be compiled into a user extension to the KB	16

16.4 Lexical Compiler (ctxlc)

The Lexical Compiler (ctxlc) is a command-line utility that enables you to create your own Chinese and Japanese lexicons (dictionaries). Such a lexicon may either be generated from a user-supplied word list or from the merging of a word list with the system lexicon for that language.

ctxlc creates the new lexicon in your current directory. The new lexicon consists of three files, `droid.dat`, `drolk.dat`, and `drolj.dat`. To change your system lexicon for Japanese or Chinese, overwrite the system lexicon with these files.

The Lexical Compiler can also generate wordlists from the system lexicons for Japanese and Chinese, enabling you to see their contents. These word lists go to the standard output and thus can be redirected into a file of your choice.

After overwriting the system lexicon, you need to re-create your indexes before querying them.

This section contains the following topics.

- [Syntax of ctxlc](#) (page 16-12)
- [ctxlc Performance Considerations](#) (page 16-13)
- [ctxlc Usage Notes](#) (page 16-13)
- [ctxlc Example](#) (page 16-13)

16.4.1 Syntax of ctxlc

ctxlc has the following syntax:

```
ctxlc -ja | -zht [ -n ] -ics character_set -i input_file
```

```
ctxlc -ja | -zht -ocs character_set [ > output_file ]
```

ctxload Mandatory Arguments

-ja | -zht

Specify the language of the lexicon to modify or create. `-ja` indicates the Japanese lexicon; `-zht` indicates the Chinese lexicon, the same for either traditional or simplified Chinese.

-ics *character_set*

Specify the character set of the input file denoted by `-i input_file`. *input_file* is the list of words, one word to a line, to use in creating the new lexicon.

-i *input_file*

Specify the file containing words to use in creating a new lexicon.

-ocs *character_set*

Specify the character set of the text file to be output.

ctxload Optional Arguments**-n**

Specify `-n` to create a new lexicon that consists only of user-supplied words taken from *input_file*. If `-n` is not specified, then the new lexicon consists of a merge of the system lexicon with *input_file*. Also, when `-n` is not selected, a text file called `drolt.dat`, is created in the current directory to enable you to inspect the contents of the merged lexicon without having to enter another `ctxlc` command.

16.4.2 ctxlc Performance Considerations

You can add up to 1,000,000 new words to a lexicon. However, creating a very large lexicon can reduce performance in indexing and querying. Performance is best when the lexicon character set is UTF-8. There is no performance impact on the Chinese or Japanese V-gram lexers, as they do not use lexicons.

16.4.3 ctxlc Usage Notes

Oracle recommends the following practices with regard to `ctxlc`:

- Save your plain text dictionary file in your environment for emergency use.
- When upgrading or downgrading your database to a different release, recompile your plain text dictionary file in the new environment so that the user lexicon will work correctly.

16.4.4 ctxlc Example

In this example, you create a new Japanese lexicon from the file `jadict.txt`, a word list that uses the JA16EUC character set. Because you are not specifying `-n`, the new lexicon is the result of merging `jadict.txt` with the system Japanese lexicon. Then replace the existing Japanese lexicon with the new, merged one.

```
% ctxlc -ja -ics JA16EUC -i jadict.txt
```

This creates new files in the current directory:

```
% ls
drol.d.dat
drolk.dat
droli.dat
drolt.dat
```

The system lexicon files for Japanese and Chinese are named `droldxx.dat`, `drolkxx.dat`, and `drolixx.dat`, where `xx` is either `JA` (for Japanese) or `ZH` (for Chinese). Rename the three new files and copy them to the directory containing the system Japanese lexicon.

```
% mv drold.dat droldJA.dat
% mv drolk.dat drolkJA.dat
% mv droli.dat droliJA.dat
% cp *dat $ORACLE_HOME/ctx/data/jalx
```

This replaces the system Japanese lexicon with one that is a merge of the old system lexicon and your wordlist from `jadict.txt`.

You can also use `ctxlc` to get a dump of a system lexicon. This example dumps the Chinese lexicon to a file called `new_chinese_dict.txt` in the current directory:

```
% ctxlc -zh -ocs UTF8 > new_chinese_dict.txt
```

This creates a file, `new_japanese.dict.txt`, using the UTF8 character set, in the current directory.

Oracle Text Alternative Spelling

This chapter describes various ways that Oracle Text handles alternative spelling of words. It also documents the alternative spelling conventions that Oracle Text uses in the German, Danish, and Swedish languages.

The following topics are covered:

- [Overview of Alternative Spelling Features](#) (page 17-1)
- [Overriding Alternative Spelling Features](#) (page 17-3)
- [Alternative Spelling Conventions](#) (page 17-4)

17.1 Overview of Alternative Spelling Features

Some languages have alternative spelling forms for certain words. For example, the German word *Schoen* can also be spelled as *Schön*.

The form of a word is either *original* or *normalized*. The original form of the word is how it appears in the source document. The normalized form is how it is transformed, if it is transformed at all. Depending on the word being indexed and which system preferences are in effect (these are discussed in this chapter), the normalized form of a word may be the same as the original form. Also, the normalized form may comprise more than one spelling. For example, the normalized form of *Schoen* is both *Schoen* and *Schön*.

Oracle Text handles indexing of alternative word forms in the following ways:

- Alternate Spelling—indexing of alternative forms is enabled
- Base-Letter Conversion—accented letters are transformed into non-accented representations
- New German Spelling—reformed German spelling is accepted

Enable these features by specifying the appropriate attribute to the BASIC_LEXER. For instance, enable alternate spelling by specifying either GERMAN, DANISH, or SWEDISH for the ALTERNATE_SPELLING attribute. As an example, here is how to enable alternate spelling in German:

```
begin
ctx_ddl.create_preference('GERMAN_LEX', 'BASIC_LEXER');
ctx_ddl.set_attribute('GERMAN_LEX', 'ALTERNATE_SPELLING', 'GERMAN');
end;
```

To disable alternate spelling, use the CTX_DDL.UNSET_ATTRIBUTE procedure as follows:

```
begin
ctx_ddl.unset_attribute('GERMAN_LEX', 'ALTERNATE_SPELLING');
end;
```

Oracle Text converts query terms to their normalized forms before lookup. As a result, users can query words with either spelling. If *Schoen* has been indexed as both *Schoen* and *Schön*, a query with *Schön* returns documents containing either form.

This section contains the following topics.

- [Alternate Spelling](#) (page 17-2)
- [Base-Letter Conversion](#) (page 17-2)
- [New German Spelling](#) (page 17-3)

17.1.1 Alternate Spelling

When Swedish, German, or Danish has more than one way of spelling a word, Oracle Text normally indexes the word in its original form; that is, as it appears in the source document.

When Alternate Spelling is enabled, Oracle Text indexes words in their normalized form. So, for example, *Schoen* is indexed both as *Schoen* and as *Schön*, and a query on *Schoen* will return documents containing either spelling. (The same is true of a query on *Schön*.)

To enable Alternate Spelling, set the BASIC_LEXER attribute ALTERNATE_SPELLING to GERMAN, DANISH, or SWEDISH. See "[BASIC_LEXER](#) (page 2-41)" for more information.

17.1.2 Base-Letter Conversion

Besides alternative spelling, Oracle Text also handles base-letter conversions. With base-letter conversions enabled, letters with umlauts, acute accents, cedillas, and the like are converted to their basic forms for indexing, so *fiancé* is indexed both as *fiancé* and as *fiance*, and a query of *fiancé* returns documents containing either form.

To enable base-letter conversions, set the BASIC_LEXER attribute BASE_LETTER to YES. See "[BASIC_LEXER](#) (page 2-41)" for more information.

When Alternate Spelling is also enabled, Base-Letter Conversion may need to be overridden to prevent unexpected results. See "[Overriding Alternative Spelling Features](#) (page 17-3)" for more information.

Generic Versus Language-Specific Base-Letter Conversions

The BASE_LETTER_TYPE attribute affects the way base-letter conversions take place. It has two possible values: GENERIC or SPECIFIC.

The GENERIC value is the default and specifies that base letter transformation uses one transformation table that applies to all languages.

The SPECIFIC value means that a base-letter transformation that has been specifically defined for your language will be used. This enables you to use accent-sensitive searches for words in your own language, while ignoring accents that are from other languages.

For example, both the GENERIC and the Spanish SPECIFIC tables will transform *é* into *e*. However, they treat the letter *ñ* distinctly. The GENERIC table treats *ñ* as an *n*

with an accent (actually, a tilde), and so transforms *ñ* to *n*. The Spanish `SPECIFIC` table treats *ñ* as a separate letter of the alphabet, and thus does not transform it.

17.1.3 New German Spelling

In 1996, new spelling rules for German were approved by representatives from all German-speaking countries. For example, under the spelling reforms, *Potential* becomes *Potenzial*, *Schiffahrt* becomes *Schiffahrt*, and *schneuzen* becomes *schnäuzen*.

When the `BASIC_LEXER` attribute `NEW_GERMAN_SPELLING` is set to `YES`, then a `CONTAINS` query on a German word that has both new and traditional forms will return documents matching both forms. For example, a query on *Potential* returns documents containing both *Potential* and *Potenzial*. The default setting is `NO`.

Note:

Under reformed German spelling, many words traditionally spelled as one word, such as *soviel*, are now spelled as two (*so viel*). Currently, Oracle Text does not make these conversions, nor conversions from two words to one (for example, *weh tun* to *wehtun*).

The case of the transformed word is determined from the first two characters of the word in the source document; that is, *schiffahrt* becomes *schiffahrt*, *Schiffahrt* becomes *Schiffahrt*, and *SCHIFFAHRT* becomes *SCHIFFFAHRT*.

As many new German spellings include hyphens, it is recommended that users choosing `NEW_GERMAN_SPELLING` define hyphens as print joins.

See "[BASIC_LEXER](#) (page 2-41)" for more information on setting this attribute.

17.2 Overriding Alternative Spelling Features

Even when alternative spelling features have been specified by lexer preference, it is possible to override them.

You can override base-letter conversion when Alternate Spelling is used, to prevent characters with alternate spelling forms, such as *ü*, *ö*, and *ä*, from also being transformed to the base letter forms.

Overriding Base-Letter Transformations with Alternate Spelling

Transformations caused by turning on `alternate_spelling` are performed before those of `base_letter`, which can sometimes cause unexpected results when both are enabled.

When Alternate Spelling is enabled, Oracle Text converts two-letter forms to single-letter forms (for example, *ue* to *ü*), so that words can be searched in both their base and alternate forms. Therefore, with Alternate Spelling enabled, a search for *Schoen* will return documents with both *Schoen* and *Schön*.

However, when Base-letter Transformation is also enabled, the *ü* in *Schlüssel* is transformed into a *u*, producing the non-existent word (in German, anyway) *Schlussel*, and the word is indexed in all three forms.

To prevent this secondary conversion, set the `OVERRIDE_BASE_LETTER` attribute to `TRUE`.

`OVERRIDE_BASE_LETTER` only affects letters with umlauts; accented letters, for example, are still transformed into their base forms.

For more on BASE_LETTER, see "[Base-Letter Conversion](#) (page 17-2)".

17.3 Alternative Spelling Conventions

The following sections show the alternative spelling substitutions used by Oracle Text.

- [German Alternate Spelling Conventions](#) (page 17-4)
- [Danish Alternate Spelling Conventions](#) (page 17-4)
- [Swedish Alternate Spelling Conventions](#) (page 17-5)

17.3.1 German Alternate Spelling Conventions

The German alphabet is the English alphabet plus the additional characters: ä ö ü ß. [Table 17-1](#) (page 17-4) lists the alternate spelling conventions Oracle Text uses for these characters.

Table 17-1 German Alternate Spelling Conventions

Character	Alternate Spelling Substitution
ä	ae
ü	ue
ö	oe
Ä	AE
Ü	UE
Ö	OE
ß	ss

17.3.2 Danish Alternate Spelling Conventions

The Danish alphabet is the Latin alphabet without the *w*, plus the special characters: ø æ å. [Table 17-2](#) (page 17-4) lists the alternate spelling conventions Oracle Text uses for these characters.

Table 17-2 Danish Alternate Spelling Conventions

Character	Alternate Spelling Substitution
æ	ae
ø	oe
å	aa
Æ	AE
Ø	OE
Å	AA

17.3.3 Swedish Alternate Spelling Conventions

The Swedish alphabet is the English alphabet without the *w*, plus the additional characters: å ä ö. [Table 17-3](#) (page 17-5) lists the alternate spelling conventions Oracle Text uses for these characters.

Table 17-3 Swedish Alternate Spelling Conventions

Character	Alternate Spelling Convention
ä	ae
å	aa
ö	oe
Ä	AE
Å	AA
Ö	OE

Oracle Text Result Tables

This appendix describes the structure of the result tables used to store the output generated by the procedures in the CTX_QUERY, CTX_DOC, and CTX_THES packages.

The following topics are discussed in this appendix:

- [CTX_QUERY Result Tables](#) (page A-1)
- [CTX_DOC Result Tables](#) (page A-6)
- [CTX_THES Result Tables and Data Types](#) (page A-9)

A.1 CTX_QUERY Result Tables

For the CTX_QUERY procedures that return results, tables for storing the results must be created before the procedure is called. The tables can be named anything, but must include columns with specific names and data types.

This section describes the following types of result tables, and their required columns:

- [EXPLAIN Table](#) (page A-1)
- [HFEEDBACK Table](#) (page A-3)

A.1.1 EXPLAIN Table

This section describes the EXPLAIN table.

- [EXPLAIN Table Structure](#) (page A-1)
- [EXPLAIN Table Operation Column Values](#) (page A-2)
- [EXPLAIN Table OPTIONS Column Values](#) (page A-3)

A.1.1.1 EXPLAIN Table Structure

[Table A-1](#) (page A-1) describes the structure of the table to which CTX_QUERY.EXPLAIN (page 12-4) writes its results.

Table A-1 *EXPLAIN Result Table*

Column Name	Datatype	Description
EXPLAIN_ID	VARCHAR2(30)	The value of the explain_id argument specified in the FEEDBACK call.

Table A-1 (Cont.) EXPLAIN Result Table

Column Name	Datatype	Description
ID	NUMBER	A number assigned to each node in the query execution tree. The root operation node has ID =1. The nodes are numbered in a top-down, left-first manner as they appear in the parse tree.
PARENT_ID	NUMBER	The ID of the execution step that operates on the output of the ID step. Graphically, this is the parent node in the query execution tree. The root operation node (ID =1) has PARENT_ID = 0.
OPERATION	VARCHAR2 (30)	Name of the internal operation performed. Refer to Table A-2 (page A-2) for possible values.
OPTIONS	VARCHAR2 (30)	Characters that describe a variation on the operation described in the OPERATION column. When an OPERATION has more than one OPTIONS associated with it, OPTIONS values are concatenated in the order of processing. See Table A-3 (page A-3) for possible values.
OBJECT_NAME	VARCHAR2 (80)	Section name, wildcard term, weight, or threshold value or term to lookup in the index.
POSITION	NUMBER	The order of processing for nodes that all have the same PARENT_ID. The positions are numbered in ascending order starting at 1.
CARDINALITY	NUMBER	Reserved for future use. You should create this column for forward compatibility.

A.1.1.2 EXPLAIN Table Operation Column Values

[Table A-2](#) (page A-2) shows the possible values for the OPERATION column of the EXPLAIN table.

Table A-2 EXPLAIN Table OPERATION Column

Operation Value	Query Operator	Equivalent Symbol
ABOUT	ABOUT	n/a
ACCUMULATE	ACCUM	,
AND	AND	&
COMPOSITE	(none)	n/a
EQUIVALENCE	EQUIV	=
MINUS	MINUS	-

Table A-2 (Cont.) EXPLAIN Table OPERATION Column

Operation Value	Query Operator	Equivalent Symbol
NEAR	NEAR	;
NOT	NOT	~
NO_HITS	(no hits will result from this query)	n/a
OR	OR	
PHRASE	(a phrase term)	n/a
SECTION	(section)	n/a
THRESHOLD	>	>
WEIGHT	*	*
WITHIN	within	n/a
WORD	(a single term)	n/a

A.1.1.3 EXPLAIN Table OPTIONS Column Values

[Table A-3](#) (page A-3) list the possible values for the OPTIONS column of the EXPLAIN table.

Table A-3 EXPLAIN Table OPTIONS Column

Options Value	Description
(\$)	Stem
(?)	Fuzzy
(!)	Soundex
(T)	Order for ordered Near.
(F)	Order for unordered Near.
(n)	A number associated with the max_span parameter for the Near operator.
[9]	Indicates that index_stems is set and query is using token_type 9.

A.1.2 HFEEDBACK Table

This section describes the HFEEDBACK table.

- [HFEEDBACK Table Structure](#) (page A-4)
- [HFEEDBACK Table Operation Column Values](#) (page A-4)
- [HFEEDBACK Table OPTIONS Column Values](#) (page A-5)
- [CTX_FEEDBACK_TYPE](#) (page A-5)

A.1.2.1 HFEEDBACK Table Structure

[Table A-4](#) (page A-4) describes the table to which CTX_QUERY.[HFEEDBACK](#) (page 12-7) writes its results.

Table A-4 HFEEDBACK Results Table

Column Name	Datatype	Description
FEEDBACK_ID	VARCHAR2 (30)	The value of the feedback_id argument specified in the HFEEDBACK call.
ID	NUMBER	A number assigned to each node in the query execution tree. The root operation node has ID =1. The nodes are numbered in a top-down, left-first manner as they appear in the parse tree.
PARENT_ID	NUMBER	The ID of the execution step that operates on the output of the ID step. Graphically, this is the parent node in the query execution tree. The root operation node (ID =1) has PARENT_ID = 0.
OPERATION	VARCHAR2 (30)	Name of the internal operation performed. Refer to Table A-5 (page A-5) for possible values.
OPTIONS	VARCHAR2 (30)	Characters that describe a variation on the operation described in the OPERATION column. When an OPERATION has more than one OPTIONS associated with it, OPTIONS values are concatenated in the order of processing. See Table A-6 (page A-5) for possible values.
OBJECT_NAME	VARCHAR2 (80)	Section name, wildcard term, weight, threshold value or term to lookup in the index.
POSITION	NUMBER	The order of processing for nodes that all have the same PARENT_ID. The positions are numbered in ascending order starting at 1.
BT_FEEDBACK	CTX_FEEDBACK_TYPE (page A-5)	Stores broader feedback terms. See Table A-7 (page A-6).
PT_FEEDBACK	CTX_FEEDBACK_TYPE (page A-5)	Stores related feedback terms. See Table A-7 (page A-6).
NT_FEEDBACK	CTX_FEEDBACK_TYPE (page A-5)	Stores narrower feedback terms. See Table A-7 (page A-6).

A.1.2.2 HFEEDBACK Table Operation Column Values

[Table A-5](#) (page A-5) shows the possible values for the OPERATION column of the HFEEDBACK table.

Table A-5 HFEEDBACK Results Table OPERATION Column

Operation Value	Query Operator	Equivalent Symbol
ABOUT	ABOUT	(none)
ACCUMULATE	ACCUM	,
AND	AND	&
EQUIVALENCE	EQUIV	=
MINUS	MINUS	-
NEAR	NEAR	;
NOT	NOT	~
OR	OR	
SECTION	(section)	
TEXT	word or phrase of a text query	
THEME	word or phrase of an ABOUT query	
THRESHOLD	>	>
WEIGHT	*	*
WITHIN	within	(none)

A.1.2.3 HFEEDBACK Table OPTIONS Column Values

[Table A-6](#) (page A-5) list the values for the OPTIONS column of the HFEEDBACK table.

Table A-6 HFEEDBACK Results Table OPTIONS Column

Options Value	Description
(T)	Order for ordered Near.
(F)	Order for unordered Near.
(n)	A number associated with the max_span parameter for the Near operator.

A.1.2.4 CTX_FEEDBACK_TYPE

The CTX_FEEDBACK_TYPE is a nested table of objects. This datatype is predefined in the CTXSYS schema. Use this type to define the columns BT_FEEDBACK, RT_FEEDBACK, and NT_FEEDBACK.

The nested table CTX_FEEDBACK_TYPE holds objects of type CTX_FEEDBACK_ITEM_TYPE, which is also predefined in the CTXSYS schema. This object is defined with three members and one method as follows:

Table A-7 CTX_FEEDBACK_ITEM_TYPE

CTX_FEEDBACK_ITEM_TYPE Members and Methods	Type	Description
text	NUMBER	Feedback term.
cardinality	NUMBER	(reserved for future use.)
score	NUMBER	(reserved for future use.)

The SQL code that defines these objects is as follows:

```
CREATE OR REPLACE TYPE ctx_feedback_type AS TABLE OF ctx_feedback_item_type;
```

```
CREATE OR REPLACE TYPE ctx_feedback_item_type AS OBJECT
(text          VARCHAR2(80),
 cardinality NUMBER,
 score         NUMBER,
 MAP MEMBER FUNCTION rank RETURN REAL,
 PRAGMA RESTRICT_REFERENCES (rank, RNDS, WNDS, RNPS, WNPS)
);
```

```
CREATE OR REPLACE TYPE BODY ctx_feedback_item_type AS
  MAP MEMBER FUNCTION rank RETURN REAL IS
  BEGIN
    RETURN score;
  END rank;
END;
```

See Also:

For an example of how to select from the HFEEDBACK table and its nested tables, refer to CTX_QUERY.[HFEEDBACK](#) (page 12-7) in [CTX_QUERY Package](#) (page 12-1)

A.2 CTX_DOC Result Tables

The CTX_DOC procedures return results stored in a table. Before calling a procedure, you must create the table. The tables can be named anything, but must include columns with specific names and data types.

This section describes the following result tables and their required columns:

- [Filter Table](#) (page A-7)
- [Gist Table](#) (page A-7)
- [Highlight Table](#) (page A-7)
- [Markup Table](#) (page A-8)
- [Theme Table](#) (page A-8)

A.2.1 Filter Table

A filter table stores one row for each filtered document returned by CTX_DOC.FILTER (page 9-2). Filtered documents can be plain text or HTML.

When you call CTX_DOC.FILTER for a document, the document is processed through the filter defined for the text column and the results are stored in the filter table you specify.

Filter tables can be named anything, but must include the following columns, with names and datatypes as specified:

Table A-8 FILTER Result Table

Column Name	Type	Description
QUERY_ID	NUMBER	The identifier for the results generated by a particular call to CTX_DOC.FILTER (only populated when table is used to store results from multiple FILTER calls)
DOCUMENT	CLOB	Text of the document, stored in plain text or HTML.

A.2.2 Gist Table

A Gist table stores one row for each Gist/theme summary generated by CTX_DOC.GIST.

Gist tables can be named anything, but must include the following columns, with names and data types as specified:

Table A-9 Gist Table

Column Name	Type	Description
QUERY_ID	NUMBER	Query ID.
POV	VARCHAR2(80)	Document theme. Case depends of how themes were used in document or represented in the knowledge base. POV has the value of GENERIC for the document GIST.
GIST	CLOB	Text of Gist or theme summary, stored as plain text

A.2.3 Highlight Table

A highlight table stores offset and length information for highlighted terms in a document. This information is generated by CTX_DOC.HIGHLIGHT (page 9-9). Highlighted terms can be the words or phrases that satisfy a word or an ABOUT query.

If a document is formatted, the text is filtered into either plain text or HTML and the offset information is generated for the filtered text. The offset information can be used to highlight query terms for the same document filtered with CTX_DOC.FILTER (page 9-2).

Highlight tables can be named anything, but must include the following columns, with names and datatypes as specified:

Table A-10 Highlight Table

Column Name	Type	Description
QUERY_ID	NUMBER	The identifier for the results generated by a particular call to CTX_DOC.HIGHLIGHT (page 9-9) (only populated when table is used to store results from multiple HIGHLIGHT calls)
OFFSET	NUMBER	The position of the highlight in the document, relative to the start of document which has a position of 1.
LENGTH	NUMBER	The length of the highlight.

A.2.4 Markup Table

A markup table stores documents in plain text or HTML format with the query terms in the documents highlighted by markup tags. This information is generated when you call CTX_DOC.MARKUP (page 9-13).

Markup tables can be named anything, but must include the following columns, with names and datatypes as specified:

Table A-11 Markup Table

Column Name	Type	Description
QUERY_ID	NUMBER	The identifier for the results generated by a particular call to CTX_DOC.MARKUP (only populated when table is used to store results from multiple MARKUP calls)
DOCUMENT	CLOB	Marked-up text of the document, stored in plain text or HTML format

A.2.5 Theme Table

A theme table stores one row for each theme generated by CTX_DOC.THEMES (page 9-44). The value stored in the THEME column is either a single theme phrase or a string of parent themes, separated by colons.

Theme tables can be named anything, but must include the following columns, with names and data types as specified:

Table A-12 Theme Table

Column Name	Type	Description
QUERY_ID	NUMBER	Query ID
THEME	VARCHAR2 (2000)	Theme phrase or string of parent themes separated by colons (:).
WEIGHT	NUMBER	Weight of theme phrase relative to other theme phrases for the document.

A.2.6 Token Table

A token table stores the text tokens for a document as output by the CTX_DOC.TOKENS procedure. Token tables can be named anything, but must include the following columns, with names and data types as specified.

Table A-13 Token Table

Column Name	Type	Description
QUERY_ID	NUMBER	The identifier for the results generated by a particular call to CTX_DOC.HIGHLIGHT (page 9-9) (only populated when table is used to store results from multiple HIGHLIGHT calls)
TOKEN	VARCHAR2 (64)	The token string in the text.
OFFSET	NUMBER	The position of the token in the document, relative to the start of document which has a position of 1.
LENGTH	NUMBER	The character length of the token.

A.3 CTX_THES Result Tables and Data Types

The CTX_THES expansion functions such as BT, NT, and SYN can return the expansions in a table of type EXP_TAB. Specify the name of your table with the restab argument.

- [EXP_TAB Table Type](#) (page A-9)

A.3.1 EXP_TAB Table Type

The EXP_TAB table type is a table of rows of type EXP_REC.

The EXP_REC and EXP_TAB types are defined as follows in the CTXSYS schema:

```
type exp_rec is record (
    xrel varchar2(12),
    xlevel number,
    xphrase varchar2(256)
);
```

```
type exp_tab is table of exp_rec index by binary_integer;
```

When you call a thesaurus expansion function and specify *restab*, the system returns the expansion as an EXP_TAB table. Each row in this table is of type EXP_REC and represents a word or phrase in the expansion. [Table A-14](#) (page A-9) describes the fields in EXP_REC:

Table A-14 EXP_TAB Table Type (EXP_REC)

EXP_REC Field	Description
xrel	The xrel field contains the relation of the term to the input term (for example, 'SYN', 'PT', 'RT', and so on). The xrel value is PHRASE when the input term appears in the expansion. For translations, the xrel value is the language.

Table A-14 (Cont.) EXP_TAB Table Type (EXP_REC)

EXP_REC Field	Description
xlevel	<p>The xlevel field is the level of the relation. This is used mainly when xrel is a hierarchical relation (BT*/NT*).</p> <p>The xlevel field is 0 when xrel is PHRASE.</p> <p>The xlevel field is 2 for translations of synonyms under TRSYN.</p> <p>The xlevel field is 1 for operators that are not hierarchical, such as PT and RT.</p>
xphrase	<p>The xphrase is the related term. This includes a qualifier in parentheses, if one exists for the related term. Compound terms are not de-compounded.</p>

Oracle Text Supported Document Formats

Oracle Text uses the HTML export technology of Oracle Outside In for automatic filtering. This appendix provides tables with the document and graphic file formats supported by the automatic `AUTO_FILTER` filtering technology for this release.

This appendix contains the following topics:

- [About Document Filtering Technology](#) (page B-1)
- [Supported Document Formats](#) (page B-4)

See Also:

["AUTO_FILTER](#) (page 2-19)" for information on using `AUTO_FILTER`

B.1 About Document Filtering Technology

The automatic filtering technology in Oracle Text enables you to convert documents to HTML for document presentation with the `CTX_DOC` package.

To use automatic filtering for indexing and DML processing, you must specify the `AUTO_FILTER` object in your filter preference.

To use automatic filtering technology for converting documents to HTML with the `CTX_DOC` package, you need not use the `AUTO_FILTER` indexing preference.

This section contains these topics:

- [Latest Updates for Patch Releases](#) (page B-1)
- [Restrictions on Format Support](#) (page B-2)
- [Supported Platforms for AUTO_FILTER Document Filtering Technology](#) (page B-2)
- [Filtering on PDF Documents and Security Settings](#) (page B-3)
- [PDF Filtering Limitations](#) (page B-4)
- [Environment Variables](#) (page B-4)
- [General Limitations](#) (page B-4)

B.1.1 Latest Updates for Patch Releases

The supported platforms and formats listed in this appendix apply for this release. These supported formats are updated for patch releases.

B.1.2 Restrictions on Format Support

The formats listed in this appendix are those formats recognized by `AUTO_FILTER`. Recognizing a format does not necessarily mean that text can be extracted from it. For example, a scanned document is usually an image and `AUTO_FILTER` does not perform optical character recognition. Similarly, text cannot be extracted for indexing from multimedia file types.

Password-protected documents and documents with password-protected content are not supported by the `AUTO_FILTER` filter.

For other limitations, see "[Supported Document Formats](#) (page B-4)" concerning specific document types.

B.1.3 Supported Platforms for `AUTO_FILTER` Document Filtering Technology

Several platforms can take advantage of `AUTO_FILTER` filter technology. `AUTO_FILTER` filter technology is supported on the following platforms:

- Windows (x86 32-bit) Windows 2000, Windows Server 2003, Windows Server 2008, Windows XP, and Windows Vista Enterprise
- Windows (x86 64-bit) Windows Server 2003 and Windows Server 2008 x64 Standard, Enterprise, and Datacenter Editions (64-bit Extended Systems)
- HP-UX (PA-RISC 64-bit) 11.i
- HP/UX (Itanium 64) 11i
- IBM AIX (32-bit pSeries) 5.1 - 5.3
- iSeries (OS/400 using PASE) V5R2
- Red Hat Linux (x86) Advanced Server 3, 4, and 5
- Red Hat Linux (x86) Red Hat Enterprise Linux (RHEL) 4
- Red Hat Linux (Itanium 64) Advanced Server 3, 4, and 5
- Red Hat Linux (zSeries, 31-bit) Advanced Server 3 and 4
- Red Hat Enterprise Linux AS/ES 3.0, 4.0 and 5.0, x86-64 (AMD64/EM64T) Oracle Linux 4.0 and 5.0, x86-64 (AMD64/EM64T)
- SuSE Linux (x86) 9, 10, and Enterprise Server 9.0
- SuSE Linux (x86 64-bit) SUSE Enterprise Server (SLES) 9, 10
- SuSE Linux (Itanium 64) Enterprise Server 8
- SuSE Linux (zSeries, 31-bit) 9
- Sun Solaris (SPARC 64-bit) 9.x - 10.x
- Sun Solaris (x86-64-bit) 10x

Note that some of these platforms may not be supported by the Oracle Database.

B.1.4 Filtering on PDF Documents and Security Settings

A PDF document can have different levels of security settings as follows:

Table B-1 *AUTO_FILTER Behavior with PDF Security Settings*

Security Level	Description	PDF Version	Encryption	AUTO_FILTER Support Level
Level 1	Requires a password for opening the document.	1.2+	40 bit RC4	Not supported.
Level 1	Requires a password for opening the document.	1.4+	128 bit RC4	Not supported.
Level 1	Requires a password for opening the document.	1.5+	128 bit RC4	Not supported.
Level 1	Requires a password for opening the document.	1.6+	128 bit AES	Not supported.
Level 1	Requires a password for opening the document.	1.7+	256 bit AES	Not supported.
Level 2	Disallows user printing of the document.	1.2+	40 bit RC4	Supported.
Level 2	Disallows user printing of the document.	1.4+	128 bit RC4	Supported.
Level 2	Disallows user printing of the document.	1.5+	128 bit RC4	Supported.
Level 2	Disallows user printing of the document.	1.6+	128 bit AES	Not supported.
Level 2	Disallows user printing of the document.	1.7+	256 bit AES	Not supported.
Level 3	Disallows user modification or change of the document.	1.2+	40 bit RC4	Supported.
Level 3	Disallows user modification or change of the document.	1.4+	128 bit RC4	Supported.
Level 3	Disallows user modification or change of the document.	1.5+	128 bit RC4	Supported.
Level 3	Disallows user modification or change of the document.	1.6+	128 bit RC4	Not supported.
Level 3	Disallows user modification or change of the document.	1.7+	256 bit AES	Not supported.
Level 4	Disallows the user from copying or extracting content from the document.	1.2+	40 bit RC4	Supported.

Table B-1 (Cont.) AUTO_FILTER Behavior with PDF Security Settings

Security Level	Description	PDF Version	Encryption	AUTO_FILTER Support Level
Level 4	Disallows the user from copying or extracting content from the document.	1.4+	128 bit RC4	Supported.
Level 4	Disallows the user from copying or extracting content from the document.	1.5+	128 bit RC4	Supported.
Level 4	Disallows the user from copying or extracting content from the document.	1.6+	128 bit AES	Not supported.
Level 4	Disallows the user from copying or extracting content from the document.	1.7+	256 bit AES	Not supported.

B.1.5 PDF Filtering Limitations

The following limitations apply when filtering PDF files:

- Multi-byte PDFs are supported, provided the PDF document is created using Character ID-keyed (CID) fonts, predefined CJK CMap files, or ToUnicode font encodings, and the document does not contain embedded fonts.
- Embedded fonts in a PDF document are not filtered correctly. They are usually displayed using the question mark (?) replacement character.
- Hyperlinks in a PDF are not active when displayed in a browser or a viewing window.
- Annotations, such as notes, sound, or movies, are not supported.

B.1.6 Environment Variables

No environment variables need to be set by the user.

B.1.7 General Limitations

AUTO_FILTER filter technology has the following limitations:

- Any ASCII characters less than 0x20 (decimal 32) are converted to hexadecimal numbers.
- Files larger than 2GB are not handled.

B.2 Supported Document Formats

Document filtering is used for indexing, DML, and for converting documents to HTML with the CTX_DOC package. The tables in this section list the document formats that Oracle Text supports for filtering.

This section contains the following topics:

- [Archive File Format](#) (page B-5)
- [Database Formats](#) (page B-6)
- [Email Formats](#) (page B-7)
- [Graphic Formats \(Raster and Vector Image\)](#) (page B-8)
- [Multimedia Formats](#) (page B-11)
- [Other Formats](#) (page B-12)
- [Presentation Formats](#) (page B-13)
- [Spreadsheet Formats](#) (page B-14)
- [Text and Markup Formats](#) (page B-15)
- [Word Processing and Desktop Publishing Formats](#) (page B-15)

Note:

These lists do not represent the complete list of formats that Oracle Text is able to process. The `USER_FILTER` and `PROCEDURE_FILTER` enable Oracle Text to process *any* document format, provided an external filter exists that can filter to some textual format like plain-text, HTML, XML, and so forth.

B.2.1 Archive File Format

When filtering an archive file, all the contents of the files inside the archive will be exported to a single output file. This will also include the contents of all subfolders and files inside the archive file.

[Table B-2](#) (page B-5) lists the archive formats that Oracle Text supports.

Table B-2 Supported Archive File Formats

Archive Format	Version
7z (BZIP2 and split archives not supported)	
7z Self Extracting .exe (BZIP2 and split archives not supported)	
LZA Self Extracting Compress	
LZH Compress	
Microsoft Office Binder	95 – 97
Microsoft Cabinet (CAB)	
RAR	1.5, 2.0, 2.9
Self-extracting .exe	
UNIX Compress	

Table B-2 (Cont.) Supported Archive File Formats

Archive Format	Version
UNIX GZip	
UNIX Tar	
Uuencode	
Zip	PKZip
Zip	WinZip

B.2.2 Database Formats

Format	Version
DataEase	4.x
dBASE	III, IV, V
First Choice DB	Through 3.0
Framework DB	3.0
Microsoft Access	1.0, 2.0
Microsoft Access Report Snapshot (File ID only)	2000 – 3000
Microsoft Works DB for DOS	1.0, 2.0
Microsoft Works DB for Macintosh	2.0
Microsoft Works DB for Windows	3.0, 4.0
Paradox for DOS	2.0 – 4.0
Paradox for Windows	1.0
Q&A Database	Through 2.0
R:BASE 5000	Through 3.1
R:BASE System V	1.0
Reflex	2.0
SmartWare II	1.02

B.2.3 Email Formats

Note:

Oracle Text does not extract text for the following file formats:

- IBM Lotus Notes NSF (File ID) 7.x, 8.x
 - IBM Lotus Notes NSF (Windows, Linux x86-32 and Oracle Solaris 32-bit only with Notes Client or Domino Server) 8.x
-
-

Format	Version
Apple Mail Message (EMLX)	2.0
Encoded mail messages	MHT
Encoded mail messages	Multi Part Alternative
Encoded mail messages	Multi Part Digest
Encoded mail messages	Multi Part Mixed
Encoded mail messages	Multi Part News Group
Encoded mail messages	Multi Part Signed
Encoded mail messages	TNEF
IBM Lotus Notes Domino XML Language DXL	8.5
MBOX Mailbox	RFC 822
Microsoft Outlook Message (MSG)	97 – 2007
Microsoft Outlook Express (EML)	MIME-encoded mail messages.
Microsoft Outlook Forms Template (OFT)	97 – 2007
Microsoft Outlook OST	97 – 2007
Microsoft Outlook PST	97 – 2007
Microsoft Outlook PST (Mac)	2001

MIME Support Notes

The following formats are supported:

- MIME formats
 - EML
 - MHT (Web Archive)
 - NWS (Newsgroup single-part and multi-part)
 - Simple Text Mail (defined in RFC 2822)

- TNEF format
- MIME encodings, including
 - base64 (defined in RFC 1521)
 - binary (defined in RFC 1521)
 - binhex (defined in RFC 1741)
 - btoa
 - quoted-printable (defined in RFC 1521)
 - utf-7 (defined in RFC 2152)
 - uue
 - xxe
 - yenc

In addition, the body of a message can be encoded in several ways. The following encodings are supported:

- HTML
- RTF
- TNEF
- Text/enriched (defined in RFC 1523)
- Text/richtext (defined in RFC1341)
- Embedded mail message (defined in RFC 822) - this is handled as a link to a new message

The attachments of a MIME message can be stored in many formats. Oracle Corporation processes all attachment types that its technology supports.

B.2.4 Graphic Formats (Raster and Vector Image)

The graphic formats that the `AUTO_FILTER` filter recognizes ensure that indexing a text column containing any of these formats produces no error. Formats are categorized as either *embedded graphics* or *standalone graphics*. Embedded graphics are inserted or referenced within a document.

This section contains the following tables for supported graphic formats:

- [Table B-3](#) (page B-9)
- [Table B-4](#) (page B-10)

Note:

The `AUTO_FILTER` filter cannot extract textual information from graphics.

Table B-3 Supported Raster Image Formats for AUTO_FILTER Filter

Format	Version
CALS Raster (GP4)	Type I
CALS Raster (GP4)	Type II
Computer Graphics Metafile	ANSI
Computer Graphics Metafile	CALS
Computer Graphics Metafile	NIST
Encapsulated PostScript (EPS)	TIFF header Only
GEM Image (Bitmap)	
Graphics Interchange Format (GIF)	
IBM Graphics Data Format (GDF)	1.0
IBM Picture Interchange Format	1.0
JBIG2	Graphic Embeddings in PDF
JFIF (JPEG not in TIFF format)	
JPEG	
JPEG 2000	JP2
Kodak Flash Pix	
Kodak Photo CD	1.0
Lotus PIC	
Lotus Snapshot	
Macintosh PICT	BMP only
Macintosh PICT2	BMP only
MacPaint	
Microsoft Windows Bitmap	
Microsoft Windows Cursor	
Microsoft Windows Icon	
OS/2 Bitmap	
OS/2 Warp Bitmap	
Paint Shop Pro (Win32 only)	5.0, 6.0
PC Paintbrush (PCX)	
PC Paintbrush DCX (multi-page PCX)	

Table B-3 (Cont.) Supported Raster Image Formats for AUTO_FILTER Filter

Format	Version
Portable Bitmap (PBM)	
Portable Graymap PGM	
Portable Network Graphics (PNG)	
Portable Pixmap (PPM)	
Progressive JPEG	
StarOffice Draw	6.x – 9.0
Sun Raster	
TIFF	Group 5 & 6
TIFF CCITT	Group 3 & 4
TruVision TGA (Targa)	2.0
Word Perfect Graphics	1.0
WBMP wireless graphics format	
X-Windows Bitmap	x10 compatible
X-Windows Dump	x10 compatible
X-Windows Pixmap	x10 compatible
WordPerfect Graphi	2.0 – 10.0

Table B-4 Supported Vector Image Formats for AUTO_FILTER Filter

Graphics Format	Version
Adobe Illustrator	4.0 – 7.0, 9.0
Adobe Illustrator (XMP only)	11 – 13 (CS 1 – 3)
Adobe InDesign (XMP only)	3.0 – 5.0 (CS 1 - 3)
Adobe InDesign Interchange (XMP only)	
Adobe Photoshop (XMP only)	8.0 – 10.0 (CS 1 – 3)
Adobe PDF	1.0 – 1.7 (Acrobat 1 – 9)
Adobe PDF Package	1.7 (Acrobat 8 – 9)
Adobe PDF Portfolio	1.7 (Acrobat 8 – 9)
Adobe Photoshop	4.0
Ami Draw	SDW
AutoCAD Drawing	2.5, 2.6

Table B-4 (Cont.) Supported Vector Image Formats for AUTO_FILTER Filter

Graphics Format	Version
AutoCAD Drawing	9.0 – 14.0
AutoCAD Drawing	2000i – 2010
AutoShade Rendering	2
Corel Draw	2.0 – 9.0
Corel Draw Clipart	5.0, 7.0
Enhanced Metafile (EMF)	
Escher graphics	
FrameMaker Graphics (FMV)	3.0 – 5.0
Gem File (Vector)	
Harvard Graphics Chart DOS	2.0 – 3.0
Harvard Graphics for Windows	
Hewlett Packard Graphics Language (HPGL)	2.0
IGES Drawing	5.1 – 5.3
Micrografx Designer (DRW)	Through 3.1
Micrografx Designer (DFS)	6.0
Micrografx Draw (DRW)	Through 4.0
Microsoft XPS (Text only)	
Novell PerfectWorks Draw	2
OpenOffice Draw	1.1 – 3.0
Oracle Open Office Draw	3.x
Visio (Page Preview mode WMF/EMF)	4.0
Visio	5.0 - 2007
Visio XML VSX (File ID only)	2007
Windows Metafile (WMF)	

B.2.5 Multimedia Formats

The multimedia formats listed below are those formats recognized by AUTO_FILTER. Recognizing a format does not necessarily mean that text can be extracted from it. Also, the file name and file header information are not indexed. A scanned document is usually an image, and AUTO_FILTER does not perform optical character recognition. Similarly, text cannot be extracted for indexing from multimedia file types.

Format	Version
AVI (Metadata extraction only)	
Flash (text extraction only)	6.x, 7.x, Lite
Flash (File ID only)	9, 10
Real Media (File ID only)	
MP3 (ID3 metadata only)	
MPEG-1 Audio layer 3 V ID3 v1 (File ID only)	
MPEG-1 Audio layer 3 V ID3 v2 (File ID only)	
MPEG-1 Video V 2 (File ID only)	
MPEG-1 Video V 3 (File ID only)	
MPEG-2 Audio (File ID only)	
MPEG-4 (Metadata extraction only)	
MPEG-7 (Metadata extraction only)	
QuickTime (Metadata extraction only)	
Windows Media ASF (Metadata extraction only)	
Windows Media DVR-MS (Metadata extraction only)	
Windows Media Audio WMA (Metadata extraction only)	
Windows Media Playlist (File ID only)	
Windows Media Video WMV (Metadata extraction only)	
WAV (Metadata extraction only)	

B.2.6 Other Formats

Format	Version
AOL Messenger (File ID only)	7.3
Microsoft InfoPath (File ID only)	2007
Microsoft Live Messenger (via XML filter)	10.0
Microsoft OneNote (File ID only)	2007
Microsoft Project (table view only)	98 – 2003
Microsoft Project (table view only)	2007, 2010
Microsoft Windows Compiled Help (File ID only)	.chm
Microsoft Windows DLL	-

Format	Version
Microsoft Windows Executable	-
Microsoft Windows Explorer Command (File ID only)	.scf
Microsoft Windows Help (File ID only)	.hlp
Microsoft Windows Shortcut (File ID only)	.lnk
Trillian Text Log File (via text filter)	4.2
Trillian XML Log File (File ID only)	4.2
TrueType Font (File ID only)	ttf, ttc
vCalendar	2.1
vCard	2.1
Yahoo Messenger	6.x – 8

B.2.7 Presentation Formats

Format	Version
Harvard Graphics Presentation DOS	3.0
IBM Lotus Symphony Presentations	1.x
Kingsoft WPS Presentation	2010
Lotus Freelance	1.0 – Millennium 9.6
Lotus Freelance for OS/3	2
Lotus Freelance for Windows	95, 97
Microsoft PowerPoint for Macintosh	4.0 – 2008
Microsoft PowerPoint for Windows	3.0 – 2010
Microsoft PowerPoint for Windows Slideshow	2007 – 2010
Microsoft PowerPoint for Windows Template	2007 – 2010
Novell Presentations	3.0, 7.0
OpenOffice Impress	1.1, 3.0
Oracle Open Office Impress	3.x
StarOffice Impress	5.2 – 9.0
WordPerfect Presentations	5.1 – X4

B.2.8 Spreadsheet Formats

Format	Version
Enable Spreadsheet	3.0 – 4.5
First Choice SS	Through 3.0
Framework SS	3.0
IBM Lotus Symphony Spreadsheets	1.x
Kingsoft WPS Spreadsheets	2010
Lotus 1-2-3	Through Millennium 9.6
Lotus 1-2-3 Charts for DOS and Windows	Through 5.0
Lotus 1-2-3 for OS/2	Through 2.0
Microsoft Excel Charts	2.x – 2007
Microsoft Excel for Macintosh	98 – 2008
Microsoft Excel for Windows	3.0 – 2010
Microsoft Excel for Windows (text only via XML filter)	2003 XML
Microsoft Excel for Windows (.xlsb)	2007 – 2010 (Binary)
Microsoft Works SS for DOS	2.0
Microsoft Works SS for Macintosh	2.0
Microsoft Works SS for Windows	3.0, 4.0
Multiplan	4.0
Novell PerfectWorks Spreadsheet	2.0
OpenOffice Calc	1.1 – 3.0
Oracle Open Office Calc	3.x
PFS: Plan	1.0
Quattro Pro for DOS	Through 5.0
Quattro Pro for Windows	Through X4
SmartWare Spreadsheet	
SmartWare II SS	1.02
StarOffice Calc	5.2 – 9.0
SuperCalc	5.0
VP-Planner	1.0

B.2.9 Text and Markup Formats

Format	Version
ANSI Text	7 and 8 bit
ASCII Text	7 and 8 bit
DOS character set	
EBCDIC	
HTML (CSS rendering not supported)	1.0 – 4.0
IBM DCA/RFT	
Macintosh character set	
Rich Text Format (RTF)	
Unicode Text	
UTF-8	
Wireless Markup Language	
XML (text only)	
XHTML (file ID only)	1.0

B.2.10 Word Processing and Desktop Publishing Formats

Format	Version
Adobe FrameMaker (MIF only)	3.0 – 6.0
Adobe Illustrator Postscript	Level 2
Ami	
Ami Pro for OS2	
Ami Pro for Windows	2.0, 3.0
DEC DX	Through 4.0
DEC DX Plus	4.0, 4.1
Enable Word Processor	3.0 – 4.5
First Choice WP	1.0, 3.0
Framework WP	3.0
Hangul	97 – 2007
IBM DCA/FFT	

Format	Version
IBM DisplayWrite	2.0 – 5.0
IBM Writing Assistant	1.01
Ichitaro	5.0, 6.0, 8.0 – 13.0, 2004, 2010
JustWrite	Through 3.0
Kingsoft WPS Writer	2010
Legacy	1.1
Lotus Manuscript	Through 2.0
Lotus WordPro	9.7, 96 – Millennium 9.6
Lotus Word Pro (non Win32)	97 – Millennium 9.6
MacWrite II	1.1
Mass 11	Through 8.0
Microsoft Publisher (File ID only)	2003 – 2007
Microsoft Word for DOS	4.0 – 6.0
Microsoft Word for Macintosh	4.0 – 6.0, 98 – 2008
Microsoft Word for Windows	1.0 – 2010
Microsoft Word for Windows (text only via XML filter)	2003 XML
Microsoft Word for Windows	98-J
Microsoft WordPad	
Microsoft Works WP for DOS	2.0
Microsoft Works WP for Macintosh	2.0
Microsoft Works WP for Windows	3.0, 4.0
Microsoft Write for Windows	1.0 – 3.0
MultiMate	Through 4.0
MultiMate Advantage	2.0
Navy DIF	
Nota Bene	3.0
Novell PerfectWorks Word Processor	2.0
OfficeWriter	4.0 – 6.0
OpenOffice Writer	1.1 – 3.0
Oracle Open Office Writer	3.x

Format	Version
PC File Doc	5.0
PFS: Write	A, B
Professional Write for DOS	1.0, 2.0
Professional Write Plus for Windows	1.0
Q&A Write	2.0, 3.0
Samna Word IV	1.0 – 3.0
Samna Word IV+	
Samsung JungUm Global (File ID only)	
Signature	1.0
SmartWare II WP	1.02
Sprint	1.0
StarOffice Writer	5.2 – 9.0
Total Word	1.2
Wang IWP	Through 2.6
WordMarc Composer	
WordMarc Composer+	
WordMarc Word Processor	
WordPerfect for DOS	4.2
WordPerfect for Macintosh	1.02 – 3.1
WordPerfect for Windows	5.1 – X4
WordStar 2000 for DOS	1.0 – 3.0
Wordstar for DOS	3.0 – 7.0
Wordstar for Windows	1.0
XyWrite	Through III+

Text Loading Examples for Oracle Text

This appendix provides examples of how to load text into a text column, and the structure of ctxload import files. This appendix contains these topics:

- [SQL INSERT Example](#) (page C-1)
- [SQL*Loader Example](#) (page C-1)
- [Structure of ctxload Thesaurus Import File](#) (page C-3)

C.1 SQL INSERT Example

A simple way to populate a text table is to create a table with two columns, `id` and `text`, using `CREATE TABLE` and then use the `INSERT` statement to load the data. This example makes the `id` column the primary key, which is optional. The `text` column is `VARCHAR2`:

```
create table docs (id number primary key, text varchar2(80));
```

To populate the `text` column, use the `INSERT` statement as follows:

```
insert into docs values(1, 'this is the text of the first document');
insert into docs values(12, 'this is the text of the second document');
```

C.2 SQL*Loader Example

The following example shows how to use SQL*Loader to load mixed format documents from the operating system to a BLOB column. The example has two steps:

- [Creating the Table](#) (page C-1)
- [Issuing the SQL*Loader Command](#) (page C-2)

The SQL*Loader command reads the control file and loads data into table

See Also:

For a complete discussion on using SQL*Loader, see *Oracle Database Utilities*

C.2.1 Creating the Table

This example loads a table `articles_formatted` created as follows:

```
CREATE TABLE articles_formatted (
  ARTICLE_ID  NUMBER PRIMARY KEY ,
  AUTHOR      VARCHAR2(30),
  FORMAT      VARCHAR2(30),
  PUB_DATE    DATE,
```

```
TITLE          VARCHAR2(256),
TEXT           BLOB
);
```

The `article_id` column is the primary key. Documents are loaded in the `text` column, which is of type `BLOB`.

C.2.2 Issuing the SQL*Loader Command

The following command starts the loader, which reads the control file `LOADER1.DAT`:

```
sqlldr userid=demo/password control=loader1.dat log=loader.log
```

- [Example Control File: loader1.dat](#) (page C-2)
- [Example Data File: loader2.dat](#) (page C-2)

C.2.2.1 Example Control File: loader1.dat

This SQL*Loader control file defines the columns to be loaded and instructs the loader to load the data line by line from `loader2.dat` into the `articles_formatted` table. Each line in `loader2.dat` holds a comma-delimited list of fields to be loaded.

```
-- load file example
load data
infile 'loader2.dat'
into table articles_formatted
append
fields terminated by ','
(article_id SEQUENCE (MAX,1),
author CHAR(30),
format,
pub_date SYSDATE,
title,
ext_fname FILLER CHAR(80),
text LOBFILE(ext_fname) TERMINATED BY EOF)
```

This control file instructs the loader to load data from `loader2.dat` to the `articles_formatted` table in the following way:

1. The ordinal position of the line describing the document fields in `loader2.dat` is written to the `article_id` column.
2. The first field on the line is written to `author` column.
3. The second field on the line is written to the `format` column.
4. The current date given by `SYSDATE` is written to the `pub_date` column.
5. The title of the document, which is the third field on the line, is written to the `title` column.
6. The name of each document to be loaded is read into the `ext_fname` temporary variable, and the actual document is loaded in the `text` `BLOB` column:

C.2.2.2 Example Data File: loader2.dat

This file contains the data to be loaded into each row of the table, `articles_formatted`.

Each line contains a comma-delimited list of the fields to be loaded in `articles_formatted`. The last field of every line names the file to be loaded in to the text column:

```
Ben Kanobi, plaintext,Kawasaki news article,..../sample_docs/kawasaki.txt,
Joe Bloggs, plaintext,Java plug-in,..../sample_docs/javaplugin.txt,
John Hancock, plaintext,Declaration of Independence,..../sample_docs/indep.txt,
M. S. Developer, Word7,Newsletter example,..../sample_docs/newsletter.doc,
M. S. Developer, Word7,Resume example,..../sample_docs/resume.doc,
X. L. Developer, Excel7,Common example,..../sample_docs/common.xls,
X. L. Developer, Excel7,Complex example,..../sample_docs/solvsamp.xls,
Pow R. Point, Powerpoint7,Generic presentation,..../sample_docs/generic.ppt,
Pow R. Point, Powerpoint7,Meeting presentation,..../sample_docs/meeting.ppt,
Java Man, PDF,Java Beans paper,..../sample_docs/j_bean.pdf,
Java Man, PDF,Java on the server paper,..../sample_docs/j_svr.pdf,
Ora Webmaster, HTML,Oracle home page,..../sample_docs/oramnu97.html,
Ora Webmaster, HTML,Oracle Company Overview,..../sample_docs/oraoverview.html,
John Constable, GIF,Laurence J. Ellison : portrait,..../sample_docs/larry.gif,
Alan Greenspan, GIF,Oracle revenues : Graph,..../sample_docs/oragraph97.gif,
Giorgio Armani, GIF,Oracle Revenues : Trend,..../sample_docs/oratrend.gif,
```

C.3 Structure of ctxload Thesaurus Import File

This section discusses the structure of the ctxload thesaurus import file in the following topics.

- [Import File Format](#) (page C-3)
- [Alternate Hierarchy Structure](#) (page C-6)
- [Usage Notes for Terms in Import Files](#) (page C-6)
- [Usage Notes for Relationships in Import Files](#) (page C-7)
- [Examples of Import Files](#) (page C-7)

C.3.1 Import File Format

The import file must use the following format for entries in the thesaurus:

```
phrase
  BT broader_term
  NT narrower_term1
  NT narrower_term2
  . . .
  NT narrower_termN

BTG broader_term
NTG narrower_term1
NTG narrower_term2
. . .
NTG narrower_termN

BTP broader_term
NTP narrower_term1
NTP narrower_term2
. . .
NTP narrower_termN

BTI broader_term
NTI narrower_term1
```

```
NTI narrower_term2
. . .
NTI narrower_termN

SYN synonym1
SYN synonym2
. . .
SYN synonymN

USE synonym1 or SEE synonym1 or PT synonym1

RT related_term1
RT related_term2
. . .
RT related_termN

SN text

language_key: term
```

phrase

is a word or phrase that is defined as having synonyms, broader terms, narrower terms, or related terms.

In compliance with ISO-2788 standards, a TT marker can be placed before a phrase to indicate that the phrase is the top term in a hierarchy; however, the TT marker is not required. In fact, ctxload ignores TT markers during import.

A top term is identified as any phrase that does not have a broader term (BT, BTG, BTP, or BTI).

Note:

The thesaurus query operators (SYN, PT, BT, BTG, BTP, BTI, NT, NTG, NTP, NTI, and RT) are reserved words and, thus, cannot be used as phrases in thesaurus entries.

BT, BTG, BTP, BTI broader_termN

are the markers that indicate `broadener_termN` is a broader (generic | partitive | instance) term for phrase.

`broadener_termN` is a word or phrase that conceptually provides a more general description or category for phrase. For example, the word *elephant* could have a broader term of *land mammal*.

NT, NTG, NTP, NTI narrower_termN

are the markers that indicate `narrower_termN` is a narrower (generic | partitive | instance) term for phrase.

If phrase does not have a broader (generic | partitive | instance) term, but has one or more narrower (generic | partitive | instance) terms, phrase is created as a top term in the respective hierarchy (in an Oracle Text thesaurus, the BT/NT, BTG/NTG, BTP/NTP, and BTI/NTI hierarchies are separate structures).

`narrower_termN` is a word or phrase that conceptually provides a more specific description for phrase. For example, the word *elephant* could have a narrower terms of *indian elephant* and *african elephant*.

SYN synonymN

is a marker that indicates `phrase` and `synonymN` are synonyms within a synonym ring.

`synonymN` is a word or phrase that has the same meaning for `phrase`. For example, the word *dog* could have a synonym of *canine*.

Note:

Synonym rings are not defined explicitly in Oracle Text thesauri. They are created by the transitive nature of synonyms.

USE SEE PT synonym1

are markers that indicate `phrase` and `synonym1` are synonyms within a synonym ring (similar to SYN).

The markers USE, SEE or PT also indicate `synonym1` is the preferred term for the synonym ring. Any of these markers can be used to define the preferred term for a synonym ring.

Note:

If the user-defined thesaurus is to be used for compiling the knowledge base, then you must specify the preferred term when a synonym ring is declared. Use one of the keywords USE, SEE, or PT to specify which synonym to use when reporting query matches. Only one term can be a preferred term.

Not using one of these keywords may result in the failure to return results defined by a word's synonym. When compiling two or more thesauri that declare elements of the same synonym ring, the preferred term must be the same in both files, which ensures that only one word is defined as the preferred word in a synonym ring.

RT related_termN

is the marker that indicates `related_termN` is a related term for `phrase`.

`related_termN` is a word or phrase that has a meaning related to, but not necessarily synonymous with `phrase`. For example, the word *dog* could have a related term of *wolf*.

Note:

Related terms are not transitive. If a phrase has two or more related terms, the terms are related only to the parent phrase and not to each other.

SN text

is the marker that indicates the following text is a scope note (for example, comment) for the preceding entry.

language_key term

`term` is the translation of `phrase` into the language specified by `language_key`.

C.3.2 Alternate Hierarchy Structure

In compliance with thesauri standards, the load file supports formatting hierarchies (BT/NT, BTG/NTG, BTP, NTP, BTI/NTI) by indenting the terms under the top term and using NT (or NTG, NTP, NTI) markers that include the level for the term:

```
phrase
  NT1 narrower_term1
    NT2 narrower_term1.1
    NT2 narrower_term1.2
      NT3 narrower_term1.2.1
      NT3 narrower_term1.2.2
  NT1 narrower_term2
  . . .
  NT1 narrower_termN
```

Using this method, the entire branch for a top term can be represented hierarchically in the load file.

C.3.3 Usage Notes for Terms in Import Files

The following conditions apply to the structure of the entries in the import file:

- Each entry (*phrase*, *BT*, *NT*, or *SYN*) must be on a single line followed by a newline character.
- Entries can consist of a single word or phrases.
- The maximum length of an entry (*phrase*, *BT*, *NT*, or *SYN*) is 255 bytes, not including the *BT*, *NT*, and *SYN* markers or the newline characters.
- Entries cannot contain parentheses or plus signs.
- Each line of the file that starts with a relationship (*BT*, *NT*, and so on) must begin with at least one space.
- A *phrase* can occur more than once in the file.
- Each *phrase* can have one or more narrower term entries (*NT*, *NTG*, *NTP*), broader term entries (*BT*, *BTG*, *BTP*), synonym entries, and related term entries.
- Each broader term, narrower term, synonym, and preferred term entry must start with the appropriate marker and the markers must be in capital letters.
- The broader terms, narrower terms, and synonyms for a *phrase* can be in any order.
- Homographs must be followed by parenthetical disambiguators everywhere they are used.

For example: *cranes (birds)*, *cranes (lifting equipment)*

- Compound terms are signified by a plus sign between each factor (for example, *buildings + construction*).
- Compound terms are allowed only as synonyms or preferred terms for other terms, never as terms by themselves, or in hierarchical relations.

- Terms can be followed by a scope note (SN), total maximum length of 2000 bytes, on subsequent lines.
- Multi-line scope notes are allowed, but require an SN marker on each line of the note.

Example of Incorrect SN usage:

```
VIEW CAMERAS
  SN Cameras with through-the lens focusing and a
  range of movements of the lens plane relative to
  the film plane
```

Example of Correct SN usage:

```
VIEW CAMERAS
  SN Cameras with through-the lens focusing and a
  SN range of movements of the lens plane relative
  SN to the film plane
```

- Multi-word terms cannot start with reserved words (for example, *use* is a reserved word, so *use other door* is not an allowed term; however, *use* is an allowed term).

C.3.4 Usage Notes for Relationships in Import Files

The following conditions apply to the relationships defined for the entries in the import file:

- related term entries must follow a phrase or another related term entry
- related term entries start with one or more spaces, the RT marker, followed by white space, then the related term on the same line
- multiple related terms require multiple RT markers

Example of incorrect RT usage:

```
MOVING PICTURE CAMERAS
  RT CINE CAMERAS
TELEVISION CAMERAS
```

Example of correct RT usage:

```
MOVING PICTURE CAMERAS
  RT CINE CAMERAS
  RT TELEVISION CAMERAS
```

- Terms are allowed to have multiple broader terms, narrower terms, and related terms

C.3.5 Examples of Import Files

This section provides three examples of correctly formatted thesaurus import files.

- [Example 1 \(Flat Structure\)](#) (page C-8)
- [Example 2 \(Hierarchical\)](#) (page C-8)
- [Example 3](#) (page C-8)

C.3.5.1 Example 1 (Flat Structure)

```
cat
  SYN feline
  NT domestic cat
  NT wild cat
  BT mammal
mammal
  BT animal
domestic cat
  NT Persian cat
  NT Siamese cat
wild cat
  NT tiger
tiger
  NT Bengal tiger
dog
  BT mammal
  NT domestic dog
  NT wild dog
  SYN canine
domestic dog
  NT German Shepard
wild dog
  NT Dingo
```

C.3.5.2 Example 2 (Hierarchical)

```
animal
  NT1 mammal
    NT2 cat
      NT3 domestic cat
        NT4 Persian cat
        NT4 Siamese cat
      NT3 wild cat
        NT4 tiger
          NT5 Bengal tiger
    NT2 dog
      NT3 domestic dog
        NT4 German Shepard
      NT3 wild dog
        NT4 Dingo
cat
  SYN feline
dog
  SYN canine
```

C.3.5.3 Example 3

```
35MM CAMERAS
  BT MINIATURE CAMERAS
CAMERAS
  BT OPTICAL EQUIPMENT
  NT MOVING PICTURE CAMERAS
  NT STEREO CAMERAS
LAND CAMERAS
  USE VIEW CAMERAS
VIEW CAMERAS
  SN Cameras with through-the lens focusing and a range of
  SN movements of the lens plane relative to the film plane
```


UF LAND CAMERAS
BT STILL CAMERAS

Oracle Text Multilingual Features

This Appendix describes the multilingual features of Oracle Text. The following topics are discussed:

- [Introduction](#) (page D-1)
- [Indexing](#) (page D-1)
- [Querying](#) (page D-7)
- [Supplied Stop Lists](#) (page D-7)
- [Knowledge Base](#) (page D-8)
- [Multilingual Features Matrix](#) (page D-8)

D.1 Introduction

This appendix summarizes the main multilingual features for Oracle Text.

For a complete list of Oracle Globalization Support languages and character set support, refer to the *Oracle Database Globalization Support Guide*.

D.2 Indexing

The following sections describe the multilingual indexing features:

- [Multilingual Features for Text Index Types](#) (page D-1)
- [Lexer Types](#) (page D-3)
- [Basic Lexer Features](#) (page D-3)
- [Multi Lexer Features](#) (page D-5)
- [World Lexer Features](#) (page D-5)

D.2.1 Multilingual Features for Text Index Types

The following sections describes the supported multilingual features for the Oracle Text index types.

- [CONTEXT Index Type](#) (page D-2)
- [CTXCAT Index Type](#) (page D-2)
- [CTXRULE Index Type](#) (page D-2)

See Also:

["Lexer Types \(page D-3\)"](#) for a description of available lexers

D.2.1.1 CONTEXT Index Type

The `CONTEXT` index type fully supports multilingual features, including use of the language and character set columns.

The following lexers are supported:

- `AUTO_LEXER`
- `MULTI_LEXER`
- `USER_LEXER`
- `WORLD_LEXER`
- `CHINESE_LEXER`
- `CHINESE_VGRAM_LEXER`
- `JAPANESE_LEXER`
- `JAPANESE_VGRAM_LEXER`
- `KOREAN_MORPH_LEXER`

D.2.1.2 CTXCAT Index Type

`CTXCAT` supports the multilingual features of the `BASIC_LEXER` with the exception of indexing themes, and supports the following additional lexers:

- `USER_LEXER`
- `WORLD_LEXER`

`CTXCAT` also supports the following lexers:

- `CHINESE_LEXER`
- `CHINESE_VGRAM_LEXER`
- `JAPANESE_LEXER`
- `JAPANESE_VGRAM_LEXER`
- `KOREAN_MORPH_LEXER`

D.2.1.3 CTXRULE Index Type

The `CTXRULE` index type supports the multilingual features of the `BASIC_LEXER` including `ABOUT` and `STEM` operators. It also supports Japanese, Chinese, and Korean (when used with the `SVM_CLASSIFIER`).

D.2.2 Lexer Types

Oracle Text supports the indexing of different languages by enabling you to choose a lexer in the indexing process. The lexer you employ determines the languages you can index. [Table D-1](#) (page D-3) describes the supported lexers.

Table D-1 Oracle Text Lexer Types

Lexer	Supported Languages
BASIC_LEXER	English and most western European languages that use white space delimited words.
MULTI_LEXER	Lexer for indexing tables containing documents of different languages such as English, German, and Japanese.
CHINESE_VGRAM	Lexer for extracting tokens from Chinese text.
CHINESE_LEXER	<p>Lexer for extracting tokens from Chinese text. This lexer offers the following benefits over the CHINESE_VGRAM lexer:</p> <ul style="list-style-type: none"> • Generates a smaller index • Better query response time • Generates real world tokens resulting in better query precision • Supports stop words
JAPANESE_VGRAM	Lexer for extracting tokens from Japanese text.
JAPANESE_LEXER	<p>Lexer for extracting tokens from Japanese text. This lexer offers the following advantages over the JAPANESE_VGRAM lexer:</p> <ul style="list-style-type: none"> • Generates smaller index • Better query response time • Generates real world tokens resulting in better precision
KOREAN_MORPH_LEXER	Lexer for extracting tokens from Korean text.
USER_LEXER	Lexer you create to index a particular language.
WORLD_LEXER	Lexer for indexing tables containing documents of different languages; autodetects languages in a document

D.2.3 Basic Lexer Features

The following features are supported with the BASIC_LEXER preference. Enable these features with attributes of the BASIC_LEXER. Features such as alternate spelling, composite, and base letter can be enabled together for better search results.

- [Theme Indexing](#) (page D-4)
- [Alternate Spelling](#) (page D-4)
- [Base Letter Conversion](#) (page D-4)
- [Composite](#) (page D-4)
- [Index stems](#) (page D-4)

D.2.3.1 Theme Indexing

Enables the indexing and subsequent querying of document concepts with the ABOUT operator with CONTEXT index types. These concepts are derived from the Oracle Text knowledge base. This feature is supported for English and French.

This feature is not supported with CTXCAT index types.

D.2.3.2 Alternate Spelling

This feature enables you to search on alternate spellings of words. For example, with alternate spelling enabled in German, a query on *gross* returns documents that contain *groß* and *gross*.

This feature is supported in German, Danish, and Swedish.

Additionally, German can be indexed according to both traditional and reformed spelling conventions.

See Also:

["Alternate Spelling \(page 17-2\)"](#) and ["New German Spelling \(page 17-3\)"](#).

D.2.3.3 Base Letter Conversion

This feature enables you to query words with or without diacritical marks such as tildes, accents, and umlauts. For example, with a Spanish base-letter index, a query of *energia* matches documents containing both *energía* and *energia*.

This feature is supported for English and all other supported whitespace delimited languages. In English and French, you can use the basic lexer to enable theme indexing.

See Also:

["Base-Letter Conversion \(page 17-2\)"](#)

D.2.3.4 Composite

This feature enables you to search on words that contain the specified term as a sub-composite. You must use the stem (\$) operator. This feature is supported for German and Dutch.

For example, in German, a query of *\$register* finds documents that contain *Bruttoregistertonne* and *Registertonne*.

D.2.3.5 Index stems

This feature enables you to specify a stemmer for stem indexing. Tokens are stemmed to a single base form at index time in addition to the normal forms. Specifying index stems enables better query performance for stem queries, for example *\$computed*.

This feature is supported for English, Dutch, French, German, Italian, and Spanish.

D.2.4 Multi Lexer Features

The `MULTI_LEXER` lexer enables you to index a column that contains documents of different languages. During indexing Oracle Text examines the language column and switches in the language-specific lexer to process the document. Define the lexer preferences for each language before indexing.

The multi lexer enables you to set different preferences for languages. For example, you can have `composite` set to `TRUE` for German documents and `composite` set to `FALSE` for Dutch documents.

D.2.5 World Lexer Features

Like `MULTI_LEXER`, the `WORLD_LEXER` lexer enables you to index documents that contain different languages. It automatically detects the languages of a document and, therefore, does not require you to create a language column in the base table.

`WORLD_LEXER` processes all database character sets and supports the Unicode 5.0 standard. For `WORLD_LEXER` to be effective with documents that use multiple languages, AL32UTF-8 or UTF8 Oracle character set encoding must be specified. This includes supplementary, or "surrogate-pair," characters.

[Table D-2](#) (page D-5) and [Table D-3](#) (page D-6) show the languages supported by `WORLD_LEXER`. This list may change as the Unicode standard changes, and in any case should not be considered exhaustive. (Languages are grouped by Unicode writing system, not by natural language groupings.)

Table D-2 Languages Supported by the World Lexer (Space-separated)

Language Group	Languages Include
Arabic	Arabic, Farsi, Kurdish, Pashto, Sindhi, Urdu
Armenian	Armenian
Bengali	Assamese, Bengali
Bopomofo	Hakka Chinese, Minnan Chinese
Cyrillic	Over 50 languages, including Belorussian, Bulgarian, Macedonian, Moldavian, Russian, Serbian, Serbo-Croatian, Ukrainian
Devenagari	Bhojpuri, Bihari, Hindi, Kashmiri, Marathi, Nepali, Pali, Sanskrit
Ethiopic	Amharic, Ge'ez, Tigrinya, Tigre
Georgian	Georgian
Greek	Greek
Gujarati	Gujarati, Kacchi
Gurmukhi	Punjabi
Hebrew	Hebrew, Ladino, Yiddish
Kaganga	Redjang

Table D-2 (Cont.) Languages Supported by the World Lexer (Space-separated)

Language Group	Languages Include
Kannada	Kanarese, Kannada
Korean	Korean, Hanja Hangul
Latin	Afrikaans, Albanian, Basque, Breton, Catalan, Croatian, Czech, Danish, Dutch, English, Esperanto, Estonian, Faeroese, Fijian, Finnish, Flemish, French, Frisian, German, Hawaiian, Hungarian, Icelandic, Indonesian, Irish, Italian, Lappish, Classic Latin, Latvian, Lithuanian, Malay, Maltese, Pinyin Mandarin, Maori, Norwegian, Polish, Portuguese, Provencal, Romanian, Rumanian, Samoan, Scottish Gaelic, Slovak, Slovene, Slovenian, Sorbian, Spanish, Swahili, Swedish, Tagalog, Turkish, Vietnamese, Welsh
Malayalam	Malayalam
Mongolian	Mongolian
Oriya	Oriya
Sinhalese, Sinhala	Pali, Sinhalese
Syriac	Aramaic, Syriac
Tamil	Tamil
Telugu	Telugu
Thaana	Dhivehi, Divehi, Maldivian

Table D-3 Languages Supported by the World Lexer (Non-space-separated)

Language Group	Languages Include
Chinese	Cantonese, Mandarin, Pinyin phonograms
Japanese	Japanese (Hiragana, Kanji, Katakana)
Khmer	Cambodian, Khmer
Lao	Lao
Myanmar	Burmese
Thai	Thai
Tibetan	Dzongkha, Tibetan

[Table D-4](#) (page D-6) shows languages not supported by the World Lexer.

Table D-4 Languages Not Supported by the World Lexer

Language Group	Languages Include
Buhid	Buhid

Table D-4 (Cont.) Languages Not Supported by the World Lexer

Language Group	Languages Include
Canadian Syllabics	Blackfoot, Carrier, Cree, Dakhelh, Inuit, Inuktitut, Naskapi, Nunavik, Nunavut, Ojibwe, Sayisi, Slavey
Cherokee	Cherokee
Cypriot	Cypriot
Limbu	Limbu
Ogham	Ogham
Runic	Runic
Tai Le (Tai Lu, Lue, Dai Le)	Tai Le
Ugaritic	Ugaritic
Yi	Yi
Yi Jang Hexagram	Yi Jang

D.3 Querying

Oracle Text supports the use of different query operators. Some operators can be set to behave in accordance with your language. This section summarizes the multilingual query features for these operators.

- Use the ABOUT operator to query on concepts. The system looks up concept information in the theme component of the index. This feature is supported for English and French with CONTEXT indexes only.
- The fuzzy operator enables you to search for words that have similar spelling to specified word. Oracle Text supports `fuzzy` for English, French, German, Italian, Dutch, Spanish, Portuguese, Japanese, Optical Character recognition (OCR), and automatic language detection.
- The stem operator enables you to search for words that have the same root as the specified term. For example, a stem of `$sing` expands into a query on the words `sang`, `sung`, `sing`. The Oracle Text stemmer supports the following languages: English, French, Spanish, Italian, German, Japanese and Dutch.

D.4 Supplied Stop Lists

A stoplist is a list of words that do not get indexed. These are usually common words in a language such as *this*, *that*, and *can* in English.

Oracle Text provides a default stoplist for English, Chinese (traditional and simplified), Danish, Dutch, Finnish, French, German, Italian, Portuguese, Spanish, and Swedish. [Oracle Text Supplied Stoplists](#) (page E-1), lists the stoplists for various languages.

D.5 Knowledge Base

An Oracle Text knowledge base is a hierarchical tree of concepts used for theme indexing, ABOUT queries, and deriving themes for document services.

Oracle Text supplies knowledge bases in English and French only. These knowledge bases are installed by default.

You can extend theme functionality to languages other than English or French by loading your own knowledge base for any single byte white space delimited language, including Spanish.

D.6 Multilingual Features Matrix

The following table summarizes the multilingual features for the supported languages.

Table D-5 *Multilingual Features for Supported Languages*

LANGUAGE	ALTERNATE SPELLING	FUZZY MATCHING	LANGUAGE SPECIFIC LEXER	DEFAULT STOP LIST	STEMMING
ENGLISH	N/A	Yes	Yes	Yes	Yes
GERMAN	Yes	Yes	Yes	Yes	Yes
JAPANESE	N/A	Yes	Yes	No	Yes
FRENCH	N/A	Yes	Yes	Yes	Yes
SPANISH	N/A	Yes	Yes	Yes	Yes
ITALIAN	N/A	Yes	Yes	Yes	Yes
DUTCH	N/A	Yes	Yes	Yes	Yes
PORTUGUESE	N/A	Yes	Yes	Yes	Yes
KOREAN	N/A	No	Yes	No	Yes
SIMPLIFIED CHINESE	N/A	No	Yes	Yes	Yes
TRADITIONAL CHINESE	N/A	No	Yes	Yes	Yes
DANISH	Yes	No	Yes	No	Yes
SWEDISH	Yes	No	Yes	Yes	Yes
FINNISH	N/A	No	Yes	No	Yes
ARABIC	N/A	No	Yes	No	Yes
GREEK	N/A	No	Yes	No	Yes
BOKMAL	N/A	No	Yes	No	Yes
POLISH	N/A	No	Yes	No	Yes
RUSSIAN	N/A	No	Yes	No	Yes

Table D-5 (Cont.) Multilingual Features for Supported Languages

LANGUAGE	ALTERNATE SPELLING	FUZZY MATCHING	LANGUAGE SPECIFIC LEXER	DEFAULT STOP LIST	STEMMING
SLOVENIAN	N/A	No	Yes	No	Yes
THAI	N/A	No	Yes	No	Yes
CATALAN	N/A	No	Yes	No	Yes
CROATIAN	N/A	No	Yes	No	Yes
HEBREW	N/A	No	Yes	No	Yes
NYNORSK	N/A	No	Yes	No	Yes
SERBIAN	N/A	No	Yes	No	Yes
TURKISH	N/A	No	Yes	No	Yes
CZECH	N/A	No	Yes	No	Yes
HUNGARIAN	N/A	No	Yes	No	Yes
PERSIAN	N/A	No	Yes	No	Yes
SLOVAK	N/A	No	Yes	No	Yes

Oracle Text Supplied Stoplists

This appendix describes the default stoplists for all the different languages supported and lists the stopwords in each. The following stoplists are described:

- [English Default Stoplist](#) (page E-1)
- [Chinese Stoplist \(Traditional\)](#) (page E-5)
- [Chinese Stoplist \(Simplified\)](#) (page E-5)
- [Danish \(dk\) Default Stoplist](#) (page E-6)
- [Dutch \(nl\) Default Stoplist](#) (page E-8)
- [Finnish \(sf\) Default Stoplist](#) (page E-16)
- [French \(f\) Default Stoplist](#) (page E-22)
- [German \(d\) Default Stoplist](#) (page E-28)
- [Italian \(i\) Default Stoplist](#) (page E-35)
- [Portuguese \(pt\) Default Stoplist](#) (page E-40)
- [Spanish \(e\) Default Stoplist](#) (page E-42)
- [Swedish \(s\) Default Stoplist](#) (page E-47)

E.1 English Default Stoplist

The following English words are defined as stop words:

- a
- all
- almost
- also
- although
- an
- and
- any
- are
- as

- at
- be
- because
- been
- both
- but
- by
- can
- could
- d
- did
- do
- does
- either
- for
- from
- had
- has
- have
- having
- he
- her
- here
- hers
- him
- his
- how
- however
- i
- if
- in
- into

- is
- it
- its
- just
- ll
- me
- might
- Mr
- Mrs
- Ms
- my
- no
- non
- nor
- not
- of
- on
- one
- only
- onto
- or
- our
- ours
- s
- shall
- she
- should
- since
- so
- some
- still
- such

- t
- than
- that
- the
- their
- them
- then
- there
- therefore
- these
- they
- this
- those
- though
- through
- thus
- to
- too
- until
- ve
- very
- was
- we
- were
- what
- when
- where
- whether
- which
- while
- who
- whose

- why
- will
- with
- would
- yet
- you
- your
- yours

E.2 Chinese Stoplist (Traditional)

The following traditional Chinese words are defined in the default stoplist for this language.

目前	由於	因此	他們	可能	沒有	希望
有關	不過	可以	如果	對於	因為	是否
但是	相當	其中	其他	雖然	我們	包括
必須	以上	之後	所以	以及	許多	最近
至於	一般	不是	不能	而且	引起	如何
除了	不少	最後	就是	分別	加強	甚至
繼續	另外	共同	只有	了解	根據	已經
過去	所有	不會	以來	任何	一直	不同
立即	左右	經過	尤其	使得	相關	當時
進入	並不	據了解	現在	只是	需要	原因
只要	否則	並未	什麼	如此	不要	

E.3 Chinese Stoplist (Simplified)

The following simplified Chinese words are defined in the default stoplist for this language.

必将	必须	并非	由于	一同	一再	一得
超过	成为	除了	处在	此项	从而	存在着
达到	大量	带来	带着	但是	当时	得到
都是	对于	这个	而且	而言	方面	各方
各种	共同	还将	还有	很少	很有	面
回到	获得了	或者	基本	基于	即可	还是
尽管	就是	具有	可能	可以	来自	较大
之一	没有	目前	哪里	那里	却是	两个
如何	什么	实在	所需	所有	它的	如果
为了	我们	下去	现在	相当	新的	他们
也是	以及	已经	以上	因此	因为	许多

E.4 Danish (dk) Default Stoplist

The following Danish words are defined in the default stoplist for this language:

- af
- aldrig
- alle
- altid
- bagved
- de
- der
- du
- efter
- eller
- en
- et
- endnu
- få
- lidt
- fjern
- for
- foran
- fra
- gennem
- god
- han
- her
- hos
- hvorfor
- hun
- hvad
- hvem
- hvor

- hvorhen
- hvordan
- I
- De
- i
- imod
- ja
- jeg
- langsom
- mange
- måske
- med
- meget
- mellem
- mere
- mindre
- når
- hvonår
- nede
- nej
- nu
- og
- oppe
- på
- rask
- hurtig
- sammen
- temmelig
- nok
- til
- uden
- udenfor

- under
- ved
- vi

E.5 Dutch (nl) Default Stoplist

The following Dutch words are defined in the default stoplist for this language:

- aan
- aangaande
- aangezien
- achter
- achterna
- afgelopen
- al
- aldaar
- aldus
- alhoewel
- alias
- alle
- allebei
- alleen
- alsnog
- altijd
- altoos
- ander
- andere
- anders
- anderszins
- behalve
- behoudens
- beide
- beiden
- ben

- beneden
- bent
- bepaald
- betreffende
- bij
- binnen
- binnenin
- boven
- bovenal
- bovendien
- bovengenoemd
- bovenstaand
- bovenvermeld
- buiten
- daar
- daarheen
- daarin
- daarna
- daarnet
- daarom
- daarop
- daarvanlangs
- dan
- dat
- de
- die
- dikwijls
- dit
- door
- doorgaand
- dus
- echter

- eer
- eerdat
- eerder
- eerlang
- eerst
- elk
- elke
- en
- enig
- enigszins
- enkel
- er
- erdoor
- even
- eveneens
- evenwel
- gauw
- gedurende
- geen
- gehad
- gekund
- geleden
- gelijk
- gemoeten
- gemogen
- geweest
- gewoon
- gewoonweg
- haar
- had
- hadden
- hare

- heb
- hebben
- hebt
- heeft
- hem
- hen
- het
- hierbeneden
- hierboven
- hij
- hoe
- hoewel
- hun
- hunne
- ik
- ikzelf
- in
- inmiddels
- inzake
- is
- jezelf
- jij
- jijzelf
- jou
- jouw
- jouwe
- juist
- jullie
- kan
- klaar
- kon
- konden

- krachtens
- kunnen
- kunt
- later
- liever
- maar
- mag
- meer
- met
- mezelf
- mij
- mijn
- mijnent
- mijner
- mijzelf
- misschien
- mocht
- mochten
- moest
- moesten
- moet
- moeten
- mogen
- na
- naar
- nadat
- net
- niet
- noch
- nog
- nogal
- nu

- of
- ofschoon
- om
- omdat
- omhoog
- omlaag
- omstreeks
- omtrent
- omver
- onder
- ondertussen
- ongeveer
- ons
- onszelf
- onze
- ook
- op
- opnieuw
- opzij
- over
- overeind
- overigens
- pas
- precies
- reeds
- rond
- rondom
- sedert
- sinds
- sindsdien
- slechts
- sommige

- spoedig
- steeds
- tamelijk
- tenzij
- terwijl
- thans
- tijdens
- toch
- toen
- toenmaals
- toenmalig
- tot
- totdat
- tussen
- uit
- uitgezonderd
- vaak
- van
- vandaan
- vanuit
- vanwege
- veeleer
- verder
- vervolgens
- vol
- volgens
- voor
- vooraf
- vooral
- vooralsnog
- voorbij
- voordat

- voordezen
- voordien
- voorheen
- voorop
- vooruit
- vrij
- vroeg
- waar
- waarom
- wanneer
- want
- waren
- was
- wat
- weer
- weg
- wegens
- wel
- weldra
- welk
- welke
- wie
- wiens
- wier
- wij
- wijzelf
- zal
- ze
- zelfs
- zichzelf
- zij
- zijn

- zijne
- zo
- zodra
- zonder
- zou
- zouden
- zowat
- zulke
- zullen
- zult

E.6 Finnish (sf) Default Stoplist

The following Finnish words are defined in the default stoplist for this language:

- ään
- ah
- ai
- aina
- alla
- alle
- alta
- ansiosta
- edessä
- een
- ehkä
- ei
- eli
- elikkä
- ellei
- elleivät
- ellemme
- ellen
- ellet

- ellette
- enemmän
- eniten
- ennen
- eräs
- että
- hän
- harva
- he
- hei
- hitaasti
- hyi
- hyvin
- iin
- ilman
- itse
- ja
- jahka
- jälkeen
- jo
- joka
- jokainen
- joku
- jollei
- jolleivat
- jollemme
- jollen
- jollet
- jollette
- jos
- joskin
- jotta

- kaikki
- kanssa
- kaukana
- ken
- keneksi
- kenelle
- kenkään
- kenties
- keskellä
- kesken
- ketkä
- kohti
- koska
- koskaan
- ksi
- kuin
- kuinka
- kuka
- kukaan
- kukin
- kumpainen
- kumpainenkaan
- kumpainenkin
- kumpi
- kumpikaan
- kumpikin
- kun
- kunhan
- kunnes
- kuten
- kyllä
- kylliksi

- lähellä
- läpi
- liian
- lla
- llä
- lle
- lta
- ltä
- luona
- me
- mikä
- mikään
- mikäli
- mikin
- miksi
- milloin
- milloinkaan
- minä
- missä
- miten
- molemmat
- mutta
- na
- nä
- näin
- nämä
- ne
- niin
- nopeasti
- nuo
- nyt
- oi

- olemme
- olen
- olet
- olette
- oli
- olimme
- olin
- olit
- olitte
- olivat
- ollut
- on
- oon
- ovat
- paitsi
- paljon
- paremmin
- parhaiten
- pian
- se
- seen
- sekä
- sen
- siellä
- sieltä
- siin
- sillä
- sinä
- sinne
- ssa
- ssä
- sta

- stä
- suoraan
- ta
- tä
- tähden
- tahi
- tai
- taikka
- takana
- takia
- tämä
- tarpeeksi
- tässä
- te
- tokko
- tta
- ttä
- tuo
- ulkopuolella
- useammin
- useimmin
- usein
- vaan
- vähän
- vähemmän
- vähiten
- vaikka
- vailla
- varten
- vastaan
- vielä
- voi

- ympäri

E.7 French (f) Default Stoplist

The following French words are defined in the default stoplist for this language:

- a
- afin
- ailleurs
- ainsi
- alors
- après
- attendant
- au
- aucun
- aucune
- au-dessous
- au-dessus
- auprès
- auquel
- aussi
- aussitôt
- autant
- autour
- aux
- auxquelles
- auxquels
- avec
- à
- beaucoup
- ça
- ce
- ceci
- cela

- celle
- celles
- celui
- cependant
- certain
- certaine
- certaines
- certains
- ces
- cet
- cette
- ceux
- chacun
- chacune
- chaque
- chez
- combien
- comme
- comment
- concernant
- dans
- de
- dedans
- dehors
- déjà
- delà
- depuis
- des
- desquelles
- desquels
- dessus
- dès

- donc
- donné
- dont
- du
- duquel
- durant
- elle
- elles
- en
- encore
- entre
- et
- étaient
- était
- étant
- etc
- eux
- furent
- grâce
- hormis
- hors
- ici
- il
- ils
- jadis
- je
- jusqu
- jusque
- la
- laquelle
- là
- le

- lequel
- les
- lesquelles
- lesquels
- leur
- leurs
- lors
- lorsque
- lui
- ma
- mais
- malgré
- me
- même
- mêmes
- mes
- mien
- mienne
- miennes
- miens
- moins
- moment
- mon
- moyennant
- ne
- ni
- non
- nos
- notamment
- notre
- autres
- nôtre

- nôtres
- nous
- nulle
- nulles
- on
- ou
- où
- par
- parce
- parmi
- plus
- plusieurs
- pour
- pourquoi
- près
- puis
- puisque
- quand
- quant
- que
- quel
- quelle
- quelqu'un
- quelqu'une
- quelque
- quelques-unes
- quelques-uns
- quels
- qui
- quiconque
- quoi
- quoique

- sa
- sans
- sauf
- se
- selon
- ses
- sien
- sienne
- siennes
- siens
- soi
- soi-même
- soit
- sont
- suis
- sur
- ta
- tandis
- tant
- te
- telle
- telles
- tes
- tienne
- tiennes
- tiens
- toi
- ton
- toujours
- tous
- toute
- toutes

- très
- trop
- tu
- un
- une
- vos
- votre
- vôtre
- vôtres
- vous
- vu
- y

E.8 German (d) Default Stoplist

The following German words are defined in the default stoplist for this language:

- ab
- aber
- allein
- als
- also
- am
- an
- auch
- auf
- aus
- außer
- bald
- bei
- beim
- bin
- bis
- bißchen

- bist
- da
- dabei
- dadurch
- dafür
- dagegen
- dahinter
- damit
- danach
- daneben
- dann
- daran
- darauf
- daraus
- darin
- darüber
- darum
- darunter
- das
- dasselbe
- daß
- davon
- davor
- dazu
- dazwischen
- dein
- deine
- deinem
- deinen
- deiner
- deines
- dem

- demselben
- den
- denn
- der
- derselben
- des
- desselben
- dessen
- dich
- die
- dies
- diese
- dieselbe
- dieselben
- diesem
- diesen
- dieser
- dieses
- dir
- doch
- dort
- du
- ebenso
- ehe
- ein
- eine
- einem
- einen
- einer
- eines
- entlang
- er

- es
- etwa
- etwas
- euch
- euer
- eure
- eurem
- euren
- eurer
- eures
- für
- fürs
- ganz
- gar
- gegen
- genau
- gewesen
- her
- herein
- herum
- hin
- hinter
- hintern
- ich
- ihm
- ihn
- Ihnen
- ihnen
- ihr
- ihre
- Ihre
- ihrem

- Ihrem
- ihren
- Ihnen
- Ihrer
- ihrer
- ihres
- Ihres
- im
- in
- ist
- ja
- je
- jedesmal
- jedoch
- jene
- jenem
- jenen
- jener
- jenes
- kaum
- kein
- keine
- keinem
- keinen
- keiner
- keines
- man
- mehr
- mein
- meine
- meinem
- meinen

- meiner
- meines
- mich
- mir
- mit
- nach
- nachdem
- nämlich
- neben
- nein
- nicht
- nichts
- noch
- nun
- nur
- ob
- ober
- obgleich
- oder
- ohne
- paar
- sehr
- sei
- sein
- seine
- seinem
- seinen
- seiner
- seines
- seit
- seitdem
- selbst

- sich
- Sie
- sie
- sind
- so
- sogar
- solch
- solche
- solchem
- solchen
- solcher
- solches
- sondern
- sonst
- soviel
- soweit
- über
- um
- und
- uns
- unser
- unsre
- unsrem
- unsren
- unsrer
- unsres
- vom
- von
- vor
- während
- war
- wäre

- wären
- warum
- was
- wegen
- weil
- weit
- welche
- welchem
- welchen
- welcher
- welches
- wem
- wen
- wenn
- wer
- weshalb
- wessen
- wie
- wir
- wo
- womit
- zu
- zum
- zur
- zwar
- zwischen

E.9 Italian (i) Default Stoplist

The following Italian words are defined in the default stoplist for this language:

- a
- affinché
- agl'

- agli
- ai
- al
- all'
- alla
- alle
- allo
- anzichè
- avere
- bensì
- che
- chi
- cioè
- come
- comunque
- con
- contro
- cosa
- da
- dachè
- dagl'
- dagli
- dai
- dal
- dall'
- dalla
- dalle
- dallo
- degl'
- degli
- dei
- del

- dell'
- delle
- dello
- di
- dopo
- dove
- dunque
- durante
- e
- egli
- eppure
- essere
- essi
- finché
- fino
- fra
- giacchè
- gl'
- gli
- grazie
- I
- il
- in
- inoltre
- io
- l'
- la
- le
- lo
- loro
- ma
- mentre

- mio
- ne
- neanche
- negl'
- negli
- nei
- nel
- nell'
- nella
- nelle
- nello
- nemmeno
- neppure
- noi
- nonchè
- nondimeno
- nostro
- o
- onde
- oppure
- ossia
- ovvero
- per
- perchè
- perciò
- però
- poichè
- prima
- purchè
- quand'anche
- quando
- quantunque

- quasi
- quindi
- se
- sebbene
- sennonchè
- senza
- seppure
- si
- siccome
- sopra
- sotto
- su
- subito
- sugl'
- sugli
- sui
- sul
- sull'
- sulla
- sulle
- sullo
- suo
- talchè
- tu
- tuo
- tuttavia
- tutti
- un
- una
- uno
- voi
- vostro

E.10 Portuguese (pt) Default Stoplist

The following Portuguese words are defined in the default stoplist for this language:

- a
- abaixo
- adiante
- agora
- ali
- antes
- aqui
- até
- atras
- bastante
- bem
- com
- como
- contra
- debaixo
- demais
- depois
- depressa
- devagar
- direito
- e
- ela
- elas
- êle
- eles
- em
- entre
- eu
- fora

- junto
- longe
- mais
- menos
- muito
- não
- ninguém
- nós
- nunca
- onde
- ou
- para
- por
- porque
- pouco
- próximo
- qual
- quando
- quanto
- que
- quem
- se
- sem
- sempre
- sim
- sob
- sobre
- talvez
- todas
- todos
- vagarosamente
- você

- vocês

E.11 Spanish (e) Default Stoplist

The following Spanish words are defined in the default stoplist for this language:

- a
- acá
- ahí
- ajena
- ajenas
- ajeno
- ajenos
- al
- algo
- alguna
- algunas
- alguno
- algunos
- algún
- allá
- allí
- aquel
- aquella
- aquellas
- aquello
- aquellos
- aquí
- cada
- cierta
- ciertas
- cierto
- ciertos
- como

- cómo
- con
- conmigo
- consigo
- contigo
- cualquier
- cualquiera
- cualquiera
- cuan
- cuanta
- cuantas
- cuánta
- cuántas
- cuanto
- cuantos
- cuán
- cuánto
- cuántos
- de
- dejar
- del
- demasiada
- demasiadas
- demasiado
- demasiados
- demás
- el
- ella
- ellas
- ellos
- él
- esa

- esas
- ese
- esos
- esta
- estar
- estas
- este
- estos
- hacer
- hasta
- jamás
- junto
- juntos
- la
- las
- lo
- los
- mas
- más
- me
- menos
- mía
- mientras
- mío
- misma
- mismas
- mismo
- mismos
- mucha
- muchas
- muchísima
- muchísimas

- muchísimo
- muchísimos
- mucho
- muchos
- muy
- nada
- ni
- ninguna
- ningunas
- ninguno
- ningunos
- no
- nos
- nosotras
- nosotros
- nuestra
- nuestras
- nuestro
- nuestros
- nunca
- os
- otra
- otras
- otro
- otros
- para
- parecer
- poca
- pocas
- poco
- pocos
- por

- porque
- que
- querer
- qué
- quien
- quienes
- quienesquiera
- quienquiera
- quién
- ser
- si
- siempre
- sí
- sín
- Sr
- Sra
- Sres
- Sta
- suya
- tuyas
- suyo
- tuyos
- tal
- tales
- tan
- tanta
- tantas
- tanto
- tantos
- te
- tener
- ti

- toda
- todas
- todo
- todos
- tomar
- tuya
- tuyo
- tú
- un
- una
- unas
- unos
- usted
- ustedes
- varias
- varios
- vosotras
- vosotros
- vuestra
- vuestras
- vuestro
- vuestros
- y
- yo

E.12 Swedish (s) Default Stoplist

The following Swedish words are defined in the default stoplist for this language:

- ab
- aldrig
- all
- alla
- allt

- alltid
- allting
- än
- andra
- andre
- annan
- annat
- ännu
- är
- åter
- att
- av
- avse
- avsedd
- avsedda
- avser
- avses
- bakom
- bara
- bäst
- bättre
- bra
- bredvid
- då
- dålig
- där
- därför
- de
- dem
- den
- denna
- deras

- dess
- dessa
- det
- detta
- du
- efter
- efteråt
- eftersom
- ej
- eller
- emot
- en
- endast
- er
- era
- ert
- ett
- få
- fall
- färre
- fastän
- flest
- flesta
- för
- först
- första
- förste
- fort
- framför
- från
- genom
- god

- goda
- gott
- ha
- hade
- haft
- han
- hans
- här
- hellre
- henne
- hennes
- heta
- heter
- hette
- hon
- honom
- hos
- hur
- i
- fall
- ifall
- in
- inga
- ingen
- ingenting
- inget
- innan
- inte
- ja
- jag
- kan
- kort

- korta
- kunde
- kunna
- lång
- långa
- långsam
- långsamma
- långsamt
- långt
- lite
- liten
- litet
- man
- med
- medan
- mellan
- men
- mer
- mera
- mest
- mesta
- mindre
- minst
- minsta
- mot
- mycket
- någon
- någonting
- något
- några
- när
- nära

- ned
- nej
- ner
- nere
- ni
- nu
- och
- också
- om
- oss
- över
- överst
- översta
- övre
- på
- så
- sådan
- sådana
- sådant
- säga
- säger
- sägs
- sämre
- sämst
- sån
- sånt
- såsom
- sin
- sist
- sista
- ska
- skall

- skulle
- som
- ta
- till
- tillräcklig
- tillräckliga
- tillräckligt
- tillsammans
- tog
- trots att
- under
- underst
- undre
- upp
- uppe
- ut
- utan
- ute
- utom
- vad
- väl
- var
- vara
- varför
- vart
- vem
- vems
- vet
- veta
- vi
- vid
- vilken

- vill
- ville
- visste
- vore

The Oracle Text Scoring Algorithm

This appendix describes how Oracle Text calculates scoring for word queries, which is different from the way it calculates scores for ABOUT queries in English. Scoring is obtained using the SCORE operator.

This appendix contains these topics:

- [Scoring Algorithm for Word Queries](#) (page F-1)
- [Word Scoring Example](#) (page F-2)
- [DML and Scoring Algorithm](#) (page F-2)

See Also:

["DEFINESCORE](#) (page 3-15)" and ["DEFINEMERGE](#) (page 3-14)" for information about user-defined scoring

F.1 Scoring Algorithm for Word Queries

To calculate a relevance score for a returned document in a word query, Oracle Text uses an inverse frequency algorithm based on Salton's formula.

Inverse frequency scoring assumes that frequently occurring terms in a document set are noise terms, and so these terms are scored lower. For a document to score high, the query term must occur frequently in the document but infrequently in the document set as a whole.

The following table illustrates Oracle Text's inverse frequency scoring. The first column shows the number of documents in the document set, and the second column shows the number of terms in the document necessary to score 100.

This table assumes that only one document in the set contains the query term.

Number of Documents in Document Set	Occurrences of Term in Document Needed to Score 100
1	34
5	20
10	17
50	13
100	12
500	10

Number of Documents in Document Set	Occurrences of Term in Document Needed to Score 100
1,000	9
10,000	7
100,000	6
1,000,000	5

Note that the score varies, depending on the set size. For example, if only one document in the set contains the query term, and there are five documents in the set, then the term must occur 20 times in the document to score 100. If 1,000,000 documents are in the set, then the term can occur only 5 times in the document to score 100.

F.2 Word Scoring Example

You have 5000 documents dealing with chemistry in which the term *chemical* occurs at least once in every document. The term *chemical* thus occurs frequently in the document set.

You have a document that contains 5 occurrences of *chemical* and 5 occurrences of the term *hydrogen*. No other document contains the term *hydrogen*. The term *hydrogen* thus occurs infrequently in the document set.

Because *chemical* occurs so frequently in the document set, its score for the document is lower with respect to *hydrogen*, which is infrequent in the document set as a whole. The score for *hydrogen* is therefore higher than that of *chemical*. This is so even though both terms occur 5 times in the document.

Note:

Even if the relatively infrequent term *hydrogen* occurred 4 times in the document, and *chemical* occurred 5 times in the document, the score for *hydrogen* might still be higher, because *chemical* occurs so frequently in the document set (at least 5000 times).

Inverse frequency scoring also means that adding documents that contain *hydrogen* lowers the score for that term in the document, and adding more documents that do not contain *hydrogen* raises the score.

F.3 DML and Scoring Algorithm

Because the scoring algorithm is based on the number of documents in the document set, inserting, updating or deleting documents in the document set is likely to change the score for any given term before and after DML.

If DML is heavy, you must optimize the index. Perfect relevance ranking is obtained by running a query right after optimizing the index.

If DML is light, Oracle Database still gives fairly accurate relevance ranking.

In either case, you must synchronize the index with `CTX_DDL.SYNC_INDEX` (page 8-68).

See Also:

["SYNC_INDEX \(page 8-68\)"](#)

Oracle Text Views

This appendix lists all of the views provided by Oracle Text. The system provides the following views:

- [CTX_ALEXER_DICTS](#) (page G-3)
- [CTX_AUTO_OPTIMIZE_INDEXES](#) (page G-3)
- [CTX_AUTO_OPTIMIZE_STATUS](#) (page G-3)
- [CTX_CLASSES](#) (page G-3)
- [CTX_FILTER_BY_COLUMNS](#) (page G-4)
- [CTX_FILTER_CACHE_STATISTICS](#) (page G-4)
- [CTX_INDEXES](#) (page G-5)
- [CTX_INDEX_ERRORS](#) (page G-6)
- [CTX_INDEX_OBJECTS](#) (page G-6)
- [CTX_INDEX_PARTITIONS](#) (page G-6)
- [CTX_INDEX_SETS](#) (page G-7)
- [CTX_INDEX_SET_INDEXES](#) (page G-7)
- [CTX_INDEX_SUB_LEXERS](#) (page G-7)
- [CTX_INDEX_SUB_LEXER_VALUES](#) (page G-7)
- [CTX_INDEX_VALUES](#) (page G-8)
- [CTX_OBJECTS](#) (page G-8)
- [CTX_OBJECT_ATTRIBUTES](#) (page G-8)
- [CTX_OBJECT_ATTRIBUTE_LOV](#) (page G-9)
- [CTX_ORDER_BY_COLUMNS](#) (page G-9)
- [CTX_PARAMETERS](#) (page G-10)
- [CTX_PENDING](#) (page G-11)
- [CTX_PREFERENCES](#) (page G-12)
- [CTX_PREFERENCE_VALUES](#) (page G-12)
- [CTX_SECTIONS](#) (page G-12)

-
- [CTX_SECTION_GROUPS](#) (page G-13)
 - [CTX_SQES](#) (page G-13)
 - [CTX_STOPLISTS](#) (page G-13)
 - [CTX_STOPWORDS](#) (page G-14)
 - [CTX_SUB_LEXERS](#) (page G-14)
 - [CTX_THESAURI](#) (page G-14)
 - [CTX_THES_PHRASES](#) (page G-15)
 - [CTX_TRACE_VALUES](#) (page G-15)
 - [CTX_USER_ALEXER_DICTS](#) (page G-15)
 - [CTX_USER_AUTO_OPTIMIZE_INDEXES](#) (page G-15)
 - [CTX_USER_EXTRACT_POLICIES](#) (page G-16)
 - [CTX_USER_EXTRACT_POLICY_VALUES](#) (page G-16)
 - [CTX_USER_EXTRACT_RULES](#) (page G-16)
 - [CTX_USER_EXTRACT_STOP_ENTITIES](#) (page G-17)
 - [CTX_USER_FILTER_BY_COLUMNS](#) (page G-17)
 - [CTX_USER_INDEXES](#) (page G-17)
 - [CTX_USER_INDEX_ERRORS](#) (page G-18)
 - [CTX_USER_INDEX_OBJECTS](#) (page G-19)
 - [CTX_USER_INDEX_PARTITIONS](#) (page G-19)
 - [CTX_USER_INDEX_SETS](#) (page G-20)
 - [CTX_USER_INDEX_SET_INDEXES](#) (page G-20)
 - [CTX_USER_INDEX_SUB_LEXERS](#) (page G-20)
 - [CTX_USER_INDEX_SUB_LEXER_VALS](#) (page G-21)
 - [CTX_USER_INDEX_VALUES](#) (page G-21)
 - [CTX_USER_ORDER_BY_COLUMNS](#) (page G-21)
 - [CTX_USER_PENDING](#) (page G-22)
 - [CTX_USER_PREFERENCES](#) (page G-22)
 - [CTX_USER_PREFERENCE_VALUES](#) (page G-22)
 - [CTX_USER_SECTIONS](#) (page G-23)
 - [CTX_USER_SECTION_GROUPS](#) (page G-23)
 - [CTX_USER_SQES](#) (page G-23)
 - [CTX_USER_STOPLISTS](#) (page G-24)

- [CTX_USER_STOPWORDS](#) (page G-24)
- [CTX_USER_SUB_LEXERS](#) (page G-24)
- [CTX_USER_THESAURI](#) (page G-25)
- [CTX_USER_THES_PHRASES](#) (page G-25)
- [CTX_VERSION](#) (page G-25)

G.1 CTX_ALEXER_DICTS

This view displays all dictionaries created by any user. This view can be queried by CTXSYS.

Column Name	Type	Description
ALD_OWNER	VARCHAR2 (30)	Name of the dictionary owner
ALD_NAME	VARCHAR2 (30)	Name of the dictionary
ALD_LANG	VARCHAR2 (30)	Language of the dictionary

G.2 CTX_AUTO_OPTIMIZE_INDEXES

This view displays all the indexes that are registered for auto optimization. It can be queried by CTXSYS.

Column Name	Type	Description
AOI_INDEX_OWNER	VARCHAR2 (30)	Index owner
AOI_INDEX_NAME	VARCHAR2 (30)	Index name
AOI_PARTITION_NAME	VARCHAR2 (30)	Partition name

G.3 CTX_AUTO_OPTIMIZE_STATUS

This view displays the status of auto optimization jobs. It can be queried by CTXSYS.

Column Name	Type	Description
AOS_TIMESTAMP	TIMESTAMP (6) WITH TIMEZONE	Time at which the auto optimization job started
AOS_STATUS	VARCHAR2 (30)	Status of the auto optimization job
AOS_ERROR	VARCHAR2 (4000)	Errors raised by the auto optimization job

G.4 CTX_CLASSES

This view displays all the preference categories registered in the Text data dictionary. It can be queried by any user.

Column Name	Type	Description
CLA_NAME	VARCHAR2 (30)	Class name
CLA_DESCRIPTION	VARCHAR2 (80)	Class description

G.5 CTX_FILTER_BY_COLUMNS

This view displays all `FILTER BY` columns registered in the Text data dictionary. It can be queried by any user.

Column Name	Type	Description
FBC_INDEX_OWNER	VARCHAR2 (30)	Index owner name
FBC_INDEX_NAME	VARCHAR2 (30)	Index name
FBC_TABLE_OWNER	VARCHAR2 (30)	Table owner name
FBC_TABLE_NAME	VARCHAR2 (30)	Table name
FBC_COLUMN_NAME	VARCHAR2 (256)	Column name
FBC_COLUMN_TYPE	VARCHAR2 (30)	Column type
FBC_SECTION_TYPE	VARCHAR2 (30)	Section type
FBC_SECTION_NAME	VARCHAR2 (30)	Section name
FBC_SECTION_ID	NUMBER	Section ID

G.6 CTX_FILTER_CACHE_STATISTICS

This view displays various statistics related to the query filter cache. This view can be queried by all users and it displays the statistics for all indexes.

Column Name	Type	Description
FCS_INDEX_OWNER	VARCHAR2 (30)	Index owner name
FCS_INDEX_NAME	VARCHAR2 (30)	Index name
FCS_PARTITION_NAME	VARCHAR2 (30)	Index partition name
FCS_SIZE	NUMBER	Current size of the filter cache in bytes
FCS_ENTRIES	NUMBER	Number of queries for which the query results are cached in the filter cache
FCS_REQUESTS	NUMBER	Number of query requests to the filter cache
FCS_HITS	NUMBER	Number of query requests for which matches were found in the filter cache

G.7 CTX_INDEXES

This view displays all indexes that are registered in the Text data dictionary for the current user. It can be queried by CTXSYS.

Column Name	Type	Description
IDX_CHARSET_COLUMN	VARCHAR2 (256)	Name of the charset column in base table
IDX_DOCID_COUNT	NUMBER	Number of documents indexed
IDX_FORMAT_COLUMNS	VARCHAR2 (256)	Name of the format column in base table
IDX_ID	NUMBER	Internal index ID
IDX_KEY_NAME	VARCHAR2 (256)	Primary key column(s)
IDX_LANGUAGE_COLUMN	VARCHAR2 (256)	Name of the language column in base table
IDX_NAME	VARCHAR2 (30)	Name of index
IDX_OWNER	VARCHAR2 (30)	Owner of index
IDX_STATUS	VARCHAR2 (12)	Status
IDX_SYNC_INTERVAL	VARCHAR2 (2000)	Interval string required by scheduler job. Only meaningful for AUTOMATIC sync. Always null for MANUAL and ON COMMIT sync.
IDX_SYNC_JOBNAME	VARCHAR2 (50)	Scheduler job name for automatic sync. Only meaningful for AUTOMATIC sync and always null for other types of sync.
IDX_SYNC_MEMORY	VARCHAR2 (100)	Sync memory size. Only meaningful for ON COMMIT and AUTOMATIC types of sync. For MANUAL sync, this is always null.
IDX_SYNC_PARA_DEGREE	NUMBER	Degree of parallelism for sync. Only meaningful for the AUTOMATIC type of sync; always null for MANUAL and ON COMMIT syncs.
IDX_SYNC_TYPE	VARCHAR2 (20)	Type of synching: MANUAL, AUTOMATIC, or ON COMMIT
IDX_TABLE	VARCHAR2 (30)	Table name
IDX_TABLE_OWNER	VARCHAR2 (30)	Owner of table
IDX_TEXT_NAME	VARCHAR2 (30)	Text column name
IDX_TYPE	VARCHAR2 (7)	Type of index: CONTEXT, CTXCAT, or CTXRULE

G.8 CTX_INDEX_ERRORS

This view displays the DML errors and is queryable by CTXSYS.

Column Name	Type	Description
ERR_INDEX_OWNER	VARCHAR2 (30)	Index owner
ERR_INDEX_NAME	VARCHAR2 (30)	Name of index
ERR_TIMESTAMP	DATE	Time of error
ERR_TEXTKEY	VARCHAR2 (18)	ROWID of errored document or name of errored operation (for example, ALTER INDEX)
ERR_TEXT	VARCHAR2 (4000)	Error text

G.9 CTX_INDEX_OBJECTS

This view displays the objects that are used for each class in the index. It can be queried by CTXSYS.

Column Name	Type	Description
IXO_INDEX_OWNER	VARCHAR2 (30)	Index owner
IXO_INDEX_NAME	VARCHAR2 (30)	Index name
IXO_CLASS	VARCHAR2 (30)	Class name
IXO_OBJECT	VARCHAR2 (30)	Object name

G.10 CTX_INDEX_PARTITIONS

This view displays all index partitions. It can be queried by CTXSYS.

Column Name	Type	Description
IXP_ID	NUMBER (38)	Index partition ID
IXP_INDEX_OWNER	VARCHAR2 (30)	Index owner
IXP_INDEX_NAME	VARCHAR2 (30)	Index name
IXP_INDEX_PARTITION_NAME	VARCHAR2 (30)	Index partition name
IXP_SYNC_TYPE	VARCHAR2 (20)	Type of synching: MANUAL, AUTOMATIC, or ON COMMIT
IXP_TABLE_OWNER	VARCHAR2 (30)	Table owner
IXP_TABLE_NAME	VARCHAR2 (30)	Table name
IXP_TABLE_PARTITION_NAME	VARCHAR2 (30)	Table partition name

Column Name	Type	Description
IXP_DOCID_COUNT	NUMBER (38)	Number of documents associated with the partition
IXP_STATUS	VARCHAR2 (12)	Partition status

G.11 CTX_INDEX_SETS

This view displays all index set names. It can be queried by any user.

Column Name	Type	Description
IXS_OWNER	VARCHAR2 (30)	Index set owner
IXS_NAME	VARCHAR2 (30)	Index set name

G.12 CTX_INDEX_SET_INDEXES

This view displays all the sub-indexes in an index set. It can be queried by any user.

Column Name	Type	Description
IXX_INDEX_SET_OWNER	VARCHAR2 (30)	Index set owner
IXX_INDEX_SET_NAME	VARCHAR2 (30)	Index set name
IXX_COLLIST	VARCHAR2 (500)	Column list of the sub-index
IXX_STORAGE	VARCHAR2 (500)	Storage clause of the sub-index

G.13 CTX_INDEX_SUB_LEXERS

This view shows the sub-lexers for each language for each index. It can be queried by CTXSYS.

Column Name	Type	Description
ISL_INDEX_OWNER	VARCHAR2 (30)	Index owner
ISL_INDEX_NAME	VARCHAR2 (30)	Index name
ISL_LANGUAGE	VARCHAR2 (30)	Language of sub-lexer
ISL_ALT_VALUE	VARCHAR2 (30)	Alternate value of language
ISL_OBJECT	VARCHAR2 (30)	Name of lexer object used for this language

G.14 CTX_INDEX_SUB_LEXER_VALUES

Shows the sub-lexer attributes and their values. Accessible by CTXSYS.

Column Name	Type	Description
ISV_INDEX_OWNER	VARCHAR2 (30)	Index owner
ISV_INDEX_NAME	VARCHAR2 (30)	Index name
ISV_LANGUAGE	VARCHAR2 (30)	Language of sub-lexer
ISV_OBJECT	VARCHAR2 (30)	Name of lexer object used for this language
ISV_ATTRIBUTE	VARCHAR2 (30)	Name of sub-lexer attribute
ISV_VALUE	VARCHAR2 (500)	Value of attribute of sub-lexer

G.15 CTX_INDEX_VALUES

This view displays attribute values for each object used in indexes. This view is queryable by CTXSYS.

Column Name	Type	Description
IXV_INDEX_OWNER	VARCHAR2 (30)	Index owner
IXV_INDEX_NAME	VARCHAR2 (30)	Index name
IXV_CLASS	VARCHAR2 (30)	Class name
IXV_OBJECT	VARCHAR2 (30)	Object name
IXV_ATTRIBUTE	VARCHAR2 (30)	Attribute name
IXV_VALUE	VARCHAR2 (500)	Attribute value

G.16 CTX_OBJECTS

This view displays all of the Text objects registered in the Text data dictionary. This view can be queried by any user.

Column Name	Type	Description
OBJ_CLASS	VARCHAR2 (30)	Object class (Datastore, Filter, Lexer, and so on)
OBJ_NAME	VARCHAR2 (30)	Object name
OBJ_DESCRIPTION	VARCHAR2 (80)	Object description

G.17 CTX_OBJECT_ATTRIBUTES

This view displays the attributes that can be assigned to preferences of each object. It can be queried by all users.

Column Name	Type	Description
OAT_CLASS	VARCHAR2 (30)	Object class (Data Store, Filter, Lexer, and so on)
OAT_OBJECT	VARCHAR2 (30)	Object name
OAT_ATTRIBUTE	VARCHAR2 (64)	Attribute name
OAT_DESCRIPTION	VARCHAR2 (80)	Description of attribute
OAT_REQUIRED	VARCHAR2 (1)	Required attribute, either Y or N
OAT_STATIC	VARCHAR2 (1)	Not currently used
OAT_DATATYPE	VARCHAR2 (64)	Attribute datatype. The value PROCEDURE indicates that the attribute of the object should be a stored procedure name.
OAT_DEFAULT	VARCHAR2 (500)	Default value for attribute
OAT_MIN	NUMBER	Minimum value
OAT_MAX	NUMBER	Maximum value
OAT_MAX_LENGTH	NUMBER	Maximum length

G.18 CTX_OBJECT_ATTRIBUTE_LOV

This view displays the allowed values for certain object attributes provided by Oracle Text. It can be queried by all users.

Column Name	Type	Description
OAL_CLASS	NUMBER (38)	Class of object
OAL_OBJECT	VARCHAR2 (30)	Object name
OAL_ATTRIBUTE	VARCHAR2 (32)	Attribute name
OAL_LABEL	VARCHAR2 (30)	Attribute value label
OAL_VALUE	VARCHAR2 (64)	Attribute value
OAL_DESCRIPTION	VARCHAR2 (80)	Attribute value description

G.19 CTX_ORDER_BY_COLUMNS

This view displays the ORDER BY columns registered in the Text data dictionary. It can be queried by any user.

Column Name	Type	Description
OBC_INDEX_OWNER	VARCHAR2 (30)	Index owner
OBC_INDEX_NAME	VARCHAR2 (30)	Index name

Column Name	Type	Description
OBC_TABLE_OWNER	VARCHAR2 (30)	Table owner
OBC_TABLE_NAME	VARCHAR2 (30)	Table name
OBC_COLUMN_NAME	VARCHAR2 (236)	Column name
OBC_COLUMN_POSITION	VARCHAR2 (30)	Column position
OBC_COLUMN_TYPE	VARCHAR2 (30)	Column type
OBC_SECTION_NAME	VARCHAR2 (30)	Section name
OBC_SECTION_TYPE	VARCHAR2 (30)	Section type
OBC_SECTION_ID	NUMBER	Section ID
OBC_SORT_ORDER	VARCHAR2 (8)	Sort order

G.20 CTX_PARAMETERS

This view displays all system-defined parameters as defined by CTXSYS. It can be queried by any user.

Column Name	Type	Description
PAR_NAME	VARCHAR2 (30)	Parameter name: auto_optimize auto_optimize_logfile max_index_memory ctx_doc_key_type default_index_memory default_datastore default_filter_binary default_filter_text default_filter_file default_section_html default_section_xml default_section_text default_lexer default_stoplist default_storage default_wordlist default_ctxcat_lexer default_ctxcat_index_set default_ctxcat_stoplist default_ctxcat_storage default_ctxcat_wordlist default_ctxrule_lexer default_ctxrule_stoplist default_ctxrule_storage default_ctxrule_wordlist log_directory file_access_role
PAR_VALUE	VARCHAR2 (500)	Parameter value. For max_index_memory and default_index_memory, PAR_VALUE stores a string consisting of the memory amount. For the other parameter names, PAR_VALUE stores the names of the preferences used as defaults for index creation.

G.21 CTX_PENDING

This view displays a row for each of the user's entries in the DML Queue. It can be queried by CTXSYS.

Column Name	Type	Description
PND_INDEX_OWNER	VARCHAR2 (30)	Index owner
PND_INDEX_NAME	VARCHAR2 (30)	Name of index

Column Name	Type	Description
PND_PARTITION_NAME	VARCHAR2 (30)	Name of partition for local partition indexes. NULL for normal indexes.
PND_ROWID	ROWID	ROWID to be indexed
PND_TIMESTAMP	DATE	Time of modification

G.22 CTX_PREFERENCES

This view displays preferences created by Oracle Text users, as well as all the system-defined preferences included with Oracle Text. The view contains one row for each preference. It can be queried by all users.

Column Name	Type	Description
PRE_OWNER	VARCHAR2 (30)	Username of preference owner
PRE_NAME	VARCHAR2 (30)	Preference name
PRE_CLASS	VARCHAR2 (30)	Preference class
PRE_OBJECT	VARCHAR2 (30)	Object used

G.23 CTX_PREFERENCE_VALUES

This view displays the values assigned to all the preferences in the Text data dictionary. The view contains one row for each value. It can be queried by all users.

Column Name	Type	Description
PRV_OWNER	VARCHAR2 (30)	Username of preference owner
PRV_PREFERENCE	VARCHAR2 (30)	Preference name
PRV_ATTRIBUTE	VARCHAR2 (64)	Attribute name
PRV_VALUE	VARCHAR2 (500)	Attribute value

G.24 CTX_SECTIONS

This view displays information about all the sections, including SDATA and MDATA sections, that have been created in the Text data dictionary. It can be queried by any user.

Column Name	Type	Description
SEC_OWNER	VARCHAR2 (30)	Owner of the section group
SEC_SECTION_GROUP	VARCHAR2 (30)	Name of the section group

Column Name	Type	Description
SEC_TYPE	VARCHAR2 (30)	Type of section, either ZONE, FIELD, SPECIAL, ATTR, STOP
SEC_ID	NUMBER	Section ID
SEC_NAME	VARCHAR2 (30)	Name of section
SEC_TAG	VARCHAR2 (64)	Section tag
SEC_VISIBLE	VARCHAR2 (1)	Y or N visible indicator for field sections only
SEC_DATATYPE	VARCHAR2 (30)	Shows the datatype name (NUMBER, VARCHAR2, DATE or RAW) if the section is an SDATA section. Otherwise, it is NULL.

G.25 CTX_SECTION_GROUPS

This view displays information about all the section groups that have been created in the Text data dictionary. It can be queried by any user.

Column Name	Type	Description
SGP_OWNER	VARCHAR2 (30)	Owner of section group
SGP_NAME	VARCHAR2 (30)	Name of section group
SGP_TYPE	VARCHAR2 (30)	Type of section group

G.26 CTX_SQES

This view displays the definitions for all SQEs that have been created by users. It can be queried by all users.

Column Name	Type	Description
SQE_OWNER	VARCHAR2 (30)	Owner of SQE
SQE_NAME	VARCHAR2 (30)	Name of SQE
SQE_QUERY	CLOB	Query Text

G.27 CTX_STOPLISTS

This view displays stoplists. Queryable by all users.

Column Name	Type	Description
SPL_OWNER	VARCHAR2 (30)	Owner of stoplist
SPL_NAME	VARCHAR2 (30)	Name of stoplist
SPL_COUNT	NUMBER	Number of stopwords

Column Name	Type	Description
SPL_TYPE	VARCHAR2 (30)	Type of stoplist, MULTI or BASIC

G.28 CTX_STOPWORDS

This view displays the stopwords in each stoplist. Queryable by all users.

Column Name	Type	Description
SPW_OWNER	VARCHAR2 (30)	Stoplist owner
SPW_STOPLIST	VARCHAR2 (30)	Stoplist name
SPW_TYPE	VARCHAR2 (10)	Stop type, either STOP_WORD, STOP_CLASS, STOP_THEME
SPW_WORD	VARCHAR2 (80)	Stopword
SPW_LANGUAGE	VARCHAR2 (30)	Stopword language
SPW_PATTERN	VARCHAR2 (512)	Stop pattern

G.29 CTX_SUB_LEXERS

This view contains information on multi-lexers and the sub-lexer preferences they contain. It can be queried by any user.

Column Name	Type	Description
SLX_OWNER	VARCHAR2 (30)	Owner of the multi-lexer preference
SLX_NAME	VARCHAR2 (30)	Name of the multi-lexer preference
SLX_LANGUAGE	VARCHAR2 (30)	Language of the referenced lexer (full name, not abbreviation)
SLX_ALT_VALUE	VARCHAR2 (30)	An alternate value for the language
SLX_SUB_OWNER	VARCHAR2 (30)	Owner of the sub-lexer
SLX_SUB_NAME	VARCHAR2 (30)	Name of the sub-lexer

G.30 CTX_THESAURI

This view displays information about all the thesauri that have been created in the Text data dictionary. It can be queried by any user.

Column Name	Type	Description
THS_OWNER	VARCHAR2 (30)	Thesaurus owner
THS_NAME	VARCHAR2 (30)	Thesaurus name

G.31 CTX_THES_PHRASES

This view displays phrase information for all thesauri in the Text data dictionary. It can be queried by any user.

Column Name	Type	Description
THP_THESAURUS	VARCHAR2 (30)	Thesaurus name
THP_PHRASE	VARCHAR2 (256)	Thesaurus phrase
THP_QUALIFIER	VARCHAR2 (256)	Thesaurus qualifier
THP_SCOPE_NOTE	VARCHAR2 (2000)	Thesaurus scope notes

G.32 CTX_TRACE_VALUES

This view contains one row for each active trace, and shows the current value of each trace.

Column Name	Type	Description
TRC_ID	BINARY_INTEGER	Trace ID
TRC_VALUE	NUMBER	Current trace value

Note:

The error "ORA-00955: name is already used by an existing object" can safely be ignored if this error is raised in the postinstall steps for patch releases. This may occur when this view is present in the database being patched.

G.33 CTX_USER_ALEXER_DICTS

This view displays all dictionaries created by the current user.

Column Name	Type	Description
ALD_NAME	VARCHAR2 (30)	Name of the dictionary
ALD_LANG	VARCHAR2 (30)	Language of the dictionary

G.34 CTX_USER_AUTO_OPTIMIZE_INDEXES

This view displays the user indexes that are registered for auto optimization. It can be queried by all users.

Column Name	Type	Description
AOI_INDEX_NAME	VARCHAR2 (30)	Index name

Column Name	Type	Description
AOI_PARTITION_NAME	VARCHAR2 (30)	Partition name

G.35 CTX_USER_EXTRACT_POLICIES

This view displays all of the entity extraction policies owned by the current user. All users can query this view.

Column Name	Type	Description
EPL_NAME	VARCHAR2 (30)	Entity extraction policy name

G.36 CTX_USER_EXTRACT_POLICY_VALUES

This view displays all of the values for the entity extraction policies owned by the current user. All users can query this view.

Column Name	Type	Description
EPV_POLICY_NAME	VARCHAR2 (30)	Entity extraction policy name
EPV_CLASS	VARCHAR2 (30)	Object class
EPV_OBJECT	VARCHAR2 (30)	Object name
EPV_ATTRIBUTE	VARCHAR2 (30)	Object attribute name
EPV_VALUE	VARCHAR2 (500)	Object attribute value

G.37 CTX_USER_EXTRACT_RULES

This view displays the entity extraction rules for the policies owned by the current user. All users can query this view.

Column Name	Type	Description
ERL_POLICY_NAME	VARCHAR2 (30)	Entity extraction policy name
ERL_RULE_ID	INTEGER	Entity extraction rule ID
ERL_LANGUAGE	VARCHAR2 (30)	Entity extraction rule language
ERL_RULE	VARCHAR2 (512)	Entity extraction rule contents
ERL_TYPE	VARCHAR2 (4000)	String mapping backreferences to entity types
ERL_STATUS	VARCHAR2 (30)	Entity extraction rule status: compiled, not compiled, to be deleted
ERL_COMMENTS	VARCHAR2 (4000)	Comments

G.38 CTX_USER_EXTRACT_STOP_ENTITIES

This view displays the stop entities owned by the current user. All users can query this view.

Column Name	Type	Description
ESE_POLICY_NAME	VARCHAR2(30)	Entity extraction policy name
ESE_NAME	VARCHAR2(512)	Stop entity name
ESE_TYPE	VARCHAR2(30)	Stop entity type
ESE_STATUS	VARCHAR2(30)	Entity extraction rule status: compiled, not compiled, to be deleted, subset
ESE_COMMENTS	VARCHAR2(4000)	Comments

G.39 CTX_USER_FILTER_BY_COLUMNS

This view displays all FILTER BY columns registered in the Text data dictionary for the current user. It can be queried by any user.

Column Name	Type	Description
FBC_INDEX_NAME	VARCHAR2(30)	Index name
FBC_TABLE_OWNER	VARCHAR2(30)	Table owner name
FBC_TABLE_NAME	VARCHAR2(30)	Table name
FBC_COLUMN_NAME	VARCHAR2(256)	Column name
FBC_COLUMN_TYPE	VARCHAR2(30)	Column type
FBC_SECTION_TYPE	VARCHAR2(30)	Section type
FBC_SECTION_NAME	VARCHAR2(30)	Section name
FBC_SECTION_ID	NUMBER	Section ID

G.40 CTX_USER_INDEXES

This view displays all indexes that are registered in the Text data dictionary for the current user. It can be queried by all users.

Column Name	Type	Description
IDX_CHARSET_COLUMN	VARCHAR2(256)	Name of the charset column of base table
IDX_DOCID_COUNT	NUMBER	Number of documents indexed
IDX_FORMAT_COLUMN	VARCHAR2(256)	Name of the format column of base table

Column Name	Type	Description
IDX_ID	NUMBER	Internal index ID
IDX_KEY_NAME	VARCHAR (256)	Primary key column(s)
IDX_LANGUAGE_COLUMN	VARCHAR2 (256)	Name of the language column of base table
IDX_NAME	VARCHAR2 (30)	Name of index
IDX_STATUS	VARCHAR2 (12)	Status, either INDEXED or INDEXING
IDX_SYNC_INTERVAL	VARCHAR2 (2000)	This is the interval string required by scheduler job. Only meaningful for AUTOMATIC sync. Always null for MANUAL and ON COMMIT sync.
IDX_SYNC_JOBNAME	VARCHAR2 (50)	This is the scheduler job name for automatic sync. Only meaningful for AUTOMATIC sync and always null for other types of sync.
IDX_SYNC_MEMORY	VARCHAR2 (100)	The sync memory size. Only meaningful for ON COMMIT and AUTOMATIC types of sync. For MANUAL sync, this is always null.
IDX_SYNC_PARA_DEGREE	NUMBER	Degree of parallelism for sync. Only meaningful for the AUTOMATIC type of sync; always null for MANUAL and ON COMMIT syncs.
IDX_SYNC_TYPE	VARCHAR2 (20)	Type of synching: AUTOMATIC, MANUAL or ON COMMIT
IDX_TABLE	VARCHAR2 (30)	Table name
IDX_TABLE_OWNER	VARCHAR2 (30)	Owner of table
IDX_TEXT_NAME	VARCHAR2 (30)	Text column name
IDX_TYPE	VARCHAR2 (30)	Type of index: CONTEXT, CTXCAT, or CTXRULE

G.41 CTX_USER_INDEX_ERRORS

This view displays the indexing errors for the current user and is queryable by all users.

Column Name	Type	Description
ERR_INDEX_NAME	VARCHAR2 (30)	Name of index
ERR_TIMESTAMP	DATE	Time of error

Column Name	Type	Description
ERR_TEXTKEY	VARCHAR2 (18)	ROWID of errored document or name of errored operation (for example, ALTER INDEX)
ERR_TEXT	VARCHAR2 (4000)	Error text

G.42 CTX_USER_INDEX_OBJECTS

This view displays the preferences that are attached to the indexes defined for the current user. It can be queried by all users.

Column Name	Type	Description
IXO_INDEX_NAME	VARCHAR2 (30)	Name of index
IXO_CLASS	VARCHAR2 (30)	Object name
IXO_OBJECT	VARCHAR2 (80)	Object description

G.43 CTX_USER_INDEX_PARTITIONS

This view displays all index partitions for the current user. It is queryable by all users.

Column Name	Type	Description
IXP_DOCID_COUNT	NUMBER (38)	Number of documents associated with the index partition
IXP_ID	NUMBER (38)	Index partition ID
IXP_INDEX_NAME	VARCHAR2 (30)	Index name
IXP_INDEX_PARTITION_NAME	VARCHAR2 (30)	Index partition name
IDX_SYNC_INTERVAL	VARCHAR2 (2000)	This is the interval string required by scheduler job. Only meaningful for AUTOMATIC sync. Always null for MANUAL and ON COMMIT sync.
IDX_SYNC_JOBNAME	VARCHAR2 (50)	This is the scheduler job name for automatic sync. It is only meaningful for AUTOMATIC sync and always null for other types of sync.
IDX_SYNC_MEMORY	VARCHAR2 (100)	The sync memory size. Only meaningful for ON COMMIT and AUTOMATIC types of sync. For MANUAL sync, this is always null.
IDX_SYNC_PARA_DEGREE	NUMBER	Degree of parallelism for sync. Only meaningful for the AUTOMATIC type of sync; always null for MANUAL and ON COMMIT syncs.

Column Name	Type	Description
IDX_SYNC_TYPE	VARCHAR2 (20)	Type of synching: AUTOMATIC, MANUAL or ON COMMIT
IXP_STATUS	VARCHAR2 (12)	Partition status
IXP_TABLE_OWNER	VARCHAR2 (30)	Table owner
IXP_TABLE_NAME	VARCHAR2 (30)	Table name
IXP_TABLE_PARTITION_NAME	VARCHAR2 (30)	Table partition name

G.44 CTX_USER_INDEX_SETS

This view displays all index set names that belong to the current user. It is queryable by all users.

Column Name	Type	Description
IXS_NAME	VARCHAR2 (30)	Index set name

G.45 CTX_USER_INDEX_SET_INDEXES

This view displays all the indexes in an index set that belong to the current user. It is queryable by all users.

Column Name	Type	Description
IXX_INDEX_SET_NAME	VARCHAR2 (30)	Index set name
IXX_COLLIST	VARCHAR2 (500)	Column list of the index
IXX_STORAGE	VARCHAR2 (500)	Storage clause of the index

G.46 CTX_USER_INDEX_SUB_LEXERS

This view shows the sub-lexers for each language for each index for the querying user. This view can be queried by all users.

Column Name	Type	Description
ISL_INDEX_NAME	VARCHAR2 (30)	Index name
ISL_LANGUAGE	VARCHAR2 (30)	Language of sub-lexer
ISL_ALT_VALUE	VARCHAR2 (30)	Alternate value of language
ISL_OBJECT	VARCHAR2 (30)	Name of lexer object used for this language

G.47 CTX_USER_INDEX_SUB_LEXER_VALS

Shows the sub-lexer attributes and their values for the querying user. This view can be queried by all users.

Column Name	Type	Description
ISV_INDEX_NAME	VARCHAR2 (30)	Index name
ISV_LANGUAGE	VARCHAR2 (30)	Language of sub-lexer
ISV_OBJECT	VARCHAR2 (30)	Name of lexer object used for this language
ISV_ATTRIBUTE	VARCHAR2 (30)	Name of sub-lexer attribute
ISV_VALUE	VARCHAR2 (500)	Value of sub-lexer attribute

G.48 CTX_USER_INDEX_VALUES

This view displays attribute values for each object used in indexes for the current user. This view is queryable by all users.

Column Name	Type	Description
IXV_INDEX_NAME	VARCHAR2 (30)	Index name
IXV_CLASS	VARCHAR2 (30)	Class name
IXV_OBJECT	VARCHAR2 (30)	Object name
IXV_ATTRIBUTE	VARCHAR2 (30)	Attribute name
IXV_VALUE	VARCHAR2 (500)	Attribute value

G.49 CTX_USER_ORDER_BY_COLUMNS

This view displays all ORDER BY columns registered in the Text data dictionary for the current user. It can be queried by any user.

Column Name	Type	Description
OBC_INDEX_NAME	VARCHAR2 (30)	Index name
OBC_TABLE_OWNER	VARCHAR2 (30)	Table owner
OBC_TABLE_NAME	VARCHAR2 (30)	Table name
OBC_COLUMN_NAME	VARCHAR2 (236)	Column name
OBC_COLUMN_POSITION	VARCHAR2 (30)	Column position
OBC_COLUMN_TYPE	VARCHAR2 (30)	Column type
OBC_SECTION_NAME	VARCHAR2 (30)	Section name

Column Name	Type	Description
OBC_SECTION_TYPE	VARCHAR2 (30)	Section type
OBC_SECTION_ID	NUMBER	Section ID
OBC_SORT_ORDER	VARCHAR2 (8)	Sort order

G.50 CTX_USER_PENDING

This view displays a row for each of the user's entries in the DML Queue. It can be queried by all users.

Column Name	Type	Description
PND_INDEX_NAME	VARCHAR2 (30)	Name of index
PND_PARTITION_NAME	VARCHAR2 (30)	Name of partition for local partition indexes. NULL for normal indexes.
PND_ROWID	ROWID	Rowid to be indexed
PND_TIMESTAMP	DATE	Time of modification

G.51 CTX_USER_PREFERENCES

This view displays all preferences defined by the current user. It can be queried by all users.

Column Name	Type	Description
PRE_NAME	VARCHAR2 (30)	Preference name
PRE_CLASS	VARCHAR2 (30)	Preference class
PRE_OBJECT	VARCHAR2 (30)	Object used

G.52 CTX_USER_PREFERENCE_VALUES

This view displays all the values for preferences defined by the current user. It can be queried by all users.

Column Name	Type	Description
PRV_PREFERENCE	VARCHAR2 (30)	Preference name
PRV_ATTRIBUTE	VARCHAR2 (64)	Attribute name
PRV_VALUE	VARCHAR2 (500)	Attribute value

G.53 CTX_USER_SECTIONS

This view displays information about the sections that have been created in the Text data dictionary for the current user. It can be queried by all users.

Column Name	Type	Description
SEC_DATATYPE	VARCHAR2 (30)	Shows the datatype name (NUMBER, VARCHAR2, DATE or RAW) if the section is an SDATA section. Otherwise, it is NULL.
SEC__SECTION_GROUP	VARCHAR2 (30)	Name of the section group
SEC_TYPE	VARCHAR2 (30)	Type of section, either ZONE, FIELD, SPECIAL, STOP, or ATTR
SEC_ID	NUMBER	Section ID
SEC_NAME	VARCHAR2 (30)	Name of section
SEC_TAG	VARCHAR2 (64)	Section tag
SEC_VISIBLE	VARCHAR2 (1)	Y or N visible indicator for field sections

G.54 CTX_USER_SECTION_GROUPS

This view displays information about the section groups that have been created in the Text data dictionary for the current user. It can be queried by all users.

Column Name	Type	Description
SGP_NAME	VARCHAR2 (30)	Name of section group
SGP_TYPE	VARCHAR2 (30)	Type of section group

G.55 CTX_USER_SESSION_SQES

This view displays the definitions of all session-duration SQEs that have been created by the current user.

Column Name	Type	Description
SQE_OWNER	VARCHAR2 (30)	Name of owner of SQE
SQE_NAME	VARCHAR2 (30)	Name of SQE (shared namespace between persistent and session-duration)
SQE_QUERY	CLOB	Query text (max size of 32k)

G.56 CTX_USER_SQES

This view displays the definitions of all persistent duration SQEs that have been created by the current user. In other words, it does not display session duration SQEs.

Column Name	Type	Description
SQE_OWNER	VARCHAR2 (30)	Owner of SQE
SQE_NAME	VARCHAR2 (30)	Name of SQE
SQE_QUERY	CLOB	Query text

G.57 CTX_USER_STOPLISTS

This view displays stoplists for current user. It is queryable by all users.

Column Name	Type	Description
SPL_NAME	VARCHAR2 (30)	Name of stoplist
SPL_COUNT	NUMBER	Number of stopwords
SPL_TYPE	VARCHAR2 (30)	Type of stoplist, MULTI or BASIC

G.58 CTX_USER_STOPWORDS

This view displays stopwords in each stoplist for current user. Queryable by all users.

Column Name	Type	Description
SPW_STOPLIST	VARCHAR2 (30)	Stoplist name
SPW_TYPE	VARCHAR2 (10)	Stop type, either STOP_WORD, STOP_CLASS, STOP_THEME
SPW_WORD	VARCHAR2 (80)	Stopword
SPW_LANGUAGE	VARCHAR2 (30)	Stopword language
SPW_PATTERN	VARCHAR2 (512)	Stop pattern

G.59 CTX_USER_SUB_LEXERS

For the current user, this view contains information on multi-lexers and the sub-lexer preferences they contain. It can be queried by any user.

Column Name	Type	Description
SLX_NAME	VARCHAR2 (30)	Name of the multi-lexer preference
SLX_LANGUAGE	VARCHAR2 (30)	Language of the referenced lexer (full name, not abbreviation)
SLX_ALT_VALUE	VARCHAR2 (30)	An alternate value for the language
SLX_SUB_OWNER	VARCHAR2 (30)	Owner of the sub-lexer
SLX_SUB_NAME	VARCHAR2 (30)	Name of the sub-lexer

G.60 CTX_USER_THESAURI

This view displays the information about all of the thesauri that have been created in the system by the current user. It can be viewed by all users.

Column Name	Type	Description
THS_NAME	VARCHAR2 (30)	Thesaurus name

G.61 CTX_USER_THES_PHRASES

This view displays the phrase information of all thesauri owned by the current user. It can be queried by all users.

Column Name	Type	Description
THP_THESAURUS	VARCHAR2 (30)	Thesaurus name
THP_PHRASE	VARCHAR2 (256)	Thesaurus phrase
THP_QUALIFIER	VARCHAR2 (256)	Phrase qualifier
THP_SCOPE_NOTE	VARCHAR2 (2000)	Scope note of the phrase

G.62 CTX_VERSION

This view displays the CTXSYS data dictionary and code version number information.

Column Name	Type	Description
VER_DICT	CHAR (9)	The CTXSYS data dictionary version number
VER_CODE	VARCHAR2 (9)	The version number of the code linked in to the Oracle Database shadow process This column fetches the version number for linked-in code. Thus, use this column to detect and verify patch releases.

Stopword Transformations in Oracle Text

This appendix describes the stopwords rewrites or transformations for each operator. In all tables, the *Stopword Expression* column describes the query expression or component of a query expression, while the right-hand column describes the way Oracle Text rewrites the query.

This appendix contains the following topics:

- [Understanding Stopword Transformations](#) (page H-1)
- [About Stopwords in Phrase Queries](#) (page H-2)
- [Word Transformations](#) (page H-2)
- [AND Transformations](#) (page H-3)
- [OR Transformations](#) (page H-3)
- [ACCUMulate Transformations](#) (page H-3)
- [MINUS Transformations](#) (page H-4)
- [MNOT Transformations](#) (page H-4)
- [NOT Transformations](#) (page H-4)
- [EQUIValence Transformations](#) (page H-5)
- [NEAR Transformations](#) (page H-5)
- [Weight Transformations](#) (page H-6)
- [Threshold Transformations](#) (page H-6)
- [WITHIN Transformations](#) (page H-6)

H.1 Understanding Stopword Transformations

When you use a stopword or stopword-only phrase as an operand for a query operator, Oracle Text rewrites the expression to eliminate the stopword or stopword-only phrase and then executes the query.

The token *stopword* stands for a single stopword or a stopword-only phrase.

The token *non_stopword* stands for either a single non-stopword, a phrase of all non-stopwords, or a phrase of non-stopwords and stopwords.

The token *no_lex* stands for a single character or a string of characters that is neither a stopword nor a word that is indexed. For example, the + character by itself is an example of a *no_lex* token.

When the *Stopword Expression* column completely describes the query expression, a rewritten expression of *no_token* means that no hits are returned when you enter such a query.

When the *Stopword Expression* column describes a component of a query expression with more than one operator, a rewritten expression of *no_token* means that a *no_token* value is passed to the next step of the rewrite.

Transformations that contain a *no_token* as an operand in the *Stopword Expression* column describe intermediate transformations in which the *no_token* is a result of a previous transformation. These intermediate transformations apply when the original query expression has at least one stopword and more than one operator.

For example, consider the following compound query expression:

```
'(this NOT dog) AND cat'
```

Assuming that *this* is the only stopword in this expression, Oracle Text applies the following transformations in the following order:

stopword NOT non-stopword => no_token

no_token AND non_stopword => non_stopword

The resulting expression is:

```
'cat'
```

H.2 About Stopwords in Phrase Queries

If used in a phrase query, a stopword will match any single word, whether that word is a stopword or not. For example, if "in" and "to" are stopwords, but "throughout" is not, then the query "hiking in California" will match any of these phrases:

- hiking in California
- hiking to California
- hiking throughout California

H.3 Word Transformations

Stopword Expression	Rewritten Expression
stopword	no_token
no_lex	no_token

The first transformation means that a stopword or stopword-only phrase by itself in a query expression results in no hits.

The second transformation says that a term that is not lexed, such as the + character, results in no hits.

H.4 AND Transformations

Stopword Expression	Rewritten Expression
<i>non_stopword</i> AND <i>stopword</i>	<i>non_stopword</i>
<i>non_stopword</i> AND <i>no_token</i>	<i>non_stopword</i>
<i>stopword</i> AND <i>non_stopword</i>	<i>non_stopword</i>
<i>no_token</i> AND <i>non_stopword</i>	<i>non_stopword</i>
<i>stopword</i> AND <i>stopword</i>	<i>no_token</i>
<i>no_token</i> AND <i>stopword</i>	<i>no_token</i>
<i>stopword</i> AND <i>no_token</i>	<i>no_token</i>
<i>no_token</i> AND <i>no_token</i>	<i>no_token</i>

H.5 OR Transformations

Stopword Expression	Rewritten Expression
<i>non_stopword</i> OR <i>stopword</i>	<i>non_stopword</i>
<i>non_stopword</i> OR <i>no_token</i>	<i>non_stopword</i>
<i>stopword</i> OR <i>non_stopword</i>	<i>non_stopword</i>
<i>no_token</i> OR <i>non_stopword</i>	<i>non_stopword</i>
<i>stopword</i> OR <i>stopword</i>	<i>no_token</i>
<i>no_token</i> OR <i>stopword</i>	<i>no_token</i>
<i>stopword</i> OR <i>no_token</i>	<i>no_token</i>
<i>no_token</i> OR <i>no_token</i>	<i>no_token</i>

H.6 ACCUMulate Transformations

Stopword Expression	Rewritten Expression
<i>non_stopword</i> ACCUM <i>stopword</i>	<i>non_stopword</i>
<i>non_stopword</i> ACCUM <i>no_token</i>	<i>non_stopword</i>
<i>stopword</i> ACCUM <i>non_stopword</i>	<i>non_stopword</i>
<i>no_token</i> ACCUM <i>non_stopword</i>	<i>non_stopword</i>
<i>stopword</i> ACCUM <i>stopword</i>	<i>no_token</i>
<i>no_token</i> ACCUM <i>stopword</i>	<i>no_token</i>

Stopword Expression	Rewritten Expression
<i>stopword</i> ACCUM <i>no_token</i>	<i>no_token</i>
<i>no_token</i> ACCUM <i>no_token</i>	<i>no_token</i>

H.7 MINUS Transformations

Stopword Expression	Rewritten Expression
<i>non_stopword</i> MINUS <i>stopword</i>	<i>non_stopword</i>
<i>non_stopword</i> MINUS <i>no_token</i>	<i>non_stopword</i>
<i>stopword</i> MINUS <i>non_stopword</i>	<i>no_token</i>
<i>no_token</i> MINUS <i>non_stopword</i>	<i>no_token</i>
<i>stopword</i> MINUS <i>stopword</i>	<i>no_token</i>
<i>no_token</i> MINUS <i>stopword</i>	<i>no_token</i>
<i>stopword</i> MINUS <i>no_token</i>	<i>no_token</i>
<i>no_token</i> MINUS <i>no_token</i>	<i>no_token</i>

H.8 MNOT Transformations

Stopword Expression	Rewritten Expression
<i>non_stopword</i> MNOT <i>stopword</i>	<i>non_stopword</i>
<i>non_stopword</i> MNOT <i>no_token</i>	<i>non_stopword</i>
<i>stopword</i> MNOT <i>non_stopword</i>	<i>no_token</i>
<i>no_token</i> MNOT <i>non_stopword</i>	<i>no_token</i>
<i>stopword</i> MNOT <i>stopword</i>	<i>no_token</i>
<i>no_token</i> MNOT <i>stopword</i>	<i>no_token</i>
<i>stopword</i> MNOT <i>no_token</i>	<i>no_token</i>
<i>no_token</i> MNOT <i>no_token</i>	<i>no_token</i>

H.9 NOT Transformations

Stopword Expression	Rewritten Expression
<i>non_stopword</i> NOT <i>stopword</i>	<i>non_stopword</i>
<i>non_stopword</i> NOT <i>no_token</i>	<i>non_stopword</i>

Stopword Expression	Rewritten Expression
<i>stopword</i> NOT <i>non_stopword</i>	<i>no_token</i>
<i>no_token</i> NOT <i>non_stopword</i>	<i>no_token</i>
<i>stopword</i> NOT <i>stopword</i>	<i>no_token</i>
<i>no_token</i> NOT <i>stopword</i>	<i>no_token</i>
<i>stopword</i> NOT <i>no_token</i>	<i>no_token</i>
<i>no_token</i> NOT <i>no_token</i>	<i>no_token</i>

H.10 EQUIValence Transformations

Stopword Expression	Rewritten Expression
<i>non_stopword</i> EQUIV <i>stopword</i>	<i>non_stopword</i>
<i>non_stopword</i> EQUIV <i>no_token</i>	<i>non_stopword</i>
<i>stopword</i> EQUIV <i>non_stopword</i>	<i>non_stopword</i>
<i>no_token</i> EQUIV <i>non_stopword</i>	<i>non_stopword</i>
<i>stopword</i> EQUIV <i>stopword</i>	<i>no_token</i>
<i>no_token</i> EQUIV <i>stopword</i>	<i>no_token</i>
<i>stopword</i> EQUIV <i>no_token</i>	<i>no_token</i>
<i>no_token</i> EQUIV <i>no_token</i>	<i>no_token</i>

Note:

When you use query explain plan, not all of the equivalence transformations are represented in the EXPLAIN table.

H.11 NEAR Transformations

Stopword Expression	Rewritten Expression
<i>non_stopword</i> NEAR <i>stopword</i>	<i>non_stopword</i>
<i>non_stopword</i> NEAR <i>no_token</i>	<i>non_stopword</i>
<i>stopword</i> NEAR <i>non_stopword</i>	<i>non_stopword</i>
<i>no_token</i> NEAR <i>non_stopword</i>	<i>non_stopword</i>
<i>stopword</i> NEAR <i>stopword</i>	<i>no_token</i>
<i>no_token</i> NEAR <i>stopword</i>	<i>no_token</i>

Stopword Expression	Rewritten Expression
<i>stopword</i> NEAR <i>no_token</i>	<i>no_token</i>
<i>no_token</i> NEAR <i>no_token</i>	<i>no_token</i>

H.12 Weight Transformations

Stopword Expression	Rewritten Expression
<i>stopword</i> * n	<i>no_token</i>
<i>no_token</i> * n	<i>no_token</i>

H.13 Threshold Transformations

Stopword Expression	Rewritten Expression
<i>stopword</i> > n	<i>no_token</i>
<i>no_token</i> > n	<i>no_token</i>

H.14 WITHIN Transformations

Stopword Expression	Rewritten Expression
<i>stopword</i> WITHIN <i>section</i>	<i>no_token</i>
<i>no_token</i> WITHIN <i>section</i>	<i>no_token</i>

Symbols

`_` wildcard, [3-52](#)
`-` operator, [3-31](#)
`,` operator, [3-7](#)
`!` operator, [3-45](#)
`?` operator, [3-20](#)
`{}` escape character, [4-1](#)
`*` operator, [3-51](#)
`\` escape character, [4-1](#)
`%` wildcard, [3-52](#)
`=` operator, [3-14](#), [3-15](#), [3-19](#)
`>` operator, [3-48](#)
`$` operator, [3-45](#)

A

ABOUT query
 example, [3-4](#)
 highlight markup, [9-13](#), [9-26](#)
 highlight offsets, [9-9](#), [9-23](#)
 viewing expansion, [12-4](#)
accumulate operator
 scoring, [3-7](#)
 stopword transformations, [H-3](#)
ADD_ATTR_SECTION procedure, [8-3](#)
ADD_AUTO_OPTIMIZE procedure, [8-4](#)
ADD_EVENT procedure, [11-1](#)
ADD_FIELD_SECTION procedure, [8-5](#)
ADD_INDEX procedure, [8-8](#)
ADD_MDATA procedure, [8-9](#), [8-11](#)
ADD_MDATA_SECTION procedure, [8-12](#)
ADD_SDATA_COLUMN procedure, [8-14](#)
ADD_SDATA_SECTION procedure, [8-16](#)
ADD_SPECIAL_SECTION procedure, [8-18](#)
ADD_STOP_SECTION procedure, [8-21](#)
ADD_STOPCLASS procedure, [8-19](#)
ADD_STOPTHEME procedure, [8-22](#)
ADD_STOPWORD procedure, [8-23](#)
ADD_SUB_LEXER procedure
 example, [2-50](#)
ADD_TRACE procedure, [11-2](#)
ADD_ZONE_SECTION procedure, [8-26](#)

adding a trace, [11-2](#)
adding an event, [11-1](#)
adding metadata, [8-9](#), [8-11](#), [8-12](#)
adding structured data, [8-14](#), [8-16](#)
AL32UTF8 character set, [2-52](#), [2-54–2-56](#)
ALTER INDEX
 Add Section Constraints, [1-17](#)
ALTER INDEX statement
 examples, [1-1](#)
 parameters syntax, [1-1](#)
 rebuild syntax, [1-1](#)
 rename syntax, [1-1](#)
 syntax overview, [1-1](#)
ALTER TABLE
 Composite Domain Index and, [1-46](#)
 UPDATE GLOBAL INDEXES, [1-19–1-21](#)
ALTER TABLE statement, [1-18](#)
ALTER_PHRASE procedure, [14-2](#)
ALTER_THESAURUS procedure, [14-4](#)
alternate grammar template, [1-32](#)
alternate language template, [1-34](#)
alternate spelling
 about, [17-1](#)
 base letter, [17-2](#)
 Danish, [17-4](#)
 disabling example, [8-71](#), [17-1](#)
 enabling example, [17-1](#)
 German, [17-4](#)
 normalized vs. original, [17-1](#)
 overriding, [17-3](#)
 Swedish, [17-5](#)
alternate_spelling attribute, [2-47](#), [17-2](#)
alternative scoring template, [1-34](#)
American
 index defaults, [2-96](#)
analyzing queries, [13-10](#)
AND operator
 stopword transformations, [H-3](#)
Asian languages
 and CTXRULE indexes, [D-2](#)
attribute section
 adding dynamically, [1-1](#)
 defining, [8-3](#)

- attribute section (*continued*)
 - dynamically adding, [1-17](#)
 - querying, [3-54](#)
 - WITHIN example, [3-54](#)
- attributes
 - alternate_spelling, [2-47](#), [17-2](#)
 - auto_filter_output_formatting, [2-23](#)
 - base_letter, [2-41](#), [17-2](#)
 - base_letter_type, [2-41](#)
 - binary, [2-7](#)
 - command, [2-26](#)
 - composite, [2-41](#)
 - continuation, [2-41](#)
 - detail_key, [2-7](#)
 - detail_lineno, [2-7](#)
 - detail_table, [2-7](#)
 - detail_text, [2-7](#)
 - disabling, [8-70](#), [8-71](#)
 - endjoins, [2-41](#)
 - ftp_proxy, [2-12](#)
 - fuzzy_match, [2-72](#)
 - fuzzy_numresults, [2-72](#)
 - fuzzy_score, [2-72](#)
 - http_proxy, [2-12](#)
 - i_index_clause, [2-82](#)
 - i_table_clause, [2-83](#)
 - index_text, [2-47](#)
 - index_themes, [2-47](#)
 - k_table_clause, [2-83](#)
 - maxthreads, [2-12](#)
 - maxurls, [2-12](#)
 - mixed_case, [2-41](#)
 - n_table_clause, [2-83](#)
 - new_german_spelling, [2-47](#), [17-3](#)
 - newline, [2-41](#)
 - no_proxy, [2-12](#)
 - numgroup, [2-41](#)
 - numjoin, [2-41](#)
 - output_type, [2-15](#)
 - override_base_letter, [17-3](#)
 - p_table_clause, [2-83](#)
 - path, [2-9](#)
 - printjoins, [2-41](#)
 - procedure, [2-14](#)
 - punctuations, [2-41](#)
 - r_table_clause, [2-84](#)
 - setting, [8-64](#), [8-66](#)
 - skipjoins, [2-41](#)
 - startjoins, [2-41](#)
 - stemmer, [2-72](#)
 - timeout, [2-12](#)
 - urlsize, [2-12](#)
 - viewing, [G-8](#)
 - viewing allowed values, [G-9](#)
 - whitespace, [2-41](#)
- auto optimization

- auto optimization (*continued*)
 - add indexes, [8-4](#)
 - add partitions, [8-4](#)
 - remove indexes, [8-58](#)
 - remove partitions, [8-58](#)
- AUTO stemming, [2-73](#)
- AUTO_FILTER Document Filtering Technology
 - Supported Platforms for, [B-2](#)
- AUTO_FILTER filter
 - character set conversion, [2-22](#)
 - index preference object, [2-19](#)
 - setting up, [B-1](#)
 - supported formats, [B-4](#)
 - supported platforms, [B-2](#)
 - unsupported formats, [B-2](#)
- AUTO_FILTER_OUTPUT_FORMATTING attribute, [2-23](#)
- AUTO_SECTION_GROUP example, [2-89](#)
- automatic index synchronization, [1-1](#), [1-40](#)
- available traces, [11-2](#)

B

- backslash escape character, [4-1](#)
- base_letter attribute, [2-41](#), [17-2](#)
- base_letter_type attribute, [2-41](#), [17-2](#)
- base-letter conversions, [17-2](#)
- base-letter conversions, overriding, [17-3](#)
- BASIC_LEXER object, [2-41](#)
- BASIC_LEXER system-defined preference, [2-97](#)
- BASIC_LEXER type
 - example, [2-49](#)
- BASIC_STOPLIST type, [8-39](#)
- BASIC_STORAGE object
 - attributes for, [2-81](#)
 - defaults, [2-85](#)
 - example, [2-85](#)
- BASIC_WORDLIST object
 - attributes for, [2-72](#)
 - example, [2-79](#)
- BFILE column
 - indexing, [1-42](#)
- binary attribute, [2-7](#), [2-17](#)
- binary documents
 - filtering, [2-4](#)
- BINARY format column value, [1-40](#)
- BLOB column
 - indexing, [1-42](#)
 - loading example, [C-1](#)
- brace escape character, [4-1](#)
- brackets
 - altering precedence, [3-4](#), [4-1](#)
 - grouping character, [4-1](#)
- broader term operators
 - example, [3-9](#)
- broader term query feedback, [12-7](#)
- BROWSE_WORDS procedure, [12-1](#)

- browsing words in index, [12-1](#)
- BT function, [14-4](#)
- BT operator, [3-9](#)
- BTG function, [14-6](#)
- BTG operator, [3-9](#)
- BTI function, [14-7](#)
- BTI operator, [3-9](#)
- BTP function, [14-9](#)
- BTP operator, [3-9](#)

C

- case-sensitive
 - ABOUT queries, [3-4](#)
- case-sensitive index
 - creating, [2-41](#)
- CATSEARCH operator, [1-23](#)
- CHAR column
 - indexing, [1-42](#)
- character sets
 - Chinese, [2-52](#)
 - conversion with AUTO_FILTER, [2-22](#)
 - Japanese, [2-54](#)
 - Korean, [2-56](#)
- characters
 - continuation, [2-41](#)
 - numgroup, [2-41](#)
 - numjoin, [2-41](#)
 - printjoin, [2-41](#)
 - punctuation, [2-41](#)
 - skipjoin, [2-41](#)
 - specifying for newline, [2-41](#)
 - specifying for whitespace, [2-41](#)
 - startjoin and endjoin, [2-41](#)
- charset column, [1-40](#)
- Chinese
 - fuzzy matching, [2-73](#)
- Chinese character sets supported, [2-52](#)
- Chinese lexicon, modifying, [16-12](#)
- Chinese text
 - indexing, [2-52](#)
- CHINESE_LEXER Attribute, [2-53](#)
- CHINESE_VGRAM_LEXER object, [2-52](#)
- classifying documents
 - clustering, [2-92](#), [7-4](#)
- CLOB column
 - indexing, [1-42](#)
- clump, [3-37](#)
- clump size in near operator, [3-36](#)
- clustering
 - KMEAN_CLUSTERING, [2-92](#)
 - types, [2-92](#)
- CLUSTERING procedure, [7-4](#)
- clustering types, [2-92](#)
- columns types
 - supported for CTXCAT index, [1-58](#)

- columns types (*continued*)
 - supported for CTXRULE index, [1-61](#)
 - supported for indexing, [1-42](#)
- command attribute, [2-26](#)
- compiler, lexical, [16-12](#)
- compMem element, [2-70](#)
- composite attribute
 - BASIC_LEXER, [2-41](#)
 - KOREAN_MORPH_LEXER, [2-57](#)
- composite domain index, [1-40](#)
- composite textkey
 - encoding, [9-19](#)
- composite word dictionary, [2-47](#)
- composite word index
 - creating for German or Dutch text, [2-41](#)
- composite words
 - viewing, [12-4](#)
- concordance, [9-40](#)
- CONTAINS operator
 - example, [1-29](#)
 - syntax, [1-29](#)
- CONTEXT index
 - about, [1-41](#)
 - default parameters, [2-99](#)
 - syntax, [1-40](#)
- context indextype, [1-40](#)
- continuation attribute, [2-41](#)
- control file example
 - SQL*Loader, [C-2](#)
- COPY_POLICY procedure, [8-29](#)
- CREATE INDEX statement
 - CONTEXT, [1-40](#)
 - CTXCAT, [1-40](#)
 - CTXRULE, [1-40](#)
 - default parameters, [2-99](#), [2-102](#)
 - failure, [5-1](#)
- CREATE_INDEX_SCRIPT procedure, [13-4](#)
- CREATE_INDEX_SET procedure, [8-29](#), [8-72](#), [8-73](#)
- CREATE_PHRASE procedure, [14-10](#)
- CREATE_POLICY procedure, [8-30](#)
- CREATE_POLICY_SCRIPT procedure, [13-5](#)
- CREATE_PREFERENCE procedure, [8-31](#)
- CREATE_RELATION procedure, [14-11](#)
- CREATE_SECTION_GROUP procedure, [8-34](#)
- CREATE_STOPLIST procedure, [8-39](#)
- CREATE_THESAURUS function, [14-12](#)
- CREATE_TRANSLATION procedure, [14-13](#)
- creating an index report, [13-2](#)
- CTX_ADM package
 - MARK_FAILED, [5-1](#)
 - RECOVER, [5-2](#)
 - RESET_AUTO_OPTIMIZE_STATUS, [5-2](#)
 - SET_PARAMETER, [5-3](#)
- CTX_ADM.MARK_FAILED, [5-1](#)
- CTX_AUTO_OPTIMIZE_INDEXES view, [G-3](#)
- CTX_AUTO_OPTIMIZE_STATUS view, [G-3](#)

CTX_CLASSES view, [G-3](#), [G-4](#), [G-9](#), [G-17](#), [G-21](#)

CTX_CLS

CLUSTERING, [7-4](#)

TRAIN, [7-1](#)

CTX_DDL package

ADD_ATTR_SECTION, [8-3](#)

ADD_AUTO_OPTIMIZE, [8-4](#)

ADD_FIELD_SECTION, [8-5](#)

ADD_MDATA, [8-9](#), [8-11](#)

ADD_MDATA_SECTION, [8-12](#)

ADD_SDATA_COLUMN, [8-14](#)

ADD_SDATA_SECTION, [8-16](#)

ADD_SPECIAL_SECTION, [8-18](#)

ADD_STOP_SECTION, [8-21](#)

ADD_STOPCLASS, [8-19](#)

ADD_STOPTHEME, [8-22](#)

ADD_STOPWORD, [8-23](#)

ADD_SUB_LEXER, [8-24](#)

ADD_ZONE_SECTION, [8-26](#)

COPY_POLICY, [8-29](#)

CREATE_INDEX_SET, [8-29](#), [8-72](#), [8-73](#)

CREATE_POLICY, [8-30](#)

CREATE_PREFERENCE, [8-31](#)

CREATE_SECTION_GROUP, [8-34](#)

CREATE_STOPLIST, [8-39](#)

DROP_POLICY, [8-40](#)

DROP_PREFERENCE, [8-41](#)

DROP_STOPLIST, [8-42](#)

OPTIMIZE_INDEX procedure, [8-44](#)

PREFERENCE_IMPLICIT_COMMIT variable,
[8-50](#)

REMOVE_AUTO_OPTIMIZE, [8-58](#)

REMOVE_MDATA, [8-59](#)

REMOVE_SECTION, [8-60](#)

REMOVE_STOPCLASS, [8-61](#)

REMOVE_STOPTHEME, [8-61](#)

REMOVE_STOPWORD, [8-62](#)

REMOVE_SUB_LEXER, [8-63](#)

REPLACE_INDEX_METADATA, [8-63](#)

SET_ATTRIBUTE, [8-64](#)

SET_SECTION_ATTRIBUTE, [8-66](#)

SYNC_INDEX procedure, [8-68](#)

UNSET_ATTRIBUTE, [8-70](#), [8-71](#)

UPDATE_SUB_LEXER, [8-71](#)

CTX_DDL.ADD_INDEX procedure, [8-8](#)

CTX_DOC package

FILTER, [9-2](#)

GIST, [9-5](#)

HIGHLIGHT, [9-9](#)

IFILTER, [9-12](#)

MARKUP, [9-13](#)

PKENCODE, [9-19](#)

POLICY_FILTER, [9-20](#)

POLICY_GIST, [9-21](#)

POLICY_HIGHLIGHT, [9-23](#)

POLICY_MARKUP, [9-26](#)

CTX_DOC package (*continued*)

POLICY_SNIPPET, [9-34](#)

POLICY_THEMES, [9-37](#)

POLICY_TOKENS, [9-39](#)

result tables, [A-6](#)

SET_KEY_TYPE, [9-40](#)

SNIPPET, [9-40](#)

THEMES, [9-44](#)

TOKENS, [9-47](#)

CTX_FEEDBACK_ITEM_TYPE type, [A-5](#)

CTX_FEEDBACK_TYPE type, [12-9](#), [A-5](#)

CTX_FILTER_CACHE_STATISTICS view, [G-4](#)

CTX_INDEX_ERRORS view

example, [1-58](#)

CTX_INDEX_OBJECTS view, [G-6](#)

CTX_INDEX_SET_INDEXES view

views

CTX_INDEX_SET_INDEXES, [G-7](#)

CTX_INDEX_SUB_LEXERS view, [G-7](#), [G-21](#)

CTX_INDEX_SUB_LEXERS_VALUES view, [G-7](#)

CTX_INDEX_VALUES view, [G-8](#)

CTX_INDEXES view, [G-5](#)

CTX_OBJECT_ATTRIBUTE_LOV view, [G-9](#)

CTX_OBJECT_ATTRIBUTES view, [G-8](#)

CTX_OBJECTS view, [G-8](#)

CTX_OUTPUT package

ADD_EVENT, [11-1](#)

ADD_TRACE, [11-2](#)

DISABLE_QUERY_STATS, [11-4](#)

ENABLE_QUERY_STATS, [11-4](#)

END_LOG, [11-5](#)

GET_TRACE_VALUE, [11-6](#)

LOG_TRACES, [11-6](#)

LOGFILENAME, [11-7](#)

REMOVE_EVENT, [11-7](#)

REMOVE_TRACE, [11-8](#)

RESET_TRACE, [11-8](#)

START_LOG, [11-9](#)

CTX_PARAMETERS view, [2-98](#), [G-10](#)

CTX_PENDING view, [G-11](#)

CTX_PREFERENCE_VALUES view, [G-12](#)

CTX_PREFERENCES view, [G-12](#)

CTX_QUERY package

BROWSE_WORDS, [12-1](#)

EXPLAIN, [12-4](#)

HFEEDBACK, [12-7](#)

REMOVE_SQE, [12-10](#)

result tables, [A-1](#)

STORE_SQE, [12-18](#)

CTX_QUERY.disable_transactional_query session
variable, [1-54](#)

CTX_REPORT output format, [13-2](#), [13-3](#), [13-5](#), [13-6](#),
[13-14](#)

CTX_REPORT package

CREATE_INDEX_SCRIPT, [13-4](#)

CREATE_POLICY_SCRIPT, [13-5](#)

CTX_REPORT package (*continued*)
 DESCRIBE_INDEX, [13-2](#)
 DESCRIBE_POLICY, [13-3](#)
 function versions of procedures, [13-2](#)
 INDEX_SIZE, [13-5](#)
 INDEX_STATS, [13-6](#)
 QUERY_LOG_SUMMARY, [13-10](#)
 TOKEN_INFO, [13-14](#)
 TOKEN_TYPE, [13-15](#)
 CTX_SECTION_GROUPS view, [G-13](#)
 CTX_SECTIONS view, [G-12](#)
 CTX_SQES view, [G-13](#)
 CTX_STOPLISTS view, [G-13](#)
 CTX_STOPWORDS view, [G-14](#)
 CTX_SUB_LEXERS view, [G-14](#)
 CTX_THES package
 ALTER_PHRASE, [14-2](#)
 ALTER_THESAURUS, [14-4](#)
 BT, [14-4](#)
 BTG, [14-6](#)
 BTI, [14-7](#)
 BTP, [14-9](#)
 CREATE_PHRASE, [14-10](#)
 CREATE_RELATION, [14-11](#)
 CREATE_THESAURUS, [14-12](#)
 DROP_PHRASE, [14-13](#)
 DROP_RELATION, [14-14](#)
 DROP_THESAURUS, [14-16](#)
 NT, [14-19](#)
 NTG, [14-21](#)
 NTI, [14-22](#)
 NTP, [14-24](#)
 OUTPUT_STYLE, [14-25](#)
 PT, [14-25](#)
 result tables, [A-9](#)
 RT, [14-27](#)
 SN, [14-28](#)
 SYN, [14-28](#)
 THES_TT, [14-30](#)
 TR, [14-31](#)
 TRSYN, [14-32](#)
 TT, [14-34](#)
 CTX_THES.CREATE_TRANSLATION, [14-13](#)
 CTX_THES.DROP_TRANSLATION, [14-16](#)
 CTX_THES.UPDATE_TRANSLATION, [14-35](#)
 CTX_THESAURI view, [G-14](#)
 CTX_TRACE_VALUES view, [G-15](#)
 CTX_ULEXER package, [15-1](#)
 CTX_USER_AUTO_OPTIMIZE_STATUS view, [G-15](#)
 CTX_USER_INDEX_ERRORS view
 example, [1-58](#)
 CTX_USER_INDEX_OBJECTS view, [G-19](#)
 CTX_USER_INDEX_SET_INDEXES view, [G-20](#)
 CTX_USER_INDEX_SETS view, [G-20](#)
 CTX_USER_INDEX_SUB_LEXERS view, [G-20](#)
 CTX_USER_INDEX_VALUES view, [G-21](#)
 CTX_USER_INDEXES view, [G-17](#)
 CTX_USER_PENDING view, [G-22](#)
 CTX_USER_PREFERENCE_VALUES view, [G-22](#)
 CTX_USER_PREFERENCES view, [G-22](#)
 CTX_USER_SECTION_GROUPS view, [G-23](#)
 CTX_USER_SECTIONS view, [G-23](#)
 CTX_USER_SQES view, [G-23](#)
 CTX_USER_STOPLISTS view, [G-24](#)
 CTX_USER_STOPWORDS view, [G-24](#)
 CTX_USER_SUB_LEXERS view, [G-24](#)
 CTX_USER_THES_PHRASES view, [G-25](#)
 CTX_USER_THESAURI view, [G-25](#)
 CTX_VERSION view, [G-25](#)
 CTXCAT index
 about, [1-40](#)
 default parameters, [2-101](#)
 supported preferences, [1-40](#)
 syntax, [1-40](#)
 unsupported preferences, [1-40](#)
 CTXFILTERCACHE operator, [3-11](#)
 ctxkbt compiler, [16-6](#)
 ctxlc (lexical compiler), [16-12](#)
 ctxload
 examples, [16-3](#)
 import file structure, [C-3](#)
 CTXRULE index
 about, [1-40](#)
 and Asian languages, [D-2](#)
 and multilingual support, [D-2](#)
 default parameters, [2-101](#)
 lexer types, [1-40](#)
 syntax, [1-40](#)
 CTXRULE Index Limitations, [2-101](#)
 CTXSYS.AUTO_FILTER system preference, [2-20](#)
 CTXSYS.DEFAULT_STOPLIST, [2-94](#)
 CTXSYS.INSO_FILTER system preference
 (deprecated), [2-21](#)

D

Danish
 alternate spelling, [17-4](#)
 index defaults, [2-96](#)
 supplied stoplist, [E-6](#)
 data storage
 defined procedurally, [2-14](#)
 direct, [2-3](#)
 example, [8-32](#)
 external, [2-9](#)
 master/detail, [2-7](#)
 URL, [2-11](#)
 datastore types, [2-2](#)
 DBMS_PCLUTIL
 BUILD_PART_INDEX, [1-57](#)
 default index
 example, [1-54](#)

- default parameters
 - changing, [2-99](#)
 - CONTEXT index, [2-99](#)
 - CTXCAT index, [2-101](#)
 - CTXRULE index, [2-101](#)
 - viewing, [2-99](#)
- DEFAULT thesaurus, [3-10](#), [3-33](#)
- DEFAULT_CTXRULE_LEXER system parameter, [2-101](#)
- DEFAULT_CTXRULE_STOPLIST system parameter, [2-101](#)
- DEFAULT_CTXRULE_WORDLIST system parameter, [2-102](#)
- DEFAULT_DATASTORE system-defined indexing preference, [2-95](#)
- DEFAULT_RULE_STORAGE system parameter, [2-101](#)
- DEFAULT_STORAGE system-defined preference, [2-98](#)
- DEFAULT_WORDLIST system-defined preference, [2-98](#)
- defaults for indexing
 - viewing, [G-10](#)
- definemerge operator, [3-14](#)
- definescore operator, [3-15](#)
- derivational stemming
 - enabling for English, [2-72](#)
- DESCRIBE_INDEX procedure, [13-2](#)
- DESCRIBE_POLICY procedure, [13-3](#)
- describing an index, [13-2](#)
- DETAIL_DATASTORE object
 - example, [2-7](#)
- detail_key attribute, [2-7](#)
- detail_lineno attribute, [2-7](#)
- detail_table attribute, [2-7](#)
- detail_text attribute, [2-7](#)
- dictionary
 - Chinese, [16-12](#)
 - Japanese, [16-12](#)
 - Korean, [2-56](#)
 - modifying, [16-12](#)
 - user, [2-47](#)
- DIRECT_DATASTORE object
 - example, [2-3](#)
- DISABLE_QUERY_STATS procedure, [11-4](#)
- disabling transactional queries, [1-54](#)
- disambiguators
 - in thesaural queries, [3-9](#)
 - in thesaurus import file, [C-6](#)
- DML
 - affect on scoring, [F-2](#)
- DML errors
 - viewing, [G-6](#)
- DML processing
 - batch, [1-1](#)
- DML queue
 - viewing, [G-11](#)
- document
 - document (*continued*)
 - classifying, [7-1](#)
 - clustering, [7-4](#)
 - filtering to HTML and plain text, [9-2](#)
 - document filtering
 - AUTO_FILTER, [B-1](#)
 - document formats
 - supported, [B-4](#)
 - unsupported, [B-2](#)
 - document loading
 - SQL*Loader, [C-1](#)
 - document presentation
 - procedures, [9-1](#)
 - document services
 - logging
 - requests, [11-9](#)
 - domain index, [1-40](#)
 - double-truncated queries, [3-52](#)
 - double-truncated searching
 - improving performance, [2-72](#)
 - DROP INDEX statement, [1-63](#)
 - DROP_PHRASE procedure, [14-13](#)
 - DROP_POLICY procedure, [8-40](#)
 - DROP_PREFERENCE procedure, [8-41](#)
 - DROP_RELATION procedure, [14-14](#)
 - DROP_STOPLIST procedure, [8-42](#)
 - DROP_THESAURUS procedure, [14-16](#)
 - DROP_TRANSLATION procedure, [14-16](#)
 - duplicating indexes with scripts, [13-4](#)
 - duplicating policy with script, [13-5](#)
 - Dutch
 - composite word indexing, [2-41](#)
 - fuzzy matching, [2-73](#)
 - index defaults, [2-96](#)
 - stemming, [2-73](#)
 - supplied stoplist, [E-8](#)

E

- e-mail
 - filtering and indexing, [2-22](#)
- embedded graphics, [B-8](#)
- empty index
 - creating, [1-40](#)
 - POPULATE | NOPOPULATE and, [1-52](#)
- EMPTY_STOPLIST system-defined preference, [2-98](#)
- ENABLE_QUERY_STATS procedure, [11-4](#)
- enabling tracing, [11-2](#)
- END_LOG procedure, [11-5](#)
- END_QUERY_LOG procedure, [11-5](#)
- ending a log, [11-5](#)
- ending a query log, [11-5](#)
- endjoins attribute, [2-41](#)
- English
 - fuzzy matching, [2-73](#)
 - index defaults, [2-96](#)
 - supplied stoplist, [E-1](#)

- english attribute (Korean lexer), [2-57](#)
- entity extraction, [10-1](#)
- environment variables
 - setting for AUTO_FILTER filter, [B-4](#)
- equivalence operator
 - stopword transformations, [H-5](#)
 - with NEAR, [3-36](#)
- errors
 - indexing, [1-58](#)
- escaping special characters, [4-1](#)
- event
 - adding, [11-1](#)
 - removing, [11-7](#)
- EVERY parameter, [1-1](#), [1-40](#)
- EXP_TAB table type, [A-9](#)
- expansion operator
 - soundex, [3-45](#)
 - stem, [3-45](#)
 - viewing, [12-4](#)
- EXPLAIN procedure
 - example, [12-6](#)
 - result table, [A-1](#)
- explain table
 - creating, [12-6](#)
 - retrieving data example, [12-6](#)
 - structure, [A-1](#)
- EXPORT_THESAURUS procedure, [14-17](#)
- extending knowledge base, [16-6](#)
- external filters
 - specifying, [2-26](#)

F

- failed index operation
 - resuming, [1-1](#)
- failure of index loading, [5-1](#)
- fast filtering, [2-23](#)
- field section
 - adding dynamically, [1-1](#)
 - defining, [8-5](#)
 - limitations, [8-5](#)
 - querying, [3-54](#)
 - repeated, [3-54](#)
 - WITHIN example, [3-54](#)
- file data storage
 - example, [8-32](#)
- FILE_DATASTORE object
 - example, [2-11](#)
- filter
 - INSO (deprecated), [2-20](#)
- filter attribute
 - MULTI_COLUMN_DATASTORE, [2-4](#)
- FILTER BY, [1-40](#)
- FILTER BY and ORDER BY with creating an index
 - example, [1-56](#)
- filter formats
 - supported, [B-4](#)

- FILTER procedure
 - example, [9-5](#)
 - in-memory example, [9-4](#)
 - result table, [A-7](#)
- filter table
 - structure, [A-7](#)
- filter types, [2-19](#)
- filtering
 - fast, with
 - AUTO_FILTER_OUTPUT_FORMATTING attribute, [2-23](#)
 - multi_column_datastore, [2-4](#)
 - stored procedures, [2-29](#)
 - to plain text, [9-12](#)
 - to plain text and HTML, [9-2](#)
- filters
 - AUTO_FILTER, [2-19](#), [B-1](#)
 - user, [2-26](#)
- Finnish
 - index defaults, [2-96](#)
 - supplied stoplist, [E-16](#)
- format column, [1-40](#)
- formatted documents
 - filtering, [2-19](#)
- fragmentation of index, [1-52](#)
- French
 - fuzzy matching, [2-73](#)
 - supplied stoplist, [E-22](#)
- French stemming, [2-73](#)
- ftp_proxy attribute, [2-12](#)
- fuzzy matching
 - automatic language detection, [2-73](#)
 - example for enabling, [2-79](#)
 - specifying a language, [2-75](#)
- fuzzy operator, [3-20](#)
- fuzzy_match attribute, [2-72](#)
- fuzzy_numresults attribute, [2-72](#)
- fuzzy_score attribute, [2-72](#)

G

- German
 - alternate spelling attribute, [2-47](#)
 - alternate spelling conventions, [17-4](#)
 - composite word indexing, [2-41](#)
 - fuzzy matching, [2-73](#)
 - index defaults, [2-96](#)
 - new spelling, querying with, [2-47](#), [17-3](#)
 - stemming, [2-73](#)
 - supplied stoplist, [E-28](#)
- GET_TRACE_VALUE procedure, [11-6](#)
- gist
 - generating, [9-5](#)
 - generating with POLICY_GIST, [9-21](#)
- GIST procedure
 - example, [9-8](#)
 - result table, [A-7](#)

GIST procedure (*continued*)
updated syntax, [9-5](#)

Gist table
structure, [A-7](#)

graphics
embedded, [B-8](#)
standalone, [B-8](#)

H

hanja attribute, [2-57](#)
HASPETH operator
and special characters, [3-22](#)
HFEEDBACK procedure
example, [12-8](#)
result table, [A-3](#)
hierarchical query feedback information
generating, [12-7](#)
hierarchical relationships
in thesaurus import file, [C-6](#)
HIGHLIGHT procedure
example, [9-12](#)
result table, [A-7](#)
highlight table
example, [9-11](#), [9-12](#)
structure, [A-7](#)
highlighting
generating markup, [9-13](#), [9-26](#)
generating offsets, [9-9](#), [9-23](#)
with NEAR operator, [3-36](#)
homographs
in broader term queries, [3-10](#)
in queries, [3-9](#)
in thesaurus import file, [C-6](#)
HTML
bypassing filtering, [2-21](#)
filtering to, [9-2](#)
generating, [9-20](#)
generating highlight offsets for, [9-9](#), [9-23](#)
highlight markup, [9-13](#), [9-26](#)
highlighting example, [9-18](#)
indexing, [2-22](#)
zone section example, [8-27](#)
HTML_SECTION_GROUP
example, [2-88](#)
HTML_SECTION_GROUP object
with NULL_FILTER, [2-22](#)
http_proxy attribute, [2-12](#)

I

i_index_clause attribute, [2-82](#)
i_table_clause attribute, [2-83](#)
IFILTER procedure, [9-12](#)
IGNORE format column value, [1-40](#)
import file
examples of, [C-7](#)

import file (*continued*)
structure, [C-3](#)

IMPORT_THESAURUS procedure, [14-18](#)

index
creating, [1-40](#)
creating a report on, [13-2](#)
creating index script, [13-4](#)
describing, [13-2](#)
duplicating with script, [13-4](#)
loading failure, [5-1](#)
renaming, [1-1](#)
script, [13-4](#)
show size of objects, [13-5](#)
show statistics, [13-6](#)
synchronizing, [1-1](#), [1-40](#)
transactional, [12-4](#)
transactional CONTEXT, [1-9](#), [1-53](#)
viewing registered, [G-5](#)

index creation
custom preference example, [1-54](#)
default example, [1-54](#)

index creation parameters
example, [2-85](#)

index errors
deleting, [1-58](#)
viewing, [1-58](#)

index fragmentation, [1-52](#)

index maintenance, [1-1](#)

index objects
viewing, [G-6](#), [G-8](#)

index preference
about, [2-1](#)
creating, [2-2](#), [8-31](#)

index reports, [13-1](#)

index requests
logging, [11-9](#)

index status, [5-1](#)

index tablespace parameters
specifying, [2-80](#)

index tokens
generating for a document, [9-39](#), [9-47](#)

INDEX_PROCEDURE user_lexer attribute, [2-60](#)

INDEX_SIZE procedure, [13-5](#)

INDEX_STATS procedure, [13-6](#)

index_stems attribute, [2-47](#)

index_text attribute, [2-47](#)

index_themes attribute, [2-47](#)

index-organized table, [1-41](#)

indexing
master/detail example, [2-9](#)
multilingual documents, [2-49](#), [2-71](#), [D-5](#)
parallel, [1-1](#), [1-40](#)
themes, [2-47](#)

indexing types
classifier, [2-90](#)
clustering, [2-92](#)
datastore, [2-2](#)

- indexing types (*continued*)
 - filter, [2-19](#)
 - lexer, [2-32](#)
 - section group, [2-86](#)
 - storage, [2-80](#)
 - vs. preferences, [2-2](#)
 - wordlist, [2-72](#)
- indexless document services, see policy-based document services, [9-2](#)
- indextype context, [1-40](#)
- inflectional stemming
 - enabling, [2-72](#)
- INPATH operator
 - and special characters, [3-22](#)
- INPUT_TYPE user_lexer attribute, [2-60](#)
- INSERT statement
 - loading example, [C-1](#)
- INSO_FILTER (deprecated), [2-20](#)
- inverse frequency scoring, [F-1](#)
- Italian
 - fuzzy matching, [2-73](#)
 - stemming, [2-73](#)
 - supplied stoplist, [E-35](#)

J

- JA16EUC character set, [2-54](#), [2-55](#)
- JA16EUCTILDE character set, [2-54](#), [2-55](#)
- JA16EUCYEN character set, [2-54](#), [2-55](#)
- JA16SJIS character set, [2-54](#), [2-55](#)
- JA16SJISTILDE character set, [2-54](#), [2-55](#)
- JA16SJISYEN character set, [2-54](#), [2-55](#)
- Japanese
 - fuzzy matching, [2-73](#)
 - index defaults, [2-97](#)
 - indexing, [2-53](#)
 - stemming, [2-73](#)
- japanese attribute (Korean lexer), [2-57](#)
- Japanese character sets supported, [2-54](#)
- Japanese EUC character set, [2-54](#)
- Japanese lexicon, modifying, [16-12](#)
- Japanese stemming, [2-73](#), [3-45](#)
- JAPANESE_LEXER, [2-54](#)
- JAPANESE_LEXER Attributes, [2-54](#)
- JAPANESE_VGRAM_LEXER Attributes, [2-53](#)
- JAPANESE_VGRAM_LEXER object, [2-53](#)
- JOB_QUEUE_PROCESSES initialization parameter, [1-40](#)
- JSON_SECTION_GROUP, [2-87](#), [8-35](#)

K

- k_table_clause attribute, [2-83](#)
- Key Word in Context. See KWIC, [9-40](#)
- KMEAN_CLUSTERING object, [2-92](#)
- knowledge base

- knowledge base (*continued*)
 - supported character set, [16-7](#)
 - user-defined, [16-11](#)
- knowledge base extension compiler, [16-6](#)
- KO16KSC5601 character set, [2-56](#)
- KO16MSWIN949 character set, [2-56](#)
- Korean
 - fuzzy matching, [2-73](#)
 - index defaults, [2-97](#)
 - unicode character support, [2-56](#)
- korean character sets supported, [2-56](#)
- Korean text
 - indexing, [2-55](#)
- KOREAN_MORPH_LEXER
 - composite example, [2-58](#)
 - supplied dictionaries, [2-56](#)
 - Unicode support, [2-56](#)
- KOREAN_MORPH_LEXER Attributes, [2-57](#)
- KWIC (Key Word in Context), [9-40](#)

L

- language
 - setting, [2-32](#)
- language column, [1-40](#)
- language-independent lexer template, [1-33](#)
- left-truncated searching
 - improving performance, [2-72](#)
- lexer types
 - and CTXRULE index, [1-40](#)
- lexical compiler, [16-12](#)
- lexicon. See entries under *dictionary*, [16-12](#)
- loading text
 - SQL INSERT example, [C-1](#)
 - SQL*Loader example, [C-1](#)
- loading thesaurus, [16-1](#)
- LOB columns
 - loading, [C-1](#)
- local partition index
 - parallelism, [1-56](#)
- local partitioned index, [1-40](#)
- LOG_DIRECTORY system parameter, [11-7](#)
- LOG_TRACES procedure, [11-6](#)
- LOGFILENAME procedure, [11-7](#)
- logging
 - ending, [11-5](#)
 - ending a log, [11-5](#)
 - getting log file name, [11-7](#)
 - index requests, [11-9](#)
- logging queries, [13-10](#)
- logging traces, [11-6](#)
- logical operators
 - with NEAR, [3-36](#)
- LONG columns
 - indexing, [1-42](#)
- long_word attribute, [2-57](#)

M

- mail filter configuration file, [2-24](#)
- mail filtering, see e-mail, [2-22](#)
- MAIL_FILTER object, [2-22](#)
- MAIL_FILTER_CONFIG_FILE system parameter, [2-24](#)
- maintaining index, [1-1](#)
- MARK_FAILED procedure, [5-1](#)
- MARKUP procedure
 - example, [9-18](#)
 - HTML highlight example, [9-18](#)
 - result table, [A-8](#)
- markup table
 - example, [9-18](#)
 - structure, [A-8](#)
- master/detail data storage
 - example, [2-7](#), [8-33](#)
- master/detail tables
 - indexing example, [2-9](#)
- MATCH_SCORE operator, [1-65](#)
- MATCHES operator, [1-63](#)
- max_span parameter in near operator, [3-36](#)
- maxthreads attribute, [2-12](#)
- maxurls attribute, [2-12](#)
- MDATA operator, [3-29](#)
- MDATA section, [8-9](#), [8-11](#), [8-12](#), [8-59](#)
- memory
 - for indexing, [1-40](#), [8-69](#)
- META tag
 - creating field sections for, [8-7](#)
 - creating zone section for, [8-27](#)
- metadata
 - replacing, [8-63](#)
- METADATA keyword
 - ALTER INDEX example, [1-15](#)
- metadata section, [8-9](#), [8-11](#), [8-12](#), [8-59](#)
- MINUS operator
 - stopword transformations, [H-4](#)
- mixed_case attribute, [2-41](#)
- mixed-format columns
 - filtering, [2-19](#)
 - indexing, [2-21](#)
 - supported formats for, [B-4](#)
- modifying user dictionary, [16-12](#)
- morpheme attribute, [2-57](#)
- MULTI_COLUMN_DATASTORE Restriction, [2-5](#)
- MULTI_LEXER object
 - CREATE INDEX example, [1-55](#)
 - example, [2-50](#)
- MULTI_LEXER type, [2-49](#)
- MULTI_STOPLIST type, [8-39](#)
- multi-language indexing, [2-49](#), [2-71](#), [8-24](#), [D-5](#)
- multi-language stoplist, [2-50](#), [2-94](#)
- multi-language tables
 - querying, [1-39](#), [2-51](#)
- multi-lexer example
 - migrating from single language, [1-15](#)

N

- n_table_clause attribute, [2-83](#)
- narrower term operators
 - example, [3-32](#)
- narrower term query feedback, [12-7](#)
- NEAR operator
 - backward compatibility, [3-36](#)
 - highlighting, [3-36](#)
 - scoring, [3-36](#)
 - stopword transformations, [H-5](#)
 - with other operators, [3-36](#)
 - with within, [3-54](#)
- nested section searching, [3-54](#)
- nested zone sections, [8-28](#)
- nested_column attribute, [2-17](#)
- NESTED_DATASTORE attribute, [2-17](#)
- NESTED_DATASTORE object, [2-16](#)
- nested_lineno attribute, [2-17](#)
- nested_text attribute, [2-17](#)
- nested_type attribute, [2-17](#)
- new_german_spelling attribute, [2-47](#), [17-3](#)
- newline attribute, [2-41](#)
- NLS_LENGTH_SEMANTICS parameter, [1-50](#)
- no_proxy attribute, [2-12](#)
- nopopulate index parameter, [1-40](#)
- nopopulate parameter, [1-40](#)
- normalization_expr attribute, [1-34](#)
- normalized word forms, [17-1](#)
- Norwegian
 - index defaults, [2-96](#)
- NOT operator
 - stopword transformations, [H-4](#)
- NT function, [14-19](#)
- NT operator, [3-32](#)
- NTG function, [14-21](#)
- NTG operator, [3-32](#)
- NTI function, [14-22](#)
- NTI operator, [3-32](#)
- NTP function, [14-24](#)
- NTP operator, [3-32](#)
- NULL_FILTER object, [2-22](#)
- number attribute, [2-57](#)
- numgroup attribute, [2-41](#)
- numjoin attribute, [2-41](#)

O

- object values
 - viewing, [G-8](#)
- objects
 - viewing index, [G-8](#)
- offsets for highlighting, [9-9](#), [9-23](#)
- on commit, [1-1](#), [1-40](#)
- one_char_word attribute, [2-57](#)
- ONLINE

ONLINE (*continued*)
 CREATE INDEX and, [1-40](#)
 OPERATION column of explain table
 values, [A-2](#)
 operator
 ABOUT, [3-4](#)
 accumulate, [3-7](#)
 broader term, [3-9](#)
 equivalence, [3-19](#)
 fuzzy, [3-20](#)
 HASPETH, [3-21](#)
 INPATH, [3-23](#)
 MATCH_SCORE, [1-65](#)
 MATCHES, [1-63](#)
 MDATA, [3-29](#)
 MINUS, [3-31](#)
 narrower term, [3-32](#)
 NEAR, [3-36](#)
 NOT, [3-39](#)
 OR, [3-40](#)
 preferred term, [3-41](#)
 related term, [3-41](#)
 SCORE, [1-65](#)
 scoring, [3-14](#), [3-15](#)
 SDATA, [3-42](#)
 soundex, [3-45](#)
 SQE, [3-46](#)
 stem, [3-45](#)
 synonym, [3-47](#)
 threshold, [3-48](#)
 top term, [3-50](#)
 TRANSFORM, [1-31](#)
 translation term, [3-11](#), [3-48](#)
 translation term synonym, [3-49](#)
 weight, [3-51](#)
 WITHIN, [3-54](#)
 operator expansion
 viewing, [12-4](#)
 operator precedence
 examples, [3-3](#)
 viewing, [12-5](#)
 operators, [3-1](#)
 optimization
 strategies, [8-44](#)
 OPTIMIZE_INDEX procedure, [8-44](#)
 OPTIONS column
 explain table, [A-3](#)
 hfeedback table, [A-5](#)
 OR operator
 stopword transformations, [H-3](#)
 ORDER BY
 Limitations with PL/SQL Packages, [1-46](#)
 original word forms, [17-1](#)
 OUTPUT_STYLE procedure, [14-25](#)
 output_type attribute, [2-15](#)
 overlapping zone sections, [8-28](#)

override_base_letter attribute, [17-3](#)
 overriding alternate spelling, [17-3](#)
 overriding base-letter conversions, [17-3](#)

P

p_table_clause, [2-83](#)
 PARAGRAPH keyword, [3-54](#)
 paragraph section
 defining, [8-18](#)
 querying, [3-54](#)
 parallel index creation, [1-56](#)
 parallel indexing
 DBMS_PCLUTIL.BUILD_PART_INDEX, [1-57](#)
 example, [1-56](#)
 local partitioned index, [1-40](#)
 parameter
 transactional, [1-9](#), [1-53](#)
 parameters
 setting, [5-3](#)
 viewing system-defined, [G-10](#)
 parentheses
 altering precedence, [3-4](#), [4-1](#)
 grouping character, [4-1](#)
 partitioned index
 creating local in parallel, [1-40](#)
 example, [1-55](#)
 local, [1-40](#)
 parallel creation, [1-57](#)
 rebuild example, [1-15](#)
 partitioned index creation
 example, [1-56](#)
 partitioned tables
 modifying, [1-18](#)
 path attribute, [2-9](#)
 PATH_SECTION_GROUP system-defined preference,
 [2-98](#)
 pending DML
 viewing, [G-11](#)
 performance
 wildcard searches, [3-52](#)
 PKENCODE function, [9-19](#)
 plain text
 bypassing filtering, [2-21](#)
 filtering to, [9-2](#), [9-12](#)
 highlight markup, [9-13](#), [9-26](#)
 indexing with NULL_FILTER, [2-22](#)
 offsets for highlighting, [9-9](#)
 policy
 create script, [13-5](#)
 duplicate with script, [13-5](#)
 report describing, [13-3](#)
 POLICY_FILTER procedure, [9-20](#)
 POLICY_GIST procedure, [9-21](#)
 POLICY_HIGHLIGHT procedure, [9-23](#)
 POLICY_MARKUP procedure, [9-26](#)
 POLICY_SNIPPET procedure, [9-34](#)

- POLICY_THEMES procedure
 - syntax, [9-37](#)
- POLICY_TOKENS procedure
 - syntax, [9-39](#)
- policy-based document services, [9-2](#)
- populate index parameter, [1-40](#)
- populate parameter, [1-40](#)
- Portuguese
 - supplied stoplist, [E-40](#)
- precedence of operators
 - altering, [3-4](#), [4-1](#)
 - equivalence operator, [3-20](#)
 - example, [3-3](#)
 - viewing, [12-4](#)
- preference classes
 - viewing, [G-3](#), [G-4](#), [G-9](#), [G-17](#), [G-21](#)
- preference values
 - viewing, [G-12](#)
- PREFERENCE_IMPLICIT_COMMIT, [8-50](#)
- preferences
 - about, [2-1](#)
 - changing, [1-1](#)
 - creating, [8-31](#)
 - dropping, [8-41](#)
 - replacing, [1-1](#)
 - specifying for indexing, [1-40](#)
 - system-defined, [2-95](#)
 - viewing, [G-12](#)
 - vs. types, [2-2](#)
- preferred term operator
 - example, [3-41](#)
- prefix_index attribute, [2-72](#)
- prefix_max_length attribute, [2-72](#)
- prefix_min_length attribute, [2-72](#)
- printjoins attribute, [2-41](#)
- privileges
 - required for indexing, [1-41](#)
- procedure
 - COPY_POLICY, [8-29](#)
 - CTX_DDL.ADD_INDEX, [8-8](#)
 - CTX_DDL.REPLACE_INDEX_METADATA, [8-63](#)
 - CTX_OUTPUT.LOG_TRACES, [11-6](#)
 - CTX_OUTPUT.ADD_TRACE, [11-2](#)
 - CTX_OUTPUT.END_QUERY_LOG, [11-5](#)
 - CTX_OUTPUT.GET_TRACE_VALUE, [11-6](#)
 - CTX_OUTPUT.REMOVE_TRACE, [11-8](#)
 - CTX_OUTPUT.RESET_TRACE, [11-8](#)
- procedure attribute, [2-14](#)
- PROCEDURE_FILTER object, [2-29](#)
- progressive relaxation template, [1-32](#)
- prove_themes attribute, [2-47](#)
- proximity operator, see NEAR operator, [3-36](#)
- PT function, [14-25](#)
- PT operator, [3-41](#)
- punctuations attribute, [2-41](#)

Q

- query
 - accumulate, [3-7](#)
 - analysis, [13-10](#)
 - AND, [3-8](#)
 - broader term, [3-9](#)
 - equivalence, [3-19](#)
 - example, [1-29](#)
 - hierarchical feedback, [12-7](#)
 - MINUS, [3-31](#)
 - narrower term, [3-32](#)
 - NOT, [3-39](#)
 - on unsynched index, [1-53](#)
 - OR, [3-40](#)
 - preferred term, [3-41](#)
 - related term, [3-41](#)
 - report of logged, [13-10](#)
 - scoring, [3-14](#), [3-15](#)
 - stored, [3-46](#)
 - synonym, [3-47](#)
 - threshold, [3-48](#)
 - top term, [3-50](#)
 - transactional, [1-53](#), [12-4](#)
 - translation term, [3-11](#), [3-48](#)
 - translation term synonym, [3-49](#)
 - weighted, [3-51](#)
- query relaxation template, [1-32](#)
- query rewrite template, [1-30](#)
- query template, [1-25](#), [1-29](#)
- query_filter_cache_size basic storage attribute, [2-83](#)
- QUERY_LOG_SUMMARY procedure, [13-10](#)
- QUERY_PROCEDURE user_lexer attribute, [2-62](#)

R

- r_table_clause, [2-84](#)
- rebuilding index
 - example, [1-15](#)
 - syntax, [1-1](#)
- RECOVER procedure, [5-2](#)
- related term operator, [3-41](#)
- related term query feedback, [12-7](#)
- relaxing queries, [1-32](#)
- relevance ranking
 - word queries, [F-1](#)
- REMOVE_AUTO_OPTIMIZE procedure, [8-58](#)
- REMOVE_EVENT procedure, [11-7](#)
- REMOVE_METADATA procedure, [8-59](#)
- REMOVE_SECTION procedure, [8-60](#)
- REMOVE_SQE procedure, [12-10](#)
- REMOVE_STOPCLASS procedure, [8-61](#)
- REMOVE_STOPTHEME procedure, [8-61](#)
- REMOVE_STOPWORD procedure, [8-62](#)
- REMOVE_SUB_LEXER procedure, [8-63](#)
- REMOVE_TRACE procedure, [11-8](#)

- removing a trace, [11-8](#)
- removing metadata, [8-59](#)
- renaming index, [1-1](#)
- repeated field sections
 - querying, [3-54](#)
- REPLACE_INDEX_METADATA procedure, [8-63](#)
- replacing, [1-1](#)
- replacing metadata, [1-1](#)
- replacing preferences, [1-1](#)
- report
 - describing index, [13-2](#)
 - describing policy, [13-3](#)
 - index objects, [13-5](#)
 - index size, [13-5](#)
 - index statistics, [13-6](#)
 - of logged queries, [13-10](#)
 - token information, [13-14](#)
- reserved words and characters
 - escaping, [4-1](#)
- RESET_AUTO_OPTIMIZE_STATUS procedure, [5-2](#)
- RESET_TRACE procedure, [11-8](#)
- resetting a trace, [11-8](#)
- result set interface, [12-11](#)
- result sets, [12-11](#)
- result table
 - TOKENS, [A-9](#)
- result tables
 - CTX_DOC, [A-6](#)
 - CTX_QUERY, [A-1](#)
 - CTX_THES, [A-9](#)
- resuming failed index
 - example, [1-14](#)
- rewriting queries, [1-30](#)
- RFC 1738 URL specification, [2-12](#)
- RFC-2045 messages
 - filtering, [2-22](#)
- RFC-822 messages
 - filtering, [2-22](#)
- RT function, [14-27](#)
- RT operator, [3-41](#)
- RULE_CLASSIFIER type, [2-90](#)
- rules
 - generating, [7-1](#)

S

- Salton's formula for scoring, [F-1](#)
- scope notes
 - finding, [14-28](#)
- SCORE operator, [1-65](#)
- scoring
 - accumulate, [3-7](#)
 - effect of DML, [F-2](#)
 - for NEAR operator, [3-36](#)
- scoring algorithm
 - word queries, [F-1](#)
- script

- script (*continued*)
 - create index, [13-4](#)
 - create policy, [13-5](#)
- SDATA operator, [3-42](#)
- SDATA section, [8-14, 8-16](#)
- section group
 - creating, [8-34](#)
 - viewing information about, [G-13](#)
- section group example, [2-88](#)
- section group types, [2-86, 8-35](#)
- section searching
 - nested, [3-54](#)
- sections
 - adding dynamically, [1-1](#)
 - constraints for dynamic addition, [1-17](#)
 - creating attribute, [8-3](#)
 - creating field, [8-5](#)
 - creating zone, [8-26](#)
 - nested, [8-28](#)
 - overlapping, [8-28](#)
 - removing, [8-60](#)
 - repeated field, [8-7](#)
 - repeated zone, [8-28](#)
 - viewing information on, [G-12](#)
- SENTENCE keyword, [3-54](#)
- sentence section
 - defining, [8-18](#)
 - querying, [3-54](#)
- SET_ATTRIBUTE procedure, [8-64](#)
- SET_KEY_TYPE procedure, [9-40](#)
- SET_PARAMETER procedure, [2-98, 5-3](#)
- SET_SECTION_ATTRIBUTE procedure, [8-66](#)
- show size of index objects, [13-5](#)
- Simplified Chinese
 - index defaults, [2-97](#)
- single-byte languages
 - indexing, [2-41](#)
- skipjoins attribute, [2-41](#)
- SN procedure, [14-28](#)
- SNIPPET procedure, [9-40](#)
- soundex operator, [3-45](#)
- Spanish
 - fuzzy matching, [2-73](#)
 - stemming, [2-73](#)
 - supplied stoplist, [E-42](#)
- special characters
 - INPATH and HASPATH operators, [3-22](#)
- special section
 - defining, [8-18](#)
 - querying, [3-54](#)
- spelling
 - alternate, [17-2](#)
 - base letter, [17-2](#)
 - new German, [17-3](#)
 - overriding alternate, [17-3](#)
- spelling, alternate, [17-1](#)

- spelling, new German, [2-47](#)
- SQE operator, [3-46](#)
- SQL commands
 - ALTER INDEX, [1-1](#)
 - CREATE INDEX, [1-40](#)
 - DROP INDEX, [1-63](#)
- SQL operators
 - CONTAINS, [1-29](#)
 - MATCH_SCORE, [1-65](#)
 - MATCHES, [1-63](#)
 - SCORE, [1-65](#)
- SQL*Loader
 - example, [C-1](#)
 - example control file, [C-2](#)
 - example data file, [C-2](#)
- sqlldr example, [C-2](#)
- standalone graphics, [B-8](#)
- START_LOG procedure, [11-9](#)
- startjoins attribute, [2-41](#)
- statistics, disabling, [11-4](#)
- statistics, enabling, [11-4](#)
- statistics, showing index, [13-6](#)
- stem indexing, [2-47](#)
- stem operator, [3-45](#)
- stemmer attribute, [2-72](#)
- stemming
 - automatic, [2-73](#)
 - example for enabling, [2-79](#)
- stop section
 - adding dynamically, [1-1](#)
 - dynamically adding example, [1-17](#)
- stop sections
 - adding, [8-21](#)
- stop_dic attribute, [2-57](#)
- stopclass
 - defining, [8-19](#)
 - removing, [8-61](#)
- stoplist
 - creating, [8-39](#)
 - Danish, [E-6](#)
 - dropping, [8-42](#)
 - Dutch, [E-8](#)
 - English, [E-1](#)
 - Finnish, [E-16](#)
 - French, [E-22](#)
 - German, [E-28](#)
 - Italian, [E-35](#)
 - modifying, [2-94](#)
 - multi-language, [2-50](#), [2-94](#)
 - Portuguese, [E-40](#)
 - Spanish, [E-42](#)
 - Swedish, [E-47](#)
- stoplists
 - about, [2-93](#)
 - creating, [2-94](#)
 - viewing, [G-13](#)
- stoptheme
 - defining, [8-22](#)
 - removing, [8-61](#)
- stopword
 - adding dynamically, [1-1](#)
 - defining, [8-23](#)
 - removing, [8-62](#)
 - viewing all in stoplist, [G-14](#)
- stopword transformation
 - viewing, [12-4](#)
- stopwords
 - adding dynamically, [2-94](#)
 - removing, [2-95](#)
- storage defaults, [2-85](#)
- storage index preference
 - example, [8-33](#)
- storage objects, [2-80](#)
- STORE_SQE procedure
 - example, [3-46](#)
 - syntax, [12-18](#)
- stored queries, [3-46](#)
- stored query expression
 - creating, [12-18](#)
 - removing, [12-10](#)
 - viewing, [G-23](#)
 - viewing definition, [G-13](#)
- structured data, [3-42](#)
- structured data section, [8-14](#), [8-16](#)
- sub-lexer preference
 - removing, [8-63](#)
- sub-lexer values
 - viewing, [G-7](#)
- sub-lexers
 - viewing, [G-7](#), [G-14](#), [G-20](#), [G-21](#)
- substring index
 - example for creating, [2-79](#)
- substring_index attribute, [2-72](#)
- supplied stoplists, [E-1](#)
- Supported Platforms for AUTO_FILTER, [B-2](#)
- Swedish
 - alternate spelling, [17-5](#)
 - index defaults, [2-96](#)
 - supplied stoplist, [E-47](#)
- SYN function, [14-28](#)
- SYN operator, [3-47](#)
- SYNC EVERY parameter, [1-1](#), [1-40](#)
- SYNC ON COMMIT parameter, [1-1](#), [1-40](#)
- sync parameter, [1-1](#), [1-40](#)
- SYNC_INDEX procedure, [8-68](#)
- synchronize index, [1-1](#), [1-40](#)
- synonym operator, [3-47](#)
- system parameters
 - defaults for indexing, [2-99](#), [2-102](#)
- system recovery
 - manual, [5-2](#)
- system-defined preferences
 - CTXSYS.AUTO_FILTER, [2-20](#)

T

- table structure
 - explain, [A-1](#)
 - filter, [A-7](#)
 - Gist, [A-7](#)
 - hfeedback, [A-3](#)
 - highlight, [A-7](#)
 - markup, [A-8](#)
 - theme, [A-8](#)
- tagged text
 - searching, [3-54](#)
- template query, [1-25](#), [1-29](#)
- text column
 - supported types, [1-42](#)
- Text data dictionary
 - cleaning up, [5-1](#), [5-2](#)
- TEXT format column value, [1-40](#)
- text-only index
 - enabling, [2-47](#)
 - example, [8-32](#)
- theme functionality
 - supported languages, [16-11](#)
- theme highlighting
 - generating markup, [9-13](#)
 - generating offsets, [9-9](#), [9-23](#)
 - HTML markup example, [9-19](#)
 - HTML offset example, [9-12](#)
- theme index
 - as default in English, [2-96](#)
 - creating, [2-47](#)
- theme proving
 - enabling, [2-47](#)
- theme summary
 - generating, [9-5](#)
 - generating top n, [9-8](#)
- theme table
 - structure, [A-8](#)
- theme_language attribute, [2-47](#)
- themes
 - generating for document, [9-37](#), [9-44](#)
 - generating highlight markup, [9-13](#), [9-26](#)
 - highlight offset example, [9-12](#)
 - indexing, [2-47](#)
 - obtaining top n, [9-47](#)
- THEMES procedure
 - result table, [A-8](#)
 - syntax, [9-44](#)
- THES_TT procedure, [14-30](#)
- thesaurus
 - compiling, [16-6](#)
 - creating, [14-12](#)
 - creating relationships, [14-10](#)
 - DEFAULT, [3-10](#)
 - dropping, [14-16](#)
 - import/export examples, [16-3](#)
 - importing/exporting, [16-1](#)
- thesaurus (*continued*)
 - procedures for browsing, [14-1](#)
 - renaming and truncating, [14-4](#)
 - viewing information about, [G-14](#)
- thesaurus import file
 - examples, [C-7](#)
 - structure, [C-3](#)
- thesaurus phrases
 - altering, [14-2](#)
 - dropping, [14-13](#)
- thesaurus relations
 - creating, [14-11](#)
 - dropping, [14-14](#)
- thesaurus scope note
 - finding, [14-28](#)
- thesaurus top terms
 - finding all, [14-30](#)
- threshold operator
 - stopword transformations, [H-6](#)
- timeout attribute, [2-12](#)
- to_upper attribute, [2-57](#)
- token report, generating, [13-14](#)
- TOKEN_INFO procedure, [13-14](#)
- TOKEN_TYPE procedure, [13-15](#)
- token, translating name into, [13-15](#)
- TOKENS procedure
 - result table, [A-9](#)
 - syntax, [9-47](#)
- top term, [3-50](#)
- top term operator, [3-50](#)
- TR function, [14-31](#)
- TR operator, [3-11](#), [3-48](#)
- trace value
 - getting, [11-6](#)
- traces, available, [11-2](#)
- tracing
 - adding a trace, [11-2](#)
 - available traces, [11-2](#)
 - CTX_TRACE_VALUES view, [G-15](#)
 - enabling, [11-2](#)
 - getting trace values, [11-6](#), [G-15](#)
 - logging traces, [11-6](#)
 - removing trace, [11-8](#)
 - resetting trace, [11-8](#)
- TRAIN procedure, [7-1](#)
- transactional CONTEXT index, [1-9](#), [1-53](#)
- transactional index, [12-4](#)
- transactional parameter, [1-9](#), [1-53](#)
- transactional text query
 - disabling, [1-54](#)
- TRANSFORM operator, [1-31](#)
- transformation
 - stopword, [H-1](#)
- translation term operator, [3-11](#), [3-48](#)
- translation term synonym operator, [3-49](#)
- translations
 - adding to thesaurus, [14-13](#)

translations (*continued*)
 dropping, [14-16](#)
 English name to numeric token, [13-15](#)
 updating, [14-35](#)
Transparent Data Encryption
 Oracle Text index on a column and, [1-42](#)
TRSYN function, [14-32](#)
TRSYN operator, [3-49](#)
TT function, [14-34](#)
TT operator, [3-50](#)
type
 MULTI_LEXER, [2-49](#)
 WORLD_LEXER, [2-71](#), [D-5](#)
types
 indexing, [2-2](#)
 see also indexing types, [2-2](#)

U

unicode support in Korean lexer, [2-56](#)
UNSET_ATTRIBUTE procedure, [8-70](#), [8-71](#)
unsupervised classification, *see* clustering, [7-4](#)
UPDATE GLOBAL INDEXES, [1-19-1-21](#)
UPDATE_SDATA procedure, [8-73](#)
UPDATE_SUB_LEXER procedure, [8-71](#)
UPDATE_TRANSLATION procedure, [14-35](#)
URL syntax, [2-12](#)
URL_DATASTORE object
 attributes for, [2-11](#)
 example, [2-13](#)
urlsize attribute, [2-12](#)
user dictionary, modifying, [16-12](#)
USER_DATASTORE object
 example, [2-15](#)
USER_DATSTORE
 filtering binary documents, [9-12](#)
user_dic attribute, [2-57](#)
USER_FILTER object
 example, [2-28](#)
USER_LEXER object, [2-59](#)
UTF8, [2-54](#)
UTF8 character set, [2-52](#), [2-54-2-56](#)
utilities
 ctxload, [16-1](#)

V

VARCHAR2 column
 indexing, [1-42](#)
verb_adjective attribute, [2-57](#)
version numbers
 viewing, [G-25](#)
viewing
 operator expansion, [12-4](#)
 operator precedence, [12-5](#)
views
 CTX_AUTO_OPTIMIZE_INDEXES, [G-3](#)

views (*continued*)

 CTX_AUTO_OPTIMIZE_STATUS, [G-3](#)
 CTX_CLASSES, [G-3](#), [G-4](#), [G-9](#), [G-17](#), [G-21](#)
 CTX_INDEX_ERRORS, [G-6](#)
 CTX_INDEX_OBJECTS, [G-6](#)
 CTX_INDEX_SUB_LEXER, [G-7](#)
 CTX_INDEX_SUB_LEXERS, [G-21](#)
 CTX_INDEX_SUB_LEXERS_VALUES, [G-7](#)
 CTX_INDEX_VALUES, [G-8](#)
 CTX_INDEXES, [G-5](#)
 CTX_OBJECT_ATTRIBUTE_LOV, [G-9](#)
 CTX_OBJECT_ATTRIBUTES, [G-8](#)
 CTX_OBJECTS, [G-8](#)
 CTX_PARAMETERS, [G-10](#)
 CTX_PENDING, [G-11](#)
 CTX_PREFERENCE_VALUES, [G-12](#)
 CTX_PREFERENCES, [G-12](#)
 CTX_SECTION_GROUPS, [G-13](#)
 CTX_SECTIONS, [G-12](#)
 CTX_SQES, [G-13](#)
 CTX_STOPLISTS, [G-13](#)
 CTX_STOPWORDS, [G-14](#)
 CTX_SUB_LEXERS, [G-14](#)
 CTX_THESAURI, [G-14](#)
 CTX_TRACE_VALUES, [G-15](#)
 CTX_USER_AUTO_OPTIMIZE_STATUS, [G-15](#)
 CTX_USER_INDEX_ERRORS, [G-18](#)
 CTX_USER_INDEX_OBJECTS, [G-19](#)
 CTX_USER_INDEX_SET_INDEXES, [G-20](#)
 CTX_USER_INDEX_SETS, [G-20](#)
 CTX_USER_INDEX_SUB_LEXERS, [G-20](#)
 CTX_USER_INDEX_VALUES, [G-21](#)
 CTX_USER_INDEXES, [G-17](#)
 CTX_USER_PENDING, [G-22](#)
 CTX_USER_PREFERENCE_VALUES, [G-22](#)
 CTX_USER_PREFERENCES, [G-22](#)
 CTX_USER_SECTION_GROUPS, [G-23](#)
 CTX_USER_SECTIONS, [G-23](#)
 CTX_USER_SQES, [G-23](#)
 CTX_USER_STOPLISTS, [G-24](#)
 CTX_USER_STOPWORDS, [G-24](#)
 CTX_USER_SUB_LEXERS, [G-24](#)
 CTX_USER_THES_PHRASES, [G-25](#)
 CTX_USER_THESAURI, [G-25](#)
 CTX_VERSION, [G-25](#)

visible flag for field sections, [8-6](#)

visible flag in field sections, [3-54](#)

W

weight operator
 stopword transformations, [H-6](#)
whitespace attribute, [2-41](#)
wildcard queries
 improving performance, [2-72](#)
wildcard searches

- wildcard searches (*continued*)
 - improving performance, [3-52](#)
- wildcard_maxterms attribute, [2-72](#)
- WILDCARD_TAB type, [15-1](#)
- WITHIN operator
 - attribute sections, [3-54](#)
 - limitations, [3-54](#)
 - nested, [3-54](#)
 - precedence, [3-3](#)
 - stopword transformations, [H-6](#)
- word forms
 - original vs. normalized, [17-1](#)
- WORLD_LEXER type, [2-71](#), [D-5](#)

X

- XML documents
 - attribute sections, [8-3](#)
 - doctype sensitive sections, [8-28](#)
 - querying, [3-54](#)
- XML report output format, [13-2](#), [13-3](#), [13-5](#), [13-6](#), [13-14](#)
- XML Search, [8-36](#)
- XML Search Index, [8-34](#)

- XML sectioning, [2-89](#)
- xml_enable, [8-34](#)
- XML_SECTION_GROUP
 - example, [2-88](#)
- XMLIndex, [xxi](#)

Z

- ZHS16CGB231280 character set, [2-52](#)
- ZHS16GBK character set, [2-52](#)
- ZHS32GB18030 character set, [2-52](#)
- ZHT16BIG5 character set, [2-52](#)
- ZHT16HKSCS character set, [2-52](#)
- ZHT16MSWIN950 character set, [2-52](#)
- ZHT32EUC character set, [2-52](#)
- ZHT32TRIS character set, [2-52](#)
- zone section
 - adding dynamically, [1-1](#)
 - creating, [8-26](#)
 - dynamically adding example, [1-16](#)
 - querying, [3-54](#)
 - repeating, [8-28](#)

