





**A Graph Search query (Facebook)**

*find all my friends who have online updates from UK*

- `friend(uid, fid)`
- `update(id, uid, country, date, post, ...)`

	friend	
	uid	fid
1	uid0	uid18
2	uid1	uid11
3	uid1	uid18
	...	...

	update					
	id	uid	country	date	post	...
1	001	uid18	US	20160103	post#1	...
2	002	uid11	UK	20150103	post#2	...
3	003	uid11	UK	20170103	photo#3	...
	...	...	...	...	...	...

```
SELECT fid  
FROM    friend AS f, update AS u  
WHERE   f.uid= uid1 AND f.fid=u.uid AND u.country=UK
```

my uid

*How does DBMS evaluate the query?*





# A Graph Search query (Facebook)

*find all my friends who have online update records from UK*

- `friend(uid, fid)`
- `update(id, uid, country, date, post, ...)`

friend	
uid	fid
1 uid0	uid18
2 uid1	uid11
3 uid1	uid18
...	...

update					
id	uid	country	date	post	...
1 001	uid18	US	20160103	post#1	...
2 002	uid11	UK	20150103	post#2	...
3 003	uid11	UK	20170103	photo#3	...
...	...	...	...	...	...

```
SELECT fid
FROM   friend AS f, update AS u
WHERE  f.uid= uid1 AND f.fid=u.uid AND u.country=UK
```

my uid

*How does DBMS evaluate the query?*

# A Conventional Query Plan

*find all my friends who have online update records from UK*

- **friend**(uid, fid)
- **update**(id, uid, country, date, post, ...)

```
SELECT fid
FROM   friend AS f, update AS u
WHERE  f.uid= uid1 AND f.fid=u.uid AND u.country=UK
```

*A Conventional DBMS plan*